




(86) Date de dépôt PCT/PCT Filing Date: 2018/02/15
 (87) Date publication PCT/PCT Publication Date: 2018/08/23
 (45) Date de délivrance/Issue Date: 2021/10/26
 (85) Entrée phase nationale/National Entry: 2019/03/11
 (86) N° demande PCT/PCT Application No.: EP 2018/053821
 (87) N° publication PCT/PCT Publication No.: 2018/149934
 (30) Priorité/Priority: 2017/02/17 (PL P.420573)

(51) Cl.Int./Int.Cl. *F04B 43/073* (2006.01)
 (72) Inventeur/Inventor:
 DOMERACKI, JERZY, PL
 (73) Propriétaire/Owner:
 OTEK ENGINEERING JERZY DOMERACKI, PL
 (74) Agent: DEETH WILLIAMS WALL LLP

(54) Titre : PROCÉDE ET DISPOSITIF POUR LE NETTOYAGE D'UN CANAL A L'AIDE D'UN MODULE DE POMPE A MEMBRANE
 (54) Title: METHOD AND DEVICE FOR CLEANING A CHANNEL USING A DIAPHRAGM PUMP MODULE



(57) **Abrégé/Abstract:**

A method and an apparatus for cleaning a channel, especially a transmission and/or cooling channel, in any type of device, machine, installation, and/or tool, particularly in any type of heat exchanger and/or a molding core, cavity and/or insert is proposed, wherein a channel is cleaned through dynamic, bi-directional pulsation of cleaning medium inside the to-be-cleaned channel, the method being realized by a cleaning apparatus equipped with a diaphragm pump module, plugged either only in the feed side of the transmission line or in the feed side and in the return side, which, after connecting the diaphragm pump module to the external energy source and shutting off the flow control system from the reservoir and the feed pump, allows for putting cleaning medium into a state of two-way dynamic pulsating motion.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
23 August 2018 (23.08.2018)



(10) International Publication Number
WO 2018/149934 A1

(51) International Patent Classification:

F04B 43/073 (2006.01)

(21) International Application Number:

PCT/EP2018/053821

(22) International Filing Date:

15 February 2018 (15.02.2018)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

P.420573 17 February 2017 (17.02.2017) PL

(71) Applicant: OTEK ENGINEERING JERZY DOMERACKI [PL/PL]; Pogodna 15, 86-032 Niemcz (PL).

(72) Inventor: DOMERACKI, Jerzy; Pogodna 15, 86-032 Niemcz (PL).

(74) Agent: ZIMMERMANN & PARTNER PATENTANWÄLTE MBB; Josephspitalstr. 15, 80331 München (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,


MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: METHOD AND DEVICE FOR CLEANING A CHANNEL USING A DIAPHRAGM PUMP MODULE



(57) Abstract: A method and an apparatus for cleaning a channel, especially a transmission and/or cooling channel, in any type of device, machine, installation, and/or tool, particularly in any type of heat exchanger and/or a molding core, cavity and/or insert is proposed, wherein a channel is cleaned through dynamic, bi-directional pulsation of cleaning medium inside the to-be-cleaned channel, the method being realized by a cleaning apparatus equipped with a diaphragm pump module, plugged either only in the feed side of the transmission line or in the feed side and in the return side, which, after connecting the diaphragm pump module to the external energy source and shutting off the flow control system from the reservoir and the feed pump, allows for putting cleaning medium into a state of two-way dynamic pulsating motion.



WO 2018/149934 A1

Method and device for cleaning a channel using a diaphragm pump module

Aspects of the invention relate to a method and an apparatus for cleaning a
5 channel, especially a transmission and/or cooling channel, in any type of device,
machine, installation, and/or tool, particularly in any type of heat exchanger and/or
molding core, cavity and/or insert.

Technical background

10 There are cleaning and conservation methods for cooling systems where
a chemically active cleaning solution with the pH value of ≤ 2 required for an effective
cleaning process is heated up to an operating temperature of approx. 50 °C (from
30°C up to the boiling temperature of certain cleaning medium). The cleaning
process is carried out by pumping the heated cleaning solution through a channel in
15 order to dissolve scale and/or rust sediment agglomerating on its interior walls. In
well-known methods, cleaning is carried out with a single pump, e.g.
centrifugal pump, feeding one or several circuits simultaneously and connected in
such a way as to automatically change the flow direction of the cleaning medium.
The circulation pump delivers the cleaning solution through the connected circuits.
20 Contamination such as scale and/or rust is dissolved and directed back to the
reservoir by means of a return line. The cleaning performance is monitored by
continuous pH measurement. The actual pH is shown on an actual-value display. At
the end of the cleaning phase, a valve unit allows the circulation pump to be switched
to the neutralizing fluid reservoir in order to neutralize the leftovers of the residual
25 solution.

More technically advanced devices are equipped with a flow measurement
system where the flow meter is installed inside the neutralizing fluid circuit or is
plugged into an additional circuit with a high-efficiency circulation pump. By
comparing the actual flow rate to the defined one, it is possible to evaluate whether
30 the channels have reached the desired patency reference value and whether the
cleaning process is completed. At the end of each stage of operation, the circuits are
optionally dried with compressed air. The cleaning process is also enhanced by
means of periodic compressed air-blow through channels. However, even these

advances systems are difficult to monitor. Moreover, it would be desirable to use the cleaning medium more efficiently, to improve the cleaning effect further, and to reduce the required time for cleaning.

Further, new generation of tools/device components, manufactured with e.g. additive manufacturing or so-called 3d printing, often cannot be maintained well-enough with currently well-known methods due to its high complexity (like single-piece heat exchangers or conformal cooling channels within molding inserts, cores and cavities).

10 Summary of the invention

It is an object of the present invention to reduce the above-described disadvantages at least partially. In view of the above, a method according to claim 1 and a device according to claim 19 are proposed. Further aspects and advantages are evident from the dependent claims, the description and the drawings.

15 Thus, according to an aspect of the invention, a method and an apparatus are provided for cleaning a channel, especially a transmission and/or cooling channel, in any type of device, machine, installation, and/or tool, particularly in a molding core, cavity, insert and/or any other heat exchanger. Therein a channel is cleaned through dynamic, bi-directional pulsation of cleaning medium inside the to-be-cleaned
20 channel, the method being realized by a cleaning apparatus equipped with a diaphragm pump module (which may also be referred to as a pulsating module) connected with transmission lines in such a way that one pump diaphragm section is plugged in the feed line and the other one in the return line, which, after connecting the two-diaphragm pump to the compressed air source and shutting off the shut-off
25 valve from the reservoir and the feed pump, allows for putting cleaning medium into a state of two-way dynamic pulsating motion.

According to an aspect, the to-be-cleaned channel is connected to the described cleaning apparatus, e.g., by a hose. According to an aspect, between the to-be-cleaned channel and the reservoir, there is a diaphragm pump chamber with a
30 diaphragm arranged within. After cutting off the flow between the diaphragm chamber and reservoir (e.g., with a single valve of any kind, or a set of them), the cleaning medium is put in alternating pulsating motion inside the channel by action of the diaphragm pump module. More specifically, the alternating, pulsating motion of the

cleaning medium is actuated by a reciprocal movement of a diaphragm(s) of the diaphragm pump module controlled by an external power source.

In the following, the external energy source is for the sake of brevity referred to as a compressed air/gas source, and the flow control system is referred to as a shut-off valve. However, any other external energy source for actuating the diaphragm pump module, and any other flow control system may be used instead. Further, air (compressed air) is herein used as an example for a gas (compressed gas). Herein, any of the (compressed) air described herein can be substituted by any (other) (compressed) gas such as CO₂ or N₂ or any other gas (mixture).

10 According to an aspect of the invention, the channel cleaning method includes forcing the medium situated in a to-be-cleaned channel into a state of dynamic, bi-directional pulsation (alternating pulsating motion inside the channel). The method is realized by means of a modified two-diaphragm pump module whose two diaphragms are preferably coupled mechanically to each other.

15 According to a preferred aspect, the pump module with a flow control system (e.g., shut-off valve) is fluidly connected in such a way that a (respective) diaphragm pump module is plugged in either one or both of the feed side and the return side. After connecting the diaphragm pump module to the compressed air source and shutting off the shut-off valve from the reservoir and the diaphragm pump module, 20 allows for putting cleaning medium into a state of two-way dynamic pulsation, increasing its turbulent movement and intensifying the cleaning process.

According to a further preferred aspect, at the end of each pulsation phase, the shut-off valve opens and the fresh portion of the chemically active solution is pumped into the cleaned area, while the used liquid returns to the reservoir where it 25 is filtered and mixed with the rest of the solution in the reservoir. The process may be automatic.

According to a further preferred aspect, the cleaning device includes a sensor system for measuring parameters such as medium flow rates and/or temperature. These measurement parameters are monitored to optimize the process. The device 30 can optionally perform intermediate flow rate measurements and define the flow rate growth curve, which allows the device to finish the cleaning process before the appointed time once the user-defined flow rate values are reached, or when the

measured flow variations between the subsequent cleaning phases are unnoticeable (below a predetermined threshold).

According to a further preferred aspect, in the case of some kinds of sediment
5 (specific from the properties and chemical composition of a cooling liquids) and/or heavily polluted channels with narrowed diameters due to deposited scale sediment, the cleaning device allows air in the form of microbubbles to be fed into the cleaning medium by means of a micro-diffuser, resulting in a lower density of the cleaning mixture generating lower flow resistance. This aeration module is built-in between the
10 feed pump and a channel input.

According to a further preferred aspect, the cleaning device comprises a heater for heating the cleaning solution to a temperature of about 50°C (30°C to up to the boiling temperature of a cleaning medium, e.g., to 70°C)

According to a further preferred aspect, the effectiveness of the cleaning
15 process is further verified by a temperature control module having temperature sensors on both sides of a cleaned channel's wall. By alternately pumping the heated up cleaning medium and the neutralizing fluid at ambient temperature, or any other two liquids with a significant temperature difference, the controller is enabled to determine the time required to equalize the indications of both temperature sensors,
20 and on basis of the result to determine the thickness of the sediment deposited on the walls of the channel. Based on this information the controller determines whether the cleaning should be continued or finished.

According to a further preferred aspect, the cleaning medium, neutralizing medium or any other liquid (preferably water) or compressed gas, can serve as a
25 diagnostics medium during flow rate and other measurements. Such a data might be used to define the condition and/or pollution level of a channel (11), taken into account for further optimization of the cleaning process and/or other channel (11) maintenance processes.

According to a further preferred aspect, the cleaning device has at least one of
30 the following:

- a first feed line having a first end and a second end (in and out) , the second end (out) of the first feed line being adapted to be connected to the first end

(in) of the channel by means of a hose with quick-connectors fixed on both ends of the hose.

- a first reservoir (2) containing a cleaning solution, connected to the second end of the first feed line;
- 5 - a first feed pump arranged in the first feed line, upstream of the first reservoir and downstream of the first chamber of the diaphragm pump; the first feed pump (feed pump for cleaning solution) being configured to supply the cleaning solution to the channel;
- a shut-off valve arranged in the first feed line, upstream of the first feed
10 pump and downstream of the first chamber of the diaphragm pump module; the shut-off valve being configured to shut-off or at least limit the supply of cleaning solution to the channel;
- a first return line having a first end and a second end, the first end (in)
15 of the first return line being adapted to be connected to the second end of the channel, and the second end of the first return line being optionally connected to the first reservoir. Thereby, a first closed-loop may be formed;
- a filtering device configured to filter the cleaning solution, the filtering
20 device being arranged upstream the first reservoir and downstream the first feed pump.

According to a further preferred aspect, the cleaning device has at least one of the following:

- a second reservoir containing a neutralizing solution;
- 25 - a second feed line connected in parallel to the first feed line (e.g., connected to the first feed line downstream of the shut-off valve and upstream of the diaphragm pump module);
- a second return line connected in parallel to the first return line, (e.g.,
30 connected downstream of the second diaphragm chamber of the diaphragm pump module);

- a second pump (feed pump for neutralizing medium) arranged in the second closed-loop, the second pump being configured to supply the neutralizing solution to the channel;
 - a measuring device for measuring the flow of the neutralizing solution, the measuring device being arranged in the second feed line;
 - a filtering device configured to filter the neutralizing solution, the filtering device being arranged on the second feed line, upstream the second reservoir and downstream the second feed pump, and/or on the second return line, upstream the second reservoir.
- 10 Thereby a second closed-loop parallel to the first closed loop (or partially parallel to and partially overlapping with the first closed loop) may be formed.

According to a further aspect, a method of cleaning a (e.g. transmission or cooling) channel comprises (wherein each of steps d to h are optional):

- 15 a) connecting a channel to the apparatus as described herein;
- b) supplying the cleaning solution to the channel;
- c) shutting-off a shut-off valve of said apparatus and subjecting the cleaning solution to a (turbulent) alternating pulsating motion using the diaphragm pump module;
- 20 d) drying the channel with compressed air coming from a compressed air source
- e) supplying the neutralizing solution to the channel;
- f) measuring the flow rate of the neutralizing solution and comparing it with a standard / predetermined flow rate value;
- g) drying the channel with compressed air coming from a compressed air source
- 25 h) optionally, repeating the above steps depending on an outcome of the measurement.

According to a further aspect, a method and an apparatus for cleaning a channel, especially a transmission and/or cooling channel in any type of device, machine, installation, and/or tool, particularly in any type of heat exchanger and/or a molding

core, cavity and/or insert are provided. Therein, a channel is cleaned through dynamic, bi-directional pulsation of cleaning medium inside the to-be-cleaned channel, the method being realized by a cleaning apparatus equipped with a diaphragm pump module, plugged either only in the feed side of the transmission line
5 or in the feed side and in the return side, which, after connecting the diaphragm pump module to the external energy source and shutting off the flow control system from the reservoir and the feed pump, allows for putting cleaning medium into a state of two-way dynamic pulsating motion.

According to an aspect, inside the cleaning apparatus, between the to-be-cleaned
10 channel (11) and a reservoir (2), there is a diaphragm chamber (diaphragm pump chamber) with an elastic diaphragm. After cutting off the flow between the diaphragm chamber and reservoir (either with a single valve of any kind, or set of them), the diaphragm is actuated for putting the cleaning medium in alternating pulsating motion inside the channel (11). More specifically, the alternating, pulsation motion of the
15 cleaning medium, is actuated by a reciprocal movement of a diaphragm/-s.

According to a further aspect, the method of cleaning a channel includes

- 20 1. Supplying a cleaning medium from a reservoir to an inside of the channel to be cleaned (e.g., by pumping the cleaning medium into the channel (11) with a feed pump);
2. Cutting off or at least limiting the flow between the reservoir and the diaphragm pump chamber (to be more specific, the flow is limited so that it cannot flow back to the reservoir, e.g., by a cutoff valve(s) upstream or downstream the feed pump (4));
- 25 3. Putting the cleaning medium in a reciprocal movement inside the channel by the at least one diaphragm pump module;
4. Optionally, pumping a fresh portion of cleaning medium into the channel and repeating the process, i.e. going back to step 1.

30 According to aspects of the invention, this method can be carried out effectively for both single and multiple channels (connected in series or in parallel) simultaneously and is dependent on the number of sections installed in the device.

Potential advantages of aspects of the invention include a change of a static, laminar flow of the chemically active solution in channels into a dynamic process, resulting in increased cleaning medium effectiveness and shortened cleaning time. For a multi-section device designed for simultaneous cleaning of channels with
5 different cross-sections, a dedicated pulsation module in each section enables similar removal conditions for sediments and guarantees high efficiency of the process.

In addition, the use of the fluid aeration micro-diffuser reduces flow resistance, which is especially useful in some kinds of sediment and/or heavily scaled channels with a small clearance. Constant process control by measuring the time needed to
10 equal temperatures at the inner and outer sides of a channel makes it possible to diagnose the actual efficiency of a cleaned cooling system as well as determine its current thermal conductivity initially reduced by the stone sediment deposited on channel's walls.

The diaphragm pump module can be provided with one single diaphragm pump
15 chamber, so that the pumping action is applied only to one side (active side) of the channel. Thereby a reciprocal motion of the cleaning medium in the channel is possible. However, a more effective cleaning is possible by providing the diaphragm pump module as a two-diaphragm pump module having two diaphragm pump chambers each having a respective diaphragm arranged therein. The two
20 diaphragms may be mechanically coupled to each other, e.g. by a pin, or they may not be directly coupled. In the latter case the coordinated motion of both diaphragm pump chambers may be ensured by an actuator adapted for opposite operation of both diaphragms (i.e., one diaphragm is operated to create overpressure when the other diaphragm is operated to create underpressure, and vice versa).

25 Herein, a diaphragm pump module is defined by comprising a chamber with an elastic diaphragm, the diaphragm being movable/deformable to change the volume and thus pressure in the chamber. The diaphragm pump or diaphragm pump module does not necessarily comprise a check valve. Therefore, the diaphragm pump module may also be referred to as a pulsator.

30

Brief description of the Figure

The Figure describes schematics of the system with a cleaning device according to an embodiment of the invention.

Detailed description of an embodiment

5 The following is a description of a preferred embodiment of a cleaning device and method. It is understood that any of the specific descriptions of this embodiment is not limiting but is merely an example. For example, while the example describes a two-diaphragm pump, also one of the two diaphragm pump modules can be omitted, so that the reciprocal motion is effected by the remaining single diaphragm pump
10 module.

According to a preferred embodiment of the invention, the method of cleaning of transmission channels includes three stages. These stages are illustrated with reference to the Figure, but are not limited to the embodiment shown in the Figure.

In a first cleaning phase, the cleaning medium with $\text{pH} \leq 2$ at about 50°C , being a
15 mixture of water and the cleaning agent, is pumped from a reservoir (2) into a channel (11) by means of a pump (4) with a 25 l/m flow rate. During the first cleaning cycle, the medium is pumped into the channel for 40 seconds, whereas subsequent cycles last 15 seconds.

After filling the channel (11) with cleaning medium, the shut-off valve (5)
20 closes and the two-diaphragm pump (6) is actuated with diaphragm (8), which alternately aspirate and pump the cleaning medium into the cut off channel, as a result of which the medium is put in a state of dynamic pulsation and turbulent motion within the channel. After the pulsating rinsing phase, the shut-off valve opens and the cleaning medium is pumped out of the channel (11) into the reservoir (2) where, after
25 being filtered through the filter (3), it is mixed with the fresh solution and then, by means of the feed pump (4), the cleaning medium is sucked back into the channel in the next cleaning cycle.

In the case of heavily polluted channels with low throughput, the cleaning fluid is additionally aerated by compressed air in the form of air-bubbles by means of the
30 micro-diffuser (10) positioned inside the feed line (15) close to the exit of the cleaning system. Looped exchange of cleaning medium and subsequent repetition of the cleaning process is carried out until the required flow rates have been reached or the

results do not differ between the individual cleaning phases. The process is automatic and is operated by the PLC controller (13) which, based on the measurement data from the flowmeter (14), analyzes the flow difference between subsequent cleaning phases. Independent pollution level diagnosis is realized by
5 monitoring the time required for temperature equalization, measured by two temperature sensors (12), one measuring the medium temperature in channel (11) and the other measuring temperature on the outside of the channel (11). Temperature sensors (12) are connected to the operating control system (13) that compares the reference thermal conductivity of a given channel with a currently
10 determined one and decides on the cleaning process end or its continuation.

The method is implemented by means of the device shown in the accompanying Figure, which is described in the following.

The device includes a neutralizing medium reservoir (1), a cleaning medium
15 reservoir (2), filters (3), a feed pump (4), a shut-off valve (5), a two-diaphragm pump (6) with diaphragms (8), compressed air sources (7), air valves controlling a diaphragm pump (9), a micro-diffuser (10), a cleaned channel (11), temperature sensors (12), an operating-control module (13), a flow meter (14), feed lines (15), return lines (16), additional flow control valves (17), a feed pump for neutralizing
20 medium (18), a diaphragm connecting pin (19), power supply (20).

Thus, the Figure illustrates a general aspect of the invention, which is summarized in the following using the reference signs of the Figure: A device for cleaning of transmission channels of e.g. liquids, and cooling channels of all equipment types, machines, installations, tools, especially molding cavities, which
25 has fluid reservoirs: with active cleaning medium (2), and neutralizing medium (1), a feed pump (4, 18), valves (5, 17) integrated into the system and connected by means of transmission lines (15, 16), and an additional pump (6) that is built into the system behind the feed pump (4) and the shut-off valve (5), the pump (6) being devoid of check valves and equipped with two Teflon rubber diaphragms (8) mechanically
30 connected by means of a pin (19), located at the inlet and outlet of a cleaned channel, one of which is built into the feed line (15) and the other into the return line (16), and/or has a micro-bubble diffuser (10), built into the feed line (15) at the output of the system, in front of the channel (11), connected to the compressed air source

(7), aerating cleaning medium entering the channel (11), and/or has a diagnostics module consisting of two temperature sensors (12), one of which being located within the channel (11) and the other one being located as close as possible to the outer wall of the cleaned channel (11), both sensors being connected to the control module
5 (13) analyzing measurement data.

While the above example has been described with a compressed air supply for actuating the diaphragms, any other external power supply may be used instead, e.g., other gases, fluids, springs, magnets, pistons and others.

Furthermore, while a single shut-off valve has been described for cutting off
10 the flow, e.g., between diaphragm chamber and reservoir, the invention is not limited to this.

Example

The method according to an embodiment of the present invention is illustrated
15 more closely by the following example of execution.

The process starts with filling the reservoir (1) with a mixture of water and neutralizing medium for passivation of the cleaning solution inside the channels after the cleaning process. Reservoir (2) is filled with a cleaning solution consisting of a mixture of water and a chemically active cleaning agent $\text{pH} \leq 2$, then heated in
20 reservoir (2) to about 50°C.

After connecting the device to the channel (11) by means of the transmission lines (15,16), a tightness and patency test is performed. If the test is successful, the machine performs the measurement of flow rates, using the ultrasonic flow meter (14). The neutralizing medium in the Reservoir (1) is pumped into the channel (11) for
25 (1) minute by means of a second feed pump (18) at a pressure of 1-6 bar. The flow rate measurement data from the ultrasonic flow meter (14) is stored and analyzed by the controller PLC (13) and the channel (11) is dried by compressed air from the compressed air source (7).

Once the diagnostics stage is completed, the device automatically moves on to
30 the proper cleaning process. The feed pump (4) pumps the cleaning medium into the channel (11) for 1-3 min at a pressure of 1-6 bar (depending on the diameter and length of the channel). After filling the channel (11) with the cleaning medium, the

system is cut off by a shut-off valve (5) and then the two-diaphragm pump (6), with Teflon rubber diaphragms (8) located on the input and output sides of the cleaned channel and mechanically connected with each other by means of the pin (19), is activated. Diaphragms (8) perform a pulsating movement alternately pushing the cleaning medium backward and forwards in the closed loop of the channel (11), as a result of which the medium is put in a state of dynamic pulsation and turbulent motion within the channel (11). The diaphragms' operating speed is defined by the operating control module (13). In the case of heavily contaminated channels the micro-diffuser (10) by means of the source of compressed air (7) injects air micro-bubbles into the cleaning medium, constituting between 1% and 60% of the overall pumped medium volume, which results in a lower density of the medium mixture.

At the end of the channel pulsation cleaning cycle the shut-off valve opens and the medium is pushed by means of the feed pump (4) into the Reservoir (2), where it is filtered by means of the filter unit (3) and then is re-pumped into the system. After the cleaning phase of channel (11) is completed, the channel is dried by compressed air and the diagnostic test is performed again to verify the efficiency of the cleaning process. The cleaning/diagnostics processes are repeated until the differences in flow rates between subsequent cleaning steps are lower than 3% or the user's defined flow rate is reached. In parallel, independent diagnostics of contamination level is being carried out by monitoring the time needed to even out the temperatures indicated by the two temperature sensors (12). The sensors are positioned so as to measure the medium temperature inside the channel (11) and the temperature outside of channel (11). Sensors (12) data is read by the operating control module (13), which computes and compares the reference thermal conductivity of a given channel with currently measured results and then decides whether the cleaning process should be finished or continued. Upon completion of the cleaning and the final diagnostics process, channel (11) is dried with compressed air.

Finally, some further embodiments are described. These embodiments can be combined with any other embodiment or aspect described herein. Reference signs, referring to the Figure, are purely illustrational but not limiting.

According to a first embodiment, a method of cleaning of transmission and cooling channels in all types of devices, machines, installations, tools, especially

molding cavities, characterized in that the active chemical solution filling the cleaned channel (11) is put into dynamic bi-directional pulsation by means of a module with a two-diaphragm pump (6) with a shut-off valve (5), both connected in such a way that the cleaned channel is inserted between two diaphragms (8) coupled mechanically
5 by means of the pin (19), which, after connecting the pump to the compressed air source (7) and cutting off the loop from the reservoir (2) and the feed pump (4) with the shut-off valve (5), results in putting the cleaning medium in alternating pulsating motion inside the channel (11).

According to a second embodiment, the method of cleaning of transmission and
10 cooling channels in all types of equipment, machines, installations, tools, especially molding cavities, characterized in that the cleaning medium, while being pumped into the cleaned channel (11), is aerated with micro-bubbles by means of a diffuser (10) integrated into the feed line (15) at the system output, powered with compressed air from the compressed air source (7), thereby decreasing the density of the mixture
15 and reducing the fluid flow resistance, the amount of air being fed depending on the degree of patency of the channel and varying from 1% to 60% of the volume of the pumped medium.

According to a third embodiment, the method of cleaning of transmission and
20 cooling channels in all types of devices, machines, installations, tools, especially molding cavities, characterized in that the measurement of the cleaning process is carried out by determining the time needed for equalization of temperatures indicated by two temperature sensors (12), one of which measures medium temperature in the channel (11) and the second one measures temperature on the outer side of the
25 channel, this measurement being made at the end of cleaning with heated chemical solution and just before the start of neutralization with cool neutralizing medium and transferring this information to the operating control unit 13, which allows for comparison of the result to the nominal value.

30 According to a fourth embodiment, the device for cleaning transmission channels of e.g. liquids, and cooling channels in all types of equipment, machines, installations, tools, especially molding cavities, containing fluid reservoirs, a pump, valves built into the system and connected by means of transmission lines,

characterized in that it has a two-diaphragm pump (6), built into the system behind the feed pump (4) and the shut-off valve (5), the pump (6) devoid of check valves, one of the pump diaphragms being built into the feed line (15) and the other into the return line (16), and/or has a micro-bubble diffuser (10) built into the feed line (15) at
5 the output of the system and connected to the compressed air source (7) that aerates the fluid, and/or has a diagnostic module consisting of two temperature sensors (12), where one sensor is located within the channel (11) and the other sensor is as close as possible to the outer wall of the cleaner channel (11), both connected to the control module (13).

10

CLAIMS

1. A method of cleaning a channel (11) using a diaphragm pump module (6) having at least one diaphragm pump chamber having a diaphragm (8) arranged therein,
5 wherein

the channel (11) is fluidly connected to the at least one diaphragm pump chamber, the method comprising:

putting, by coordinated reciprocal motion of the diaphragm (8), a cleaning medium in alternating pulsating motion inside the channel (11).

10

2. The method of cleaning a channel according to claim 1, wherein the cleaning medium, while being pumped into the channel (11), is aerated with micro-bubbles by means of a diffuser (10) integrated into a feed line (15) for feeding the cleaning medium to the channel (11), the diffuser (10) being fed with compressed air or gas from a
15 compressed air or gas source (7).

3. The method of cleaning a channel according to claim 1 or claim 2, wherein the cleaning method includes a cleaning step carried out with the heated chemical solution, and a neutralization step carried out with a cool (non-heated) neutralizing
20 medium,

and wherein the method further comprises:

measuring, by a first temperature sensor (12), a medium temperature in the channel (11), and measuring, by a second temperature sensor (12), a temperature on the outer side of the channel (11), the temperature measurements being made at the end of the
25 cleaning step and just before the start of the neutralization step or at any other point in between applying any two liquids with a significantly different temperature,

determining the time needed for equalization of the temperatures indicated by the first and second temperature sensors (12), and

comparing the determined time needed for equalization to a nominal value.

4. The method of cleaning a channel according to claim 3, wherein the two liquids have a temperature difference of 10°C or more.

5
5. The method of cleaning a channel according to claim 3 or claim 4, wherein the two liquids comprise a cleaning liquid and a neutralization liquid.

6. The method of cleaning a channel according to any one of claims 1 to 5,
10 wherein the channel is a transmission channel, a heating channel, and/or cooling channel.

7. The method of cleaning a channel according to claim 6, wherein the channel is in a molding cavity.

15 8. The method of cleaning a channel according to any one of claims 1 to 7, wherein the at least one diaphragm pump chamber comprises two diaphragm pump chambers each having a respective diaphragm (8) arranged therein, and wherein the channel (11) extends between the two diaphragm chambers.

20 9. The method of cleaning a channel according to claim 8, wherein one of the diaphragm chambers of the diaphragm pump module (6) is provided in a feed line (15) connecting a reservoir (2) to the channel (11) and comprising a feed pump (4) and a shut-off valve (5) on the reservoir side of the two-diaphragm pump module (6), and wherein the method optionally comprises cutting off the channel (11) and the
25 diaphragm pump module (6) from the reservoir (2) and optionally from the feed pump (4) by means of the shut-off valve (5) after filling the channel (11) with cleaning medium.

10. The method of cleaning a channel according to claim 9, wherein the channel is filled with cleaning medium prior to actuating the alternating pulsating motion of the cleaning medium.

11. The method of cleaning a channel according to any one of claims 1 to 10, wherein the diaphragm is actuated by an external energy source.

5 12. The method of cleaning a channel according to claim 11, wherein the external energy source comprises at least one element selected from the group consisting of a fluid, compressed gas, compressed air, a spring, a magnet, and a piston.

10 13. The method of cleaning a channel according to claim 8 or to any one of claims 1 to 11 depending on claim 8, wherein the two diaphragms (8) are coupled mechanically to each other by means of a pin (19), and wherein the two diaphragms (8) are put to coordinated reciprocal motion by action of a fluid such as compressed air.

15 14. The method of cleaning a channel according to claim 13, wherein the two diaphragms (8) are mechanically coupled to each other.

15. The method of cleaning a channel according to claim 14, wherein the two diaphragms (8) are mechanically coupled to each other with a pin (19).

20 16. The method of cleaning a channel according to any one of claims 13 to 15, wherein

the two diaphragms (8) are driven by a drive unit adapted for coordinated, bi-directional motion of the diaphragms (8) in such a manner that one of the diaphragms is driven to create an underpressure in the corresponding diaphragm pump chamber when the other one of the diaphragms is driven to create an overpressure in the corresponding diaphragm pump chamber.

25

17. The method of cleaning a channel according to any one of claims 13 to 16, further comprising

putting, by coordinated reciprocal motion of the two diaphragms (8), a cleaning medium in alternating pulsating motion inside the channel (11).

5

18. The method of cleaning a channel according to any one of claims 1 to 17, wherein, the pulsation pump module comprises one or two-diaphragms and the cut-off valves (5) and (17) have an active or inactive state, such that the diaphragms can work as suction only, suction-pumping, or pumping only mode.

10

19. The method of cleaning a channel according to any one of claims 1 to 18, wherein the diaphragm pump module (6) is devoid of any check valve.

20. The method of cleaning a channel according to any one of claims 1 to 19, wherein the diaphragm pump module (6) is placed between the to-be-cleaned channel and a feed pump (4), and separated by a controllable shut-off valve (5).

15

21. The method of cleaning a channel according to any one of claims 1 to 20, wherein

the at least one diaphragm pump chamber is placed between the to-be-cleaned channel (11) and a reservoir (2), wherein

20

the diaphragm pump chamber and the reservoir (2) are separated by a flow control system (5, 17),

22. The method of cleaning a channel according to any one of claims 1 to 21, wherein the method further comprises:

25

feeding the channel (11) with the cleaning medium,

thereafter, limiting the flow of the cleaning medium between a reservoir for the cleaning medium and the diaphragm chamber by a flow control system, the flow control system preferably including a cut-off valve.

23. The method of cleaning a channel according to claim 22, wherein limiting
5 the flow of the cleaning medium comprises cutting off the flow.

24. The method of cleaning a channel according to claim 22 or claim 23, wherein the coordinated reciprocal motion of the diaphragm is initiated after the flow of the cleaning medium has been limited.

10
25. The method of cleaning a channel according to any one of claims 1 to 22, wherein

the diaphragm pump module is adapted to work in any one of suction only mode, suction-pressure pumping mode, or pressure pumping only mode.

15
26. A device for cleaning a channel, the device comprising:
a diaphragm pump module (6) having at least one diaphragm pump chamber having a diaphragm (8) arranged therein, the at least one diaphragm pump chamber being adapted to be connected to the channel; and
20 an drive unit for actuating the pump module (6) for generating reciprocal motion of the at least one diaphragm (8), thereby putting a cleaning medium in alternating pulsating motion inside the channel (11).

25
27. The device for cleaning a channel according to claim 26, the device further comprising:

a micro-bubble diffuser (10) integrated into a feed line (15) for feeding the cleaning medium to the channel (11), the diffuser (10) being connected to a compressed air or gas

source (7) for aerating the fluid in the diffuser, e.g., the cleaning medium before it enters the channel (11).

28. The device for cleaning a channel according to claim 26 or claim 27, wherein
5 the diaphragm pump module (6) is devoid of any check valve.

29. The device for cleaning a channel according to any one of claims 19 to 28,
further comprising a heater for heating the cleaning medium being fed to the channel (11).

10 30. The device for cleaning a channel according to any one of claims 26 to 29,
wherein

the diaphragm pump module (6) is a two-diaphragm pump module (6) having two
diaphragm pump chambers each having a respective diaphragm (8) arranged therein, the
two diaphragm pump chambers being adapted to be connected to the channel such that
15 the channel (11) extends between the two diaphragm chambers, and wherein

the drive unit is adapted for generating coordinated reciprocal motion of the
diaphragms (8), thereby putting the cleaning medium in alternating pulsating motion inside
the channel (11).

20 31. The device of cleaning a channel according to claim 30, wherein
the two diaphragms (8) are mechanically coupled to each other.

32. The device of cleaning a channel according to claim 31, wherein
the two diaphragms (8) are mechanically coupled to each other with a pin (19).

25 33. The device of cleaning a channel according to any one of claims 26 to 32,
wherein

the drive unit for actuating the pump (6) comprises an external energy supply for generating coordinated reciprocal motion of the two diaphragms (8).

5 34. The device of cleaning a channel according to claim 33, wherein the external energy supply is a compressed fluid supply.

35. The device of cleaning a channel according to claim 34, wherein the compressed fluid supply is a compressed air supply (7).

10 36. The device for cleaning a channel according to any one of claims 26 to 33, wherein

the diaphragm pump module (6) is a diaphragm pump module (6) having a diaphragm chamber having a respective diaphragm (8) arranged therein, the diaphragm chamber being adapted to be connected to the to-be-cleaned channel (11) such that the diaphragm chamber is placed between the channel (11) and a reservoir (2),

the drive unit is adapted for actuating coordinated reciprocal motion of the diaphragm (8), thereby putting the cleaning medium in alternating pulsating motion inside the channel (11).

20 37. System comprising a cooling channel (11) and the device according to any one of claims 26 to 36 for cleaning the cooling channel, the channel (11) fluidly connected to the at least one diaphragm pump chambers, the at least one diaphragm pump chamber feeding the channel (11) input and/or output.

25 38. System according to the claim 37, wherein the device for cleaning a channel is according to any one of claims 23 to 36, the channel (11) extending between the two diaphragm chambers.

39. The system according to claim 38, wherein the first chamber feeds the channel (11) input, and the second chamber feeds the channel (11) output.

5 40. System according to claim 37 or claim 38, further comprising a feed pump (4) and a shut-off valve (5), wherein

one of the diaphragm chambers of the diaphragm pump module (6) is provided in a feed line connecting a reservoir (2) to the channel (11) and comprising a feed pump (4) and a shut-off valve (5) on the reservoir side of the diaphragm pump module (6), and the other one of the diaphragm chambers is provided in a return line (16) from the channel
10 (11).

41. System according to any one of claims 37 to 40, wherein

the feed line (15) comprises a flow control system (17) for selectively supplying to the diaphragm pump module (6): a) a cleaning medium from the reservoir (2) being a
15 cleaning medium reservoir, or b) a neutralizing medium from a neutralizing medium reservoir (1), and

wherein optionally the return line (16) comprises a flow control system (17) for selectively supplying to the diaphragm pump module (6): a) a cleaning medium from the reservoir (2) being a cleaning medium reservoir, or b) a neutralizing medium from a
20 neutralizing medium reservoir (1).

42. The system according to claim 41, wherein the flow control system (17) of the feed and/or return line comprises a shut-off valve.

25 43. System according to claim 41, wherein the cooling channel (11) is comprised in a channel network having a plurality of channels connected in series and/or in parallel.




FIG.1

