



US009618224B2

(12) **United States Patent**
Emmons et al.

(10) **Patent No.:** **US 9,618,224 B2**

(45) **Date of Patent:** **Apr. 11, 2017**

(54) **AIR QUALITY BASED VENTILATION CONTROL FOR HVAC SYSTEMS**

(56) **References Cited**

(71) Applicant: **Honeywell International Inc.**,
Morristown, NJ (US)

U.S. PATENT DOCUMENTS
4,266,599 A 5/1981 Saunders et al.
4,308,911 A 1/1982 Mandl et al.
(Continued)

(72) Inventors: **David J. Emmons**, Plymouth, MN (US); **Brad Terlson**, Maple Grove, MN (US); **Amy Ragland**, Brooklyn Center, MN (US); **David Quam**, Golden Valley, MN (US); **Brad Paine**, Minnetonka, MN (US)

FOREIGN PATENT DOCUMENTS

CN 201126229 Y 10/2008
CN 102235728 A 11/2011
(Continued)

(73) Assignee: **Honeywell International Inc.**, Morris Plains, NJ (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 466 days.

Ackerly et al., "Occupant Response to Window Control Signaling Systems," Center for the Built Environment, CBE, Summary Report, 28 pages, Apr. 2011.

(Continued)

Primary Examiner — Kidest Bahta
(74) *Attorney, Agent, or Firm* — Seager, Tufte & Wickhem, LLP

(21) Appl. No.: **13/952,256**

(22) Filed: **Jul. 26, 2013**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2015/0032264 A1 Jan. 29, 2015


An HVAC controller and/or server may be programmed to determine if ventilation of a building is desired based, at least in part, on the one or more user-specified air quality thresholds stored in a memory, and one or more of a measure of indoor air quality and a measure of outdoor air quality. The air quality parameter threshold may relate to an air quality index, an air pollutant concentration, a smog alert, a pollen count, a dew point, a chance of precipitation, and/or the like. In addition, the HVAC controller and/or server may take into account current or future weather conditions when determining the ventilation needs of a building. Upon determining that ventilation is needed or recommended, the HVAC controller may send or display a message to the user. The message may recommendation that the user open a window or operate a ventilation system, as desired.

(51) **Int. Cl.**
G06F 19/00 (2011.01)
F24F 11/00 (2006.01)

(52) **U.S. Cl.**
CPC ... **F24F 11/0017** (2013.01); **F24F 2011/0002** (2013.01); **F24F 2011/0019** (2013.01);
(Continued)

(58) **Field of Classification Search**
USPC 700/276, 44, 54, 299; 62/150–151
See application file for complete search history.

17 Claims, 17 Drawing Sheets



(52) U.S. Cl.

CPC F24F 2011/0058 (2013.01); F24F 2011/0071 (2013.01); Y02B 30/78 (2013.01)

2010/0070082 A1 3/2010 Chessel et al.
 2010/0070086 A1* 3/2010 Harrod F24F 11/0086
 700/276
 2010/0102973 A1* 4/2010 Grohman G05B 23/0272
 340/584

(56)

References Cited

U.S. PATENT DOCUMENTS

4,338,791 A 7/1982 Stamp et al.
 4,353,409 A 10/1982 Saunders et al.
 4,567,939 A 2/1986 Dumbleck et al.
 5,822,997 A 10/1998 Atterbury et al.
 5,902,183 A 5/1999 D'Souza et al.
 5,909,378 A 6/1999 De Milleville et al.
 6,216,756 B1* 4/2001 Mason B27B 31/003
 144/246.2
 6,269,650 B1 8/2001 Shaw
 6,478,233 B1 11/2002 Shah
 6,941,193 B2* 9/2005 Frecska G05B 15/02
 236/49.3
 6,968,295 B1 11/2005 Carr
 7,302,313 B2* 11/2007 Sharp G01N 1/26
 700/275
 7,434,413 B2 10/2008 Wruck
 7,839,275 B2 11/2010 Spalink et al.
 8,063,775 B2 11/2011 Reed et al.
 8,121,734 B2 2/2012 Larsen et al.
 8,165,721 B2 4/2012 Petit
 8,239,066 B2 8/2012 Jennings et al.
 2004/0117330 A1 6/2004 Ehlers et al.
 2004/0230344 A1 11/2004 Gallupe et al.
 2005/0021710 A1* 1/2005 Johnson G05B 15/02
 709/223
 2005/0038567 A1* 2/2005 Maeda F24F 11/0086
 700/276
 2007/0264927 A1* 11/2007 Choi F24F 11/0001
 454/196
 2008/0015740 A1 1/2008 Osann
 2008/0217418 A1 9/2008 Helt
 2009/0308372 A1 12/2009 Nordberg et al.
 2010/0025483 A1 2/2010 Hoeynck et al.
 2010/0036531 A1 2/2010 Chessel et al.

2010/0211224 A1 8/2010 Keeling et al.
 2010/0304193 A1 12/2010 Karlsson et al.
 2010/0318227 A1 12/2010 Steinberg et al.
 2011/0035061 A1 2/2011 Altonen et al.
 2011/0223850 A1 9/2011 Narayanamurthy et al.
 2012/0095601 A1 4/2012 Abraham et al.
 2012/0145802 A1 6/2012 Peterson et al.
 2012/0165993 A1 6/2012 Whitehouse
 2012/0221151 A1 8/2012 Steinberg
 2012/0232702 A1 9/2012 Vass et al.
 2012/0239603 A1 9/2012 Raestik et al.
 2012/0245740 A1 9/2012 Raestik et al.
 2012/0259470 A1 10/2012 Nijhawan et al.

FOREIGN PATENT DOCUMENTS

JP 2005003321 1/2005
 JP 2006329584 A 12/2006
 JP 2007172406 A 7/2007
 JP 2009076106 A 4/2009
 JP 2010065937 A 3/2010
 JP 2011007366 A 1/2011
 WO 2010144451 A2 12/2010
 WO 2012024692 A2 2/2012
 WO 2012047938 A2 4/2012

OTHER PUBLICATIONS

Bourgeois et al., "Hybrid Ventilation of Canadian Non-Domestic Buildings: A Procedure for Assessing IAQ, Comfort and Energy Conservation," Air Distribution in Rooms, (ROOMVENT 2000), pp. 761-766, Jul. 9-12, 2000.
 Henze et al., "HVAC Control Algorithms for Mixed Mode Buildings," United States Green Building Council Green Building Research Fund Final Report, 133 pages, May 25, 2002.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

260

Menu > Air Quality Settings

Please select an air quality parameter.

- 268a Air Quality Index
- 268b Smog Alert Level
- 268c Pollen Count
- 268d Air Pollutant Concentration(s)
- 268e Chance Precipitation
- 268f Dew Point

Navigation: Left arrow button, Right arrow button, Done button, Cancel button.

Figure 7




Figure 8

300

302 Please assign a priority level to each of the different parameters listed below.

	Lowest	1	2	3	4	5	Highest
308a Temp.				3			
308b Humidity				4			
308c Pollen Count						5	
308d Air Quality Index				3			

312 312 312 312 312

Help Cancel Done

Figure 9

314 ↗

316 — Prioritize Indoor Air Quality over Energy Efficiency?

Yes 318a

No 318b

Help Done

Figure 10

320




Figure 11




Figure 12




Figure 13

450

Ventilation conditions will be favorable
456 from now until 7:30am tomorrow.
460 Ventilate?

Yes

No

Figure 14

470




Figure 15

500 ↗




Figure 16

530

538 — !Ventilation is no longer needed.

540 — Resume normal operation of HVAC system?

536

Yes

No

OK

Figure 17

1

AIR QUALITY BASED VENTILATION CONTROL FOR HVAC SYSTEMS

TECHNICAL FIELD

The present disclosure relates generally to HVAC controllers and more particularly to HVAC controllers configured to determine ventilation needs of a building based, at least in part, on a measure of air quality.

BACKGROUND

Heating, ventilation, and/or air conditioning (HVAC) systems are often used to control the comfort level within a building or other structure. Such HVAC systems typically include an HVAC controller that controls various HVAC components of the HVAC system in order to affect and/or control one or more environmental conditions within the building. Ventilation may be used to introduce fresh air into the building or structure to improve the overall indoor air quality, and, in some instances, reduce the HVAC system's energy demands. Ventilation may be provided by mechanical/forced air ventilator, an economizer, or simply by opening one or more windows of the building. Because the need for ventilation is dependent on a variety of factors, such as the enthalpy of the indoor and outdoor air, the air quality of the indoor and outdoor air, and/or other factors, it may be difficult for the occupants to determine when ventilation is needed and/or beneficial.

SUMMARY

The present disclosure relates generally to HVAC controllers and more particularly to HVAC controllers configured to determine ventilation needs of a building based, at least in part, on a measure of air quality.

In one illustrative embodiment, a building controller may be configured to communicate with and control one or more components of an HVAC system. The building controller may include, for example, an input/output port for sending and/or receiving data over a network; a memory for storing one or more operating parameters including one or more user-specified air quality thresholds, and a user interface. The building controller may also include a controller coupled to the input/output port, the memory, and the user interface. The controller may be configured to receive and accept one or more user-specified air quality thresholds from a user via the user interface. Additionally, the controller may be configured to receive a first signal indicative of a measure of indoor air quality and a second signal indicative of a measure of outdoor air quality. The controller may be configured to determine if ventilation of the building is desired based, at least in part, on the one or more user-specified air quality thresholds stored in the memory and one or more of the measure of indoor air quality and the measure of outdoor air quality. In some instances, the controller may provide an alert on the user interface of the building controller when the controller determines that ventilation of the building is desired. In some cases, the alert may notify the user that window ventilation is desired. In some cases, an alert may be provided on a user interface of a mobile computing device (such as a mobile phone, tablet computer, lap top computer, etc.) when the controller determines that ventilation of the building is desired.

In another illustrative embodiment, a server may be provided. The server may be connectable to a building controller located within a building over a network. The

2

server may include a data storage device for storing data indicative of environmental conditions inside of and outside of the building. This data may be retrieved from any number of sources including, for example, the building controller for environmental conditions inside of the building, other servers such as servers hosting weather, smog and other data, and/or any other suitable source of data. The controller may be configured to monitor the data indicative of environmental conditions inside of and outside of the building and determine if ventilation of the building is desired based, at least in part, on the data indicative of environmental conditions inside of and outside of the building, and in some cases on one or more user-specified air quality thresholds. The server may include an input/output block for providing an alert to a user when the controller determines that ventilation of the building is desired. For example, the server may provide an alert to the building controller for presentation to a user of the building controller and/or to a mobile computing device for presentation to a user of the mobile computing device.

The preceding summary is provided to facilitate an understanding of some of the innovative features unique to the present disclosure and is not intended to be a full description. A full appreciation of the disclosure can be gained by taking the entire specification, claims, drawings, and abstract as a whole.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure may be more completely understood in consideration of the following description of various illustrative embodiments in connection with the accompanying drawings, in which:

FIG. 1 is a schematic view of an illustrative HVAC system servicing a building or structure;

FIG. 2 is a schematic view of an illustrative ventilation system that may be incorporated into the HVAC system shown in FIG. 1;

FIG. 3 is a schematic view of an illustrative HVAC control system that may facilitate access and/or control of the HVAC system of FIG. 1;

FIG. 4 is a schematic block diagram of an illustrative HVAC controller;

FIG. 5 is a schematic block diagram of an illustrative web server; and

FIGS. 6-17 are exemplary screens that may be displayed via a user interface of an HVAC controller and/or mobile device.

While the disclosure is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit aspects of the disclosure to the particular illustrative embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

DESCRIPTION

The following description should be read with reference to the drawings wherein like reference numerals indicate like elements throughout the several views. The description and drawings show several embodiments which are meant to be illustrative in nature.

FIG. 1 is a schematic view of a building 2 including one or more operable windows 5. The illustrative building 2 has

3

a heating, ventilation, and air conditioning (HVAC) system 4. While FIG. 1 shows a typical forced air type HVAC system, other types of HVAC systems are contemplated including, but not limited to, boiler systems, radiant heating systems, electric heating systems, cooling systems, heat pump systems, and/or any other suitable type of HVAC system, as desired. The illustrative HVAC system 4 of FIG. 1 includes one or more HVAC components 6, a system of ductwork and air vents including a supply air duct 10 and a return air duct 14, and one or more HVAC controllers 18. While the HVAC system 4 shown in FIG. 1 is primarily located within the building 2, it will be generally understood that, in some embodiments, one or more of the HVAC components may be positioned outside of the building such as on a rooftop of the building. The one or more HVAC components 6 may include, but are not limited to, a furnace, a heat pump, an electric heat pump, a geothermal heat pump, an electric heating unit, an air conditioning unit, a damper, a valve, and/or the like. In some cases, the one or more HVAC components may include one or more indoor air quality (IAQ) components including, but not limited to, a humidifier, a dehumidifier, an air exchanger, an economizer, one or more dampers and/or valves, and/or the like. In some instances, the HVAC system 4 may also include a ventilation system (e.g. an air exchanger, an economizer, etc.) that is adapted to ventilate the building 2 with fresh air from outside the building, and may be a mechanical/forced air ventilator or a natural ventilation system. In a natural ventilation system, one or more operable windows 5 may be used (i.e. opened), at least in part, to ventilate the building. In some cases, at least one of the one or more windows 5 may be a power operated window that is configured to open and/or close upon receiving a signal or command from the HVAC controller 18.

It is contemplated that the HVAC controller(s) 18 may be configured to control the comfort level in the building 2 or structure by activating and deactivating the HVAC component(s) 6 in a controlled manner. Additionally, it is contemplated that the HVAC controller(s) may be configured to at least partially control the indoor air quality in the building or structure by activating and deactivating one or more IAQ components, as described herein. In some cases, the HVAC controller 18 may notify the user as to when one or more windows may be opened and/or closed to ventilate the building 2 or structure. The HVAC controller(s) 18 may be configured to control the HVAC component(s) 6 via a wired or wireless communication link 20. In some cases, the HVAC controller(s) 18 may be a thermostat, such as, for example, a wall mountable thermostat, but this is not required in all embodiments. Such a thermostat may include (e.g. within the thermostat housing) or have access to a temperature sensor for sensing an ambient temperature at or near the thermostat. In some cases, the temperature sensor may be located remotely from the thermostat. Additionally, in some instances, the HVAC controller(s) 18 may be a zone controller, or may include multiple zone controllers each monitoring and/or controlling the comfort level within a particular zone in the building or other structure.

In the illustrative HVAC system 4 shown in FIG. 1, the HVAC component(s) 6 may provide heated air (and/or cooled air) via the ductwork throughout the building 2. As illustrated, the HVAC component(s) 6 may be in fluid communication with every room and/or zone in the building 2 via the ductwork 10 and 14, but this is not required. In operation, when a heat call signal is provided by the HVAC controller(s) 18, an HVAC component 6 (e.g. forced warm air furnace) may be activated to supply heated air to one or

4

more rooms and/or zones within the building 2 via supply air ducts 10. The heated air may be forced through supply air duct 10 by a blower or fan 22. In this example, the cooler air from each zone may be returned to the HVAC component 6 (e.g. forced warm air furnace) for heating via return air ducts 14. Similarly, when a cool call signal is provided by the HVAC controller(s) 18, an HVAC component 6 (e.g. air conditioning unit) may be activated to supply cooled air to one or more rooms and/or zones within the building or other structure via supply air ducts 10. The cooled air may be forced through supply air duct 10 by the blower or fan 22. In this example, the warmer air from each zone may be returned to the HVAC component 6 (e.g. air conditioning unit) for cooling via return air ducts 14. In some cases, the HVAC system 4 may include an internet gateway or other device that may allow one or more of the HVAC components 6, as described herein, to communicate over a wide area network (WAN) such as, for example, the Internet.

In some cases, the system of vents or ductwork 10 and/or 14 can include one or more dampers 24 to regulate the flow of air, but this is not required. For example, one or more dampers 24 may be coupled to one or more HVAC controller(s) 18, and can be coordinated with the operation of one or more HVAC components 6. The one or more HVAC controller(s) 18 may actuate dampers 24 to an open position, a closed position, and/or a partially open position to modulate the flow of air from the one or more HVAC components to an appropriate room and/or zone in the building or other structure. The dampers 24 may be particularly useful in zoned HVAC systems, and may be used to control which zone(s) receives conditioned air from the HVAC component (s) 6.

In many instances, one or more air filters 30 may be used to remove dust and other pollutants from the air inside the building 2. In the illustrative example shown in FIG. 1, the air filter(s) 30 is installed in the return air duct 14, and may filter the air prior to the air entering the HVAC component 6, but it is contemplated that any other suitable location for the air filter(s) 30 may be used. The presence of the air filter(s) 30 may not only improve the indoor air quality, but may also protect the HVAC components 6 from dust and other particulate matter that would otherwise be permitted to enter the HVAC component.

FIG. 2 provides a schematic view of an exemplary ventilation system 50 that may be incorporated into the HVAC system 4 as described herein with reference to FIG. 1. In some instances, the ventilation system 50 may be a demand control ventilation system such as shown and described in U.S. Pat. No. 8,364,318 entitled "DEMAND CONTROL VENTILATION SYSTEM WITH FAN SPEED CONTROL", which is incorporated herein by reference in its entirety for all purposes, but this is not required. It will be generally understood that different types of ventilation systems may be incorporated in to the HVAC system 4, as described herein, depending upon the building design and the ventilation needs of the building. In some cases, as shown, the ventilation system 50 may be located upstream of the one or more HVAC components 6 such as, for example, a heating and/or an air conditioning unit, but this is not required.

As shown in FIG. 2, the ventilation system 50 may include an outside air intake 58 and/or an exhaust vent 60. A return air stream 62 may be provided for drawing return air from the inside space of the building 2 through one or more return registers 64. The illustrative HVAC system 4 also includes a fan 69, which may be a single, multiple or infinitely variable multiple speed fan, which can be con-

5

trolled by a controller (e.g. HVAC controller **18**) to induce a desired air flow through one or more HVAC components **6** such as, for example, a furnace or air conditioning unit and to the building **2** as shown at **66** through one or more supply registers **68**. As shown, the ventilation system **50** may employ one or more dampers to control air flows within the various ducts of the ventilation system **50** of the HVAC system **4**. These dampers may include an exhaust damper **70** to regulate the fraction of the return air stream **62** that is exhausted **71** from the building **2**, an intake damper **72** to regulate the flow of an incoming outside air stream **73** into the building **2**, and/or a return damper **74** to regulate the flow of the retained return air stream **75** to mix with the incoming outside air stream **73**. In some cases, the dampers **70**, **72**, and/or **74** may be mechanically coupled together to open and close in a coordinated manner, but this is not required. For example, in some illustrative embodiments, dampers **70** and **72** may open and close together or in sequence, and damper **74** may open and close in an opposite manner to dampers **70** and **72**. It will be generally understood that more or fewer of the dampers **70**, **72**, and **74** may be employed, depending on the HVAC system **4**, the size of the building **2**, and/or the building's ventilation requirements.

In some embodiments, the ventilation system **50**, including the dampers **70**, **72**, **74** and associated duct work, may be included in an economizer. Under some conditions, such an economizer may be used to provide free cooling by mixing cooler incoming outside air **73** with the sometimes warmer retained return air **75** to provide a cooler mixed air stream **82**. In some instances, the HVAC system **4** may include a heat exchanger generally shown at **84** to transfer heat energy between the incoming outside air stream **73** and the exhausted air stream **71**, which may be useful under some operating conditions.

FIG. 3 is a schematic view of an illustrative HVAC control system **100** that facilitates remote access and/or control of the HVAC system **4**, as shown in FIG. 1. As discussed herein, the HVAC system **4** may incorporate a ventilation system such as, for example, ventilation system **50** as shown in FIG. 2. The illustrative HVAC control system **100** may include an HVAC controller, as for example, HVAC controller **18** (see FIG. 1) that is configured to communicate with and control one or more components **6** of the HVAC system **4**. Additionally, in some cases, the HVAC controller **18** may be configured to communicate with and/or control the one or more dampers **70**, **72**, and/or **74** of the ventilation system **50** of the HVAC system **4** to ventilate and, in some instances, provide free heating and/or cooling to the building **2**.

The HVAC controller **18** may communicate with the one or more components **6** of the HVAC system **4** and/or the one or more dampers of the ventilation system **50** via a wired or wireless link. Additionally, the HVAC controller **18** may be adapted to communicate over one or more wired or wireless networks that may facilitate remote access and/or control of the HVAC controller **18** via another device such as a smart phone, a PDA, a tablet computer, a laptop or personal computer, wireless network-enabled key fobs, an e-reader and/or the like. As shown in FIG. 3, the HVAC controller **18** may include a first communications port **102** for communicating over a first network **104**, and in some cases, a second communications port **106** for communicating over a second network **108**. In some cases, the first network **104** (when provided) may be a wireless local area network (LAN), and the second network **108** (when provided) may be a wide area network or global network (WAN) including, for example, the Internet. In some cases, the wireless local area network

6

104 may provide a wireless access point and/or a network host device that is separate from the HVAC controller **18**. In other cases, the wireless local area network **104** may provide a wireless access point and/or a network host device that is part of the HVAC controller **18**. In some cases, the wireless local area network **54** may be an ad-hoc wireless network, but this is not required.

Depending upon the application and/or where the HVAC user is located, remote access and/or control of the HVAC controller **18** may be provided over the first network **104** and/or the second network **108**. A variety of remote wireless devices **112** may be used to access and/or control the HVAC controller **18** from a remote location (e.g. remote from HVAC Controller **18**) over the first network **104** and/or second network **108** including, but not limited to, mobile phones including smart phones, PDAs, tablet computers, laptop or personal computers, wireless network-enabled key fobs, e-readers and the like.

In many cases, the remote wireless devices **112** are configured to communicate wirelessly over the first network **104** and/or second network **108** with the HVAC controller **18** via one or more wireless communication protocols including, but not limited to, cellular communication, ZigBee, REDLINK™, Bluetooth, WiFi, IrDA, dedicated short range communication (DSRC), EnOcean, and/or any other suitable common or proprietary wireless protocol, as desired.

In some cases, the HVAC controller **18** may be programmed to communicate over the second network **108** with an external web service hosted by one or more external servers **116**. A non-limiting example of such an external web service is Honeywell's TOTAL CONNECT™ web service. The HVAC controller **18** may be configured to upload selected data via the network **108** to the external web service where it may be collected and stored on the external server **66**. In some cases, the data may be indicative of the performance of the HVAC system **4**. In some cases, the data may be indicative of indoor air quality and/or outdoor air quality (e.g. temperature, humidity, CO concentration, particulate contamination (dust, pollen, etc)). Additionally, the HVAC controller **18** may be configured to receive and/or download selected data, settings and/or services including software updates from the external web service over the second network **108**. The data, settings and/or services may be received automatically from the web service, downloaded periodically in accordance with a control algorithm, and/or downloaded in response to a user request. In some cases, for example, the HVAC controller **18** may be configured to receive and/or download an HVAC operating schedule and operating parameter settings such as, for example, temperature set points, humidity set points, comfort and/or economy settings, user-specified air quality thresholds, start times, end times, schedules, window frost protection settings, and/or the like. Additionally, the HVAC controller **18** may receive outdoor air quality data. Exemplary outdoor air quality data may include, but is not limited to a current outdoor temperature and/or outdoor humidity, weather related data, pollen forecast and/or pollen count, a current air pollutant concentration, an air quality index and/or air quality alert, a smog alert, and/or the like. An air pollutant concentration may include an ozone concentration, a particulate matter concentration, a carbon monoxide concentration, a nitrogen oxides (NO_x) concentration, a sulfur dioxide concentration, and/or a lead concentration, but not limited to these. The weather related data may include a current weather forecast and/or may include severe weather alerts and other outdoor air quality risks such as, for example, a UV index, a heat index, a heat advisory, a wind

chill, wind direction and/or wind speed. The weather data may be provided to the HVAC controller **18** by a different external server such as, for example, a web server maintained by the National Weather Service. In some instances, the external server **66** may collect appropriate air quality data from one or more other servers, and may deliver data to the HVAC controller **18**. In some cases, the HVAC controller **18** may perform some or all of the determination of whether ventilation is desired based on internal and/or external air quality. In some cases, the external server **66** may perform some or all of the determination of whether ventilation is desired based on internal and/or external air quality, and may communicate results to the HVAC controller **18**. These are just some examples.

FIG. 4 is a schematic view of an illustrative HVAC controller **18** of a thermal comfort control system. In some instances, the HVAC controller **18** may be a thermostat, but this is not required. Additionally, in some cases, the HVAC controller **18** may be accessed and/or controlled from a remote location over a network **108** (FIG. 3) using a mobile wireless device **112** such as, for example, a smart phone, a PDA, a tablet computer, a laptop or personal computer, a wireless network-enabled key fob, an e-reader, and/or the like. As shown in FIGS. 3 and 4, the illustrative HVAC controller **18** may include an input port **102** for communicating with one or more internal and/or remotely located sensors. In some cases, the input port **102** may be in communication with one or more internal sensors. In addition, the input port **102** may be adapted to receive a signal indicative of a measure related to an environmental condition inside or outside of the building. In some cases, the input port **102** may receive the measure related to an environmental condition inside or outside of the building over a wireless network such as, for example, a wireless LAN, but this is not required. The network port **106** may be a wired communications port. In other cases, the network port **106** may be a wireless communications port including a wireless transceiver for sending and/or receiving signals over a wireless network such as for example a wireless local area network (LAN) or a wide area network (WAN) such as, for example, the Internet **108**. In some cases, the network port **106** may be in communication with a wired or wireless router or gateway for connecting to the network **108**, but this is not required. In some cases, the router or gateway may be integral to the HVAC controller **18** or may be provided as a separate device.

Additionally, the illustrative HVAC controller **18** may include a processor (e.g. microprocessor, microcontroller, etc.) **114** and a memory **122**. The processor **114** may be in communication the input port **102** and/or the network port **106** and with the memory **122**. The processor **114** and the memory **122** may be situated within a housing **120** that may include at least one bracket for mounting the HVAC controller **18** to a wall located within the building or structure. In addition, the HVAC controller **18** may include a user interface **118** including a display, but this is not required. In some instances, the user interface **118** may be secured relative to the housing **120**. In other instances, the user interface **118** may be located at a remote device such as any one of the remote devices disclosed herein.

In some cases, HVAC controller **18** may include a timer (not shown). The timer may be integral to the processor **114** or may be a separate component. The HVAC controller **18** may optionally include an input/output block (I/O block) **128** for receiving one or more signals from the HVAC system **4** and/or for providing one or more control signals to the HVAC system **4**. For example, the I/O block **128** may

communicate with one or more HVAC components **6** of the HVAC system **4**. Alternatively, or in addition to, the I/O block **128** may communicate with another controller, which is in communication with one or more HVAC components of the HVAC system **4**, such as a zone control panel in a zoned HVAC system, equipment interface module (EIM), or any other suitable building control device.

The illustrative HVAC controller **18** may include an internal temperature sensor **130** located within the housing **120**, but this is not required. The HVAC controller may also include an internal humidity sensor **132** located within the housing **120**, but this is also not required. When provided, the temperature sensor **130** and/or the humidity sensor **132** may be coupled to the input port **102** which, in turn, is coupled to the processor **114**. In some cases, the HVAC controller **18** may communicate with one or more remote temperature sensors, humidity sensors, occupancy and/or other sensors located throughout the building or structure via, for example, the input port **102** and/or network port **106**. Additionally, in some cases, the HVAC controller may communicate with a temperature sensor and/or humidity sensor located outside of the building or structure for sensing an outdoor temperature and/or humidity if desired. As such, and in some cases, the HVAC controller **18** may receive at least one of a measure related to an indoor temperature inside the building or structure, a measure related to an indoor humidity inside the building or structure, and a measure related to an outdoor temperature and/or outdoor humidity outside of the building or structure.

In some cases, the HVAC controller **18** may receive outdoor air quality related data including data indicative of an outdoor air quality parameter via the network port **106**. The outdoor air quality related data may include a current outdoor temperature and/or outdoor humidity, weather related data, pollen forecast and/or pollen count, a current air pollutant concentration, an air quality index and/or air quality alert, a smog alert, and/or the like. An air pollutant concentration may include an ozone concentration, a particulate matter concentration, a carbon monoxide concentration, a nitrogen oxides (NO_x) concentration, a sulfur dioxide concentration, and/or a lead concentration, but not limited to these. Because of their possible effect on public health, these six common air pollutants are monitored by different agencies and reported by to the Environmental Protection Agency (EPA). The weather related data may include a current or future weather forecast and/or may include severe weather alerts and other outdoor air quality risks such as, for example, a UV index, a heat index, a wind chill, wind direction and/or wind speed. Severe weather alerts may include, but are not limited to, such as for example, a thunderstorm watch or warning, a tornado watch or warning, a flash flood watch or warning, and/or the like. These are just some examples of outdoor air quality related data that may be received by the HVAC controller **18**. Such severe weather alerts and/or information about other air quality risks may be displayed as an alert to the user via the display of the HVAC controller **18**. Additionally, an air quality alert, a pollen forecast or related alert, a smog alert, an air quality index alert and/or heat advisory, but not limited to these, may also be displayed to the user via the display of the HVAC controller **18**. In some cases, the air quality alert may indicate the short term and/or long term health risks associated with the air quality alert.

The processor **114** may operate in accordance with an algorithm that controls or at least partially controls one or more HVAC components of an HVAC system such as, for example, HVAC system **4** shown in FIG. 1. The processor

114, for example, may operate in accordance with a control algorithm that provides temperature set point changes, humidity set point changes, schedule changes, air quality thresholds, start and end time changes, window frost protection setting changes, operating mode changes, ventilation changes, and/or the like. At least a portion of the control algorithm may be stored locally in the memory **122** of the HVAC controller **18** and, in some cases, may be received from an external web service over the second network **108**. The control algorithm (or portion thereof) stored locally in the memory **122** of the HVAC controller **18** may be periodically updated in accordance with a predetermined schedule (e.g. once every 24 hours, 48 hours, 72 hours, weekly, monthly, etc.), updated in response to any changes to the control algorithm made by a user, and/or updated in response to a user's request. The updates to the control algorithm or portion of the control algorithm stored in the memory **122** may be received from an external web service over the second network **108**. In some cases, the control algorithm may include settings such as set points.

In some cases, the processor **114** may operate according to a first operating mode having a first temperature set point, a second operating mode having a second temperature set point, a third operating mode having a third temperature set point, and/or the like. In some cases, the first operating mode may correspond to an occupied mode and the second operating mode may correspond to an unoccupied mode. In some cases, the third operating mode may correspond to a holiday or vacation mode wherein the building or structure in which the HVAC system **4** is located may be unoccupied for an extended period of time. In other cases, the third operating mode may correspond to a sleep mode wherein the building occupants are either asleep or inactive for a period of time. These are just some examples. It will be understood that the processor **114** may be capable of operating in additional modes as necessary or desired. The number of operating modes and the operating parameter settings associated with each of the operating modes may be established locally through a user interface, and/or through an external web service and delivered to the HVAC controller via the second network **108** where they may be stored in the memory **122** for reference by the processor **114**.

In some cases, the processor **114** may operate according to one or more predetermined operating parameter settings associated with a user profile for an individual user. The user profile may be stored in the memory **122** of the HVAC controller **18** and/or may be hosted by an external web service and stored on an external web server. The user profile may include one or more user-selected settings for one or more operating modes that may be designated by the user. In addition, the user profile may include one or more air quality thresholds that may be specified by the user and which, in some cases may be utilized by the processor to determine and/or anticipate the ventilation needs of the building for when the HVAC system **4** is operating in a selected operating mode. For example, the processor **114** may operate according to a first operating mode having a first temperature set point associated with a first user profile, a second operating mode having a second temperature set point associated with the first user profile, a third operating mode having a third temperature set point associated with the first user profile, and/or the like. In some cases, the first operating mode may correspond to an occupied mode, the second operating mode may correspond to an unoccupied mode, and the third operating mode may correspond to a vacation or extended away mode wherein the building or structure in which the HVAC system **4** is located may be unoccupied for

an extended period of time. In some cases, multiple user profiles may be associated with the HVAC controller **18**. In certain cases where two or more user profiles are associated with the HVAC controller **18**, the processor **114** may be programmed to include a set of rules for determining which individual user profile takes precedence for controlling the HVAC system when both user profiles are active.

In the illustrative embodiment of FIG. **4**, the user interface **118**, when provided, may be any suitable user interface that permits the HVAC controller **18** to display and/or solicit information, as well as accept one or more user interactions with the HVAC controller **18**. For example, the user interface **118** may permit a user to locally enter data such as temperature set points, humidity set points, air quality thresholds for one or more air quality parameters, starting times, ending times, schedule times, diagnostic limits, responses to alerts, and the like. In one embodiment, the user interface **118** may be a physical user interface that is accessible at the HVAC controller **18**, and may include a display and/or a distinct keypad. The display may be any suitable display. In some instances, a display may include or may be a liquid crystal display (LCD), and in some cases a fixed segment display or a dot matrix LCD display. In other cases, the user interface **118** may be a touch screen LCD panel that functions as both display and keypad. The touch screen LCD panel may be adapted to solicit values for a number of operating parameters and/or to receive such values, but this is not required. In still other cases, the user interface **118** may be a dynamic graphical user interface.

In some instances, the user interface **118** need not be physically accessible to a user at the HVAC controller **18**. Instead, the user interface **118** may be a virtual user interface that is accessible via the first network **104** and/or second network **108** using a mobile wireless device such as one of those devices **112** previously described herein. In some cases, the virtual user interface may include one or more web pages that are broadcasted over the first network **104** (e.g. LAN) by an internal web server implemented by the processor **114**. When so provided, the virtual user interface may be accessed over the first network **104** using a remote wireless device **112** such as any one of those listed above. Through the one or more web pages, the processor **114** may be configured to display information relevant to the current operating status of the HVAC system **4** including the current operating mode, temperature set point, actual temperature within the building, outside temperature, outside humidity, and/or the like. Additionally, the processor **114** may be configured to display information relevant to the current indoor and/or outdoor air quality including an air quality index or alert, air pollutant concentrations, UV index, wind direction and wind speed, smog alerts, pollen forecast and/or pollen count, weather forecast data including any weather related alerts, and/or the like. In some instances, this information may be displayed to the user via a dashboard that displays multiple data and alerts in a single screen. In some cases, the dashboard maybe a user interactive dashboard that may permit a user to select a data item or alert for additional information. The processor **114** may also be configured to display or transmit one or more messages to the user regarding the ventilation needs and/or status of the building. Additionally, the processor **114** may be configured to receive and accept any user inputs entered via the virtual user interface **118** including temperature set points, humidity set points, air quality thresholds, starting times, ending times, schedule times, window frost protection settings, diagnostic limits, responses to alerts, and the like.

In other cases, the virtual user interface may include one or more web pages that are broadcasted over the second network 108 (e.g. WAN or the Internet) by an external server (e.g. web server 116). The one or more web pages forming the virtual user interface may be hosted by an external web service and associated with a user account having one or more user profiles. The external server 116 may receive and accept any user inputs entered via the virtual user interface and associate the user inputs with a user's account on the external web service. If the user inputs include any changes to the existing control algorithm including any temperature set point changes, humidity set point changes, schedule changes, air quality parameter threshold changes, start and end time changes, window frost protection setting changes, operating mode changes, and/or changes to a user's profile, the external web server may update the control algorithm, as applicable, and transmit at least a portion of the updated control algorithm over the second network 108 to the HVAC controller 18 where it is received via the second network port 106 and may be stored in the memory 122 for execution by the processor 114.

The memory 122 of the illustrative HVAC controller 18 may be in communication with the processor 114. The memory 122 may be used to store any desired information, such as the aforementioned control algorithm, set points, schedule times, air quality thresholds, and the like. The memory 122 may be any suitable type of storage device including, but not limited to, RAM, ROM, EPROM, flash memory, a hard drive, and/or the like. In some cases, the processor 114 may store information within the memory 122, and may subsequently retrieve the stored information from the memory 122.

In some instances, the processor 114 may be programmed to determine, at least in part, the ventilation needs of the building or structure 2. The ventilation needs of the building may include a current or future time period when ventilation may be desirable or beneficial. Additionally, the ventilation needs may include a current or future time period when ventilation is not required or recommended. It will be generally understood that in some cases a current time period may overlap, at least in part, with a future time period.

In some cases, the processor 114 may be programmed to determine and/or predict when window ventilation is recommended to ventilate the building to improve and/or maintain an indoor air quality of the building 2. In some cases, the processor 114 may be configured to determine and/or predict when operation of a ventilation system such as that shown in FIG. 2 and/or an economizer is desired to improve and/or maintain an indoor air quality of the building 2. The processor 114 may also be programmed to determine if a combination of window ventilation and mechanical ventilation is desirable. Additionally, the processor 114 may be configured to determine and/or predict when ventilation (window, mechanical, or a combination thereof) is no longer needed and/or recommended. The processor 114 may be programmed to determine and/or predict the ventilation needs of the building or structure 2 based on a number of different parameters indicative of indoor or outdoor air quality including, but not limited to an indoor temperature, an indoor humidity, an outdoor temperature, an outdoor humidity, a current or future weather forecast, a pollen forecast and/or pollen count, a current air pollutant concentration, an air quality index and/or air quality alert, a smog alert, one or more user-specified air quality thresholds, and/or the like. In some instances, the processor 114 may determine that ventilation is needed at a current time (e.g.

now) and for some predetermined amount of time into the future extending beyond the current time. The predetermined period of time may range from about 15 minutes up to about 5 days, but not limited to this.

In some cases, the processor 114 may be programmed to determine and/or predict the ventilation needs of the building 2 based, at least in part, on a measure indicative of indoor air quality, a measure indicative of outdoor air quality, and a user-specified air quality threshold. The user-specified air quality threshold may be accepted from a user via the user interface 118 of the HVAC controller 18 and stored in the memory 122. The user-specified air quality threshold may relate to an indoor air quality parameter and/or an outdoor air quality parameter. Exemplary indoor air quality parameters may include an indoor temperature and an indoor humidity. Exemplary outdoor air quality parameters may include a current outdoor temperature and/or outdoor humidity, weather related data, pollen forecast and/or pollen count, a current air pollutant concentration, an air quality index and/or air quality alert, a smog alert, and/or the like. An air pollutant concentration may include an ozone concentration, a particulate matter concentration, a carbon monoxide concentration, a nitrogen oxides (NO_x) concentration, a sulfur dioxide concentration, and/or a lead concentration, but not limited to these. The weather related data may include a current or future weather forecast and/or may include severe weather alerts and other outdoor air quality risks such as, for example, a UV index, a heat index, a wind chill, wind direction and/or wind speed. Severe weather alerts may include, but are not limited to, such as for example, a thunderstorm watch or warning, a tornado watch or warning, a flash flood watch or warning, and/or the like. These are just some examples. In many cases, the user-specified air quality parameter threshold relates to an outdoor air quality parameter such as discussed herein.

The processor 114 may be programmed to solicit and accept one or more air quality thresholds from a user via the user interface 118 of the HVAC controller 18. The one or more air quality thresholds specified by the user may be based on the user's needs and/or desired comfort level. For example, an allergy sufferer may specify a lower threshold for a pollen count than someone who does not suffer from pollen allergies. Similarly, someone having poor respiratory health or an elderly person may specify a lower threshold for a smog alert level or air quality index level than an average adult having a good overall health profile. In yet another example, someone who cannot tolerate high humidity may specify a lower humidity threshold. These are just some examples. In some instances, where a user has not specified any air quality thresholds, the processor 114 may be configured to rely on default values determined by the manufacturer or installer, which in some cases may be based on the needs of the average population. The default values may be stored in the memory 122 where they may be retrieved by the processor 114. The default values for one or more air quality parameters may be altered by the processor 114 upon receiving a user-specified air quality parameter threshold from a user via the user interface 118 of the HVAC controller 18.

In addition to the one or more user-specified air-quality thresholds received from a user, the processor 114 may receive one or more signals indicative of an indoor air quality and/or outdoor air quality via the input port 102 and/or network port 106. In some cases, for example, the processor 114 may receive a first signal indicative of a measure of indoor air quality from either an internal sensor such as, for example, internal temperature sensor 130 or

13

internal humidity sensor **132** and/or a from a temperature or humidity sensor external to the HVAC controller **18**, but located within the building **2** via the input port **102**. Additionally, the processor **114** may receive a second signal indicative of a measure of outdoor air quality via the input port **102** and/or, the network port **106**. In some cases, the second signal indicative of a measure of outdoor air quality may be received from a sensor such as, for example, a temperature or humidity sensor located outside of the building or structure **2**, and may be indicative of an outdoor temperature, outdoor humidity and/or any other suitable outdoor air quality parameter.

Additionally, the processor **114** may be programmed to receive a variety of weather related data and/or air quality data via the network port **106**. In some cases, the processor **114** may receive data indicative of a pollen forecast and/or a pollen count, a smog alert level, an air quality index level, an air pollutant concentration level, a dew point, a wind speed and/or wind direction, current weather conditions, a future weather forecast, any weather related alerts including a severe weather alert, wind chill advisory, heat advisory and/or the like, a UV index value, a chance percent of precipitation, and/or any other suitable weather related data via the network port **106**. The various data may be received from one or more external servers **66** that host such data such as, for example, a web server hosted by the NOAA's National Weather Service, AccuWeather.com (www.accuweather.com), California's South Coast Air Quality Management District, Colorado's Air Quality Control Commission, the National Allergy Bureau, and/or a web service (such as Honeywell's TOTAL CONNECT™ Web Service) that collects and aggregates the appropriate data. In some cases, regional air quality management agencies or reporting agencies may provide data indicative of smog alert levels, air quality index levels, air pollutant concentrations, and/or pollen counts. These are just some examples.

The processor **114** may utilize the weather and/or air quality data received via the network when determining and/or anticipating the current and/or future ventilation needs of the building **2**. For example, in some cases, the processor **114** may receive data indicative of current weather conditions and may determine and/or anticipate the ventilation needs of the building **2** based, at least in part, on the current weather conditions in addition to a user-specified air quality threshold parameter value and measures related to an indoor air quality and an outdoor air quality. In some cases, the processor **114** may receive data indicative of a smog alert level and may determine and/or anticipate the ventilation needs of the building **2** based, at least in part, on the smog alert level. In yet another example, the processor **114** may receive data indicative of a current pollen count and may determine and/or anticipate the ventilations needs of the building **2** based, at least in part, on the current pollen count. In still yet another example, the processor **114** may receive indicative of one or more air pollutant concentrations and may determine and/or anticipate the ventilation needs of the building **2** based, at least in part, on the air pollutant concentrations. These are just some examples. It will be generally understood that the processor **114** may be programmed to determine and/or anticipate the ventilation needs of the building **2** based on a combination of a number of different parameters including, but not limited to one or more measures related to an indoor air quality and/or an outdoor air quality, one or more user specified air quality thresholds, and weather and/or air quality related data.

In some cases, the processor **114** may be programmed to compare the weather and/or air quality data received via the

14

network port **106** to air quality thresholds, including any user-specified air quality thresholds, that are stored in the memory **122** and, based at least in part on the comparison, determine and/or anticipate the current and/or future ventilation needs of the building **2**. For example, if the processor **114** determines that an air quality index value is lower than a user-specified threshold for an air quality index, then the processor **114** may determine that ventilating with fresh air from the outside is recommended or desired. Ventilation of the building may be accomplished by opening one or more windows **5** in the building **2** and/or by operating a ventilation system which draws in fresh air from outside the building **2** as shown and described in reference to FIG. **2**. In some cases, ventilation of the building may be accomplished by automatically opening one or more power operated windows **5** in the building **2**. In other cases, the processor **114** may display a message to the user via the user interface **118** of the HVAC controller recommending that the user manually open one or more windows **5** in the building **2** for ventilation. In still other cases, the processor **114** may transmit a message to the user via SMS text message or email recommending that the user manually open one or more windows **5** in the building **2** for ventilation. Similarly, when the processor **114** determines that ventilation is no longer necessary or recommended, the processor may display or transmit a message to the user recommending that the user close any open windows **5** or cease operation of any ventilation equipment. In other cases, when the processor **114** determines that ventilation is no longer necessary or recommended, the processor may display or transmit a message notifying the user that ventilation is no longer necessary and/or recommended and may automatically close one or more windows and/or cease operation of a ventilation system associated with the building **2**. Additionally, in some cases, the processor **114** may cause the HVAC controller **18** to control one or more HVAC controller to regulate the environmental conditions within the building according to an operating schedule previously stored in the memory of the HVAC controller **18**.

Additionally, in some instances, the processor **114** may be configured to prioritize a user-specified air quality parameter threshold over measures related to an indoor air quality and an outdoor air quality when determining the ventilation needs of the building **2**. For example, if the outdoor temperature is lower than an indoor temperature, it would be generally expected that the processor **114** may determine that window ventilation is recommended. However, if a pollen count is higher than a user-specified threshold parameter value for the pollen count then, based on the higher priority assigned to the user specified threshold parameter which, in this case, is a pollen count, the processor **114** may determine that window or other ventilation is not recommended. This is just one example. In some cases, the processor **114** may be configured to solicit and accept user-determined priority for a number of different parameters including, but not limited to, one or more measures related to an indoor air quality and/or an outdoor air quality, one or more user specified air quality thresholds, and/or a variety of weather and/or air quality related data.

In some instances, when determining and/or anticipating the ventilation needs of the building, the processor **114** may be programmed to assign a user-determined priority or weight to a number of different parameters related to an indoor air quality and/or an outdoor air quality. The processor **114** may use the weighted indoor air quality parameter values and/or outdoor air quality parameter values when determining the indoor air quality and the outdoor air quality

15

and/or when comparing the indoor air quality to the outdoor air quality when determining the ventilation needs of the building 2.

Equation 1 is an exemplary equation that may be used by the processor 114 when determining an outdoor air quality. Each of the parameters used to determine an outdoor air quality value may be assigned a weight based, at least in part, on a user-determined priority for each of the different parameters. The outdoor air quality value may be at least a function of the sum of each of the different parameter values and in some cases, may be an average value. A normalization factor could also be used.

$$\text{Outdoor Air Quality} = w_t \text{Outdoor Air Temp} + w_{hum} \text{Outdoor Humidity} + w_p \text{Pollen Count} + w_{AQI} \text{Air Quality Index} \quad \text{Eq. 1}$$

Equation 2 is an exemplary equation that may be used by the processor 114 when determining an outdoor air quality. Each of the parameters used to determine an outdoor air quality value may be assigned a weight based, at least in part, on a user-determined priority for each of the different parameters. The outdoor air quality value may be at least a function of the sum of each of the different parameter values and in some cases, may be an average value. A normalization factor could also be used.

$$\text{Indoor Air Quality} = w_t \text{Indoor Air Temp} + w_{hum} \text{Indoor Humidity} + w_{CO2} \text{CO}_2 + w_{CO} \text{CO} \quad \text{Eq. 2}$$

In some cases, the processor 114 may be programmed to ventilate the building or recommend ventilation of the building when the processor 114 determines that the outdoor air quality is greater than the indoor air quality. Under certain circumstances, ventilating the building 2 maybe less energy efficient than continuing to operate the HVAC system 4 according to its current program. In some instances, the processor 114 may be configured to prompt the user to enter their preference as to ventilating the building using outside air to maintain or improve the indoor air quality, even when it is less energy efficient to do so. In other words, the processor 114 may present an option to the user via the user interface 118 for the user to override a more energy efficient operation of the HVAC system 4 in favor of increasing the indoor air quality of the building 2. In many cases, the override of a more energy efficient operation configuration in favor of maintaining or increasing the indoor air quality is temporary.

The processor 114 may also be programmed to determine an amount of time in which ventilation is needed and/or recommend based on one or more user-specified air quality parameter thresholds and/or any weather related or air quality data, as described herein. The amount of time determined for ventilation may be based, at least in part, on one or more user-specified air quality thresholds and any weather and/or air quality data received via the network port 106. In some cases, the processor 114 may also be configured to predict when ventilation is recommended based, at least in part, on any weather and/or air quality data received via the network port 106.

Upon determining the ventilation needs of the building 2, the processor 114 may be configured to automatically transmit one or more command signals to an IAQ component or other HVAC component 6 via the input/output block 128 to ventilate the building 2. The building 2 may be ventilated by opening one more powered windows and/or operation of mechanical ventilation system. In other instances, upon determining the ventilation needs of the building 2, the processor 114 may be configured to notify the user that ventilation is recommended and/or needed. In some cases,

16

the processor 114 may be configured to notify that the user that the building 2 is currently being ventilation and may provide an amount of time for ventilation. For example, the processor 114 may be configured to transmit a data package to a user via the input port 102 and/or network port 106. The data package transmitted to the user may be in the form of a SMS text message or an email, and may notify the user to operate an IAQ component or that window ventilation is recommended. Alternatively, or in addition, the processor 114 may be configured to display a message or alert to the user via the user interface 118 of the HVAC controller 18 indicating the need for ventilation. The message may instruct the user to operate any IAQ components such as, for example, a mechanical ventilation system and/or economizer or, in some cases, may indicate that window ventilation is recommended. In other instances, the message may notify the user that the HVAC controller 18 is commencing operation of any ventilation equipment and/or opening any power operated windows 5 located within the building 2. Additionally, the message may indicate the length of time desired or needed for adequate ventilation and/or may include a prediction as to when conditions for ventilation may be favorable.

In still other instances, the processor 114 may be programmed to follow one or more pre-set or customized programs for ventilating the building 2. The pre-set or customized programs may be utilized ventilate the building 2 under selected conditions, and may be selected by the user through the user interface 118 of the HVAC controller 18. For example, a first pre-set or custom program may be selected by a user when a building occupant is ill, and may cause the processor 114 to control transmit one or more command signals to an IAQ component or other HVAC component 6 to increase ventilation and humidity and, in some cases, maintain an elevated temperature overnight. Another pre-set or customized program may be selected by a user when the building is occupied above typical levels (e.g., when the occupants are hosting a gathering), and may cause the processor 114 transmit one or more command signals to an IAQ component or other HVAC component 6 to increase ventilation, lower indoor humidity and, in some cases, lower the temperature within the building. Still another pre-set or customized program may be selected by a user for operating the HVAC components 6, including any IAQ components during allergy season when pollen count levels are expected to be elevated, and may cause the processor 114 to transmit one or more command signals to an IAQ component or other HVAC component 6 to minimize outdoor ventilation and increase the blower speed within the building 2 when the pollen count has reached a pre-determined level. These are just some examples.

Referring back to FIG. 3, in some instances, the HVAC controller 18 may be programmed to communicate over the network 108 with an external web service hosted by one or more external servers 116. A non-limiting example of such an external web service is Honeywell's TOTAL CONNECT™ web service. In some cases, as will be discussed in greater detail below, the server 116 may be configured to determine the ventilation needs of the building in which the HVAC controller 18 is located based, at least in part, on data received from one or more sensors indicative of the environmental conditions inside of the building, outside of the building, and/or weather related data including air quality data sometimes received from another web server such as a National Weather Service web server which may also be in communication with the server 116 and/or HVAC controller 18. In some cases, the server 116 may also be configured to

17

receive one or more user specified air quality thresholds that may be provided by the user via the user interface **118** of the HVAC controller **18** and/or via one or more remote devices **112**. The one or more user specified air quality thresholds may also be used by the server **116** when determining the ventilation needs of the building **2**. As discussed herein, the user interface **118** may be located at the HVAC controller **18** or provided at a remote device **112**. In some cases, the server **116** may serve up on or more web pages forming the user interface **118** for the HVAC controller **18** that may be accessible to a user over a network such as, for example, network **108** when using a remote device such as any of those devices **112** discussed herein or that may be displayed on the display of the HVAC controller **18**.

FIG. 5 is a schematic view of an external server **116** for hosting an external web service as discussed herein. As discussed above with reference to FIG. 3, the external server **116** may be in communication with the HVAC controller **18** over a network **108** such as, for example, the Internet. As shown in FIG. 5, the external server **116** can include at least one input/output port **220** for sending and/or receiving data over the network **108** to and from the HVAC controller **18** and/or another remote device **112**. Additionally, the external server **116** may send and/or receive data to and from another web server over the network **108** via the input/output port **220**. The external server **116** can also include a data storage device **214**, and a controller **218** coupled to the input output port **220** and the data storage device **214**. In some cases, the controller **218** may be configured to implement a web application **222** for serving up one or more web pages over the network **108** via the input/output port **220**. The one or more web pages may be accessed and viewed by a user using a remote device such as, for example, any one of the remote devices **112** described herein or at the HVAC controller **18**. In some cases, the one or more web pages may provide a virtual user interface **118** for interacting with the HVAC controller **18**. Through the one or more web pages forming the virtual user interface **118**, a user may respond to alerts and may enter or change various HVAC operating parameters including, but not limited, to temperature set points, humidity set points, starting times, ending times, schedule times, diagnostic limits, and/or the like, as well as respond to one or more alerts. Additionally, through the one or more web pages, a user may provide one or more air quality thresholds as discussed herein. In some cases, rather than providing one or more web pages, an application (app) may be downloaded to a remote device **112**. The application may connect to the external server **116** and provide the virtual user interface **118** on the remote device.

In some instances, the controller **218** may be programmed to determine and/or anticipate the current and/or future ventilation needs of the building or structure **2** in which the HVAC controller **18** is connected. For example, in some cases, the controller **218** may be programmed to determine and/or anticipate when window ventilation is recommended to ventilate the building to improve and/or maintain an indoor air quality of the building **2**. In other cases, the controller **218** may be configured to determine and/or anticipate when operation of a ventilation system such as that shown in FIG. 2 and/or an economizer is necessary to improve and/or maintain an indoor air quality of the building **2**. In some cases, the controller **218** may receive data related to the indoor and/or outdoor air quality from the HVAC controller **18**. In some cases, the controller **218** may be programmed to determine if a combination of window ventilation and mechanical ventilation is desired. Additionally, the processor **114** may be configured to determine

18

and/or anticipate when ventilation is no longer needed and/or recommended. The controller **218** may be programmed to determine and/or anticipate the ventilation needs of the building or structure **2** based on a number of different parameters indicative of indoor or outdoor air quality including, but not limited to an indoor temperature, an indoor humidity, an outdoor temperature, an outdoor humidity, a pollen forecast and/or a pollen count, a smog alert level, an air quality index level, a dew point, a wind speed and/or wind direction, current weather conditions, a future weather forecast, a chance percent of precipitation, a user-specified air quality parameter threshold value, and/or the like.

In some cases, the controller **218** may be programmed to determine the ventilation needs of the building **2** based, at least in part, on a measure indicative of indoor air quality, a measure indicative of outdoor air quality, and one or more user-specified air quality thresholds. The user-specified air quality threshold(s) may be accepted from user via the user interface **118** of the HVAC controller **18** and stored in the memory **122**. In some instances, as discussed herein, the user interface **118** may be provided by one or more web pages served up by the server **116** over a network **108**, which may be accessed at the HVAC controller **18** or by using a remote device **112**. In some cases, the HVAC controller **18** and/or remote device **112** may execute an application (app) that provides the user interface.

The user-specified air quality threshold may relate to an indoor air quality parameter and/or an outdoor air quality parameter. Exemplary indoor air quality parameters may include an indoor temperature and an indoor humidity. Exemplary outdoor air quality parameters may include a current outdoor temperature and/or outdoor humidity, weather related data, pollen forecast and/or pollen count, a current air pollutant concentration, an air quality index and/or air quality alert, a smog alert, and/or the like. An air pollutant concentration may include an ozone concentration, a particulate matter concentration, a carbon monoxide concentration, a nitrogen oxides (NO_x) concentration, a sulfur dioxide concentration, and/or a lead concentration, but not limited to these. The weather related data may include a current weather forecast and/or may include severe weather alerts and other outdoor air quality risks such as, for example, a UV index, a heat index, a wind chill, wind direction and/or wind speed. Severe weather alerts may include, but are not limited to, such as for example, a thunderstorm watch or warning, a tornado watch or warning, a flash flood watch or warning, and/or the like. These are just some examples. In many cases, the user-specified air quality parameter threshold relates to an outdoor air quality parameter such as discussed herein.

The controller **218** of the server **116** may be programmed to solicit and accept one or more air quality parameter threshold(s) from a user via the user interface **118** of the HVAC controller **18** and/or via a virtual user interface on a remote device **112**. The one or more air quality parameter threshold(s) specified by the user may be based on the user's needs and/or desired comfort level. For example, an allergy sufferer may specify a lower threshold value for a pollen count than someone who does not suffer from allergies. Similarly, someone having poor respiratory health or an elderly person may specify a lower threshold value for a smog alert level or air quality index level than the average adult having a good overall health profile. In yet another example, someone who cannot tolerate high humidity may specify a lower threshold value for indoor humidity. These are just some examples. In some instances, where a user has not specified

19

any air quality parameter threshold, the controller **218** may be configured to rely on default values determined by the manufacturer or the installer for a variety of air quality parameters. These default values may be stored in the data storage device **214** where they may be retrieved by the controller **218**. The default values for one or more air quality thresholds may be altered by the controller **218** upon receiving a user-specified air quality parameter threshold from a user via the user interface **118** of the HVAC controller **18** or via a virtual user interface.

The controller **218** may receive one or more signals indicative of an indoor air quality and/or outdoor air quality transmitted over the network **108** via the input/output port **220**. In some cases, the one or more signals indicative of an indoor air quality and/or outdoor air quality may be transmitted by the HVAC controller **18** to the server **116** where they may be received by the controller **218** via the input/output port **220**. In other cases, the one or more signals indicative of an indoor air quality and/or outdoor air quality may be transmitted by one or more network enabled sensors (e.g. sensors) which may be capable of transmitting and/or receiving signals indicative of indoor and/or outdoor environmental conditions over a network such as, for example, network **108** where they may be received by the controller **218** via the input/output port. In some cases, the signals may be incorporated into a data transmission package which may contain additional data, but this is not required.

In some cases, the controller **218** may be programmed to receive a variety of weather related data and/or air quality data via an additional input/output port **220**. In some cases, the controller **218** may receive data indicative of a pollen forecast and/or a pollen count, a smog alert level, an air quality index level, an air pollutant concentration level, a dew point, a wind speed and/or wind direction, current weather conditions, a future weather forecast, any weather related alerts including a severe weather alert, wind chill advisory, heat advisory, and/or the like, a UV index value, a chance percent of precipitation, and/or any other suitable weather related from another web server via the input/output port **220**. The various data may be received from one or more external servers **66** that host such data such as, for example, a web server hosted by the NOAA's National Weather Service, AccuWeather.com (www.accuweather.com), California's South Coast Air Quality Management District, Colorado's Air Quality Control Commission, the National Allergy Bureau, and/or a web service (such as Honeywell's TOTAL CONNECT™ Web Service) that collects and aggregates the appropriate data. In some cases, regional air quality management agencies or reporting agencies may provide data indicative of smog alert levels, air quality index levels, air pollutant concentrations, and/or pollen counts. These are just some examples.

It is contemplated that the controller **218** may utilize any weather and/or air quality data received via the network when determining the ventilation needs of the building. For example, in some cases, the controller **218** may receive data indicative of current weather conditions and may determine the ventilation needs of the building **2** based, at least in part, on the current weather conditions in addition to a user-specified air quality threshold parameter value and measures related to an indoor air quality value received from the HVAC controller **18**. Similarly, the controller **218** may receive data indicative of a smog alert level and may determine and/or predict the ventilation needs of the building **2** based, at least part, on the smog alert level in addition to a user-specified air quality threshold. In yet another example, the controller **218** may receive data indicative of a

20

current pollen count and may determine and/or predict the ventilations needs of the building **2** based, at least in part, on the current pollen count in addition to a user-specified air quality threshold. In still yet another example, the controller **218** may receive indicative of one or more air pollutant concentrations and may determine and/or predict the ventilation needs of the building **2** based, at least in part, on the air pollutant concentrations. These are just some examples. In some instances, the controller **218** may be programmed to determine and/or anticipate the ventilation needs of the building **2** based on a combination of two or more different parameters including, but not limited to one or more measures related to an indoor air quality, one or more measures related to an outdoor air quality, and/or one or more user specified air quality thresholds.

In some cases, the controller **218** may be programmed to compare the weather and/or air quality data received via the input/output port **220** to the air quality thresholds, including any user-specified air quality thresholds stored in the memory **122** and, based at least in part on the comparison, determine the ventilation needs of the building **2**. In one example, if the controller **218** determines that an air quality index value is lower than a user-specified threshold for an air quality index, then the controller **218** may determine that ventilating with fresh air from the outside of the building is desirable or recommended. Ventilation of the building may be accomplished by, for example, opening one or more windows of the building and/or by operating a ventilation system which draws in fresh air from outside the building as shown and described in reference to FIG. **2**. In some cases, ventilation of the building may be accomplished by automatically opening one or more power operated windows **5** in the building **2**. In other cases, the controller **218** may display a message to the user via the user interface **118** of the HVAC controller recommending that the user manually open one or more windows **5** in the building **2** for ventilation. In still other cases, the controller **218** may transmit a message to the user via SMS text message or email recommending that the user manually open one or more windows **5** in the building **2** for ventilation. Similarly, when the controller **218** determines that ventilation is no longer necessary or recommended, the processor may display or transmit a message to the user recommending that the user close any open windows **5** or cease operation of any ventilation equipment. In other cases, when the controller **218** determines that ventilation is no longer necessary or recommended, the controller **218** may display or transmit a message notifying the user that ventilation is no longer necessary and/or recommended and may automatically close one or more windows and/or cease operation of a ventilation system associated with the building **2**. Additionally, in some cases, the controller **218** may cause the HVAC controller **18** to control one or more HVAC controller to regulate the environmental conditions within the building **2** according to an operating schedule previously stored on the server.

In some instances, the controller **218** may be configured to prioritize user-specified air quality thresholds when determining the ventilation needs of the building. For example, if the outdoor temperature is lower than an indoor temperature, it would be generally expected that the controller **218** may determine that window (or other) ventilation is recommended. However, if a pollen count is higher than a user-specified parameter threshold for the pollen count, then based on the higher priority assigned to the user specified parameter threshold of pollen count (in this example), the controller **218** may determine that window (or other) ventilation is not recommended. This is just one example. In

21

some cases, the controller **218** may be configured to display one or more web pages that are configured to solicit and/or accept a user-determined priority for two or more different parameters including, but not limited to, one or more measures related to an indoor air quality and/or an outdoor air quality.

In some instances, when determining the ventilation needs of the building, the controller **218** may be programmed to assign a user-determined priority or weight to a number of different parameters related to an indoor air quality and/or an outdoor air quality. The processor **114** may use the weighted indoor air quality parameter values and/or outdoor air quality parameter values when determining the indoor air quality and the outdoor air quality and/or when comparing the indoor air quality to the outdoor air quality when determining the ventilation needs of the building **2**. The controller **218** may be configured to utilize Equations 1 and 2 when determining the ventilation needs of the building **2**, as described herein.

In some cases, the controller **218** may be programmed to ventilate the building or recommend ventilation of the building when the controller **218** determines that the outdoor air quality is greater than the indoor air quality. Under certain circumstances, ventilating the building **2** maybe less energy efficient than continuing to operate the HVAC system **4** according to its current program. In some instances, the controller **218** may be configured to display one or more web pages that are configured to prompt the user to enter their preference as to ventilating the building using outside air to maintain or improve the indoor air quality, even when it is less energy efficient to do so. In other words, the controller **218** may display an option to the user via the one or more web pages forming the user interface **118** for the user to override a more energy efficient operation of the HVAC system **4** in favor of increasing the indoor air quality of the building **2**. In many cases, the override of a more energy efficient operation configuration in favor of maintaining or increasing the indoor air quality is temporary.

The controller **218** may also be programmed to determine an amount of time in which ventilation is needed and/or recommend based on one or more user-specified air quality parameter thresholds and/or any weather related or air quality data, as described herein. The amount of time determined for ventilation may be based, at least in part, on one or more user-specified air quality thresholds and any weather and/or air quality data received via the input/output port **220**. In some cases, the controller **218** may also be configured to predict when ventilation is recommended based, at least in part, on any weather and/or air quality data received via the input/output port **220**.

In some instances, upon determining the ventilation needs of the building **2**, the controller **218** may transmit a data package to the HVAC controller **18** via the input/output port **220**, including a command to operate an IAQ component or other HVAC component **6** of the HVAC system **4** of the building **2**. The building **2** may be ventilated by opening one more powered windows and/or operation of mechanical ventilation system. In other instances, upon determining the ventilation needs of the building **2**, the controller **218** may notify the user of the building that ventilation is recommended and/or needed and may specify an amount of time needed or recommended for adequate ventilation. Additionally, the controller **218** may notify the user that the building is currently being ventilated. For example, the controller **218** may be configured to transmit a data package to a user via the input/output port **220**. The data package may be in the form of a SMS text message or an email, and may instruct

22

the user to operate an IAQ component or indicate that window ventilation is recommended. In other cases, the controller **218** may be configured to display a message or alert on the user interface **118** of the HVAC controller **18** indicating the desirability of ventilation. As discussed herein, the user interface **118** may be located at the HVAC controller **18** and/or provided at a remote device **112** such as any of those remote devices described herein. The message may instruct the user to operate any IAQ components such as, for example, a mechanical ventilation system and/or economizer or, in some cases, may indicate that window ventilation is recommended. In other instances, the message may notify the user that the HVAC controller **18** is commencing operation of any ventilation equipment and/or opening any power operated windows **5** located within the building **2**. Additionally, the message may indicate the length of time desired or needed for adequate ventilation and/or may include a prediction as to when conditions for ventilation may be favorable.

In still other instances, the controller **218** may be programmed to follow one or more pre-set or customized programs for ventilating the building **2**. The pre-set or customized programs may be utilized ventilate the building **2** under selected conditions, and may be selected by the user through the user interface **118** of the HVAC controller **18**. For example, a first pre-set or custom program may be selected by a user when a building occupant is ill, and may cause the controller **218** to control transmit one or more command signals via the input/output port **220** to an IAQ component or other HVAC component **6** to increase ventilation and humidity and, in some cases, maintain an elevated temperature overnight. Another pre-set or customized program may be selected by a user when the building is occupied above typical levels (e.g., when the occupants are hosting a gathering), and may cause the controller **218** transmit one or more command signals via the input/output port **220** to an IAQ component or other HVAC component **6** to increase ventilation, lower indoor humidity and, in some cases, lower the temperature within the building. Still another pre-set or customized program may be selected by a user for operating the HVAC components **6**, including any IAQ components during allergy season when pollen count levels are expected to be elevated, and may cause the controller **218** to transmit one or more command signals via the input/output port **220** to an IAQ component or other HVAC component **6** to minimize outdoor ventilation and increase the blower speed within the building **2** when the pollen count has reached a pre-determined level. These are just some examples.

FIGS. **6-7** show exemplary screens **250**, **260** that may be displayed by the HVAC controller **18** and/or server **116** via a user interface (e.g. user interface **118**), and that may be used to solicit and/or accept one or more air quality thresholds from a user. In some cases, screen **260** of FIG. **7** may be accessed though a menu screen such as, for example, menu screen **250** shown in FIG. **6**. Menu screen **250** may include a table or a drop down menu **256** that includes one or more menu options **258a-258e** that may be selected by a user. As can be seen in FIG. **6**, the menu options can include an "Air Quality Settings" option **258c**. In some cases, the "Air Quality Settings" menu option **258c** may be available under an advanced setting menu option such as for example, menu option **258e**, but this is not required.

In the example shown, selection of the "Air Quality Settings" menu option **258c** may cause the processor **114** or controller **218** to display at least one additional screen **260**, shown in FIG. **7**, which may prompt select a user to select

an air quality parameter from a menu including one or more selectable options **268a-268f**, where each selectable option **268a-268f** corresponds to a different air quality parameter. In some cases, the one or more selectable options **268a-268f** may be displayed in a table or in a drop down menu as shown, although this is not required. As shown in FIG. 7, selectable options **268a-268f** may correspond to an air quality index, a smog alert level, a pollen count, air pollutant concentration(s), a chance of precipitation, and a dew point, respectively. It will be generally understood that selectable options **268a-268f** may correspond to other air quality parameters depending upon the application and/or the needs of the consumer (e.g. humidity, etc.).

In one illustrative example, selection of the “Air Quality Index” option **268a** may cause the processor **114** or controller **218** to display screen **270**, as shown in FIG. 8, which may include a user prompt **272** that instructs the user to select an air quality threshold value. Screen **270** may display a table **276** including a list of air quality index values and/or range of index values **280a-280e**. The table **276** also include a descriptor **284a-284e** associated with each index value or range of index values **280a-280e**. The air quality index values or range of index values **280a-280e** and their related descriptors **284a-284e** may vary by country or region if desired. In some cases, the air quality index values or range of index values **280a-280e** and their related descriptors **284a-284e** may be color coded, but this is not required. In the example shown, the air quality index values or range of index values **280a-280e** include quantitative values, and their related descriptors **284a-284e** include qualitative descriptions. The qualitative descriptions **284a-284e** may aid a user in making a proper selection.

In some cases, screen **270** may include a slider bar **288** including an indicator **292** that may interact with the index values **280a-280e** listed in table **276**. The user may use the indicator **292** slider bar **288** to select an air quality threshold value. In some cases, as the user manipulates the slider bar **288**, the indicator **292** may indicate the actual air quality index value. In other cases, a user may simply select the desired air quality index value or range of values from the list of such values displayed by table **276**. Upon selecting the desired air quality index values or range of index values, the user may select the done button **296**. Selection of the done button **296** may cause the processor **114** or controller **218** to store the air quality index threshold value in the memory **122** or **214**. Additionally, selection of the done button **296** may cause the processor **114** or controller **218** to return to the previous screen **260** from which the user may select another air quality parameter for inputting another user-specified air quality parameter threshold, as desired.

In some cases, after a user has provided one or more air quality threshold values, the processor **114** or controller **218** may display at least one additional screen **300**, as shown in FIG. 9, that may prompt a user to assign a ranking or prioritize one or more air quality parameters. Screen **300** may include a natural language prompt **302** that may prompt the user to assign a ranking or priority level on using a ranking scale **304** that may be displayed on screen **300**. The ranking scale **304** displayed on screen **300** may be a star ranking scale, a ranking scale of 1 to 10, or a ranking scale of 1 to 5 (shown). These are just some examples. Other ranking scales may be utilized. In addition, ranking scale **304** may include qualitative labels **306a**, **306b** indicating the high and low ends of the scales. As shown in FIG. 9, a ranking scale **304** may be displayed for each different air quality parameter **308a-308d** identified on screen **300**. It will be generally understood that the number and/or type of air

quality parameters for which a ranking scale **304** is displayed may differ depending on the desired application and/or needs of the consumer. In some cases, as shown, each of the ranking scales may include a slider bar **310** and a slider control **312** that may be manipulated by a user to assign a ranking to each of the different air quality parameters. This is just one example. Other selection features, such as radio buttons, may be displayed and utilized by the user to assign a ranking or priority to one or more air quality parameters. In some cases, instead of soliciting specific air quality threshold values as described above in reference to FIGS. 7 and 8, the processor **114** or controller **218** may be programmed to only prompt a user to rank or prioritize a number of different air quality parameters.

Additionally, in some cases, after a user has provided one or more air quality threshold value, the processor **114** or the controller **218** may be configured to display yet another screen **314** that may prompt a user to indicate their preference for prioritizing indoor air quality over energy efficiency. This may be applicable when the processor **114** or controller **218** determines that the outdoor air quality is greater than the indoor air quality, but energy efficiency of the building **2** may be compromised or decreased if ventilation is commenced. Screen **314** may display a user prompt **316** that may query a user about their preference. Screen **314** may include a first checkbox **318a** labeled “Yes” and a second checkbox **318b** labeled “No” that a user may use to indicate their preference. Upon receiving and accepting the user’s indicated preference, the processor **114** and the controller **218** may be configured to store the user’s preference in a memory.

FIG. 11 shows another exemplary screen **320** that may be displayed by the HVAC controller **18** and/or server **116** via a user interface (e.g. user interface **118**). Screen **320** may be displayed upon selection of the “IAQ Programs” selection option **258d** displayed on menu screen **250** shown in FIG. 6. As can be seen in FIG. 9, screen **320** includes one or more selectable IAQ program options **324a-324c** that may be selected by a user. Each of the selectable IAQ program options **324a-324c** correspond to a pre-set or customized IAQ program that may be executed by the processor **114** or, in some cases, the controller **218** for operating one or more IAQ components or other HVAC components **6** for managing the indoor air quality of the building **2** under selected conditions. In some instances, each of the selectable IAQ program options **324a-324c** include a descriptor which may aid a user in selecting the most appropriate program for the user’s selected conditions. In addition, screen **320** may also include a button labeled “Help” that when selected may cause the processor **114** or controller **218** to display additional information about each of the selectable options **324a-324c**. Upon selecting the desired IAQ program options **324a**, **324b** or **324c**, the user may select the done button **332**. Selection of the done button **332** may cause the processor **114** or controller **218** to execute the selected IAQ program. Additionally, selection of the done button **332** may cause the processor **114** or controller **218** to return to a previous screen (e.g. menu screen **250**) from which the user may select another option, as desired.

FIG. 12—show exemplary screens that may be displayed to a user upon determining that ventilation is needed or desired. As shown in FIG. 12, screen **400** includes a user prompt **406** indicating that window ventilation is recommended. Screen **412** of FIG. 13 includes a user prompt **416** instructing the user to operate a ventilation system. In some

cases, user prompt **416** may include a recommended duration for operation of the ventilation system, but this is not required.

In another illustrative example, as shown in FIG. **14**, screen **450** may include a user message **456** predicting when conditions for ventilation are favorable. In some instances, screen **450** may also include a natural language prompt **460** that may query the user about ventilating the building. Screen **450** may include a first checkbox **462a** labeled “Yes” and a second checkbox **462b** labeled “No” that a user may use to indicate their preference. Upon receiving and accepting the user’s response, the processor **114** or controller **218** may send a signal to one or more IAQ components or one or more powered windows to ventilate the building.

The exemplary screen **470** shown in FIG. **15** is similar to that shown in FIG. **14**. As shown in FIG. **15**, screen **470** includes a user message **476** that informs the user that ventilation conditions are favorable for a predetermined amount of time (e.g. next 36 hours). Ventilation may be carried out by operation of any mechanical ventilation equipment and/or by opening one or more manual or powered windows. In some cases, the user message **476** may also include a time indicator **480** indicating the amount of time the building is being ventilated. The amount of time displayed by the time indicator may vary depending upon the ventilation needs of the building **2** determined by the processor **114** or controller **218**, and may range from a few hours to several days.

FIGS. **16** and **17** show exemplary screens **500**, **530** that may be displayed by the processor **114** or controller **218** upon determining that ventilation is no longer needed and/or recommended. As shown in FIG. **16**, screen **500** includes a first user message **506** that notifies a user that ventilation is no longer needed. Additionally, screen **500** may also include a second user message **510** that instructs a user to close any open windows. Similarly, screen **530** includes a first user message **536** that alerts a user that ventilation is no longer needed and/or recommended. In some cases, the first user message **536** may include a symbol **538** such as an exclamation point or other alert symbol displayed adjacent to and/or associated with the first user message. The symbol may visually alert the user that the user message **536** is being displayed. In some cases, screen **530** may include a second user message **540** that may query the user about resuming a normal or scheduled operation of the HVAC system **4**. Screen **530** may include a first checkbox **542a** labeled “Yes” and a second checkbox **542b** labeled “No” that a user may use to indicate their preference. Upon receiving and accepting the user’s response, the processor **114** or controller **218** may cause the HVAC controller **18** to send a signal to one or more HVAC components to resume operation according to an operating schedule of the HVAC system **4** stored in memory.

It will be generally understood that, depending upon the application, the notifications, alerts, and/or messages shown in connection with screens **400**, **412**, **450**, **470**, **500** and/or **530** may also be transmitted via SMS text message or email to a user’s remote device.

Having thus described several illustrative embodiments of the present disclosure, those of skill in the art will readily appreciate that yet other embodiments may be made and used within the scope of the claims hereto attached. Numerous advantages of the disclosure covered by this document have been set forth in the foregoing description. It will be understood, however, that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of parts

without exceeding the scope of the disclosure. The disclosure’s scope is, of course, defined in the language in which the appended claims are expressed.

What is claimed is:

1. A building controller configured to communicate with and control one or more components of an HVAC system of a building that includes ventilation equipment that introduces outdoor air into the building to provide ventilation to the building, the building controller comprising:

an input/output port for sending and/or receiving data over a network;

a memory for storing one or more operating parameters including one or more user-specified air quality thresholds;

a user interface; and

a controller coupled to the input/output port, the memory, and the user interface, the controller configured to receive and accept one or more user-specified air quality thresholds from a user via the user interface, the controller further configured to receive a first signal indicative of a measure of indoor air quality, the controller configured to receive a second signal indicative of a measure of outdoor air quality, the controller further configured to determine if ventilation of the building is desired to improve indoor air quality based, at least in part, on the one or more user-specified air quality thresholds stored in the memory, the measure of indoor air quality, and the measure of outdoor air quality, wherein the controller is configured to automatically operate the ventilation equipment to introduce outdoor air into the building when the controller determines that ventilation is desired, and wherein the controller is further configured to initiate an alert for display on a user interface of a mobile computing device notifying the user when the controller is automatically operating the ventilation equipment.

2. The building controller of claim **1**, wherein the ventilation equipment includes a powered window, and the alert notifies the user that the controller has automatically opening the powered window.

3. The building controller according to claim **1**, wherein the controller is further configured to receive data indicative of weather conditions and wherein the controller is further configured to determine if ventilation is desired based, at least in part, on weather conditions.

4. The building controller according to claim **1**, wherein the controller is further configured to receive data indicative of an air quality index value, and wherein the controller is further configured to determine if ventilation is desired based, at least in part, on the air quality index value.

5. The building controller according to claim **1**, wherein the controller is further configured to receive data indicative of a pollen count, and wherein the controller is further configured to determine if ventilation is desired based, at least in part, on the pollen count.

6. The building controller according to claim **1**, wherein the controller is further configured to receive data indicative of a concentration of at least one air pollutant, and wherein the controller is further configured to determine if ventilation is desired based, at least in part, on the concentration of the at least one air pollutant.

7. The building controller according to claim **1**, wherein the first signal is indicative of an indoor temperature and/or an indoor humidity and wherein the second signal is indicative of an outdoor temperature and/or an outdoor humidity.

27

8. The building controller according to claim 1, wherein the ventilation equipment includes a damper that regulates a flow of outdoor air into the building.

9. The building controller according to claim 1, wherein the ventilation equipment includes one or more powered windows.

10. The building controller according to claim 1, wherein the building controller is a thermostat.

11. The building controller according to claim 1, wherein the one or more user-specified air quality thresholds include an indoor air quality threshold value.

12. The building controller according to claim 1, wherein the one or more user-specified air quality thresholds include an outdoor air quality threshold value.

13. The building controller according to claim 1, wherein at least one of the one or more user-specified air quality thresholds relates to an air quality index value, a pollen count, a smog alert level, an air pollutant concentration, a percent humidity, a dew point, a wind speed, or a chance percent of precipitation.

14. A server connectable to a building controller located within a building over a network, the server comprising:

a data storage device for storing data indicative of environmental conditions inside of and outside of the building;

a controller configured to monitor the data indicative of environmental conditions inside of and outside of the building and determine whether ventilation of the building is desired based, at least in part, on the data indicative of environmental conditions inside of and outside of the building and on one or more user-specified air quality thresholds, wherein ventilation includes introducing outdoor air into the building, wherein the controller is further configured to automatically operate ventilation equipment that introduces outdoor air into the building; and

an input/output block for providing an alert to a mobile computing device for presentation to a user of the mobile computing device, notifying a user that the

28

controller is automatically operating the ventilation equipment to introduce outdoor air into the building when the controller determines that ventilation of the building is desired.

15. The server according to claim 14, wherein the alert is also provided to the building controller for presentation to a user of the building controller.

16. The server according to claim 14, wherein the alert further instructs the user to open a window to provide window ventilation.

17. A building controller configured to communicate with and control one or more components of an HVAC system that includes a damper that regulates a flow of outdoor air into the building, the building controller comprising:

an input/output port for sending and/or receiving data over a network;

a memory for storing one or more operating parameters including one or more user-specified air quality thresholds;

a user interface;

a controller coupled to the input/output port, the memory, and the user interface, the controller configured to receive a first signal indicative of a measure of indoor air quality, the controller configured to receive a second signal indicative of a measure of outdoor air quality, the controller configured to communicate either directly or indirectly with a mobile computing device, the controller further configured to determine if opening the damper to provide a flow of outdoor air into the building is desired based, at least in part, on the measure of indoor air quality, the measure of outdoor air quality and the one or more user-specified air quality thresholds stored in the memory; and

the controller further configured to provide an alert to a user via the mobile computing device, alerting the user when the controller is opening the damper to provide a flow of outdoor air into the building.

* * * * *