



US009270364B2

(12) **United States Patent**  
**Huibers et al.**

(10) **Patent No.:** **US 9,270,364 B2**

(45) **Date of Patent:** **Feb. 23, 2016**

- (54) **BUMP BUTTON**
- (71) Applicant: **Google Inc.**, Mountain View, CA (US)
- (72) Inventors: **Andrew G. Huibers**, Los Altos, CA (US); **David F. Lieb**, San Francisco, CA (US); **Jacob Mintz**, San Francisco, CA (US)
- (73) Assignee: **Google Inc.**, Mountain View, CA (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 44 days.
- (21) Appl. No.: **13/848,576**
- (22) Filed: **Mar. 21, 2013**

(65) **Prior Publication Data**  
US 2013/0217335 A1 Aug. 22, 2013

**Related U.S. Application Data**  
(60) Division of application No. 12/859,695, filed on Aug. 19, 2010, which is a continuation-in-part of application No. 12/699,692, filed on Feb. 3, 2010, now Pat. No. 8,577,292.

(51) **Int. Cl.**  
**H04B 7/00** (2006.01)  
**H04B 7/26** (2006.01)  
**G06Q 20/32** (2012.01)  
**G06F 15/16** (2006.01)  
**H04B 5/00** (2006.01)  
**H04M 1/2745** (2006.01)  
**H04M 1/725** (2006.01)

(52) **U.S. Cl.**  
CPC **H04B 7/26** (2013.01); **G06F 15/16** (2013.01); **G06Q 20/3278** (2013.01); **G06F 2200/1636** (2013.01); **H04B 5/0056** (2013.01); **H04B 5/0062** (2013.01); **H04M 1/274516** (2013.01); **H04M 1/7253** (2013.01)

(58) **Field of Classification Search**  
CPC ..... H04W 84/18; H04W 84/20; H04W 88/00; H04W 8/02; H04W 88/02

USPC ..... 455/41.1, 41.2, 41.3  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,366,202	B1 *	4/2002	Rosenthal	.....	G08B 21/0222	340/539.32
6,573,833	B1 *	6/2003	Rosenthal	.....	G08B 21/0222	340/539.1
6,807,564	B1 *	10/2004	Zellner	.....	G08B 25/016	370/310
6,961,555	B1 *	11/2005	Philyaw	.....	G06F 17/30876	455/403
6,970,183	B1	11/2005	Monroe			
7,191,247	B1 *	3/2007	Philyaw	.....	H04W 76/021	370/338
7,427,926	B2 *	9/2008	Sinclair	.....	G06F 21/445	340/3.1
7,542,770	B2 *	6/2009	Zegelin	.....	H04L 63/0492	342/450
7,719,422	B1 *	5/2010	Steinmetz	.....	F16P 3/147	340/10.1
7,769,927	B2 *	8/2010	Dubs	.....	H04L 67/16	340/10.42
8,391,786	B2 *	3/2013	Hodges	.....	G06F 1/1626	455/3.01

(Continued)

OTHER PUBLICATIONS


Smart Card Alliance, "Proximity Mobile Payments: Leveraging NFC and the Contactless Financial Payments Infrastructure," Sep. 2007, Princeton Junction, NJ.

*Primary Examiner* — April G Gonzales  
(74) *Attorney, Agent, or Firm* — Troutman Sanders LLP; James E. Schutz; Christopher C. Close, Jr.

(57) **ABSTRACT**

A fixed bump button may: (1) report its identification to a server connected to the internet when the button is bumped by a mobile device; and/or (2) emit a beacon signal identifying the button to a mobile device.

**4 Claims, 5 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

8,970,480 B2 \* 3/2015 Herrod ..... G06F 8/65  
345/156  
9,008,616 B2 \* 4/2015 Wall ..... G06Q 30/06  
455/407  
2002/0155844 A1 \* 10/2002 Rankin ..... H04W 4/02  
455/456.1  
2003/0167207 A1 \* 9/2003 Berardi ..... G06Q 10/025  
705/16  
2003/0171984 A1 \* 9/2003 Wodka ..... G06Q 20/387  
705/14.25  
2004/0088345 A1 \* 5/2004 Zellner ..... G06Q 50/24  
709/200  
2004/0150521 A1 8/2004 Stilp  
2004/0192383 A1 \* 9/2004 Zacks ..... H04L 63/102  
455/557  
2004/0203381 A1 \* 10/2004 Cahn ..... H04B 5/0012  
455/41.2  
2004/0203638 A1 10/2004 Chan et al.  
2004/0264404 A1 \* 12/2004 Zegelin ..... H04L 63/0492  
370/328  
2005/0140507 A1 6/2005 Nam et al.  
2005/0153707 A1 \* 7/2005 Ledyard ..... G01S 5/0018  
455/456.1  
2006/0125693 A1 \* 6/2006 Recker ..... G01S 5/14  
342/458  
2006/0258289 A1 11/2006 Dua  
2006/0267731 A1 \* 11/2006 Chen ..... G06Q 10/08  
340/10.1  
2006/0290496 A1 \* 12/2006 Peeters ..... A61B 5/0002  
340/572.1  
2007/0136102 A1 6/2007 Rodgers  
2007/0188323 A1 8/2007 Sinclair et al.  
2007/0222618 A1 9/2007 Randall et al.  
2008/0041936 A1 \* 2/2008 Vawter ..... G06Q 20/00  
235/380  
2008/0201212 A1 8/2008 Hammad et al.  
2009/0024770 A1 1/2009 Dubs et al.  
2009/0043658 A1 \* 2/2009 Webb ..... G06Q 30/0224  
705/14.25

2009/0068982 A1 \* 3/2009 Chen ..... G06Q 20/108  
455/407  
2009/0112630 A1 \* 4/2009 Collins, Jr. .... G06F 19/327  
705/3  
2009/0153342 A1 \* 6/2009 Thorn ..... G06F 1/1626  
340/669  
2009/0192935 A1 \* 7/2009 Griffin ..... G06Q 20/10  
705/41  
2009/0201122 A1 8/2009 Stobbe  
2009/0253476 A1 10/2009 Pestotnik  
2010/0023449 A1 \* 1/2010 Skowronek ..... G06Q 20/10  
705/39  
2010/0040029 A1 \* 2/2010 Doppler ..... H04W 28/18  
370/338  
2010/0042493 A1 2/2010 Nino et al.  
2010/0075758 A1 3/2010 Balosetti  
2010/0082491 A1 \* 4/2010 Rosenblatt ..... G06Q 10/02  
705/65  
2010/0109914 A1 5/2010 Tieman et al.  
2010/0125492 A1 \* 5/2010 Lin ..... G06Q 20/3274  
705/14.5  
2010/0174599 A1 \* 7/2010 Rosenblatt ..... G06Q 30/02  
705/14.37  
2010/0257033 A1 \* 10/2010 Roberts ..... G06Q 20/20  
705/14.3  
2010/0295943 A1 11/2010 Cha et al.  
2010/0311385 A1 12/2010 Hurwitz  
2011/0074582 A1 3/2011 Alexis  
2011/0076941 A1 \* 3/2011 Taveau ..... G06Q 10/10  
455/41.1  
2011/0076942 A1 \* 3/2011 Taveau ..... H04M 1/2745  
455/41.1  
2011/0126009 A1 \* 5/2011 Camp, Jr. .... H04L 9/0825  
713/168  
2011/0136468 A1 6/2011 McNamara et al.  
2011/0164509 A1 7/2011 Wengrovitz  
2011/0191438 A1 \* 8/2011 Huibers ..... G06F 15/16  
709/217  
2012/0027196 A1 2/2012 Martin  
2013/0100942 A1 \* 4/2013 Rudnick ..... H04B 7/2656  
370/337

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

1

**BUMP BUTTON**

## RELATED APPLICATIONS

This application is a division of U.S. patent application Ser. No. 12/859,695, "Bump button", filed on Aug. 19, 2010 which is a continuation-in-part of U.S. patent application Ser. No. 12/699,692, "Bump validation", filed on Feb. 3, 2010 and incorporated herein by reference.

## TECHNICAL FIELD

The disclosure is generally related to the field of information exchange between fixed and mobile electronic devices.

## BACKGROUND

Recently a simple and quick way to exchange information between mobile electronic devices was developed. When people meet, they can bump their smart phones together to rapidly exchange business cards, music playlists, digital photos, money, or other information. The act of bumping tells a device to start information transfer.

Bumps between mobile devices occur when two devices at the same place at the same time indicate their intention to establish a connection for transferring information. Principles for determining when two devices are at "the same place at the same time" are described in U.S. patent application Ser. No. 12/699,692, "Bump validation", filed on 3 Feb. 2010 and incorporated herein by reference.

Bumps may also occur between mobile and fixed devices. If one of the participants in a bump is fixed at a known place, the problem of determining bump location for the fixed device is solved in advance. What are needed, therefore, are fixed bump terminals.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A shows a fixed bump button.

FIG. 1B shows the button of FIG. 1A participating in a bump with a mobile device.

FIG. 2A shows a bump button communicating with the internet via a wireless connection.

FIG. 2B shows a bump button communicating with the internet via a wired connection.

FIG. 3A shows a mobile device bumping a keyboard.

FIG. 3B shows a mobile device bumping a touch screen.

FIG. 4 is a schematic block diagram of a bump button that may connect to the internet.

FIG. 5 is a schematic block diagram of a bump button that does not connect to the internet.

## DETAILED DESCRIPTION

Bumps between electronic devices occur when two devices at the same place at the same time indicate their intention to establish a connection for transferring information. When a mobile device bumps another device that is fixed at a known place, the problem of determining the location of the fixed device is solved in advance.

FIG. 1A shows a fixed bump button **100**, an example of a device that may be a fixed participant in a bump. FIG. 1B shows the button of FIG. 1A participating in a bump with a mobile device. In FIGS. 1A and 1B, a bump button includes a fixed base **105** and a button **110**. In one configuration, base **105** includes a processor and memory, and an internet connection as described below. The bump button is designed to be

2

placed in a known, fixed location such as a cash register in a shop, an information kiosk in a train station, or fan club booth at a musical concert.

In FIG. 1B, mobile device **115** is bumping the fixed bump button. The act of bumping has depressed button **110** slightly into base **105**. When a mobile device (e.g. **115**) bumps a fixed bump button (e.g. **100**), both devices report their intentions to a server. The mobile device sends a status report including time, position and bump request. The bump button need only send its identification, however. The bump button's location is fixed and already known to the server. Optionally, the button may also send the time of the bump to the server if the button is equipped with a clock.

FIGS. 2A and 2B show examples of bump buttons communicating via the internet. FIG. 2A shows a bump button communicating with the internet via a wireless connection while FIG. 2B shows a bump button communicating with the internet via a wired connection. In FIG. 2A fixed bump button **200** includes a fixed base **205** and a button **210**. Base **205** includes a processor and memory. Button **200** also includes a wireless internet connection represented symbolically by antenna **220**. The wireless connection may be based on Wi-Fi, Wi-Max, Bluetooth, EDGE, 3G or 4G cellular or other radio standards. In FIG. 2B button **200** is shown with a wired internet connection represented symbolically by wires **225**. The wired connection may be based on cable television networks, telephone digital subscriber line, ethernet or other wired internet standards.

When a mobile device bumps a fixed bump button, a server receives information from both the mobile device and the fixed button. A few examples serve to illustrate how bump information may be used. In a first example, a bump button is located at the cash register of a retail shop such as a coffee shop, clothing store, supermarket, etc. A customer pays for a purchase by bumping his mobile device (e.g. smart phone, personal digital assistant, etc.) against the bump button. When the bump occurs, the mobile device sends position and time estimates, and a bump request to a server, and the fixed button sends its identification to the server. The server sends a message to the mobile device prompting the customer to enter an amount of money to be sent to the retail shop. Thus, the bump button helps the server match the customer and the retail shop and initiate an electronic payment.

In another example, a bump button is located at an information kiosk in a train station. A traveler bumps the button with his mobile device. When the bump occurs, the mobile device sends position and time estimates, and a bump request to a server, and the fixed button sends its identification to the server. The server sends a message to the mobile device that directs the device to display travel information to the traveler. The message might be the uniform resource locator for a train timetable web page, for example. Thus, the bump button helps the server match the traveler with information relevant to the traveler's current position.

In another example, a bump button is located at a fan club booth at a musical concert. When a music fan attending the concert bumps the button with her smart phone or other mobile device, the device sends position and time estimates, and a bump request to a server, and the fixed button sends its identification to the server. The server sends the fan's email address to a band playing in the concert or registers the fan as a "friend" of the band in a social network, as examples. Thus, the bump button helps the server match the fan with the band.

In another example, a person using a computer needs to enter identifying information (e.g. user name, password, personal identification number, encryption key, etc.) to access a web site or other online resource. The web site displays a

message: “bump now”. The person bumps his mobile device against any of the keys on the computer’s keyboard. The device sends position and time estimates, and a bump request to a server. The web site also reports the bump to the server. The server may then send identifying information to the web site on behalf of the person using the computer thus saving him from a tedious login process.

In another example, a sports fan is using a touch screen input device at stadium to buy beer from a vending machine. The fan bumps his mobile devices against the touch screen to initiate payment (as described above) and also to send an encrypted identification key that identifies him as someone old enough to buy beer. The bump button helps the server match the fan with the beer vendor and allows the vendor to offer additional services to the fan.

Many alternatives devices to the buttons depicted in FIGS. 1 and 2 are possible. For example, FIG. 3A shows a mobile device 315 bumping a keyboard 305 while FIG. 3B shows the device bumping a touch screen 330. The keyboard or touch screen is connected to a processor, memory and network connection so that it can transmit bump information to a server. A fixed bump device may also use a computer mouse button, camera, microphone or radio receiver, as examples, to detect the presence of a mobile device.

In dense user environments a bump button may emit a short-range beacon signal to help a mobile device improve its position estimate. For example, a bump button may emit a coded audio signal. A mobile device may use its microphone to record part of the audio signal. The audio recording may then be interpreted by the mobile device or sent to a server for further processing. A bump button may instead (or also) emit a radio or optical signal as a beacon. Further the beacon may be continuous or may be turned on briefly when a bump occurs. In either case, receipt of a beacon signal by a mobile device during a bump provides another way to validate the bump in the presence of multiple nearby mobile devices.

A bump button may be implemented in many different forms as described above. In one configuration, each of these share basic components as outlined in FIG. 4 which is a schematic block diagram of a bump button. In FIG. 4, fixed bump device (“button”) 400 includes an input sensor 405, an internet communications unit 425, a processor and memory 430, and an optional beacon 435. Input sensor 405 may be a button or touch input device (e.g. touch screen) 410, a microphone 415 that listens for characteristic sounds (e.g. thuds, impacts) of a bump, a camera 420 that recognizes a picture (e.g. barcode) displayed by a mobile device, a radio receiver or another sensor. A fixed device supported by a spring may include an accelerometer as a sensor. A computer keyboard operating as a fixed bump device may use its keys to sense a bump.

In a basic form, a bump button has only one capability: when its sensor is triggered, it sends a message stored in memory to a server via the internet. The memory may be read-only memory as the message need only identify the bump button. The button’s fixed location is already known to the server. Thus, a button’s processor does not perform any general purpose computer function other than sending the message stored in the read-only memory

If a button also contains a clock, then the server may determine the button’s clock offset as described in U.S. patent application Ser. No. 12/699,692, “Bump validation”, filed on 3 Feb. 2010 and incorporated herein by reference. However, time reporting ability is not required in basic bump button implementations. A bump button’s optional beacon may emit audio, radio and/or optical signals. The signals may be continuous tones or may contain coded information. Finally, the

beacon signals may be emitted continuously or briefly (e.g. a few seconds) when a bump occurs.

In another configuration, a fixed bump button does not include a system for communicating with the internet. FIG. 5 is a schematic block diagram of a bump button that does not connect to the internet, for example. In FIG. 5, fixed bump device (“button”) 500 includes an optional input sensor 505 and a beacon 535. Input sensor 505 may be a button or other touch input device (e.g. touch screen) 510, a microphone 515 that listens for characteristic sounds (e.g. thuds, impacts) of a bump, a camera 520 that recognizes a picture (e.g. barcode) displayed by a mobile device, a radio receiver, a motion sensor such as an accelerometer or gyroscope, or another sensor. A fixed device supported by a spring may include an accelerometer as a sensor.

If a bump button constructed according to FIG. 5 has an input sensor, then the button may activate its beacon when its sensor is triggered. If the button does not have an input sensor, then the button’s function is simply to emit its beacon signal continuously or at set repetition intervals. The bump button’s beacon may emit audio, radio and/or optical signals. These beacon signals may be continuous tones or may contain coded information. An example of a radio beacon signal is a Wi-Fi broadcast of a button’s MAC (media access control) address. Finally, the beacon signals may be emitted continuously or briefly (e.g. a few seconds) when a bump occurs.

A bump button that has no internet communication ability still adds information when a mobile device bumps it. When a mobile device bumps a beacon-only button, the mobile device reports the beacon signal, and thus the button’s identity, to a server. The button’s fixed location is already known to the server, so the location of the mobile device is known with improved accuracy compared to a case where no button is present.

Fixed bump buttons as described herein facilitate matching mobile device users with specific locations such as retail shops, information kiosks or vending machines. When mobile and fixed devices are matched in a bump, information transfers between the mobile device and a server can carry money, identification or other information. Fixed bump buttons in different forms may include internet connection ability and/or emit beacon signals.

The above description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the disclosure. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the principles defined herein may be applied to other embodiments without departing from the scope of the disclosure. Thus, the disclosure is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

What is claimed is:

1. A fixed device comprising:
  - an input sensor button configured to receive, from a nearby mobile device, an indication of an intention of the nearby mobile device to establish a connection to transfer information;
  - a beacon that, when triggered by the input sensor button, sends a short-range signal to the nearby mobile device, the short-range signal comprising a MAC address and identifying the fixed device, wherein the fixed device is incapable of communication via the internet.
2. The device of claim 1 wherein the short-range signal is a coded audio signal.

**5**

**6**

3. The device of claim 1 wherein the short-range signal is a radio signal.

4. The device of claim 1 wherein the short-range signal is an optical signal.

\* \* \* \* \*