




US 20120221978A1


(19) **United States**(12) **Patent Application Publication**
Matas et al.(10) **Pub. No.: US 2012/0221978 A1**(43) **Pub. Date: Aug. 30, 2012**(54) **TOUCH SCREEN DEVICE, METHOD, AND
GRAPHICAL USER INTERFACE FOR
DISPLAYING AND SELECTING
APPLICATION OPTIONS****Publication Classification**(51) **Int. Cl.**
G06F 3/048 (2006.01)(52) **U.S. Cl.** **715/835**(76) Inventors: **Michael Matas**, San Francisco, CA
(US); **Christ Blumenberg**, San
Francisco, CA (US); **Stephen O.**
Lemay, San Francisco, CA (US);
Richard Williamson, Los Gatos,
CA (US)(21) Appl. No.: **13/461,635**(22) Filed: **May 1, 2012****Related U.S. Application Data**

- (63) Continuation of application No. 12/143,741, filed on
Jun. 20, 2008, now Pat. No. 8,171,432.
- (60) Provisional application No. 61/019,295, filed on Jan.
6, 2008, provisional application No. 61/019,296, filed
on Jan. 6, 2008.

(57) **ABSTRACT**

In accordance with some embodiments, a flat version of an application interface is displayed. In response to detecting a user gesture on a view options icon while the flat version of the application interface is displayed, a curled version of the application interface is displayed. The curled version of the application interface includes an image of a curled page that obscures a first portion of the flat version of the application interface, and a roll-up region in a display region formerly occupied by a second portion of the flat version of the application interface. The roll-up region includes a plurality of option icons. When a user selection gesture on one or more of the plurality of option icons is detected, the flat version of the application interface is redisplayed with information corresponding to the option icons upon which user selection gestures were detected.








Figure 1B




Figure 2




Figure 3




Figure 4A




Figure 4B




Figure 5A



Figure 5B




Figure 5C




Figure 5D




Figure 5E




Figure 5F




Figure 5G



Figure 5H



Figure 5I




Figure 5J




Figure 5K




Figure 5L




Figure 5M




Figure 5N




Figure 50




Figure 5P




Figure 5Q




Figure 5R




Figure 5S




Figure 5T




Figure 5U




Figure 5V




Figure 5W




Figure 5X




Figure 5Y




Figure 5Z




Figure 5AA




Figure 6A




Figure 6B




Figure 6C




Figure 7




Figure 8A




Figure 8B

900




Figure 9




Figure 10A




Figure 10B



Figure 10C




Figure 10D




Figure 10E




Figure 10F




Figure 11




Figure 12A

Display user selectable region for obtaining information associated with marker:




Figure 12B

Move Marker:




Figure 12C(1)




Figure 12C(2)




Figure 12C(4)




Figure 12C(3)





Figure 12C(5)




Figure 12D




Figure 12E




Figure 13

1400




Figure 14




Figure 15

TOUCH SCREEN DEVICE, METHOD, AND GRAPHICAL USER INTERFACE FOR DISPLAYING AND SELECTING APPLICATION OPTIONS

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. application Ser. No. 12/143,741, filed Jun. 20, 2008, now U.S. Pat. No. 8,171,432, which claims priority to U.S. Provisional Patent Application Nos. 61/019,295, "Portable Multifunction Device, Method, and Graphical User Interface for Displaying and Selecting Application Options," filed Jan. 6, 2008; and 61/019,296, "Portable Multifunction Device, Method, and Graphical User Interface for Providing Maps, Directions, and Location-Based Information," filed Jan. 6, 2008, all of which are incorporated by reference herein in their entirety.

[0002] This application is related to the following applications: (1) U.S. patent application Ser. No. 10/188,182, "Touch Pad For Handheld Device," filed Jul. 1, 2002; (2) U.S. patent application Ser. No. 10/722,948, "Touch Pad For Handheld Device," filed Nov. 25, 2003; (3) U.S. patent application Ser. No. 10/643,256, "Movable Touch Pad With Added Functionality," filed Aug. 18, 2003; (4) U.S. patent application Ser. No. 10/654,108, "Ambidextrous Mouse," filed Sep. 2, 2003; (5) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (6) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (7) U.S. Patent Application No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices" filed Jan. 18, 2005; (8) U.S. patent application Ser. No. 11/057,050, "Display Actuator," filed Feb. 11, 2005; (9) U.S. patent application Ser. No. 11/969,211, "Portable Multifunction Device, Method, and Graphical User Interface for Providing Maps and Directions," filed Jan. 3, 2008; (10) U.S. Provisional Patent Application No. 61/019,296, "Portable Multifunction Device, Method, and Graphical User Interface for Providing Maps, Directions, and Location-Based Information," filed Jan. 6, 2008; (11) U.S. Provisional Application No. 60/937,993, "Portable Multifunction Device," filed Jun. 29, 2007; (12) U.S. Provisional Application No. 60/936,725, "Portable Multifunction Device, Method, and Graphical User Interface for Providing Maps and Directions," filed Jun. 22, 2007; and (13) U.S. patent application Ser. No. 12/143,752, "Portable Multifunction Device, Method, and Graphical User Interface for Providing Maps, Directions, and Location-Based Information," filed Jun. 20, 2008. All of these applications are incorporated by reference herein in their entirety.

TECHNICAL FIELD

[0003] The disclosed embodiments relate generally to computing devices with touch screen displays, and more particularly, to selecting application options on computing devices with touch screen displays.

BACKGROUND

[0004] As portable electronic devices become more compact, and the number of functions performed by a given device increase, it has become a significant challenge to design a user interface that allows users to easily interact with a multifunction device. This challenge is particularly significant for handheld portable devices, which have much smaller screens than desktop or laptop computers. This situation is

unfortunate because the user interface is the gateway through which users receive not only content but also responses to user actions or behaviors, including user attempts to access a device's features, tools, and functions. Some portable communication devices (e.g., mobile telephones, sometimes called mobile phones, cell phones, cellular telephones, and the like) have resorted to adding more pushbuttons, increasing the density of push buttons, overloading the functions of pushbuttons, or using complex menu systems to allow a user to access, store and manipulate data. These conventional user interfaces often result in complicated key sequences and menu hierarchies that must be memorized by the user.

[0005] Many conventional user interfaces, such as those that include physical pushbuttons, are also inflexible. This is unfortunate because it may prevent a user interface from being configured and/or adapted by either an application running on the portable device or by users. When coupled with the time consuming requirement to memorize multiple key sequences and menu hierarchies, and the difficulty in activating a desired pushbutton, such inflexibility is frustrating to most users.

[0006] For example, mapping applications are available for mobile phones (e.g., Google maps for mobile, available at www.google.com/gmm). But navigating in such applications using physical push buttons (e.g., the number keys on a hard keyboard) or touch screens in existing mobile phones is cumbersome for most users. Thus, at present, relatively few people use mapping applications in mobile phones and other computing devices with touch screen displays. Similar problems arise in selecting application options in other applications on computing devices with touch screen displays.

[0007] Accordingly, there is a need for computing devices with touch screen displays that have more transparent and intuitive user interfaces for displaying and selecting application options. Such interfaces increase the effectiveness, efficiency and user satisfaction with such devices.

SUMMARY

[0008] The above deficiencies and other problems associated with user interfaces for devices with touch screen displays are reduced or eliminated by the disclosed multifunction device. In some embodiments, the device is portable. In some embodiments, the device has a touch-sensitive display (also known as a "touch screen") with a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI primarily through finger contacts and gestures on the touch-sensitive display. In some embodiments, the functions may include providing maps and directions, telephoning, video conferencing, e-mailing, instant messaging, blogging, digital photographing, digital videoing, web browsing, digital music playing, and/or digital video playing. Instructions for performing these functions may be included in a computer readable storage medium or other computer program product configured for execution by one or more processors.

[0009] In accordance with some embodiments, a computer-implemented method is performed at a computing device with a touch screen display. In the method, a flat version of an application interface is displayed. In response to detecting a user gesture on a view options icon while the flat version of the application interface is displayed, a curled version of the application interface is displayed. The curled version of the

application interface includes an image of a curled page that obscures a first portion of the flat version of the application interface, and a roll-up region in a display region formerly occupied by a second portion of the flat version of the application interface, wherein the roll-up region includes a plurality of option icons, each respective option icon in the plurality of option icons responsive to a user selection gesture on the respective option icon. When a user selection gesture on one or more of the plurality of option icons is detected, the flat version of the application interface is redisplayed with information corresponding to the one or more option icons upon which user selection gestures were detected.

[0010] In accordance with some embodiments, a computing device comprises a touch screen display, one or more processors, memory, and one or more programs. The one or more programs are stored in the memory and configured to be executed by the one or more processors. The one or more programs include instructions for displaying a flat version of an application interface and instructions for in response to detecting a user gesture on a view options icon while the flat version of the application interface is displayed, displaying a curled version of the application interface. The curled version of the application interface includes an image of a curled page that obscures a first portion of the flat version of the application interface and a roll-up region in a display region formerly occupied by a second portion of the flat version of the application interface. The roll-up region includes a plurality of option icons, each respective option icon in the plurality of option icons responsive to a user selection gesture on the respective option icon. The programs also include instructions for detecting a user selection gesture on one or more of the plurality of option icons and instructions for redisplaying the flat version of the application interface with information corresponding to the one or more option icons upon which user selection gestures were detected.

[0011] In accordance with some embodiments, a computer readable storage medium has stored instructions, which when executed by a device with a touch screen display cause the device to display a flat version of an application interface. The instructions also cause the device to display a curled version of the application interface in response to detecting a user gesture on a view options icon while the flat version of the application interface is displayed. The curled version of the application interface includes an image of a curled page that obscures a first portion of the flat version of the application interface, and a roll-up region in a display region formerly occupied by a second portion of the flat version of the application interface. The roll-up region includes a plurality of option icons, each respective option icon in the plurality of option icons responsive to a user selection gesture on the respective option icon. The instructions also cause the device to detect a user selection gesture on one or more of the plurality of option icons and redisplay the flat version of the application interface with information corresponding to the one or more option icons upon which user selection gestures were detected.

[0012] In accordance with some embodiments, a graphical user interface (GUI) on a device with a touch screen display comprises a flat version of an application interface, a view options icon, and a curled version of the application interface. The curled version of the application interface includes an image of a curled page that obscures a first portion of the flat version of the application interface, and a roll-up region in a display region formerly occupied by a second portion of the

flat version of the application interface. The roll-up region includes a plurality of option icons, each respective option icon in the plurality of option icons responsive to a user selection gesture on the respective option icon. In response to detecting a user gesture on the view options icon while the flat version of the application interface is displayed, the curled version of the application interface is displayed. When user selection gestures are detected on one or more of the plurality of option icons, the flat version of the application interface is redisplayed with information corresponding to the one or more of the plurality of option icons upon which user selection gestures were detected.

[0013] In accordance with some embodiments, an electronic device comprises a touch screen display; means for displaying a flat version of an application interface; and means for, in response to detecting a user gesture on a view options icon while the flat version of the application interface is displayed, displaying a curled version of the application interface. The curled version of the application interface includes an image of a curled page that obscures a first portion of the flat version of the application interface, and a roll-up region in a display region formerly occupied by a second portion of the flat version of the application interface. The roll-up region includes a plurality of option icons, each respective option icon in the plurality of option icons responsive to a user selection gesture on the respective option icon. The device further comprises means for detecting a user selection gesture on one or more of the plurality of option icons, and means for redisplaying the flat version of the application interface with information corresponding to the one or more option icons upon which user selection gestures were detected.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] For a better understanding of the aforementioned embodiments of the invention as well as additional embodiments thereof, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

[0015] FIGS. 1A and 1B are block diagrams illustrating portable multifunction devices with touch-sensitive displays in accordance with some embodiments.

[0016] FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

[0017] FIG. 3 illustrates an exemplary user interface for unlocking a portable electronic device in accordance with some embodiments.

[0018] FIGS. 4A and 4B illustrate exemplary user interfaces for a menu of applications on a portable multifunction device in accordance with some embodiments.

[0019] FIGS. 5A-5AA illustrate exemplary user interfaces for a map application in accordance with some embodiments.

[0020] FIGS. 6A-6C illustrate exemplary user interfaces for displaying an approximate location of a computing device on a map in accordance with some embodiments.

[0021] FIG. 7 is flow diagram illustrating a method of displaying an approximate location of a computing device on a map in accordance with some embodiments.

[0022] FIG. 8A illustrates an exemplary user interface for displaying and selecting application options in accordance with some embodiments.

[0023] FIG. 8B illustrates an exemplary user interface with user-requested information overlaid on a map in accordance with some embodiments.

[0024] FIG. 9 is a flow diagram illustrating a method of displaying and selecting application options in accordance with some embodiments.

[0025] FIG. 10A illustrates an exemplary user interface for displaying a map application with a user-moveable location marker in accordance with some embodiments.

[0026] FIG. 10B illustrates an exemplary user interface for displaying user-selectable option icons associated with a user-moveable location marker in accordance with some embodiments.

[0027] FIG. 10C illustrates an exemplary user interface for obtaining directions to a location corresponding to a user-moveable location marker in accordance with some embodiments.

[0028] FIG. 10D illustrates an exemplary user interface for obtaining directions from a location corresponding to a user-moveable location marker in accordance with some embodiments.

[0029] FIG. 10E illustrates an exemplary user interface for adding a location marker to a set of bookmarks in accordance with some embodiments.

[0030] FIG. 10F illustrates an exemplary user interface with a current location of a computing device included in a list of bookmarks in accordance with some embodiments.

[0031] FIG. 11 is a flow diagram illustrating a method for displaying and moving a user-moveable location marker on a map in accordance with some embodiments.

[0032] FIGS. 12A-12E illustrate examples of user interactions with a displayed map, a user-moveable location marker, and information associated with the location marker via finger gestures in accordance with some embodiments.

[0033] FIG. 13 is a flow diagram illustrating a method for interacting with a displayed map and a location marker in accordance with some embodiments.

[0034] FIG. 14 is a flow diagram illustrating a method for obtaining directions in accordance with some embodiments.

[0035] FIG. 15 is a flow diagram illustrating a method for displaying and moving a user-moveable location marker on a map in accordance with some embodiments.

DESCRIPTION OF EMBODIMENTS

[0036] Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

[0037] It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first gesture could be termed a second gesture, and, similarly, a second gesture could be termed a first gesture, without departing from the scope of the present invention.

[0038] The terminology used in the description of the invention herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used in the description of the invention and the appended claims, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0039] As used herein, the term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

[0040] Embodiments of a portable multifunction device, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device such as a mobile telephone that also contains other functions, such as PDA and/or music player functions.

[0041] The user interface may include a physical click wheel in addition to a touch screen or a virtual click wheel displayed on the touch screen. A click wheel is a user-interface device that may provide navigation commands based on an angular displacement of the wheel or a point of contact with the wheel by a user of the device. A click wheel may also be used to provide a user command corresponding to selection of one or more items, for example, when the user of the device presses down on at least a portion of the wheel or the center of the wheel. Alternatively, breaking contact with a click wheel image on a touch screen surface may indicate a user command corresponding to selection. For simplicity, in the discussion that follows, a portable multifunction device that includes a touch screen is used as an exemplary embodiment. It should be understood, however, that some of the user interfaces and associated processes may be applied to other devices, such as personal computers and laptop computers, which may include one or more other physical user-interface devices, such as a physical click wheel, a physical keyboard, a mouse and/or a joystick.

[0042] The device supports a variety of applications, such as one or more of the following: a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a blogging application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

[0043] The various applications that may be executed on the device may use at least one common physical user-interface device, such as the touch screen. One or more functions of the touch screen as well as corresponding information displayed on the device may be adjusted and/or varied from one application to the next and/or within a respective appli-

cation. In this way, a common physical architecture (such as the touch screen) of the device may support the variety of applications with user interfaces that are intuitive and transparent.

[0044] The user interfaces may include one or more soft keyboard embodiments. The soft keyboard embodiments may include standard (QWERTY) and/or non-standard configurations of symbols on the displayed icons of the keyboard, such as those described in U.S. patent application Ser. No. 11/459,606, "Keyboards For Portable Electronic Devices," filed Jul. 24, 2006, and Ser. No. 11/459,615, "Touch Screen Keyboards For Portable Electronic Devices," filed Jul. 24, 2006, the contents of which are hereby incorporated by reference in their entirety. The keyboard embodiments may include a reduced number of icons (or soft keys) relative to the number of keys in existing physical keyboards, such as that for a typewriter. This may make it easier for users to select one or more icons in the keyboard, and thus, one or more corresponding symbols. The keyboard embodiments may be adaptive. For example, displayed icons may be modified in accordance with user actions, such as selecting one or more icons and/or one or more corresponding symbols. One or more applications on the portable device may utilize common and/or different keyboard embodiments. Thus, the keyboard embodiment used may be tailored to at least some of the applications. In some embodiments, one or more keyboard embodiments may be tailored to a respective user. For example, one or more keyboard embodiments may be tailored to a respective user based on a word usage history (lexicography, slang, individual usage) of the respective user. Some of the keyboard embodiments may be adjusted to reduce a probability of a user error when selecting one or more icons, and thus one or more symbols, when using the soft keyboard embodiments.

[0045] Attention is now directed towards embodiments of the device. FIGS. 1A and 1B are block diagrams illustrating portable multifunction devices 100 with touch-sensitive displays 112 in accordance with some embodiments. The touch-sensitive display 112 is sometimes called a "touch screen" for convenience, and may also be known as or called a touch-sensitive display system. The device 100 may include a memory 102 (which may include one or more computer readable storage mediums), a memory controller 122, one or more processing units (CPU's) 120, a peripherals interface 118, RF circuitry 108, audio circuitry 110, a speaker 111, a microphone 113, an input/output (I/O) subsystem 106, other input or control devices 116, and an external port 124. The device 100 may include one or more optical sensors 164. These components may communicate over one or more communication buses or signal lines 103.

[0046] It should be appreciated that the device 100 is only one example of a portable multifunction device 100, and that the device 100 may have more or fewer components than shown, may combine two or more components, or may have a different configuration or arrangement of the components. The various components shown in FIGS. 1A and 1B may be implemented in hardware, software or a combination of both hardware and software, including one or more signal processing and/or application specific integrated circuits.

[0047] Memory 102 may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory 102 by other components of the

device 100, such as the CPU 120 and the peripherals interface 118, may be controlled by the memory controller 122.

[0048] The peripherals interface 118 couples the input and output peripherals of the device to the CPU 120 and memory 102. The one or more processors 120 run or execute various software programs and/or sets of instructions stored in memory 102 to perform various functions for the device 100 and to process data.

[0049] In some embodiments, the peripherals interface 118, the CPU 120, and the memory controller 122 may be implemented on a single chip, such as a chip 104. In some other embodiments, they may be implemented on separate chips.

[0050] The RF (radio frequency) circuitry 108 receives and sends RF signals, also called electromagnetic signals. The RF circuitry 108 converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. The RF circuitry 108 may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. The RF circuitry 108 may communicate with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication may use any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for email (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), and/or Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS)), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

[0051] The audio circuitry 110, the speaker 111, and the microphone 113 provide an audio interface between a user and the device 100. The audio circuitry 110 receives audio data from the peripherals interface 118, converts the audio data to an electrical signal, and transmits the electrical signal to the speaker 111. The speaker 111 converts the electrical signal to human-audible sound waves. The audio circuitry 110 also receives electrical signals converted by the microphone 113 from sound waves. The audio circuitry 110 converts the electrical signal to audio data and transmits the audio data to the peripherals interface 118 for processing. Audio data may be retrieved from and/or transmitted to memory 102 and/or the RF circuitry 108 by the peripherals interface 118. In some embodiments, the audio circuitry 110 also includes a headset jack (e.g. 212, FIG. 2). The headset jack provides an interface between the audio circuitry 110 and removable

audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

[0052] The I/O subsystem **106** couples input/output peripherals on the device **100**, such as the touch screen **112** and other input/control devices **116**, to the peripherals interface **118**. The I/O subsystem **106** may include a display controller **156** and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input or control devices **116**. The other input/control devices **116** may include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** may be coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. 2) may include an up/down button for volume control of the speaker **111** and/or the microphone **113**. The one or more buttons may include a push button (e.g., **206**, FIG. 2). A quick press of the push button may disengage a lock of the touch screen **112** or begin a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **206**) may turn power to the device **100** on or off. The user may be able to customize a functionality of one or more of the buttons. The touch screen **112** is used to implement virtual or soft buttons and one or more soft keyboards.

[0053] The touch-sensitive touch screen **112** provides an input interface and an output interface between the device and a user. The display controller **156** receives and/or sends electrical signals from/to the touch screen **112**. The touch screen **112** displays visual output to the user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output may correspond to user-interface objects, further details of which are described below.

[0054] A touch screen **112** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. The touch screen **112** and the display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on the touch screen **112** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on the touch screen. In an exemplary embodiment, a point of contact between a touch screen **112** and the user corresponds to a finger of the user.

[0055] The touch screen **112** may use LCD (liquid crystal display) technology, or LPD (light emitting polymer display) technology, although other display technologies may be used in other embodiments. The touch screen **112** and the display controller **156** may detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with a touch screen **112**.

[0056] A touch-sensitive display in some embodiments of the touch screen **112** may be analogous to the multi-touch sensitive tablets described in the following U.S. Patents: U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in its entirety. However, a touch screen **112** displays visual output from the portable device **100**, whereas touch sensitive tablets do not provide visual output.

[0057] A touch-sensitive display in some embodiments of the touch screen **112** may be as described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

[0058] The touch screen **112** may have a resolution in excess of 100 dpi. In an exemplary embodiment, the touch screen has a resolution of approximately 160 dpi. The user may make contact with the touch screen **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which are much less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

[0059] In some embodiments, in addition to the touch screen, the device **100** may include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from the touch screen **112** or an extension of the touch-sensitive surface formed by the touch screen.

[0060] In some embodiments, the device **100** may include a physical or virtual click wheel as an input control device **116**. A user may navigate among and interact with one or more graphical objects (henceforth referred to as icons) displayed in the touch screen **112** by rotating the click wheel or by moving a point of contact with the click wheel (e.g., where the amount of movement of the point of contact is measured by its angular displacement with respect to a center point of the click wheel). The click wheel may also be used to select one or more of the displayed icons. For example, the user may press down on at least a portion of the click wheel or an associated button. User commands and navigation commands

provided by the user via the click wheel may be processed by an input controller **160** as well as one or more of the modules and/or sets of instructions in memory **102**. For a virtual click wheel, the click wheel and click wheel controller may be part of the touch screen **112** and the display controller **156**, respectively. For a virtual click wheel, the click wheel may be either an opaque or semitransparent object that appears and disappears on the touch screen display in response to user interaction with the device. In some embodiments, a virtual click wheel is displayed on the touch screen of a portable multi-function device and operated by user contact with the touch screen.

[0061] The device **100** also includes a power system **162** for powering the various components. The power system **162** may include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

[0062] The device **100** may also include one or more optical sensors **164**. FIGS. **1A** and **1B** show an optical sensor coupled to an optical sensor controller **158** in I/O subsystem **106**. The optical sensor **164** may include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. The optical sensor **164** receives light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with an imaging module **143** (also called a camera module), the optical sensor **164** may capture still images or video. In some embodiments, an optical sensor is located on the back of the device **100**, opposite the touch screen display **112** on the front of the device, so that the touch screen display may be used as a viewfinder for either still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image may be obtained for videoconferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of the optical sensor **164** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **164** may be used along with the touch screen display for both video conferencing and still and/or video image acquisition.

[0063] The device **100** may also include one or more proximity sensors **166**. FIGS. **1A** and **1B** show a proximity sensor **166** coupled to the peripherals interface **118**. Alternately, the proximity sensor **166** may be coupled to an input controller **160** in the I/O subsystem **106**. The proximity sensor **166** may perform as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device," filed Sep. 30, 2005; Ser. No. 11/240,788, "Proximity Detector In Handheld Device," filed Sep. 30, 2005; Ser. No. 11/620,702, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices," filed Oct. 24, 2006; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables the touch screen **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call). In some embodiments, the proximity sensor keeps the screen off when

the device is in the user's pocket, purse, or other dark area to prevent unnecessary battery drainage when the device is a locked state.

[0064] The device **100** may also include one or more accelerometers **168**. FIGS. **1A** and **1B** show an accelerometer **168** coupled to the peripherals interface **118**. Alternately, the accelerometer **168** may be coupled to an input controller **160** in the I/O subsystem **106**. The accelerometer **168** may perform as described in U.S. Patent Publication No. 20050190059, "Acceleration-based Theft Detection System for Portable Electronic Devices," and U.S. Patent Publication No. 20060017692, "Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer," both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers.

[0065] In some embodiments, the software components stored in memory **102** may include an operating system **126**, a communication module (or set of instructions) **128**, a contact/motion module (or set of instructions) **130**, a graphics module (or set of instructions) **132**, a text input module (or set of instructions) **134**, a Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or set of instructions) **136**.

[0066] The operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0067] The communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by the RF circuitry **108** and/or the external port **124**. The external port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used on iPod (trademark of Apple Computer, Inc.) devices.

[0068] The contact/motion module **130** may detect contact with the touch screen **112** (in conjunction with the display controller **156**) and other touch sensitive devices (e.g., a touchpad or physical click wheel). The contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred, determining if there is movement of the contact and tracking the movement across the touch screen **112**, and determining if the contact has been broken (i.e., if the contact has ceased). Determining movement of the point of contact may include determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations may be applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, the contact/motion module **130** and the display controller **156** also detects contact on a touchpad. In some embodiments, the contact/motion module **130** and the controller **160** detects contact on a click wheel.

[0069] The graphics module 132 includes various known software components for rendering and displaying graphics on the touch screen 112, including components for changing the intensity of graphics that are displayed. As used herein, the term “graphics” includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

[0070] The text input module 134, which may be a component of graphics module 132, provides soft keyboards for entering text in various applications (e.g., contacts 137, e-mail 140, IM 141, blogging 142, browser 147, and any other application that needs text input).

[0071] The GPS module 135 determines the location of the device and provides this information for use in various applications (e.g., to telephone 138 for use in location-based dialing, to camera 143 and/or blogger 142 as picture/video meta-data, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

[0072] The applications 136 may include the following modules (or sets of instructions), or a subset or superset thereof:

[0073] a contacts module 137 (sometimes called an address book or contact list);

[0074] a telephone module 138;

[0075] a video conferencing module 139;

[0076] an e-mail client module 140;

[0077] an instant messaging (IM) module 141;

[0078] a blogging module 142;

[0079] a camera module 143 for still and/or video images;

[0080] an image management module 144;

[0081] a video player module 145;

[0082] a music player module 146;

[0083] a browser module 147;

[0084] a calendar module 148;

[0085] widget modules 149, which may include weather widget 149-1, stocks widget 149-2, calculator widget 149-3, alarm clock widget 149-4, dictionary widget 149-5, and other widgets obtained by the user, as well as user-created widgets 149-6;

[0086] widget creator module 150 for making user-created widgets 149-6;

[0087] search module 151;

[0088] video and music player module 152, which merges video player module 145 and music player module 146;

[0089] notes module 153;

[0090] map module 154; and/or

[0091] online video module 155.

[0092] Examples of other applications 136 that may be stored in memory 102 include other word processing applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

[0093] In conjunction with touch screen 112, display controller 156, contact module 130, graphics module 132, and text input module 134, the contacts module 137 may be used to manage an address book or contact list, including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail

addresses to initiate and/or facilitate communications by telephone 138, video conference 139, e-mail 140, or IM 141; and so forth.

[0094] In conjunction with RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, touch screen 112, display controller 156, contact module 130, graphics module 132, and text input module 134, the telephone module 138 may be used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in the address book 137, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation and disconnect or hang up when the conversation is completed. As noted above, the wireless communication may use any of a plurality of communications standards, protocols and technologies.

[0095] In conjunction with RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, touch screen 112, display controller 156, optical sensor 164, optical sensor controller 158, contact module 130, graphics module 132, text input module 134, contact list 137, and telephone module 138, the videoconferencing module 139 may be used to initiate, conduct, and terminate a video conference between a user and one or more other participants.

[0096] In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact module 130, graphics module 132, and text input module 134, the e-mail client module 140 may be used to create, send, receive, and manage e-mail. In conjunction with image management module 144, the e-mail module 140 makes it very easy to create and send e-mails with still or video images taken with camera module 143.

[0097] In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact module 130, graphics module 132, and text input module 134, the instant messaging module 141 may be used to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages and to view received instant messages. In some embodiments, transmitted and/or received instant messages may include graphics, photos, audio files, video files and/or other attachments as are supported in a MMS and/or an Enhanced Messaging Service (EMS). As used herein, “instant messaging” refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

[0098] In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact module 130, graphics module 132, text input module 134, image management module 144, and browsing module 147, the blogging module 142 may be used to send text, still images, video, and/or other graphics to a blog (e.g., the user’s blog).

[0099] In conjunction with touch screen 112, display controller 156, optical sensor(s) 164, optical sensor controller 158, contact module 130, graphics module 132, and image management module 144, the camera module 143 may be used to capture still images or video (including a video stream) and store them into memory 102, modify characteristics of a still image or video, or delete a still image or video from memory 102.

[0100] In conjunction with touch screen 112, display controller 156, contact module 130, graphics module 132, text input module 134, and camera module 143, the image management module 144 may be used to arrange, modify or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

[0101] In conjunction with touch screen 112, display controller 156, contact module 130, graphics module 132, audio circuitry 110, and speaker 111, the video player module 145 may be used to display, present or otherwise play back videos (e.g., on the touch screen or on an external, connected display via external port 124).

[0102] In conjunction with touch screen 112, display system controller 156, contact module 130, graphics module 132, audio circuitry 110, speaker 111, RF circuitry 108, and browser module 147, the music player module 146 allows the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files. In some embodiments, the device 100 may include the functionality of an MP3 player, such as an iPod (trademark of Apple Computer, Inc.).

[0103] In conjunction with RF circuitry 108, touch screen 112, display system controller 156, contact module 130, graphics module 132, and text input module 134, the browser module 147 may be used to browse the Internet, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

[0104] In conjunction with RF circuitry 108, touch screen 112, display system controller 156, contact module 130, graphics module 132, text input module 134, e-mail module 140, and browser module 147, the calendar module 148 may be used to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to do lists, etc.).

[0105] In conjunction with RF circuitry 108, touch screen 112, display system controller 156, contact module 130, graphics module 132, text input module 134, and browser module 147, the widget modules 149 are mini-applications that may be downloaded and used by a user (e.g., weather widget 149-1, stocks widget 149-2, calculator widget 149-3, alarm clock widget 149-4, and dictionary widget 149-5) or created by the user (e.g., user-created widget 149-6). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

[0106] In conjunction with RF circuitry 108, touch screen 112, display system controller 156, contact module 130, graphics module 132, text input module 134, and browser module 147, the widget creator module 150 may be used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

[0107] In conjunction with touch screen 112, display system controller 156, contact module 130, graphics module 132, and text input module 134, the search module 151 may be used to search for text, music, sound, image, video, and/or other files in memory 102 that match one or more search criteria (e.g., one or more user-specified search terms).

[0108] In conjunction with touch screen 112, display controller 156, contact module 130, graphics module 132, and text input module 134, the notes module 153 may be used to create and manage notes, to do lists, and the like.

[0109] In conjunction with RF circuitry 108, touch screen 112, display system controller 156, contact module 130, graphics module 132, text input module 134, GPS module 135, and browser module 147, the map module 154 may be used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data).

[0110] In conjunction with touch screen 112, display system controller 156, contact module 130, graphics module 132, audio circuitry 110, speaker 111, RF circuitry 108, text input module 134, e-mail client module 140, and browser module 147, the online video module 155 allows the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port 124), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module 141, rather than e-mail client module 140, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Dec. 31, 2007, the content of which is hereby incorporated by reference in its entirety.

[0111] Each of the above identified modules and applications correspond to a set of instructions for performing one or more functions described above. These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules may be combined or otherwise re-arranged in various embodiments. For example, video player module 145 may be combined with music player module 146 into a single module (e.g., video and music player module 152, FIG. 1B). In some embodiments, memory 102 may store a subset of the modules and data structures identified above. Furthermore, memory 102 may store additional modules and data structures not described above.

[0112] In some embodiments, the device 100 is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen 112 and/or a touchpad. By using a touch screen and/or a touchpad as the primary input/control device for operation of the device 100, the number of physical input/control devices (such as push buttons, dials, and the like) on the device 100 may be reduced.

[0113] The predefined set of functions that may be performed exclusively through a touch screen and/or a touchpad include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates the device 100 to a main, home, or root menu from any user interface that may be displayed on the device 100. In such embodiments, the touchpad may be referred to as a "menu button." In some other embodiments, the menu button may be a physical push button or other physical input/control device instead of a touchpad.

[0114] FIG. 2 illustrates a portable multifunction device 100 having a touch screen 112 in accordance with some embodiments. The touch screen may display one or more graphics within user interface (UI) 200. In this embodiment, as well as others, a user may select one or more of the graphics

by making contact or touching the graphics, for example, with one or more fingers **202** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the contact may include a gesture, such as one or more taps, one or more swipes (from left to right, right to left, upward and/or downward) and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with the device **100**. In some embodiments, inadvertent contact with a graphic may not select the graphic. For example, a swipe gesture that sweeps over an application icon may not select the corresponding application when the gesture corresponding to selection is a tap.

[0115] The device **100** may also include one or more physical buttons, such as “home” or menu button **204**. As described previously, the menu button **204** may be used to navigate to any application **136** in a set of applications that may be executed on the device **100**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI in touch screen **112**.

[0116] In one embodiment, the device **100** includes a touch screen **112**, a menu button **204**, a push button **206** for powering the device on/off and locking the device, volume adjustment button(s) **208**, a Subscriber Identity Module (SIM) card slot **210**, a head set jack **212**, and a docking/charging external port **124**. The push button **206** may be used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, the device **100** also may accept verbal input for activation or deactivation of some functions through the microphone **113**.

[0117] Attention is now directed towards embodiments of user interfaces (“UI”) and associated processes that may be implemented on a portable multifunction device **100**.

[0118] FIG. 3 illustrates an exemplary user interface for unlocking a portable electronic device in accordance with some embodiments. In some embodiments, user interface **300** includes the following elements, or a subset or superset thereof:

[0119] Unlock image **302** that is moved with a finger gesture to unlock the device;

[0120] Arrow **304** that provides a visual cue to the unlock gesture;

[0121] Channel **306** that provides additional cues to the unlock gesture;

[0122] Time **308**;

[0123] Day **310**;

[0124] Date **312**; and

[0125] Wallpaper image **314**.

[0126] In some embodiments, the device detects contact with the touch-sensitive display (e.g., a user’s finger making contact on or near the unlock image **302**) while the device is in a user-interface lock state. The device moves the unlock image **302** in accordance with the contact. The device transitions to a user-interface unlock state if the detected contact corresponds to a predefined gesture, such as moving the unlock image across channel **306**. Conversely, the device maintains the user-interface lock state if the detected contact does not correspond to the predefined gesture. As noted above, processes that use gestures on the touch screen to

unlock the device are described in U.S. patent application Ser. No. 11/322,549, “Unlocking A Device By Performing Gestures On An Unlock Image,” filed Dec. 23, 2005, and Ser. No. 11/322,550, “Indication Of Progress Towards Satisfaction Of A User Input Condition,” filed Dec. 23, 2005, which are hereby incorporated by reference in their entirety.

[0127] FIGS. 4A and 4B illustrate exemplary user interfaces for a menu of applications on a portable multifunction device in accordance with some embodiments. In some embodiments, user interface **400A** includes the following elements, or a subset or superset thereof:

[0128] Signal strength indicator(s) **402** for wireless communication(s), such as cellular and Wi-Fi signals;

[0129] Time **404**;

[0130] Battery status indicator **406**;

[0131] Tray **408** with icons for frequently used applications, such as:

[0132] Phone **138**, which may include an indicator **414** of the number of missed calls or voicemail messages;

[0133] E-mail client **140**, which may include an indicator **410** of the number of unread e-mails;

[0134] Browser **147**; and

[0135] Music player **146**; and

[0136] Icons for other applications, such as:

[0137] IM **141**;

[0138] Image management **144**;

[0139] Camera **143**;

[0140] Video player **145**;

[0141] Weather **149-1**;

[0142] Stocks **149-2**;

[0143] Blog **142**;

[0144] Calendar **148**;

[0145] Calculator **149-3**;

[0146] Alarm clock **149-4**;

[0147] Dictionary **149-5**; and

[0148] User-created widget **149-6**.

[0149] In some embodiments, user interface **400B** includes the following elements, or a subset or superset thereof:

[0150] **402, 404, 406, 141, 148, 144, 143, 149-3, 149-2, 149-1, 149-4, 410, 414, 138, 140, and 147**, as described above;

[0151] Bluetooth indicator **405**;

[0152] Map **154**;

[0153] Notes **153**;

[0154] Settings **412**, which provides access to settings for the device **100** and its various applications **136**, as described further below;

[0155] Video and music player module **152**, also referred to as iPod (trademark of Apple Computer, Inc.) module **152**; and

[0156] Online video module **155**, also referred to as YouTube (trademark of Google, Inc.) module **155**.

[0157] In some embodiments, UI **400A** or **400B** displays all of the available applications **136** on one screen so that there is no need to scroll through a list of applications (e.g., via a scroll bar). In some embodiments, as the number of applications increase, the icons corresponding to the applications may decrease in size so that all applications may be displayed on a single screen without scrolling. In some embodiments, having all applications on one screen and a menu button enables a user to access any desired application with at most two inputs, such as activating the menu button **204** and then activating the desired application (e.g., by a tap or other finger gesture on the icon corresponding to the application).

[0158] In some embodiments, UI 400A or 400B provides integrated access to both widget-based applications and non-widget-based applications. In some embodiments, all of the widgets, whether user-created or not, are displayed in UI 400A or 400B. In other embodiments, activating the icon for user-created widget 149-6 may lead to another UI that contains the user-created widgets or icons corresponding to the user-created widgets.

[0159] In some embodiments, a user may rearrange the icons in UI 400A or 400B, e.g., using processes described in U.S. patent application Ser. No. 11/459,602, "Portable Electronic Device With Interface Reconfiguration Mode," filed Jul. 24, 2006, which is hereby incorporated by reference in its entirety. For example, a user may move application icons in and out of tray 408 using finger gestures.

[0160] In some embodiments, UI 400A or 400B includes a gauge (not shown) that displays an updated account usage metric for an account associated with usage of the device (e.g., a cellular phone account), as described in U.S. patent application Ser. No. 11/322,552, "Account Information Display For Portable Communication Device," filed Dec. 23, 2005, which is hereby incorporated by reference in its entirety.

[0161] FIGS. 5A-5AA illustrate exemplary user interfaces for a map application in accordance with some embodiments.

[0162] In some embodiments, a computer-implemented method is performed at a portable electronic device (e.g., 100) with a touch screen display 112.

[0163] In some embodiments, in response to detecting a finger gesture 5230 (e.g., a finger tap gesture) on a search icon 5232 (FIG. 5C), the device displays a search term input area 5202 (e.g., text input box, FIG. 5A) for entering one or more search terms.

[0164] In some embodiments, in response to detecting a finger gesture 5234 (e.g., a finger tap gesture) on the search term input area, the device displays a keyboard 5236 for entering the one or more search terms.

[0165] In some embodiments, in response to detecting a finger gesture 5238 (e.g., a finger tap gesture) on an input icon 5204 (FIG. 5A) associated with the search term input area 5202, the device displays a list 5240 (FIG. 5F) of bookmarked locations 5242. In response to detecting a finger gesture 5244 (e.g., a finger tap gesture) on a bookmarked location (e.g., 5242-3) in the list 5240 of bookmarked locations, an area corresponding to the bookmarked location is displayed on a digital map (not shown).

[0166] In some embodiments, in response to detecting a finger gesture 5238 (e.g., a finger tap gesture) on an input icon 5204 associated with the search term input area 5202, the device displays a list 5246 (FIG. 5H) of recent queries 5248 by a user. In response to detecting a finger gesture 5250 (e.g., a finger tap gesture) on a recent query (e.g., 5248-6) in the list 5246 of recent queries by a user, results corresponding to the recent query are displayed on a digital map (not shown).

[0167] In some embodiments, in response to detecting a finger gesture 5238 (e.g., a finger tap gesture) on an input icon 5204 (FIG. 5A) associated with the search term input area 5202, the device displays a list 5252 (FIG. 5J) of contacts 5254. In response to detecting a finger gesture 5256 (e.g., a finger tap gesture) on a contact (e.g., 5254-3) in the list of contacts, an area associated with the contact (e.g., an area that includes an address associated with the contact 5254-3 in the contact list) is displayed on a digital map (not shown).

[0168] In some embodiments, in response to detecting a finger gesture 5238 (e.g., a finger tap gesture) on an input icon 5204 (FIG. 5A) associated with the search term input area 5202, the device displays either:

[0169] a list 5240 (FIG. 5F) of bookmarked locations 5242, wherein in response to detecting a finger gesture 5244 (e.g., a finger tap gesture) on a bookmarked location (e.g., 5242-3) in the list 5240 of bookmarked locations, an area corresponding to the bookmarked location is displayed on a digital map (not shown);

[0170] a list 5246 (FIG. 5H) of recent queries 5248 by a user, wherein in response to detecting a finger gesture 5250 (e.g., a finger tap gesture) on a recent query (e.g., 5248-6) in the list 5246 of recent queries by a user, results corresponding to the recent query are displayed on a digital map (not shown); or

[0171] a list 5252 (FIG. 5J) of contacts 5254, wherein in response to detecting a finger gesture 5256 (e.g., a finger tap gesture) on a contact (e.g., 5254-3) in the list of contacts, an area associated with the contact (e.g., an area that includes an address associated with the contact 5254-3 in the contact list) is displayed on a digital map (not shown).

In some embodiments, the list (i.e., 5240, 5246, or 5252) which is displayed in response to finger gesture 5238 (e.g., a finger tap gesture) on input icon 5204 corresponds to the list (i.e., 5240, 5246, or 5252) that was most recently displayed prior to finger gesture 5238.

[0172] In some embodiments, in response to detecting a finger gesture 5258 (e.g., a finger tap gesture) on a search initiation icon 5260 (FIG. 5B), the device: sends one or more entered search terms 5262 (e.g., Cupertino Starbucks) to a remote computer (e.g., a map application server), receives one or more search results, and displays at least some of the search results 5264 on a digital map 5266 (FIG. 5C). In some embodiments, the digital map comprises a graphic image, a satellite image, or a hybrid combination of a graphic image and a satellite image. For example, the search results may be displayed on a graphical map if map icon 5206 is selected (FIG. 5C), whereas the search results may be displayed on a satellite image if satellite icon 5208 is selected.

[0173] In some embodiments, in response to detecting a single finger tap gesture 5268 (FIG. 5C) on the digital map, the device magnifies the area near the single finger tap gesture 5268. In some embodiments, the tap gesture is a single tap. In some embodiments, the tap gesture is a double tap. In some embodiments, the magnification includes a zoom-in animation.

[0174] In some embodiments, in response to detecting a finger down gesture 5270 and a finger drag gesture 5272 on the digital map 5266 (FIG. 5C), the device translates the digital map 5266 on the touch screen display in accordance with the finger drag gesture 5272.

[0175] In some embodiments, in response to detecting a two finger tap gesture 5274 (FIG. 5C) on the digital map, the device demagnifies the area near the two finger tap gesture 5274. In some embodiments, the tap gesture is a single tap. In some embodiments, the tap gesture is a double tap. In some embodiments, the demagnification includes a zoom-out animation.

[0176] In some embodiments, a first respective icon (e.g., 5264-3, FIG. 5C) is displayed for a respective search result, wherein in response to detecting a finger gesture 5280 on the first respective icon, a second respective icon 5276 for the

respective search result is displayed. In some embodiments, in response to detecting a finger gesture **5282** on the second respective icon, an interface **5200L** (FIG. 5D) for the respective search result is displayed.

[0177] In some embodiments, a first respective icon (e.g., **5264-3**, FIG. 5C) is displayed for a respective search result, wherein in response to detecting a finger gesture **5280** on the first respective icon, a second respective icon **5276** and a third respective icon **5278** for the respective search result are displayed. In some embodiments, in response to detecting a finger gesture **5280** on the second respective icon, the second respective icon and the third respective icon cease to be displayed. In some embodiments, in response to detecting a finger gesture **5284** on the third respective icon, an interface **5200L** (FIG. 5D) for the respective search result is displayed.

[0178] In some embodiments, a respective icon (e.g., **5278**) is displayed for a respective search result, wherein in response to detecting a finger gesture **5284** on the respective icon, an interface **5200L** (FIG. 5D) is displayed for the respective search result.

[0179] In some embodiments, the interface **5200L** (FIG. 5D) for the respective search result includes:

- [0180] a name for the respective search result;
- [0181] a local map of the respective search result;
- [0182] an electronic address for the respective search result (e.g., a URL);
- [0183] a physical address for the respective search result;
- [0184] a phone number associated with the respective search result, which when activated by a finger gesture initiates a phone call to the phone number;
- [0185] an icon that when activated by a finger gesture enters the physical address as an end point in a request for directions (e.g., "Directions to here" icon);
- [0186] an icon that when activated by a finger gesture enters the physical address as a starting point in a request for directions (e.g., "Directions from here" icon);
- [0187] an icon that when activated by a finger gesture initiates creation of a bookmark for the respective search result (e.g., "Add to bookmarks" icon initiates creation of a bookmark via interface **5200M**, FIG. 5E);
- [0188] an icon that when activated by a finger gesture initiates creation of a contact list entry for the respective search result (e.g., "Create new contact" icon); and/or
- [0189] an icon that when activated by a finger gesture initiates addition of the respective search result to an existing contact (e.g., "Add to existing contact" icon).

[0190] In some embodiments, a bookmarks user interface **5200N** (FIG. 5F) includes a list **5240** of locations bookmarked by a user. In some embodiments, in response to detecting a finger gesture **5286** on a configuration icon **5290** (e.g., Edit icon, FIG. 5F) for a list of bookmarks, the device displays respective deletion icons and/or respective moving-affordance icons for respective bookmarks in the list of bookmarks (FIG. 5G). Use of the deletion and moving-affordance icons is described in U.S. Provisional Patent Application Nos. 60/883,814, "Deletion Gestures on a Portable Multifunction Device," filed Jan. 7, 2007, and 60/883,808, "System and Method for Managing Lists," filed Jan. 7, 2007, which applications are incorporated by reference herein in their entirety in their entirety.

[0191] In some embodiments, a user interface **5200P** (FIG. 5H) includes a list of recent location, search, and/or route queries (collectively, a list of recent queries) by a user. In some embodiments, in response to a finger gesture (e.g., a

finger tap gesture) on a recent location query, the location is displayed on a digital map or entered as a start or end point in a route search query, depending on context. In some embodiments, in response to a finger gesture (e.g., a finger tap gesture) on a recent search query, the results of the recent search query are displayed on a digital map. In some embodiments, in response to a finger gesture (e.g., a finger tap gesture) on a recent route query, at least a portion of the corresponding routing instructions (e.g., driving directions) are displayed.

[0192] In some embodiments, a contacts UI **5200P** (FIG. 5J) includes a list of individual contacts **5254** and an icon **5298** that when activated by a finger gesture **5201** displays a list of groups of contacts (e.g., UI **5200S**, FIG. 5K). In some embodiments, in response to detecting a finger gesture **5256** on a contact in the list of contacts, an area associated with the contact (e.g., an area that includes an address associated with the contact in the contact list) is displayed on a digital map.

[0193] In some embodiments, a respective icon (e.g., icon **5203**, FIG. 5M) is displayed for a contact, wherein in response to detecting a finger gesture **5205** on the respective icon, an interface **5200V** (FIG. 5N) is displayed for the contact.

[0194] In some embodiments, the interface **5200V** for the contact includes:

- [0195] a name for the contact (e.g., Craig Buhler);
- [0196] a physical address for the contact;
- [0197] an image associated with the contact;
- [0198] an electronic address for the contact (e.g., a URL);
- [0199] a phone number associated with the contact;
- [0200] an icon that when activated by a finger gesture enters the physical address for the contact as an end point in a request for directions (e.g., "Directions to here" icon);
- [0201] an icon that when activated by a finger gesture enters the physical address for the contact as a starting point in a request for directions (e.g., "Directions from here" icon); and/or
- [0202] an icon that when activated by a finger gesture initiates creation of a bookmark for the contact (e.g., "Add to bookmarks" icon initiates creation of a bookmark via interface **5200W**, FIG. 5O).

[0203] In some embodiments, in response to finger contacts on icons **5292**, **5294**, and **5296** in the user interfaces for bookmarks (UI **5200N**, FIG. 5F), recent queries (UI **5200P**, FIG. 5H), and contacts (UI **5200R**, FIG. 5J), the device displays the corresponding user interface, which makes navigating between these interfaces simple and intuitive.

[0204] In some embodiments, in response to detecting a finger gesture on a route search icon **5207** (FIG. 5A), the device displays an endpoints area **5209** (FIG. 5P) comprising:

- [0205] a first area **5213** for entering a first location;
- [0206] a second area **5215** for entering a second location;
- [0207] and an icon **5211** for swapping information in the first area **5213** with information in the second area **5215**.

[0208] In some embodiments, in response to detecting a finger gesture **5239** (FIG. 5Q) (e.g., a finger tap gesture) on the first area ("Start:"), the device displays a keyboard for entering the first location (FIG. 5Q). In some embodiments, in response to detecting a finger gesture **5241** (e.g., a finger tap gesture) on the second area ("End:"), the device displays a keyboard for entering the second location.

[0209] In some embodiments, in response to detecting a finger gesture **5217** (FIG. 5P) (e.g., a finger tap gesture) on an input icon **5219** associated with the first area **5213**, the device displays:

[0210] a list **5240** (FIG. 5F) of bookmarked locations, wherein in response to detecting a finger gesture (e.g., **5244**) on a bookmarked location (e.g., **5242-3**) in the list of bookmarked locations, an address or name corresponding to the bookmarked location (e.g., **5242-3**) is entered in the first area;

[0211] a list **5246** (FIG. 5H) of recent searches, wherein in response to detecting a finger gesture on a location in the list of recent searches, an address corresponding to the location is entered in the first area; or

[0212] a list **5252** (FIG. 5J) of contacts, wherein in response to detecting a finger gesture on a contact **5254** in the list of contacts, an address associated with the contact (e.g., an address associated with the contact in the contact list) is entered in the first area.

[0213] In some embodiments, in response to detecting a finger gesture **5221** (FIG. 5P) (e.g., a finger tap gesture) on an input icon **5223** associated with the second area **5215**, the device displays:

[0214] a list **5240** (FIG. 5F) of bookmarked locations, wherein in response to detecting a finger gesture (e.g., **5244**) on a bookmarked location (e.g., **5242-3**) in the list of bookmarked locations, an address or name corresponding to the bookmarked location (e.g., **5242-3**) is entered in the second area;

[0215] a list **5246** (FIG. 5H) of recent searches, wherein in response to detecting a finger gesture on a location in the list of recent searches, an address corresponding to the location is entered in the second area; or

[0216] a list **5252** (FIG. 5J) of contacts, wherein in response to detecting a finger gesture on a contact **5254** in the list of contacts, an address associated with the contact (e.g., an address associated with the contact in the contact list) is entered in the second area.

[0217] In some embodiments, in response to detecting a finger gesture **5225** (FIG. 5R) on a route search initiation icon **5227**, the device: sends the first location (e.g., 2 Infinite Loop, Cupertino, Calif.) and the second location (e.g., 100 Main St., Seattle, Wash.) to a remote computer (e.g., a map application server, such as Google maps); receives routing information between the first location and the second location; and displays at least some of the routing information between the first location and the second location on a digital map (e.g., FIGS. 5S-5AA)

[0218] In some embodiments, the received routing information includes all of the digital map information needed to display the waypoints in the route between the first location and the second location. In some embodiments, the received routing information is stored (e.g., cached) so that the device can display the routing information even if the device loses access to the remote computer.

[0219] In some embodiments, in response to detecting a finger gesture **5231** (e.g., a finger tap gesture) on a start icon **5229** (FIG. 5S), the device displays the first location and the first portion of the routing information (FIG. 5T). Similarly, in some embodiments, in response to detecting a finger gesture (e.g., a finger tap gesture) on a next waypoint icon **5237**, the device displays the next waypoint and the corresponding map information (FIGS. 5T-5Z). In some embodiments, in response to detecting a finger gesture (e.g., a finger tap ges-

ture) on a previous waypoint icon **5239**, the device displays the previous waypoint and the corresponding map information.

[0220] In some embodiments, if the distance to the next waypoint is large relative to the area displayed around a waypoint on the digital map, the user interface may zoom out, display an animated movement to the next waypoint, and then zoom back in to the next waypoint, as illustrated in FIGS. 5U-5Y.

[0221] In some embodiments, in response to detecting a finger gesture **5235** (e.g., a finger tap gesture) on a list icon **5233** (FIG. 5S), the device displays an itemized list of the routing information (e.g., turn-by-turn driving directions), as shown in UI **5200II** (FIG. 5AA). In some embodiments, in response to detecting a finger gesture **5237** (e.g., a finger tap gesture) on a particular item in the list (FIG. 5AA), the corresponding portion of routing information is shown on a digital map (e.g., UI **5200LL**, FIG. 5U).

[0222] FIGS. 6A-6C illustrate exemplary user interfaces for displaying an approximate location of a computing device on a map in accordance with some embodiments. FIG. 6A shows an example of a map application including a view location icon **602**, a view options icon **608**, a search mode icon **604**, and a directions mode icon **606**.

[0223] FIG. 6B shows a visual indicator **614** on a displayed map **5266** indicating an approximate region in which a computing device (e.g., portable multifunction device **100**) is located. FIG. 6C shows a second visual indicator **618** on the displayed map **5266** that is displayed when the displayed map is entirely within the approximate region in which the device is located.

[0224] In some embodiments, the user interfaces UI **600A** (FIG. 6A), UI **600B** (FIG. 6B), and UI **600C** (FIG. 6C) include the following elements, or a subset or superset thereof:

[0225] **402, 404, 406, 5202, and 5266**, as described above;

[0226] an input icon **5204** that when activated (e.g., by a finger tap on the icon) initiates display of a UI for accessing bookmarks, recent queries, or contacts.

[0227] a view location icon **602** that when activated (e.g., by a finger tap on the icon) initiates a process that displays the approximate region in which a computing device is located on a map;

[0228] a search mode icon **604** that when activated (e.g., by a finger tap on the icon) initiates display of a UI for entering search terms (e.g., UI **600A**);

[0229] a directions mode icon **606** that when activated (e.g., by a finger tap on the icon) initiates display of a UI for entering start and end points for a route search (e.g., UI **1000C**, FIG. 10C);

[0230] a view options icon **608** that when activated (e.g., by a finger tap on the icon) initiates display of a UI for displaying and selecting applications options (e.g., UI **800A**, FIG. 8A);

[0231] a first visual indicator **614** (FIG. 6B) that indicates an approximate region in which the computing device is located in accordance with the received location information when the approximate region lies within the displayed map **5266**; and

[0232] a second visual indicator **618** (FIG. 6C) around a perimeter of the displayed map **5266** that is displayed when the approximate region in which the computing

device is located includes the displayed map **5266** and also extends beyond the displayed map.

[0233] The user interfaces in FIGS. 6A-6C are used to illustrate the process **700** described below with respect to FIG. 7.

[0234] FIG. 7 is flow diagram illustrating a method of displaying an approximate location of a computing device on a map in accordance with some embodiments. The method is performed at a computing device with a touch screen display (e.g., portable multifunction device **100**). The method **700** provides a simple way for a user to view the device's present location along with a visual indication of the accuracy with which the device's location is known.

[0235] A map application (e.g., **154**, FIG. 1B) is displayed (**702**). The map application is configured to display a map (e.g., map **5266**, FIG. 6A).

[0236] Location information for the computing device is received (**704**). In some embodiments, the location information corresponds to one or more terrestrial transmitting devices (e.g., cell towers, Wi-Fi sources, or other computing devices) from which the computing device receives signals.

[0237] In some embodiments, the device receives signals from a plurality of services capable of providing the location information, and selects location information from one of the plurality of services in accordance with location information selection criteria. For example, the location information received by the device may be GPS information, Wi-Fi information, or information from cell towers. After receiving this information, the device may select the GPS information (if available) rather than Wi-Fi or cell tower information. If GPS information is not available, the device may choose to use either Wi-Fi or cell tower information or a combination thereof. In some embodiments, the device may use Wi-Fi information only if the Wi-Fi information is consistent with the information from cell tower sources.

[0238] In response to detecting a user gesture on a view location icon (e.g., gesture **610** on view location icon **602**, FIG. 6A) while the map application is displayed, the device displays (**706**) a first visual indicator on a portion of the displayed map that indicates an approximate region in which the computing device is located in accordance with the received location information when the approximate region lies within the displayed map. For example, in FIG. 6B, the displayed map includes a cross-hair circle **614** as a first visual indicator on a portion of the displayed map **5266**. The area within the indicator's perimeter represents an approximate region on the map in which the computing device is located. In some embodiments, the first visual indicator **614** includes a circle displayed on the displayed map **5266**.

[0239] In some embodiments, detecting the user gesture on the view location icon initiates (**708**) a request for the location information for the computing device. In some embodiments, the device receives (**710**) location information from a transmitting device that is located within the region corresponding to the displayed first visual indicator (e.g., cross-hair circle **614**, FIG. 6B).

[0240] In response to detecting a user gesture on a view location icon (e.g., gesture **610** on view location icon **602**, FIG. 6A) while the map application is displayed, the device displays (**706**) a second visual indicator (e.g., cross-hair rectangle **618**, FIG. 6C) around a perimeter of the displayed map when the approximate region includes the displayed map and also extends beyond the displayed map. In some embodi-

ments, the second visual indicator includes a rectangle displayed at the boundary of the displayed map.

[0241] The device changes (**712**) from displaying the first visual indicator to displaying the second visual indicator in response to magnifying an area of the map that includes the approximate region in which the computing device is located. For example, in response to a de-pinching finger gesture (e.g., gesture **616**, FIG. 6B), which magnifies an area of the map, the device changes from displaying the first visual indicator **614** (FIG. 6B) to displaying the second visual indicator **618** (FIG. 6C).

[0242] The device changes (**714**) from displaying the second visual indicator to displaying the first visual indicator in response to de-magnifying an area of the map that includes the approximate region in which the computing device is located. For example, in response to a pinching finger gesture (e.g., gesture **620**, FIG. 6C), which demagnifies an area of the map, the device changes from displaying the second visual indicator **618** (FIG. 6C) to displaying the first visual indicator **614** (FIG. 6B).

[0243] FIG. 8A illustrates an exemplary user interface for displaying and selecting application options in accordance with some embodiments. FIG. 8A includes a curled version of a map application interface. But the curled version of the application interface is not limited to a map application. FIG. 8B illustrates an exemplary user interface with user-requested information overlaid on a map in accordance with some embodiments.

[0244] In some embodiments, UI **800A** (FIG. 8A) includes the following elements, or a subset or superset thereof:

[0245] **402, 404, 406, 5202, 5204, 602, 604, 606, and 608**, as described above;

[0246] a portion **802** of a flat version of an application interface;

[0247] an image of a curled page **804** that obscures a portion of the flat version of the application interface;

[0248] a roll-up region **806** in a display region formerly occupied by another portion of the flat version of the application interface, wherein the roll-up region includes a plurality of option icons.

[0249] For a map application, the plurality of options icons in the roll-up region **806** includes the following icons, or a subset or superset thereof:

[0250] a drop pin icon **808** that when activated (e.g., by a finger tap on the icon) initiates display of a user-movable location marker on a flat version of a map;

[0251] a show traffic icon **810** that when activated (e.g., by a finger tap on the icon) initiates display of traffic conditions on a flat version of a map;

[0252] a map view icon **812** that when activated (e.g., by a finger tap on the icon) initiates display of a flat version of a graphical map;

[0253] a satellite view icon **814** that when activated (e.g., by a finger tap on the icon) initiates display of a flat version of a satellite image corresponding to the graphical map;

[0254] a hybrid view icon **816** that when activated (e.g., by a finger tap on the icon) initiates display of a flat version of a hybrid combination of a satellite image and a corresponding graphical map; and

[0255] a list view icon **818** that when activated (e.g., by a finger tap on the icon) initiates display of a list of search results.

[0256] In some embodiments, UI **800B** (FIG. **8B**) includes the following elements, or a subset or superset thereof:

[0257] **402, 404, 406, 5202, 5204, 602, 604, 606, and 608**, as described above;

[0258] gas information icon **826** that is overlaid on the map when a gas information option icon (not shown) is selected;

[0259] lodging information icon **830** that is overlaid on the map when a lodging information option icon (not shown) is selected;

[0260] post office information icon **824** that is overlaid on the map when a post office information option icon (not shown) is selected; and

[0261] food information icon **828** that is overlaid on the map when a food information option icon (not shown) is selected.

[0262] The user interfaces in FIGS. **6A** and **8A-8B** are used to illustrate the process described below with respect to FIG. **9**.

[0263] FIG. **9** is a flow diagram illustrating a method of displaying and selecting application options in accordance with some embodiments. The method **900** is performed at a computing device with a touch screen display (e.g., portable multifunction device **100**). The method **900** provides a simple and intuitive way for a user to view and select various options when displaying an application. A map application is used here for exemplary and explanatory purposes. The method **900** is not limited to map applications.

[0264] A flat version of an application interface is displayed (**902**). For example, user interface **600A** (FIG. **6A**) illustrates a flat version of an application interface for a map application.

[0265] In response to detecting a user gesture (e.g., a finger tap gesture **612**, FIG. **6A**) on a view options icon (e.g., **608**, FIG. **6A**) while the flat version of the application interface is displayed, a curled version of the application interface is displayed (**904**).

[0266] The curled version of the application interface (e.g., interface **800A**, FIG. **8A**) includes an image of a curled page that obscures a first portion of the flat version of the application interface. For example, in FIG. **8A**, curled page **804** obscures the portion of the map underneath the curled page.

[0267] The curled version of the application interface also includes a roll-up region (e.g., roll-up region **806**, FIG. **8A**) in a display region formerly occupied by a second portion of the flat version of the application interface. The roll-up region **806** includes a plurality of option icons (e.g., icons **808, 810, 812, 814, 816, and 818** in FIG. **8A**), with each respective icon in the plurality of option icons responsive to a user selection gesture on the respective option icon (**904**).

[0268] In some embodiments, the curled version of the application interface includes (**906**) a third portion of the flat version of the application interface. For example, in FIG. **8A**, the curled version of the map application interface **800A** includes a third portion **802** of the flat version of the map application interface that is not obscured by the image of the curled page **804**.

[0269] In some embodiments, the third portion is displayed in the curled version of the application interface in a manner that is visually distinct from display of the third portion in the flat version of the application interface. For example, the flat portion **802** in FIG. **8A** may be darkened relative to the corresponding flat portion of the map **5266** in FIG. **6A**. Continuing to show a portion **802** of the flat version of the application helps maintain the application context for the user

while simultaneously permitting the user to view the application options in the roll-up region **806** (FIG. **8A**).

[0270] In some embodiments, a roll up animation is displayed (**908**) that transitions from displaying the flat version of the application interface to displaying the curled version of the application interface. For example, in response to detecting user gesture **612** on the view options icon **608** (FIG. **6A**), a roll up animation may transition from FIG. **6A** (the flat version) to FIG. **8A** (the curled version).

[0271] In some embodiments, the application is a map application (e.g., **154**, FIG. **1B**) and the flat version of the application interface includes a map (e.g., map **5266**, FIG. **6A**).

[0272] In some embodiments, for the map application, the plurality of option icons include a satellite view option icon **814**, a hybrid view option icon **816**, and a traffic information overlay option icon **810** (FIG. **8A**).

[0273] In some embodiments, for the map application, the plurality of option icons include an icon for adding a user-moveable location marker to the map. For example, FIG. **8A** includes a drop pin icon **808** for adding a user-moveable location marker (e.g., pin **1002**, FIG. **10A**) to map **5266**.

[0274] In some embodiments, for the map application, the plurality of option icons include a plurality of map overlay option icons. For example, there may be option icons allowing the user to overlay additional information on to the map **5266**, such as traffic **810**, gas, food, and lodging. FIG. **8B** illustrates an exemplary user interface **800B** for displaying the additional information overlaid on the map (e.g., gas **826**, lodging **830**, food **828**, and mail **824**) in response to user selection of corresponding map overlay option icons.

[0275] In some embodiments, the curled page includes a translucent representation of a portion of the flat version of the application interface. For example, the curled page **804** in FIG. **8A** may display a translucent representation of map **5266** (not shown). In some embodiments, the curled page includes an inverted, translucent representation of a portion of the flat version of the application interface. For example, the curled page **804** in FIG. **8A** may display an inverted, translucent representation of map **5266** (not shown).

[0276] A user selection gesture (e.g., gesture **822**, FIG. **8A**) on one or more of the plurality of option icons is detected (**910**). In some embodiments, the user selection gestures are finger gestures on the touch screen display. For example, in FIG. **8A**, user selection of the drop pin icon **808** is by finger gesture **822**. In some embodiments, the application interface displayed on the touch screen is responsive to stylus input gestures on the touch screen display.

[0277] The flat version of the application interface is redisplayed (**912**) with information corresponding to the one or more option icons upon which the user selection gestures were detected. For example, FIG. **10A** shows a user-moveable location marker **1002** added to map **5266** and FIG. **8B** shows information icons **824, 826, 828, and 830**, which correspond to overlay option icons selected by the user, added to map **5266**.

[0278] In some embodiments, the flat version of the application interface is redisplayed in response to detecting a second user gesture on the view options icon. For example, in FIG. **8A**, in response to a finger tap gesture **820** on the view options icon **608**, display of the curled version **800A** transitions to redisplay of the flat version of the application inter-

face with information corresponding to the one or more option icons upon which the user selection gestures were detected.

[0279] In some embodiments, user selection gestures are detected on at least two of the plurality of option icons, and the flat version of the application interface is redisplayed with information corresponding to the at least two of the plurality of option icons upon which user selection gestures were detected. For example, in the roll up region 806 of the curled version of the map application (FIG. 8A), the user may select both the show traffic icon 810 and the satellite icon 814 prior to redisplaying the flat version of the application interface. In response to a finger tap gesture 820 on the view options icon 608, the device will redisplay the flat version of the map application interface with a satellite view and with traffic information overlaid on the map.

[0280] For some options icons, selection of the option icon may result in an immediate transition to the flat application interface with the corresponding option added, without requiring detection of a second gesture on the view options icon (or some other close options icon). For example, detection of gesture 822 on the drop pin icon 808 may result in the immediate transition to the flat application interface with a user moveable location marker added to the map (e.g., pin 1002 added to map 5266 in FIG. 10A).

[0281] In some embodiments, a roll down animation is displayed (914) that transitions from displaying the curled version of the application interface to redisplaying the flat version of the application interface with information corresponding to the one or more option icons upon which user selection gestures were detected. For example, in response to user selection of the view options icon 608 (FIG. 8A), a roll down animation may transition from FIG. 8A (the curled version) to FIG. 6A (the flat version).

[0282] The map application is just one example of an application that can use this method of displaying and selecting application options. Other applications that can use this method include, without limitation: contacts 137; telephone 138; video conferencing 139; e-mail client 140; instant messaging (IM) 141; blogging 142; camera 143; image management 144; video player 145; music player 146; browser 147; calendar 148; widgets 149 (e.g., weather widget 149-1, stocks widget 149-2, calculator widget 149-3, alarm clock widget 149-4, dictionary widget 149-5, and other widgets obtained by the user, as well as user-created widgets 149-6); widget creator 150; search 151; video and music player 152; notes 153; and online video 155.

[0283] FIG. 10A illustrates an exemplary user interface for displaying a map application with a user-moveable location marker in accordance with some embodiments.

[0284] FIG. 10B illustrates an exemplary user interface for displaying user-selectable option icons associated with a user-moveable location marker in accordance with some embodiments.

[0285] FIG. 10C illustrates an exemplary user interface for obtaining directions to a location corresponding to a user-moveable location marker in accordance with some embodiments. FIG. 10D illustrates an exemplary user interface for obtaining directions from a location corresponding to a user-moveable location marker in accordance with some embodiments.

[0286] FIG. 10E illustrates an exemplary user interface for adding a location marker to a set of bookmarks in accordance with some embodiments.

[0287] FIG. 10F illustrates an exemplary user interface with a current location of a computing device included in a list of bookmarks in accordance with some embodiments.

[0288] In some embodiments, UI 1000A (FIG. 10A) includes the following elements, or a subset or superset thereof:

[0289] 402, 404, 406, 5202, 5204, 5266, 602, 604, 606, 608, and 614 as described above;

[0290] a user-moveable location marker 1002;

[0291] a user-selectable region 1004 that when activated (e.g., by a finger tap 1010 on the region) initiates display of an interface (e.g., UI 1000B, FIG. 10B) for obtaining information associated with the current location of a corresponding user-moveable location marker 1002-1; and

[0292] a user-selectable region 1006 next to region 1004 that when activated (e.g., by a finger tap 1018 on region 1006) ceases display of region 1004 and region 1006;

[0293] UI 1000B (FIG. 10B) includes the following elements, or a subset or superset thereof:

[0294] 402, 404, and 406, as described above;

[0295] a name 1019 (e.g., "Dropped Pin") for an associated user-moveable location marker (e.g., marker 1002-1, FIG. 10A);

[0296] a return to map icon 1020 that when activated (e.g., by a finger tap on the icon) initiates display of a map application interface with the corresponding user-moveable location marker (e.g., UI 1000A, FIG. 10A);

[0297] an image 1022 of a portion of the map application interface with the corresponding user-moveable location marker (e.g., UI 1000A, FIG. 10A);

[0298] an add to bookmarks icon 1024 that when activated (e.g., by a finger tap 1036 on the icon) initiates replacement of UI 1000B with display of a user interface for adding an entry to a set of bookmarked locations (e.g., UI 1000E, FIG. 10E), the added entry corresponding to the current location of the user-moveable location marker 1002-1 on the map 5266 (FIG. 10A);

[0299] a directions to here icon 1026 that when activated (e.g., by a finger tap 1038 on the icon) initiates replacement of UI 1000B with display of a user interface for getting directions to the current location of the user-moveable location marker 1002-1 on the map 5266 from another location (e.g., UI 1000C, FIG. 10C);

[0300] a directions from here icon 1028 that when activated (e.g., by a finger tap 1040 on the icon) initiates replacement of UI 1000B with display of a user interface for getting directions from the current location of the user-moveable location marker 1002-1 on the map 5266 to another location (e.g., UI 1000D, FIG. 10D);

[0301] a remove location marker icon 1030 (e.g., "Remove Pin") that when activated (e.g., by a finger tap 1042 on the icon) initiates deletion of the corresponding user-moveable location marker 1002-1 from the map 5266 (FIG. 10A);

[0302] a create new contact icon 1032 that when activated (e.g., by a finger tap 1044 on the icon) initiates replacement of UI 1000B with display of a user interface for adding an entry to a set of contacts, the added entry including location information corresponding to the location of the user-moveable location marker 1002-1 on the map 5266 (FIG. 10A); and

[0303] an add to existing contact icon 1034 that when activated (e.g., by a finger tap 1046 on the icon) initiates

replacement of UI 1000B with display of a user interface (or a series of user interfaces) for updating an entry in a set of contacts to include location information corresponding to the location of the user-moveable location marker 1002-1 on the map 5266 (FIG. 10A).

[0304] UI 1000C (FIG. 10C) and UI 1000D (FIG. 10D) include the following elements, or a subset or superset thereof:

[0305] 402, 404, 406, 5209, 5211, 5213, 5215, 5219, 5223, 5227, and 5236 as described above; and

[0306] a keyboard 5216 for entering locations in areas 5213 and/or 5215;

[0307] a delete icon 1050 that when activated (e.g., by a finger tap on the icon) initiates deletion of any text entered in the corresponding area.

[0308] UI 1000E (FIG. 10E) is analogous to UI 5200M (FIG. 5E, described above).

[0309] UI 1000F (FIG. 10F) includes the following elements, or a subset or superset thereof:

[0310] 402, 404, 406, 5240, 5290, 5292, 5294, and 5296 as described above; and

[0311] current location 1070 that corresponds to the current location information for the device (e.g., portable multifunction device 100), whether or not the current location information has been added to a set of bookmarks (e.g., via UI 1000E, FIG. 10E); and

[0312] dropped pin 1072 that corresponds to the location information of a corresponding user-moveable location marker 1002 on the map 5266, whether or not the user-moveable location marker 1002 has been added to a set of bookmarks (e.g., via UI 1000E, FIG. 10E).

[0313] The user interfaces in FIGS. 8A and 10A-10F are used to illustrate the process 1100 described below with respect to FIG. 11 and the process 1500 described below with respect to FIG. 15.

[0314] FIG. 11 is a flow diagram illustrating a method 1100 for displaying and moving a user-moveable location marker on a map in accordance with some embodiments. The method 1100 is performed at a computing device with a touch screen display (e.g., portable multifunction device 100). The method 1100 provides a simple way for a user to place a location marker on the displayed map, and retrieve information associated with the location of the marker (e.g., the address of the marker and directions to or from the marker).

[0315] A map application (e.g., 154, FIG. 1B) is displayed (1102). The map application is configured to display a map (e.g., map 5266, FIG. 10A).

[0316] A first finger gesture is detected (1104) on an icon for adding a user-moveable location marker to the map (e.g., gesture 822, FIG. 8A).

[0317] The device displays (1105) the user-moveable location marker (e.g., marker 1002-1, FIG. 10A) on the map. In some embodiments, the user-moveable location marker 1002 is immediately displayed in response to detecting (1104) the finger gesture on the icon for adding a user-moveable location marker to the map (e.g., gesture 822, FIG. 8A). In some embodiments, the user-moveable location marker 1002 is not displayed on the map until a finger gesture on a view options icon 608 (e.g., gesture 820, FIG. 8A) or a close options icon is detected.

[0318] In some embodiments, the icon for adding a user-moveable location marker to the map is located in a curled version of the map application interface (e.g., icon 808 in UI 800A, FIG. 8A).

[0319] In some embodiments, the device also displays text identifying the current location of the user-moveable location marker on the map. For example, the device may be configured to automatically display text identifying the current location in user-selectable region 1006 (FIG. 10A). In some embodiments, text identifying the location of the marker may be displayed elsewhere in UI 1000A (FIG. 10A) or in an interface (e.g., UI 1000B, FIG. 10B) for displaying additional options and information associated with the location marker.

[0320] In some embodiments, the device transmits a request for a reverse lookup of the current location of the user-moveable location marker on the map and receives information identifying the current location of the user-moveable location marker on the map. In some embodiments, the device transmits the request for the reverse lookup without user intervention at predetermined times (e.g., when the marker is initially placed on the map and after the marker has been moved on the map). In some embodiments, the device transmits the request for the reverse lookup in response to a user request (e.g., in response to detecting a finger tap gesture 1016 on location marker 1002-1 (FIG. 10A)). In some embodiments, UI 1000A (FIG. 10A) or UI 1000B (FIG. 10B) contains a reverse lookup icon (not shown) allowing the user to request a reverse lookup of the marker location.

[0321] In response to detecting a second finger gesture on the user-moveable location marker, the device moves (1106) the user-moveable location marker on the map in accordance with the second finger gesture. For example, in FIG. 10A, the device moves the location marker 1002-1 in accordance with a second finger gesture 1012.

[0322] In some embodiments, the second finger gesture (e.g., 1012, FIG. 10A) includes a finger contact area that moves on the touch screen. In some embodiments, moving the user-moveable location marker on the map in accordance with the second finger gesture includes displaying the user-moveable location marker offset from the moving finger contact area during the second finger gesture. For example, in FIG. 10A the second finger gesture includes a finger contact area 1013 that moves on the touch screen. The user-moveable location marker 1002-1 is offset from the moving finger contact area 1013. More details on moving the marker 1002-1 will be discussed with respect to FIGS. 12C(1)-12C(5) below.

[0323] In some embodiments, the user-moveable location marker is offset from the moving finger contact area such that a user's view of the user-moveable location marker is not obscured by the second finger gesture while moving the user-moveable location marker on the map in accordance with the second finger gesture. For example, the finger contact area (e.g., area 1013, FIG. 10A, and area 1214, FIGS. 12C(2)-12C(4)) is offset from the moving location marker 1002-1 so that the location marker is not obscured by the second finger gesture (FIG. 10A). More details on moving the location marker 1002-1 will be discussed in reference to FIG. 12C(1)-12C(5) below.

[0324] While displaying the map and the user-moveable location marker, the device displays (1108) a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map. For example, UI 1000A (FIG. 10A) includes a user selectable region 1004 for obtaining information associated with the marker 1002-1. In some embodiments, the user-selectable region 1004 is denoted by a chevron (e.g., ">") and moves with the marker. In some embodiments, the display of user-selectable regions 1006 and 1004 is toggled on by a finger tap

on the location marker **1002-1** and toggled off by a finger tap on region **1006**. In other embodiments, region **1006** is a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map.

[0325] In response to detecting a third finger gesture on the user-selectable region for obtaining information, the display of the map and the user-moveable location marker is replaced (**1110**) with a display of a plurality of option icons. For example, in response to a third finger gesture **1010** on the user-selectable region **1004** (FIG. **10A**), the device replaces the display of the map **5266** and the marker **1002-1** with a display of a plurality of option icons (e.g., icons **1024**, **1026**, **1028**, **1030**, **1032**, and **1034** in UI **1000B**, FIG. **10B**). The plurality of option icons includes a first icon (add to bookmarks icon **1024**), a second icon (directions to here icon **1026**), and a third icon (directions from here icon **1028**) that are described in more detail below.

[0326] In response to detection of a finger gesture on the first icon, the display of the plurality of option icons is replaced (**1110**) with a display of a user interface for adding an entry to a set of bookmarked locations. The added entry corresponds to the current location of the user-moveable location marker on the map. For example, in UI **1000B** (FIG. **10B**), in response to detection of a finger gesture **1036** on the add to bookmarks icon **1024**, the display of the plurality of option icons is replaced with a display of a user interface (e.g., UI **1000E** FIG. **10E**) for adding an entry to a set of bookmarked locations. UI **1000E** may include a text input box for modifying the name of the location marker (“Dropped Pin”, FIG. **10E**) with a soft keyboard **5236**.

[0327] In some embodiments, adding the entry to the set of bookmarked locations includes displaying a sequence of graphical user interfaces responsive to user gestures for adding the entry to the set of bookmarked locations.

[0328] In response to detection of a finger gesture on the second icon, the display of the plurality of option icons is replaced (**1110**) with a display of a user interface for getting directions to the current location of the user-moveable location marker on the map from another location. For example, in response to a finger gesture **1038** (FIG. **10B**) on the directions to here icon **1026**, the display of the plurality of option icons is replaced with a display of a user interface UI **1000C** (FIG. **10C**) for getting directions to the location of the marker on the map. In UI **1000C** (FIG. **10C**), the area **5215** for entering the end point is automatically populated with the name of the location marker (e.g., “Dropped Pin” in FIG. **10C**). The user then merely has to enter the starting location and activate the route initiation icon **5227** (e.g., by a finger tap on the icon) to obtain directions to the current location of the user-moveable location marker on the map. In some embodiments, the device requests a reverse lookup to identify the current location of the marker.

[0329] In response to detection of a finger gesture on the third icon, the display of the plurality of option icons is replaced (**1110**) with a display of a user interface for getting directions from the current location of the user-moveable location marker on the map to another location. For example, in response to a finger gesture **1040** (FIG. **10B**) on the directions from here icon **1028**, the display of the plurality of option icons is replaced with a display of a user interface UI **1000D** (FIG. **10D**) for getting directions from the location of the marker on the map. In UI **1000D** (FIG. **10D**), the area **5213** for entering the start point is automatically populated

with the name of the location marker (e.g., “Dropped Pin” in FIG. **10D**). The user then merely has to enter the ending location and activate the route initiation icon **5227** (e.g., by a finger tap on the icon) to obtain directions from the current location of the user-moveable location marker on the map. In some embodiments, the device requests a reverse lookup to identify the current location of the marker.

[0330] In some embodiments, the plurality of option icons include a fourth icon (remove location marker icon **1030**), wherein in response to detection of a finger gesture on the fourth icon, the user-moveable location marker is deleted. For example, in response to a finger gesture **1042** (FIG. **10B**) on the remove location marker icon **1030** (e.g., “Remove Pin”), the corresponding user-moveable location marker **1002-1** is deleted from the map **5266** (FIG. **10A**).

[0331] In some embodiments, the plurality of option icons include an icon for adding an entry to a list of contacts, the added entry including location information corresponding to the map location of the marker. For example, in response to a finger gesture **1044** (FIG. **10B**) on the create new contact icon **1032**, UI **1000B** is replaced with display of a user interface (or series of user interfaces) for adding an entry to a set of contacts, the added entry including location information corresponding to the location of the user-moveable location marker **1002-1** on the map **5266** (FIG. **10A**).

[0332] In some embodiments, the plurality of option icons include an icon for updating an entry in a list of contacts to include location information corresponding to the current location of the user-moveable location marker on the map. For example, in response to a finger gesture **1046** (FIG. **10B**) on the add to existing contact icon **1034**, UI **1000B** is replaced with display of a user interface (or series of user interfaces) for updating an entry in a set of contacts to include location information corresponding to the location of the user-moveable location marker **1002-1** on the map **5266** (FIG. **10A**).

[0333] FIGS. **12A-12E** illustrate examples of user interactions with a displayed map, a user-moveable location marker, and information associated with the location marker via finger gestures in accordance with some embodiments. FIGS. **12A-12E** are used to illustrate the process **1300** described below with respect to FIG. **13**.

[0334] FIG. **13** is a flow diagram illustrating a method **1300** for interacting with a displayed map and a location marker in accordance with some embodiments. The method **1300** distinguishes between gestures intended to move a map, gestures intended to move a location marker rather than the map, gestures intended for getting additional information about the location marker, and gestures intended for other types of interactions with the map. The method **1300** occurs at a portable computing device with a touch screen display (e.g., portable multifunction device **100**). The method permits a map application on a touch screen display to respond to imprecise finger gestures in a manner that conforms to a user’s expectations. In other words, the method enables a user’s finger gestures to control a map application in a simple, intuitive way.

[0335] In response to detecting a first finger gesture on a marker on a digital map on the touch screen display, the device moves (**1302**) the digital map on the touch screen display. The first finger gesture moves a finger contact area more than a first predetermined distance in a first predetermined time when a finger in the first finger gesture initially touches the touch screen display.

[0336] For example, in FIG. 12A, first finger gesture 1202 moves a finger contact area 1204 more than a first predetermined distance (e.g., 3-5 mm) in a first predetermined time (e.g., 0.2-0.3 seconds) when a finger in the first finger gesture 1202 initially touches the touch screen display. In response to detecting first finger gesture 1202 on a marker 1002 on a digital map 5266 on the touch screen display, the device moves (1302) the digital map 5266 on the touch screen display, as shown in FIG. 12A.

[0337] The device interprets the initial movement in the first finger gesture 1202 as an instruction to move the displayed map (e.g., in accordance with the movement of the first finger gesture), rather than interpreting the first finger gesture as some other instruction (e.g., an instruction associated with the second, third, fourth, or fifth finger gestures, described below).

[0338] In response to detecting a second finger gesture on the marker on the digital map on the touch screen display, the device displays (1304) a user-selectable region for obtaining information associated with the marker on the touch screen display. The second finger gesture is a single tap gesture that moves a finger contact area less than a second predetermined distance and lasts less than a second predetermined time.

[0339] For example, in FIG. 12B, second finger gesture 1206 is a single tap gesture that moves a finger contact area 1208 less than a second predetermined distance (e.g., 3-5 mm) and lasts less than a second predetermined time (e.g., 0.2-0.3 seconds). In response to detecting the second finger gesture 1206 on the marker 1002 on the digital map 5266 on the touch screen display, the device displays (1304) a user-selectable region 1004 for obtaining information associated with the marker 1002 on the touch screen display, as shown in FIG. 12B.

[0340] The device interprets the second finger single tap gesture 1206 as an instruction to display user-selectable region 1004 for obtaining information associated with the marker 1002, rather than interpreting the second finger gesture as some other instruction (e.g., an instruction associated with the first, third, fourth, or fifth finger gestures).

[0341] In some embodiments, the second predetermined distance for the second gesture is the same as the first predetermined distance for the first gesture. Alternatively, in some embodiments, the second predetermined distance for the second gesture is different from the first predetermined distance for the first gesture. In some embodiments, the second predetermined time for the second gesture is the same as the first predetermined time for the first gesture. Alternatively, in some embodiments, the second predetermined time for the second gesture is different from the first predetermined time for the first gesture.

[0342] In response to detecting a third finger gesture on a user-moveable location marker on the digital map on the touch screen display, the device moves (1306) the user-moveable location marker on the digital map in accordance with the third finger gesture. The third finger gesture includes a stationary (or substantially stationary) contact followed by translation of a finger contact area on the touch screen display after the second predetermined time ends. The stationary (or substantially stationary) contact moves the finger contact area less than a third predetermined distance and lasts more than the second predetermined time.

[0343] For example, in FIG. 12C, third finger gesture 1212 includes a stationary (or substantially stationary) contact 1212-1 followed by translation 1212-2 of a finger contact area

on the touch screen display after the second predetermined time ends. The stationary (or substantially stationary) contact 1212-1 moves the finger contact area less than a third predetermined distance (e.g., 3-5 mm) and lasts more than the second predetermined time (e.g., 0.2-0.3 seconds). In response to detecting the third finger gesture 1212 on a user-moveable location marker 1002 (FIG. 12C) on the digital map on the touch screen display, the device moves (1306) the user-moveable location marker 1002 on the digital map in accordance with the third finger gesture (e.g., in FIGS. 12C(1)-12C(5), from 4th street to 6th street in accordance with translation 1212-2).

[0344] In some embodiments, the third finger gesture 1212 includes a finger contact area 1214 that moves on the touch screen. In some embodiments, moving the user-moveable location marker 1002 on the map 5266 in accordance with the third finger gesture 1212-2 includes displaying the user-moveable location marker 1002 offset from the moving finger contact area 1214 during the third finger gesture 1212-2. For example, in FIG. 12C(1), the user-moveable location marker 1002 is initially obscured by finger contact area 1214. After contact 1212-1 has exceeded the second predetermined time (e.g., 0.2-0.3 seconds), the user-moveable location marker 1002 may be offset from the finger contact area 1214 (FIG. 12C(2)). In some embodiments, an animation is displayed that shows the user-moveable location marker 1002 being offset from the finger contact area 1214 (e.g., an animation that transitions from FIG. 12C(1) to FIG. 12C(2)). In some embodiments, a shadow 1210 of the user-moveable location marker 1002 is displayed. In some embodiments, the shadow 1210 touches the user-moveable location marker 1002 to indicate that the marker 1002 is "attached" to the map 5266 and cannot be moved (e.g., FIGS. 12C(1) and 12C(5)). In some embodiments, the shadow 1210 is separated from the user-moveable location marker 1002 to indicate that the marker 1002 has been "detached" or "lifted up" from the map 5266 so that the marker 1002 (but not the map 5266) will move in accordance with the finger gesture (e.g., the marker moves in accordance with gesture 1212-2 in FIGS. 12C(2)-12C(4), with the shadow 1210 separated from the marker 1002).

[0345] In some embodiments, the user-moveable location marker 1002 is offset from the moving finger contact area such that a user's view of the user-moveable location marker is not obscured by the third finger gesture while moving the user-moveable location marker 1002 on the map 5266 in accordance with the third finger gesture. For example, the finger contact area 1214 in FIGS. 12C(2)-12C(4) is offset from the moving location marker 1002 so that the location marker 1002 is not obscured by the third finger gesture.

[0346] The device interprets the third finger gesture 1212 as an instruction to move the user-moveable location marker 1002 on the digital map in accordance with the third finger gesture 1212, rather than interpreting the third finger gesture as some other instruction (e.g., an instruction associated with the first, second, fourth, or fifth finger gestures).

[0347] In some embodiments, in response to detecting a fourth finger gesture on or near the marker on the digital map on the touch screen display, the device magnifies (1308) an area of the map that includes the marker on the touch screen display. The fourth finger gesture is a single-finger, double tap gesture that moves a finger contact area less than a fourth predetermined distance and lasts less than a fourth predetermined

mined time. In some embodiments, the fourth predetermined time is equal to the second predetermined time.

[0348] For example, in FIG. 12D, the fourth finger gesture 1216 is a single-finger, double tap gesture that moves a finger contact area 1218 less than a fourth predetermined distance (e.g., 3-5 mm) and lasts less than a fourth predetermined time (e.g., 0.2-0.3 seconds). In some embodiments, in response to detecting the fourth finger gesture 1216 on or near the marker 1002 on the digital map 5266 on the touch screen display, the device magnifies (1308) an area of the map that includes the marker 1002 on the touch screen display (FIG. 12D). In some embodiments, the fourth predetermined time is equal to the second predetermined time. In some embodiments, the device compares the time delay between detection of a first tap gesture and a second tap gesture to a predetermined value (e.g., 0.1-0.2 seconds) to determine if the user is making a double tap gesture. In some embodiments, the device also compares a change in location of the first tap gesture and the second tap gesture to a predetermined value (e.g., 3-5 mm) to determine if the user is making a double tap gesture.

[0349] The device interprets the fourth finger gesture 1216 as an instruction to magnify an area of the map that includes the marker, rather than interpreting the fourth finger gesture as some other instruction (e.g., an instruction associated with the first, second, third, or fifth finger gestures).

[0350] In some embodiments, in response to detecting a fifth finger gesture on the marker on the digital map on the touch screen display, the device demagnifies (1310) an area of the map that includes the marker on the touch screen display. The fifth finger gesture is a two-finger, double tap gesture that lasts less than a fifth predetermined time. In some embodiments, the fifth predetermined time is equal to the second predetermined time.

[0351] For example, in FIG. 12E, the fifth finger gesture 1218 is a two-finger, double tap gesture that lasts less than a fifth predetermined time (e.g., 0.2-0.3 seconds). In response to detecting the fifth finger gesture 1218 on the marker 1002 on the digital map 5266 on the touch screen display, the device demagnifies (1310) an area of the map that includes the marker on the touch screen display (FIG. 12E). In some embodiments, the fifth predetermined time is equal to the second predetermined time. In some embodiments, the device compares the time delay between detection of a first two-finger tap gesture and a second two-finger tap gesture to a predetermined value (e.g., 0.1-0.2 seconds) to determine if the user is making a two-finger double tap gesture. In some embodiments, the device also compares changes in locations of the two fingers in the first tap gesture and the two fingers in the second tap gesture to predetermined values (e.g., 3-5 mm) to determine if the user is making a two-finger double tap gesture.

[0352] The device interprets the fifth finger gesture 1218 as an instruction to demagnify an area of the map that includes the marker, rather than interpreting the fifth finger gesture as some other instruction (e.g., an instruction associated with the first, second, third, or fourth finger gestures).

[0353] FIG. 14 is a flow diagram illustrating a method 1400 for obtaining directions in accordance with some embodiments. The method 1400 occurs at a computing device with a touch screen display (e.g., portable multifunction device 100).

[0354] The computing device displays (1402) a map application. The map application is configured to separately display:

[0355] a list 5240 (FIG. 10F) of bookmarked locations, wherein a current location icon 1070 for the device is displayed at the top of the list of bookmarked locations 5434;

[0356] a list 5246 (FIG. 5H) of recent queries by a user;

[0357] a list 5252 (FIG. 5J) of contacts for the user; and

[0358] a keyboard 5216 with a route search initiation icon 5225 (FIG. 5R);

[0359] In some embodiments, if the view location icon 602 (FIG. 6A) is activated (e.g., by a finger tap 610 on the icon), a current location icon 1070 corresponding to the current location of the device is displayed at the top of the list of bookmarked locations 5434 even if the current location has not been made into a bookmark (e.g., even if UI 1000E (FIG. 10E) is not used on the current location). In process 1400, the current location icon 1070 is treated as a bookmarked location even if it is not an actual bookmarked location.

[0360] In some embodiments, the list 5240 (FIG. 10F) of bookmarked locations may include an entry 1070 corresponding to the current location of the device and an entry 1072 (e.g., "Dropped Pin") corresponding to the location of a user-moveable marker 1002. In some embodiments, entries 1070 and 1072 are displayed at the top of the list of bookmarked locations 5434 (e.g., in the first two positions in the list) even if these two entries have not been made into bookmarks (e.g., even if UI 1000E (FIG. 10E) is not used on the current location or the location of a corresponding user-moveable marker 1002). In process 1400, entries 1070 and 1072 are treated as bookmarked locations even if entries 1070 and 1072 are not actual bookmarked locations. Having one or both of these entries at the top of the list of bookmarked locations makes it easy for a user to add these locations to a search, to the starting location of a route search, and/or to the ending location of a route search (e.g., by a finger tap on entry 1070 or entry 1072).

[0361] In response to detecting a finger gesture on an input icon associated with the first area (e.g., input icon 5219 associated with area 5213, FIG. 10C), the device displays (1408):

[0362] the list 5240 (FIG. 10F) of bookmarked locations, wherein in response to detecting a finger gesture on a bookmarked location (including entry 1070 or entry 1072) in the list of bookmarked locations, the map application receives an address or name, corresponding to the bookmarked location, when the address or name is entered in the first area;

[0363] the list 5246 (FIG. 5H) of recent queries by the user, wherein in response to detecting a finger gesture on a location in the list of recent queries by the user, the map application receives an address corresponding to the location when the address is entered in the first area; or

[0364] the list 5252 (FIG. 5J) of contacts for the user, wherein in response to detecting a finger gesture on a contact in the list of contacts for the user, the map application receives an address associated with the contact when the address is entered in the first area;

[0365] In response to detecting a finger gesture on an input icon associated with the second area (e.g., input icon 5223 associated with area 5215, FIG. 10C), the device displays (1410):

[0366] the list 5240 (FIG. 10F) of bookmarked locations, wherein in response to detecting a finger gesture on a bookmarked location (including entry 1070 or entry 1072) in the list of bookmarked locations, the map application receives an address or name, corresponding to the

bookmarked location, when the address or name corresponding to the bookmarked location is entered in the second area;

[0367] the list **5246** (FIG. 5H) of recent queries by the user, wherein in response to detecting a finger gesture on a location in the list of recent queries by the user, the map application receives an address corresponding to the location when the address corresponding to the location is entered in the second area; or

[0368] the list **5252** (FIG. 5J) of contacts for the user, wherein in response to detecting a finger gesture on a contact in the list of contacts for the user, the map application receives an address associated with the contact when the address associated with the contact is entered in the second area.

[0369] In response to detecting a finger gesture on the route search initiation icon (e.g., **5227**, FIG. 10C), the device (**1412**):

[0370] sends the first location and the second location to a remote computer;

[0371] receives routing information between the first location and the second location; and

[0372] displays at least some of the routing information between the first location and the second location on a digital map.

[0373] FIG. 15 is a flow diagram illustrating a method for displaying and moving a user-moveable location marker **1002** on a map in accordance with some embodiments. The method **1500** occurs at a portable computing device with a touch screen display (e.g., portable multifunction device **100**). The method **1500** provides a simple way for a user to place a location marker on the displayed map, and retrieve information associated with the location of the marker (e.g., the address of the marker and directions to or from the marker).

[0374] The device displays (**1502**) a map application (e.g., **154**, FIG. 1B). The map application is configured to display a map (e.g., map **5266**, FIG. 10A). In response to detecting a stationary first finger gesture (e.g., **1016**, FIG. 10A) on the displayed map for greater than a predetermined time, the device displays (**1504**) a user-moveable location marker (e.g., marker **1002-1**, FIG. 10A) on the map. Thus, in method **1500**, a user-moveable location marker is added to a map merely by touching and holding a finger on the touch screen display for greater than a predetermined time (e.g., 0.5-1.0 seconds). The remainder of method **1500** is similar to method **1100**, described above

[0375] In response to detecting a second finger gesture on the user-moveable location marker, the device moves (**1506**) the user-moveable location marker on the map in accordance with the second finger gesture. For example, in FIG. 10A, the device moves the location marker **1002-1** in accordance with a second finger gesture **1012**.

[0376] In some embodiments, the second finger gesture (e.g., **1012**, FIG. 10A) includes a finger contact area that moves on the touch screen. In some embodiments, moving the user-moveable location marker on the map in accordance with the second finger gesture includes displaying the user-moveable location marker offset from the moving finger contact area during the second finger gesture. For example, in FIG. 10A the second finger gesture includes a finger contact area **1013** that moves on the touch screen. The user-moveable marker **1002-1** is offset from the moving finger contact area

1013. More details on moving the marker **1002-1** were discussed with respect to FIG. 12C(1)-12C(5) above.

[0377] In some embodiments, the user-moveable location marker is offset from the moving finger contact area such that a user's view of the user-moveable location marker is not obscured by the second finger gesture while moving the user-moveable location marker on the map in accordance with the second finger gesture. For example, the finger contact area (e.g., area **1013**, FIG. 10A, and area **1214**, FIG. 12C(2)-12C(4)) is offset from the moving location marker **1002-1** so that the location marker is not obscured by the second finger gesture (FIG. 10A). More details on moving the location marker **1002-1** were discussed in reference to FIG. 12C(1)-12C(5) above.

[0378] In some embodiments, the device displays (**1508**) text identifying the current location of the user-moveable location marker on the map. For example, the device may be configured to automatically display text identifying the current location in user-selectable region **1006** (FIG. 10A). In some embodiments, text identifying the location of the marker may be displayed elsewhere in UI **1000A** (FIG. 10A) or in an interface (e.g., UI **1000B**, FIG. 10B) for displaying additional options and information associated with the location marker.

[0379] In some embodiments, the device transmits (**1510**) a request for a reverse lookup of the current location of the user-moveable location marker on the map and receives information identifying the current location of the user-moveable location marker on the map. In some embodiments, the device transmits the request for the reverse lookup without user intervention at predetermined times (e.g., when the marker is initially placed on the map and after the marker has been moved on the map). In some embodiments, the device transmits the request for the reverse lookup in response to a user request (e.g., in response to detecting a finger tap gesture **1016** on location marker **1002-1** (FIG. 10A)). In some embodiments, UI **1000A** (FIG. 10A) or UI **1000B** (FIG. 10B) contains a reverse lookup icon (not shown) allowing the user to request a reverse lookup of the marker location.

[0380] While displaying the map and the user-moveable location marker, the device displays (**1512**) a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map. For example, UI **1000A** (FIG. 10A) includes a user selectable region **1004** for obtaining information associated with the marker **1002-1**. In some embodiments, the user-selectable region **1004** is denoted by a chevron (e.g., ">") and moves with the marker. In some embodiments, the display of user-selectable regions **1006** and **1004** is toggled on by a finger tap on the location marker **1002-1** and toggled off by a finger tap on region **1006**. In other embodiments, region **1006** is a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map

[0381] In response to detecting a third finger gesture on the user-selectable region for obtaining information, the display of the map and the user-moveable location marker is replaced (**1514**) with a display of a plurality of option icons. For example, in response to a third finger gesture **1010** on the user-selectable region **1004** (FIG. 10A), the device replaces the display of the map **5266** and the marker **1002-1** with a display of a plurality of option icons (e.g., icons **1024**, **1026**, **1028**, **1030**, **1032**, and **1034** in UI **1000B**, FIG. 10B). The plurality of option icons includes a first icon (add to book-

marks icon **1024**), a second icon (directions to here icon **1026**), and a third icon (directions from here icon **1028**) that are described in more detail below.

[0382] In response to detection of a finger gesture on the first icon, the display of the plurality of option icons is replaced (**1514**) with a display of a user interface for adding an entry to a set of bookmarked locations. The added entry corresponds to the current location of the user-moveable location marker on the map. For example, in UI **1000B** (FIG. **10B**), in response to detection of a finger gesture **1036** on the add to bookmarks icon **1024**, the display of the plurality of option icons is replaced with a display of a user interface (e.g., UI **1000E** FIG. **10E**) for adding an entry to a set of bookmarked locations. UI **1000E** may include a text input box for modifying the name of the location marker (“Dropped Pin”, FIG. **10E**) with a soft keyboard **5236**.

[0383] In some embodiments, adding the entry to the set of bookmarked locations includes displaying a sequence of graphical user interfaces responsive to user gestures for adding the entry to the set of bookmarked locations.

[0384] In response to detection of a finger gesture on the second icon, the display of the plurality of option icons is replaced (**1514**) with a display of a user interface for getting directions to the current location of the user-moveable location marker on the map from another location. For example, in response to a finger gesture **1038** (FIG. **10B**) on the directions to here icon **1026**, the display of the plurality of option icons is replaced with a display of a user interface UI **1000C** (FIG. **10C**) for getting directions to the location of the marker on the map. In UI **1000C** (FIG. **10C**), the area **5215** for entering the end point is automatically populated with the name of the location marker (e.g., “Dropped Pin” in FIG. **10C**). The user then merely has to enter the starting location and activate the route initiation icon **5227** (e.g., by a finger tap on the icon) to obtain directions to the current location of the user-moveable location marker on the map. In some embodiments, the device requests a reverse lookup to identify the current location of the marker.

[0385] In response to detection of a finger gesture on the third icon, the display of the plurality of option icons is replaced (**1514**) with a display of a user interface for getting directions from the current location of the user-moveable location marker on the map to another location. For example, in response to a finger gesture **1040** (FIG. **10B**) on the directions from here icon **1028**, the display of the plurality of option icons is replaced with a display of a user interface UI **1000D** (FIG. **10D**) for getting directions from the location of the marker on the map. In UI **1000D** (FIG. **10D**), the area **5213** for entering the start point is automatically populated with the name of the location marker (e.g., “Dropped Pin” in FIG. **10D**). The user then merely has to enter the ending location and activate the route initiation icon **5227** (e.g., by a finger tap on the icon) to obtain directions from the current location of the user-moveable location marker on the map. In some embodiments, the device requests a reverse lookup to identify the current location of the marker.

[0386] In some embodiments, the plurality of option icons include a fourth icon (remove location marker icon **1030**), wherein in response to detection of a finger gesture on the fourth icon, the user-moveable location marker is deleted. For example, in response to a finger gesture **1042** (FIG. **10B**) on the remove location marker icon **1030** (e.g. “Remove Pin”), the corresponding user-moveable location marker **1002-1** is deleted from the map **5266** (FIG. **10A**).

[0387] In some embodiments, the plurality of option icons include an icon for adding an entry to a list of contacts, the added entry including location information corresponding to the map location of the marker. For example, in response to a finger gesture **1044** (FIG. **10B**) on the create new contact icon **1032**, UI **1000B** is replaced with display of a user interface (or series of user interfaces) for adding an entry to a set of contacts, the added entry including location information corresponding to the location of the user-moveable location marker **1002-1** on the map **5266** (FIG. **10A**).

[0388] In some embodiments, the plurality of option icons include an icon for updating an entry in a list of contacts to include location information corresponding to the current location of the user-moveable location marker on the map. For example, in response to a finger gesture **1046** (FIG. **10B**) on the add to existing contact icon **1034**, UI **1000B** is replaced with display of a user interface (or series of user interfaces) for updating an entry in a set of contacts to include location information corresponding to the location of the user-moveable location marker **1002-1** on the map **5266** (FIG. **10A**).

[0389] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A method, comprising:

at a computing device with a touch screen display:

displaying a map application, wherein the map application is configured to display a map;

detecting a first finger gesture on an icon for adding a user-moveable location marker to the map;

displaying the user-moveable location marker on the map;

in response to detecting a second finger gesture on the user-moveable location marker, moving the user-moveable location marker on the map in accordance with the second finger gesture;

while displaying the map and the user-moveable location marker, displaying a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map;

in response to detecting a third finger gesture on the user-selectable region for obtaining information, replacing the display of the map and the user-moveable location marker with a display of a plurality of option icons, wherein the plurality of option icons include:

a first icon, wherein in response to detection of a finger gesture on the first icon, the display of the plurality of icons is replaced with a display of a user interface for adding an entry to a set of bookmarked locations, the added entry corresponding to the current location of the user-moveable location marker on the map;

a second icon, wherein in response to detection of a finger gesture on the second icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions to the current loca-

- tion of the user-moveable location marker on the map from another location; and
- a third icon, wherein in response to detection of a finger gesture on the third icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions from the current location of the user-moveable location marker on the map to another location.
2. The method of claim 1, wherein the icon for adding a user-moveable location marker to the map is located in a curled version of a map application interface.
3. The method of claim 1, wherein:
- the second finger gesture includes a finger contact area that moves on the touch screen, and
 - moving the user-moveable location marker on the map in accordance with the second finger gesture includes displaying the user-moveable location marker offset from the moving finger contact area during the second finger gesture.
4. The method of claim 3, wherein the user-moveable location marker is offset from the moving finger contact area such that a user's view of the user-moveable location marker is not obscured by the second finger gesture while moving the user-moveable location marker on the map in accordance with the second finger gesture.
5. The method of claim 1, wherein the plurality of option icons include a fourth icon, wherein in response to detection of a finger gesture on the fourth icon, the user-moveable location marker is deleted.
6. The method of claim 1, including displaying text identifying the current location of the user-moveable location marker on the map.
7. The method of claim 6, including transmitting a request for a reverse lookup of the current location of the user-moveable location marker on the map and receiving information identifying the current location of the user-moveable location marker on the map.
8. The method of claim 1, wherein adding the entry to the set of bookmarked locations includes displaying a sequence of graphical user interfaces responsive to user gestures for adding the entry to the set of bookmarked locations.
9. The method of claim 1, including adding an entry to a set of contacts, the added entry including location information corresponding to the map location of the marker.
10. The method of claim 1, including updating an entry in a set of contacts to include location information corresponding to the current location of the user-moveable location marker on the map.
11. A computing device, comprising:
- a touch screen display;
 - one or more processors;
 - memory; and
 - one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for:
 - displaying a map application, wherein the map application is configured to display a map;
 - detecting a first finger gesture on an icon for adding a user-moveable location marker to the map;
 - displaying the user-moveable location marker on the map;
 - in response to detecting a second finger gesture on the user-moveable location marker, moving the user-moveable location marker on the map in accordance with the second finger gesture;

- while displaying the map and the user-moveable location marker, displaying a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map;
 - in response to detecting a third finger gesture on the user-selectable region for obtaining information, replacing the display of the map and the user-moveable location marker with a display of a plurality of option icons, wherein the plurality of option icons include:
 - a first icon, wherein in response to detection of a finger gesture on the first icon, the display of the plurality of icons is replaced with a display of a user interface for adding an entry to a set of bookmarked locations, the added entry corresponding to the current location of the user-moveable location marker on the map;
 - a second icon, wherein in response to detection of a finger gesture on the second icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions to the current location of the user-moveable location marker on the map from another location; and
 - a third icon, wherein in response to detection of a finger gesture on the third icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions from the current location of the user-moveable location marker on the map to another location.
12. The device of claim 11, wherein the icon for adding a user-moveable location marker to the map is located in a curled version of a map application interface.
13. The device of claim 11, wherein:
- the second finger gesture includes a finger contact area that moves on the touch screen, and
 - moving the user-moveable location marker on the map in accordance with the second finger gesture includes displaying the user-moveable location marker offset from the moving finger contact area during the second finger gesture.
14. The device of claim 13, wherein the user-moveable location marker is offset from the moving finger contact area such that a user's view of the user-moveable location marker is not obscured by the second finger gesture while moving the user-moveable location marker on the map in accordance with the second finger gesture.
15. The device of claim 11, wherein the plurality of option icons include a fourth icon, wherein in response to detection of a finger gesture on the fourth icon, the user-moveable location marker is deleted.
16. The device of claim 11, including instructions for displaying text identifying the current location of the user-moveable location marker on the map.
17. The device of claim 16, including instructions for transmitting a request for a reverse lookup of the current location of the user-moveable location marker on the map and instructions for receiving information identifying the current location of the user-moveable location marker on the map.
18. The device of claim 11, wherein adding the entry to the set of bookmarked locations includes displaying a sequence of graphical user interfaces responsive to user gestures for adding the entry to the set of bookmarked locations.
19. The device of claim 11, including instructions for adding an entry to a set of contacts, the added entry including location information corresponding to the map location of the marker.

20. The device of claim **11**, including instructions for updating an entry in a set of contacts to include location information corresponding to the current location of the user-moveable location marker on the map.

21. A non-transitory computer readable storage medium having stored therein instructions, which when executed by a device with a touch screen display, cause the device to:

display a map application, wherein the map application is configured to display a map;

detect a first finger gesture on an icon for adding a user-moveable location marker to the map;

display the user-moveable location marker on the map;

in response to detecting a second finger gesture on the user-moveable location marker, move the user-moveable location marker on the map in accordance with the second finger gesture;

while displaying the map and the user-moveable location marker, display a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map;

in response to detecting a third finger gesture on the user-selectable region for obtaining information, replace the display of the map and the user-moveable location marker with a display of a plurality of option icons, wherein the plurality of option icons include:

a first icon, wherein in response to detection of a finger gesture on the first icon, the display of the plurality of icons is replaced with a display of a user interface for adding an entry to a set of bookmarked locations, the added entry corresponding to the current location of the user-moveable location marker on the map;

a second icon, wherein in response to detection of a finger gesture on the second icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions to the current location of the user-moveable location marker on the map from another location; and

a third icon, wherein in response to detection of a finger gesture on the third icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions from the current location of the user-moveable location marker on the map to another location.

22. The storage medium of claim **21**, wherein the icon for adding a user-moveable location marker to the map is located in a curled version of a map application interface.

23. The storage medium of claim **21**, wherein:

the second finger gesture includes a finger contact area that moves on the touch screen, and

moving the user-moveable location marker on the map in accordance with the second finger gesture includes displaying the user-moveable location marker offset from the moving finger contact area during the second finger gesture.

24. The storage medium of claim **23**, wherein the user-moveable location marker is offset from the moving finger contact area such that a user's view of the user-moveable location marker is not obscured by the second finger gesture while moving the user-moveable location marker on the map in accordance with the second finger gesture.

25. The storage medium of claim **21**, wherein the plurality of option icons include a fourth icon, wherein in response to detection of a finger gesture on the fourth icon, the user-moveable location marker is deleted.

26. The storage medium of claim **21**, including instructions which when executed cause the device to display text identifying the current location of the user-moveable location marker on the map.

27. The storage medium of claim **26**, including instructions which when executed cause the device to transmit a request for a reverse lookup of the current location of the user-moveable location marker on the map and receive information identifying the current location of the user-moveable location marker on the map.

28. The storage medium of claim **21**, wherein adding the entry to the set of bookmarked locations includes displaying a sequence of graphical user interfaces responsive to user gestures for adding the entry to the set of bookmarked locations.

29. The storage medium of claim **21**, including instructions which when executed cause the device to add an entry to a set of contacts, the added entry including location information corresponding to the map location of the marker.

30. The storage medium of claim **21**, including instructions which when executed cause the device to update an entry in a set of contacts to include location information corresponding to the current location of the user-moveable location marker on the map.

31. A graphical user interface on a device with a touch screen display, comprising:

a map displayed by a map application;

wherein:

a first finger gesture is detected on an icon for adding a user-moveable location marker to the map;

the user-moveable location marker is displayed on the map;

in response to detecting a second finger gesture on the user-moveable location marker, the user-moveable location marker is moved on the map in accordance with the second finger gesture;

while displaying the map and the user-moveable location marker, a user-selectable region for obtaining information associated with a current location of the user-moveable location marker on the map is displayed;

in response to detecting a third finger gesture on the user-selectable region for obtaining information, the display of the map and the user-moveable location marker is replaced with a display of a plurality of option icons, wherein the plurality of option icons include:

a first icon, wherein in response to detection of a finger gesture on the first icon, the display of the plurality of icons is replaced with a display of a user interface for adding an entry to a set of bookmarked locations, the added entry corresponding to the current location of the user-moveable location marker on the map;

a second icon, wherein in response to detection of a finger gesture on the second icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions to the current location of the user-moveable location marker on the map from another location; and

a third icon, wherein in response to detection of a finger gesture on the third icon, the display of the plurality of icons is replaced with a display of a user interface for getting directions from the current location of the user-moveable location marker on the map to another location.