




Fig. 1A
(Prior Art)




Fig. 1B
(Prior Art)





Fig. 2






Fig. 3B




Fig. 3C




Fig. 4




Fig. 5

600

fcn_call_split_data_dep_error

New Font Size

Message

Source

Reported by

Summary

Interface error	Chart	Stateflow	A function-call signal, originating at initiator 'fcn_call_split_data_dep_error'
● Parse Log	fcn_call_split_data_dep_error	Parse	
● Coders Log	fcn_call_split_data_dep_error	Coder	
● Make Log	fcn_call_split_data_dep_error	Make	

fcn_call_split_data_dep_error'Chart

Stateflow Interface Error: A function-call signal, originating at initiator 'fcn_call_split_data_dep_error/Chart/SFunction', is branched incorrectly. The function-call block 'fcn_call_split_data_dep_error/g', which is part of this branched function-call network, violates the following requirement: the block output signals may not be fed back directly to the initiator. Consider inserting a block to provide a delay on this feedback signal.

Open

Help

Close

Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10
(Prior Art)




Fig. 11




Fig. 12




Fig. 13
(Prior Art)




Fig. 14
(Prior Art)





Fig. 15
(Prior Art)

**Fig. 16**




Fig. 17




Fig. 18
(Prior Art)




Fig. 19A




Fig. 19B





Fig. 19C



2000

Function Block Parameters: Function - Call Group [X]

Function- Call Group

Group a Function-Call control signal with data signals and provide return values to the Function-Call initiator

Parameters

Function-call name

φ

Number of inputs

2

Signal return values and data types

{ 'b', -1 }

Has pre-execution blocks

0

2010

OK Cancel Help Apply

Fig. 20A

2030

Function Block Parameters: Function - Call Group - run 1 [X]

Function- Call Group

Group a Function-Call control signal with data signals and provide return values to the Function-Call initiator

Parameters

Function-call name

run_1

2032

Number of inputs

1

Signal return values and data types

{'y', -1}

☒ Has pre-execution blocks

2034

OK Cancel Help Apply

Fig. 20B





Fig fcn_call_parallel_h1_and_h2.mdl

Fig. 21

**Fig. 22**





Fig. 23

**Fig. 24**






Fig. 25

**Fig. 26**

***Fig. 27***




Fig. 28




Fig. 29





Fig. 30

***Fig. 31***

MULTI-THREADED SUBGRAPH EXECUTION CONTROL IN A GRAPHICAL MODELING ENVIRONMENT

RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application Ser. No. 61/121,747 filed Dec. 11, 2008, the contents of which are incorporated by reference herein in their entirety. This application is related to application Ser. No. _____, entitled "Subgraph Execution Control in a Graphical Modeling Environment," filed Dec. 9, 2009

BACKGROUND INFORMATION

[0002] Various classes of graphical models or graphical programming describe computations that can be performed on application specific computational hardware, such as a computer, microcontroller, field programmable gate array (FPGA), and custom hardware. Examples of graphical models can include time-based block diagrams such as those found within the Simulink® environment from the Math-Works, Inc. Natick Ma, discrete-event diagrams such as those found within the SimEvents® environment from the Math-Works, Inc. and data-flow diagrams. A common characteristic among these various forms of graphical models is that they define semantics on how to execute the diagram.

[0003] Historically, engineers and scientists have utilized graphical models in numerous scientific areas such as feed-back control theory and signal processing, to study, design, debug, and refine dynamic systems. Dynamic systems are systems whose behaviors change over time. Dynamic systems may be representative of many real-world systems, such as control systems. Graphical modeling has become common technique for designing models of dynamic systems because graphical modeling software packages provide sophisticated software platforms with a rich suite of support tools that makes the analysis and design of dynamic systems efficient, methodical, and cost-effective.

[0004] Graphical modeling environments can include one or more graphical models. These graphical models can be described by a graph consisting of nodes (often called blocks) connected by edges (often called lines or signals). The edges form dependencies between the nodes. The nodes generally describe computations, though it is also possible for the edges to have semantic meaning. The semantic behavior of the graphical model is different in each domain. For example, in time-based block diagrams edges represent signal quantities that vary with time (e.g., data signals) and the nodes are blocks representing dynamic systems (e.g., components of a controller). The signals may form a time-based dependency between blocks. In contrast, the semantic behavior in a discrete-event system may differ from the semantic behavior of the time-based model. For example, in a discrete-event system, the edges generally represent entity paths by which entities can travel from node to node. Each node in a discrete-event system may represent an action to perform on the entity. In a data flow diagram, nodes may represent operations. The edges may represent values and the nodes may be executed based upon data availability.

[0005] In the above classes of graphical models, it is possible to provide explicit execution control via a control edge connecting a control initiator with a node (or nodes) within a model. The controlled nodes are referred to as a subgraph. For example, Simulink provides function-call and action signals

which are used to explicitly control the execution of sub-systems or other models. In this existing system, function-call and action signals take precedence over the data signals. Existing techniques may provide desired operating characteristics for graphical models in some situations; however, in other situations models may not operate as desired. For example, data dependencies may be ignored when explicit execution control is used in conventional modeling environments.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate one or more embodiments of the invention and, together with the description, explain the invention. In the drawings,

[0007] FIG. 1A—illustrates a prior art graphical model that employs a conventional technique for explicitly controlling execution of subgraphs in a graphical model.

[0008] FIG. 1B—illustrates a prior art graphical model that employs a conventional technique for controlling execution of a portion of a model;

[0009] FIG. 2—illustrates an embodiment containing a graphical model that includes a Function-Call Split block, which creates a subgraph that is explicitly controlled while honoring data dependencies;

[0010] FIGS. 3A-3C—illustrate embodiments containing graphical models that include a Function-Call Split block, which creates a subgraph that is explicitly controlled while honoring data dependencies where the subgraph has a loop that is broken by latching an input of a function-call subsystem;

[0011] FIG. 4—illustrates the model of FIG. 3A where there is no need to break a loop within an explicitly controlled subgraph;

[0012] FIG. 5—illustrates an embodiment where a data dependency violation exists within an explicitly controlled subgraph;

[0013] FIG. 6—illustrates a user interface for displaying information about an error in the model of FIG. 5;

[0014] FIG. 7—illustrates an embodiment that performs supervisory control using explicit subgraph control of two separate subgraphs running at different rates;

[0015] FIG. 8—illustrates an embodiment that includes Function-Call Split blocks that can be configured to invoke a subgraph according to data dependencies and the ordering of the blocks within the subgraph is annotated on the blocks after analyzing the model;

[0016] FIG. 9—illustrates an embodiment that includes a Function-Call Split block where the ordering of the outgoing function-calls is annotated using numerical identifiers;

[0017] FIG. 10—illustrates a graphical model that employs a conventional technique for combining function-call control signals;

[0018] FIG. 11—illustrates an embodiment that includes a Function-Call Join block to predictably provide multiple control initiators to a subgraph;

[0019] FIG. 12—illustrates an embodiment that includes a Function-Call Split block that creates a subgraph which honors data dependencies and within the subgraph a Function-Call Join block is used to predictably provide multiple control initiators to a subgraph;

[0020] FIG. 13—illustrates a conventional technique that uses external function invocations;

[0021] FIG. 14—illustrates a conventional technique that uses external function invocations with an implicit input to a function-call subsystem;

[0022] FIG. 15—illustrates a conventional technique that uses external function invocations across subsystem boundaries;

[0023] FIG. 16—illustrates an exemplary embodiment of the invention that provides the ability to create components with control signal (e.g. function-call or action signal) inputs and outputs of the components;

[0024] FIG. 17—illustrates an exemplary technique for allowing a user to create and/or edit the signatures of a function-call subsystem signals;

[0025] FIG. 18—illustrates a conventional model that uses conventional implementations of function call subsystems;

[0026] FIG. 19A—illustrates an embodiment that uses function-call group and ungroup blocks to enable componentization of systems with a control signal crossing the systems boundaries;

[0027] FIG. 19B—illustrates an embodiment that uses function-call group and ungroup blocks to enable componentization of systems with multiple control signals crossing the systems boundaries;

[0028] FIGS. 19C-19E—illustrate embodiments that further provide examples of componentization in graphical models consistent with principles of the invention;

[0029] FIG. 20A—illustrates an embodiment of a Function-Call Group block dialog;

[0030] FIG. 20B—illustrates an embodiment of a Function-Call Group block dialog with 'Has pre-execution' blocks selected;

[0031] FIG. 21—illustrates an embodiment of a Function-Call Split block that invokes Function-Call Subsystems in parallel on new threads;

[0032] FIG. 22—illustrates an embodiment of a Function-Call Split block that invokes one of the Function-Call Subsystems on a new thread;

[0033] FIG. 23—illustrates an embodiment of a subgraphs that are explicitly controlled while honoring data dependencies and the subgraph consists of Function-Call Split block that invokes one of the Function-Call subsystems in another thread, where the another thread is synchronized with the main thread via a Function-Call Sync block;

[0034] FIG. 24—illustrates an embodiment of a chart making a function-call;

[0035] FIG. 25—illustrates an embodiment that includes subgraphs that are explicitly controlled while honoring data dependencies and where the subgraph consists of a Function-Call Split block that invokes one of the Function-Call subsystems in another thread, where the thread is then synchronized with the main thread via a Function-Call Sync block;

[0036] FIG. 26—illustrates an embodiment of a function-call subsystem from FIG. 25 containing source blocks that are executed when needed;

[0037] FIG. 27—illustrates an embodiment of a function-call subsystem from FIG. 25 containing sink blocks that are executed when needed;

[0038] FIG. 28—illustrates an embodiment of a continuous-time system that uses a spawn block to speed up execution by running transformations in parallel;

[0039] FIG. 29—illustrates an exemplary flow chart illustrating exemplary processing for implementing an embodiment of the invention;

[0040] FIG. 30—illustrates an exemplary computing architecture for implementing an embodiment of the invention; and

[0041] FIG. 31—illustrates an exemplary distributed processing architecture for implementing an embodiment of the invention.

DETAILED DESCRIPTION

[0042] Exemplary embodiments are discussed in connection with graphical models created and executed in the Simulink environment (hereinafter "Simulink"). Current or past versions of Simulink will be used to discuss conventional (prior art) techniques for providing execution control over portions of a graphical model. For example, Simulink 7.3 is one example of a conventional application that will be used to present existing techniques. A Simulink-based representation will be used for discussing novel techniques provided by aspects of the invention that provide explicit execution control over portions of a graphical model.

[0043] Control signals such as function-call or action signals found within Simulink's time-based block diagram environment are used to provide explicit execution control of a portion of a model. Explicitly controlled portions of a model may be referred to as subgraphs. Within a model, a subgraph is a subset of the blocks and the lines connected to the subset of blocks. With conventional modeling techniques, these control signals take precedence over data signals. FIG. 1A illustrates a graphical model that employs a conventional technique for explicitly controlling execution of subgraphs in a graphical model. The model of FIG. 1A was created using Simulink version 7.3 (R2009a). Model 100 represents a control system and can include components (blocks), such as chart 105, init 110, merge 115, plant 120, src 125, f 130, and g 135. In model 100, plant 120 is the entity being controlled (e.g. a car) and the other blocks in model 100 (e.g., chart 105, init 110, merge 115, f 130, and g 135) are used to control plant 120. In model 100, dashed lines, such as signal 140, are control signals, which are referred to as function-call signals within the Simulink 7.3 environment.

[0044] A control initiator is a block that uses a control signal to execute one or more destination blocks. For example, in Model 100 chart 105 is a control initiator, which can also be referred to as a function-call initiator, and is responsible for executing function-call subsystems, such as function-call subsystems represented by f 130 and g 135.

[0045] In model 100, solid lines, such as signal 145, represent numerical time-varying quantities and can be referred to as data signals. Data signals may represent inputs and outputs to dynamic systems defined by blocks in a model, such as model 100. In a time-based block diagram environment, blocks perform transformations on the data signals. Blocks not explicitly controlled by a control signal initiator, such as chart 105, execute according to time-based semantics, i.e. execute when they have a sample hit.

[0046] In model 100, chart 105 may be a Stateflow chart block that contains or implements a finite-state machine responsible for supervisory control of blocks init 110, f 130, and g 135. Chart 105 may run an init function-call subsystem, implemented via init 110, at start-up or when another condition is detected, such as an invalid input (u) to the plant (which may be conveyed to chart 105 via signal 150). In model 100, normal run-time activities of the controller are represented by the function-call subsystem blocks f 130 and g 135. Chart 105 runs init 110, f 130, and g 135 as defined by user-specific state

and control-flow logic within the state chart using the function-call control signals **140**, **149**, and **148**.

[0047] For example, chart **105** can run the function-call subsystems zero, one, or more times on every time step of model **100** by sending commands via the function-call control signals **140**, **149**, and **148** to run the function-call subsystems. These commands are realized by run-time functions (e.g. C++ class methods) on the function-call subsystems. Simulink 7.3 will ensure that the output of function of src **125** is executed prior to the output function of chart **105**. On a given time-step chart **105** may choose to run **f 130** and then immediately run the output and update methods of **g 135**. In this case, **f 130**, will see the previous value of output **s2 147** (because **g**'s output method has yet to be invoked). **g 135** will see the current value of output **s1 155** (because **f 130** was previously executed). The chart **105**, before invoking **f 130**, will compute signal **' 145**, where **'i** is an input to **f 130**. After executing **f 130**, the chart, **105** can immediately use signal, **'r 160** in the user-defined chart logic to make other decisions. The signal, **r 160**, is referred to as a return-value.

[0048] As illustrated in the example of model **100**, data dependencies implied by signals **s1 155** and **s2 147** are ignored in determining the order in which **f130** and **g135** execute—the control signal initiator blocks use the control signals to cause immediate execution of the subsystems **f 130** and **g 135**. Phrased another way, the execution order of subsystems **f 130** and **g 135** are not dictated by the data signals connecting them but instead by the explicit control signal invocations of Chart **105**.

[0049] The explicit control of subgraphs contrasts with conventional execution in a Simulink block diagram that follows data dependency order. Consider the example of FIG. 1B. Referring now to FIG. 1B, the Sine Wave block **180** always executes before the Gain block **181**, and Gain block **181** always executes before the Scope block **184**. The blocks in FIG. 1B are said to execute in the order of their data dependencies. Any delays in the reading of data during execution need to be introduced explicitly as shown in FIG. 1B where the block Gain **1 182** reads a delayed value of signal **s1**, where the delayed value of signal **s1** is produced using unit delay block **183**.

[0050] The behavior described in connection with FIG. 1B contrasts with the semantic defined by explicit execution control consistent with aspects of the invention. While the explicit execution control semantic is well-defined, it can result in unexpected behavior for users that are familiar with execution that is based upon data dependencies. In the case of explicit execution control, some signals experience delays even when no explicit Delay block was introduced in the model. This unexpected behavior can be especially difficult to trace when constructing large models consisting of many thousands of blocks. For example, it may be difficult for a user to understand when a given function-call subsystem is executing using current input signal values or delayed (previous value) input signal values when the user is working with conventional modeling environments. The phrase “data dependencies are not satisfied” is used herein to indicate situations and/or examples where a delay may be introduced as a result of explicit execution control.

[0051] Chart **105** may be generally referred to as a control initiator. A control initiator block has one or more control signal outputs that are used to explicitly invoke destination blocks. Referring back to model **100**, chart **105** has three control signal outputs, signal **140** to init **110**, signal **149** to **f**

130, and signal **148** to **g 135**. These control signals are referred to as function-call signals. Function-call signals are one form of a control signal. Simulink 7.3 also contains action signals which are control signals that come from a control initiator, which is either a Switch Case or If block. Concepts described herein can be extended to classes of signals discussed in connection with disclosed embodiments consistent with the principles of the invention.

[0052] While the behavior of Simulink 7.3 and other conventional types of graphical environments is well-defined, there may be a need to ensure data dependencies are satisfied during model execution, while also allowing for explicit execution control. To enable explicit execution control, while satisfying data dependencies, an exemplary embodiment employs a novel semantic via a Control Signal Split block. In general a Control Signal Split (or equivalently a Control Signal Branch block) block can accept a control-signal and then in turn execute one or more destination blocks. A Control Signal Split block can be realized in an embodiment as a Function-Call Split block.

[0053] A Function-Call Split block may be a block that accepts a function-call signal and splits (branches) it into two or more function-call signals. When a function-call invocation (message) is received at the input port to the Function-Call Split block, function-calls are initiated at all outputs. These resulting function-calls are executed in a manner such that data dependencies are satisfied. In another embodiment, a Function-Call Split block may be realized as an Action Split block that accepts an Action signal and splits (branches) the action signal into two or more action signals that invoke Action subsystems.

[0054] FIG. 2 illustrates an embodiment containing a graphical model that includes a Function-Call Split block, **245**, which creates a subgraph whose execution is explicitly controlled while honoring data dependencies. FIG. 2 illustrates model **200** that can include chart **205**, function call subsystems init **210**, **f 230** and **g 235**, src block **225**, merge block **215**, plant subsystem **220**, function-call loop break block **240** and Function-Call Split block **245**. In model **200**, **f 230**, **g 235** and the Function-call Loop Break block **240** form a subgraph where execution of the subgraph is explicitly controlled by the function-call signal **f 250** from the chart **205**. Within model **200**, two types of control signals may be defined, namely function-call signals and action signals. In model **200**, a control signal may define when subordinate blocks as identified by the subgraph are executed. In model **200**, a control initiator may initiate execution of the subgraph. By way of example, chart **205** is the control initiator in FIG. 2 (often referred to as a function-call initiator) and the signals connected to the output ports, **f** and **init** of chart **205** are control signals (of specific type function-call). In FIG. 2, there are two subgraphs, the init Function-call Subsystem that includes init **210** and the subgraph consisting of the Function-call Subsystems, **f 230**, **g 235**, and the Function-call Loop Break block **240**.

[0055] Function-call Loop Break block **240** can be realized in a variety of ways, such as via a Unit Delay or Memory block which outputs a prior value of the signal by maintaining state within the block. The Function-call Loop Break block **240** must run at the same rate as the other blocks in the subgraph. Another realization of the Function-call Loop Break block **240** can be realized by eliminating the need for

the Function-call Loop break block **240** and by providing a parameter on the Inport block of the function-call subsystem that allows feedback.

[0056] The Function-call Split block **245** ‘branches’ the function-call control signal connected to the output port **f** of the chart **205** into two respective signals, **g 255** and **f 260**. The Function-call Split block **245** can be configured to execute the out-going function-call control signals (in this case **f** and **g**) in any desired order based on a user specification. In FIG. 2, the Function-call Split block **245** executes **f 230** first and then **g 235** second. The Function-call Loop Break block **240** provides the Function-call Subsystem, **f 230** with the previous value of **s2** from **g 235**. If the Function-call Loop Break block **240** were not present, there would be an algebraic loop involving the two Function-call Subsystems, **f 230** and **g 235**. This would result in an error condition unless the algebraic conditions are solved using an algebraic loop solver.

[0057] FIG. 3A illustrates an embodiment containing a graphical model that includes a Function-Call Split block, **345**, which creates a subgraph whose execution is explicitly controlled while honoring data dependencies where the subgraph has a loop consisting of signals **s1** and **s2** where the loop is broken by latching the 3rd input of **330**. The latching is achieved by selecting the “Latch input for feedback signals of function-call subsystems outputs” parameter on the Inport block dialog of the Function-Call Subsystem, **f 330**. In the embodiment of FIG. 3A, the Function-Call subsystem, **f 330**, has indicated that the 3rd input (**In3**) is latched, meaning that **f 330** specified that it is using the prior value of the signal feedback from function-call subsystem **g 335**. The specification is done by opening the Function-call subsystem, **f 330** and setting the “Latch input for feedback signals of function-call subsystems” on the Inport block, **In3**. In FIG. 3, dialog window **344** may be used to specify the latch input. Specifying the loop break property on the subordinate blocks (in this case, **f 330**) has the advantage over the Loop break blocks in that documentation of the system is improved. For example, in FIG. 3A it may be clear to a model designer that **f 330** is using a latched value at input port **3** from the prior execution of **g 335** via signal **s2** because of the annotation on **330**.

[0058] An embodiment illustrated in FIG. 3B can represent an improvement over the pattern explored in FIG. 3A, namely that the Function-Call Split block can be entirely subsumed into the functionality of the Initiator. FIG. 3B illustrates how the Chart **305** and the Split block **345**, of FIG. 3A, are subsumed into the single hierarchical level of the model **360**. Further, as illustrated in FIG. 3C, the entire Chart **305** can be programmed to subsume the functionality of the Split block **345** without introducing an explicit Split block shown in the model. For example, and referring to FIG. 3C, the fact that **f** executes before **g** is indicated by the number **1** near the **f** port **370** of the Chart and the number **2** near the **g** port **375** of the Chart. The representation of FIG. 3C may represent an improvement that allows **f** and **g** to execute in accordance to their data dependencies. The example of FIGS. 3A, B, and C contrast with the example shown in FIG. 1A where the **f 130** and **g 135** could execute in any arbitrary order dictated by the Chart.

[0059] Embodiments can return processed results from all or any subgraphs connected to a Function-Call Split block back to the Initiator of the function-call control signal. This is illustrated in FIG. 4 where **f 430** returns a signal **r** to the Chart **405**. Use of signals, such as **r**, does not require the use of a loop break block because there is no implied delay in the

signal. This concept can be extended to return a value from **g 435** as well. The Chart can then use these two values to control the Plant.

[0060] In certain situations, a conflict may be created between explicit subgraph execution control and execution ordering determined by data dependencies. When this situation occurs, an error may be produced as shown in FIG. 5 at chart **405** via the shaded fill pattern. The error may also cause an error log to be produced and displayed via a user interface. An exemplary error log that can accompany the graphically depicted error of FIG. 5 is illustrated in FIG. 6 via window **600**. If a user were to specify on the Function-Call Split block that the right function-call output executes before the bottom function-call output (with dot showing next to the right function-call output), then data dependencies would be satisfied because the Function-Call Subsystem, **g** would execute before the Function-Call Subsystem, **f** and the model would execute without error.

[0061] The need for explicit execution control of subgraphs arises in many situations where explicit ordering (often referred to as sequencing or scheduling) of the subgraphs enables supervisory control. For example, one subgraph may represent activities to be performed at initialization and another subgraph may represent run-time behavior. In the example of FIG. 3A, the initialization subgraph defined by the init Function-Call Subsystem is executed when the system starts up or is reset while running. Within a subgraph that is explicitly controlled, it may further be desired that data dependencies are satisfied ensuring each block within the subgraph is operating on current (e.g., up-to-date) information. Referring back to FIG. 3A, the subgraph starting at the Function-Call Split block, **345** represent run-time dynamics that control the plant **320** and within this subgraph, data dependencies are satisfied.

[0062] Explicit control of subgraphs can provide at least two capabilities for the model designer:

- (1) modeling of systems where there needs to be explicit scheduling of subsystems by elements of a block-diagram, which can be referred to as supervisory control, and
- (2) modeling of systems where certain block diagram elements need to perform auxiliary intermediate computations that are needed for performing their overall computation, which can be referred to as external function invocation.

[0063] These capabilities are provided by explicit control of subgraphs can used separately or together as shown in FIG. 3A. Referring back to FIG. 3A, based upon the state of the system, chart **305** invokes either the initialization function-call subsystem, **init 310**, or the run-time logic consisting of the subgraph consisting of the Function-Call Split block **345**, and **f 330** and **g 335** Function-Call Subsystems. This type of decision making can be referred to as supervisory control. In addition the chart uses the signal **r 350**, computed by the function-call subsystem **f 330**. In this context the chart is making an external function invocation and using **r 350** for further processing.

[0064] FIG. 7 illustrates an embodiment that performs supervisory control using explicit subgraph control of two separate subgraphs running at different rates. In FIG. 7, there are two separate charts, namely chart **710** and chart **720**, responsible for supervisory control of two separate subgraphs, subgraph **730** and subgraph **740**, respectively. In an embodiment, Charts **710** and **720** can further produce periodic signals. In this figure, the 1 m-sec (one millisecond) chart

710 produces a periodic signal at its first output port **715**. This signal is transformed by blocks and used elsewhere in the model.

[0065] Similarly the 2 m-sec chart **720** produces a periodic signal at its first output port **725** which is used elsewhere in the model. The second output port **717** of chart **710** is then connected to subgraph **730** consisting of three blocks. The 1 m-sec chart **710** on every (1 m-sec) time step decides if it should execute subgraph **730**. When chart **710** executes subgraph **730**, all three blocks in subgraph **730** execute while satisfying data dependencies, i.e., the 3 blocks of subgraph **730** are evaluated left to right because of data dependencies. In subgraph **730**, the size of the execution control split block (in this case a Function-Call Split block **735**) has been reduced to a very small dot representing a branch-point. Likewise, the 2 m-sec chart **720** executes the subgraph **740** connected to its second output port **727** based on logic, which may or may not run the subgraph **740** on the 2 m-sec time-step. A Rate Transition block **750** is used to convert the data from the 2 m-sec task to the 1 m-sec task. The Function-Call Split block **735** decides the order in which the subordinate blocks are executed.

[0066] FIG. 8 illustrates an embodiment **800** that includes Function-Call Split blocks **810A**, **B**, **C** that can be configured to invoke a subgraph according to data dependencies and the ordering of the blocks within the subgraph is annotated on the blocks after analyzing the model. FIG. 8 can include function call generator **805**, Function-Call Split block **810A**, **B**, and **C**, sine wave generator **815**, function call subsystems **820**, **825**, **830** and **835**, and output **840**. Subsystems **820**, **825**, **830** and **835** may be subordinate function-call subsystems in an embodiment. These subsystems can optionally be annotated using a nomenclature, such as “B#”, where “#” is an integer indicating the execution ordering sequence for the subsystems. For example, in FIG. 8, subsystem **820** may execute first, subsystem **825** may execute second, subsystem **830** may execute third and subsystem **835** may execute fourth, or last.

[0067] The ordering of how subsystems execute can be represented using alternative graphical techniques. An example of an alternative technique for representing an explicit ordering for subsystem execution is illustrated in FIG. 9.

[0068] FIG. 9 includes Function-Call Split block **905** that receives signal **906** from function call generator **904**. Function-call split block **905** includes two output signals identified using “1” for signal **907A** that goes to subsystem **920** and “2” for signal **907B** that goes to subsystem **925**. In FIG. 9, Function-Call Split block **905** includes a graphical representation in the form of a dot proximate to where signal **907A** intersects the border of Function-Call Split block **905**. The dot indicates which function-call branch is executed first, namely the one for signal **907A**. The “1” next to the signal indicates Function-Call Subsystem **h1** runs first and the “2” next to the other signal indicates Function-Call Subsystem **h2** runs second. When cascaded Function-Call Split blocks are used for splitting a function-call signal to call more than two function-call subsystems, users may also choose to show absolute execution sequence (like “1”, “2”, “3” . . .) or hierarchical execution sequence (such as “1.1.2”, “1.2.1”). Users can manually insert a Function-Call Split block to branch a function-call signal, or can simply branch a function-call signal and a Function-Call Split block will be automatically added.

[0069] In FIG. 9 a round subgraph block is used and represents one exemplary technique for graphically representing

functionality associated with subgraph control. Other embodiments can use other techniques (e.g., shapes) for representing subgraph blocks or subgraph functionality. For example, a rectangular block or another shape block could be used. Furthermore, if there are no options, a simple branch (i.e., no block) may be used to represent the concept of a Function-Call Split. Similarly, an implementation may include more than two output signals, i.e. it is possible to split a function-call into 3 function-call signals by either cascading two Function-Call Split blocks or providing a split block that has 3 outputs.

[0070] If a user were to instruct the Function-Call Split block **905** to execute its branches according to data dependencies in this model, there would be ambiguities because there is no dependency between **h1** and **h2**. In this case an error message would be generated indicating that insufficient data dependencies exist in model **900** to ensure a unique execution ordering. If there are no ambiguities and a unique ordering can be found, as in FIG. 8, choosing a branch ordering based on data dependency can result in deterministic execution sequencing.

[0071] A Control Signal Split block can be referred to using different names according to environments in which the block is used and/or according to particular functionality implemented using the block. For example, in a Simulink environment, when used with Function-Call signals, the block may be referred to as the Function-Call Split block, Function-Call Branch block, Function-Call Branch Point block, Function-Call Split Junction block, Function-Call Splitter, etc. When used with Simulink’s action signals the Control Signal Split block may be referred to as the Action Branch Point block, Action Branch block, Action Split block, Action Split Junction block, Action Splitter, etc.

[0072] A subgraph loop break block can also be referred to using different names. For example, in a Simulink environment, when used with Function-Call signals, it may be referred to as the Function-Call Loop Break block, when used with action signals (similar to function-call signals), it may be referred to as the Action Loop Break block. Alternatively, the term loop break may be replaced with “memory” or “delay” or “latch”. It should be recognized that several different names can be used to describe this block. The property of breaking loops can also be realized as a parameter (property) of the subordinate blocks that are executed (run) by the control initiator.

[0073] A conventional technique for joining control signals together that can produce unexpected results may be realized using Simulink 7.3 (R2009a). For example, Simulink 7.3 provides a Mux block as shown in FIG. 10. In FIG. 10 function-calls are combined into a wide function-call signal **1020** that includes signals **f** and **g**. The wide function call signal is used to invoke the Function-Call Subsystem **1015**. The wide function-call signal **1020** enables either Chart1 **1005** or Chart2 **1010** to run the Function-Call Subsystem **1015**.

[0074] A potential downside of the implementation of FIG. 10 is that the ordering of the control initiators (Chart1 **1005** and Chart2 **1010**) is not clearly demarcated to a user. The semantics of Simulink 7.3 indicate that either Chart1 **1005** or Chart2 **1010** can be first in the sorted-list. The sorted-list of blocks is generated when analyzing the model by using data dependencies among the blocks. The sorted-list is then used to create block function execution lists that are used to run the model. Execution lists may also be referred to as block method execution lists because blocks are often implemented

using object oriented programming techniques where the functions are methods of a class. Switching the ordering of Chart1 1005 and Chart2 1010 in the sorted-list will change the result, or answer when FCSS 1015 has blocks with state inside it. Since there are no data dependencies between Chart1 1005 and Chart2 1010, the order is inferred from block priorities when block priorities are specified; otherwise, the block names are used. Thus, seemingly insignificant changes to a block (e.g., a new block name) can produce significant changes in a result, or answer, produced by a model.

[0075] An exemplary embodiment of the invention can overcome limitations, such as those associated with the Simulink 7.3 embodiment of FIG. 10. For example, an embodiment of the invention can use a control signal join block to predictably provide multiple control initiators to a subgraph. An alternative name for the Function-Call Join block would be a Function-Call Sequence block. For example, a Control Signal Join block is used when it is desirable to have multiple control initiators of a given subgraph (or single block). A Control Signal Join block specifies the ordering when two or more invocations of the Join block are initiated on the same time step.

[0076] For example, and referring to FIG. 11, the Function-Call Join block 1120 can include a dialog window 1130 that can be used to display information regarding operation of join block 1120. For example, dialog window 1130 can display information indicating that join block 1120 uses an ordering that is either left-to-right, right-to-left, or specified. When specified is selected in dialog window 1130, a set of indices corresponding to the input ports are provided giving the desired ordering. In the embodiment illustrated in FIG. 11, left-to-right ordering has been selected.

[0077] Referring to FIG. 11, a left-to-right ordering means that Chart2 1110 must be placed before Chart1 1105 in the sorted list. The sorted list may be a data structure that is used by a simulation or code generation engine to generate execution lists. This ensures that on any given time step, if both Chart1 1105 and Chart2 1110 are invoking subgraph 1115, then Chart2 1110 will come first. Within the Function-Call Subsystem, FCSS, 1115, the user can add logic that makes decisions based on which specific initiator invoked the function-call subsystem. For example, if Chart1 1105 invoked FCSS, 1115 then one action could be taken otherwise if Chart2, 1110 invoked FCSS 1115, then another action could be taken.

[0078] The Function-Call Join block 1120 is useful for handling a subgraph created by a Function-Call Split block. In FIG. 12, model 1200 includes a chart 1205 that initiates execution of the subgraph defined by the Function-Call Split block 1225, Function-Call Subsystems, f 1230, g 1235, h 1250, Merge block 1245, and the Function-Call Join block 1240. Within the subgraph, both Function-Call Subsystems f 1230 and g 1235 use the Function-Call Subsystem h 1250. Both f 1230 and g 1235 provide an input, In1 to Function-Call Subsystem h 1250 via a Merge block 1245. The Function-Call subsystem f 1230 uses the result of calling h 1250 during its processing and the Function-Call Subsystem g 1235 invokes h 1250 to produce the final answer of the subgraph which is provided to the plant 1220 via the Merge block 1215. As before, the chart 1205 can choose to either run the init (initialization) Function-Call Subsystem 1210, typically at system startup, or run the subgraph by invoking a function-call on f 1230.

[0079] The Function-Call Join block (or generally a Control Signal Join) block output is either connected to a subgraph being explicitly controlled as in FIG. 11 or it can be connected to another Join block. The cascading of join blocks in effect produces a network of join blocks that result in one join operation.

[0080] Conventional techniques may infer function-call signatures from a graphical diagram. FIG. 13 illustrates a conventional technique using Simulink 7.3 external function invocations.

[0081] In FIG. 13, chart 1305 invokes the function-call subsystem 1310 with Inputs 1320 and receives the results of the computation via result signal 1325 for immediate use during the time-step. The construct illustrated in FIG. 13, when used with many input signals and result signals, produces a diagram that is difficult for users to understand and/or follow. Furthermore, the analysis of the model 1300 requires that all blocks be available to a compiler used to execute the model. This prevents a user from componentizing (or partitioning) the model into two independent parts, one consisting of the Chart 1305 and the other consisting of the Function-Call Subsystem, 1310.

[0082] Referring to FIG. 14, consisting of a conventional technique for external function invocations, the function-call subsystem f 1420 has two inputs—one from the initiator function-call subsystem, 11405 and the other from the Gain block, G 1415. The function-call itself, therefore, has two inputs, namely signal 1429 and signal 1430. Similarly, the function-call has one return value (result of computation) from f 1420 back to the Initiator 1405 via signal 1435. The implications of this signature are two fold:

[0083] 1. During simulation, before the invocation of the function-call subsystem f 1420 by the initiator 11405 both inputs need to be ready. This implies that G 1415 needs to execute prior to 11405

[0084] 2. When code is automatically generated from the model, the function generated for f 1420 will have two inputs and one return value.

[0085] In FIG. 14, the signature of the function-call is implied by the connectivity of model 1400 and is derived during the compilation process. For example, this process is used in Simulink 7.3 and earlier versions of Simulink.

[0086] Approaches to extracting the signature of the function-call, such as is shown in FIG. 14, does not scale to complex systems where different components of a system may be modeled with only knowledge of the interfaces of systems they interact with. By way of example, consider FIG. 15 illustrating a conventional technique using external function invocations that includes model 1500, identified as TOP and subsystems A 1510 and B 1530 which we'd like to make components

[0087] Model 1500 uses (references) two separate subsystems, namely subsystem A 1510 and subsystem B 1530. We'd like to make A 1510 and B 1530 components that can be independently analyzed (compiled for execution). In Simulink 7.3, components may be referred to as Model Reference blocks. In general componentization lets a user define reusable model components that can be compiled independently of their use. For example, if 1510 and 1530 were a components (Model Reference blocks), 1510 may be compiled independent of 1530. However, in conventional environments components cannot be created that have control

signals such as the function-call signal **1535** cross system boundaries. In some embodiments, a component may represent a model.

[0088] By way of example, FIG. 15 may illustrate an embodiment configured to depict three separate component models, one for the TOP, one for the A **1510**, and one for B **1530**. If this were the case, then it would be possible to independently open and execute A **1510** or to use model A **1510** from another model. Therefore, when constructing model A **1510**, it should be possible to build model A **1510** without knowing the contents of model B **1530** or how TOP (model **1500**) might be using model A **1510**. This workflow may imply two things:

[0089] 1. The builder of model A **1510** needs to be able to capture information regarding signals marked a **1540**, b **1550**, and c **1545** in model A **1510** because signals a **1540**, b **1550**, and c **1545** all constitute the signature of the function-call invoked in model B **1530**.

[0090] 2. The builder of model B **1530** needs to be able to build the function-call subsystem without knowing the contents of model A **1510**.

[0091] To satisfy 1 and 2 above, builders of models A **1510** and B **1530** each need a mechanism (or a contract) for capturing the signature of the function-call the two models share.

[0092] FIG. 16 illustrates an exemplary embodiment of the invention that provides the ability to create components with control signal (e.g. function-call or action signal) inputs and outputs of the components. FIG. 16 produces the same answer as FIG. 15. However, a difference between FIG. 15 and FIG. 16 is that FIG. 16 has componentized the subsystem A **1510** into Model Reference component A **1610** as indicated by the solid triangles in the corners of the model block. Similarly, FIG. 16 has componentized the subsystem B **1530** into Model Reference component B **1630**.

[0093] 1. In model A **1610**, the builder will have the ability to produce a single signal **1650** that includes the invocation signal of the function call, the input arguments from the initiator of the function-call and the return values (results of processing) of the function-call. This is referred to in general as subgraph control signals with input and output arguments, further illustrated in FIG. 16. In contrast, conventional techniques express each function call as a separate signal.

[0094] 2. In model B **1630**, the builder will have the ability to capture the input arguments and return values expected from the initiator in a structured form. One structured form could be a table which corresponds to a Subgraph Control Signal Class from which objects describing the signature are created, further illustrated in FIG. 16.

[0095] 3. In model A **1610**, the builder will have the ability to capture the fact that gain G **1620** is an implicit input to the function-call invoked from A **1610**. One way of capturing this information graphically is shown in the Subgraph Control Signals with Input and Output arguments illustrated in FIG. 16 via the Add Input **1660** Marshal block.

[0096] The exemplary mechanisms listed above facilitate the following:

[0097] 1. Models A **1610** and model B **1630** can be compiled in isolation and a user can generate code for one model without the presence of the other.

[0098] 2. The execution order of blocks in model A **1610** can be determined without the presence of Model B **1630**.

[0099] 3. When Model A **1610** and model B **1630** are connected together, a user can easily check that the contract for the function-call is met by both model A **1610** and model B **1630** because the signatures of the function-calls are specified at both models.

[0100] 4. The builders of model A **1610** and model B **1630** can build their models in a modular fashion.

[0101] FIG. 17 illustrates an exemplary technique for allowing a user to create and/or edit the signatures of a function-call subsystem signal such as **1650**. For example, a function-call subsystem **1705** may be associated with a dialog window **1750** that allows a user to input information associated with function-call subsystem **1705** which represents the input value a and output value b of the function-call subsystem **1625** of FIG. 16.

[0102] Exemplary embodiments can use Control Signal Group and Control Signal Ungroup blocks to allow models to be decomposed into separate units that can be independently compiled and/or reused. For example, a model may include control signals that cross boundaries of subsystems in the model. The model may use control signal group blocks or control signal ungroup blocks along with input and/or output data signals to provide independent control to respective subsystems in the model. The use of control signal group and/or ungroup blocks may allow the subsystems to be independently compiled and reused. The use of control signal group and ungroup blocks can provide models with the capability to have control signals cross hierarchical boundaries of the model, enable parallel compilation of components (e.g., subsystems) in the model, allow for independent verification of components of the model and provide users with improved development workflows (e.g., when many people are working on a model).

[0103] FIG. 18 illustrates a conventional model that uses function call subsystems. In FIG. 18, model **1810**, named Top, consists of two subsystems, SYS1 **1820** and SYS2 **1840**. SYS1 **1820** contains a state chart, Chart1 **1822**, that invokes a Function-Call Subsystem, FCSS **1850** in SYS2 **1840** via the function-call control signal, f **1832**. SYS1 **1820** also contains a Sine Wave block **1824** and a Gain block **1826**. Because the output signal, c **1828**, of the Gain block **1826** is an input to the Function-Call Subsystem, FCSS **1850**, the gain must be computed before Chart1 **1830** is executed because Chart1 is responsible for executing FCSS **1850** and FCSS has a data dependency on c **1828**, which is computed by the Gain block, **1826** using the sine wave value **1824**. Thus, to sort SYS1 **1820**, we need to know the contents of SYS2 **1840** and how SYS2 **1840** is using the signal, c **1828**. Had SYS2 **1840** used the signal c **1828** (its 3rd input) elsewhere and not by the FCSS **1850**, then Sine Wave **1824** and Gain **1826** could be executed before or after Chart1 **1830** because there is no execution (data) dependency in this case.

[0104] However, in FIG. 18, an execution dependency requires that the Sine Wave **1824** and Gain **1826** execute before Chart1 **1830** is executed. The contents of the Chart1 **1830** consist of a single state that produces 'a' which is set to x+2, where x is an internal state of Chart1 **1830** and is initialized to 0 by the chart. After computing a, Chart1 **1830** continues to execute the Function Call Subsystem, FCSS **1850**, by invoking it via the Function-Call control signal, f via the f statement. FCSS **1850** then transforms the signal a (which

will be 2 on the first time step), via the Lookup Table (2-D) **1852** and provides this transformed signal to the 1st Output block **1854** labeled b. FCSS **1850** then transforms this signal (b) again using the Discrete Zero-Pole block **1858** and provides this signal to the 2nd Output block **1856** labeled out.

[0105] After FCSS **1850** finishes executing, execution control is returned to Chart1 **1830** where the transformed signal, b, is saved by Chart1 **1830** in its internal state, x via the x=b statement. The direct feed-through bit on b was cleared because it is a return value from the invoked Function-Call subsystem, FCSS **1850**. Therefore, to generate the correct sorted list and block method execution order, the contents of SYS2 **1850** are also needed to determine which signal are return values. After SYS1 **1820** finishes executing, SYS2 **1840** executes. Since FCSS **1850** is not directly executed by SYS2 **1840** (its execution initiator is Chart1 **1830** which already ran), the only other blocks in SYS2 **1840** which need to be evaluated is the Scope block **1842** which plots the value of out computed by Chart1 **1830** via the FCSS **1850** invocation. This completes the execution of the first time step for the model **1810**. This process continues with time advancing until the desired stop time is reached.

[0106] FIG. 19A illustrates an embodiment that uses function-call group and ungroup blocks to enable componentization of systems with a control signal crossing the systems boundaries. In FIG. 19A, the system of FIG. 18 is implemented in an embodiment of the invention that uses function-call group blocks and function-call ungroup blocks. The implementation of FIG. 19A employs a technique referred to as componentization (e.g., model referencing) to simplify representing the system to a user. For example, and referring to FIG. 19A, model TOP **1902** can include two subsystem. For example, one subsystem can be represented as SYS1 **1904** using a Model Reference block that can be compiled and/or analyzed without knowledge of the contents of SYS2 **1930**, another Model Reference block, and vice versa. For example, if a user were to right-click on the f-group signal **1922** or **1932** or the signal **1915** connecting SYS1 to SYS2, the user could inspect the contents of the signal and the contents would show that the signal is a bundled signal consisting of a function-call control signal originating at **1906** and terminating at **1940** with data input signals a **1910** and c **1916** and return value signal b, **1944**. This inspection could be shown either textually or graphically in a dialog.

[0107] SYS1 **1904** includes Chart1 **1908**, which is implemented using logic similar to that of the Chart1 **1830** in FIG. 18. The Function-Call control signal, f **1906** is provided for a Function-Call Group block **1918** along with the Function-Call input data signal, a **1910**. The output of the Gain block **1914**, c **1916**, is also provided to the Function-Call Group block **1918**. The Function-Call Group block **1918** can be configured to specify the return values and signal attributes (data type, dimensions, sampling modes, etc.) such as their data type as show in FIG. 20A.

[0108] Referring now to FIG. 20A, dialog **2000** may include one or more fields **2010** in which a user can specify signal values, signal attributes for the signals, etc. In an embodiment, dialog **2000** may allow users to specify signal values and signal attributes using MATLAB cell syntax. For example, the ith element of a cell array and the data type for the respective return value signal is the i+1th element. In FIG. 20A, a user may have specified that the data type is inherited, meaning that the signal attributes will be back inherited from the Chart1 input. Alternatively, the properties of the Function-

Call Proxy and Function-Call Proxy Adaptors could be specified textually using an object-oriented syntax such as MATLAB's Class system.

[0109] Referring now to FIG. 19A, at SYS1 **1904** in isolation (without knowledge of the contents of SYS2 **1930**) the model of SYS1 can be analyzed to identify all information about the function-call f **1906**, initiated by the Chart1 **1908** to enable independent compilation. It may be known that the output signal, a **1910**, from the Chart1 **1908** is a function-call input. In addition, it may be known that data signal c **1916**, produced by the Gain block **1914**, is an implicit input to the same function-call. Moreover, it may be known that input b **1920** to the Chart1 **1908** is a return value data signal from the same function-call. This information ensures the compilation process of SYS1 **1904** will place the Sine Wave block **1912** and Gain block **1914** before Chart1 **1908**. The compilation process will also clear the direct feed through of the input port, b, of the Chart1 **1908** because b is a function-call return value. The bundled signal created by the Function-Call group **1918** is passed to the 1st Output block **1922**, named f-group.

[0110] In Top/SYS2 **1930** the first input port **1932** is connected to a Function-Call Ungroup block **1934**. Block **1934** unbundles the f-group signal and produces function-call control signal **1940** used to invoke the Function-Call Subsystem, FCSS **1942**. Block **1934** also unbundles the signals a **1938** and c **1942**, which are also provided to FCSS **1942**. Block **1934** may be associated with a dialog to allow users to enter information associated with block **1934**. For example, a dialog for block **1934** may be similar to dialog **2000** that is associated Function-Call Group block **1918**. A dialog window for block **1942** may allow a user to define that there is one return value from the Function-Call Subsystem, FCSS **1942**, labeled, b **1944**. Based on this information, we can compile SYS2 **1930** can be compiled without knowledge of any other parts of the model.

[0111] The embodiment of FIG. 19A makes use of explicit signatures to ensure that users can compile components with control signal inputs and outputs without having knowledge of the control signal sources or destinations outside of the component being compiled. This enables componentization, parallel compilation, independent development and testing of the components. An additional capability provided by control signal inputs and outputs such as the function-call control signal input SYS1 and function-call control signal output of SYS2 is the ability to have multiple function-call inputs and outputs.

[0112] FIG. 19B, includes two componentized systems, SYS_A **1961** and SYS_B **1967** (Model Reference blocks in Simulink) used with model **1961**. SYS_A **1961** is invoking two entry points on SYS_B **1967**, the init entry point **1962** and the run1 entry point **1963** via function-call grouped signals output from function group blocks **1964** and **1965**, respectively. SYS_A/chart **1954** initiates execution of either the init block **1964** or run1 block **1965** on any given time step. SYS_A **1961** illustrates the ability to have multiple function-call control signals from a chart and the ability to Merge (map to same memory location) the return values from the invoked function-call subsystems.

[0113] FIG. 20B illustrates a dialog window that can be used with, for example, Function-Call Group—run1 (block **1965**). Dialog **2030** includes fields **2032** and a check box **2034** for 'Has pre-execution blocks'. When check box **2034** is selected, the selection indicates that before the run1 function-call can be invoked, some (unknown) set of blocks has to be

executed before the control signal initiator (in this case **1966**) because they are feeding the function-call subsystem being executed. To ensure the pre-execution blocks run, SYS_A **1961** issues a run1_pre_execute 'hidden' function-call (message) via the run1 f-group signal before running the Chart **1966**.

[0114] Referring back to FIG. 19B, Top/SYS_B **1967**, includes function-call ungroup blocks **1968** and **1969** used to unbundle the function-call control signal and the data signals. The Function-Call Subsystem, run1 **1970**, has an A/D block **1971** feeding it. To ensure correct results from SYS_B **1967**, A/D block **1971** needs to run before run1 **1970** is run. To achieve this, SYS_B **1967** creates a 'hidden' function-call input that can conceptually be part of the run1 f-group but with name run1_pre_execute().

[0115] In the embodiment of FIG. 19B, any component providing a grouped function-call signal must run this entry point. When compiling the Top system **1960**, the signatures of the signals between the components can be observed to detect mismatches. For example, if the Top/SYS_A/Function-Call Group—run1 block **1965** did not check the 'Has pre-execution blocks' checkbox, a signature match would have been detected during compilation of Top **1960** and an error would be produced.

[0116] The block names Function-Call Group and Function-Call Ungroup are used convey that the blocks bundle signals together and then unbundle the signals, respectively. An alternative naming scheme would be to use the terms Function-Call Proxy and Function-Call Proxy Adaptor as shown in FIG. 19C.

[0117] FIG. 19C is similar to FIG. 19A, and includes renamed blocks. Generally, these blocks can be referred to as Control Signal Proxy and Control Signal Proxy Adaptor blocks. The basic functionality of these blocks may remain the same. For example, in FIG. 19C, the Function-Call Proxy block **1974** creates a bundled control signal labeled f-proxy **1975**. The signal line is displayed using a contrasting line style to indicate the signal is a bundled control signal. If a user were to inspect the signal either textually or graphically using a dialog box, the user would see the bundled signal contains a function-call signal with a first input signal, a second implicit input signal c, and a return value signal, b. The dialogs of the Function-Call Proxy and Function-Call Unproxy block may be similar to FIG. 20A and FIG. 20B.

[0118] The Function-Call Proxy blocks and Function-Call Proxy Adaptor blocks need not have the same names in the signals. For example, in FIG. 19C, the signal inspection dialog **1973** shows that the f-proxy signal has elements named a, b, and c. Similarly TOP/SYS2 **1976** is defined with signals a, b, and c. Alternatively, different signal names could have been specified in TOP/SYS2 **1976** for the Function-Call Adaptor **1977** and/or the Function-Call Subsystem, FCSS **1978** as long as the signal attributes (data types, dimension, etc.) are consistent the model would be correctly defined and would execute.

[0119] It should be recognized that the Function-Call Proxy (or equivalently Function-Call Group) block is a form of Marshal block **1660** of FIG. 16. Both the Marshal and Function-Call Proxy block are used to create a bundled signal. Signal **1650** of FIG. 16 is a bundle that consists of a function-call signal, an input 'a' and a return value signal 'b'. signal f-proxy **1975** of FIG. 19C has a similar signature and they are effectively the same when Marshal block **1660** is used. The overall inputs the function-call subsystems, F **1630** of FIG. 16

and FCSS of FIG. 19C have the same signature (2 inputs, one output). If a user were to add a 2nd input to the Marshal block **1660** of FIG. 16 the function-call subsystem **1625** of FIG. 16 would have 3 input arguments. Likewise if a user were to add a 3rd input signal to the Function-Call Proxy block **1979**, the function-call signal bundle, f-proxy would have 3 input arguments and the FCSS subsystem **1978** of FIG. 19C would have 3 inputs. Similar flexibility and consistency is provided at the Function-Call Proxy Adaptor **1977**.

[0120] Recognizing that the bundled signal **1650** of FIG. 16 may be preferred by certain users, the Chart **1980** of FIG. 19C can be configured to produce a function-call control signal bundle containing a bundled signal. This is shown in FIG. 19D.

[0121] In FIG. 19D, Chart **1980** is making a function-call passing in the value a, and receiving the value b via signal **1981**. From a functional perspective, the models of FIG. 19C and FIG. 19D are equivalent and produce the same answer. The Function-Call Proxy block **1982** is used to create the f-proxy bundled function-call control signal consisting of two inputs (a and c) and one return value (b). The Function-Call Proxy Adaptor **1983** is used to unbundle the f-proxy signal and provide the bundled functional-call control signal f(in: a, out: b) to the function-call subsystem, FCSS **1984**.

[0122] One additional depiction of the Function-Call Proxy block **1982** would be to eliminate the explicit output port signal of the Function-Call Proxy block **1982** and in turn provide a paired function-call proxy port block that produces the function-call proxy signal at the top of the component. Additionally, the Function-Call Proxy Adaptor block **1983** could be depicted without the bundled function-call control signal and in turn have a paired function-call proxy adaptor port block that receives a bundled function-call control signal and implicitly provides it to the Function-Call Proxy Adaptor. This idea is illustrated in FIG. 19E.

[0123] In FIG. 19E, the Proxy blocks inside SysA **1985** do not have an explicit output ports for the respective function-call groups. Instead, the Proxy block **1986** is directly "hyperlinked" to the Server port blocks A **1987** and B **1988**. Similarly within SysB **1989**, the Adapter blocks **1990**, **1991** do not have explicit connections to the function-call group signals. Instead, they are hyperlinked to the Server blocks A **1987** and B **1988** inside SysB **1989**. The respective Server Port blocks of SysA **1985** and SysB **1989** are connected to indicate that the function-call group signals of SysA **1985** are served by function-call blocks inside SysB **1989**.

[0124] A Subgraph Split block can be setup to perform parallel execution of the subordinate blocks. For example, FIG. 21 illustrates a Function-Call Split block **2110** (a realization of the general concept of Subgraph Split block) has been configured to invoke its subordinate blocks, Function-Call Subsystem h1 **2130** and Function-Call Subsystem h2 **2140** in two new threads as annotated with the f_p to in the icon to indicate parallel execution and the Th₁ **2150** and Th₂ **2160** function-call control signal labels (for thread 1 and thread 2).

[0125] In FIG. 21, there are no data dependencies and computations performed by the Function-Call Subsystems h1 **2130** and h2 **2140** are independent.

[0126] To improve efficiency threads may be created at model start and the threads may remain active. The act of invoking function-call on another thread signals via a semaphore or other synchronization entity thus activating execution of the subordinate function-call subsystem.

[0127] The term thread within the context of FIG. 21 refers to a separate thread of execution. In one implementation, the separate thread of execution can be a child thread of the process executing the model. Alternatively, the term thread can also mean a separate process running on the same computer or a process on a different computer. Generally, child threads of the current process are preferred because they use fewer resources. However, separate processes for the execution threads are required on some systems that don't support child threads within a process. There are numerous other reasons for using separate processes such as increased parallelism by leveraging multiple computers or multiple heterogeneous cores on a multicore system. In this case, a message passing interconnect is setup to communicate between the processes.

[0128] A parameter of Function-Call Split block 2110 can specify that the subordinate controlled blocks, namely h1 2130 and h2 2140, execute in new threads as shown in FIG. 21. In another embodiment, a user may specify that none or a subset of the subordinate controlled blocks execute in new threads. For example and referring to FIG. 22, h1 2130 executes in the same thread as the control initiator 2120 (Function-Call Generator) and h2 2140 executes in a new thread labeled, Th1 2230. One advantage of having h1 2130 run in the same thread of execution as the main model is that fewer resources will be used while still ensuring that both h1 2130 and h2 2140 do run in parallel.

[0129] Threading may introduce a new constraint on data signals, such as the need to ensure deterministic execution. For example and considering FIG. 23, model 2300 may represent an engine controller. In model 2300 there are three analog-to-digital (A/D) converters. The Engine On A/D converter 2302 detects when the engine is to be controlled to the desired speed as provided to model 2300 via the Desired Engine Speed A/D converter 2306. The Engine Speed A/D converter 2304 provides the current engine speed. The chart block 2308 is responsible for running either the init Function-Call Subsystem 2310 or the subgraph defined by the three function call branch blocks 2329, 2331, and 2332, the Function-Call Subsystems, f1 2312, f2 2314, f3 2316, and f4 2318 and the sync block 2320 (or more formally a data synchronization block). This subgraph is responsible for the "running" state of the engine where it computes the desired throttle position provided to the Engine Throttle Position D/A converter 2324 through the Merge block 2322. The init Function-Call Subsystem 2310 sets the desired throttle position when the system starts up by providing the value to the Engine Throttle Position D/A 2324 converter through the Merge block 2322. The Merge block 2322 outputs the merged signal of init_u or run_u. In FIG. 23 did not require a synchronization block between f1 2312 and f3 2316 which is running in a different thread because f1 will have finished execution before f3 starts running. This synchronization is achieved by 2329 which executes its bottom branch f1 2312 prior to executing is right-most branch 2331. It should also be clear to one skilled in the art that an incorrectly placed data synchronization block would result in an error. For example, if a data synchronization block were placed on the In1 signal feeding 2316, then during model analysis an error would be produced.

[0130] In FIG. 23, the Function-Call Subsystem f3 2316 is executing in a child thread (th2) 2326 and thus the Function-Call Subsystems f2 2314 and f3 2316 run in parallel. In the embodiment of FIG. 23, parallel execution increases the processing speed of the system for the automobile. The sync

block 2320 is a Function-Call Synchronization (or more generally a Control Signal Synchronization) block that is used to synchronize the child thread containing f3 with the main thread 2328. The Function-Call Subsystem f4 2318, cannot start processing until both f2 2314 and f3 2316 is complete. If Function-Call Subsystem f2 2314 finishes before f3 2316 is complete, then the sync block 2320 will cause the main thread 2328 to wait for the child thread 2330 of f2 2314. Once the child thread is complete, the right-most Function-Call Split block 2332 will invoke the Function-Call Subsystem f4 2318.

[0131] The contents of the chart block 2308 are shown in FIG. 24. In FIG. 24, f_init function call is invoked at start up. Then the chart enters the waiting state 2410. When the "Engine On" (A/D) converter 2302 produces a 1, the chart will enter the running state 2420. In the running state 2420, the chart periodically executes the subgraph of FIG. 23 at a discrete-time (sampled) rate.

[0132] When FIG. 23 is examined, e.g., by a user or programmatically, it may be determined that efficiency can be improved by using function-call subsystems to control when the Engine Speed, Desired Engine Speed and Engine Throttle Position blocks run. In FIG. 23, these will run when the chart is in the waiting state. FIG. 25 illustrates an embodiment that can provide improved performance with respect to the embodiment of FIG. 23 by using function-call subsystems to control aspect of the system.

[0133] In FIG. 25, the two source A/D converters of FIG. 24 (2304, 2306) have been placed into Function-Call Subsystem f0 2510 whose contents are show in FIG. 26. Referring to FIG. 25, The chart 2308, when in the running state, runs the f0 2510 first then runs f1 2312 to prefilter the input, then creates child thread, th2 2326 to run f3 2316 and at the same time runs f2 2314 in the main thread. Then f4 2318 runs after f2 2314 finishes and after f3 2316 finishes. The sync block 2320 ensures f3 2316 finishes. The Merge block 2322 merges the output of the init subsystem 2310 with the output of f4 2318. By definition the merge block 2322 is a virtual block meaning that it doesn't have any run-time behavior. Merge block 2322 ensures Out1 from the init subsystem 2310 and Out1 of f4 2318 occupy the same memory location. Because init 2310 and f4 2318 never execute on the same time step, the output of the Merge block 2322 represents the output of init 2310 or f4 2318 that ran last. The Merge block 2322 output is provided to the Function-Call Subsystem Engine Throttle Position block 2530. FIG. 27 illustrates the contents of block 2530. The join block 2540 is used to ensure block 2530 will only execute after init 2310 runs or after f4 2318 runs thus ensuring the D/A converter of FIG. 27 is only run when its input signal value may have changed.

[0134] Employing a Function-Call Split block operating in parallel mode is one way in which to spawn child threads of execution. The general concept may be referred to as spawn control signal initiator. One realization of the spawn control signal initiator is via the block illustrated in FIG. 28. FIG. 28 represents a model of a portion of an automotive engine (the plant). In FIG. 28, the plant may be modeled using time-based block diagram semantics such as continuous-time dynamics, hybrid (continuous+one or more discrete rates) dynamics, or discrete dynamics (one or more discrete rates). To improve execution speed, the plant is broken up into two sections and supporting blocks for those sections as shown in the figure.

[0135] In FIG. 28, the signals coming from the In1 and In2 Input blocks 2810 and 2820, respectively, are in the main thread. The Spawn block 2805 creates a new thread (th) 2807.

The section 1 subsystem **2820** contains blocks that transform the In1 signal into an output signal which is provided to a thread synchronization block **2830**, sync. After the main thread starts executing the child thread, the main thread immediately continues to execute the subsystem defined by section **2 2825** this subsystem transforms the In2 signals and provides them to the Out2 block **2840**.

[0136] If section 2 completes before section 1 is done, then the sync block **2830** will wait for section **1 2820** to complete. This ensures that both Out1 **2835** and Out2 **2840** are in the main thread. The implementation of the embodiment of FIG. **28** requires that the modeling environment produce a sorted list consisting having the following ordering: Action Spawn, Section 1, Section 2, and Sync. The requirements of the arrangement of FIG. **28** are that the sync block be placed as late as possible and that the Action spawn blocks **2805** be placed as early as possible. One means by which to achieve this is in the graph that is sorted, in the initial per-sort list, place the Action Spawn blocks **2805** first and the Sync blocks **2830** last. An alternative implementation for the sync block **2830** would be to have the users explicitly draw a dependency signal from the output of section **2 2825** to the input of the sync block **2830**. This signal would visually show the execution dependency and eliminate the need to explicitly pre-sort sync blocks last before sorting the graph defined by the blocks.

[0137] If the Spawn block were not present, the model in FIG. **28** would produce an error when the model is analyzed by the simulation/execution engine.

[0138] In addition, to having the Synchronization block synchronize threads, the Synchronization block may also include a timeout threshold, wherein if the subgraph does not complete execution before the threshold is reached an error is detected. The error condition may be to stop execution and report an error or the spawn block can produce an error signal that is used by other blocks to programmatically take corrective action, thus ensuring the model continues to execute.

[0139] Explicit execution control description thus far has primarily focused on time-based graphical models such as the block diagrams found within Simulink. Explicit execution control can apply to many different graphical modeling environments, including, but not necessarily limited to, discrete event such as the models found within SimEvents and data flow modeling environments. One difference between data flow and time-based graphical models is that in most data flow modeling environments, the execution of blocks is defined by data availability rather than a time hit as in time-based systems. In a data flow model, control signals can be used to execute subgraphs and within the subgraphs data dependencies are honored using the capabilities and techniques described herein. In addition, the other capabilities including explicit signatures for components via Control Signal Proxy and Control Signal Proxy Adaptor blocks, threading, and data sync block, etc. are suitable for such environments.

[0140] FIG. **29** illustrates exemplary processing that can be performed using embodiments of the invention. Referring to FIG. **29**, a time-based graphical model may be provided and may consist of a set of blocks connected by data signal lines (act **2905**). Each block defines a dynamic system that is characterized by a set of equations defined by system theory including but not limited to initialization, pre_execute, output, update, derivative, termination run-time functions. The model may be converted into an executable form to analyze the model or compile it (act **2910**). Model compilation con-

sists of sorting the blocks according to data dependencies. In an embodiment, sorting may be performed using a variant of depth first sorting that handles strongly connected components. Using the compiled information, the model may be linked via a link phase that generates block function execution lists from the sorted-list, one for each block run-time function of a given rate (sample time) (act **2915**).

[0141] Before running a simulation or generating code, the initialize functions are called to setup the system state. In an interpretive simulation, the block run-time functions are executed in a simulation loop using the block function execution lists, where the output functions are executed first, and then the update functions for discrete states are executed (act **2920**). Finally integration of the continuous states is computed by integrating the derivatives and time is advanced.

[0142] The addition of control signals to a time-based graphical model is handled during compilation by ignoring these signals for the block sorting based on data dependencies. Each control signal initiator is provided with objects it can use to run functions on the connected subgraph. For example a Stateflow chart with a function-call control signal output may be connected to a Function-Call Split block. The chart will be provided with an object that can be used to run the various runtime methods associated with the control signal. If the Function-Call Split block is connected to a Function-Call Subsystems, then the object will aggregate the run-time methods of both subsystems.

[0143] In stead of using an interpretive simulation, generated code can be produced from the graphical model (act **2925**). Code generation is performed by using the sorted list and the results of initialization to create an intermediate representation that is transformed to generated code such as C or C++. Alternatively, hardware can be synthesized from the model by producing code that conforms to a hardware description language HDL such as Verilog.

[0144] FIG. **30** illustrates an exemplary computer architecture that can be used to implement computer **3000**. FIG. **30** is an exemplary diagram of an entity corresponding to computer **3000**. As illustrated, the entity may include a bus **3010**, processing logic **3020**, a main memory **3030**, a read-only memory (ROM) **3040**, a storage device **3050**, an input device **3060**, an output device **3070**, and/or a communication interface **3080**. Bus **3010** may include a path that permits communication among the components of the entity.

[0145] Processing logic **3020** may include a processor, microprocessor, or other types of processing logic that may interpret and execute instructions. In one implementation, processing logic **3020** may include a single core processor or a multi-core processor. In another implementation, processing logic **3020** may include a single processing device or a group of processing devices, such as a processor cluster or computing grid. In still another implementation, processing logic **3020** may include multiple processors that may be local or remote with respect each other, and may use one or more threads while processing.

[0146] Main memory **3030** may include a random access memory (RAM) or another type of dynamic storage device that may store information and instructions for execution by processing logic **3020**. ROM **3040** may include a ROM device or another type of static storage device that may store static information and/or instructions for use by processing logic **3020**. Storage device **3050** may include a magnetic, solid state and/or optical recording medium and its corre-

sponding drive, or another type of static storage device that may store static information and/or instructions for use by processing logic 3020.

[0147] Input device 3060 may include logic that permits an operator to input information to the entity, such as a keyboard, a mouse, a pen, a touchpad, an accelerometer, a microphone, voice recognition, camera, neural interface, biometric mechanisms, etc. Output device 3070 may include a mechanism that outputs information to the operator, including a display, a printer, a speaker, etc. Communication interface 3080 may include any transceiver-like logic that enables the entity to communicate with other devices and/or systems. For example, communication interface 3080 may include mechanisms for communicating with another device or system via a network.

[0148] The entity depicted in FIG. 30 may perform certain operations in response to processing logic 3020 executing software instructions contained in a computer-readable medium, such as main memory 3030. A computer-readable medium may be defined as a physical or logical memory device. The software instructions may be read into main memory 3030 from another computer-readable storage medium, such as storage device 3050, or from another device via communication interface 3080. The software instructions contained in main memory 3030 may cause processing logic 3020 to perform processes described herein when the software instructions are executed on processing logic. Alternatively, hardwired circuitry may be used in place of or in combination with software instructions to implement processes described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

[0149] Although FIG. 30 shows exemplary components of the entity, in other implementations, the entity may contain fewer, different, or additional components than depicted in FIG. 30. In still other implementations, one or more components of the entity may perform one or more tasks described as being performed by one or more other components of the entity.

[0150] One or more embodiments of the invention may be implemented in a distributed environment. FIG. 31 illustrates an example of a distributed environment 3100 that may be configured to implement one or more embodiments of the invention. Referring to FIG. 31, environment 3100 may contain various entities including computing device 3000, target environment 3110, service provider 3120, cluster 3130, and network 3140. Note that the distributed environment 3100 is just one example of a distributed environment that may be used with embodiments of the invention. Other distributed environments that may be used with embodiments of the invention may contain more entities, fewer entities, entities in arrangements that differ from the arrangement illustrated in FIG. 31. Moreover, the distributed environments may be configured to implement various cloud computing frameworks.

[0151] Details of computing device 3000 were described above with respect to FIG. 30. In distributed environment 3100, computing device 3000 may be configured to, among other things, exchange information (e.g., data) with other entities on network 3140 (e.g., target environment 3110, service provider 3120, and cluster 3130). Computing device 3000 may interface with the network 3140 via communication interface 180.

[0152] Target environment 3110 may be configured to execute and/or interpret a compiled version of a model, which

may be generated in or otherwise available to the distributed environment 3100. The network 3140 may include a communication network capable of exchanging information between the entities in the network 3140. The network 3140 may include digital and/or analog aspects. The information may include machine-readable information having a format that may be adapted for use, for example, in the network 3140 and/or with one or more entities in the network 3140. For example, the information may be encapsulated in one or more packets that may be used to transfer the information through the network 3140.

[0153] Information may be exchanged between entities using various network protocols, such as, but not limited to, the Internet Protocol (IP), Asynchronous Transfer Mode (ATM), Synchronous Optical Network (SONET), the User Datagram Protocol (UDP), Transmission Control Protocol (TCP), Institute of Electrical and Electronics Engineers (IEEE) 802.11, etc.

[0154] The network 3140 may include various network devices, such as gateways, routers, switches, firewalls, servers, repeaters, address translators, etc. Portions of the network 3140 may be wired (e.g., using wired conductors, optical fibers, etc.) and/or wireless (e.g., using free-space optical (FSO), radio frequency (RF), acoustic transmission paths, etc.). Portions of network 3140 may include a substantially open public network, such as the Internet. Portions of network 3140 may include a more restricted network, such as a private corporate network or virtual private network (VPN).

[0155] It should be noted that implementations of networks and/or devices operating on networks described herein are not limited with regards to, for example, information carried by the networks, protocols used in the networks, and/or the architecture/configuration of the networks.

[0156] Service provider 3120 may include logic that makes a service available to another entity in the distributed environment 3100. Service provider 3120 may also include a server operated by, for example, an individual, a corporation, an educational institution, a government agency, and so on, that provides one or more services to a destination, such as computing device 3000. The services may include software containing computer-executable instructions that implement one or more embodiments of the invention or portions thereof, and may be executed, in whole or in part, by (1) a destination, (2) the service provider 3120 on behalf of the destination, or (3) some combination thereof.

[0157] For example, in an embodiment, service provider 3120 may provide one or more subscription-based services that may be available to various customers. The services may be accessed by a customer via network 3140. The customer may access the services using a computer system, such as computing device 3000. The services may include services that implement one or more embodiments of the invention or portions thereof. Service provider 3120 may limit access to certain services based on, e.g., a customer service agreement between the customer and service provider 3120.

[0158] The service agreement may allow the customer to access the services that may allow the customer to build, execute, and/or analyze a model, such as model 300, as described above. The service agreement may include other types of arrangements, such as certain fee-based arrangements or restricted access arrangements. For example, a customer may pay a fee which provides the customer unlimited access to a given package of services for a given time period (e.g., per minute, hourly, daily, monthly, yearly, etc.). For

services not included in the package, the customer may have to pay an additional fee in order to access the services. Still other arrangements may be resource-usage based. For example, the customer may be assessed a fee based on an amount of computing resources and/or network bandwidth used.

[0159] Cluster **3130** may include a number of units of execution (UEs) **3132** that may perform processing of one or more embodiments of the invention or portions thereof on behalf of computing device **3000** and/or another entity, such as service provider **3120**. The UEs **3132** may reside on a single device or chip or on multiple devices or chips. For example, the UEs **3132** may be implemented in a single ASIC or in multiple ASICs. Likewise, the UEs **3132** may be implemented in a single computer system or multiple computer systems. Other examples of UEs **3132** may include FPGAs, CPLDs, ASIPs, processors, multiprocessor systems-on-chip (MPSoCs), graphic processing units, microprocessors, etc. The UEs **3132** may be configured to perform operations on behalf of another entity.

[0160] Exemplary embodiments may include or may be implemented in a technical computing environment that includes hardware and/or hardware-software based logic. The logic may provide a computing environment that allows users to perform tasks related to disciplines, such as, but not limited to, mathematics, science, engineering, medicine, business, etc., more efficiently than if the tasks were performed in another type of computing environment, such as an environment that required the user to develop code in a conventional programming language, such as C++, C, Fortran, Pascal, etc. In one implementation, the technical computing environment may include a dynamically typed language that can be used to express problems and/or solutions in mathematical notations familiar to those of skill in the relevant arts. For example, the technical computing environment may use an array as a basic element, where the array may not require dimensioning. These arrays may be used to support array programming in that operations can apply to an entire set of values, such as values in an array. Array programming may allow array based operations to be treated as a high-level programming technique or model that lets a programmer think and operate on whole aggregations of data without having to resort to explicit loops of individual non-array, i.e., scalar operations.

[0161] The technical computing environment may further be adapted to perform matrix and/or vector formulations that can be used for data analysis, data visualization, application development, simulation, modeling, algorithm development, etc. These matrix and/or vector formulations may be used in many areas, such as statistics, finance, image processing, signal processing, control design, life sciences, education, discrete event analysis and/or design, state based analysis and/or design, etc.

[0162] The technical computing environment may further provide mathematical functions and/or graphical tools (e.g., for creating plots, surfaces, images, volumetric representations, etc.). In one implementation, the technical computing environment may provide these functions and/or tools using toolboxes (e.g., toolboxes for signal processing, image processing, data plotting, parallel processing, optimization, etc.). In another implementation, the technical computing environment may provide these functions as block sets (e.g., an optimization block set). In still another implementation, the technical computing environment may provide these func-

tions in another way, such as via a library, etc. The technical computing environment may be implemented as a text based environment, a graphically based environment, or another type of environment, such as a hybrid environment that is both text and graphically based.

[0163] For example, a text-based embodiment may implement the technical computing environment using one or more text-based products. For example, a text-based technical computing environment (TCE), may be implemented using products such as, but not limited to, MATLAB® by The MathWorks, Inc.; Octave; Python; Comsol Script; MATRIXx from National Instruments; Mathematica from Wolfram Research, Inc.; Mathcad from Mathsoft Engineering & Education Inc.; Maple from Maplesoft; Extend from Imagine That Inc.; Scilab from The French Institution for Research in Computer Science and Control (INRIA); Virtuoso from Cadence; or Modelica or Dymola from Dynasim. The text-based TCE may support one or more commands that support remote processing using one or more units of execution or other types of remote processing devices.

[0164] A graphically-based embodiment may implement the technical computing environment in a graphically-based technical computing environment using products such as, but not limited to, Simulink®, Stateflow®, SimEvents™, etc., by The MathWorks, Inc.; VisSim by Visual Solutions; LabView® by National Instruments; Dymola by Dynasim; SoftWIRE by Measurement Computing; WiT by DALSA Coreco; VEE Pro or SystemVue by Agilent; Vision Program Manager from PPT Vision; Khoros from Khoros Research; Gedae by Gedae, Inc.; Scicos from (INRIA); Virtuoso from Cadence; Rational Rose from IBM; Rhapsody or Tau from Telelogic; Ptolemy from the University of California at Berkeley; or aspects of a Unified Modeling Language (UML) or SysML environment. The graphically-based TCE may support remote processing using one or more units of execution or other types of remote processing devices. Implementations may provide a modeling environment that allows states to be implicitly reset while a model executes.

[0165] The foregoing description of exemplary embodiments of the invention provides illustration and description, but is not intended to be exhaustive or to limit the invention to the precise form disclosed. Modifications and variations are possible in light of the above teachings or may be acquired from practice of the invention. For example, while a series of acts has been described with regard to FIG. 29, the order of the acts may be modified in other implementations consistent with the principles of the invention. Further, non-dependent acts may be performed in parallel.

[0166] In addition, implementations consistent with principles of the invention can be implemented using devices and configurations other than those illustrated in the figures and described in the specification without departing from the spirit of the invention. Devices and/or components may be added and/or removed from the implementations of FIGS. 30 and 31 depending on specific deployments and/or applications. Further, disclosed implementations may not be limited to any specific combination of hardware. Further, certain portions of the invention may be implemented as “logic” that performs one or more functions. This logic may include hardware, such as hardwired logic, an application-specific integrated circuit, a field programmable gate array, a microprocessor, software, or a combination of hardware and software.

[0167] No element, act, or instruction used in the description of the invention should be construed as critical or essen-

tial to the invention unless explicitly described as such. Also, as used herein, the article “a” is intended to include one or more items. Where only one item is intended, the term “one” or similar language is used. Further, the phrase “based on,” as used herein is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

[0168] Headings and sub-headings used herein are to aid the reader by dividing the specification into subsections. These headings and sub-headings are not to be construed as limiting the scope of the invention or as defining the invention.

[0169] The scope of the invention is defined by the claims and their equivalents.

What is claimed is:

1. A computer-implemented method in a graphical modeling environment, the method comprising:

providing a control initiator, where the control initiator provides a control signal to a control signal splitter;

providing a first subgraph in the modeling environment, where:

the first subgraph includes one or more blocks, and
the first subgraph is connected to the control signal splitter;

providing a second subgraph in the modeling environment, where:

the second subgraph includes one or more blocks, and
the second subgraph is connected to the control signal splitter;

executing the first subgraph on a first thread to produce a first result when the first subgraph receives the control signal from the control signal splitter; and

executing the second subgraph on a second thread to produce a second result when the second subgraph receives the control signal from the control signal splitter.

2. The method of claim 1, further comprising:

providing a data synchronization block; and
maintaining data integrity between the first thread and the second thread using the data synchronization block.

3. The method of claim 1, where the first thread is a calling thread and the second thread is a new thread called by the calling thread.

4. The method of claim 1, where the second thread is the calling thread and the first thread is a new thread called by the calling thread.

5. The method of claim 1, further comprising:
providing a calling thread.

6. The method of claim 5, further comprising:
calling the first thread using the calling thread; and
calling the second thread using the calling thread.

7. The method of claim 1, further comprising a second control signal splitter, the second control signal splitter connected to the control signal splitter.

8. The method of claim 1, where the control signal splitter splits the control signal into more than two output control signals.

9. The method of claim 1, where the control initiator is a state chart.

10. The method of claim 1, where the model is a time-based model, a data flow model, or an event-based model.

11. The method of claim 1, where the control signal is a function-call or an action signal.

12. The method of claim 1, where the model includes one or more data signals.

13. A computer-implemented method in a graphical modeling environment, the method comprising:

providing a first control initiator, where the first control initiator is connected to a first subgraph by a first control signal;

executing the first subgraph in a first thread;

providing a second control initiator, where the second control initiator is connected to a second subgraph by a second control signal;

executing the second subgraph in a second thread; and

interacting with a data synchronization block, where:

the interacting allows a result from the first subgraph to be used by the second subgraph when the second subgraph is executing, and

the data synchronization block waits for the first thread to finish executing before allowing the first result to be used by the second subgraph when the second subgraph is executing.

14. The method of claim 13, where the graphical modeling environment includes a graphical representation that represents the first control initiator and the second control initiator.

15. The method of claim 14, where the graphical representation is a block.

16. The method of claim 13, where graphical modeling environment further includes a splitter block, where the splitter block connects the first control initiator to the first subgraph and the second control initiator to the second subgraph.

17. The method of claim 13, where the synchronization block includes a timeout threshold.

18. The method of claim 17, further comprising:

producing an error when the timeout threshold is exceeded.

19. The method of claim 13, where the control initiator is a state chart.

20. The method of claim 13, where the model is a time-based model, a data flow model, or an event-based model.

21. The method of claim 13, where the control signal is a function-call or an action signal.

22. The method of claim 13, where the model includes one or more data signals.

23. A computer-implemented method in a graphical modeling environment, the method comprising:

providing a spawn control initiator, the spawn control initiator executing on a main thread in the modeling environment;

providing a subgraph in the modeling environment, where:
the subgraph includes one or more blocks, and
the subgraph is connected to the spawn control initiator via a control signal;

directly providing inputs to the subgraph; and

executing the subgraph on a separate thread, the separate thread differing from the main thread, the executing producing a result.

24. The method of claim 23, where the modeling environment further includes:

a synchronization block, connected to the output of the subgraph the synchronization block waiting for the separate thread to finish executing before allowing the result to be used by the main thread.

25. The method of claim 23, where the modeling environment produces an error when the result is used in the main thread without first passing through a synchronization block.

26. The method of claim 25, where the synchronization block is the last block executed on the main thread.

27. The method of claim 25, where the synchronization block includes additional inputs, the additional inputs depicting when the result is needed by the main thread.

28. The method of claim 25, where the synchronization block includes a timeout threshold.

29. The method of claim 28, further comprising:
producing an error when the timeout threshold is exceeded.

30. The method of claim 23, where the control initiator is a state chart.

31. The method of claim 23, where the model is a time-based model, a data flow model, or an event-based model.

32. The method of claim 23, where the control signal is a function-call or an action signal.

33. The method of claim 23, where the model includes one or more data signals.

34. A computer-readable medium holding executable instructions that when executed on a processor control subgraph execution in a model, the medium holding one or more instructions for:

providing a control initiator, where the control initiator provides a control signal to a control signal splitter;
providing a first subgraph in the modeling environment, where:

the first subgraph includes one or more blocks, and
the first subgraph is connected to the control signal splitter;
providing a second subgraph in the modeling environment, where:

the second subgraph includes one or more blocks, and
the second subgraph is connected to the control signal splitter;

executing the first subgraph on a first thread to produce a first result when the first subgraph receives the control signal from the control signal splitter; and

executing the second subgraph on a second thread to produce a second result when the second subgraph receives the control signal from the control signal splitter.

35. A computer-readable medium holding executable instructions that when executed on a processor control subgraph execution in a model, the medium holding one or more instructions for:

providing a first control initiator, where the first control initiator is connected to a first subgraph by a first control signal;

executing the first subgraph in a first thread;

providing a second control initiator, where the second control initiator is connected to a second subgraph by a second control signal;

executing the second subgraph in a second thread; and

interacting with a data synchronization block, where:

the interacting allows a result from the first subgraph to be used by the second subgraph when the second subgraph is executing, and

the data synchronization block waits for the first thread to finish executing before allowing the first result to be used by the second subgraph when the second subgraph is executing.

36. A computer-readable medium holding executable instructions that when executed on a processor control execution of a subgraph in a model, the medium holding one or more instructions for:

providing a spawn control initiator, the spawn control initiator executing on a main thread in the modeling environment;

providing a subgraph in the modeling environment, where:
the subgraph includes one or more blocks, and
the subgraph is connected to the spawn control initiator via a control signal;

directly providing inputs to the subgraph; and

executing the subgraph on a separate thread, the separate thread differing from the main thread, the executing producing a result.

* * * * *