



US011640621B2

(12) **United States Patent**
Salmon et al.

(10) **Patent No.:** **US 11,640,621 B2**

(45) **Date of Patent:** ***May 2, 2023**

(54) **SYSTEMS AND METHODS TO PROVIDE A USER INTERFACE FOR REDEMPTION OF LOYALTY REWARDS**

(58) **Field of Classification Search**

None

See application file for complete search history.

(71) Applicant: **Visa International Service Association**, San Francisco, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,941,090 A 7/1990 McCarthy
5,025,372 A 6/1991 Burton et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2003502763 A 1/2003
JP 2004303015 A 10/2004
(Continued)

OTHER PUBLICATIONS

Wells Fargo, "Credit card alerts can help protect what matters to you", retrieved from <https://www.wellsfargo.com/credit-cards/alerts/>, available on Mar. 23, 2010 (Year: 2010).*

(Continued)

(72) Inventors: **Diane C. Salmon**, Lafayette, CA (US); **James Alan VonDerheide**, Pasadena, CA (US); **Laura DiGiacchino**, San Mateo, CA (US); **Edward Scheidelman**, Fairfax, CA (US); **Nancy L. Kim**, San Francisco, CA (US)

(73) Assignee: **Visa International Service Association**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/720,339**

(22) Filed: **Apr. 14, 2022**

Primary Examiner — Sam Refai

(74) *Attorney, Agent, or Firm* — The Webb Law Firm

(65) **Prior Publication Data**

US 2022/0237649 A1 Jul. 28, 2022

Related U.S. Application Data

(63) Continuation of application No. 15/959,751, filed on Apr. 23, 2018, now Pat. No. 11,328,315, which is a (Continued)


(51) **Int. Cl.**
G06Q 30/0226 (2023.01)
G06Q 20/38 (2012.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06Q 30/0233** (2013.01); **G06Q 20/387** (2013.01); **G06Q 20/40** (2013.01); **G06Q 20/42** (2013.01); **G06Q 30/0226** (2013.01)

(57) **ABSTRACT**

A system includes a rule engine to determine details of loyalty reward currency redemption from one or more reward accounts as part of the processing of a payment transaction in a payment account of a user. The redemption details are determined based on user preferences and rules of the loyalty programs, and transmitted to the user during the authorization of the payment transaction. During the authorization and/or within a time window after the authorization, but before the settlement of the payment transaction, the user may provide a confirmation message that may accept, reject, or modify the redemption details. A transaction handler is configured to authorize and/or settle the payment transaction, as modified by the redemption details initially com-

(Continued)



puted by the rule engine and subsequently confirmed, rejected or modified by the user via an optional confirmation message.

20 Claims, 22 Drawing Sheets

Related U.S. Application Data

continuation of application No. 14/523,185, filed on Oct. 24, 2014, now Pat. No. 9,990,646.

(60) Provisional application No. 61/895,269, filed on Oct. 24, 2013.

(51) **Int. Cl.**
G06Q 20/40 (2012.01)
G06Q 20/42 (2012.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,117,355	A	5/1992	McCarthy	7,428,498	B2	9/2008	Voltmer et al.
5,202,826	A	4/1993	McCarthy	7,606,730	B2	10/2009	Antonucci
5,287,268	A	2/1994	McCarthy	7,624,041	B2	11/2009	Postrel
5,465,206	A	11/1995	Hilt et al.	7,630,986	B1	12/2009	Herz et al.
5,477,038	A	12/1995	Levine et al.	7,665,660	B2	2/2010	Degliantoni et al.
5,530,232	A	6/1996	Taylor	7,680,688	B2	3/2010	Hessburg et al.
5,621,201	A	4/1997	Langhans et al.	7,686,218	B2	3/2010	Hessburg et al.
5,689,100	A	11/1997	Carrithers et al.	7,742,943	B2	6/2010	Postrel
5,774,870	A	6/1998	Storey	7,753,264	B2	7/2010	Shafer et al.
RE36,116	E	2/1999	McCarthy	7,765,124	B2	7/2010	Postrel
5,923,016	A	7/1999	Fredregill et al.	7,769,630	B2	8/2010	Postrel
5,937,391	A	8/1999	Ikeda et al.	7,828,206	B2	11/2010	Hessburg et al.
5,956,694	A	9/1999	Powell	7,853,529	B1	12/2010	Walker et al.
6,032,136	A	2/2000	Brake, Jr. et al.	7,868,218	B2	1/2011	Clark et al.
6,055,512	A	4/2000	Dean et al.	7,870,022	B2	1/2011	Bous et al.
6,101,477	A	8/2000	Hohle et al.	7,894,634	B2	2/2011	Chung
6,129,274	A	10/2000	Suzuki	8,010,405	B1	8/2011	Bortolin et al.
6,138,911	A	10/2000	Fredregill et al.	8,046,256	B2	10/2011	Chien et al.
6,243,687	B1	6/2001	Powell	8,090,657	B2	1/2012	Mitchell et al.
6,247,129	B1	6/2001	Keathley et al.	8,155,999	B2	4/2012	de Boer et al.
6,251,017	B1	6/2001	Leason et al.	8,180,671	B2	5/2012	Cohagan et al.
6,332,126	B1	12/2001	Peirce et al.	8,265,993	B2	9/2012	Chien et al.
6,334,108	B1	12/2001	Deaton et al.	8,285,643	B2	10/2012	Isaacson et al.
6,336,099	B1	1/2002	Barnett et al.	8,301,593	B2	10/2012	Hoffmann et al.
6,341,353	B1	1/2002	Herman et al.	8,302,030	B2	10/2012	Soroca et al.
6,408,286	B1	6/2002	Heiden	8,313,023	B1	11/2012	McGhie et al.
6,450,407	B1	9/2002	Freeman et al.	8,315,929	B2	11/2012	Allen-Rouman et al.
6,560,581	B1	5/2003	Fox et al.	8,332,290	B1*	12/2012	Venture G06Q 30/00
6,571,216	B1	5/2003	Garg et al.				705/33
6,594,640	B1	7/2003	Postrel	8,342,399	B1	1/2013	McGhie et al.
6,606,745	B2	8/2003	Maggio	8,401,967	B1	3/2013	Postrel
6,663,105	B1	12/2003	Sullivan et al.	8,478,640	B2	7/2013	Postrel
6,721,743	B1	4/2004	Sakakibara	8,511,550	B1	8/2013	McGhie et al.
6,741,968	B2	5/2004	Jacoves et al.	8,660,893	B2	2/2014	Fordyce, III
6,748,365	B1	6/2004	Quinlan et al.	8,682,791	B2	3/2014	Bies et al.
6,820,061	B2	11/2004	Postrel	9,460,436	B2	10/2016	Ovick et al.
6,829,586	B2	12/2004	Postrel	2001/0016827	A1	8/2001	Fernandez
6,842,739	B2	1/2005	Postrel	2001/0054003	A1	12/2001	Chien et al.
6,856,820	B1	2/2005	Kolls	2001/0054006	A1	12/2001	Lee et al.
6,865,547	B1	3/2005	Brake, Jr. et al.	2002/0026348	A1	2/2002	Fowler et al.
6,947,898	B2	9/2005	Postrel	2002/0046116	A1	4/2002	Hohle et al.
6,978,250	B1	12/2005	Kawan et al.	2002/0062249	A1	5/2002	Iannacci
7,054,830	B1	5/2006	Eggleston et al.	2002/0082920	A1	6/2002	Austin et al.
7,072,864	B2	7/2006	Brake, Jr. et al.	2002/0123926	A1	9/2002	Bushold et al.
7,096,190	B2	8/2006	Postrel	2002/0143614	A1	10/2002	MacLean et al.
7,134,087	B2	11/2006	Bushold et al.	2002/0160761	A1	10/2002	Wolfe
7,163,145	B2	1/2007	Cohagan et al.	2003/0004808	A1	1/2003	Elhaoussine et al.
7,263,507	B1	8/2007	Brake, Jr. et al.	2003/0040964	A1	2/2003	Lacek
7,370,811	B2	5/2008	Turner et al.	2003/0055727	A1	3/2003	Walker et al.
7,376,580	B1	5/2008	Walker et al.	2003/0144907	A1	7/2003	Cohen, Jr. et al.
7,398,225	B2	7/2008	Voltmer et al.	2003/0158818	A1	8/2003	George et al.
7,424,617	B2	9/2008	Boyd et al.	2003/0200144	A1	10/2003	Antonucci et al.
				2003/0212626	A1	11/2003	Vulkan
				2003/0216967	A1	11/2003	Williams
				2003/0225618	A1	12/2003	Hessburg et al.
				2003/0233439	A1	12/2003	Stone et al.
				2003/0236704	A1	12/2003	Antonucci
				2003/0236712	A1	12/2003	Antonucci et al.
				2004/0049423	A1	3/2004	Kawashima et al.
				2004/0078342	A1	4/2004	Goldschmidt Iki et al.
				2004/0083170	A1	4/2004	Bam et al.
				2004/0088216	A1	5/2004	Bangalore
				2004/0088376	A1	5/2004	McCanne et al.
				2004/0104760	A1	6/2004	Ando
				2004/0117250	A1	6/2004	Lubow et al.
				2004/0133472	A1	7/2004	Leason et al.
				2004/0138949	A1	7/2004	Darnton et al.
				2004/0148224	A1	7/2004	Gauthier et al.
				2004/0186773	A1	9/2004	George et al.
				2004/0203648	A1	10/2004	Wong
				2004/0238622	A1	12/2004	Freiberg
				2004/0249710	A1	12/2004	Smith et al.
				2004/0260608	A1	12/2004	Lewis et al.
				2005/0010533	A1	1/2005	Cooper
				2005/0021399	A1	1/2005	Postrel
				2005/0021401	A1	1/2005	Postrel
				2005/0055272	A1	3/2005	Ryan et al.
				2005/0060225	A1	3/2005	Postrel
				2005/0071225	A1	3/2005	Bortolin et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0071227	A1	3/2005	Hammad et al.	2008/0249861	A1	10/2008	Carotta et al.
2005/0080727	A1	4/2005	Postrel	2008/0313034	A1	12/2008	Wise
2005/0091152	A1	4/2005	Suisa	2009/0006203	A1	1/2009	Fordyce et al.
2005/0114213	A1	5/2005	Smith et al.	2009/0018909	A1	1/2009	Grecia
2005/0119938	A1	6/2005	Smith et al.	2009/0030793	A1	1/2009	Fordyce
2005/0149394	A1	7/2005	Postrel	2009/0048916	A1	2/2009	Nuzum et al.
2005/0205666	A1	9/2005	Ward et al.	2009/0076911	A1	3/2009	Vo et al.
2005/0240472	A1	10/2005	Postrel	2009/0076912	A1	3/2009	Rajan et al.
2005/0240478	A1	10/2005	Lubow et al.	2009/0106112	A1	4/2009	Dalmia et al.
2005/0240536	A1	10/2005	Davis et al.	2009/0106115	A1	4/2009	James et al.
2005/0251469	A1	11/2005	Nandakumar	2009/0106300	A1	4/2009	Brown
2006/0010033	A1	1/2006	Thomas	2009/0112721	A1	4/2009	Hammad et al.
2006/0020511	A1	1/2006	Postrel	2009/0176580	A1	7/2009	Herrmann et al.
2006/0053056	A1	3/2006	Alspach-Goss et al.	2009/0198572	A1	8/2009	Jurgens
2006/0059040	A1	3/2006	Eldred et al.	2009/0271262	A1*	10/2009	Hammad G06Q 20/40 709/204
2006/0129456	A1	6/2006	Walker et al.	2009/0307118	A1	12/2009	Baumgartner
2006/0136299	A1	6/2006	Ruhmkorf	2009/0307130	A1	12/2009	Tan
2006/0184419	A1	8/2006	Postrel	2010/0010901	A1	1/2010	Marshall et al.
2006/0190337	A1	8/2006	Ayers et al.	2010/0030688	A1	2/2010	Patterson
2006/0206376	A1	9/2006	Gibbs et al.	2010/0042517	A1	2/2010	Paintin et al.
2006/0208065	A1	9/2006	Mendelovich et al.	2010/0051691	A1	3/2010	Brooks et al.
2006/0218024	A1	9/2006	Lulla	2010/0057551	A1	3/2010	Blaisdell
2006/0224454	A1	10/2006	Kantor et al.	2010/0057553	A1	3/2010	Ameiss et al.
2006/0253320	A1	11/2006	Heywood	2010/0075638	A1	3/2010	Carlson et al.
2006/0253321	A1	11/2006	Heywood	2010/0076820	A1	3/2010	Davis
2006/0259364	A1	11/2006	Strock et al.	2010/0106598	A1	4/2010	Grimes
2006/0261149	A1	11/2006	Raghavendra Tulluri	2010/0125737	A1	5/2010	Kang
2006/0287943	A1	12/2006	Postrel	2010/0145855	A1	6/2010	Fordyce et al.
2007/0005416	A1	1/2007	Jackson et al.	2010/0174596	A1	7/2010	Gilman et al.
2007/0011044	A1*	1/2007	Hansen G06Q 30/0213 705/14.15	2010/0211445	A1	8/2010	Bodington
2007/0038515	A1	2/2007	Postrel	2010/0211469	A1	8/2010	Salmon et al.
2007/0043619	A1	2/2007	Leason et al.	2010/0274655	A1	10/2010	Postrel
2007/0043620	A1	2/2007	Leason et al.	2010/0274659	A1	10/2010	Antonucci et al.
2007/0078719	A1	4/2007	Schmitt et al.	2010/0280892	A1	11/2010	Uzumalioglu et al.
2007/0100691	A1	5/2007	Patterson	2010/0299194	A1	11/2010	Snyder et al.
2007/0112629	A1	5/2007	Solomon et al.	2010/0306032	A1	12/2010	Jolley
2007/0124204	A1	5/2007	de Boer et al.	2010/0312626	A1	12/2010	Cervenka
2007/0129955	A1	6/2007	Dalmia et al.	2010/0312631	A1	12/2010	Cervenka
2007/0129998	A1	6/2007	Postrel	2010/0312632	A1	12/2010	Cervenka
2007/0130011	A1	6/2007	Postrel	2010/0312633	A1	12/2010	Cervenka
2007/0143178	A1	6/2007	Citrin	2010/0312634	A1	12/2010	Cervenka
2007/0156530	A1	7/2007	Schmitt et al.	2010/0312635	A1	12/2010	Cervenka
2007/0192784	A1	8/2007	Postrel	2011/0022448	A1	1/2011	Strock et al.
2007/0198335	A1	8/2007	Edwards et al.	2011/0022514	A1	1/2011	Lal et al.
2007/0198338	A1	8/2007	Heywood	2011/0035278	A1	2/2011	Fordyce et al.
2007/0214049	A1	9/2007	Postrel	2011/0047019	A1*	2/2011	Cervenka G06Q 30/0225 705/14.26
2007/0226059	A1	9/2007	Postrel	2011/0066483	A1	3/2011	Salmon et al.
2007/0260509	A1	11/2007	Hines et al.	2011/0082739	A1	4/2011	Pourfallah
2007/0288313	A1	12/2007	Brodson et al.	2011/0087530	A1	4/2011	Fordyce et al.
2008/0010154	A1	1/2008	Tietzen et al.	2011/0087531	A1	4/2011	Winters et al.
2008/0011820	A1	1/2008	Brown et al.	2011/0125565	A1*	5/2011	Macllwaine G06Q 30/0273 705/14.1
2008/0021784	A1	1/2008	Hessburg et al.	2011/0145148	A1	6/2011	Hammad
2008/0040222	A1	2/2008	Gee	2011/0161230	A1	6/2011	Singh
2008/0040270	A1	2/2008	Buchheit et al.	2011/0218868	A1	9/2011	Young et al.
2008/0059302	A1	3/2008	Fordyce, III et al.	2011/0231258	A1	9/2011	Winters
2008/0059303	A1	3/2008	Fordyce	2011/0238483	A1	9/2011	Yoo et al.
2008/0059306	A1	3/2008	Fordyce et al.	2011/0276493	A1	11/2011	Graham et al.
2008/0059307	A1	3/2008	Fordyce, III et al.	2011/0276495	A1	11/2011	Varadarajan et al.
2008/0071640	A1	3/2008	Nguyen	2011/0288918	A1	11/2011	Cervenka et al.
2008/0077499	A1	3/2008	Ariff et al.	2011/0288924	A1	11/2011	Thomas et al.
2008/0103968	A1	5/2008	Bies et al.	2011/0295675	A1	12/2011	Reodica
2008/0120221	A1	5/2008	Toneguzzo	2012/0010940	A1	1/2012	Masi
2008/0133350	A1*	6/2008	White G06Q 20/20 705/14.27	2012/0016728	A1	1/2012	Ahmad et al.
2008/0133351	A1	6/2008	White et al.	2012/0035998	A1	2/2012	Chien et al.
2008/0147534	A1	6/2008	Ephrati et al.	2012/0041812	A1	2/2012	Postrel
2008/0154676	A1	6/2008	Suk	2012/0101881	A1	4/2012	Taylor et al.
2008/0154722	A1	6/2008	Galinos	2012/0101894	A1	4/2012	Sterling et al.
2008/0177627	A1	7/2008	Cefail	2012/0123849	A1	5/2012	Armstrong
2008/0195528	A1	8/2008	Keithley	2012/0179531	A1	7/2012	Kim
2008/0201224	A1	8/2008	Owens et al.	2012/0191525	A1	7/2012	Singh et al.
2008/0217397	A1	9/2008	Degliantoni et al.	2012/0215610	A1	8/2012	Amaro et al.
2008/0228563	A1	9/2008	Zellner et al.	2012/0215614	A1	8/2012	Hochstatter et al.
2008/0228583	A1	9/2008	MacDonald et al.	2012/0215624	A1	8/2012	Ramer et al.
				2012/0215638	A1	8/2012	Bennett et al.
				2012/0221446	A1	8/2012	Grigg et al.
				2012/0226545	A1	9/2012	Gebb et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0226604	A1	9/2012	Isaacson et al.
2012/0239477	A1	9/2012	Cueli et al.
2012/0245987	A1	9/2012	Isaacson et al.
2012/0267432	A1	10/2012	Kuttuva
2012/0271689	A1	10/2012	Etheredge et al.
2012/0271691	A1	10/2012	Hammad et al.
2012/0271697	A1	10/2012	Gilman et al.
2012/0290950	A1	11/2012	Rapaport et al.
2012/0303425	A1	11/2012	Katzin et al.
2012/0316945	A1	12/2012	Wolf et al.
2012/0323663	A1	12/2012	Leach
2013/0006848	A1	1/2013	Kuttuva
2013/0060679	A1	3/2013	Oskolkov et al.
2013/0124278	A1	5/2013	Najm
2013/0132283	A1	5/2013	Hayhow et al.
2013/0151323	A1	6/2013	Shepard et al.
2013/0151401	A1	6/2013	Scipioni et al.
2013/0246150	A1	9/2013	Ovick et al.
2013/0282586	A1	10/2013	Ovick et al.
2014/0129310	A1	5/2014	Fordyce
2015/0088626	A1	3/2015	Salmon et al.
2015/0088633	A1	3/2015	Salmon et al.
2016/0358197	A1	12/2016	Ovick et al.

FOREIGN PATENT DOCUMENTS

KR	20010083521	A	9/2001
KR	20010096673	A	11/2001
KR	1020020050219	A	6/2002
KR	20030075916	A	9/2003
KR	20030080111	A	10/2003

KR	1020040016771	A	2/2004
KR	20040028110	A	4/2004
KR	1020040040253	A	5/2004
KR	1020040077077	A	9/2004
KR	1020050061661	A	6/2005
KR	20060101241	A	9/2006
KR	100717590	B1	5/2007
KR	20070075986	A	7/2007
KR	1020060060283	A	8/2007
KR	1020070110241	A	11/2007
KR	100836484	B1	6/2008
KR	20080102439	A	11/2008
MX	PA01013136	A	6/2004
WO	2000079461	A1	12/2000
WO	2001011512	A1	2/2001
WO	2005022342	A2	3/2005
WO	2006121541	A1	11/2006
WO	2008016923	A2	2/2008
WO	2008028154	A1	3/2008
WO	2008052073	A2	5/2008
WO	2008102935	A1	8/2008
WO	2009015222	A2	1/2009
WO	2010093893	A2	8/2010
WO	2010135642	A2	11/2010
WO	2011044137	A2	4/2011
WO	2013138756	A1	9/2013
ZA	200200475	B	6/2003

OTHER PUBLICATIONS

G. Wells Fargo, "Credit card alerts can help protect what matters to you", retrieved from <https://www.wellsfargo.com/credit-cards/alerts/> (Year: 2010).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19






FIG. 20



535

FIG. 21



537

FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32

**SYSTEMS AND METHODS TO PROVIDE A
USER INTERFACE FOR REDEMPTION OF
LOYALTY REWARDS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application is a continuation application of U.S. patent application Ser. No. 15/959,751, filed Apr. 23, 2018 and entitled "Systems and Methods to Provide a User Interface for Redemption of Loyalty Rewards", which is a continuation application of U.S. patent application Ser. No. 14/523,185, filed Oct. 24, 2014, now issued as U.S. Pat. No. 9,990,646 and entitled "Systems and Methods to Provide a User Interface for Redemption of Loyalty Rewards", which claims the benefit of provisional U.S. Pat. App. No. 61/895,269, filed Oct. 24, 2013 and entitled "Systems and Methods to Provide a User Interface for Redemption of Loyalty Rewards," the disclosures of which are hereby incorporated herein by reference.

The present application relates to U.S. patent application Ser. No. 14/494,986, filed Sep. 24, 2014 and entitled "Systems and Methods to Redeem Loyalty Rewards during Payment Transactions", U.S. patent application Ser. No. 14/495,107, filed Sep. 24, 2014 and entitled "Systems and Methods to Reserve and Release Rewards for Redemption during Payment Transactions", U.S. Pat. App. Pub. No. 2013/0282586, entitled "Systems and Methods to Apply the Benefit of Offers via a Transaction Handler," U.S. Pat. App. Pub. No. 2013/0246150, entitled "Systems and Methods to Apply the Benefit of Offers via a Transaction Handler," U.S. Pat. App. Pub. No. 2009/0030793, entitled "Multi-Vendor Multi-Loyalty Currency Program," U.S. Pat. App. Pub. No. 2013/0151323, entitled "Systems and Methods for Facilitating Issuance and Redemption of a Reward," U.S. Pat. App. Pub. No. 2010/0211445, entitled "Incentives Associated with Linked Financial Accounts," U.S. Pat. App. Pub. No. 2010/0211469, entitled "Point of Interaction Loyalty Currency Redemption in a Transaction," and U.S. Pat. App. Pub. No. 2011/0125565, entitled "Systems and Methods for Multi-Channel Offer Redemption" the entire disclosures of which applications are hereby incorporated herein by reference.

FIELD OF THE TECHNOLOGY

At least some embodiments of the present disclosure relate to the processing of payment transactions, such as payments made via credit cards, debit cards, prepaid cards, etc., and the redemption of the benefits of offers, such as coupons, deals, discounts, rewards, etc.

BACKGROUND

Millions of transactions occur daily through the use of payment cards, such as credit cards, debit cards, prepaid cards, etc. Payment processing systems, involving acquirer systems, issuer systems, transaction handlers to interconnect the acquirer systems and issuer systems, etc., have been developed to facilitate secure and efficient communications among parties involved in the payment transactions.

For example, U.S. Pat. App. Pub. No. 2009/0271262, published Oct. 28, 2009, discloses a first authorization request generated to include split payment data. After the first authorization request message is analyzed using a server computer, a second authorization request message is sent to a first service provider, and a third authorization request

message is sent to a second service provider, to facilitate the split payment according to the split payment data.

Offers, such as coupons, deals, discounts, rewards, etc., typically involve benefits that are provided to the recipients of the offers after the redemption requirements of the respective offers are satisfied. A typical requirement involves the purchase of a product or service relevant to the corresponding offer.

Processing payments and offers using substantially separate systems have drawbacks, such as inefficient use of computation resources for security measures and processing, duplicative allocation of computation resources for the separate systems, time delay from the time when redemption requirements of offers are satisfied and the completion of the provisioning of the benefits of the offers, etc.

Some systems have been developed to at least partially integrate the payment processing and the offer processing. For example, U.S. Pat. App. Pub. No. 2011/0125565, published May 26, 2011, discloses a system to associate an offer with an account of a user in a data warehouse, in which a transaction handler is configured to identify a payment transaction in the account for a purchase eligible for the redemption of the offer. If the payment transaction is identified, the transaction handler provides the benefit of the offer to the account of the user via statement credits. For example, U.S. Pat. App. Pub. No. 2009/0112721, published Oct. 28, 2009, discloses a Value-Added Service Engine programmed to determine a benefit associated with a product after receiving transaction information identifying the product and after communicating with a supplier of the product.

U.S. Pat. App. Pub. No. 2010/0312626, published Dec. 9, 2010, discloses a transaction handler configured to receive an authorization request for a discount associated with an electronic coupon for a purchase. The electronic coupon has been received by the merchant to give the discount on a purchase by a consumer. The discount is to be debited from the sponsor account and credited to an account of the merchant.

U.S. Pat. App. Pub. No. 2011/0047019, published Feb. 24, 2011, discloses a transaction handler configured to forward a coupon authorization request message, identifying a sponsor account and a coupon, from a merchant's acquirer to a sponsor account's issuer, and when the coupon is eligible, to forward the corresponding authorization response from the issuer to the acquirer.

U.S. Pat. App. Pub. No. 2008/0133351, published Jun. 5, 2008, discloses a "Method and Apparatus for Reward Messaging, Discounting and Redemption at the Point of Interaction," in which, upon determining that the transaction is eligible for a discount, the authorization request message is updated to indicate that it is a discount transaction, and this updated authorization request message is then forwarded to the issuer (or issuer processor) for authorization. When a promo code is used by the POS terminal or merchant system to apply or calculate a discount amount at the point of interaction, the full transaction price may be authorized by the issuer, and full transaction price less the discount amount is then cleared and settled between the acquirer and the issuer after the transaction. When a promo code is not used, the authorization system forwards an authorization request message to the issuer for the purchase amount less the discount.

U.S. Pat. App. Pub. No. 2007/0011044, published Jan. 11, 2007, discloses a host system configured to transmit an authorization request to a credit provider. After discounts available for application to the transaction are identified with

the host system and from the identifier of a credit instrument, a modified transaction having a total transaction cost reduced by application of at least one of the separate discounts is coordinated between the host system and the merchant.

U.S. Pat. No. 8,332,290, issued Dec. 11, 2012, discloses transmitting a redemption alert to a customer based on information regarding a transaction associated with a financial account of the customer. A respond of the customer to the redemption alert may include an instruction to use a portion of the rewards balance of the customer to pay for the transaction.

U.S. Pat. App. Pub. No. 2008/0133350, published Jun. 5, 2008, discloses that in response to a request from a customer to redeem reward points for a portion of the purchase amount, a determination is made that the customer has sufficient reward points for the portion of the purchase amount; and then, an updated purchase amount reduced by the portion of the purchase amount is calculated.

The disclosures of the above discussed patent documents are hereby incorporated herein by reference.

The present application includes systems and methods configured to further improve the overall system performances, including interoperability, transaction integrity, efficiency in processing payments in combination with offers, time delay in processing, resource allocation, etc.

BRIEF DESCRIPTION OF THE DRAWINGS

The embodiments are illustrated by way of example and not limitation in the figures of the accompanying drawings in which like references indicate similar elements.

FIG. 1 illustrates a system to provide services based on transaction data according to one embodiment.

FIG. 2 illustrates the generation of an aggregated spending profile according to one embodiment.

FIG. 3 shows a method to generate an aggregated spending profile according to one embodiment.

FIG. 4 shows a system to provide information based on transaction data according to one embodiment.

FIG. 5 illustrates a transaction terminal according to one embodiment.

FIG. 6 illustrates an account identifying device according to one embodiment.

FIG. 7 illustrates a data processing system according to one embodiment.

FIG. 8 shows the structure of account data for providing loyalty programs according to one embodiment.

FIG. 9 shows a system to obtain purchase details according to one embodiment.

FIG. 10 shows a system to automate the processing of offers in response to purchases made in various channels according to one embodiment.

FIGS. 11-14 illustrate user interfaces for multi-channel offer redemption according to one embodiment.

FIG. 15 illustrates a notification of offer redemption according to one embodiment.

FIG. 16 illustrates a method for offer redemption according to one embodiment.

FIGS. 17-21 illustrate screen images of a user interface for offer redemption according to one embodiment.

FIG. 22 shows an example to send a mobile message when an offer is saved according to one embodiment.

FIG. 23 shows a system to apply a discount offer via an authorization request according to one embodiment.

FIG. 24 shows a system to apply a discount offer via an authorization response according to one embodiment.

FIG. 25 shows a system to provide the benefit of an offer according to one embodiment.

FIG. 26 shows a method to provide the benefit of an offer according to one embodiment.

FIG. 27 shows a system to apply the benefit of an offer via a transaction handler according to one embodiment.

FIG. 28 shows a method to process a transaction according to one embodiment.

FIG. 29 shows a system to process loyalty redemption as part of the processing of a payment transaction according to one embodiment.

FIG. 30 shows a method to process loyalty redemption as part of the processing of a payment transaction according to one embodiment.

FIG. 31 shows a system to provide a user interface for the confirmation of loyalty redemption details according to one embodiment.

FIG. 32 shows a method to provide a user interface for the confirmation of loyalty redemption details according to one embodiment.

DETAILED DESCRIPTION

Introduction

In one embodiment, a transaction handler is configured to determine whether a transaction in a payment account, as identified in an authorization request, received from an acquirer processor for the transaction, is eligible for the benefit of an offer associated with the payment account, and if so, split the transaction originally requested in the payment account into two or more transactions with an issuer processor of the payment account and one or more sponsor processors of the offer to apply the benefit of the offer to the authorization request for the transaction requested. The two or more transactions are combined for the transaction terminal of the merchant and/or the acquirer processor, such that the details of the two or more transactions are insulated from the transaction terminal and/or the acquirer processor. Thus, a conventional transaction terminal and/or a conventional acquirer processor can be used in the system configured to apply the benefit of an offer during the processing of a transaction initiated and completed at the transaction terminal. Further details and examples are provided in the section entitled "SPLIT TRANSACTION."

In one embodiment, a portal is configured to receive information about loyalty rewards earned by a user of a consumer account. In response to a payment transaction in the consumer account, the transaction handler is configured to determine, in an automated way, loyalty reward redemption details applicable to the payment transaction in the consumer account of the user. The loyalty reward redemption details are determined based on the preferences of the user on redemption of the loyalty rewards and in accordance with the rules of the loyalty rewards specified by the sponsors and/or merchants involved in the loyalty rewards. Thus, the loyalty currencies earned by the user can be applied to payment transactions of the user during the processing of the payment transactions. Further details and examples are provided in the section entitled "LOYALTY CURRENCY REDEMPTION."

In one embodiment, the portal is configured to communicate with a user device, such as a mobile phone, a tablet computer, a personal media player, a personal digital assistant, etc. to provide an optional user interface that allows the user to optionally confirm and/or modify the loyalty reward redemption details initially computed for the user based on

the rules and preferences stored in connection with the consumer account of the user. Further details and examples are provided in the section entitled “REDEMPTION CONFIRMATION AND ADJUSTMENT.”

To facilitate offer redemption via the split-transaction technique as identified above, data associating offers with account information identifying the consumer accounts or payment accounts of the users can be stored in a data warehouse coupled with the transaction handler. For example, in one embodiment of associating offers with consumer/payment accounts, a portal of the transaction handler is configured to store data representing offers, and to associate user selected offers with the financial accounts of the respective users, if the users select advertisements containing the offers. When the financial accounts are used to make payments processed by the transaction handler for purchases that satisfy the respective redemption conditions of the offers, the transaction handler and/or the portal are configured to detect such payment transactions and fulfill the offers in an automated way, such as in the embodiment of the split-transaction identified above.

For example, the advertisement providing the offer can be configured to have multiple selectable regions when the advertisement is presented in a web browser of a user. Examples of offers include discounts, incentives, rebates, coupons, rewards, cash back, etc. One of the selectable-regions contains a Uniform Resource Locator (URL) of the advertiser or merchant, which, when selected, directs the user to the website of the advertiser or merchant. A separate one of the selectable regions contains a Uniform Resource Locator (URL) of the portal of the transaction handler, which, when selected, directs the user to the portal for access to a user interface to register the offer with a financial account of the user. Examples of financial accounts of users include credit card accounts, debit card accounts, prepaid card accounts, bank accounts, etc. Some details and examples about associating offers with financial accounts are provided in the section entitled “OFFER REDEMPTION.”

After the offer is associated with the financial account of the user, the transaction handler and/or the portal are configured to detect that the user is making a payment using the financial account for a purchase that satisfies the redemption requirements of the offer. In response to the detection, the portal may optionally notify the user of the eligibility of the redemption of the offer using a communication reference associated with the financial account, and the transaction handler and/or the portal are configured to automate the processing of the offer for redemption, such as using the split-payment embodiment identified above, or via statement credits to the financial account of the user, or via benefits afforded via a loyalty program, such as reward points, loyalty points, etc. Some details and examples about offer fulfillment operations are provided in the section entitled “OFFER REDEMPTION.”

When an offer is sponsored by the merchant, the transaction handler can be configured in one embodiment to apply the benefit of the registered offer during the authorization and/or settlement of the transaction that meets the requirement for the redemption of the offer via modifying the transaction amount. For example, the authorization amount can be changed by the transaction handler to provide the benefit of the registered offer during the authorization phase of the transaction in one embodiment, and the settlement amount can be changed by the transaction handler to provide the benefit of the registered offer during the settlement phase of the transaction in another embodiment. Some

details and examples about redeeming offer benefits via modifying transaction amounts are provided in the section entitled “APPLY OFFER.”

Since the transaction handler records the transaction data for transactions made in various purchase channels, such as online marketplaces, offline in retail stores, phone orders, etc., the registered offer can be redeemed in an automated way, without being limited by the channel used to make the purchase and limited by the context of the purchase. Thus, the system provides a normalized, real-time, online and offline, redemption service for offers in combination with, and integrated with, the processing of payment transactions.

The transaction data, such as records of transactions made via credit accounts, debit accounts, prepaid accounts, bank accounts, stored value accounts and the like, can be further processed to optionally provide information for various services, such as reporting, benchmarking, advertising, content or offer selection, customization, personalization, prioritization, etc. In one embodiment of improving privacy protections, users are required to enroll in a service program and provide consent to allow the system to use related transaction data and/or other data for the related services, and the system is configured to provide the services while protecting the privacy of the users in accordance with the enrollment agreement and user consent.

For example, based on the transaction data, an advertising network in one embodiment is provided to present personalized or targeted advertisements/offers on behalf of advertisers. A computing apparatus of, or associated with, the transaction handler uses the transaction data and/or other data, such as account data, merchant data, search data, social networking data, web data, etc., to develop intelligence information about individual customers, or certain types or groups of customers. The intelligence information can be used to select, identify, generate, adjust, prioritize, and/or personalize advertisements/offers to the customers. The transaction handler may be further automated to process the advertisement fees charged to the advertisers, using the accounts of the advertisers, in response to the advertising activities.

Split Transaction

FIG. 27 shows a system to apply the benefit of an offer (186) via the transaction handler (103) according to one embodiment. In FIG. 27, after the transaction handler (103) (e.g., as in a payment processing system illustrated in FIG. 4) receives an authorization request (168) from an acquirer processor (147) associated with the transaction terminal (105) of a merchant, the transaction handler (103) determines whether there is an offer (e.g., 186) that is applicable to the transaction requested by the authorization request (168) in a payment account that is issued to a user and identified by account information provided in the authorization request (168). If there is an offer (e.g., 186) that has a benefit applicable to the transaction, the transaction handler (103) is configured to generate a plurality of authorization requests (e.g., 641, 645) in accordance with the original authorization request (168) received from the acquirer processor (147) and the offer (186) stored in the data warehouse (149), in association with the account information (142), as identified in the original authorization request (168). The plurality of authorization requests (e.g., 641, 645) are generated by and transmitted from the transaction handler (103) for a plurality of transactions, which, when combined, correspond to the original transaction requested by the authorization request (168) received from the acquirer processor (147). When the plurality of authorization requests (e.g., 641, 645) are approved, a message

can be optionally transmitted by a portal (143), coupled with the data warehouse (149) and/or the transaction handler (103), using the communication reference (611) stored in the data warehouse (149) in association with the account information (142). The message is transmitted to a communication device of the user (101) to inform the user (101) of the benefit that is applied to the transaction requested by the transaction terminal (105). When the plurality of authorization requests (e.g., 641, 645) are approved, the transaction handler (103) provides a single authorization response (138) responsive to the original authorization request (168) to the acquirer processor (147). Thus, the details of the plurality of transactions generated from the original authorization request (168) are shielded from the acquirer processors (147) and/or the transaction terminal (105), such that a conversational acquirer processor (147) and/or a conversational transaction terminal (105) can also be used in the system for the combined processing of payment transaction and benefit redemption. Thus, the interoperability of the combined payment and offer benefit processing system is improved for existing infrastructure of acquirer processors and/or transaction terminals.

In FIG. 27, the offer (186) is stored in the data warehouse (149) in association with the account information (142) of the payment account (e.g., consumer account (146) illustrated FIG. 4) of the user (e.g., 101 illustrated in FIG. 1). The association of the offer (186) with the account information (142) allows the offer (186) to be applied to transactions while the transactions are being processed by the transaction handler (103). Such an arrangement allows the reduction of processing time delay between the time at which redemption requirements of the offer (186) are satisfied and the time at which the benefit of the offer (186) is provided, and/or the time the redemption of the benefit of the offer (186) is communicated to the respective user (e.g., 101).

In FIG. 27, since the transaction handler (103) processes the plurality of transactions concurrently, via the transmission of the authorization requests (e.g., 641, 645) and the reception of the authorization response (e.g., 643, 647) for the respective transactions, the processing time delay is further reduced.

Further, in FIG. 27, since the generation of the plurality of transactions and combination of the plurality of transactions are arranged between the reception of the original authorization request (168) from the acquirer processor (147) and the transmission of the respective authorization response (138) back to the acquirer processor (147), the payment transaction and the benefit redemption and application would both be approved, or rejected as a whole. Thus, the integrity of the combined transaction and benefit redemption is improved.

In FIG. 27, the centralized processing of payment transaction and offer benefit redemption allows improved computation resource allocation and improved computation efficiency, when compared with implementations that require separate systems for payment processing and offer redemption, or compared with implementations that require add-on features in the acquirer processors and/or the transaction terminals.

In FIG. 27, in one embodiment of determining whether the original authorization request (168) has an applicable offer (e.g., 186), a trigger record (613) is used. A trigger record (e.g., 613) is configured to identify a standardized set of requirements to be satisfied by the authorization request (168) to trigger an action identified in the trigger record (613). For the determination of whether the benefit of the offer (186) identified by the trigger record (613) is applicable

to the authorization request (168), the trigger record (613) for the offer (186) is generated to specify a subset of redemption requirements of the offer (186), selected in accordance with the standardized set predetermined for the trigger records, and the trigger record (613) for the offer (186) further identifies an action to process the offer (186) if the requirements specified in the trigger record (613) are satisfied.

Since requirements used in the trigger records (613) are in the standardized set, the operation of the transaction handler (103) in determining whether an action requested in the trigger record (613) is triggered by the authorization request (168) can be optimized for performance improvement, while supporting a variety of diverse services corresponding to actions that can be specified in trigger records (e.g., 613), such as the processing of the benefit redemptions of different offers that may have diverse redemption requirements. The use of the standardized set of requirements for trigger records (613) can reduce and limit the performance impact on the transaction handler (103) in processing payment transactions, since not all requirements are initially examined by the transaction handler (103) and the standardization permits optimized operation efficiency.

In FIG. 27, the trigger record (613) is generated for the transaction handler (103) to monitor transactions processed by the transaction handler (103) for the detection of transactions relevant to the offer (186). The trigger record (613) includes a set of conditions to match against transactions that are processed by the transaction handler (103). When the conditions specified in the trigger record (613) are not satisfied by a transaction, the transaction is not relevant to the offer (186). When a transaction satisfies the conditions specified in the trigger record (613), the trigger record (613) further identifies a task to process the offer (186). The task includes determining whether all redemption requirements of the offer (186) have been met; and if so, providing the benefit of the offer (186) to the transaction, such as via the generation of the multiple authorization requests (e.g., 641, 645) which, when combined, correspond to the original authorization request (168). Thus, the trigger record (613) allows the transaction handler (103) to trigger actions to process the offer (186) while reducing the burden on the transaction handler (103) in processing transactions not applicable to the offer (186), thus improving the overall efficiency of the transaction handler (103) in processing transactions that may or may not be relevant to offers (e.g., 186) in general.

The system illustrated in FIG. 27 allows a conventional transaction terminal (105) and/or a conventional acquirer processor (147) to be used to initiate a conventional authorization request (168), while the redemption of the benefit of the offer (186) can still be applied to the transaction when the redemption requirements are satisfied by the transaction identified by the conventional authorization request (168).

Further, the system as illustrated in FIG. 27 allows the benefit of the offer (186) to be applied to a transaction initiated at the transaction terminal (105) before the transaction is approved at the acquirer processor (147) and the transaction terminal (105).

In FIG. 27, the transaction terminal (105) initiates the transaction via transmitting an authorization request (168) to the acquirer processor (147), which propagates the authorization request (168) to the transaction handler (103). The transaction handler (103) is configured to match the transaction against applicable trigger records (e.g., 613) to determine if a further action is to be triggered for the transaction corresponding to the authorization request (168). Although

FIG. 27 illustrates the use of the trigger records (e.g., 613) to identify applicable offers (e.g., 186) for incoming authorization requests (e.g., 168), the transaction handler (103) may process the offers (186) directly in alternative implementations without the use of the trigger records (e.g., 613).

In FIG. 27, if the authorization request (168) satisfies the conditions of the trigger record (613), the transaction handler (103) is configured to process the offer (186) identified by the matching trigger record (613).

The offer (186) specifies a set of conditions, which, when satisfied, allow a benefit sponsored by the sponsor processor (649) to be applied to the respective transaction. Thus, when the authorization request (168) satisfies the trigger record (613) generated for the offer (186), the transaction handler (103) and/or the portal (143) (or a separate processor coupled with the transaction handler (103)) is configured to determine whether the entire set of the conditions of the offer (186) is satisfied for the award of the benefit to the respective transaction, in view of the authorization request (168) received from the acquirer processor (147).

If the benefit of the offer (186) is determined to be applicable to the transaction corresponding to the authorization request (168), the transaction handler (103) communicates an authorization request (645) to the sponsor processor (649) for the authorization of an amount to be applied to the transaction initiated on the transaction terminal (105), and separately communicates an authorization request (641) to the issuer processor (145) for the authorization of an amount from the consumer account (146) identified via the account information (142) submitted by the transaction terminal (105) to initiate the respective transaction.

In one embodiment of the generation of the authorization requests (e.g., 641, 645), the transaction handler (103) (or the portal (143), or a separate processor coupled with the transaction handler (103)) is configured to determine the transaction amounts for the authorization requests (645 and 641) based on the transaction amount requested in the authorization request (168) received from the acquirer processor (147) and the benefit specified in the offer (186).

In FIG. 27, the transaction amount in the authorization request (645) to the sponsor processor (649) corresponds to the benefit of the offer (186), which may be a fixed amount that is independent of the transaction amount requested in the authorization request (168) received from the acquirer processor (147), or a predetermined percentage of the transaction amount requested in the authorization request (168) received from the acquirer processor (147).

In FIG. 27, the transaction amount in the authorization request (641) to the issuer processor (145) corresponds to the difference between the transaction amount requested in the authorization request (168) received from the acquirer processor (147) and the benefit of the offer (186) that corresponds to the transaction amount in the authorization request (645) to the sponsor processor (649).

Thus, the transaction handler (103) effectively splits the transaction corresponding to the authorization request (168) received from the acquirer processor (147) into two transactions corresponding to the authorization requests (641 and 645) to the issuer processor (145) and the sponsor processor (649), respectively.

FIG. 27 illustrates an example of an offer (186) that is sponsored by a sponsor processor (649). The technique can be extended to the processing of an offer (186) that is sponsored by a plurality of sponsor processors (e.g., 649). The transaction handler (103) can be configured to split the transaction corresponding to the authorization request (168) received from the acquirer processor (147) into multiple

transactions corresponding to the authorization requests to the issuer processor (145) and the sponsor processors (e.g., 649) respectively.

In FIG. 27, the transaction handler (103) is configured to identify the issuer processor (145) based on the account information (142) identified in the authorization request (168) received from the acquirer processor (147), and to identify the sponsor processor (649) based on the offer (186) that is associated with the account information (142) and identified via the trigger record (613).

In FIG. 27, after the transaction handler (103) receives the authorization responses (647 and 643) from the sponsor processor (649) and the issuer processor (145), respectively, for the authorization requests (645 and 641), the transaction handler (103) is configured to combine the authorization responses (647 and 643) received from the sponsor processor (649) and the issuer processor (145), respectively, to generate an authorization response (138) to the acquirer processor (147), which further propagates the authorization response (138) to the acquirer processor (147) and the transaction terminal (105).

Since the authorization responses (647 and 643) are combined by the transaction handler (103) to generate a single authorization response (138) for the acquirer processor (147), the implementation details of the application of the offer (186) are separate from the transaction terminal (105), and thus a conventional transaction terminal (105) can be used to apply the benefit of the offer (186) to the eligible transaction, without a need for modification in hardware and/or software. The transaction terminal (105) submits the transaction authorization request (168) and receives the authorization response (138), as if the transaction were processed using the consumer account (146), as identified by the account information (142), and as if the transaction were processed without the involvement of the offer (186) and/or the sponsor processor (649).

The transaction terminal (105) of one embodiment has no information about the application of the benefit of the offer (186) to the transaction initiated and approved on the transaction terminal (105). The transaction terminal (105) thus produces a receipt, which may be interpreted to indicate that the entire transaction amount is funded by the consumer account (146) identified by the account information (142). To inform the user (101) of the applicable benefit of the offer (186), the portal (143) is configured to generate and send a message to the point of interaction (107) (e.g., a mobile phone, a mobile computer, a personal media player, a personal digital assistant, a tablet computer, a digital wallet, a social networking site, an email inbox, etc.) identified by the communication reference (611) associated with the account information (142) of the user (101).

For example, a text message is transmitted in accordance with the communication reference (611) to a mobile phone of the user (101) to inform the user (101) of the application of the benefit of the offer (186) to the transaction initiated and approved on the transaction terminal (105). Alternatively or in combination, the notification about the awarded/redeemed benefit of the offer (186) can be transmitted via an email message, a web-based message, a voice message, etc.

The portal (143) of one embodiment is configured to transmit the notification message about the award/redemption of the benefit of the offer (186) in response to the authorization responses (641 and 645) from the issuer processor (145) and the sponsor processor (649), prior to or in parallel with the transmission of the authorization response (138) to the acquirer processor (147). Thus, the transmission of the notification is substantially concurrent with the propa-

gation of the authorization of the transaction to the transaction terminal (105). As a result, the delay to the user reception of the notification is reduced.

The transaction handler (103) is configured in one embodiment to further settle the transactions corresponding to the authorization responses (643 and 647) from the issuer processor (145) and the sponsor processor (649) to effectively complete the transaction corresponding to the authorization response (138) to the acquirer processor (147).

FIG. 27 illustrates the use of a sponsor processor (649) to apply the benefit of the offer (186). In general, a plurality of sponsor processors (e.g., 649) can be used when the offer (186) is sponsored by a plurality of entities. In some examples of the offers (186), the sponsor processor (649) may be the same as the issuer processor (145) (e.g., when the benefit is sponsored by the issuer). In some examples, the sponsor processor (649) is connected to a computing system of the merchant (e.g., when the benefit is sponsored by the merchant).

FIG. 27 illustrates an embodiment in which the transaction handler (103), interconnecting acquirer processors (e.g., 147) and issuer processors (e.g., 145) in a payment communications network, is configured to split the authorization requests in view of applicable offers and combine corresponding authorization responses generated from splitting such operations; the technique can be extended to implementing such operations on other components on a payment communications network, such as a payment processor interconnecting transaction terminals and acquirer processors and/or transaction handlers of different payment communications networks, an acquirer processor interconnecting transaction terminals and transaction handlers of different payment communications networks, etc.

FIG. 28 shows a method to process a transaction according to one embodiment. For example, the method as shown in FIG. 28 can be implemented in the system shown in FIG. 27, or modified systems as discussed above.

In FIG. 28, a computing device is configured to store (651) data associating an offer (186), sponsored by a sponsor account administrated by a sponsor processor (649), with a consumer account (146) that is under control of an issuer processor (145) and associated with a communication reference (611). The offer (186) may be sponsored by more than one sponsor account administrated by more than one sponsor processor connected in a payment communications network interconnected by a transaction handler (e.g., 103).

In FIG. 28, after the computing device receives (653) an authorization request (168) for a first transaction amount in the consumer account (146) from an acquirer processor (147), the computing device determines (655) whether the offer (186) is applicable to the first transaction amount, and if not, communicates (659) with the issuer processor (145) to obtain an authorization response (643) for the first transaction amount without contacting the sponsor processor (649).

If the offer (186) is applicable (655) to the first transaction amount, the computing device is configured to determine (657) a second transaction amount applicable to the consumer account (146) according to the offer (186) and the first transaction amount, and determine (671) a third transaction amount applicable to a sponsor account according to the offer (186). The computing device communicates (673) with the sponsor processor (649) to obtain an authorization response (647) for the third transaction amount, and communicates (659) with the issuer processor (145) to obtain an authorization response (643) for the second transaction amount.

If the computing device determines (661) that the offer (186) is applicable to the authorization request (168) received from the acquirer processor (147), the computing device is configured to combine (663) the responses (641 and 647) from the issuer processor (145) and the sponsor processor (649) to generate the authorization response (138) to the acquirer processor (147), and transmit (669) a notification about the benefit of the second transaction amount afforded by the offer (186), using the communication reference (611).

If the computing device determines (661) that the offer (186) is not applicable to the authorization request (168) received from the acquirer processor (147), the computing device is configured to generate (665) the authorization response (138) based on the authorization response (643) from the issuer processor (145).

The computing device communicates (667) the authorization response (138) for the first transaction amount to the acquirer processor (147), as a response to the authorization request (168) received from the acquirer processor (147).

Since the transaction terminal (105) is arranged to process the transactions that may or may not involve the redemption of the benefit of the offers (e.g., 186) in a conventional way, the system can be used with conventional transaction terminals (e.g., 105) without modification.

Preferably, the authorization requests (e.g., 168, 641, 645) and the authorization responses (e.g., 138, 643, 647) are in accordance with existing standards, and thus the system can be used with existing acquirer processors (e.g., 147) and issuer processors (e.g., 145) without modifications.

The computing device of one embodiment includes at least one of: the data warehouse (149), the transaction handler (103), and the portal (143). For example, the warehouse (149) is configured to store data associating the offer (186), the account information (142), and the communication reference (611), as illustrated in FIG. 27; the transaction handler (103) is configured to detect the authorization request (168) that has a corresponding applicable offer (186), to split the authorization request (168) to generate multiple authorization requests (641, 645), and combine respective authorization responses (643, 647); and the portal (143) is configured to transmit a notification of the application of the benefit of the offer (186) to a point of interaction (107) identified by the communication reference (611) after the respective authorization responses (643, 647) are received.

The computing device can be implemented using one or more data processing systems as illustrated in FIG. 7, having at least one microprocessor (173) and memory (167) storing instructions configured to instruct the at least one microprocessor (173) to perform operations discussed above.

In one embodiment, the computing apparatus is configured, at least in part via instructions, to: receive an authorization request (e.g., 168) identifying a transaction of a first amount in an account (e.g., 146) of a user (e.g., 101); and determine, based on data (e.g., 186 and 142) stored to associate an offer with the account, whether a benefit of the offer (e.g., 186) is applicable to the transaction. In response to a determination that the benefit of the offer is applicable to the transaction, the computing apparatus is further configured to: communicate with a sponsor processor (e.g., 649) of the benefit for authorization of the benefit of a second amount; communicate with an issuer processor (e.g., 145) of the account for authorization to a third amount determined from a difference between the first amount and the second amount; and generate a third authorization response (e.g., 138) for the authorization request based on a first authori-

zation response (e.g., 647) for the second amount from the sponsor processor (e.g., 649) and a second authorization response (e.g., 643) for the third amount from the issuer processor (e.g., 145).

The authorization request (e.g., 168) may be received from an acquirer processor (e.g., 147) and the authorization response (e.g., 138) transmitted to the acquirer processor (e.g., 147) as a response to the authorization request (e.g., 168), where the authorization request (e.g., 168) identifies the account (e.g., 146) as a single source of payment for the transaction.

If the authorization request (168) is referred to as a third authorization request, in communicating with the sponsor processor (649) the computing apparatus is configured in one embodiment to transmit to the sponsor processor (649) a first authorization request (645) identifying the benefit and receive the first authorization response (647); and in communicating with the issuer processor (145) the computing apparatus is configured to transmit to the issuer processor (145) a second authorization request (641) identifying a second transaction amount in the account and receive the second authorization response (643).

If the third authorization request (168) identifies a third transaction amount in the account, the computing apparatus is configured in one embodiment to determine the second transaction amount by reducing the third transaction amount according to the benefit of the offer.

In one embodiment, the third authorization response (138) is generated to approve the transaction, if the first authorization response (647) approves the benefit and the second authorization response (643) approves the second transaction amount in the account; and the third authorization response (138) is generated to reject the transaction, if the first authorization response (647) rejects the benefit or the second authorization response (643) rejects the second transaction amount in the account.

When the benefit of the offer (186) of one embodiment is controlled by multiple sponsor processors, in response to the determination that the benefit of the offer is applicable to the transaction, the computing apparatus is configured to communicate with a further sponsor processor for authorization of a further benefit of the offer, in addition to communication with the sponsor processor (649); and the third authorization response (138) is generated based on a further authorization response from the further sponsor processor, the first authorization response (647), and the second authorization response (643).

The computing apparatus may optionally store a trigger record (613) identifying a first set of requirements and the offer for enhanced performance. When the trigger record (613) is used, the determining of whether the benefit of the offer is applicable to the transaction may include: determining whether the transaction satisfies the first set of requirements specified in the trigger record (613), and in response to a determination that the transaction satisfies the first set of requirements, identifying the offer based on the trigger record and determining whether a second set of requirements of the offer (186) are satisfied to qualify the transaction for the benefit.

The computing apparatus is configured in one embodiment to communicate with the sponsor processor and the issuer processor concurrently.

The computing apparatus can further store data (e.g., 611, 142) associating a communication reference with the account of the user, and transmit a notification about application of the benefit to the transaction concurrently with transmitting the third authorization response (138).

In one embodiment, a transaction amount approved in the third authorization response (138) is equal to the sum of a transaction amount approved in the first authorization response (647) and a transaction amount approved in the second authorization response (643).

For example, the computing apparatus includes a transaction handler (103) in a payment communications network interconnected by the transaction handler; and the computing apparatus uses the transaction handler (103) to communicate with the sponsor processor (649) and the issuer processor (145) using on the payment communications network.

In one embodiment, the computing apparatus includes a portal (143) to transmit a notification of a reduction in transaction amount in the account, reduced in accordance with the offer (186), to the user at a communication reference (611) associated with the account information (142) of the user (101). When the authorization request (168) is received from an acquirer processor (147), the notification can be transmitted in parallel with transmission of the third authorization response (138) to the acquirer processor (168).

In one embodiment, to determine whether the benefit of the offer (186) is applicable to the transaction, the computing apparatus is configured to: store a trigger record (613) identifying the offer (186) and a portion of requirements of the offer (186) to be satisfied by the transaction to qualify for a benefit of the offer; identifying the transaction based on matching the transaction with the portion of requirements; and after the transaction and the offer are identified via matching the trigger record with transactions, determining whether the transaction satisfies the requirements for awarding the benefit of the offer (186).

The computing apparatus has at least one processor and memory storing instructions configured to instruct the at least one processor to perform operations. For example, the computing apparatus of one embodiment includes a data warehouse (149) configured to store first data associating a communication reference (611) with an account (146) of a user and second data associating an offer (186) with the account (146) identified by the account information (142). The second data may include a trigger record (613) identifying the offer (186) and a first set of conditions that requires a transaction in the account to be satisfied. The offer (186) has a benefit applicable to a transaction satisfying a second set of conditions that includes the first set. The computing apparatus further includes a transaction handler (103) configured to process payment transactions to detect an authorization request (168) for a first transaction when the first transaction satisfies the first set of conditions specified in the trigger record (613). After the authorization request is detected, the computing apparatus identifies the offer (186) based on the trigger record (613) matching the first transaction and determines whether the second set of conditions is satisfied in view of the first transaction. If the second set of conditions is satisfied, the transaction handler is configured to communicate with a sponsor processor (649) of the benefit for authorization of the benefit, communicate with an issuer processor (145) of the account for authorization in the account, and generate a third authorization response (138) for the authorization request (168) based on a first authorization response (647) from the sponsor processor (649) and a second authorization response (643) from the issuer processor (145). The computing apparatus further includes a portal (143) configured to transmit a notification to the communication reference (611) about application of the offer to the first transaction, concurrently with transmission of the third authorization response (138).

In one embodiment, the notification is transmitted to the communication reference when the third authorization response (138) approves the first transaction; and the transaction handler (103) is configured to concurrently transmit the first authorization request (645) and the second authorization request (641).

Loyalty Currency Redemption

In one embodiment, a payment transaction initiated in a consumer account of a user is processed to include loyalty reward currency redemption from one or more loyalty reward programs. Redemption details are determined, by a transaction handler processing the authorization of the payment transaction, based on the stored preferences of the user, rules of the respective loyalty reward programs, and/or the preferences, rules and offers of the merchant involved in the payment transaction. The payment transaction in the consumer account is modified during the authorization process based on the redemption details; and transactions in the corresponding loyalty reward accounts of the user are initiated as part of the payment transaction.

In one embodiment, the transaction amount of the payment transaction that triggers the loyalty reward redemption is modified during the authorization of the payment transaction to reflect the benefit of the loyalty reward redemption, in a way similar to the modification of the payment transaction in the redemption of the benefit of the stored offer (186), as illustrated in FIGS. 23-28 and discussed in the sections entitled "APPLY OFFER" and "SPLIT TRANSACTION."

FIG. 29 shows a system to process loyalty redemption as part of the processing of a payment transaction according to one embodiment.

In FIG. 29, the data warehouse (149) is configured to store rewards information, such as reward sources (e.g., 701, . . . , 703) identifying reward accounts (725, . . . , 727) respectively.

For example, the portal (143) is configured in one embodiment to present a user interface that allows the user (101) of the consumer account (146), identified by the account information (142), to provide the reward information, including the reward sources (e.g., 701, . . . , 703) identifying reward accounts (725, . . . , 727) respectively, for association with the account information (142) identifying the consumer payment account (146). Based on the user input received in the user interface, the data warehouse (149) stores the data associating the account information (142) with the reward sources (701, . . . , 703).

In one embodiment, the reward sources (701, . . . , 703) identifies the reward accounts (725, . . . , 707) that are under the control of sponsor processors (726, . . . 728). The sponsor processors (728) maintain the balances of the reward accounts (725, . . . , 727) of the user (101) and/or have the authority to approve or reject the redemption requests.

In FIG. 29, the data warehouse (149) stores rules (e.g., 705) applicable to the redemption of the loyalty rewards accumulated in the respective reward account (e.g., 725) identified by the respective reward source (e.g., 701). The rules (e.g., 705) may include a portion specified by the sponsor of the reward account (e.g., 725), and/or a portion specified by participating merchants of the loyalty reward program relevant to the reward account (e.g., 725).

Some of the sponsor processors (e.g., 726, . . . , 728) may be operated by participating merchants, issuers of consumer payment accounts (e.g., 146), and/or third party loyalty reward vendors.

Some of the sponsor processors (e.g., 726, . . . , 728) may be a broker processor which interfaces with the transaction

handler (103) on behalf of one or more sponsors or sponsor processors of respective reward accounts such that the respective reward accounts appear to be under the control of the broker processor in a way similar to a sponsor processor actually controlling a reward account (725).

The balances of the reward accounts (725, . . . , 727) may be in various reward currencies, such as reward points, dollars, airline miles, virtual currency, reward tokens, etc. Different reward accounts (725, . . . , 727) may use different reward currencies.

In FIG. 29, the data warehouse also stores offers (e.g., 707) that are applicable to the redemption of the loyalty rewards from the respective reward account (e.g., 725) identified by the corresponding reward source (e.g., 701).

For example, the sponsor of the reward account (725) may provide an incentive to encourage the user (101) to redeem loyalty rewards from the reward account (725).

For example, a participating merchant may provide a discount to encourage the user (101) to redeem loyalty rewards from the reward account (725) for purchases made from the merchant.

For example, the operator of the transaction handler may provide a benefit to encourage the user (101) to use the reward redemption system as illustrated in FIG. 29.

An offer (707) associated with a reward source (701) can also be processed in a way as the processing of an offer (186) illustrated in FIGS. 23-28.

In FIG. 29, the data warehouse (149) further stores user preferences (e.g., 709, . . . , 719) applicable to the redemption of the loyalty rewards from the reward accounts (e.g., 725, . . . , 727) identified by the respective reward sources (e.g., 701, . . . , 703).

For example, the user (101) may specify the priority ranks of the reward accounts (e.g., 725, . . . , 727) such that redemption from a high ranking reward account (e.g., 725) is preferred over redemption from a low ranking reward account (e.g., 727), when it is possible to redeem from both accounts (e.g., 725 and 727).

For example, the user (101) may specify an upper limit and/or a lower limit for redemption amount from a specific reward account (e.g., 725). The redemption amount limit may be applicable to a single payment transaction, or transactions within a predetermined time period, such as a day, a week, or a month.

For example, the user (101) may specify a balance threshold for a reward account (e.g., 725), such that when the reward balance in the reward account (e.g., 725) is below the balance threshold, no redemption from the reward account (e.g., 725) is preferred.

For example, the user (101) may specify a balance threshold for a reward account (e.g., 725), such that when the reward balance in the reward account (e.g., 725) is above the balance threshold, the priority of redemption from the reward account (e.g., 725) is increased.

In one embodiment, the data warehouse (149) is configured to store a trigger record (613) that is configured to detect, among various payment transactions processed by the transaction handler (103), a payment transaction that may be eligible for the benefit of redeeming loyalty rewards from one or more of the reward accounts (e.g., 275, . . . , 727).

In FIG. 29, when an authorization request (168) from an acquirer processor (147) of a transaction terminal (105) of a merchant, or an authorization response (643) from an issuer processor (145) of a consumer account (146) of the user (101), is detected for a payment transaction initiated in the consumer account (146) using the account information (142)

(e.g., detected via the trigger record (613)), the rule engine (721) coupled with the data warehouse (149) is configured to identify redemption details (723) based on the rules (e.g., 705), preferences (e.g., 709, . . . , 719), and/or offers (e.g., 707) applicable to the reward sources (e.g., 701, . . . , 703) associated with the account information (142).

The redemption details (723) may include the identification of the reward account (e.g., 725) from which redemption is to be performed, and the amount of loyalty rewards to be redeemed from the identified reward account (e.g., 725).

Since the redemption details are determined by the rule engine (721), the user (101) (and/or the merchant) does not have to specify the redemption details at the transaction terminal (105).

Based on the redemption details, the transaction handler (103) is configured to adjust the transaction amount to be provided in the authorization request (641) to the issuer processor (145) for the payment transaction and/or the transaction amount in the authorization response (138) provide to the acquirer processor (147) associated with the transaction terminal (105) of the merchant, in ways similar to the adjustment of transaction amounts for the redemption of the benefit of the offer (186) in FIGS. 23-28 and discussed in the sections entitled "SPLIT TRANSACTION" and "APPLY OFFER."

The adjustment to the transaction amount includes the benefit of the redeemed loyalty rewards and the applicable offers (e.g., 707) associated with the respective reward sources (e.g., 701).

In one embodiment, when a portion of the benefits identified in the redemption details is sponsored by the merchant operating the transaction terminal (105), the portion is deducted from the transaction amount identified in the authorization request (168) received from the acquirer processor (147) to generate the transaction amount for the authorization response (138); and when none of the benefits identified in the redemption details is sponsored by the merchant operating the transaction terminal (105), the transaction amount provided in the authorization response (138) to the acquirer processor (138) is equal to the transaction amount identified in the authorization request (168) received from the acquirer processor (147).

The sponsor processors (e.g., 726, . . . , 728) are configured to reimburse the merchant for the redeemed benefits; and the transaction handler (103) is configured to combine the reimbursements from the sponsor processors (e.g., 726, . . . , 728) and the transaction amount from the consumer account (146) to settle the transaction requested by original authorization request (168).

The transaction amount in the authorization request (641) in the consumer account is generated from deducting, from the transaction amount identified in the authorization request (168) received from the acquirer processor (147), the benefits identified in the redemption details (723). Thus, the transaction in the consumer account (146) is accurate in reflecting the benefits identified in the redemption details, without the need for a subsequent credit to the consumer account (146).

Thus, the system as illustrated in FIG. 28 integrates the process of the redemption of loyalty rewards from one or more reward accounts (e.g., 725, . . . , 727) of the user (101) within the processing of a payment transaction initiated in the consumer account (146), based on various preferences and rules of the user, merchants, loyalty programs, and point

identifies applicable loyalty currency sources, and obtain balance information and/or redemption authorization to formulate the redemption details (723) to apply available loyalty currencies to the transaction.

In one embodiment, the reward sources (e.g., 701, . . . , 703) are stored in association with account information (142) of a plurality of consumer accounts (e.g., 146) of the user (101), such that the user (101) may use any of the consumer accounts (e.g., 146) to trigger the redemption.

In one embodiment, the rule engine (721) is configured to optimize the redemption details (723) to maximize the benefit to the user (101).

Further, when the account information (142) identifies multiple consumer accounts (142), the redemption details (723) may include the identification of one or more desirable consumer accounts (e.g., 146), which may be different from the consumer account used on the transaction terminal (105) to initiate the payment transaction, such that one or more portions of the payment transactions are charged to the identified one or more desirable consumer accounts (e.g., 146) to maximize the benefit to the user (101), and/or manage the balances of the consumer accounts.

In one embodiment, the authorization request (e.g., 645) to a sponsor (726) may or may not specify a redemption amount; and the authorization response (647) from the sponsor processor (726) identifies a balance of the reward account (725) that may be redeemed for the payment transaction. The rule engine (721) is configured to use the balance information received in the authorization responses (647) received from the sponsor processors (e.g., 726, . . . , 728).

In one embodiment, after the redemption details are determined by the rule engine (721), the transaction handler (103) is configured to communicate with the sponsor processors (e.g., 726, . . . , 728) to reserve loyalty currencies to be redeemed from the reward accounts (e.g., 725, . . . , 727) for the payment transaction and/or release loyalty currencies not used for the payment transaction.

For example, after the redemption amount is determined for the reward account (725), the transaction handler (103) is configured to communicate the redemption amount to the sponsor processor (726) to reserve the correct amount of loyalty reward currency for the payment transaction.

In one embodiment, the redemption details (723) identifies a sequence for redeeming from the reward accounts (725); and the transaction handler (103) is configured to communicate with the sponsor processor (e.g., 726, . . . , 728) sequentially according to the identified sequence.

For example, the transaction handler (103) is configured to communicate with the current sponsor processor (e.g., 726) to determine a redeemed amount from the corresponding reward account (e.g., 725); and if the sum of the redeemed amount from the corresponding reward account (e.g., 725) and the redeemed amounts already determined for other accounts, if any, is less than the transaction amount requested in the authorization request (168) from the acquirer processor (147), the transaction handler (103) is configured to communicate with the next sponsor processor (e.g., 728) to determine a redeemed amount from the next corresponding reward account (e.g., 727). The process can be repeated until the sum of determined redeemed amount(s) (and the benefit of the applicable offers (e.g., 707)) satisfies the authorization request (168) from the acquirer processor (147), or no further reward account is available to cover a balance between the transaction amount requested by the authorization request (168) and the sum of the redeemed amount(s) (and the benefit of the applicable offers (e.g., 707)). The balance is then charge to the consumer account

(146) via the authorization request (641) transmitted to the issuer processor (145), which may provide the authorization response (643).

In one embodiment of the sequential processing of the redemption from reward accounts (e.g., 725, . . . , 727) in connection with the payment transaction in the consumer account (146), the transaction handler (103) is configured to provide, to the acquirer processor (147), a partial authorization response for each determined redemption amount, such that the transaction terminal (105) may process the progress of the sequential redemption in a split-tender fashion. For example, when the redemption from the current reward account (725) is determined and authorized, the transaction handler (103) provides a partial authorization response (138) to the transaction terminal (105) via the acquirer processor (147), which causes the transaction terminal (105) to accept the redeemed amount as a partial payment, and optionally generate a subsequent updated authorization request for the remaining amount of the transaction in the consumer account (146).

The partial authorization response reduces the time gap between the authorization request initiated by the transaction terminal (105) and any response received by the transaction terminal (105) and thus reduces the chances of timeout (e.g., the transaction terminal (105) fails to receive a response to an authorization request within a predetermined period of time).

Further, the partial authorization response can be configured to identify the reward account (e.g., 725) from which the redemption of the loyalty reward is successful and the amount of redemption. Thus, the merchant and/or the user (101) is informed of the progress of the redemption and/or payment processing.

In one embodiment, the partial authorization response may optionally identify the redemption detail for the next reward account, such as an identification of the next reward account (e.g., 728), and/or a proposed redemption amount. The user (101) may be provided a user interface to optionally modify the redemption detail, by specifying a redemption amount desired by the user (101), rejecting the proposed redemption for the next reward account (e.g., 728), etc. The transaction terminal (105) may communicate the user input via the subsequent, updated authorization request (e.g., 168), or via a separate communication connection to the portal (143) (e.g., through Internet).

In one embodiment, the partial authorization response (138) may optionally identify an offer (707) for approval by the merchant operating the transaction terminal (105).

Alternatively, the transaction handler (103) can be configured to communicate with the sponsor processors (726, . . . , 728) of the reward accounts (725, . . . , 728) and/or the issuer processor (145) of the consumer account (146) in parallel.

For example, the authorization requests (e.g., 645) to the sponsor processors (726) can be used to query for the available balance for application the payment transaction; and based on the balance information received in the authorization responses (e.g., 647) provided by the sponsor processor (e.g., 726, . . . , 728), the rule engine (721) is configured to determine actual redemption amounts from each of the reward accounts (e.g., 725, . . . , 727).

For example, the authorization responses (e.g., 645) to the sponsor processors (726) can be used to request authorization of redemption amounts according to the redemption details (723) preliminarily determined by the rule engine (721); and the sponsor processors (726, . . . , 728) are configured to provide the approved amounts in the respec-

tive authorization responses (e.g., 647). Based on the approved amounts identified by the sponsor processor (e.g., 726, . . . , 728), the rule engine (721) is configured to determine actual redemption amounts from each of the reward accounts (e.g., 725, . . . , 727).

The transaction handler (103) is configured in one embodiment to further communicate with the sponsor processors (e.g., 726, . . . , 728) to release the reservation of the balance between the approved amounts and the actual redemption amounts, prior to the settlement of the redemption transactions.

Alternatively, the transaction handler (103) may skip the communication regarding the releasing of the reservation of the balance between the approved amounts and the actual redemption amounts, and communicate with the sponsor processors (e.g., 726, . . . , 728) to settle the redemption transactions according to the actual redemption amounts calculated by the rule engine (721).

In one embodiment, the transaction handler (103) may process some of the authorization requests (e.g., 647, 643) in parallel and some of the authorization requests (e.g., 647, 643) sequentially.

FIG. 30 shows a method to process loyalty redemption as part of the processing of a payment transaction according to one embodiment.

In FIG. 30, a computing apparatus is configured to store (731) a user profile (e.g., including reward sources (701, . . . , 703), preferences (709, . . . , 719)) identifying reward accounts (725, . . . , 727) of a user (101) having a consumer payment account (146); detect (733) an authorization request (168) for a payment transaction in the payment account (146); compute (735) amounts of loyalty rewards redeemed from the reward accounts (725, . . . , 727); obtain (737) authorizations for the redemption of the computed amounts from the reward accounts (725, . . . , 727); adjust (739) the payment transaction in the consumer account (146) based on the amounts of loyalty rewards redeemed from the reward accounts (725, . . . , 727); obtain (741) authorization for the payment transaction; and provide (743) at least one authorization response (138) to the authorization request (168).

In one embodiment, the computing apparatus includes at least one of: the data warehouse (149), the transaction handler (103), the portal (143), the rule engine (721), each of which can be implemented using one or more data processing system, such as a data processing system illustrated in FIG. 7.

FIG. 29 illustrates an example in which the reward sources (e.g., 701, . . . , 703) are associated with the account information (142) in the data warehouse (149) coupled with the transaction handler (103) to implement redemption via the transaction handler (103). The system can be modified to store similar data in a data warehouse coupled with the issuer processor (145) to implement redemption via the issuer processor (145) in a similar way.

Redemption Confirmation and Adjustment

In one embodiment, a redemption notification is transmitted to a user during the processing of the authorization of a payment transaction for a payment from a payment account of a user to a merchant. The redemption notification identifies the reward redemption details computed in accordance with the preferences and/or rules of the user, the merchant, and/or the loyalty programs. The redemption notification prompts the user to confirm and/or modify the redemption details. If the user confirmation and/or modification is received within a predetermined period of time from the redemption notification, the reward redemption is

processed for the payment transaction in accordance with the user input. If the user does not provide an input, a predetermined action is taken regarding the reward redemption in connection with the payment transaction.

In one embodiment, for example, after the redemption details (723) are determined by the rule engine (721) in a way as illustrated in FIGS. 29 and 30 and as discussed in the section entitled “LOYALTY CURRENCY REDEMPTION”, the portal (143) is configured to communicate with a point of interaction (107) identified by the communication reference (611) that is associated in the data warehouse (149) with the account information (142) of the user (101). The portal (143) is configured to communicate with the point of interaction (107) to provide an optional user interface for the user (101) to confirm, accept, reject, and/or modify the redemption details (723) initially computed by the rule engine (721).

FIG. 31 shows a system to provide a user interface for the confirmation of loyalty redemption details according to one embodiment.

In FIG. 31, the rule engine (721) is configured to generate the redemption details (723) based on the rules (e.g., 705), offers (707), and preferences (e.g., 709, . . . , 719) associated with the reward sources (e.g., 701, . . . , 703), balances of the reward accounts (e.g., 725, . . . , 727) identified by the reward sources (e.g., 701, . . . , 703), and/or authorization information (e.g., 645) of redemption from the reward sources (e.g., 701, . . . , 703), in ways discussed in details in the section entitled “LOYALTY CURRENCY REDEMPTION.”

In FIG. 31, after the rule engine (721) determines the redemption details (723), and/or during the transaction handler (103) processes the authorization of the payment transaction in accordance with the redemption details (723), the portal (143) is configured to communicate with the point of interaction (107) identified by the communication reference (611) that is associated with the account information (142) used to initiate the payment transaction.

For example, the point of interaction (107) can be a mobile phone, a tablet computer, a portal computer, a personal media player, a notebook computer, a desktop computer, etc. The point of interaction (107) is generally a computing device separate from the transaction terminal (105) on which the payment transaction is initiated; however, in some embodiments, the point of interaction (107) may be the same device as the transaction terminal (105).

The communication reference (611) may include a phone number, a user name, and/or a network address.

For example, the portal (143) can be configured to communicate with the point of interaction (107) via text message, mobile messaging, instant messaging, email, mobile application, web page, etc.

In FIG. 31, the portal (143) is configured to use the communication reference (611) to transmit the redemption details (723) to the point of interaction (107) via a redemption notification (751) and provide the user (101) with an opportunity to send a redemption confirmation (753) regarding the redemption operations in the payment transaction.

In one embodiment, the redemption notification (751) is transmitted to the point of interaction (107) according to the communication reference (611) in parallel with the processing of the authorization of the payment transaction to which the redemption details (723) can be applied.

In one embodiment, the processing of the authorization of the payment transaction is in response to the authorization request (168) received from the transaction terminal (105), via the acquirer processor (147). The processing of the

authorization of the payment transaction results in the authorization response (138) transmitted via the acquirer processor (147) to the transaction terminal (105).

In one embodiment, the authorization request (168) identifies the consumer payment account (146) as the only source of funding for the payment transaction. The rule engine (721) is configured to identify reward accounts (725, . . . , 727), under the control of the respective sponsor processors (726, . . . , 728), as additional sources of funding, based on the identification data of the reward sources (701, . . . , 703) stored in association with the account information (142) that identifies the consumer account (146).

In one embodiment, based on the rules (e.g., 705), offers (707), preferences (e.g., 709, . . . , 719), the rule engine (721) computes the redemption details (723) that identify one or more reward accounts from which reward currencies are redeemed to satisfy the payment transaction requested in the authorization request (168) from the transaction terminal (105) and the amounts of reward currencies to be redeemed from the respective reward accounts.

In the redemption confirmation (753), the user (101) may accept the redemption details (723) without modification, partially modify the redemption details (723), or reject the redemption details (723).

In one embodiment, the transaction handler (103) is configured to process the reward redemption according to the redemption details (723), confirmed implicitly via the lack of a redemption confirmation (753), confirmed explicitly via the redemption confirmation (753), or modified via the redemption confirmation (753). After applying the reward benefits/currencies towards the payment transaction, the transaction handler (103) computes a modified transaction amount for the authorization request (641) of the issuer processor (145) of the consumer account (146) to obtain the corresponding authorization response (643) for the modified transaction amount.

In one embodiment, a response to the redemption notification (751) is optional. When the response to the redemption notification (751) is not received from the user (101) within a predetermined period of time, the transaction handler (103) is configured to process the authorization of the payment transaction in accordance with the pre-stored confirmation preference (747).

For example, via a user interface of the portal (143), the user (101) may specify a confirmation preference (747) prior to the payment transaction. The confirmation preference (747) identifies a preference of the user (101) in using redemption details (e.g., 723) during the processing payment transactions initiated using the account information (142). The data warehouse (149) stores the confirmation preference (747) in association with the account information (142) for the processing of subsequent transactions in the consumer account (146) identified by the account information (142).

For example, if the portal (143) does not receive a redemption confirmation (e.g., 753) within a predetermined time period from the transmission of the redemption notification (751), the confirmation preference (747) may be set to allow the transaction handler (103) to apply redemption details (e.g., 723) computed by the rule engine (721) to a payment transaction corresponding to an authorization request (e.g., 168) identifying the account information (142) of the user (101).

For example, the confirmation preference (747) may be set to prohibit the transaction handler (103) from applying redemption details (e.g., 723) computed by the rule engine (721) for a payment transaction corresponding to an authorization request (e.g., 168) identifying the account informa-

tion (142) of the user (101) without the redemption confirmation (753). Thus, if the portal (143) does not receive a redemption confirmation (e.g., 753) within a predetermined time period from the transmission of the redemption notification (751), the transaction handler (103) is configured to process the payment transaction without redeeming loyalty rewards from any of the reward accounts (e.g., 725, . . . , 727) identified by the reward sources (e.g., 701, . . . , 703) that are associated with the account information (142) in the data warehouse (149).

For example, the confirmation preference (747) may be set to allow the transaction handler (103) to apply redemption details (e.g., 723) to the corresponding payment transaction in absence of the redemption confirmation (e.g., 753), if the payment transaction and/or the redemption details (e.g., 723) satisfy certain conditions specified in the confirmation preference (747). Such conditions may be based on the identity of the merchant, the transaction amount, the time and/or day of the transaction, the redemption amount, etc.

In one embodiment, after the redemption notification (751) is transmitted to the point of interaction (107) and the payment transaction is processed in accordance with the redemption details (723) and/or the confirmation preference (747), the user (101) is allowed to provide the redemption confirmation (753) to modify the payment transaction within a time window (e.g., before the settlement of the transaction, or within a predetermined time period from the authorization response (138) being transmitted to the acquirer processor (147)). The transaction handler (103) is configured to settle the payment transaction in accordance with the redemption details approved and/or modified in the redemption confirmation (753).

For example, if the confirmation preference (747) is configured to prevent the transaction handler (103) from applying the redemption details (723) computed by the rule engine (721) without the redemption confirmation (753), the transaction handler (103) may provide the authorization response (138) without applying the redemption details (723) when the redemption confirmation (753) is not received in time to generate the authorization response (138). However, if the redemption confirmation (753) is subsequently received for the payment transaction within a predetermined time window, or before the settlement of the payment transaction, the transaction handler (103) is configured to modify the payment transaction according to the redemption details (723) approved and/or modified by the redemption confirmation (753), during settlement of the payment transaction.

For example, if the confirmation preference (747) is configured to allow the transaction handler (103) to apply the redemption details (723) computed by the rule engine (721) without the redemption confirmation (753), the transaction handler (103) may apply the redemption details (723) to the payment transaction to generate the authorization response (138) when the redemption confirmation (753) is not received in time to generate the authorization response (138). If the redemption confirmation (753) is subsequently received for the payment transaction within the predetermined time window, or before the settlement of the payment transaction, the transaction handler (103) is configured to modify, during the settlement of the payment transaction, the payment transaction according to the modification of the redemption details (723) provided in the redemption confirmation (753).

In one embodiment, the user (101) may provide multiple redemption confirmations (e.g., 753) corresponding to the same redemption notification (751); and the transaction

handler (103) is configured to apply the latest redemption confirmation (753) that is received prior to the end of the predetermined time period, and/or prior to the settlement of the payment transaction.

FIG. 32 shows a method to provide a user interface for the confirmation of loyalty redemption details according to one embodiment. For example, the method of FIG. 32 can be implemented in a system illustrated in FIG. 31.

In FIG. 32, a computing apparatus is configured to: receive (751) an authorization request (168) for a payment transaction in a payment account (146) that is associated, in the data warehouse (149), with one or more reward accounts (725, . . . , 727) of a user (101); compute (753) details (723) of redeeming loyalty rewards from the reward accounts (725, . . . , 727) for application to the payment transaction; and provide (755) a notification (751) of the details (723) to the user (101) using a communication reference (611) associated with the payment account (146).

If a confirmation (753) responsive to the notification (751) is received (757) within a first time period (e.g., before a time limit for responding to the authorization request), the computing apparatus is configured to process and/or provide (759) an authorization response (138) according to the confirmation (753), which may accept the details, reject the details, or provide a modification to the details; otherwise, the computing apparatus is configured to process and/or provide (761) an authorization response (138) according to a confirmation preference (747) controlling a default action for redeeming loyalty rewards.

For example, in response to the redemption confirmation (753), the transaction amount for the payment transaction in the consumer account (146) is adjusted to include the benefit of rewards redeemed in accordance with the redemption confirmation (753). For example, if the redemption confirmation (753) authorizes no reward redemption by the user (101), the transaction amount for the payment transaction in the consumer account (146) is not adjusted.

Similar to the redemption confirmation (753), the confirmation preference (747) controlling the default action may accept or reject the redemption details (723), in absence of a redemption confirmation (753) within the first time period.

If a confirmation (753) responsive to the notification (751) is received (763) within a second time period (e.g., after the transmission of the authorization response (138) to the acquirer processor (147), but before the settlement of the payment transaction), the computing apparatus is configured to modify (765) the transaction according to the confirmation (753) received during the second time period; otherwise, the transaction as previously authorized in the authorization response (138) is not modified.

In FIG. 32, the computing apparatus is configured to settle (767) the transaction as determined in accordance to the above discussed operations. The determined transaction may or may not include redemption of loyalty rewards from the reward accounts (e.g., 725, . . . , 727) as initially computed by the rule engine (721) and may or may not be subsequently modified by the redemption confirmation (753) responsive to the redemption notification (751) of the redemption details (723).

In one embodiment, the computing apparatus includes at least one of: the data warehouse (149), the transaction handler (103), the portal (143), the rule engine (721), each of which can be implemented using one or more data processing systems, such as a data processing system illustrated in FIG. 7.

FIG. 31 illustrates an example in which the data warehouse (149), the rule engine (721), and the portal (143) are

configured to operation in connection with transaction processing performed by the transaction handler (103). The system can be modified to perform similar operations in connection with the transaction processing performed by the issuer processor (145) to implement redemption via the issuer processor (145) in a similar way.

For example, in one embodiment, a payment processing apparatus configured to process payment transactions in a payment processing network, e.g., as illustrated in FIG. 4, is configured with a rule engine, a data warehouse, and a portal. The payment processing apparatus may include and/or be configured around the transaction handler (103), or the issuer processor (145), or the acquirer processor (147).

The data warehouse (149) of the payment processing apparatus is configured to store data associating: a user profile of a user, a payment account of the user, and a communication reference of the user, where the user profile is configured to identify a plurality of loyalty programs of the user, as well as the preferences and rules for redeeming loyalty currencies of the user from the loyalty programs.

After the payment processing apparatus receives (e.g., in the transaction handler (103), the issuer processor (145), the acquirer processor (147)) an authorization request for a payment transaction in the payment account, the rule engine (721) of the payment processing apparatus computes details (723) of redemption of loyalty currencies from the loyalty programs in accordance with the preferences and rules identified in the user profile. The portal (143) of the payment processing apparatus then transmits, in parallel with the processing of the authorization request, a redemption notification to the communication reference stored in the data warehouse in association with the payment account. The redemption notification provides the details (723) of the redemption of the loyalty currencies from the loyalty programs. Based on the redemption notification (751), the portal (143) of the payment processing apparatus is configured to communicate with the point of interaction (107) of the user (101) to provide a user interface prompting the user to confirm the details (723) of the redemption of the loyalty currencies from the loyalty programs.

In one embodiment, the redemption notification includes a user interface element selectable by the user to generate a confirmation message transmitted from a computing device of the user to the computing apparatus.

For example, the redemption notification may include a hyperlink, which when selected causes the computer device of the user to send the redemption confirmation (753) via text message, email, or a web request to the portal (143) sent via Hypertext Transfer Protocol (HTTP). Alternatively, the hyperlink may cause the computing device to launch an application to communicate with the portal (143) and/or provide a user interface for specifying the redemption confirmation (753).

For example, the computing device of the user (101) can be a mobile phone; and the communication reference can be a phone number of the mobile phone that can be used for establish communication between the portal (143) and the mobile phone of the user (101).

In one embodiment, when the confirmation message (753) accepts the details (723) for the redemption, the payment processing apparatus is configured to redeem loyalty rewards from the loyalty programs according to the details (723) for the redemption and apply the loyalty rewards to the payment transaction.

For example, the redeemed loyalty rewards can be used as part of the payments to the merchant; and the transaction

amount in the consumer account (146) can be reduced in view of the payments made via the redeemed loyalty rewards.

In one embodiment, the redemption notification includes a user interface element selectable by the user when the redemption notification is presented on a computing device of the user; in response to a user selection of the user interface element, the user interface element causes the computing device of the user to communicate with the computing apparatus to present the user interface prompting the user to confirm the details of the redemption of the loyalty currencies.

For example, the user interface element can be implemented as a hyperlink embedded in the redemption notification; and the hyperlink is configured to cause the mobile phone of the user (101) to request a web form from the portal (143) to present the details (723), accept user input to modify the details (723), and/or accept or reject the details (723). Alternatively, the user interface can be implemented as a mobile application running the mobile phone of the user (101).

In one embodiment, the user interface presented in the computing device of the user as a result of the redemption notification (168) prompts the user to confirm the details (723) of the redemption of the loyalty currencies and provides an option to modify the details of the redemption of the loyalty currencies to generate a modified redemption plan.

In response to receiving, within a predetermined time period from the redemption notification, the modified redemption plan, the payment processing apparatus redeems loyalty rewards from the loyalty programs according to the modified redemption plan, and applies the loyalty rewards to the payment transaction. The loyalty rewards can be applied to the payment transaction during the authorization of the payment transaction, or during the settlement of the payment transaction.

In response to having not received a redemption plan within a predetermined time period from transmission of the redemption notification, the payment processing apparatus redeems loyalty rewards from the loyalty programs according to the details of the redemption of the loyalty currencies computed by the rule engine (121), and applies the loyalty rewards to the payment transaction, during the authorization and/or settlement of the payment transaction.

In one embodiment, the preferences and rules specified in the user profile include a preference of the user. The preference specifies whether or not the details of the redemption of the loyalty currencies computed by the computing apparatus are considered to be accepted by the user, if no confirmation or modification is received from the user in response to the redemption notification.

In one embodiment, prior to receiving the modified redemption plan via the user interface presented on the user device, the payment processing apparatus redeems loyalty rewards from the loyalty programs according to the details of the redemption of the loyalty currencies computed by the rule engine in accordance with the preferences and rules identified in the user profile, and applies the loyalty rewards to the authorization of the payment transaction. After receiving the modified redemption plan via the user interface presented on the user device, the payment processing apparatus modifies redemption of loyalty rewards from the loyalty programs according to the modified redemption plan, and applies, by the computing apparatus, loyalty rewards to the settlement of the payment transaction according to the modified redemption plan.

In one embodiment, the payment processing apparatus determines, during a first time period from the redemption notification, whether not a first user input responsive to the redemption notification is received. After receiving the first user input during the first time period, the payment processing apparatus processes the authorization of the payment transaction in accordance with the user input.

The payment processing apparatus then further determines, during a second time period from the redemption notification, whether not a second user input responsive to the redemption notification is received. After receiving the second user input during the second time period, the payment processing apparatus processes settlement of the payment transaction in accordance with the second user input.

In absence of a user input during the first and/or second time period, the payment processing apparatus processes loyalty benefit redemption for the authorization and/or settlement of the payment transaction in accordance with a default action identified in the user profile. The default action may be based at least in part on a merchant with which the payment transaction is made, a transaction amount of the payment transaction, a time of the transaction during the day, a day of the transaction during the week, etc.

The computing apparatus can be further implemented, optionally, to perform other operations discussed below, such as the operations discussed in the section entitled "TRANSACTION DATA BASED SERVICES." Some of the hardware arrangements are discussed in the sections entitled "CENTRALIZED DATA WAREHOUSE" and "HARDWARE."

For example, the transaction handler (103) discussed above can be used to record transaction data (109) to provide transaction data based services as illustrated in FIG. 1 and discussed in the section entitled "TRANSACTION DATA BASED SERVICES."

Transaction Data Based Services

FIG. 1 illustrates a system to provide services based on transaction data according to one embodiment. In FIG. 1, the system includes a transaction terminal (105) to initiate financial transactions for a user (101), a transaction handler (103) to generate transaction data (109) from processing the financial transactions of the user (101) (and the financial transactions of other users), a profile generator (121) to generate transaction profiles (127) based on the transaction data (109) to provide information/intelligence about user preferences and spending patterns, a point of interaction (107) to provide information and/or offers to the user (101), a user tracker (113) to generate user data (125) to identify the user (101) using the point of interaction (107), a profile selector (129) to select a profile (131) specific to the user (101) identified by the user data (125), and an advertisement selector (133) to select, identify, generate, adjust, prioritize and/or personalize advertisements for presentation to the user (101) on the point of interaction (107) via a media controller (115).

In FIG. 1, the system further includes a correlator (117) to correlate user specific advertisement data (119) with transactions resulting from the user specific advertisement data (119). The correlation results (123) can be used by the profile generator (121) to improve the transaction profiles (127).

The transaction profiles (127) of one embodiment are generated from the transaction data (109) in a way as illustrated in FIGS. 2 and 3. For example, in FIG. 2, an aggregated spending profile (341) is generated via the factor analysis (327) and cluster analysis (329) to summarize (335) the spending patterns/behaviors reflected in the transaction records (301).

In one embodiment, a data warehouse (149) as illustrated in FIG. 4 is coupled with the transaction handler (103) to store the transaction data (109) and other data, such as account data (111), transaction profiles (127) and correlation results (123). In FIG. 4, a portal (143) is coupled with the data warehouse (149) to provide data or information derived from the transaction data (109), in response to a query request from a third party or as an alert or notification message.

In FIG. 4, the transaction handler (103) is coupled between an issuer processor (145) in control of a consumer account (146) and an acquirer processor (147) in control of a merchant account (148). An account identification device (141) is configured to carry the account information (142) that identifies the consumer account (146) with the issuer processor (145) and provide the account information (142) to the transaction terminal (105) of a merchant to initiate a transaction between the user (101) and the merchant.

FIGS. 5 and 6 illustrate examples of transaction terminals (105) and account identification devices (141). FIG. 7 illustrates the structure of a data processing system (170) that can be used to implement, with more or fewer elements, at least some of the components in the system, such as the point of interaction (107), the transaction handler (103), the portal (143), the data warehouse, the account identification device (141), the transaction terminal (105), the user tracker (113), the profile generator (121), the profile selector (129), the advertisement selector (133), the media controller (115), etc. Some embodiments use more or fewer components than those illustrated, such as, in FIGS. 1, 4-7, and other figures, as further discussed in the section entitled "VARIATIONS."

In one embodiment, the transaction data (109) relates to financial transactions processed by the transaction handler (103); and the account data (111) relates to information about the account holders involved in the transactions. Further data, such as merchant data that relates to the location, business, products and/or services of the merchants that receive payments from account holders for their purchases, can be used in the generation of the transaction profiles (127, 341).

In one embodiment, the financial transactions are made via an account identification device (141), such as financial transaction cards (e.g., credit cards, debit cards, banking cards, etc.); the financial transaction cards may be embodied in various devices, such as plastic cards, chips, radio frequency identification (RFID) devices, mobile phones, personal digital assistants (PDAs), etc.; and the financial transaction cards may be represented by account identifiers (e.g., account numbers or aliases). In one embodiment, the financial transactions are made via directly using the account information (142), without physically presenting the account identification device (141).

Further features, modifications and details are provided in various sections of this description.

Centralized Data Warehouse

In one embodiment, the transaction handler (103) couples with a centralized data warehouse (149) organized around the transaction data (109). For example, the centralized data warehouse (149) may include, and/or support the determination of, spend band distribution, transaction count and amount, merchant categories, merchant by state, cardholder segmentation by velocity scores, and spending within merchant target, competitive set and cross-section. For example, the centralized data warehouse (149) may include the advertisement data (135) and/or offers of benefits such as discount, reward, points, cashback, etc. The offers can be

communicated to the users (e.g., **101**) via the advertisement data (**135**) or as part of the advertisement data (**135**).

In one embodiment, the centralized data warehouse (**149**) provides centralized management but allows decentralized execution. For example, a third party strategic marketing analyst, statistician, marketer, promoter, business leader, etc., may access the centralized data warehouse (**149**) to analyze customer and shopper data, to provide follow-up analyses of customer contributions, to develop propensity models for increased conversion of marketing campaigns, to develop segmentation models for marketing, etc. The centralized data warehouse (**149**) can be used to manage advertisement campaigns and analyze response profitability.

In one embodiment, the centralized data warehouse (**149**) includes merchant data (e.g., data about sellers), customer/business data (e.g., data about buyers), and transaction records (**301**) between sellers and buyers over time. The centralized data warehouse (**149**) can be used to support corporate sales forecasting, fraud analysis reporting, sales/customer relationship management (CRM) business intelligence, credit risk prediction and analysis, advanced authorization reporting, merchant benchmarking, business intelligence for small business, rewards, etc.

In one embodiment, the transaction data (**109**) is combined with external data, such as surveys, benchmarks, search engine statistics, demographics, competition information, emails, etc., to flag key events and data values, to set customer, merchant, data or event triggers, and to drive new transactions and new customer contacts.

Transaction Profile

In FIG. 1, the profile generator (**121**) generates transaction profiles (**127**) based on the transaction data (**109**), the account data (**111**), and/or other data, such as non-transactional data, wish lists, merchant provided information, address information, information from social network websites, information from credit bureaus, information from search engines, and other examples discussed in U.S. Pat. App. Pub. No. 2011/0054981, entitled "Analyzing Local Non-Transactional Data with Transactional Data in Predictive Models," the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the transaction profiles (**127**) provide intelligence information on the behavior, pattern, preference, propensity, tendency, frequency, trend, and budget of the user (**101**) in making purchases. In one embodiment, the transaction profiles (**127**) include information about what the user (**101**) owns, such as points, miles, or other rewards currency, available credit, and received offers, such as coupons loaded into the accounts of the user (**101**). In one embodiment, the transaction profiles (**127**) include information based on past offer/coupon redemption patterns. In one embodiment, the transaction profiles (**127**) include information on shopping patterns in retail stores as well as online, including frequency of shopping, amount spent in each shopping trip, distance of merchant location (retail) from the address of the account holder(s), etc.

In one embodiment, the transaction handler (**103**) (and/or the portal (**143**)) is configured to provide at least part of the intelligence for the prioritization, generation, selection, customization and/or adjustment of the advertisement for delivery within a transaction process involving the transaction handler (**103**). For example, the advertisement may be presented to a customer in response to the customer making a payment via the transaction handler (**103**).

Some of the transaction profiles (**127**) are specific to the user (**101**), or to an account of the user (**101**), or to a group of users of which the user (**101**) is a member, such as a

household, family, company, neighborhood, city, or group identified by certain characteristics related to online activities, offline purchase activities, merchant propensity, etc.

The profile generator (**121**) may generate and update the transaction profiles (**127**) in batch mode periodically, or generates the transaction profiles (**127**) in real time, or just in time, in response to a request received in the portal (**143**) for such profiles.

The transaction profiles (**127**) of one embodiment include the values for a set of parameters. Computing the values of the parameters may involve counting transactions that meet one or more criteria, and/or building a statistically-based model in which one or more calculated values or transformed values are put into a statistical algorithm that weights each value to optimize its collective predictiveness for various predetermined purposes.

Further details and examples about the transaction profiles (**127**) in one embodiment are provided in the section entitled "AGGREGATED SPENDING PROFILE."

Non-Transactional Data

In one embodiment, the transaction data (**109**) is analyzed in connection with non-transactional data to generate transaction profiles (**127**) and/or to make predictive models.

In one embodiment, transactions are correlated with non-transactional events, such as news, conferences, shows, announcements, market changes, natural disasters, etc. to establish cause and effect relations to predict future transactions or spending patterns. For example, non-transactional data may include the geographic location of a news event, the date of an event from an events calendar, the name of a performer for an upcoming concert, etc. The non-transactional data can be obtained from various sources, such as newspapers, websites, blogs, social networking sites, etc.

When the cause and effect relationships between the transactions and non-transactional events are known (e.g., based on prior research results, domain knowledge, expertise), the relationships can be used in predictive models to predict future transactions or spending patterns, based on events that occurred recently or are happening in real time.

In one embodiment, the non-transactional data relates to events that happened in a geographical area local to the user (**101**) that performed the respective transactions. In one embodiment, a geographical area is local to the user (**101**) when the distance from the user (**101**) to locations in the geographical area is within a convenient range for daily or regular travel, such as 20, 50 or 100 miles from an address of the user (**101**), or within the same city or zip code area of an address of the user (**101**). Examples of analyses of local non-transactional data in connection with transaction data (**109**) in one embodiment are provided in U.S. Pat. App. Pub. No. 2011/0054981, entitled "Analyzing Local Non-Transactional Data with Transactional Data in Predictive Models," the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the non-transactional data is not limited to local non-transactional data. For example, national non-transactional data can also be used.

In one embodiment, the transaction records (**301**) are analyzed in frequency domain to identify periodic features in spending events. The periodic features in the past transaction records (**301**) can be used to predict the probability of a time window in which a similar transaction would occur. For example, the analysis of the transaction data (**109**) can be used to predict when a next transaction having the periodic feature would occur, with which merchant, the probability of a repeated transaction with a certain amount, the probability of exception, the opportunity to provide an

advertisement or offer such as a coupon, etc. In one embodiment, the periodic features are detected through counting the number of occurrences of pairs of transactions that occurred within a set of predetermined time intervals and separating the transaction pairs based on the time intervals. Some examples and techniques for the prediction of future transactions based on the detection of periodic features in one embodiment are provided in U.S. Pat. App. Pub. No. 2010/0280882, entitled "Frequency-Based Transaction Prediction and Processing," the disclosure of which is hereby incorporated herein by reference.

Techniques and details of predictive modeling in one embodiment are provided in U.S. Pat. Nos. 6,119,103, 6,018,723, 6,658,393, 6,598,030, and 7,227,950, the disclosures of which are hereby incorporated herein by reference.

In one embodiment, offers are based on the point-of-service to offeree distance to allow the user (101) to obtain in-person services. In one embodiment, the offers are selected based on transaction history and shopping patterns in the transaction data (109) and/or the distance between the user (101) and the merchant. In one embodiment, offers are provided in response to a request from the user (101), or in response to a detection of the location of the user (101). Examples and details of at least one embodiment are provided in U.S. Pat. App. Pub. No. 2008/0319843, entitled "Supply of Requested Offer Based on Point-of Service to Offeree Distance," U.S. Pat. App. Pub. No. 2008/0300973, entitled "Supply of Requested Offer Based on Offeree Transaction History," U.S. Pat. App. Pub. No. 2009/0076896, entitled "Merchant Supplied Offer to a Consumer within a Predetermined Distance," U.S. Pat. App. Pub. No. 2009/0076925, entitled "Offeree Requested Offer Based on Point-of Service to Offeree Distance," and U.S. Pat. App. Pub. No. 2010/0274627, entitled "Receiving an Announcement Triggered by Location Data," the disclosures of which applications are hereby incorporated herein by reference.

Targeting Advertisement

In FIG. 1, an advertisement selector (133) prioritizes, generates, selects, adjusts, and/or customizes the available advertisement data (135) to provide user specific advertisement data (119) based at least in part on the user specific profile (131). The advertisement selector (133) uses the user specific profile (131) as a filter and/or a set of criteria to generate, identify, select and/or prioritize advertisement data for the user (101). A media controller (115) delivers the user specific advertisement data (119) to the point of interaction (107) for presentation to the user (101) as the targeted and/or personalized advertisement.

In one embodiment, the user data (125) includes the characterization of the context at the point of interaction (107). Thus, the use of the user specific profile (131), selected using the user data (125), includes the consideration of the context at the point of interaction (107) in selecting the user specific advertisement data (119).

In one embodiment, in selecting the user specific advertisement data (119), the advertisement selector (133) uses not only the user specific profile (131), but also information regarding the context at the point of interaction (107). For example, in one embodiment, the user data (125) includes information regarding the context at the point of interaction (107); and the advertisement selector (133) explicitly uses the context information in the generation or selection of the user specific advertisement data (119).

In one embodiment, the advertisement selector (133) may query for specific information regarding the user (101) before providing the user specific advertisement data (119). The queries may be communicated to the operator of the

transaction handler (103) and, in particular, to the transaction handler (103) or the profile generator (121). For example, the queries from the advertisement selector (133) may be transmitted and received in accordance with an application programming interface or other query interface of the transaction handler (103), the profile generator (121) or the portal (143) of the transaction handler (103).

In one embodiment, the queries communicated from the advertisement selector (133) may request intelligence information regarding the user (101) at any level of specificity (e.g., segment level, individual level). For example, the queries may include a request for a certain field or type of information in a cardholder's aggregate spending profile (341). As another example, the queries may include a request for the spending level of the user (101) in a certain merchant category over a prior time period (e.g., six months).

In one embodiment, the advertisement selector (133) is operated by an entity that is separate from the entity that operates the transaction handler (103). For example, the advertisement selector (133) may be operated by a search engine, a publisher, an advertiser, an ad network, or an online merchant. The user specific profile (131) is provided to the advertisement selector (133) to assist the customization of the user specific advertisement data (119).

In one embodiment, advertising is targeted based on shopping patterns in a merchant category (e.g., as represented by a Merchant Category Code (MCC)) that has high correlation of spending propensity with other merchant categories (e.g., other MCCs). For example, in the context of a first MCC for a targeted audience, a profile identifying second MCCs that have high correlation of spending propensity with the first MCC can be used to select advertisements for the targeted audience.

In one embodiment, the aggregated spending profile (341) is used to provide intelligence information about the spending patterns, preferences, and/or trends of the user (101). For example, a predictive model can be established based on the aggregated spending profile (341) to estimate the needs of the user (101). For example, the factor values (344) and/or the cluster ID (343) in the aggregated spending profile (341) can be used to determine the spending preferences of the user (101). For example, the channel distribution (345) in the aggregated spending profile (341) can be used to provide a customized offer targeted for a particular channel, based on the spending patterns of the user (101).

In one embodiment, mobile advertisements, such as offers and coupons, are generated and disseminated based on aspects of prior purchases, such as timing, location, and nature of the purchases, etc. In one embodiment, the size of the benefit of the offer or coupon is based on purchase volume or spending amount of the prior purchase and/or the subsequent purchase that may qualify for the redemption of the offer. Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2008/0201226, entitled "Mobile Coupon Method and Portable Consumer Device for Utilizing Same," the disclosure of which is hereby incorporated herein by reference.

In one embodiment, conditional rewards are provided to the user (101); and the transaction handler (103) monitors the transactions of the user (101) to identify redeemable rewards that have satisfied the respective conditions. In one embodiment, the conditional rewards are selected based on transaction data (109). Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2008/0082418, entitled "Consumer Specific Conditional Rewards," the disclosure of which is hereby incorporated

herein by reference. The techniques to detect the satisfied conditions of conditional rewards can also be used to detect the transactions that satisfy the conditions specified to locate the transactions that result from online activities, such as online advertisements, searches, etc., to correlate the transactions with the respective online activities.

Further details about targeted offer delivery in one embodiment are provided in U.S. Pat. App. Pub. No. 2010/0030644, entitled "Targeted Advertising by Payment Processor History of Cashless Acquired Merchant Transaction on Issued Consumer Account," and in U.S. Pat. App. Pub. No. 2011/0035280, entitled "Systems and Methods for Targeted Advertisement Delivery," the disclosures of which applications are hereby incorporated herein by reference.

Profile Matching

In FIG. 1, the user tracker (113) obtains and generates context information about the user (101) at the point of interaction (107), including user data (125) that characterizes and/or identifies the user (101). The profile selector (129) selects a user specific profile (131) from the set of transaction profiles (127) generated by the profile generator (121), based on matching the characteristics of the transaction profiles (127) and the characteristics of the user data (125). For example, the user data (125) indicates a set of characteristics of the user (101); and the profile selector (129) selects the user specific profile (131) that is for a particular user or a group of users and that best matches the set of characteristics specified by the user data (125).

In one embodiment, the profile selector (129) receives the transaction profiles (127) in a batch mode. The profile selector (129) selects the user specific profile (131) from the batch of transaction profiles (127) based on the user data (125). Alternatively, the profile generator (121) generates the transaction profiles (127) in real time; and the profile selector (129) uses the user data (125) to query the profile generator (121) to generate the user specific profile (131) in real time, or just in time. The profile generator (121) generates the user specific profile (131) that best matches the user data (125).

In one embodiment, the user tracker (113) identifies the user (101) based on the user activity on the transaction terminal (105) (e.g., having visited a set of websites, currently visiting a type of web pages, search behavior, etc.).

In one embodiment, the user data (125) includes an identifier of the user (101), such as a global unique identifier (GUID), a personal account number (PAN) (e.g., credit card number, debit card number, or other card account number), or other identifiers that uniquely and persistently identify the user (101) within a set of identifiers of the same type. Alternatively, the user data (125) may include other identifiers, such as an Internet Protocol (IP) address of the user (101), a name or user name of the user (101), or a browser cookie ID, which identify the user (101) in a local, temporary, transient and/or anonymous manner. Some of these identifiers of the user (101) may be provided by publishers, advertisers, ad networks, search engines, merchants, or the user tracker (113). In one embodiment, such identifiers are correlated to the user (101) based on the overlapping or proximity of the time period of their usage to establish an identification reference table.

In one embodiment, the identification reference table is used to identify the account information (142) (e.g., account number (302)) based on characteristics of the user (101) captured in the user data (125), such as browser cookie ID, IP addresses, and/or timestamps on the usage of the IP addresses. In one embodiment, the identification reference table is maintained by the operator of the transaction handler

(103). Alternatively, the identification reference table is maintained by an entity other than the operator of the transaction handler (103).

In one embodiment, the user tracker (113) determines certain characteristics of the user (101) to describe a type or group of users of which the user (101) is a member. The transaction profile of the group is used as the user specific profile (131). Examples of such characteristics include geographical location or neighborhood, types of online activities, specific online activities, or merchant propensity. In one embodiment, the groups are defined based on aggregate information (e.g., by time of day, or household), or segment (e.g., by cluster, propensity, demographics, cluster IDs, and/or factor values). In one embodiment, the groups are defined in part via one or more social networks. For example, a group may be defined based on social distances to one or more users on a social network website, interactions between users on a social network website, and/or common data in social network profiles of the users in the social network website.

In one embodiment, the user data (125) may match different profiles at a different granularity or resolution (e.g., account, user, family, company, neighborhood, etc.), with different degrees of certainty. The profile selector (129) and/or the profile generator (121) may determine or select the user specific profile (131) with the finest granularity or resolution with acceptable certainty. Thus, the user specific profile (131) is most specific or closely related to the user (101).

In one embodiment, the advertisement selector (133) uses further data in prioritizing, selecting, generating, customizing and adjusting the user specific advertisement data (119). For example, the advertisement selector (133) may use search data in combination with the user specific profile (131) to provide benefits or offers to a user (101) at the point of interaction (107). For example, the user specific profile (131) can be used to personalize the advertisement, such as adjusting the placement of the advertisement relative to other advertisements, adjusting the appearance of the advertisement, etc.

Browser Cookie

In one embodiment, the user data (125) uses browser cookie information to identify the user (101). The browser cookie information is matched to account information (142) or the account number (302) to identify the user specific profile (131), such as aggregated spending profile (341) to present effective, timely, and relevant marketing information to the user (101), via the preferred communication channel (e.g., mobile communications, web, mail, email, POS, etc.) within a window of time that could influence the spending behavior of the user (101). Based on the transaction data (109), the user specific profile (131) can improve audience targeting for online advertising. Thus, customers will get better advertisements and offers presented to them; and the advertisers will achieve better return-on-investment for their advertisement campaigns.

In one embodiment, the browser cookie that identifies the user (101) in online activities, such as web browsing, online searching, and using social networking applications, can be matched to an identifier of the user (101) in account data (111), such as the account number (302) of a financial payment card of the user (101) or the account information (142) of the account identification device (141) of the user (101). In one embodiment, the identifier of the user (101) can be uniquely identified via matching IP address, timestamp, cookie ID and/or other user data (125) observed by the user tracker (113).

In one embodiment, a look up table is used to map browser cookie information (e.g., IP address, timestamp, cookie ID) to the account data (111) that identifies the user (101) in the transaction handler (103). The look up table may be established via correlating overlapping or common portions of the user data (125) observed by different entities or different user trackers (113).

In one embodiment, the portal (143) is configured to identify the consumer account (146) based on the IP address identified in the user data (125) through mapping the IP address to a street address.

In one embodiment, the portal (143) uses a plurality of methods to identify consumer accounts (146) based on the user data (125). The portal (143) combines the results from the different methods to determine the most likely consumer account (146) for the user data (125).

Details about the identification of consumer account (146) based on user data (125) in one embodiment are provided in U.S. Pat. App. Pub. No. 2011/0093327, entitled "Systems and Methods to Match Identifiers," the disclosure of which is hereby incorporated herein by reference.

Close the Loop

In one embodiment, the correlator (117) is used to "close the loop" for the tracking of consumer behavior across an on-line activity and an "off-line" activity that results at least in part from the on-line activity. In one embodiment, online activities, such as searching, web browsing, social networking, and/or consuming online advertisements, are correlated with respective transactions to generate the correlation result (123) in FIG. 1. The respective transactions may occur offline, in "brick and mortar" retail stores, or online but in a context outside the online activities, such as a credit card purchase that is performed in a way not visible to a search company that facilitates the search activities.

The correlator (117) is configured in one embodiment to identify transactions resulting from searches or online advertisements. For example, in response to a query about the user (101) from the user tracker (113), the correlator (117) identifies an offline transaction performed by the user (101) and sends the correlation result (123) about the offline transaction to the user tracker (113), which allows the user tracker (113) to combine the information about the offline transaction and the online activities to provide significant marketing advantages.

For example, a marketing department could correlate an advertising budget to actual sales. For example, a marketer can use the correlation result (123) to study the effect of certain prioritization strategies, customization schemes, etc. on the impact on the actual sales. For example, the correlation result (123) can be used to adjust or prioritize advertisement placement on a web site, a search engine, a social networking site, an online marketplace, or the like.

In one embodiment, the profile generator (121) uses the correlation result (123) to augment the transaction profiles (127) with data indicating the rate of conversion from searches or advertisements to purchase transactions. In one embodiment, the correlation result (123) is used to generate predictive models to determine what a user (101) is likely to purchase when the user (101) is searching using certain keywords or when the user (101) is presented with an advertisement or offer. In one embodiment, the portal (143) is configured to report the correlation result (123) to a partner, such as a search engine, a publisher, or a merchant, to allow the partner to use the correlation result (123) to measure the effectiveness of advertisements and/or search result customization, to arrange rewards, etc.

In one embodiment, the correlator (117) matches the online activities and the transactions based on matching the user data (125) provided by the user tracker (113) and the records of the transactions, such as transaction data (109) or transaction records (301). In another embodiment, the correlator (117) matches the online activities and the transactions based on the redemption of offers/benefits provided in the user specific advertisement data (119).

In one embodiment, the portal (143) is configured to receive a set of conditions and an identification of the user (101), determine whether there is any transaction of the user (101) that satisfies the set of conditions, and if so, provide indications of the transactions that satisfy the conditions and/or certain details about the transactions, which allows the requester to correlate the transactions with certain user activities, such as searching, web browsing, consuming advertisements, etc.

In one embodiment, the requester may not know the account number (302) of the user (101); and the portal (143) is to map the identifier provided in the request to the account number (302) of the user (101) to provide the requested information. Examples of the identifier being provided in the request to identify the user (101) include an identification of an iFrame of a web page visited by the user (101), a browser cookie ID, an IP address and the day and time corresponding to the use of the IP address, etc.

The information provided by the portal (143) can be used in pre-purchase marketing activities, such as customizing content or offers, prioritizing content or offers, selecting content or offers, etc., based on the spending pattern of the user (101). The content that is customized, prioritized, selected, or recommended may be the search results, blog entries, items for sale, etc.

The information provided by the portal (143) can be used in post-purchase activities. For example, the information can be used to correlate an offline purchase with online activities. For example, the information can be used to determine purchases made in response to media events, such as television programs, advertisements, news announcements, etc.

Details about profile delivery, online activity to offline purchase tracking, techniques to identify the user specific profile (131) based on user data (125) (such as IP addresses), and targeted delivery of advertisement/offer/benefit in some embodiments are provided in U.S. Pat. App. Pub. No. 2011/0035278, entitled "Systems and Methods for Closing the Loop between Online Activities and Offline Purchases," the disclosure of which application is incorporated herein by reference.

Loyalty Program

In one embodiment, the transaction handler (103) uses the account data (111) to store information for third party loyalty programs.

FIG. 8 shows the structure of account data (111) for providing loyalty programs according to one embodiment. In FIG. 8, data related to a third party loyalty program may include an identifier of the loyalty benefit offeror (183) that is linked to a set of loyalty program rules (185) and loyalty record (187) for the loyalty program activities of the account identifier (181). In one embodiment, at least part of the data related to the third party loyalty program is stored under the account identifier (181) of the user (101), such as the loyalty record (187).

FIG. 8 illustrates the data related to one third party loyalty program of a loyalty benefit offeror (183). In one embodiment, the account identifier (181) may be linked to multiple loyalty benefit offerors (e.g., 183), corresponding to different third party loyalty programs. The third party loyalty program

of the loyalty benefit offeror (183) provides the user (101), identified by the account identifier (181), with benefits, such as discounts, rewards, incentives, cash back, gifts, coupons, and/or privileges.

In one embodiment, the association between the account identifier (181) and the loyalty benefit offeror (183) in the account data (111) indicates that the user (101) having the account identifier (181) is a member of the loyalty program. Thus, the user (101) may use the account identifier (181) to access privileges afforded to the members of the loyalty programs, such as rights to access a member only area, facility, store, product or service, discounts extended only to members, or opportunities to participate in certain events, buy certain items, or receive certain services reserved for members.

In one embodiment, it is not necessary to make a purchase to use the privileges. The user (101) may enjoy the privileges based on the status of being a member of the loyalty program. The user (101) may use the account identifier (181) to show the status of being a member of the loyalty program.

For example, the user (101) may provide the account identifier (181) (e.g., the account number of a credit card) to the transaction terminal (105) to initiate an authorization process for a special transaction which is designed to check the member status of the user (101), as if the account identifier (181) were used to initiate an authorization process for a payment transaction. The special transaction is designed to verify the member status of the user (101) via checking whether the account data (111) is associated with the loyalty benefit offeror (183). If the account identifier (181) is associated with the corresponding loyalty benefit offeror (183), the transaction handler (103) provides an approval indication in the authorization process to indicate that the user (101) is a member of the loyalty program. The approval indication can be used as a form of identification to allow the user (101) to access member privileges, such as access to services, products, opportunities, facilities, discounts, permissions, which are reserved for members.

In one embodiment, when the account identifier (181) is used to identify the user (101) as a member to access member privileges, the transaction handler (103) stores information about the access of the corresponding member privilege in loyalty record (187). The profile generator (121) may use the information accumulated in the loyalty record (187) to enhance transaction profiles (127) and provide the user (101) with personalized/targeted advertisements, with or without further offers of benefit (e.g., discounts, incentives, rebates, cash back, rewards, etc.).

In one embodiment, the association of the account identifier (181) and the loyalty benefit offeror (183) also allows the loyalty benefit offeror (183) to access at least a portion of the account data (111) relevant to the loyalty program, such as the loyalty record (187) and certain information about the user (101), such as name, address, and other demographic data.

In one embodiment, the loyalty program allows the user (101) to accumulate benefits according to loyalty program rules (185), such as reward points, cash back, levels of discounts, etc. For example, the user (101) may accumulate reward points for transactions that satisfy the loyalty program rules (185); and the user (101) may use the reward points to redeem cash, gift, discounts, etc. In one embodiment, the loyalty record (187) stores the accumulated benefits; and the transaction handler (103) updates the loyalty record (187) associated with the loyalty benefit offeror (183) and the account identifier (181), when events that satisfy the loyalty program rules occur.

In one embodiment, the accumulated benefits as indicated in the loyalty record (187) can be redeemed when the account identifier (181) is used to perform a payment transaction, when the payment transaction satisfies the loyalty program rules. For example, the user (101) may redeem a number of points to offset or reduce an amount of the purchase price.

In one embodiment, when the user (101) uses the account identifier (181) to make purchases as a member, the merchant may further provide information about the purchases; and the transaction handler (103) can store the information about the purchases as part of the loyalty record (187). The information about the purchases may identify specific items or services purchased by the member. For example, the merchant may provide the transaction handler (103) with purchase details at stock-keeping unit (SKU) level, which are then stored as part of the loyalty record (187). The loyalty benefit offeror (183) may use the purchase details to study the purchase behavior of the user (101); and the profile generator (121) may use the SKU level purchase details to enhance the transaction profiles (127).

In one embodiment, the SKU level purchase details are requested from the merchants or retailers via authorization responses (e.g., as illustrated in FIG. 9), when the account (146) of the user (101) is enrolled in a loyalty program that allows the transaction handler (103) (and/or the issuer processor (145)) to collect the purchase details.

A method to provide loyalty programs of one embodiment includes the use of the transaction handler (103) as part of a computing apparatus. The computing apparatus processes a plurality of payment card transactions. After the computing apparatus receives a request to track transactions for a loyalty program, such as the loyalty program rules (185), the computing apparatus stores and updates loyalty program information in response to transactions occurring in the loyalty program. The computing apparatus provides to a customer (e.g., 101) an offer of a benefit when the customer satisfies a condition defined in the loyalty program, such as the loyalty program rules (185). In one embodiment, the loyalty benefit as identified in the loyalty record (187) can be redeemed in connection with a transaction in a way the benefit of an offer stored in association with the account identifier (181) is redeemed.

Examples of loyalty programs through collaboration between collaborative constituents in a payment processing system, including the transaction handler (103) in one embodiment are provided in U.S. Pat. App. Pub. No. 2008/0059302, entitled "Loyalty Program Service," U.S. Pat. App. Pub. No. 2008/0059306, entitled "Loyalty Program Incentive Determination," and U.S. Pat. App. Pub. No. 2008/0059307, entitled "Loyalty Program Parameter Collaboration," the disclosures of which applications are hereby incorporated herein by reference.

Examples of processing the redemption of accumulated loyalty benefits via the transaction handler (103) in one embodiment are provided in U.S. Pat. App. Pub. No. 2008/0059303, entitled "Transaction Evaluation for Providing Rewards," the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the incentive, reward, or benefit provided in the loyalty program is based on the presence of correlated related transactions. For example, in one embodiment, an incentive is provided if a financial payment card is used in a reservation system to make a reservation and the financial payment card is subsequently used to pay for the reserved good or service. Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No.

2008/0071587, entitled “Incentive Wireless Communication Reservation,” the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the transaction handler (103) provides centralized loyalty program management, reporting and membership services. In one embodiment, membership data is downloaded from the transaction handler (103) to acceptance point devices, such as the transaction terminal (105). In one embodiment, loyalty transactions are reported from the acceptance point devices to the transaction handler (103); and the data indicating the loyalty points, rewards, benefits, etc. are stored on the account identification device (141). Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2004/0054581, entitled “Network Centric Loyalty System,” the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the portal (143) of the transaction handler (103) is used to manage reward or loyalty programs for entities such as issuers, merchants, etc. The cardholders, such as the user (101), are rewarded with offers/benefits from merchants. The portal (143) and/or the transaction handler (103) track the transaction records for the merchants for the reward or loyalty programs. Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2008/0195473, entitled “Reward Program Manager,” the disclosure of which is hereby incorporated herein by reference.

In one embodiment, a loyalty program includes multiple entities providing access to detailed transaction data, which allows the flexibility for the customization of the loyalty program. For example, issuers or merchants may sponsor the loyalty program to provide rewards; and the portal (143) and/or the transaction handler (103) stores the loyalty currency in the data warehouse (149). Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2009/0030793, entitled “Multi-Vender Multi-Loyalty Currency Program,” the disclosure of which is hereby incorporated herein by reference.

In one embodiment, an incentive program is created on the portal (143) of the transaction handler (103). The portal (143) collects offers from a plurality of merchants and stores the offers in the data warehouse (149). The offers may have associated criteria for their distributions. The portal (143) and/or the transaction handler (103) may recommend offers based on the transaction data (109). In one embodiment, the transaction handler (103) automatically applies the benefits of the offers during the processing of the transactions when the transactions satisfy the conditions associated with the offers. In one embodiment, the transaction handler (103) communicates with transaction terminals (105) to set up, customize, and/or update offers based on market focus, product categories, service categories, targeted consumer demographics, etc. Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2010/0049620, entitled “Merchant Device Support of an Integrated Offer Network,” the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the transaction handler (103) is configured to provide offers from merchants to the user (101) via the payment system, making accessing and redeeming the offers convenient for the user (101). The offers may be triggered by and/or tailored to a previous transaction, and may be valid only for a limited period of time starting from the date of the previous transaction. If the transaction handler (103) determines that a subsequent transaction processed by the transaction handler (103) meets the conditions for the redemption of an offer, the transaction

handler (103) may credit the consumer account (146) for the redemption of the offer and/or provide a notification message to the user (101). Further details and examples of one embodiment are provided in U.S. Pat. App. Pub. No. 2010/0114686, entitled “Real-Time Statement Credits and Notifications,” the disclosure of which is hereby incorporated herein by reference.

Details on loyalty programs in one embodiment are provided in U.S. Pat. App. Pub. No. 2011/0087530, entitled “Systems and Methods to Provide Loyalty Programs,” the disclosure of which is hereby incorporated herein by reference.

SKU

In one embodiment, merchants generate stock-keeping unit (SKU) or other specific information that identifies the particular goods and services purchased by the user (101) or customer. The SKU information may be provided to the operator of the transaction handler (103) that processed the purchases. The operator of the transaction handler (103) may store the SKU information as part of transaction data (109), and reflect the SKU information for a particular transaction in a transaction profile (127 or 131) associated with the person involved in the transaction.

When a user (101) shops at a traditional retail store or browses a website of an online merchant, an SKU-level profile associated specifically with the user (101) may be provided to select an advertisement appropriately targeted to the user (101) (e.g., via mobile phones, POS terminals, web browsers, etc.). The SKU-level profile for the user (101) may include an identification of the goods and services historically purchased by the user (101). In addition, the SKU-level profile for the user (101) may identify goods and services that the user (101) may purchase in the future. The identification may be based on historical purchases reflected in SKU-level profiles of other individuals or groups that are determined to be similar to the user (101). Accordingly, the return on investment for advertisers and merchants can be greatly improved.

In one embodiment, the user specific profile (131) is an aggregated spending profile (341) that is generated using the SKU-level information. For example, in one embodiment, the factor values (344) correspond to factor definitions (331) that are generated based on aggregating spending in different categories of products and/or services. A typical merchant offers products and/or services in many different categories.

In one embodiment, the SKU level purchase details are requested from the merchants or retailers via authorization responses (e.g., as illustrated in FIG. 9), when the account (146) of the user (101) is enrolled in a program that allows the transaction handler (103) (and/or the issuer processor (145)) to collect the purchase details. Based on the SKU information and perhaps other transaction data, the profile generator (121) may create an SKU-level transaction profile for the user (101). In one embodiment, based on the SKU information associated with the transactions for each person entering into transactions with the operator of the transaction handler (103), the profile generator (121) may create an SKU-level transaction profile for each person.

Details on SKU-level profile in one embodiment are provided in U.S. Pat. App. Pub. No. 2011/0093335, entitled “Systems and Methods for Advertising Services Based on an SKU-Level Profile,” the disclosure of which is hereby incorporated herein by reference.

Purchase Details

In one embodiment, the transaction handler (103) is configured to selectively request purchase details via authorization responses. When the transaction handler (103) (and/

or the issuer processor (145) needs purchase details, such as identification of specific items purchased and/or their prices, the authorization responses transmitted from the transaction handler (103) is to include an indicator to request for the purchase details for the transaction that is being authorized. The merchants are to determine whether or not to submit purchase details based on whether or not there is a demand indicated in the authorization responses from the transaction handler (103).

FIG. 9 shows a system to obtain purchase details according to one embodiment. In FIG. 9, when the user (101) uses the consumer account (146) to make a payment for a purchase, the transaction terminal (105) of the merchant or retailer sends an authorization request (168) to the transaction handler (103). In response, an authorization response (138) is transmitted from the transaction handler (103) to the transaction terminal (105) to inform the merchant or retailer of the decision to approve or reject the payment request, as decided by the issuer processor (145) and/or the transaction handler (103). The authorization response (138) typically includes an authorization code (137) to identify the transaction and/or to signal that the transaction is approved.

In one embodiment, when the transaction is approved and there is a need for purchase details (169), the transaction handler (103) (or the issuer processor (145)) is to provide an indicator of the request (139) for purchase details in the authorization response (138). The optional request (139) allows the transaction handler (103) (and/or the issuer processor (145)) to request purchase details (169) from the merchant or retailer on demand. When the request (139) for purchase details is present in the authorization response (138), the transaction terminal (105) is to provide the purchase details (169) associated with the payment transaction to the transaction handler (103) directly or indirectly via the portal (143). When the request (139) is absent from the authorization response (138), the transaction terminal (105) does not have to provide the purchase details (169) for the payment transaction.

In one embodiment, prior to transmitting the authorization response (138), the transaction handler (103) (and/or the issuer processor (145)) determines whether there is a need for transaction details. When there is no need for the purchase details (169) for a payment transaction, the request (139) for purchase details (169) is not provided in the authorization response (138) for the payment transaction. When there is a need for the purchase details (169) for a payment transaction, the request (139) for purchase details is provided in the authorization response (138) for the payment transaction. The merchants or retailers do not have to send detailed purchase data to the transaction handler (103) when the authorization response message does not explicitly request detailed purchase data.

Offer Redemption

FIG. 10 shows a system to automate the processing of offers in response to purchases made in various channels according to one embodiment.

In FIG. 10, the transaction handler (103) has a portal (143) and a data warehouse (149) storing the transaction data (109) recording the transactions processed by the transaction handler (103). The advertisement server (201) is to provide an advertisement (205) to the point of interaction (107), such as a web browser of the user (101).

In FIG. 10, the advertisement (205) is to include a link to the merchant website (203) and an offer (186) with a link to the portal (143). When the link to the merchant website (203) is selected on the point of interaction (107), the user (101) is to visit the merchant website (203) for further details

about the products and/or services of the merchant or advertiser. When the link to the portal (143) is selected, the offer (186) is identified to the portal (143) for association with a consumer account (146) of the user (101) identified by the account information (142).

In one embodiment, when the link to the portal (143) is selected, the user (101) is to provide the account information (142) to the portal (143) via the point of interaction (107) to identify the consumer account (146) of the user (101). After both the consumer account (146) of the user (101) and the offer (186) are identified, the data warehouse (149) is to store the data to associate offer (186) with the account information (142) in the account data (111) of the user (101).

In one embodiment, the account information (142) is pre-stored in the account data (111) of the user (101). The portal (143) is to authenticate the identity of the user (101) in response to the user selection of the link to the portal (143). After the user (101) is identified via authentication, the data warehouse (149) stores the data to associate offer (186) with the account information (142) in the account data (111) of the user (101).

In one embodiment, the account data (111) of the user (101) may have multiple consumer accounts (e.g., 146) under the control of one or more issuer processors (e.g., 145). When the user (101) has multiple consumer accounts (e.g., 146), the portal (143) is to prompt the user (101) to associate the offer (186) with one of the consumer accounts (e.g., 146). The transaction handler (103) and/or the portal (143) are to monitor the activity in the consumer account (e.g., 146) with which the offer (186) is associated to detect a transaction that qualifies for the redemption of the offer (186).

After the offer (186) is associated with account information (142), the transaction handler (103) and/or the portal (143) is to monitor the transaction activities in the corresponding consumer account (146) to detect one or more transactions that qualify for the redemption of the offer (186). For example, if the user (101) uses the account information (142) in the transaction terminal (105) to pay for a qualified purchase, the transaction handler (103) and/or the portal (143) is to identify the transaction from the multiplicity of transactions processed by the transaction handler (103) and to provide the benefit to the user (101) in accordance with the offer (186).

For example, in one embodiment, when processing a transaction at the transaction handler (103), the account information (142) involved in the transaction is checked to identify the associated offers (e.g., 186). If one or more offers (e.g., 186) are identified for the transaction, the transaction record for the transaction and/or other information about the transaction is used to determine if the redemption conditions of the offer (186) are met by the transaction. If the redemption conditions of the offer (186) are met, the transaction handler (103) is to redeem the offer (186) on behalf of the user (101) via statement credits to the consumer account (146) identified by the account information (142).

In one embodiment, when the user (101) has multiple consumer accounts (e.g., 146), the transaction handler (103) and/or the portal (143) is to monitor the activity in the multiple consumer accounts to detect a transaction that qualifies for the redemption of the offer (186). When a qualified transaction is detected in a consumer account (146), the transaction handler (103) is to provide the statement credits to the consumer account (146) with which the offer (186) is associated to detect a transaction that qualifies for the redemption of the offer (186). In one embodiment, when the user (101) has multiple consumer accounts (e.g.,

146), the portal (143) is to allow the user (101) to not associate the offer (186) with a particular consumer account; and when a qualified transaction is detected in a consumer account (146), the transaction handler (103) is to provide the statement credits to the consumer account (146) in which the qualified transaction occurred.

In one embodiment, the offer (186) is pre-registered in the data warehouse (149) prior to the delivery of the advertisement (205) from the advertisement sever (201) to the point of the interaction (107). For example, in one embodiment, the merchant or advertiser is to use the portal (143) to store data representing the offer (186) in the data warehouse (149). The data representing the offer (186) includes the specification of the benefit of the offer (186) and/or conditions for the redemption of the offer (186). In response, the portal (143) provides an identifier of the offer (186) to uniquely identify the offer (186) among a plurality of offers registered in the data warehouse (149). In one embodiment, the identifier of the offer (186) is included in the link to the portal (143) embedded in the advertisement (205). Thus, when the link containing the identifier of the offer (186) is selected, the identifier of the offer (186) is provided from the point of interaction (107) to the portal (143) to identify the offer (186).

In one embodiment, the pre-registration of the offer (186) in the data warehouse (149) by the merchant is not required. For example, the details of the offer (186), such as the specification of the benefit and the conditions for the redemption of the offer (186), are embedded in the link from the advertisement (205) to the portal (143). In one embodiment, the link from the advertisement (205) to the portal (143) includes a location from which the portal (143) can obtain the details of the offer (186). For example, in one embodiment, the details of the offer (186) are stored in the merchant website (203) and provided by the merchant website (203) via a web service. For example, in one embodiment, the details of the offer (186) are stored in the advertisement server (201), or a third party web service.

In FIG. 10, the advertisement (205) is provided by an advertisement server (201) that is distinct and separate from the portal (143). For example, the advertisement server (201) may be operated by a third party advertisement network, a search engine, a social networking website, an online marketplace, etc. In one embodiment, the advertisement (205) is presented in a web page of the advertisement server (201), such as in the search results of a search engine. In one embodiment, the advertisement (205) is presented in a web page of a third party media channel, such as a blog site, a social networking website, an online newspaper, etc. In one embodiment, the advertisement (205) is provided by the portal (143).

FIGS. 11-14 illustrate user interfaces for multi-channel offer redemption according to one embodiment. In FIG. 11, the presentation of content (407) in a website is illustrated. The content (407) may be presented with one or more advertisements (e.g., 409 and 401). In FIG. 11, the advertisement providing the offer (401) also has a portion (403) which can be selected using a cursor (405) (or other selection mechanisms, such as touch screen, voice command, etc.)

In one embodiment, when the portion (403) is selected as in FIG. 11, a user interface (411) as illustrated in FIG. 12 is presented to allow the user (101) to store the offer (401) on the web portal (143) (e.g., under the control of the transaction handler (103)).

The user (101) may have already logged into the web portal (143) using the web browser running on the point of

interaction (107) (e.g., as Ashley illustrated in FIG. 12). After the user (101) has logged into the web portal (143) using the web browser, the web portal (143) may store a browser cookie in the web browser of the user (101) to identify the user (101). Based on the cookie returned from the web browser while the user (101) follows the link embedded in the portion (403) of the advertisement, the user interface (411) prompts the user (101) to confirm the storing of the offer (401) in the account.

In FIG. 12, the link (413) allows the user (101) to log into a different account to store the offer (401), if the account as indicated by the browser cookie is not the account of the user (101), or not the desired account of the user (101). If the user (101) does not already have an account with the web portal (143), the user (101) may follow the link (415 or 413) to sign into the web portal (143) as a new user.

In one embodiment, the user (101) has multiple financial transaction cards supported by the web portal (143). The web portal (143) allows the user (101) to store the offer (401) with one of the financial transaction cards, as illustrated in FIG. 13. For example, in one embodiment, the user (101) may select the radio button using the cursor (405) to associate the offer (401) with the card having a number ending with "7776." When a transaction qualified for the offer (401) is made via the card that is associated with the offer (401), the web portal (143) is to automatically process the offer (401) for fulfillment/redemption.

In another embodiment, the offer (401) is stored in association with one or more (or all) of the cards identified in the account. Thus, the offer (401) can be redeemed in an automated way, when any of the associated cards is used to make the payment for the purchases that qualify for the offer (401).

FIG. 14 illustrates a user interface to allow the user (101) to sign in as an existing user or a new user of the web portal (143), when the browser does not have a valid browser cookie to identify the consumer account (146) of the user (101).

FIG. 15 illustrates a notification of offer redemption according to one embodiment, in which a notification message (423) is sent to the mobile phone (421) of the user (101) via wireless telecommunication (e.g., short message service (SMS), multi-media messaging service (MMS), email, instant message, voice message, etc.). In one embodiment, the message (423) is sent to the user (101) while the transaction submitted from the transaction terminal (105) is being processed by the transaction handler (103).

FIG. 16 illustrates a method for offer redemption according to one embodiment. In FIG. 16, a web portal (143) is designed to present (501) a user interface to a merchant to manage creation and distribution of an offer to be presented in an advertisement. A computer associated with web portal (143) is used to select (503) the advertisement for presentation to the user (101) based on substantially real-time activities in an account of the user (101). A web server is used to provide (505) the user (101) with the online advertisement having a first portion (403) linked to an offer redemption portal and a second portion (e.g., offer 401) optionally linked to a website of an advertiser. When the user (101) selects the first portion (403) of the advertisement, the web portal (143) presents (507) a user interface to allow the user (101) to associate the offer (401) with the account of the user (101). When the user (101) pays for a purchase as advertised by the advertisement using the account, the transaction handler (103) processes (509) the transaction in the account of the user (101) for the purchase and credits the account for redemption of the offer (401). The web portal

(143) may provide (511) a mobile message to the user (101) about the redemption while processing the transaction for the purchase and charge (513) the advertiser a predetermined fee for the advertisement, in response to the redemption of the offer (401).

FIGS. 17-21 illustrate screen images of a user interface for offer redemption according to one embodiment. FIG. 17 illustrates an example when a user (101) arrives at a publisher site like Media Channel ABC. At the Media Channel ABC website, the user (101) sees a Merchant XYZ offer (523) with the insert (521) linked to the portal (143). When the user (101) clicks the advertisement/offer (523) (not the insert (521)), the user (101) is taken to the Merchant XYZ website, as illustrated in FIG. 18. At the Merchant XYZ website, as illustrated in FIG. 18, the user (101) can click the "back" button (524) of the browser to return to the Media Channel ABC webpage illustrated in FIG. 17. In FIG. 17, if the user (101) clicks on the insert (521) and the user (101) is recognized by the offer redemption site (e.g., via a browser cookie), the offer redemption site (e.g., hosted on the portal (143)) displays the web page (526) in a separate window as illustrated in FIG. 19, which allows the user (101) to select a card of the user and save the offer (523) to the selected card. In FIG. 19, the advertisement/offer (523) is also displayed in the user interface (526) to store the offer (523), but without the insert (521). Once the user (101) clicks the "save" button (527), the offer redemption site displays a confirmation page as illustrated in FIG. 20.

In FIG. 20, the user (101) can click the "close" button (529) to close the window (533) and return to the Media Channel ABC website as illustrated in FIG. 20.

In one embodiment, the user (101) may also provide a phone number of a mobile phone (421) to the offer redemption site (e.g., as a user selected preference to receive mobile notification of saved offers); and once the offer (523) is saved with a card of the user (101), the offer redemption site can transmit a mobile message (537) to the user (101), as illustrated in FIG. 22.

If the user (101) is not recognized by the offer redemption site (e.g., via a browser cookie), or the user (101) clicks the "not John" link (525) in FIG. 19 to sign in as a different user of the offer redemption site, the offer redemption site displays the web page (535) as illustrated in FIG. 21 to allow the user (101) to sign in and to have the browser store a browser cookie to identify the user (101).

Further details and examples of one embodiment of offer fulfillment are provided in U.S. Pat. App. Pub. No. 2011/0288918, entitled "Systems and Methods for Redemption of Offers," the disclosure of which is hereby incorporated herein by reference.

Apply Offer

The transaction handler (103) of one embodiment is configured to process authorization/settlement requests to enable to real time discount at transaction terminal (105) in accordance with the offer (186) stored, in association with the account data (111) of the user (101), in the data warehouse (149) of the transaction handler (103).

FIG. 23 shows a system to apply a discount offer via an authorization request according to one embodiment. In FIG. 23, the authorization request (168) from the acquirer processor (147) to the issuer processor (145) is modified by the transaction handler (103) to apply the offer (186) to the transaction that satisfies the requirements of the offer (186).

In FIG. 23, after the transaction handler (103) receives the authorization request (168) from the acquirer processor (147), the transaction handler (103) determines whether the offer (186) is applicable to the transaction associated with

the authorization request (168). If the offer (186) is applicable, the transaction handler (103) changes the transaction amount A (601) to the transaction amount B (605) in the authorization request (168) transmitted to the issuer processor (145). If the issuer processor (145) authorizes the transaction amount B (605), the transaction handler (103) transmits to the transaction terminal (105), via the acquirer processor (147), the authorization response (138) to indicate the approval of the transaction amount B (605) and the applicable offer (186). The transaction terminal (105) is configured to accept the modified transaction amount B (605) and print the receipt that shows the applicable offer (186) and the application of the offer (186) to the transaction.

FIG. 24 shows a system to apply a discount offer via an authorization response according to one embodiment. In one embodiment, the authorization amount is not modified by transaction handler (103) during propagation of the authorization request (168) from the acquirer processor (147) to the issuer processor (145). In FIG. 24, the authorization response (138) from the issuer processor (145) to the acquirer processor (147) is modified by the transaction handler (103) to apply the offer (186) to the transaction that satisfies the requirements of the offer (186).

In FIG. 24, after the transaction handler (103) receives the authorization response (138) from the issuer processor (145), the transaction handler (103) determines whether the offer (186) is applicable to the transaction associated with the authorization response (138). If the offer (186) is applicable, the transaction handler (103) changes the transaction amount A (601) to the transaction amount B (605) in the authorization response (138) transmitted to the acquirer processor (147). In the embodiment, the authorization response (138) provided to the transaction terminal (105), via the acquirer processor (147), is further configured by the transaction handler (103) to indicate the applicable offer (186). The transaction terminal (105) is configured to accept the modify the transaction amount B (605), which is different from the initial transaction amount A (601) submitted by the transaction terminal (105) in the authorization request (168) to the acquirer processor (147), and print the receipt that shows the applicable offer (186) and the application of the offer (186) to the transaction.

In FIGS. 23 and 24, the transaction handler (103) is configured to apply the offer (186) during the authorization phase of the transaction to cause the receipt presented by the transaction terminal (105) to show that the benefit of the offer (186) has been applied to the transaction. For example, in one embodiment, the transaction terminal (105) is configured to provide a user interface that allows the merchant to accept the modified transaction amount (605) in view of the applicable offer (186) identified in the authorization response (138).

In one embodiment, the issuer processor (145) is configured to apply the offer (186) by change the authorization response (138).

In one embodiment, the acquirer processor (147) is configured to apply the offer (186) by change the authorization response (138) or the authorization request (168) (e.g., after receiving the authorization request (168) from the transaction terminal (105) and before transmitting the authorization request (168) having the modified transaction amount (605) to the transaction handler (103)).

In one embodiment, the transaction handler (103) further uses a communication reference (e.g., a mobile phone number, an email address, an instant message user identifier) that is stored in the account data (111) to provide a notification

to the user (101) about the applicable offer (186) and the benefit of the offer (186) that has been applied to the transaction, in parallel with the processing of the authorization request (168) and/or the authorization response (138). Details and examples of using such a communication reference for notification in one embodiment are provided in U.S. Pat. No. 8,359,274, entitled "Systems and Methods to Provide Messages in Real-Time with Transaction Processing," the disclosure of which is incorporated herein by reference in its entirety.

In one embodiment, the transaction handler (103) is configured to detect the applicability of the offer (186) during the settlement phase of the transaction and apply the applicable offer (186) during settlement of the transaction.

FIG. 25 shows a system to provide the benefit of an offer according to one embodiment. In FIG. 25, the data warehouse (149) coupled with the transaction handler (103) and the portal (143) is configured to store data associating the offer (186) with the account information (142) of the consumer account (146).

In one embodiment, the portal (143) is configured with a user interface to allow the user (101) of the consumer account (146) specify a communication reference (611) that is stored in association with the account information (142). If the user (101) provides the communication reference (611) for association with the account information (142), the user (101) is provided with notification services using the communication reference (611). Examples of the communication reference (611) include a phone number for notification via voice mails, a mobile phone number for notification via short message service or mobile application, an email address for notification via emails, a user name in an instant messaging system for notification via instant messages, a member ID of a social networking site for notification via messages transmitted via the social networking site, etc.

In FIG. 25, the data warehouse (149) is configured with one or more trigger records associated with the offer (186). The trigger record (613) specifies a set of conditions and identifies an action, which is to be performed when a transaction processed by the transaction handler (103) satisfies the set of conditions.

In FIG. 25, when the account information (142) is used at the transaction terminal (105) (e.g., a point of sales device) to initiate a transaction in the consumer account (146), the transaction terminal (105) communicates with the acquirer processor (147) to generate an authorization request (168). The transaction handler (103) is configured to receive the authorization request (168) from the acquirer processor (147) and identify the issuer processor (145) based on the account information (142).

In FIG. 25, transaction handler (103) is configured to determine whether or not the offer (186) is applicable to the authorization request (168), after receiving the authorization request (168) from the acquirer processor (147) and prior to sending the corresponding authorization request (168) to the issuer processor (145) associated with the account information (142). If the offer is applicable to the transaction associated with the authorization request (168), the transaction handler (103) changes the transaction amount according to the offer (186) and uses the changed transaction amount to communicate with the issuer processor (145) for the authorization of the transaction, in a way as illustrated in FIG. 23.

In FIG. 25, the transaction terminal (105) is configured to present the information about the offer (186) provided in the authorization response (138). Thus, the user (101) can verify

the application of the offer (186) to the transaction from the receipt produced by the transaction terminal (105). For example, the transaction terminal (105) uses a printer to produce a paper receipt.

In one embodiment, when the authorization response (138) received from the issuer processor (145) indicates the approval of the transaction that receives the benefit of the offer (186), the portal (143) is configured to use the communication reference (611) to send a notification to the point of interaction (107) of the user (101). The notification includes at least some of the above discussed information about the offer (186) that is applied to the authorization request (168) in the authorization response (168).

In FIG. 25, the application of the offer (186) is implemented via the transaction handler (103). Alternatively, the application of the offer (186) can be implemented in the acquirer processor (147), or the issuer processor (145), in a way similar to that described above in connection with the transaction handler (103).

FIG. 26 shows a method to provide the benefit of an offer according to one embodiment. In FIG. 26, a computing apparatus is configured to store (621) data associating an offer (186) and a consumer account (146) that is under control of an issuer processor (145) and associated with a communication reference (611), and receive (623) an authorization request (168) for the consumer account (146) from an acquirer processor (147). In response to the authorization request (168), the computing apparatus determines (625) whether the offer (186) is applicable; and if so, the computing apparatus adjusts (627) the transaction amount according to the offer (186) and communicates (629) with the issuer processor (145) to obtain authorization response (138).

Prior to communicating (635) the authorization response (138) to the transaction terminal (105) via the acquirer processor (138), the computing apparatus is configured to determine whether the offer (186) is applicable; and if so, the computing apparatus configures (633) the authorization response to identify the offer (186) and the benefit applied to the transaction in accordance with the offer (186) (e.g., the reduced transaction amount).

In one embodiment, when the authorization response approves the transaction, the computing apparatus is configured to optionally transmit (637) a notification about the offer (186) to the point of interaction (107) of the user (101) using the communication reference (611).

Further details and examples of applying offer benefit via adjusting transaction amount in some embodiments are provided in U.S. Pat. App. Pub. No. 2013/0124287, entitled "Systems and Methods to Provide Discount at Point of Sales Terminals," the disclosure of which is hereby incorporated herein by reference.

Variations

Some embodiments use more or fewer components than those illustrated in the figures.

In one embodiment, at least some of the profile generator (121), correlator (117), profile selector (129), and advertisement selector (133) are controlled by the entity that operates the transaction handler (103). In another embodiment, at least some of the profile generator (121), correlator (117), profile selector (129), and advertisement selector (133) are not controlled by the entity that operates the transaction handler (103).

In one embodiment, the products and/or services purchased by the user (101) are also identified by the information transmitted from the merchants or service providers. Thus, the transaction data (109) may include identification of the individual products and/or services, which allows the

profile generator (121) to generate transaction profiles (127) with fine granularity or resolution. In one embodiment, the granularity or resolution may be at a level of distinct products and services that can be purchased (e.g., stock-keeping unit (SKU) level), or category or type of products or services, or vendor of products or services, etc.

In one embodiment, the entity operating the transaction handler (103) provides the intelligence information in real time as the request for the intelligence information occurs. In other embodiments, the entity operating the transaction handler (103) may provide the intelligence information in batch mode. The intelligence information can be delivered via online communications (e.g., via an application programming interface (API) on a website, or other information server), or via physical transportation of a computer readable media that stores the data representing the intelligence information.

In one embodiment, the intelligence information is communicated to various entities in the system in a way similar to, and/or in parallel with the information flow in the transaction system to move money. The transaction handler (103) routes the information in the same way it routes the currency involved in the transactions.

In one embodiment, the portal (143) provides a user interface to allow the user (101) to select items offered on different merchant websites and store the selected items in a wish list for comparison, reviewing, purchasing, tracking, etc. The information collected via the wish list can be used to improve the transaction profiles (127) and derive intelligence on the needs of the user (101); and targeted advertisements can be delivered to the user (101) via the wish list user interface provided by the portal (143). Examples of user interface systems to manage wish lists are provided in U.S. Pat. App. Pub. No. 2010/0174623, entitled "System and Method for Managing Items of Interest Selected from Online Merchants," the disclosure of which is hereby incorporated herein by reference.

Aggregated Spending Profile

In one embodiment, the characteristics of transaction patterns of customers are profiled via clusters, factors, and/or categories of purchases. The transaction data (109) may include transaction records (301); and in one embodiment, an aggregated spending profile (341) is generated from the transaction records (301), in a way illustrated in FIG. 2, to summarize the spending behavior reflected in the transaction records (301).

In FIG. 2, each of the transaction records (301) is for a particular transaction processed by the transaction handler (103). Each of the transaction records (301) provides information about the particular transaction, such as the account number (302) of the consumer account (146) used to pay for the purchase, the date (303) (and/or time) of the transaction, the amount (304) of the transaction, the ID (305) of the merchant who receives the payment, the category (306) of the merchant, the channel (307) through which the purchase was made, etc. Examples of channels include online, offline in-store, via phone, etc. In one embodiment, the transaction records (301) may further include a field to identify a type of transaction, such as card-present, card-not-present, etc.

A "card-present" transaction typically involves physically presenting the account identification device (141), such as a financial transaction card, to the merchant (e.g., via swiping a credit card at a POS terminal of a merchant); and a "card-not-present" transaction typically involves presenting the account information (142) of the consumer account (146) to the merchant to identify the consumer account (146)

without physically presenting the account identification device (141) to the merchant or the transaction terminal (105).

The transaction records (301) of one embodiment may further include details about the products and/or services involved in the purchase.

When there is voluminous data representing the transaction records (301), the spending patterns reflected in the transaction records (301) can be difficult to recognize by an ordinary person.

In FIG. 2, the voluminous transaction records (301) are summarized (335) into aggregated spending profiles (e.g., 341) to concisely present the statistical spending characteristics reflected in the transaction records (301). The aggregated spending profile (341) uses values derived from statistical analysis to present the statistical characteristics of transaction records (301) of an entity in a way easy to understand by an ordinary person.

In FIG. 2, the transaction records (301) are summarized (335) via factor analysis (327) to condense the variables (e.g., 313, 315) and via cluster analysis (329) to segregate entities by spending patterns.

In FIG. 2, a set of variables (e.g., 311, 313, 315) are defined based on the parameters recorded in the transaction records (301). The variables (e.g., 311, 313, and 315) are defined in a way to have meanings easily understood by an ordinary person. For example, variables (311) measure the aggregated spending in super categories; variables (313) measure the spending frequencies in various areas; and variables (315) measure the spending amounts in various areas. In one embodiment, each of the areas is identified by a merchant category (306) (e.g., as represented by a merchant category code (MCC), a North American Industry Classification System (NAICS) code, or a similarly standardized category code). In other embodiments, an area may be identified by a product category, a SKU number, etc.

Examples of the spending frequency variables (313) and spending amount variables (315) defined for various merchant categories (e.g., 306) in one embodiment are provided in U.S. Pat. App. Pub. No. 2010/0306029, entitled "Cardholder Clusters," and in U.S. Pat. App. Pub. No. 2010/0306032, entitled "Systems and Methods to Summarize Transaction Data," the disclosures of which applications are hereby incorporated herein by reference.

In FIG. 2, the aggregation (317) includes the application of the definitions (309) for these variables (e.g., 311, 313, and 315) to the transaction records (301) to generate the variable values (321). The transaction records (301) are aggregated to generate aggregated measurements (e.g., variable values (321)) that are not specific to a particular transaction, such as frequencies of purchases made with different merchants or different groups of merchants, the amounts spent with different merchants or different groups of merchants, and the number of unique purchases across different merchants or different groups of merchants, etc. The aggregation (317) can be performed for a particular time period and for entities at various levels.

The transaction records (301) can be aggregated according to a buying entity, or a selling entity. For example, the aggregation (317) can be performed at account level, person level, family level, company level, neighborhood level, city level, region level, etc. to analyze the spending patterns across various areas (e.g., sellers, products or services) for the respective aggregated buying entity. For example, the transaction records (301) for a particular merchant having transactions with multiple accounts can be aggregated for a merchant level analysis. For example, the transaction

records (301) for a particular merchant group can be aggregated for a merchant group level analysis. The aggregation (317) can be formed separately for different types of transactions, such as transactions made online, offline, via phone, and/or “card-present” transactions vs. “card-not-present” transactions, which can be used to identify the spending pattern differences among different types of transactions.

In FIG. 2, the variable values (e.g., 323, 324, . . . , 325) associated with an entity ID (322) are considered the random samples of the respective variables (e.g., 311, 313, 315), sampled for the instance of an entity represented by the entity ID (322). Statistical analyses (e.g., factor analysis (327) and cluster analysis (329)) are performed to identify the patterns and correlations in the random samples.

Once the cluster definitions (333) are obtained from the cluster analysis (329), the identity of the cluster (e.g., cluster ID (343)) that contains the entity ID (322) can be used to characterize spending behavior of the entity represented by the entity ID (322). The entities in the same cluster are considered to have similar spending behaviors.

In FIG. 2, the random variables (e.g., 313 and 315) as defined by the definitions (309) have certain degrees of correlation and are not independent from each other. For example, merchants of different merchant categories (e.g., 306) may have overlapping business, or have certain business relationships. For example, certain products and/or services of certain merchants have cause and effect relationships. For example, certain products and/or services of certain merchants are mutually exclusive to a certain degree (e.g., a purchase from one merchant may have a level of probability to exclude the user (101) from making a purchase from another merchant). Such relationships may be complex and difficult to quantify by merely inspecting the categories. Further, such relationships may shift over time as the economy changes.

In FIG. 2, a factor analysis (327) is performed to reduce the redundancy and/or correlation among the variables (e.g., 313, 315). The factor analysis (327) identifies the definitions (331) for factors, each of which represents a combination of the variables (e.g., 313, 315). A factor from the factor analysis (327) is a linear combination of a plurality of the aggregated measurements (e.g., variables (313, 315)) determined for various areas (e.g., merchants or merchant categories, products or product categories). Once the relationship between the factors and the aggregated measurements is determined via factor analysis, the values for the factors can be determined from the linear combinations of the aggregated measurements and be used in a transaction profile (127 or 341) to provide information on the behavior of the entity represented by the entity ID (e.g., an account, an individual, a family).

Once the factor definitions (331) are obtained from the factor analysis (327), the factor definitions (331) can be applied to the variable values (321) to determine factor values (344) for the aggregated spending profile (341). Since redundancy and correlation are reduced in the factors, the number of factors is typically much smaller than the number of the original variables (e.g., 313, 315). Thus, the factor values (344) represent the concise summary of the original variables (e.g., 313, 315).

For example, there may be thousands of variables on spending frequency and amount for different merchant categories; and the factor analysis (327) can reduce the factor number to less than one hundred (and even less than twenty). In one example, a twelve-factor solution is obtained, which allows the use of twelve factors to combine the thousands of the original variables (313, 315); and thus, the spending

behavior in thousands of merchant categories can be summarized via twelve factor values (344). In one embodiment, each factor is combination of at least four variables; and a typical variable has contributions to more than one factor.

In FIG. 2, an aggregated spending profile (341) for an entity represented by an entity ID (e.g., 322) includes the cluster ID (343) and factor values (344) determined based on the cluster definitions (333) and the factor definitions (331). The aggregated spending profile (341) may further include other statistical parameters, such as diversity index (342), channel distribution (345), category distribution (346), zip code (347), etc., as further discussed below.

In general, an aggregated spending profile (341) may include more or fewer fields than those illustrated in FIG. 2. For example, in one embodiment, the aggregated spending profile (341) further includes an aggregated spending amount for a period of time (e.g., the past twelve months); in another embodiment, the aggregated spending profile (341) does not include the category distribution (346); and in a further embodiment, the aggregated spending profile (341) may include a set of distance measures to the centroids of the clusters.

FIG. 3 shows a method to generate an aggregated spending profile according to one embodiment. In FIG. 3, computation models are established (351) for variables (e.g., 311, 313, and 315). In one embodiment, the variables are defined in a way to capture certain aspects of the spending statistics, such as frequency, amount, etc.

In FIG. 3, data from related accounts are combined (353); recurrent/installment transactions are combined (355); and account data are selected (357) according to a set of criteria related to activity, consistency, diversity, etc.

In FIG. 3, the computation models (e.g., as represented by the variable definitions (309)) are applied (359) to the remaining account data (e.g., transaction records (301)) to obtain data samples for the variables. The data points associated with the entities, other than those whose transactions fail to meet the minimum requirements for activity, consistency, diversity, etc., are used in factor analysis (327) and cluster analysis (329).

In FIG. 3, the data samples (e.g., variable values (321)) are used to perform (361) factor analysis (327) to identify factor solutions (e.g., factor definitions (331)). The factor solutions can be adjusted (363) to improve similarity in factor values of different sets of transaction data (109).

The data samples can also be used to perform (365) cluster analysis (329) to identify cluster solutions (e.g., cluster definitions (333)). The cluster solutions can be adjusted (367) to improve similarity in cluster identifications based on different sets of transaction data (109). For example, cluster definitions (333) can be applied to the transactions in the time period under analysis (e.g., the past twelve months) and be applied separately to the transactions in a prior time period (e.g., the twelve months before the past twelve months) to obtain two sets of cluster identifications for various entities. The cluster definitions (333) can be adjusted to improve the correlation between the two set of cluster identifications.

Optionally, human understandable characteristics of the factors and clusters are identified (369) to name the factors and clusters. For example, when the spending behavior of a cluster appears to be the behavior of an internet loyalist, the cluster can be named “internet loyalist” such that if a cardholder is found to be in the “internet loyalist” cluster, the spending preferences and patterns of the cardholder can be easily perceived.

In one embodiment, the factor analysis (327) and the cluster analysis (329) are performed periodically (e.g., once a year, or six months) to update the factor definitions (331) and the cluster definitions (333), which may change as the economy and the society change over time.

In FIG. 3, transaction data (109) are summarized (371) using the factor solutions and cluster solutions to generate the aggregated spending profile (341). The aggregated spending profile (341) can be updated more frequently than the factor solutions and cluster solutions, when the new transaction data (109) becomes available. For example, the aggregated spending profile (341) may be updated quarterly or monthly.

Details about aggregated spending profile (341) in one embodiment are provided in U.S. Pat. App. Pub. No. 2010/0306032, entitled "Systems and Methods to Summarize Transaction Data," the disclosure of which is hereby incorporated herein by reference.

In one embodiment, a set of profiles are generated from the transaction data for a plurality of geographical regions, such as mutually exclusive, non-overlapping regions defined by postal codes. Transactions of account holders residing in the regions are aggregated according to merchant categories for the respective regions and subsequently normalized to obtain preference indicators that reveal the spending preferences of the account holders in the respective regions. Each of the profiles for respective regions is based on a plurality of different account holders and/or households to avoid revealing private information about individual account holders or families. Further, the profiles are constructed in a way to make it impossible to reverse calculate the transaction amounts. Further details and examples about profiles constructed for regions in one embodiment are provided in U.S. Pat. App. Pub. No. 2013/0124263, entitled "Systems and Methods to Summarize Transaction data," the disclosure of which is hereby incorporated herein by reference.

Transaction Processing and Data

FIG. 4 shows a system to provide information and/or services based on transaction data (109) according to one embodiment.

In FIG. 4, the transaction handler (103) is coupled between an issuer processor (145) and an acquirer processor (147) to facilitate authorization and settlement of transactions between a consumer account (146) and a merchant account (148). The transaction handler (103) records the transactions in the data warehouse (149). The portal (143) is coupled to the data warehouse (149) to provide information based on the transaction records (301), such as the transaction profiles (127), aggregated spending profile (341), offer redemption notification, etc. The portal (143) may be implemented as a web portal, a telephone gateway, a file/data server, etc.

In FIG. 4, the transaction terminal (105) initiates the transaction for a user (101) (e.g., a customer) for processing by a transaction handler (103). The transaction handler (103) processes the transaction and stores transaction data (109) about the transaction, in connection with account data (111), such as the account profile of an account of the user (101). The account data (111) may further include data about the user (101), collected from issuers or merchants, and/or other sources, such as social networks, credit bureaus, merchant provided information, address information, etc. In one embodiment, a transaction may be initiated by a server (e.g., based on a stored schedule for recurrent payments).

The accumulated transaction data (109) and the corresponding account data (111) are used to generate intelligence

information about the purchase behavior, pattern, preference, tendency, frequency, trend, amount and/or propensity of the users (e.g., 101), as individuals or as a member of a group. The intelligence information can then be used to generate, identify and/or select targeted advertisements for presentation to the user (101) on the point of interaction (107), during a transaction, after a transaction, or when other opportunities arise.

In FIG. 4, the consumer account (146) is under the control of the issuer processor (145). The consumer account (146) may be owned by an individual, or an organization such as a business, a school, etc. The consumer account (146) may be a credit account, a debit account, or a stored value account. The issuer may provide the consumer (e.g., user (101)) an account identification device (141) to identify the consumer account (146) using the account information (142). The respective consumer of the account (146) can be called an account holder or a cardholder, even when the consumer is not physically issued a card, or the account identification device (141), in one embodiment. The issuer processor (145) is to charge the consumer account (146) to pay for purchases.

The account identification device (141) of one embodiment is a plastic card having a magnetic strip storing account information (142) identifying the consumer account (146) and/or the issuer processor (145). Alternatively, the account identification device (141) is a smartcard having an integrated circuit chip storing at least the account information (142). The account identification device (141) may optionally include a mobile phone having an integrated smartcard.

The account information (142) may be printed or embossed on the account identification device (141). The account information (142) may be printed as a bar code to allow the transaction terminal (105) to read the information via an optical scanner. The account information (142) may be stored in a memory of the account identification device (141) and configured to be read via wireless, contactless communications, such as near field communications via magnetic field coupling, infrared communications, or radio frequency communications. Alternatively, the transaction terminal (105) may require contact with the account identification device (141) to read the account information (142) (e.g., by reading the magnetic strip of a card with a magnetic strip reader).

The transaction terminal (105) is configured to transmit an authorization request message to the acquirer processor (147). The authorization request includes the account information (142), an amount of payment, and information about the merchant (e.g., an indication of the merchant account (148)). The acquirer processor (147) requests the transaction handler (103) to process the authorization request, based on the account information (142) received in the transaction terminal (105). The transaction handler (103) routes the authorization request to the issuer processor (145) and may process and respond to the authorization request when the issuer processor (145) is not available. The issuer processor (145) determines whether to authorize the transaction based at least in part on a balance of the consumer account (146).

The transaction handler (103), the issuer processor (145), and the acquirer processor (147) may each include a subsystem to identify the risk in the transaction and may reject the transaction based on the risk assessment.

The account identification device (141) may include security features to prevent unauthorized uses of the consumer account (146), such as a logo to show the authenticity of the account identification device (141), encryption to protect the account information (142), etc.

The transaction terminal (105) of one embodiment is configured to interact with the account identification device (141) to obtain the account information (142) that identifies the consumer account (146) and/or the issuer processor (145). The transaction terminal (105) communicates with the acquirer processor (147) that controls the merchant account (148) of a merchant. The transaction terminal (105) may communicate with the acquirer processor (147) via a data communication connection, such as a telephone connection, an Internet connection, etc. The acquirer processor (147) is to collect payments into the merchant account (148) on behalf of the merchant.

In one embodiment, the transaction terminal (105) is a POS terminal at a traditional, offline, "brick and mortar" retail store. In another embodiment, the transaction terminal (105) is an online server that receives account information (142) of the consumer account (146) from the user (101) through a web connection. In one embodiment, the user (101) may provide account information (142) through a telephone call, via verbal communications with a representative of the merchant; and the representative enters the account information (142) into the transaction terminal (105) to initiate the transaction.

In one embodiment, the account information (142) can be entered directly into the transaction terminal (105) to make payment from the consumer account (146), without having to physically present the account identification device (141). When a transaction is initiated without physically presenting an account identification device (141), the transaction is classified as a "card-not-present" (CNP) transaction.

In general, the issuer processor (145) may control more than one consumer account (146); the acquirer processor (147) may control more than one merchant account (148); and the transaction handler (103) is connected between a plurality of issuer processors (e.g., 145) and a plurality of acquirer processors (e.g., 147). An entity (e.g., bank) may operate both an issuer processor (145) and an acquirer processor (147).

In one embodiment, the transaction handler (103), the issuer processor (145), the acquirer processor (147), the transaction terminal (105), the portal (143), and other devices and/or services accessing the portal (143) are connected via communications networks, such as local area networks, cellular telecommunications networks, wireless wide area networks, wireless local area networks, an intranet, and Internet. Dedicated communication channels may be used between the transaction handler (103) and the issuer processor (145), between the transaction handler (103) and the acquirer processor (147), and/or between the portal (143) and the transaction handler (103).

In FIG. 4, the transaction handler (103) uses the data warehouse (149) to store the records about the transactions, such as the transaction records (301) or transaction data (109).

Typically, the transaction handler (103) is implemented using a powerful computer, or cluster of computers functioning as a unit, controlled by instructions stored on a computer readable medium. The transaction handler (103) is configured to support and deliver authorization services, exception file services, and clearing and settlement services. The transaction handler (103) has a subsystem to process authorization requests and another subsystem to perform clearing and settlement services. The transaction handler (103) is configured to process different types of transactions, such credit card transactions, debit card transactions, prepaid card transactions, and other types of commercial transactions. The transaction handler (103) interconnects the issuer

processors (e.g., 145) and the acquirer processor (e.g., 147) to facilitate payment communications.

In FIG. 4, the transaction terminal (105) is configured to submit the authorized transactions to the acquirer processor (147) for settlement. The amount for the settlement may be different from the amount specified in the authorization request. The transaction handler (103) is coupled between the issuer processor (145) and the acquirer processor (147) to facilitate the clearing and settling of the transaction. Clearing includes the exchange of financial information between the issuer processor (145) and the acquirer processor (147); and settlement includes the exchange of funds.

In FIG. 4, the issuer processor (145) is configured to provide funds to make payments on behalf of the consumer account (146). The acquirer processor (147) is to receive the funds on behalf of the merchant account (148). The issuer processor (145) and the acquirer processor (147) communicate with the transaction handler (103) to coordinate the transfer of funds for the transaction. The funds can be transferred electronically.

The transaction terminal (105) may submit a transaction directly for settlement, without having to separately submit an authorization request.

In one embodiment, the portal (143) provides a user interface to allow the user (101) to organize the transactions in one or more consumer accounts (146) of the user with one or more issuers. The user (101) may organize the transactions using information and/or categories identified in the transaction records (301), such as merchant category (306), transaction date (303), amount (304), etc. Examples and techniques in one embodiment are provided in U.S. Pat. App. Pub. No. 2007/0055597, entitled "Method and System for Manipulating Purchase Information," the disclosure of which is hereby incorporated herein by reference.

In one embodiment, the portal (143) provides transaction based statistics, such as indicators for retail spending monitoring, indicators for merchant benchmarking, industry/market segmentation, indicators of spending patterns, etc. Further examples can be found in U.S. Pat. App. Pub. No. 2009/0048884, entitled "Merchant Benchmarking Tool," the disclosures of which applications are hereby incorporated herein by reference.

Transaction Terminal

FIG. 5 illustrates a transaction terminal according to one embodiment. The transaction terminal (105) illustrated in FIG. 5 can be used in various systems discussed in connection with other figures of the present disclosure. In FIG. 5, the transaction terminal (105) is configured to interact with an account identification device (141) to obtain account information (142) about the consumer account (146).

In one embodiment, the transaction terminal (105) includes a memory (167) coupled to the processor (151), which controls the operations of a reader (163), an input device (153), an output device (165) and a network interface (161). The memory (167) may store instructions for the processor (151) and/or data, such as an identification that is associated with the merchant account (148).

In one embodiment, the reader (163) includes a magnetic strip reader. In another embodiment, the reader (163) includes a contactless reader, such as a radio frequency identification (RFID) reader, a near field communications (NFC) device configured to read data via magnetic field coupling (in accordance with ISO standard 14443/NFC), a Bluetooth transceiver, a WiFi transceiver, an infrared transceiver, a laser scanner, etc.

In one embodiment, the input device (153) includes key buttons that can be used to enter the account information

(142) directly into the transaction terminal (105) without the physical presence of the account identification device (141). The input device (153) can be configured to provide further information to initiate a transaction, such as a personal identification number (PIN), password, zip code, etc. that may be used to access the account identification device (141), or in combination with the account information (142) obtained from the account identification device (141).

In one embodiment, the output device (165) may include a display, a speaker, and/or a printer to present information, such as the result of an authorization request, a receipt for the transaction, an advertisement, etc.

In one embodiment, the network interface (161) is configured to communicate with the acquirer processor (147) via a telephone connection, an Internet connection, or a dedicated data communication channel.

In one embodiment, the instructions stored in the memory (167) are configured at least to cause the transaction terminal (105) to send an authorization request message to the acquirer processor (147) to initiate a transaction. The transaction terminal (105) may or may not send a separate request for the clearing and settling of the transaction. The instructions stored in the memory (167) are also configured to cause the transaction terminal (105) to perform other types of functions discussed in this description.

In one embodiment, a transaction terminal (105) may have fewer components than those illustrated in FIG. 5. For example, in one embodiment, the transaction terminal (105) is configured for “card-not-present” transactions; and the transaction terminal (105) does not have a reader (163).

In one embodiment, a transaction terminal (105) may have more components than those illustrated in FIG. 5. For example, in one embodiment, the transaction terminal (105) is an ATM machine, which includes components to dispense cash under certain conditions.

Account Identification Device

FIG. 6 illustrates an account identifying device according to one embodiment. In FIG. 6, the account identification device (141) is configured to carry account information (142) that identifies the consumer account (146).

In one embodiment, the account identification device (141) includes a memory (167) coupled to the processor (151), which controls the operations of a communication device (159), an input device (153), an audio device (157) and a display device (155). The memory (167) may store instructions for the processor (151) and/or data, such as the account information (142) associated with the consumer account (146).

In one embodiment, the account information (142) includes an identifier identifying the issuer (and thus the issuer processor (145)) among a plurality of issuers, and an identifier identifying the consumer account among a plurality of consumer accounts controlled by the issuer processor (145). The account information (142) may include an expiration date of the account identification device (141), the name of the consumer holding the consumer account (146), and/or an identifier identifying the account identification device (141) among a plurality of account identification devices associated with the consumer account (146).

In one embodiment, the account information (142) may further include a loyalty program account number, accumulated rewards of the consumer in the loyalty program, an address of the consumer, a balance of the consumer account (146), transit information (e.g., a subway or train pass), access information (e.g., access badges), and/or consumer information (e.g., name, date of birth), etc.

In one embodiment, the memory includes a nonvolatile memory, such as magnetic strip, a memory chip, a flash memory, a Read Only Memory (ROM), etc. to store the account information (142).

In one embodiment, the information stored in the memory (167) of the account identification device (141) may also be in the form of data tracks that are traditionally associated with credits cards. Such tracks include Track 1 and Track 2. Track 1 (“International Air Transport Association”) stores more information than Track 2, and contains the cardholder’s name as well as the account number and other discretionary data. Track 1 is sometimes used by airlines when securing reservations with a credit card. Track 2 (“American Banking Association”) is currently most commonly used and is read by ATMs and credit card checkers. The ABA (American Banking Association) designed the specifications of Track 1 and banks abide by it. It contains the cardholder’s account number, encrypted PIN, and other discretionary data.

In one embodiment, the communication device (159) includes a semiconductor chip to implement a transceiver for communication with the reader (163) and an antenna to provide and/or receive wireless signals.

In one embodiment, the communication device (159) is configured to communicate with the reader (163). The communication device (159) may include a transmitter to transmit the account information (142) via wireless transmissions, such as radio frequency signals, magnetic coupling, or infrared, Bluetooth or WiFi signals, etc.

In one embodiment, the account identification device (141) is in the form of a mobile phone, personal digital assistant (PDA), etc. The input device (153) can be used to provide input to the processor (151) to control the operation of the account identification device (141); and the audio device (157) and the display device (155) may present status information and/or other information, such as advertisements or offers. The account identification device (141) may include further components that are not shown in FIG. 6, such as a cellular communications subsystem.

In one embodiment, the communication device (159) may access the account information (142) stored on the memory (167) without going through the processor (151).

In one embodiment, the account identification device (141) has fewer components than those illustrated in FIG. 6. For example, an account identification device (141) does not have the input device (153), the audio device (157) and the display device (155) in one embodiment; and in another embodiment, an account identification device (141) does not have components (151-159).

For example, in one embodiment, an account identification device (141) is in the form of a debit card, a credit card, a smartcard, or a consumer device that has optional features such as magnetic strips, or smartcards.

An example of an account identification device (141) is a magnetic strip attached to a plastic substrate in the form of a card. The magnetic strip is used as the memory (167) of the account identification device (141) to provide the account information (142). Consumer information, such as account number, expiration date, and consumer name may be printed or embossed on the card. A semiconductor chip implementing the memory (167) and the communication device (159) may also be embedded in the plastic card to provide account information (142) in one embodiment. In one embodiment, the account identification device (141) has the semiconductor chip but not the magnetic strip.

In one embodiment, the account identification device (141) is integrated with a security device, such as an access card, a radio frequency identification (RFID) tag, a security card, a transponder, etc.

In one embodiment, the account identification device (141) is a handheld and compact device. In one embodiment, the account identification device (141) has a size suitable to be placed in a wallet or pocket of the consumer.

Some examples of an account identification device (141) include a credit card, a debit card, a stored value device, a payment card, a gift card, a smartcard, a smart media card, a payroll card, a health care card, a wrist band, a keychain device, a supermarket discount card, a transponder, and a machine readable medium containing account information (142).

Point of Interaction

In one embodiment, the point of interaction (107) is to provide an advertisement to the user (101), or to provide information derived from the transaction data (109) to the user (101).

In one embodiment, an advertisement is a marketing interaction which may include an announcement and/or an offer of a benefit, such as a discount, incentive, reward, coupon, gift, cash back, or opportunity (e.g., special ticket/admission). An advertisement may include an offer of a product or service, an announcement of a product or service, or a presentation of a brand of products or services, or a notice of events, facts, opinions, etc. The advertisements can be presented in text, graphics, audio, video, or animation, and as printed matter, web content, interactive media, etc. An advertisement may be presented in response to the presence of a financial transaction card, or in response to a financial transaction card being used to make a financial transaction, or in response to other user activities, such as browsing a web page, submitting a search request, communicating online, entering a wireless communication zone, etc. In one embodiment, the presentation of advertisements may be not a result of a user action.

In one embodiment, the point of interaction (107) can be one of various endpoints of the transaction network, such as point of sale (POS) terminals, automated teller machines (ATMs), electronic kiosks (or computer kiosks or interactive kiosks), self-assist checkout terminals, vending machines, gas pumps, websites of banks (e.g., issuer banks or acquirer banks of credit cards), bank statements (e.g., credit card statements), websites of the transaction handler (103), websites of merchants, checkout websites or web pages for online purchases, etc.

In one embodiment, the point of interaction (107) may be the same as the transaction terminal (105), such as a point of sale (POS) terminal, an automated teller machine (ATM), a mobile phone, a computer of the user for an online transaction, etc. In one embodiment, the point of interaction (107) may be co-located with, or near, the transaction terminal (105) (e.g., a video monitor or display, a digital sign), or produced by the transaction terminal (e.g., a receipt produced by the transaction terminal (105)). In one embodiment, the point of interaction (107) may be separate from and not co-located with the transaction terminal (105), such as a mobile phone, a personal digital assistant, a personal computer of the user, a voice mail box of the user, an email inbox of the user, a digital sign, etc.

For example, the advertisements can be presented on a portion of media for a transaction with the customer, which portion might otherwise be unused and thus referred to as a "white space" herein. A white space can be on a printed matter (e.g., a receipt printed for the transaction, or a printed

credit card statement), on a video display (e.g., a display monitor of a POS terminal for a retail transaction, an ATM for cash withdrawal or money transfer, a personal computer of the customer for online purchases), or on an audio channel (e.g., an interactive voice response (IVR) system for a transaction over a telephonic device).

In one embodiment, the white space is part of a media channel available to present a message from the transaction handler (103) in connection with the processing of a transaction of the user (101). In one embodiment, the white space is in a media channel that is used to report information about a transaction of the user (101), such as an authorization status, a confirmation message, a verification message, a user interface to verify a password for the online use of the account information (142), a monthly statement, an alert or a report, or a web page provided by the portal (143) to access a loyalty program associated with the consumer account (146) or a registration program.

In other embodiments, the advertisements can also be presented via other media channels which may not involve a transaction processed by the transaction handler (103). For example, the advertisements can be presented on publications or announcements (e.g., newspapers, magazines, books, directories, radio broadcasts, television, digital signage, etc., which may be in an electronic form, or in a printed or painted form). The advertisements may be presented on paper, on websites, on billboards, on digital signs, or on audio portals.

In one embodiment, the transaction handler (103) purchases the rights to use the media channels from the owner or operators of the media channels and uses the media channels as advertisement spaces. For example, white spaces at a point of interaction (e.g., 107) with customers for transactions processed by the transaction handler (103) can be used to deliver advertisements relevant to the customers conducting the transactions; and the advertisement can be selected based at least in part on the intelligence information derived from the accumulated transaction data (109) and/or the context at the point of interaction (107) and/or the transaction terminal (105).

In general, a point of interaction (e.g., 107) may or may not be capable of receiving inputs from the customers, and may or may not co-located with a transaction terminal (e.g., 105) that initiates the transactions. The white spaces for presenting the advertisement on the point of interaction (107) may be on a portion of a geographical display space (e.g., on a screen), or on a temporal space (e.g., in an audio stream).

In one embodiment, the point of interaction (107) may be used to primarily to access services not provided by the transaction handler (103), such as services provided by a search engine, a social networking website, an online marketplace, a blog, a news site, a television program provider, a radio station, a satellite, a publisher, etc.

In one embodiment, a consumer device is used as the point of interaction (107), which may be a non-portable consumer device or a portable computing device. The consumer device is to provide media content to the user (101) and may receive input from the user (101).

Examples of non-portable consumer devices include a computer terminal, a television set, a personal computer, a set-top box, or the like. Examples of portable consumer devices include a portable computer, a cellular phone, a personal digital assistant (PDA), a pager, a security card, a wireless terminal, or the like. The consumer device may be implemented as a data processing system as illustrated in FIG. 7, with more or fewer components.

In one embodiment, the consumer device includes an account identification device (141). For example, a smart card used as an account identification device (141) is integrated with a mobile phone, or a personal digital assistant (PDA).

In one embodiment, the point of interaction (107) is integrated with a transaction terminal (105). For example, a self-service checkout terminal includes a touch pad to interact with the user (101); and an ATM machine includes a user interface subsystem to interact with the user (101).

Hardware

In one embodiment, a computing apparatus is configured to include some of the components of systems illustrated in various figures, such as the transaction handler (103), the profile generator (121), the media controller (115), the portal (143), the profile selector (129), the advertisement selector (133), the user tracker (113), the correlator, and their associated storage devices, such as the data warehouse (149).

In one embodiment, at least some of the components such as the transaction handler (103), the transaction terminal (105), the point of interaction (107), the user tracker (113), the media controller (115), the correlator (117), the profile generator (121), the profile selector (129), the advertisement selector (133), the portal (143), the issuer processor (145), the acquirer processor (147), and the account identification device (141), can be implemented as a computer system, such as a data processing system (170) illustrated in FIG. 7. Some of the components may share hardware or be combined on a computer system. In one embodiment, a network of computers can be used to implement one or more of the components.

Further, the data illustrated in the figures, such as transaction data (109), account data (111), transaction profiles (127), and advertisement data (135), can be stored in storage devices of one or more computers accessible to the corresponding components. For example, the transaction data (109) can be stored in the data warehouse (149) that can be implemented as a data processing system illustrated in FIG. 7, with more or fewer components.

In one embodiment, the transaction handler (103) is a payment processing system, or a payment card processor, such as a card processor for credit cards, debit cards, etc.

FIG. 7 illustrates a data processing system according to one embodiment. While FIG. 7 illustrates various components of a computer system, it is not intended to represent any particular architecture or manner of interconnecting the components. One embodiment may use other systems that have fewer or more components than those shown in FIG. 7.

In FIG. 7, the data processing system (170) includes an inter-connect (171) (e.g., bus and system core logic), which interconnects a microprocessor(s) (173) and memory (167). The microprocessor (173) is coupled to cache memory (179) in the example of FIG. 7.

In one embodiment, the inter-connect (171) interconnects the microprocessor(s) (173) and the memory (167) together and also interconnects them to input/output (I/O) device(s) (175) via I/O controller(s) (177). I/O devices (175) may include a display device and/or peripheral devices, such as mice, keyboards, modems, network interfaces, printers, scanners, video cameras and other devices known in the art. In one embodiment, when the data processing system is a server system, some of the I/O devices (175), such as printers, scanners, mice, and/or keyboards, are optional.

In one embodiment, the inter-connect (171) includes one or more buses connected to one another through various bridges, controllers and/or adapters. In one embodiment the I/O controllers (177) include a USB (Universal Serial Bus)

adapter for controlling USB peripherals, and/or an IEEE-1394 bus adapter for controlling IEEE-1394 peripherals.

In one embodiment, the memory (167) includes one or more of: ROM (Read Only Memory), volatile RAM (Random Access Memory), and non-volatile memory, such as hard drive, flash memory, etc.

Volatile RAM is typically implemented as dynamic RAM (DRAM) which requires power continually in order to refresh or maintain the data in the memory. Non-volatile memory is typically a magnetic hard drive, a magnetic optical drive, an optical drive (e.g., a DVD RAM), or other type of memory system which maintains data even after power is removed from the system. The non-volatile memory may also be a random access memory.

The non-volatile memory can be a local device coupled directly to the rest of the components in the data processing system. A non-volatile memory that is remote from the system, such as a network storage device coupled to the data processing system through a network interface such as a modem or Ethernet interface, can also be used.

In this description, some functions and operations are described as being performed by or caused by software code to simplify description. However, such expressions are also used to specify that the functions result from execution of the code/instructions by a processor, such as a microprocessor.

Alternatively, or in combination, the functions and operations as described here can be implemented using special purpose circuitry, with or without software instructions, such as using Application-Specific Integrated Circuit (ASIC) or Field-Programmable Gate Array (FPGA). Embodiments can be implemented using hardwired circuitry without software instructions, or in combination with software instructions. Thus, the techniques are limited neither to any specific combination of hardware circuitry and software, nor to any particular source for the instructions executed by the data processing system.

While one embodiment can be implemented in fully functioning computers and computer systems, various embodiments are capable of being distributed as a computing product in a variety of forms and are capable of being applied regardless of the particular type of machine or computer-readable media used to actually effect the distribution.

At least some aspects disclosed can be embodied, at least in part, in software. That is, the techniques may be carried out in a computer system or other data processing system in response to its processor, such as a microprocessor, executing sequences of instructions contained in a memory, such as ROM, volatile RAM, non-volatile memory, cache or a remote storage device.

Routines executed to implement the embodiments may be implemented as part of an operating system or a specific application, component, program, object, module or sequence of instructions referred to as "computer programs." The computer programs typically include one or more instructions set at various times in various memory and storage devices in a computer, and that, when read and executed by one or more processors in a computer, cause the computer to perform operations necessary to execute elements involving the various aspects.

A machine readable medium can be used to store software and data which when executed by a data processing system causes the system to perform various methods. The executable software and data may be stored in various places including for example ROM, volatile RAM, non-volatile memory and/or cache. Portions of this software and/or data

may be stored in any one of these storage devices. Further, the data and instructions can be obtained from centralized servers or peer to peer networks. Different portions of the data and instructions can be obtained from different centralized servers and/or peer to peer networks at different times and in different communication sessions or in a same communication session. The data and instructions can be obtained in entirety prior to the execution of the applications. Alternatively, portions of the data and instructions can be obtained dynamically, just in time, when needed for execution. Thus, it is not required that the data and instructions be on a machine readable medium in entirety at a particular instance of time.

Examples of computer-readable media include but are not limited to recordable and non-recordable type media such as volatile and non-volatile memory devices, read only memory (ROM), random access memory (RAM), flash memory devices, floppy and other removable disks, magnetic disk storage media, optical storage media (e.g., Compact Disk Read-Only Memory (CD ROMS), Digital Versatile Disks (DVDs), etc.), among others. The computer-readable media may store the instructions.

The instructions may also be embodied in digital and analog communication links for electrical, optical, acoustical or other forms of propagated signals, such as carrier waves, infrared signals, digital signals, etc. However, propagated signals, such as carrier waves, infrared signals, digital signals, etc. are not tangible machine readable medium and are not configured to store instructions.

In general, a machine readable medium includes any mechanism that provides (i.e., stores and/or transmits) information in a form accessible by a machine (e.g., a computer, network device, personal digital assistant, manufacturing tool, any device with a set of one or more processors, etc.).

In various embodiments, hardwired circuitry may be used in combination with software instructions to implement the techniques. Thus, the techniques are neither limited to any specific combination of hardware circuitry and software nor to any particular source for the instructions executed by the data processing system.

Other Aspects

The description and drawings are illustrative and are not to be construed as limiting. The present disclosure is illustrative of inventive features to enable a person skilled in the art to make and use the techniques. Various features, as described herein, should be used in compliance with all current and future rules, laws and regulations related to privacy, security, permission, consent, authorization, and others. Numerous specific details are described to provide a thorough understanding. However, in certain instances, well known or conventional details are not described in order to avoid obscuring the description. References to one or an embodiment in the present disclosure are not necessarily references to the same embodiment; and, such references mean at least one.

The use of headings herein is merely provided for ease of reference, and shall not be interpreted in any way to limit this disclosure or the following claims.

Reference to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the disclosure. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment, and are not necessarily all referring to separate or alternative embodiments mutually exclusive of other embodiments. Moreover, various features are described

which may be exhibited by one embodiment and not by others. Similarly, various requirements are described which may be requirements for one embodiment but not other embodiments. Unless excluded by explicit description and/or apparent incompatibility, any combination of various features described in this description is also included here. For example, the features described above in connection with “in one embodiment” or “in some embodiments” can be all optionally included in one implementation, except where the dependency of certain features on other features, as apparent from the description, may limit the options of excluding selected features from the implementation, and incompatibility of certain features with other features, as apparent from the description, may limit the options of including selected features together in the implementation.

The disclosures of the above discussed patent documents are hereby incorporated herein by reference.

In the foregoing specification, the disclosure has been described with reference to specific exemplary embodiments thereof. It will be evident that various modifications may be made thereto without departing from the broader spirit and scope as set forth in the following claims. The specification and drawings are, accordingly, to be regarded in an illustrative sense rather than a restrictive sense.

What is claimed is:

1. A method, comprising:

receiving, with at least one processor, an authorization request for a payment transaction involving a payment account of a user from an electronic payment processing network, wherein the authorization request comprises an account identifier of the payment account of the user;

determining, with at least one processor, an offer associated with a loyalty program of a plurality of loyalty programs for the user and details of the offer;

transmitting, with at least one processor, a redemption notification to a computing device, the redemption notification comprising the offer and the details of the offer;

causing, with at least one processor, a user interface to be provided on the computing device, wherein the user interface includes a selectable element to cause the computing device to transmit a confirmation message;

receiving, with at least one processor, the confirmation message from the computing device within a first time period of receiving the authorization request or a second time period that follows the first time period;

adjusting, with at least one processor, the payment transaction based on the details of the offer included in the confirmation message, wherein adjusting the payment transaction comprises:

adjusting the payment transaction by transmitting an authorization response for the authorization request based on the confirmation message when the confirmation message is received within the first time period; and

transmitting the authorization response for the authorization request based on preferences and rules identified in a user profile of the user and adjusting the payment transaction based on the details of the offer during settlement of the payment transaction when the confirmation message is received within the second time period;

receiving, with at least one processor, an authorization response from an issuer processor associated with the payment account of the user; and

65

processing, with at least one processor, the offer after receiving the authorization response.

2. The method of claim 1, wherein the offer is associated with a redemption of loyalty currencies from a reward account of a loyalty program of the plurality of loyalty programs.

3. The method of claim 2, further comprising: redeeming the loyalty currencies from the reward account of the loyalty program of the plurality of loyalty programs according to the details of the offer and applying the loyalty currencies to the payment transaction.

4. The method of claim 1, wherein transmitting the redemption notification to the computing device comprises: transmitting the redemption notification to the computing device via a communication reference of the computing device; and

wherein the computing device comprises a mobile phone and the communication reference includes a phone number of the mobile phone.

5. The method of claim 1, wherein the selectable element of the user interface is selectable when the redemption notification is presented on the computing device.

6. The method of claim 5, wherein the user interface comprises:

another selectable element associated with an option to modify the details of the redemption of loyalty currencies to generate a modified redemption plan.

7. The method of claim 6, further comprising, in response to receiving the modified redemption plan within a predetermined time period from transmitting the redemption notification:

redeeming loyalty rewards based on the modified redemption plan; and

applying the loyalty rewards to the payment transaction.

8. The method of claim 7, wherein the loyalty rewards are applied to the payment transaction during authorization of the payment transaction.

9. The method of claim 7, wherein the loyalty rewards are applied to the payment transaction during settlement of the payment transaction.

10. The method of claim 6, further comprising: redeeming loyalty rewards from a reward account of a loyalty program of the plurality of loyalty programs according to the details of the offer in response to not receiving the modified redemption plan within a predetermined time period from transmitting the redemption notification; and

applying the loyalty rewards to the payment transaction.

11. A system, comprising:

at least one processor programmed or configured to:

receive an authorization request for a payment transaction involving a payment account of a user from an electronic payment processing network, wherein the authorization request comprises an account identifier of the payment account of the user;

determine an offer associated with a loyalty program of a plurality of loyalty programs for the user and details of the offer;

transmit a redemption notification to a computing device, the redemption notification comprising the offer and the details of the offer;

cause a user interface to be provided on the computing device, wherein the user interface includes a selectable element to cause the computing device to transmit a confirmation message;

66

receive the confirmation message from the computing device within a first time period of receiving the authorization request or a second time period that follows the first time period;

adjust the payment transaction based on the details of the offer included in the confirmation message, wherein when adjusting the payment transaction, the at least one processor is programmed or configured to: adjust the payment transaction by transmitting an authorization response for the authorization request based on the confirmation message when the confirmation message is received within the first time period; and

transmit an authorization response for the authorization request based on preferences and rules identified in a user profile of the user and adjust the payment transaction based on the details of the offer during settlement of the payment transaction when the confirmation message is received within the second time period;

receive an authorization response from an issuer processor associated with the payment account of the user; and

process the offer after receiving the authorization response.

12. The system of claim 11, wherein the offer is associated with a redemption of a loyalty currencies from a reward account of a loyalty program of the plurality of loyalty programs.

13. The system of claim 12, wherein the at least one processor is further programmed or configured to: redeem the loyalty currencies from the reward account of the loyalty program of the plurality of loyalty programs according to the details of the offer and applying the loyalty currencies to the payment transaction.

14. The system of claim 11, wherein, when transmitting the redemption notification to the computing device, the at least one processor is programmed or configured to:

transmit the redemption notification to the computing device via a communication reference of the computing device; and

wherein the computing device comprises a mobile phone and the communication reference includes a phone number of the mobile phone.

15. The system of claim 11, wherein the selectable element is selectable when the redemption notification is presented on the computing device.

16. A computer program product comprising at least one non-transitory computer-readable medium including one or more instructions that, when executed by at least one processor, cause the at least one processor to:

receive an authorization request for a payment transaction involving a payment account of a user from an electronic payment processing network, wherein the authorization request comprises an account identifier of the payment account of the user;

determine an offer associated with a loyalty program of a plurality of loyalty programs for the user and details of the offer;

transmit a redemption notification to a computing device, the redemption notification comprising the offer and the details of the offer;

cause a user interface to be provided on the computing device, wherein the user interface includes a selectable element to cause the computing device to transmit a confirmation message;

67

receive the confirmation message from the computing device within a first time period of receiving the authorization request or a second time period that follows the first time period;
 adjust the payment transaction based on the details of the offer included in the confirmation message, wherein the one or more instructions that cause the at least one processor to adjust the payment transaction, cause the at least one processor to:
 adjust the payment transaction by transmitting an authorization response for the authorization request based on the confirmation message when the confirmation message is received within the first time period; and
 transmit the authorization response for the authorization request based on preferences and rules identified in a user profile of a user and adjust the payment transaction based on the details of the offer during settlement of the payment transaction when the confirmation message is received within the second time period;
 receive an authorization response from an issuer processor associated with the payment account of the user; and
 process the offer after receiving the authorization response.

68

17. The computer program product of claim 16, wherein the offer is associated with a redemption of a loyalty currencies from a reward account of a loyalty program of the plurality of loyalty programs.
 18. The computer program product of claim 17, wherein the one or more instructions further cause the at least one processor to:
 redeem the loyalty currencies from the reward account of the loyalty program of the plurality of loyalty programs according to the details of the offer and applying the loyalty currencies to the payment transaction.
 19. The computer program product of claim 11, wherein the one or more instructions that cause the at least one processor to transmit the redemption notification to the computing device, cause the at least one processor to:
 transmit the redemption notification to the computing device via a communication reference of the computing device; and
 wherein the computing device comprises a mobile phone and the communication reference includes a phone number of the mobile phone.
 20. The computer program product of claim 11, wherein the selectable element of the user interface is selectable when the redemption notification is presented on the computing device.

* * * * *