

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199861538 B2
(10) Patent No. 738919

(54) Title
Oxygen scavenger accelerator

(51)⁷ International Patent Classification(s)
A23L 003/3436

(21) Application No: **199861538** (22) Application Date: **1998.02.06**

(87) WIPO No: **WO98/51168**

(30) Priority Data

(31) Number **08/856448** (32) Date **1997.05.14** (33) Country **US**

(43) Publication Date : **1998.12.08**

(43) Publication Journal Date : **1999.01.28**

(44) Accepted Journal Date : **2001.09.27**

(71) Applicant(s)
Pactiv Corporation

(72) Inventor(s)
Gary Delduca; Alan E. Deyo; Vindod K. Luthra; Wen P. Wu

(74) Agent/Attorney
DAVIES COLLISON CAVE,GPO Box 3876,SYDNEY NSW 2001

(56) Related Art
US 4762722
GB 1556853



IN

(51) International Patent Classification ⁶ : A23L 3/3436		A1	(11) International Publication Number: WO 98/51168 (43) International Publication Date: 19 November 1998 (19.11.98)
(21) International Application Number: PCT/US98/02532 (22) International Filing Date: 6 February 1998 (06.02.98) (30) Priority Data: 08/856,448 14 May 1997 (14.05.97) US <i>Packaging Corporation</i> (71) Applicant: TENNECO PACKAGING INC. [US/US]; 1900 West Field Court, Lake Forest, IL 60045 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(72) Inventors: DELDUCA, Gary; 82 Howell Street, Canandaigua, NY 14424 (US). DEYO, Alan, E.; 66 South Main Street, Rushville, NY 14544 (US). LUTHRA, Vindod, K.; 21 Barrington Hills, Pittsford, NY 14534 (US). WU, Wen, P.; 4 Silver Pines Drive, Pittsford, NY 14534 (US). (74) Agent: BOLDINGH, Mary Jo; Arnold, White & Durkee, P.O. Box 4433, Houston, TX 77210 (US).		Published <i>With international search report.</i>	
(54) Title: OXYGEN SCAVENGER ACCELERATOR			
(57) Abstract			
<p>An iron-based oxygen scavenging packet is set forth in which the rate of uptake of oxygen is increased by virtue of the presence of an oxygen uptake accelerator such as water which is introduced into the packet. Methods of increasing the rate of oxygen absorption by the iron-based oxygen scavenging packet are also set forth.</p>			



OXYGEN SCAVENGER ACCELERATOR

FIELD OF THE INVENTION

The present invention relates generally to a device and method for maximizing the rate of oxygen uptake of an oxygen absorber. More particularly, the invention relates 5 to an iron based oxygen scavenging packet having an improved composition for accelerating the rate of oxygen absorption wherein the packet is specifically designed to be used in a packaging system designed to keep meat fresh.

BACKGROUND OF THE INVENTION

Perishable foods, such as meats, fruits, and vegetables are typically placed into 10 packaging systems after harvesting in order to preserve these foods for as long as possible. Maximizing the time in which the food remains preserved, especially the time between initial packaging at the plant and delivery at the retail grocery store, increases the profitability of all entities in the chain of distribution by minimizing the amount of spoilage.

15 The environment in which the food is preserved is a critical factor in the preservation process. Not only is maintaining an adequate temperature important, but the molecular and chemical content of the gases surrounding the food is important as well. By providing an appropriate gas content to the environment surrounding the food, the food can be better preserved when maintained at the proper temperature or even when it 20 is exposed to variations in temperature. This gives the food producer some assurance that after the food leaves his or her control, the food will be in an acceptable condition when it reaches the retail grocery store and ultimately, the consumer.

In meat packaging, in particular, packaging systems which provide extremely low 25 levels of oxygen are desirable because it is well known that the fresh quality of meat can be preserved longer under anaerobic conditions than under aerobic conditions.

Maintaining low levels of oxygen minimizes the growth and multiplication of aerobic bacteria.

One way to insure a minimal level of oxygen in a meat package is to subject the package or rigid gas barrier materials to a vacuum in order to remove as much of the gas 30 in the package as possible prior to sealing the package. The package can then be sealed

and the meat maintained in a "zero" atmosphere environment (commonly referred to as vacuum packaging). Under vacuum packaging conditions, red meat turns purple. Consumers, however, prefer to see their meat bright red. As a result, vacuum packaging has not been well accepted for consumer cuts of meat.

5 Another means of insuring a minimal level of oxygen in a meat package is to seal the meat in a refill modified atmosphere packaging system. This kind of modified atmosphere packaging technology (MAP) is so successful that meat can be cut and packaged several weeks before purchase and still remain fresh. Such systems typically utilize multiple layers of packaging. The outside layer of packaging is generally a rigid
10 container with good barrier properties. The inner layer of packaging is an oxygen permeable film. To provide a modified atmosphere environment, the air-evacuated package is typically filled with a mixture of gases consisting of about 30 percent carbon dioxide (CO₂) and 70 percent nitrogen (N₂). Refilling the air-evacuated package with such a mixture of gases is believed to suppress the growth of anaerobic bacteria. The
15 outer layer is peeled off just prior to presenting the consumer cut for sale at the supermarket. This allows the meat to rebloom to a bright red color. An excellent example of such an evacuation and refill MAP process is described in U.S. Patent No. 5,115,624 to Garwood. Vacuum packaging and refill MAP is very expensive for three reasons. First, the rigid part of the package is expensive. Second, processing speeds are
20 slow due to the vacuum and refill steps. And third, the equipment to do these procedures is very complicated and expensive.

Another less expensive means of insuring a minimal level of oxygen in a meat package is to use a gas flush MAP process. The complicated steps of evacuating the package and refilling with the desired gas mixture are eliminated. The outer bag (a
25 barrier layer), is simply flushed with the proper gas mixture as it is formed around the inner container. The flush process reduces the oxygen content of the package to about two percent. An oxygen scavenger is placed in the package to absorb additional oxygen just prior to or simultaneously with forming and flushing the outer bag. An excellent example of such a MAP system is described in the patent application entitled "Modified
30 Atmosphere Package" filed on April 3, 1996, and given Serial No. 08/627,137.

just prior to or simultaneously with forming and flushing the outer bag. An excellent example of such a MAP system is described in the patent application entitled "Modified Atmosphere Package" filed on April 3, 1996, and given Serial No. 08/627,137.

A critical feature of a gas flush MAP packaging system is the ability to keep meat 5 looking fresh and palatable. Oxidised meat turns an undesirable brown colour. Accordingly, as discussed, an oxygen scavenger is typically placed inside the meat package in order to absorb any residual oxygen within the package after gas flushing and sealing the package. It is critically important to quickly remove the oxygen from meat to prevent it from turning brown. Especially important in preventing the irreversible change 10 from red to brown is the rate at which oxygen is scavenged. If oxygen is removed quickly, the packaged meat turns a purple red colour. This purple red colour quickly "blooms" to a bright red colour upon removal of the outer layer of packaging.

Oxygen scavengers are increasingly being used in packaging systems in order to protect various products from the detrimental effects of oxygen exposure. Several oxygen 15 scavengers utilise the oxidation of particulate iron as a method to absorb oxygen. A small amount of water is essential for this reaction. In some instances, a water attracting agent such as silica gel can be used to attract water and at times to supply water in the packet initially. A major drawback to this technology is, however, the limited amount of water that can be supplied. Typically, a major portion of the water needed for the oxidation of 20 particulate iron is provided by the product and/or packaging environment being protected. This is oftentimes an inadequate amount to promote the efficient and expedient oxidation of iron. And as mentioned, the slower the rate of oxygen reduction, the more likely meat will turn irreversibly brown.

A need thus exists to accelerate the rate of oxygen scavengers, particularly in the 25 confines of a modified atmosphere packaging system. Optimally, it would be desirable to lower the oxygen level to about 0.04 percent (400 PPM) within 90 minutes and to about zero within 24 hours. This need will be addressed by the present invention.

SUMMARY OF THE INVENTION

In one broad form the present invention seeks to provide an oxygen scavenging packet, 30 comprising:



- 4 -

- a. an oxygen permeable material formed into a closed packet for holding an oxygen absorber;
- b. an oxygen absorber comprising iron within the packet of (a); and
- c. a liquid oxygen uptake accelerator, said accelerator comprising water, said

5 accelerator being present in an amount relative to the amount of said oxygen absorber, such that when the liquid accelerator and oxygen absorber are brought into contact the oxygen absorber is capable of reducing the oxygen content of a predetermined volume containing about 2 vol. % oxygen to less than 0.5 vol. % oxygen at a temperature of about 34°F in no more than 90 minutes after said accelerator and oxygen absorber are brought

10 into contact.

In another broad form the present invention seeks to provide a method of reducing the oxygen concentration in an enclosed space comprising:

- a. placing an oxygen scavenging packet within said enclosed space, said oxygen scavenging packet comprising:
 - i. an oxygen permeable material formed into a closed packet; and
 - ii. an oxygen absorber within said closed packet, said oxygen absorber comprising iron;
- b. introducing a liquid oxygen uptake accelerator comprising water directly onto said oxygen absorber, wherein said liquid oxygen uptake accelerator is introduced in

20 an amount relative to the amount of said oxygen absorber, such that when the oxygen uptake accelerator and oxygen absorber are brought into contact, the oxygen absorber is capable of reducing the oxygen content of a predetermined volume containing about 2 vol. % oxygen to less than 0.5 vol. % oxygen at a temperature of about 34°F in no more than 90 minutes after said oxygen uptake accelerator and oxygen absorber are brought into contact.

25 **BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention will become more fully understood from the following detailed description of a preferred but non-limiting embodiments thereof, described in connection with the accompanying drawings wherein:

30 FIG. 1 illustrates an oxygen scavenging packet in which the oxygen uptake accelerator is being introduced into the packet via a syringe.



- 4A -

FIGS. 2a and 2b, respectively, illustrate an oxygen scavenging packet containing a capsule which can be ruptured at an appropriate time to release the oxygen uptake accelerator and a packet containing a capsule being ruptured.

FIGS. 3a and 3b, respectively, illustrate an oxygen scavenging packet including a
5 protruding wick for absorption of the oxygen uptake accelerator into the packet and an oxygen scavenging packet in which the wick is being dipped into the oxygen scavenger accelerator.

FIG. 4 is an isometric view of the oxygen scavenging packet of the instant invention inside a modified atmosphere packaging system.

10 FIG. 5 is a graph illustrating the rate of oxygen absorption when a dry oxygen scavenging packet is introduced into a quart sized container which also includes 0.5 ml of water.

15 FIG. 6 is a graph illustrating the rate of oxygen absorption when an oxygen scavenging packet having 0.5 ml of water injected into the packet is introduced into a quart sized container.

FIG. 7 is a graph illustrating the rate of oxygen absorption as a function of the amount of water injected into oxygen scavenging packets.



FIG. 9 is a graph illustrating the rate of oxygen absorption as a function of the number of oxygen scavenging packets introduced into a one quart jar.

FIG. 10 is a graph showing the percent oxygen after 1 hour as a function of the amount of acetic acid (vinegar) injected into each of two oxygen scavenging packets.

5 FIG. 11 is a graph showing the percent oxygen as a function of time and as a function of the material injected into the oxygen scavenging packets.

FIG. 12 is a graph illustrating the rate of oxygen absorption as a function of the amount of acetic acid injected into an iron containing packet and further as a function of whether or not the packet contains impregnated silica gel.

10 FIG. 13 is a graph illustrating the rate of oxygen absorption as a function of time and the concentration of acetic acid in water.

While the invention is susceptible to various modifications and alternative forms, certain specific embodiments thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the 15 intention is not to limit the invention to the particular forms described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Turning now to the drawings, FIGS. 1 through 3 (a and b) depict an oxygen 20 scavenging packet having a liquid oxygen uptake accelerator present in some form within the packet.

Specifically, FIG. 1 depicts an oxygen scavenging packet 10 containing elemental iron 12 and in which an oxygen uptake accelerator 14 is introduced into the packet utilizing a syringe 16. Injection can be performed manually with a syringe and hand 25 placement of the packet inside the package. Alternatively, the injection process can be automated by using a commercially available metering and dispensing pump such as the Luft Systematic model 45/50 and appropriate conveying equipment to position the packets for injection and then subsequently to place the packets into a package.

FIG. 2a depicts an oxygen scavenging packet 20 containing elemental iron 22 and 30 in which an oxygen uptake accelerator 24 is present inside a capsule 26. As FIG. 2b shows, the capsule 26 may be ruptured by mechanical force at an appropriate time in

order to release the oxygen uptake accelerator 24. Optimally, the capsule should be ruptured immediately prior to or immediately after the sealing of the package in order to properly activate the iron-based scavenger for accelerated oxygen uptake.

FIG. 3a depicts an iron-based oxygen scavenging packet 30 containing elemental 5 iron (not specifically shown) and in which an oxygen uptake accelerator 32 can be introduced into the packet by absorption onto a wick 34 which protrudes from the packet. As FIG. 3b shows, the wick 34 dipped into the oxygen uptake accelerator 32. An appropriate amount of oxygen uptake accelerator 32 is absorbed through the wick 34 into the packet 30. Optimally, the dipping occurs immediately prior to the sealing of the 10 package in order to properly activate the iron based scavenger for accelerated oxygen uptake.


Further information concerning the construction of the oxygen absorber packet preferred for use in the instant invention may be obtained from U.S. Patent No. 5,262,375 to McKedy, entitled "Oxygen Absorber." The preferred oxygen absorber 15 packets are manufactured by Multiform Desiccants Incorporated. However, other iron-based oxygen absorbers will work comparably well in the instant invention.

The instant invention particularly concerns an iron-based oxygen scavenging packet which contains an oxygen uptake accelerator consisting of water or an aqueous solution of some other substance dissolved in or mixed with water. The oxygen uptake 20 accelerator accelerates the rate of oxygen uptake of the oxygen absorber. Water alone will activate and accelerate iron-based oxygen absorbers via the presence of hydronium ions in the water. However, dilute acid solutions are preferred oxygen uptake accelerators.


Acids provide increased numbers of hydronium ions which increase the oxidation 25 rate of iron by acting as electron acceptors. These electron acceptors facilitate the ionization of neutral iron. Once ionized, the iron readily reacts with the available oxygen and water to form a hydrated iron oxide. Other electron acceptors such as the positively charged ions making up salt solutions or metals such as copper also facilitate the ionization of neutral iron.

The preferred aqueous solution of the instant invention is an aqueous solution 30 which contains approximately five percent acetic acid.

The introduction of water or an aqueous solution of acid, salt or appropriate metal into the oxygen absorber packet of an iron-based oxygen absorber serves to activate and dramatically increase the rate of oxygen uptake of the iron inside the packet. The particulate iron in the packet, in effect, turns to rust as oxygen is absorbed from the 5 atmosphere surrounding the packaged meat or other packaged food product. As discussed, the water or aqueous solution enhances oxygen absorption by the iron by acting as an electron acceptor. A proposed mechanism for rust formation is as follows:



In step (1) ferrous ions are produced by loss of electrons from the elemental particulate iron in the packet. However, this process cannot go very far unless there is some way to get rid of the electrons which accumulate on the residual Fe. One way to do 15 this is by step (2) in which H_3O^+ ions either from the water or from acid substances in the water, pick up the electrons to form neutral H atoms. Since Fe is known to be a good catalyst for hydrogenation reactions in general, it is believed that step (3) now occurs to use up the H atoms. In the meantime, the ferrous ion reacts with O_2 gas by step (4) to form the rust and restore H_3O^+ required for step (2). The net reaction, obtained by adding 20 all four steps is



Acid accelerates the reaction by providing excess hydronium ions (H_3O^+) and driving step 2. Therefore, the preferred embodiment of the present invention utilizes a dilute aqueous solution of acid. Such acid solutions should, of course, be compatible 25 with food products and include, for instance, acetic acid and/or citric acid.

Salt solutions also drive step (2) of the aforementioned reaction by providing an electron acceptor, thus they are suitable for use in the aqueous solution of the instant invention. Additionally, it has been found that adding copper to water and/or dilute aqueous solution of acid speeds the rate of oxygen absorption by the iron. It is believed 30 that the copper induces a phenomena called electrolytic corrosion. Electrons flow from

the iron to the copper, where their energy is lower. This removes the excess negative charge from the iron. In addition H atoms, which now form on the negative copper surface instead of the iron, detach themselves more readily from copper than from iron, thus accelerating step (3) of the aforementioned reaction.

5 As shown in FIGS. 1-3 (a and b), the aqueous solution can be introduced into the packet utilizing an injection type process. Alternatively, the solution can be included in the absorber packet in a separate capsule or compartment which can be ruptured at the time of sealing the meat package. Also, a wick could be included in, and protrude from, the packet such that the wick could be dipped in liquid just prior to sealing the meat
10 package.

A preferred embodiment of the present invention involves the injection of an oxygen uptake accelerator comprising water into the MRM absorbers manufactured by Multiform Desiccants Incorporated. This is done just prior to the placement of the absorber into a package. This can be done manually with a syringe and hand placement
15 or the process can be automated by using a commercially available metering and dispensing pump such as the Luft Systematic model 45/50 and appropriate conveying equipment to position the packets for injection and then subsequently to place the packets into a package.

The following data, depicted in FIGS. 5-13 and in Table 1 is specific to
20 Multiform's MRM 100 scavenger packets. All of these experiments involve using these scavengers. The MRM 100 oxygen scavengers are specifically formulated to work in the presence of CO₂ and refrigeration. MRM 100 oxygen scavengers contain approximately 2.5 grams of iron and silica gel impregnated with a carbon dioxide generator, NaHCO₃. A carbon dioxide generator is utilized to replace gas volume in the sealed meat package
25 as O₂ is absorbed. The iron in MRM absorbers is electrolytically reduced and annealed which means that the iron is reduced by the passage of electric current through a solution of the iron which is in the form of a molten salt. As one skilled in the art will appreciate, while MRM 100 scavenger packets were used in the following described experiments, similarly constituted scavenger packets would be expected to have comparably enhanced
30 oxygen scavenging activities with the addition of water and other accelerators.

FIGS. 5 and 6 illustrate that the oxygen uptake accelerator, in this case water, must be contained within the oxygen scavenging packet in order to increase the rate of oxygen absorption. Specifically, FIG. 5 shows the decrease in percent oxygen as a function of time when 0.5 ml of water is merely present in a quart-sized jar along with an oxygen scavenging packet. As shown in FIG. 5, at 40°F it takes approximately 30 hours for the percent oxygen to be reduced to approximately 0.5% (5,000 PPM) and more than 40 hours for the percent oxygen to be reduced to near 0.0% oxygen. By contrast, FIG. 6 shows the decrease in percent oxygen as a function of time when 0.5 ml of water is injected into an oxygen scavenging packet which is then placed in a quart-sized jar. At 10 40°F, it takes approximately 15 hours for the percent oxygen to be reduced to approximately 0.5% and about 20 hours for the percent oxygen to be reduced to near 0.0% oxygen. At 70°F, oxygen is scavenged much more quickly.

FIG. 7 shows that the oxygen scavenging rate is maximized when 0.6 ml of water is present in the oxygen scavenging packet.

15 FIG. 8 shows that oxygen absorption appears to be independent of the amount of carbon dioxide in the container.

FIG. 9 shows that two oxygen scavenging packets absorb oxygen at nearly twice the rate of one packet.

As shown in FIG. 10, acetic acid, commonly known as vinegar acid, works 20 particularly well in accelerating the rate of oxygen absorption of an MRM oxygen scavenger packet. Specifically, the injection of .5 ml. of acetic acid into each of two absorber packets reduces the amount of oxygen in a quart jar to approximately .1% O₂ (1000 PPM) in one hour. As shown in FIG. 11, the percent O₂ is reduced to approximately .04% O₂ (400 PPM) in about ninety minutes when .5 ml. of acetic acid is 25 injected into each of two MRM 100 scavenger packets. Two conclusions can be drawn from the data in FIGS. 10 and 11. First, injected acetic acid seems to work better than plain water in increasing the rate of oxygen absorption of an absorber packet. Second, from FIG. 10, .5 ml. acetic acid appears to work particularly well in increasing the rate and total amount of oxygen absorption. In the experiments resulting in the data in FIGS. 30 10 and 11, the starting level of oxygen in the jars was 2.0%, simulating the amount of

oxygen which would be present after the gas flush step of a gas flush MAP process. Also, the experiments were performed under refrigeration.

Below is a table which shows the results of an experiment designed to determine the range of amounts of water needed to be introduced into an oxygen scavenging packet containing approximately 2.5 grams of iron in order to satisfactorily activate the packets in a gas flush MAP packaging process for red meat.

TABLE 1

Sample No.	Water Injection	Initial Oxygen	Final Oxygen	Color Rating - 1.5 hrs. Of Bloom (Day 8)	Color Rating - 24 hrs. Of Bloom (Day 9)
1	.8 ml	1.9%	0.00%	Dark Red	Some Browning
2	.6 ml	1.24%	0.00%	Dark Red	Bright Red
3	1.0 ml	2.30%	0.26%	Major Browning	Major Browning
4	.4 ml	2.20%	0.00%	Dark Red	Bright Red
5	.2 ml	1.70%	0.00%	Dark Red	Dark Red
6	.4 ml	1.50%	14.9%	Excluded (Leaked)	Excluded
7	.8 ml	1.70%	0.00%	Dark Red	Dark Red
8	.6 ml	1.55%	0.00%	Dark Red	Bright Red
9	1.0 ml	2.20%	0.00%	Dark Red	Some Browning
10	.2 ml	2.40%	0.00%	Major Browning	Major Browning

The results show that water injections greater than .2 ml but less than .8 ml per 2.5 grams of iron (approximately 100cc of absorber capacity) are required. For adequate oxygen scavenging, water injections must be within this range, preferably at .6 milliliters. Water injections outside of this range will result in a high risk of metmyoglobin formation (browning) due to initial oxygen exposure. This experiment was performed utilizing Multiform's MRM oxygen scavengers but other similar iron-based absorbers are believed to work comparably.

15 EXAMPLE 1 - Determination of Range of Water Volume Necessary for Optimal Oxygen Scavenging of an Iron Based Oxygen Scavenging Packet

A ten pound chunk of fresh boneless beef (five days post mortem) was cut into ten pieces and individually placed on meat trays or a soaker pad. The meat trays had one and one half inch tall side walls. The meat

and trays were then stretch wrapped with a standard PVC film on a Hobart machine. After wrapping, a half inch diameter hole was created through the PVC in one corner of the tray to allow free flow of gases in and out of this "inner package." Next, two MRM 100 scavengers were injected with 5 a precisely measured amount of water and attached to one of the inner packages containing the beef. The water injections were varied from .2 to 1.0 mils per scavenger. The inner package, with the oxygen absorbers attached, was then immediately run through a Fuji/Foremost form fill and seal machine and packaged in a flushed outer bag made from Print Pack 10 861D 2.5 mil barrier film. The flush gas was approximately 80% nitrogen and 20% carbon dioxide. The initial O₂ level in the barrier bag was measured through a rubber septum with a Dansensor oxygen analyzer and recorded. The completed packages were then placed in a refrigerator and stored at 34°F for eight days. On the eighth day the final oxygen level was 15 measured and the barrier bag and oxygen absorbers removed. The meat was allowed to rebloom in the inner package for one and a half hours in the refrigerator. At that time the packages were removed from the refrigerator and the meat visually rated for color acceptability. The packages were then returned to the refrigerator for another 24 hours after 20 which the meat was again rated for color acceptability.

The tray that was used for the experiment detailed in Example 1 and the data detailed in Table 1 left a significant amount of air space surrounding the meat, necessitating the use of two MRM 100 scavengers. However, beef has been successfully packaged on shallow wall meat trays 25 using only one MRM 100 scavenger with a .5 ml injection of acetic acid.

FIG. 12 shows that maximum oxygen absorption occurs at an amount of vinegar between about .4 and .6 ml acetic acid. FIG. 12 also illustrates that maximum oxygen absorption occurs when the oxygen scavenging packet contains silica gel impregnated with NaHCO₃ in addition to iron. MRM-100 absorbers and other similarly formulated absorbers employ silica gel to absorb and release atmospheric H₂O. As discussed 30 previously, silica gel will not by itself absorb enough water to satisfactorily accelerate

the oxygen scavenging ability of the iron to allow for the preservation of meats for longer than a few days at a time. For this reason, the present inventors have affirmatively added concrete amounts of water to the oxygen scavenging packets of the instant invention.

FIG. 13 shows the rate of oxygen absorption as a function of time and the 5 concentration of acetic acid in water. As can be seen, 5% acetic acid performs very well at accelerating the rate of oxygen absorption at 30, 60 and 90 minutes. Furthermore, 5% acetic acid is very easy to obtain, being common table vinegar.

The present invention is particularly useful when used in a modified atmosphere packaging (MAP) process for fresh meats. The MAP process is a gas flush process that 10 initially flushes the package to an oxygen atmosphere of about two percent or less. The oxygen scavenging packet of the instant invention is utilized to additionally reduce the oxygen level of the package to 400 PPM (0.04%) or less within ninety minutes.

A brief description of the typical modified atmosphere package will follow. This 15 description is not meant to be limiting, but instead is provided merely to elucidate one particular use for the instant invention.

FIG. 4 depicts a modified atmosphere package 40 including an outer container 42 and an inner container 44. The inner container 44 includes a conventional semi-rigid plastic tray 46 thermoformed from a sheet of polymeric material which is substantially permeable to oxygen. Exemplary polymers which may be used to form the non-barrier 20 tray 46 include polystyrene foam, cellulose pulp, polyethylene, polypropylene, etc. In a preferred embodiment, the polymeric sheet used to form the tray 46 is substantially composed of polystyrene foam and has a thickness ranging from about 100 mils to about 300 mils. The use of a common polystyrene foam tray 46 is desirable because it has a high consumer acceptance. The inner container 44 further includes a stretch film 25 wrapping or cover 48 substantially composed of a polymeric material, such as polyvinyl chloride (PVC), which is substantially permeable to oxygen. In a preferred embodiment, the stretch film used to form the cover 48 contains additives which allow the film to cling to itself and has a thickness ranging from about 0.5 mil to about 1.5 mils. One preferred stretch film is Resinite™ meat film commercially available from Borden Packaging and 30 Industrial Products of North Andover, Massachusetts.

A food item such as a retail cut of raw meat 50 is located inside the inner container 44. Prior to fully wrapping the tray 46 with the cover 48, the partially formed inner container 44 may be flushed with an appropriate mixture of gases, typically a mixture of about 30 percent carbon dioxide and about 70 percent nitrogen, to lower the 5 oxygen level in the inner container 44 to about 1.5 to 5.0 percent. The foregoing mixture of gases displaces the oxygen within the inner container 44 during the flushing operation. After flushing the inner container 44, the tray 46 is manually or automatically wrapped with the cover 48. The cover 48 is wrapped over the retail cut of raw meat 50 and about 10 the bottom of the tray 46. The free ends of the cover 48 are overlapped along the underside of the bottom wall of the tray 46, and, due to the cling characteristic inherent in the cover 48, these overlapping free ends cling to one another to hold the cover 48 in place. If desired, the overwrapped tray 46, i.e., the inner container 44, may be run over a hot plate to thermally fuse the free ends of the cover 48 to one another and thereby prevent these free ends from potentially unraveling.

15 The outer container 42 is preferably a flexible polymeric bag composed of a single or multilayer plastics material which is substantially impermeable to oxygen. The outer container 42 may, for example, include an oriented polypropylene (OPP) core coated with an oxygen barrier coating such as polyvinylidene chloride and further laminated with a layer of sealant material such as polyethylene to facilitate heat sealing. 20 In a preferred embodiment, the outer container 42 is composed of a multilayer barrier film commercially available as product no. 325C44-0EX861D from PrintPack, Inc. of Atlanta, Georgia. The co-extruded film has a thickness ranging from about 2 mils to about 6 mils. Prior to sealing the peripheral edges of the outer container 42, the inner container 44 is placed within the outer container 42. Also, the outer container 42 is 25 flushed with an appropriate mixture of gases, typically about 30 percent carbon dioxide and about 70 percent nitrogen, to lower the oxygen level in the outer container 42 to about 0.05 to 5.0 percent or 500 to 50,000 parts per million (PPM). Prior to or simultaneously with flushing the outer container 42, but still prior to sealing the outer container 42, the oxygen scavenging packet 52 is placed in the outer container 42 30 external to the sealed inner container 44. The outer container 42 is then sealed.


might permeate into the outer container 42 from the ambient environment. In FIGS. 1 through 4, the oxygen scavenger 10, 20, 30, and 52 respectively, is illustrated as a packet or label which is inserted into the outer container 42 prior to sealing the outer container 42. Alternatively, an oxygen scavenging material may be added to the polymer or polymers 5 used to form the outer container 42 so that the oxygen scavenging material is integrated into the outer container 42 itself

The retail cut of raw meat 50 within the package 40 takes on a purple-red colour when the oxygen is removed from the interior of the package 40. The meat-filled modified atmosphere package 40 may now be stored in a refrigeration unit for several weeks prior to 10 being offered for sale at a grocery store. A short time (e.g., less than one hour) prior to being displayed at the grocery store, the inner container 44 is removed from the outer container 42 to allow oxygen from the ambient environment to permeate the non-barrier tray 46 and non-barrier cover 48. The purple-red colour of the raw meat 50 quickly changes or "blooms" to a generally acceptable bright red colour when the raw meat 50 is 15 oxygenated by exposure to air.

While the present invention has been described with reference to one or more particular embodiments, those skilled in the art will recognise that many changes may be made thereto without departing from the spirit and scope of the present invention. Each of these embodiments and obvious variations thereof is contemplated as falling within the 20 spirit and scope of the claimed invention, which is set forth in the following claims.

Throughout the specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or 25 steps.

The reference to any prior art in this specification is not, and should not be taken as, an acknowledgment or any form of suggestion that that prior art forms part of the common general knowledge in Australia.



- 15 -

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An oxygen scavenging packet, comprising:
 - 5 a. an oxygen permeable material formed into a closed packet for holding an oxygen absorber;
 - b. an oxygen absorber comprising iron within the packet of (a); and
 - c. a liquid oxygen uptake accelerator, said accelerator comprising water, said accelerator being present in an amount relative to the amount of said oxygen absorber,
- 10 such that when the liquid accelerator and oxygen absorber are brought into contact the oxygen absorber is capable of reducing the oxygen content of a predetermined volume containing about 2 vol. % oxygen to less than 0.5 vol. % oxygen at a temperature of about 34°F in no more than 90 minutes after said accelerator and oxygen absorber are brought into contact.
- 15
2. An oxygen scavenging packet of Claim 1, wherein said oxygen absorber of (b) further comprises silica gel and a carbon dioxide generator.
- 20
3. An oxygen scavenging packet of Claim 1, wherein said iron is electrolytically annealed and reduced.
4. An oxygen scavenging packet of Claim 1, wherein said oxygen uptake accelerator further comprises a salt.
- 25
5. An oxygen scavenging packet of Claim 1, wherein said oxygen uptake accelerator further comprises an acid.
6. An oxygen scavenging packet of Claim 1, wherein said oxygen uptake accelerator is contained within an enclosed space within said packet.

30



- 16 -

7. An oxygen scavenging packet of Claim 1, wherein said oxygen uptake accelerator is contained within a bibulous wick, said wick extending from the exterior of said packet into the interior of said packet.

5 8. A method of reducing the oxygen concentration in an enclosed space comprising:
a. placing an oxygen scavenging packet within said enclosed space, said oxygen scavenging packet comprising:

- i. an oxygen permeable material formed into a closed packet; and
- ii. an oxygen absorber within said closed packet, said oxygen absorber

10 comprising iron;

b. introducing a liquid oxygen uptake accelerator comprising water directly onto said oxygen absorber, wherein said liquid oxygen uptake accelerator is introduced in an amount relative to the amount of said oxygen absorber, such that when the oxygen uptake accelerator and oxygen absorber are brought into contact, the oxygen absorber is
15 capable of reducing the oxygen content of a predetermined volume containing about 2 vol. % oxygen to less than 0.5 vol. % oxygen at a temperature of about 34°F in no more than 90 minutes after said oxygen uptake accelerator and oxygen absorber are brought into contact.

9. A method of Claim 8, wherein said oxygen absorber further comprises silica gel
20 and a carbon dioxide generator.

10. A method of Claim 8, wherein said oxygen uptake accelerator further comprises a salt.

25 11. A method of Claim 8, wherein said iron is electrolytically annealed and reduced.

12. A method of Claim 8, wherein said oxygen uptake accelerator further comprises an acid.

30 13. An oxygen scavenging pocket as substantially hereinbefore described with reference to accompanying drawings.



14. A method of reducing the oxygen concentration in an enclosed space as substantially hereinbefore described.

5

Dated this 7th day of August, 2001

Pactiv Corporation

By their Patent Attorneys

DAVIES COLLISON CAVE

卷之三



1/8




Fig. 1

Fig. 2b






Fig. 2a

2/8



3/8




Fig. 5




Fig. 6

4/8




Fig. 7




Fig. 8

5/8




Fig. 9




Fig. 10




Fig. 11

7/8




Fig. 12

8/8




Fig. 13