



US 20170116158A9

(19) **United States**
(12) **Patent Application Publication**
Chen et al.

(10) **Pub. No.: US 2017/0116158 A9**
(48) **Pub. Date: Apr. 27, 2017**
CORRECTED PUBLICATION

(54) **TECHNIQUES TO PERFORM
INTERPOLATION FOR STATISTICAL TESTS**

(60) Provisional application No. 61/819,791, filed on May 6, 2013.

(71) Applicants: **Xilong Chen**, Chapel Hill, NC (US);
Mark Roland Little, Cary, NC (US)

Publication Classification

(51) **Int. Cl.**
G06F 17/18 (2006.01)

(72) Inventors: **Xilong Chen**, Chapel Hill, NC (US);
Mark Roland Little, Cary, NC (US)

(52) **U.S. Cl.**
CPC **G06F 17/18** (2013.01)

(73) Assignee: **SAS INSTITUTE INC.**, Cary, NC
(US)

(57) **ABSTRACT**

Techniques to perform interpolation for statistical tests are described. An apparatus may comprise processor circuitry and a simulated data component for execution by the processor circuitry to generate simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution. The apparatus may further comprise a statistic simulator component for execution by the processor circuitry to simulate statistics for the parameter vectors from the simulated data, each parameter vector represented with a single point in a grid of points. The apparatus may further comprise a code generator component for execution by the processor circuitry to remove selective points from the grid of points to form a subset of points, and generate interpolation code to interpolate a statistic of the statistical test on any point. Other embodiments are described and claimed.

(21) Appl. No.: **14/270,825**

(22) Filed: **May 6, 2014**

Prior Publication Data


(15) Correction of US 2015/0324327 A1 Nov. 12, 2015
See (63) and (60) Related U.S. Application Data.

(65) US 2015/0324327 A1 Nov. 12, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/270,662, filed on May 6, 2014, now Pat. No. 9,208,131.

Computing System 600



Automated Statistical Test System 100




FIG. 1

200




FIG. 2




FIG. 3




FIG. 4

Operational Environment 500




FIG. 5

Computing System 600




FIG. 6

Distributed Computing System 610




FIG. 7

800

*GENERATE SIMULATED DATA FOR A STATISTICAL TEST, THE
STATISTICAL TEST BASED ON PARAMETER VECTORS TO
FOLLOW A PROBABILITY DISTRIBUTION OF A KNOWN OR AN
UNKNOWN FORM*

802

*SIMULATE STATISTICS FOR THE PARAMETER VECTORS
FROM THE SIMULATED DATA WITH A DISTRIBUTED
COMPUTING SYSTEM COMPRISING MULTIPLE NODES EACH
HAVING ONE OR MORE PROCESSORS CAPABLE OF
EXECUTING MULTIPLE THREADS, THE SIMULATION TO
OCCUR BY DISTRIBUTION OF PORTIONS OF THE
SIMULATED DATA ACROSS THE MULTIPLE NODES OF THE
DISTRIBUTED COMPUTING SYSTEM*

804

*CONTROL TASK EXECUTION ON DISTRIBUTED PORTIONS OF
THE SIMULATED DATA ON EACH NODE OF THE
DISTRIBUTED COMPUTING SYSTEM WITH A VIRTUAL
SOFTWARE CLASS ARRANGED TO COORDINATE TASK AND
SUB-TASK OPERATIONS ACROSS THE NODES OF THE
DISTRIBUTED COMPUTING SYSTEM*

806

FIG. 8

Replacement Sheet (Clean)

900




FIG. 9





FIG. 10

1100

Thread Execution 1170



TKVRT Extension 1180




FIG. 11

1200

*GENERATE SIMULATED DATA FOR A STATISTICAL TEST, THE
STATISTICAL TEST BASED ON PARAMETER VECTORS TO
FOLLOW A PROBABILITY DISTRIBUTION OF A KNOWN OR AN
UNKNOWN FORM*

1202

*SIMULATE STATISTICS FOR THE PARAMETER VECTORS
FROM THE SIMULATED DATA, EACH PARAMETER VECTOR
TO COMPRISE A SINGLE POINT IN A GRID OF POINTS, WITH
A GRID COMPUTING SYSTEM COMPRISING MULTIPLE
NODES EACH HAVING ONE OR MORE PROCESSORS
CAPABLE OF EXECUTING MULTIPLE THREADS, THE
SIMULATION TO OCCUR BY DISTRIBUTION OF PORTIONS OF
THE SIMULATED DATA ACROSS THE MULTIPLE NODES OF
THE GRID COMPUTING SYSTEM IN ACCORDANCE WITH A
COLUMN-WISE OR COLUMN-WISE-BY-GROUP DISTRIBUTION
ALGORITHM*

1204

*CREATE A COMPUTATIONAL REPRESENTATION ARRANGED
TO GENERATE AN APPROXIMATE PROBABILITY FUNCTION
FOR EACH POINT IN THE GRID OF POINTS FROM THE
SIMULATED STATISTICS*

1206

FIG. 12

Simulated Data Structure 1300

Cells 1306-i

Columns 1304-h

Rows 1302-g

Simu ID	p	m1	m2	m3	m4	p	m1	m2	m3	...
...										
1003	4	0.56978	0.71148	0.83731	0.46257	5	0.98292	0.96405	0.06801	
1004	4	0.38887	0.31690	0.96108	0.66402	5	0.97956	0.78485	0.85835	
1005	4	0.96355	0.48102	0.19284	0.40935	5	0.05094	0.23776	0.93339	
1006	4	0.33847	0.79626	0.25415	0.23356	5	0.72523	0.25972	0.64032	
1007	4	0.29916	0.50072	0.30471	0.71059	5	0.13851	0.74346	0.87603	
...										

FIG. 13

Operational Environment 1400




FIG. 14

<i>Simu ID</i>	<i>p</i>	<i>m1</i>	<i>m2</i>	<i>m3</i>	<i>m4</i>	<i>WDmaxF</i>	<i>p</i>	<i>m1</i>	<i>m2</i>	<i>m3</i>	<i>WDmaxF</i>	<i>...</i>
...												
I003	4	0.56978	0.71148	0.83731	0.46257	0.82125	5	0.98292	0.96405	0.06801	0.98292	
I004	4	0.38887	0.31690	0.96108	0.66402	0.95008	5	0.97956	0.78485	0.85835	0.97956	
I005	4	0.96355	0.48102	0.19284	0.40935	0.96355	5	0.05094	0.23776	0.93339	0.92808	
I006	4	0.33847	0.79626	0.25415	0.23356	0.78712	5	0.72523	0.25972	0.64032	0.72523	
I007	4	0.29916	0.50072	0.30471	0.71059	0.70001	5	0.13851	0.74346	0.87603	0.86177	
...	<i>Group 1</i>						<i>Group 2</i>					

FIG. 15

Groups
1508-n

Operational Environment 1600




FIG. 16




FIG. 17

1800




FIG. 18

Operational Environment 1900




FIG. 19

2000

*GENERATE SIMULATED DATA FOR A STATISTICAL TEST,
STATISTICS OF THE STATISTICAL TEST BASED ON
PARAMETER VECTORS TO FOLLOW A PROBABILITY
DISTRIBUTION OF A KNOWN OR AN UNKNOWN FORM*

2002

*SIMULATE STATISTICS FOR THE PARAMETER VECTORS
FROM THE SIMULATED DATA, EACH PARAMETER VECTOR
TO COMPRISE A SINGLE POINT IN A GRID OF POINTS*

2004

*REMOVE SELECTIVE POINTS FROM THE GRID OF POINTS TO
FORM A SUBSET OF POINTS*

2006

*GENERATE INTERPOLATION SOURCE CODE TO
INTERPOLATE A STATISTIC OF THE STATISTICAL TEST ON
ANY POINT*

2008

FIG. 20

Operational Environment 2100




FIG. 21A

2150




FIG. 21B

Operational Environment 2200




FIG. 22

2300

RECEIVE A COMPUTATIONAL REPRESENTATION ARRANGED TO GENERATE AN APPROXIMATE PROBABILITY DISTRIBUTION FOR STATISTICS OF A STATISTICAL TEST, THE COMPUTATIONAL REPRESENTATION TO INCLUDE A SIMULATED DATA STRUCTURE WITH INFORMATION FOR ESTIMATED CUMULATIVE DISTRIBUTION FUNCTION (CDF) CURVES FOR ONE OR MORE PARAMETER VECTORS OF THE STATISTICAL TEST, EACH PARAMETER VECTOR TO COMPRISE A SINGLE POINT IN A GRID OF POINTS

2302

EVALUATE THE SIMULATED DATA STRUCTURE TO DETERMINE WHETHER ANY POINTS IN THE GRID OF POINTS ARE REMOVABLE FROM THE SIMULATED DATA STRUCTURE GIVEN A TARGET LEVEL OF PRECISION

2304

REDUCE THE SIMULATED DATA STRUCTURE IN ACCORDANCE WITH THE EVALUATION TO PRODUCE A REDUCED SIMULATED DATA STRUCTURE HAVING A SMALLER DATA STORAGE SIZE RELATIVE TO THE SIMULATED DATA STRUCTURE, THE REDUCED SIMULATED DATA STRUCTURE TO REDUCE A DATA STORAGE SIZE FOR THE COMPUTATIONAL REPRESENTATION

2306

FIG. 23

2400




FIG. 24

2500




FIG. 25

2600




FIG. 26

2700




FIG. 27

Statistical Test Subsystem 140




FIG. 28A

User Interface View 2850




FIG. 28B

2900




FIG. 29

Centralized System 3000




FIG. 30

Distributed System 3100




FIG. 31




FIG. 32

3300




FIG. 33




FIG. 34

TECHNIQUES TO PERFORM INTERPOLATION FOR STATISTICAL TESTS

RELATED CASES

[0001] This application is a continuation of U.S. patent application Ser. No. 14/270,662 titled “TECHNIQUES TO SIMULATE STATISTICAL TESTS” filed on May 6, 2014, which is hereby incorporated by reference in its entirety.

BACKGROUND

[0002] In some cases, a computer system may be used to perform statistical tests. This decision is normally a function of, in part, a size of a data set needed to perform a given statistical test. Even a moderately complex statistical test may require a massive data set, sometimes on the order of terabytes for example, to produce sufficiently accurate results.

SUMMARY

[0003] The following presents a simplified summary in order to provide a basic understanding of some novel embodiments described herein. This summary is not an extensive overview, and it is not intended to identify key/critical elements or to delineate the scope thereof. One purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

[0004] Various embodiments are generally directed to techniques to perform automated statistical testing. Some embodiments are particularly directed to techniques to determine statistical significance of test results from a statistical test using a distributed processing system. In one embodiment, for example, an apparatus may comprise processor circuitry and a simulated data component for execution by the processor circuitry to generate simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution. The apparatus may further comprise a statistic simulator component for execution by the processor circuitry to simulate statistics for the parameter vectors from the simulated data, each parameter vector represented with a single point in a grid of points. The apparatus may further comprise a code generator component for execution by the processor circuitry to remove selective points from the grid of points to form a subset of points, and generate interpolation code to interpolate a statistic of the statistical test on any point. Other embodiments are described and claimed.

[0005] To the accomplishment of the foregoing and related ends, certain illustrative aspects are described herein in connection with the following description and the annexed drawings. These aspects are indicative of the various ways in which the principles disclosed herein can be practiced and all aspects and equivalents thereof are intended to be within the scope of the claimed subject matter. Other features will become apparent from the following detailed description when considered in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates an example of an automated statistical test system.

[0007] FIG. 2 illustrates an example of a first logic flow for a simulation subsystem.

[0008] FIG. 3 illustrates an example of a first operational environment.

[0009] FIG. 4 illustrates an example of a second operational environment.

[0010] FIG. 5 illustrates an example of a third operational environment.

[0011] FIG. 6 illustrates an example of a computing system.

[0012] FIG. 7 illustrates an example of a distributed computing system.

[0013] FIG. 8 illustrates an example of a second logic flow for a simulation subsystem.

[0014] FIG. 9 illustrates an example of a third logic flow for a simulation subsystem.

[0015] FIG. 10 illustrates an example of a fourth logic flow for a simulation subsystem.

[0016] FIG. 11 illustrates an example of a fifth logic flow for a simulation subsystem.

[0017] FIG. 12 illustrates an example of a sixth logic flow for a simulation subsystem.

[0018] FIG. 13 illustrates an example of a first simulated data structure.

[0019] FIG. 14 illustrates an example of a fourth operational environment.

[0020] FIG. 15 illustrates an example of a second simulated data structure.

[0021] FIG. 16 illustrates an example of a fifth operational environment.

[0022] FIG. 17 illustrates an example of a third simulated data structure.

[0023] FIG. 18 illustrates an example of a seventh logic flow for a simulation subsystem.

[0024] FIG. 19 illustrates an example of a sixth operational environment.

[0025] FIG. 20 illustrates an example of an eighth logic flow for a simulation subsystem.

[0026] FIG. 21A illustrates an example of a seventh operational environment.

[0027] FIG. 21B illustrates an example of a ninth logic flow for a simulation subsystem.

[0028] FIG. 22 illustrates an example of an eighth operational environment.

[0029] FIG. 23 illustrates an example of a tenth logic flow for a simulation subsystem.

[0030] FIG. 24 illustrates an example of an eleventh logic flow for a simulation subsystem.

[0031] FIG. 25 illustrates an example of a twelfth logic flow for a simulation subsystem.

[0032] FIG. 26 illustrates an example of a thirteenth logic flow for a simulation subsystem.

[0033] FIG. 27 illustrates an example of a fourteenth logic flow for a simulation subsystem.

[0034] FIG. 28A illustrates an example of a statistical test subsystem.

[0035] FIG. 28B illustrates an example of a user interface view for a statistical test subsystem.

[0036] FIG. 29 illustrates an example of a logic flow for a statistical test subsystem.

[0037] FIG. 30 illustrates an example of a centralized system.

[0038] FIG. 31 illustrates an example of a distributed system.

[0039] FIG. 32 illustrates an example of a computing architecture.

[0040] FIG. 33 illustrates an example of a communications architecture.

[0041] FIG. 34 illustrates an example of an article of manufacture.

DETAILED DESCRIPTION

[0042] In statistics, a result is considered statistically significant if, for example, it has been predicted as unlikely to have occurred by chance alone, according to a pre-determined threshold probability, referred to as a significance level. A statistical test is used in determining what outcomes of a study would lead to a rejection of a null hypothesis for a pre-specified level of significance. A null hypothesis refers to a default position, such as there is no relationship between two measured phenomena, for example, that a potential medical treatment has no effect. Statistical significance is instructive in determining whether results contain enough information to cast doubt on the null hypothesis.

[0043] Various embodiments described and shown herein are generally directed to techniques to perform enhanced automated statistical testing. Some embodiments are particularly directed to an automated statistical test system arranged to determine statistical significance of test results from a statistical test. In one embodiment, for example, the automated statistical test system may include a simulation subsystem and a statistical test subsystem. The simulation subsystem may, among other features, generate an approximate probability distribution for the statistics of a statistical test. The statistical test subsystem may, among other features, generate statistical significance values for results of a statistical test using an approximate probability distribution. Embodiments are not limited to these subsystems.

[0044] With general reference to notations and nomenclature used herein, the detailed descriptions which follow may be presented in terms of program procedures executed on a computer or network of computers. These procedural descriptions and representations are used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art.

[0045] A procedure is here, and generally, conceived to be a self-consistent sequence of operations leading to a desired result. These operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical, magnetic or optical information capable of being stored, transferred, combined, compared, and otherwise manipulated. It proves convenient at times, principally for reasons of common usage, to refer to this "information" as bits, values, elements, symbols, characters, terms, numbers, or the like. It should be noted, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to those quantities.

[0046] Further, the manipulations performed are often referred to in terms, such as adding or comparing, which are commonly associated with mental operations performed by a human operator. No such capability of a human operator is necessary, or desirable in most cases, in any of the operations described herein which form part of one or more embodiments. Rather, the operations are machine operations. Useful machines for performing operations of various embodiments include general purpose digital computers or similar devices.

[0047] Various embodiments also relate to apparatus or systems for performing these operations. This apparatus may be specially constructed for the required purpose or it may comprise a general purpose computer as selectively activated or reconfigured by a computer program stored in the computer. The procedures presented herein are not inherently related to a particular computer or other apparatus. Various general purpose machines may be used with programs written in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these machines will appear from the description given.

[0048] Reference is now made to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding thereof. It may be evident, however, that the novel embodiments can be practiced without these specific details. In other instances, well known structures and devices are shown in block diagram form in order to facilitate a description thereof. The intention is to cover all modifications, equivalents, and alternatives consistent with the claimed subject matter.

[0049] FIG. 1 illustrates a block diagram for an automated statistical test system 100. In one embodiment, the automated statistical test system 100 may be implemented as a computer system having a simulation subsystem 120 and a statistical test subsystem 140. The subsystems 120, 140 may each be implemented as a separate or integrated software application comprising one or more components, such as components 122-a as shown for the simulation subsystem 120 in FIG. 1. Although the automated statistical test system 100 shown in FIG. 1 has a limited number of elements in a certain topology, it may be appreciated that the automated statistical test system 100 may include more or less elements in alternate topologies as desired for a given implementation.

[0050] It is worthy to note that "a" and "b" and "c" and similar designators as used herein are intended to be variables representing any positive integer. Thus, for example, if an implementation sets a value for a=4, then a complete set of components 122-a may include components 122-1, 122-2, 122-3 and 122-4. The embodiments are not limited in this context.

[0051] In various embodiments, portions of the automated statistical test system 100 may be implemented as software components comprising computer executable instructions implemented in a given programming language. In one embodiment, for example, the computer executable instructions may be implemented in a specific programming language as developed by SAS® Institute, Inc., Cary, N.C. For instance, the computer executable instructions may be implemented in a procedure referred to herein as HPSIMULATE, which is a procedure suitable for execution within a SAS programming language and computing environment. In such embodiments, the computer executable instructions may follow syntax and semantics associated with HPSIMULATE, as described in more detail with reference to FIG. 34, infra. However, embodiments are not limited to HPSIMULATE, and further, do not need to necessarily follow the syntax and semantics associated with HPSIMULATE. Embodiments are not limited to a particular type of programming language.

[0052] As shown in FIG. 1, the automated statistical test system 100 may include two subsystems, a simulation subsystem 120 and a statistical test subsystem 140. The simulation subsystem 120 may generate a computational representation 130 arranged to generate approximate probability distribution 132 for a statistical test 114. The statistical test subsystem 140 may generate statistical significance values for results of the statistical test 114 using an approximate probability distribution 132 generated by the computational representation 130.

[0053] The simulation subsystem 120 may be generally arranged to perform a statistical simulation for a variety of statistical tests 114. The statistical test 114 may include any known statistical test as represented by the statistical test function 112. Some examples for the statistical test 114 may include without limitation median test, mode test, R test, means test, t-test for single means, independent t-test, dependent t-test, Wald-Wolfowitz runs test, Kolmogorov Smirnov test, Mann-Whitney U test, sign test, Wilcoxon matched pairs test, alternative to one-way between-groups analysis of variance (ANOVA) test, one-way ANOVA test, Kruskal-Wallis ANOVA test, repeated measures ANOVA test, Friedman ANOVA test, Kendall Concordance test, Pearson product moment correlation test, Spearman correlation test, linear regression test, data mining decision tree tests, neural network tests, nonlinear estimation test, discriminant analysis test, predictor importance test, KPSS unit root test, Shin cointegration test, ERS unit root test, Bai and Perron's multiple structural change tests (e.g., maxF, UDmaxF, WDmaxF, supF_{t+1/T}, etc.), Im, Pesaran and Shin (2003) panel unit root test, Bhargava, Franzini and Narendranathan (1982) test, generalized Durbin-Watson statistics, generalized Berenblut-Webb statistics for first-order correlation in a fixed effects model, Gourieroux, Holly and Monfort (1982) test for random effects (two way), Johansen's cointegration rank test, and many others. Embodiments are not limited in this context.

[0054] The simulation subsystem 120 may be arranged to generate an approximate probability distribution, probability distribution function, or distribution function (collectively referred to herein as an "approximate probability distribution") for the statistics of a statistical test 114. A probability distribution assigns a probability to each measurable subset of possible outcomes of a random experiment, survey, or procedure of statistical inference. A probability distribution can either be univariate or multivariate. A univariate distribution gives the probabilities of a single random variable taking on various alternative values. A multivariate distribution gives probabilities of a random vector (e.g., a set of two or more random variables) taking on various combinations of values.

[0055] More particularly, a statistical test 114 is normally based on a "test statistic." In statistical hypothesis testing, a hypothesis test is typically specified in terms of a test statistic, which is a function of the sample. A test statistic is considered as a numerical summary of a data-set that reduces the data to one value that can be used to perform a hypothesis test. In general, a test statistic is selected or defined in such a way as to quantify, within observed data, behaviors that would distinguish the null from the alternative hypothesis where such an alternative is prescribed, or that would characterize the null hypothesis if there is no explicitly stated alternative hypothesis.

[0056] An important property of a test statistic is that its sampling distribution under the null hypothesis must be calculable, either exactly or approximately, which allows p-values to be calculated. A test statistic is a function of associated data and a model. Under the assumptions of a null hypothesis and the model the test statistic has an associated "sampling distribution." A sampling distribution refers to a probability distribution for values of the test statistic over hypothetical repeated random samples of the data, for random data samples having the probability distribution assumed for the data by the model and null hypothesis.

[0057] In one embodiment, for example, the simulation subsystem 120 attempts to determine and approximate a sampling distribution of a test statistic under an assumed null hypothesis to generate an approximate probability distribution. The simulation subsystem 120 determines an approximate probability distribution for a given set of statistics of a statistical test 114. It is worthy to note that in some embodiments when an approximate probability distribution is said to be associated with a given statistical test 114, it implies that the approximate probability distribution is associated with a set of statistics for the statistical test 114 rather than the statistical test 114 alone.

[0058] In various embodiments, a probability distribution may have a "known form" and/or an "unknown form." A probability distribution of a "known form" means that the analytical formula of the cumulative distribution function (CDF) of the distribution can be efficiently computed, for example, the CDF is a closed-form expression, or the CDF can be well approximated in a numerical method. A probability distribution of an "unknown form" means that the analytical formula of the CDF of the distribution is unavailable, or cannot be efficiently computed or approximated by any known numerical method. Accordingly, the probability distribution of an "unknown form" is to be evaluated through simulation.

[0059] In various embodiments, the simulation subsystem 120 may be arranged to generate a probability distribution for the statistics of a given statistical test having a known form and/or an unknown form. In one embodiment, for example, a probability distribution for the statistics of a given statistical test 114 is a known form, such as a Gaussian distribution, a log-normal distribution, a discrete uniform distribution, a continuous uniform distribution, and many others. However, the statistics of some statistical tests 114 may follow a probability distribution of unknown form. In such cases, a probability distribution of unknown form may be approximated through empirical measure. An empirical measure is a random measure arising from a particular realization of a (usually finite) sequence of random variables. As such, in another embodiment, the simulation subsystem 120 may generate an approximate probability distribution 132 for the statistics of a given statistical test 114 where a probability distribution for the statistics of the statistical test is an unknown form. This may be particularly useful in those cases where the statistics of a statistical test 114 follow a probability distribution for which no known mathematical formula is available to compute its values and which therefore can only be evaluated through simulation.

[0060] The simulation subsystem 120 may receive as input a simulated data function 110 arranged to generate simulated data for a given statistical test 114. The simulation subsystem 120 may further receive as input a statistical test function 112 arranged to perform the statistical test 114. The

simulation subsystem **120** may execute the simulated data function **110** to generate simulated data for the statistical test **114**, and the statistical test function **112** to simulate statistics from the simulated data, and create a computational representation **130** to generate an approximate probability distribution **132** from the simulated statistics. The computational representation **130** may, for example, be used by another software program at some future time to perform an actual statistical test **114**, such as a statistical test subsystem **140**. The statistical test subsystem **140** may, for example, perform the statistical test **114** on actual data sets (e.g., organization data, business data, enterprise data, etc.), and generate statistical significance values utilizing one or more approximate probability distributions **132** generated by the computational representation **130**.

[0061] Examples for an approximate probability distribution **132** may include without limitation an empirical distribution function or empirical CDF. An empirical CDF is a cumulative distribution function associated with an empirical measure of a sample. The simulation subsystem **120** may generate other approximate probability distributions **132** as well using the techniques described herein. The embodiments are not limited in this context.

[0062] The simulation subsystem **120** may generate an approximate probability distribution **132** for the statistics of a statistical test **114** where an actual probability distribution for the statistics of the statistical test **114** is of a known or unknown form. For example, when a statistical test **114** has a probability distribution of a known form, the approximate probability distribution **132** may be useful to evaluate or refine the known probability function. In another example, when the statistics of a statistical test **114** follow a probability distribution of an unknown form, the approximate probability distribution **132** may be useful to generate statistical significance values for a statistical test **114**. The latter example may be particularly useful in those cases where a statistical test **114** has a level of complexity that makes manual estimation of an approximate probability distribution **132** untenable.

[0063] The simulated subsystem **120** may comprise a simulated data component **122-1**. The simulated data component **122-1** may be generally arranged to generate simulated data for a statistical test **114** utilizing the simulated data function **110**. The simulated data function **110** may be stored as part of a software library. In this way, the simulated data component **122-1** may generate many different types of simulated data for a given statistical test **114**, without having to alter or modify instructions for the simulated data component **122-1**. Alternatively, the simulated data function **110** may be integrated with the simulated data component **122-1**. The simulated data component **122-1** may be described in more detail with reference to FIG. 3, *infra*.

[0064] The simulated subsystem **120** may comprise a statistic simulator component **122-2**. The statistic simulator component **122-2** may be generally arranged to simulate statistics for the statistical test **114** from the simulated data utilizing the statistical test function **112**. As with the simulated data function **110**, the statistical test function **112** may be stored as part of a software library. In this way, the statistic simulator component **122-2** may simulate many different types of statistical tests **114** with a given set of simulated data, without having to alter or modify instructions for the statistic simulator component **122-2**. Alternatively, the statistical test function **112** may be integrated with

the statistical simulator component **122-2**. The statistic simulator component **122-2** may be described in more detail with reference to FIG. 4, *infra*.

[0065] The simulated data function **110** and the statistical test function **112** may be dependent or independent with respect to each other. In one embodiment, the simulated data function **110** and the statistical test function **112** may be complementary, where a simulated data set is specifically tuned for a given statistical test **114**. In one embodiment, the simulated data function **110** and the statistical test function **112** may be independently designed.

[0066] The statistic simulator component **122-2** may include a simulation control engine **124**. In one embodiment, the simulation control engine **124** may be generally arranged to control simulation operations across a distributed computing system. A distributed computing system may comprise, for example, multiple nodes each having one or more processors capable of executing multiple threads, as described in more detail with reference to FIG. 6, *infra*.

[0067] The use of a distributed computing system to generate simulated statistics may be useful for statistical tests **114** that need a larger data set. While simulating a statistic for one specific parameter vector may be relatively easy, simulating statistics for all possible parameter vectors could be computationally intensive. As such, a distributed computing system may reduce simulation time.

[0068] The simulation control engine **124** may distribute portions of simulated data or simulated statistics across multiple nodes of the distributed computing system in accordance with a column-wise or a column-wise-by-group distribution algorithm, for example. The use of a distributed computing system in general, and the column-wise or column-wise-by-group distribution algorithm in particular, substantially reduces an amount of time needed to perform the simulation. In some cases, an amount of time needed to perform a simulation may be reduced by several orders of magnitude (e.g., years to days or hours), particularly with larger data sets (e.g., terabytes) needed for even moderately complex statistical tests. The simulation control engine **124** may be described in more detail with reference to FIG. 5, *infra*.

[0069] The simulation subsystem **120** may comprise a code generator component **122-3**. The code generator component **122-3** may be generally arranged to create a computational representation **130**. The computational representation **130** may be arranged to generate an approximate probability distribution **132** for the statistics of a statistical test **114** on a parameter vector from the simulated statistics. The code generator component **122-3** may be described in more detail with reference to FIG. 19, *infra*.

[0070] The computational representation **130** may be created as any software component suitable for execution by a processor circuit. Examples for the computational representation **130** may include without limitation a function, procedure, method, object, source code, object code, assembly code, binary executable file format, simple executable (COM) file, executable file (EXE), portable executable (PE) file, new executable (NE) file, a dynamic-link library (DLL), linear executable (LX) file, mixed linear executable (LE) file, a collection of LE files (W3) file, a compressed collection of LE files (W4) file, or other suitable software structures. The computational representation **130** may be generated in any computer programming language. Embodiments are not limited in this context.

[0071] The simulated subsystem **120** may comprise an evaluation component **122-4**. The evaluation component **122-4** may be generally arranged to evaluate a computational representation **130** for performance. For instance, the evaluation component **122-4** may receive a computational representation **130** arranged to generate an approximate probability distribution **132** for the statistics of the statistical test **114** on a parameter vector from the simulated statistics. The computational representation **130** may include a simulated data structure with information for one or more estimated CDF curves. The evaluation component **122-4** may perform at least two kinds of evaluations on the computational representation **130**.

[0072] A first type of evaluation is a performance evaluation. The direct evaluation attempts to determine whether the computational representation **130** performs according to a defined set of criteria. If the computational representation **130** does not meet one or more of the defined set of criteria, the evaluation component **122-4** may determine whether points should be added to the simulated data structure to improve performance of the computational representation **130**.

[0073] A second type of evaluation is a reduction evaluation. As with the performance evaluation, the reduction evaluation may attempt to determine whether the computational representation **130** performs according to a defined set of criteria. If the computational representation **130** does not meet one or more of the defined set of criteria, the evaluation component **122-4** may further determine whether points can be removed from the simulated data structure to give a same or similar level of performance. Removing points from the simulated data structure may reduce a data storage size for the simulated data structure, and a data storage size for a corresponding computational representation **130** having the reduced simulated data structure.

[0074] When reduction is possible, the evaluation component **122-4** may attempt to reduce a data storage size for a computational representation **130**. The evaluation component **122-4** may evaluate the simulated data structure to determine whether any points in the grid of points is removable from the simulated data structure given a target level of precision. The evaluation component **122-4** may reduce the simulated data structure in accordance with the evaluation to produce a reduced simulated data structure, the reduced simulated data structure to reduce a data storage size for the computational representation **130**. In some cases, the reduced simulated data structure may be obtained by lowering a level of precision for the reduced simulated data structure relative to the original simulated data structure. The evaluation component **122-4** may be described in more detail with reference to FIG. 22, *infra*.

[0075] Included herein is a set of flow charts representative of exemplary methodologies for performing novel aspects of the disclosed architecture. While, for purposes of simplicity of explanation, the one or more methodologies shown herein, for example, in the form of a flow chart or flow diagram, are shown and described as a series of acts, it is to be understood and appreciated that the methodologies are not limited by the order of acts, as some acts may, in accordance therewith, occur in a different order and/or concurrently with other acts from that shown and described herein. For example, those skilled in the art will understand and appreciate that a methodology could alternatively be represented as a series of interrelated states or events, such

as in a state diagram. Moreover, not all acts illustrated in a methodology may be required for a novel implementation.

[0076] FIG. 2 illustrates one example of a logic flow **200**. The logic flow **200** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the simulation subsystem **120** of the automated statistical test system **100**.

[0077] In the illustrated embodiment shown in FIG. 2, the logic flow **200** may generate simulated data for a statistical test, the statistics of the statistical test based on parameter vectors to follow a probability distribution of a known or unknown form at block **202**. For example, the simulated data component **122-1** may generate simulated data for a statistical test **114**, while the statistics of the statistical test **114** based on parameter vectors follow a probability distribution of a known or unknown form. The simulated data component **122-1** may generate the simulated data with a simulated data function **110**. In one embodiment, for example, the simulated data function **110** may be designed to generate simulated data for a multiple structural change (maxF) test.

[0078] The logic flow **200** may simulate statistics for the parameter vectors from the simulated data, each parameter vector to be represented with a single point in a grid of points at block **204**. For example, the statistic simulator component **122-2** may receive simulated data from the simulated data component **122-1**, and simulate statistics for a statistical test **114** with a statistical test function **112**. In one embodiment, for example, the statistical test function **112** may be designed to implement a multiple structural change (maxF) test.

[0079] The statistic simulator component **122-2** may simulate statistics for one or more parameter vectors of the statistical test, each parameter vector to comprise a single point in a grid of points. The statistic simulator component **122-2** may simulate statistics for all given parameter vectors (p) for a statistical test (T) from the simulated data. The statistics of the statistical test T based on a given parameter vector p follow some probability distribution (D). The simulation subsystem **120** may approximate D with simulation. For any given parameter vector p , the statistic simulator component **122-2** can randomly draw a sample $X=\{X_i\}_{i=1}^N$ from D and construct an approximate probability distribution **132** in the form of an empirical CDF $\hat{T}(p, x)$. The empirical CDF $\hat{T}(p, x)$ may have a level of precision as measured by a Kolmogorov-Smirnov statistic shown in Equation (1) as follows:

$$\sqrt{N} \sup_x |\hat{T}(p, x) - T(p, x)| \sim K \quad \text{Equation (1)}$$

where $T(p, x)$ represents a true unknown CDF, and distribution K is a Kolmogorov distribution and a table of the distribution shows $K(3)$ of almost 1. In accordance with Equation (1), the empirical CDF $\hat{T}(p, x)$ may have a precision of approximately $1/\sqrt{N}$ and in almost all cases below $3/\sqrt{N}$, where N is the sample size, or the number of simulated statistics, for the given parameter vector p . For example, when $N=1,000,000$, the precision is about 0.001.

[0080] As the statistic simulator component **122-2** may utilize various interpolation techniques to generate approximate probability distributions **132** for one or more parameter vectors for a statistical test **114**, each parameter vector may be referred to as a “point” in a grid of points (M) used for interpolation. In this context, for example, the term “point”

is a mathematical point within a defined problem space. In one embodiment, for instance, the problem space may comprise a “parameter space” for a statistical test 114, with the parameter space made up of a given set of parameter vectors for the statistical test 114. In other words, a specific value of a parameter vector is a point in the “parameter space” of a mathematical problem. If elements of one or more parameter vectors (e.g., the parameters of the problem) are plotted on Cartesian coordinates, then the parameter vector may be mapped to a point on a graph in a conventional manner.

[0081] The logic flow 200 generates quantiles for each point in the grid of points at block 208. For example, the statistic simulator component 122-2 may generate quantiles for each point in the grid of points. Quantiles may refer to data values taken at regular intervals from the cumulative distribution function (CDF) of a random variable. The data values may mark boundaries between consecutive data subsets of an ordered set of data.

[0082] The logic flow 200 involves fitting an estimated CDF curve for each point in the grid of points independently from other points in the grid of points using a number of curve parameters to provide a given level of precision at block 210. For example, the statistic simulator component 122-2 may fit an estimated CDF curve for each point in the grid of points independently from other points in the grid of points using a number of curve parameters to provide a given level of precision. Fitting an estimated CDF curve for each point independently can significantly reduce computational resources needed for curve-fitting operations. For instance, in a simple case, the dimension of the point, p , is only 1; that is to say, p is a real number. Rather than fitting estimated CDF curves for all points in the grid of points simultaneously to build an actual three-dimensional surface, $(p, x, \hat{T}(p, x))$, the statistic simulator component 122-2 fits an estimated curve, $(x, \hat{T}(p, x))$, for each point p in sequence or parallel, and then combines the estimated curves to form an approximate three-dimensional surface. Although the approximate three-dimensional surface may have a reduced level of precision relative to the actual three-dimensional surface, curve-fitting operations are greatly accelerated and may consume fewer computational resources. Reducing latency may be of particular importance with larger data sets or multi-dimensional parameter vectors needed for some statistical tests.

[0083] The statistic simulator component 122-2 may fit an estimated CDF curve for each point in the grid of points using various types of curve-fitting techniques. For instance, the statistic simulator component 122-2 may utilize, for example, a Gaussian mixture model (EM algorithm), a Bernstein-Polynomials mixture model (EM algorithm), or a monotone cubic spline technique. In one embodiment, the statistic simulator component 122-2 may perform curve-fitting utilizing a monotonic cubic spline interpolation technique with beta transformation, as described in more detail with reference to FIG. 18, *infra*. Embodiments are not limited to this example.

[0084] The logic flow 200 may generate a computational representation as source code to interpolate an estimated CDF curve for any point of the statistical test at block 212. For example, the code generator component 122-3 may generate a computational representation 130 as source code to interpolate an estimated CDF curve for any given point of the statistical test 114. In one embodiment, the point may be

within the grid of points. In one embodiment, the point may be outside the grid of points. In one embodiment, the point may be entirely disassociated from the grid of points.

[0085] In one embodiment, the computational representation 130 may be generated in computer programming language, such as C or C++ for example. However, embodiments are not limited to these particular computer programming languages.

[0086] The logic flow 200 may reduce a data storage size for the computation representation at block 214. For example, the evaluation component 122-4 may reduce a data storage size for the computational representation 130 through reduction of various components of the computational representation 130, with a corresponding loss in precision. In one embodiment, the data reduction operations may be described in more detail with reference to FIG. 22, *infra*. Embodiments are not limited to this example.

[0087] The logic flow 200 involves controlling task execution of a distributed computing system using a virtual software class at block 216. For example, the simulation control engine 124 of the statistic simulator component 122-2 may control task execution of a distributed computing system using a virtual software class. In addition, a virtual software class may also be used for other operations of the logic flow 200, including without limitation blocks 202, 208, 210, 212 and 214, for example. A virtual software class may be described in more detail with reference to FIG. 5, *infra*.

[0088] FIG. 3 illustrates an example of an operational environment 300. The operational environment 300 may illustrate operation of portions of the automated statistical test system 100, such as the simulated data component 122-1, for example.

[0089] As shown in FIG. 3, the simulated data component 122-1 may have a simulated data generator 320. In addition to, or as an alternative of, receiving a simulated data function 110, the simulated data generator 320 may receive a structured input file 310 and a randomizer function 312. The structured input file 310 may have definitions to generate simulated data 330. The randomizer function 312 may generate seeds or random numbers (e.g., a random number generator) for the simulated data 330. The simulated data generator 320 may utilize the simulated data function 110, the structured input file 310, and/or the randomizer function 312 to generate the simulated data 330. The simulated data generator 320 may store the simulated data 330 in a simulation database 340. In one embodiment, for example, the simulated data 330 may be stored in the simulation database 340 in accordance with definitions provided by the structured input file 310.

[0090] The structured input file 310 may generally comprise one or more input files with data generation specifications and definitions useful for the simulated data component 122-1 to automatically producing simulated data 330. The specifications and definitions may be in addition to, or replacement of, specifications and definitions used by the simulated data function 110. The structured input file 310 may utilize any format as long as the input files are structured in a known and well-defined manner. The structured input file 310 provides information about the simulated data 330 and the simulation database 340, among other types of information. For instance, the structured input file 310 may provide information about a computing environment in which the simulation subsystem 120 will run, a database to store the simulated data 330, data structures for the simu-

lated data **330**, table space (e.g., table, columns, rows, indices, etc.), the type of simulated data **330** required by each column of output tables in the simulation database **340**, how to generate each type of simulated data **330**, relationships between columns in a same table and columns in different tables, and other information pertinent to generating simulated data **330**.

[0091] A particular number of data sets for the simulated data **330** may be dependent, in part, on a particular type of statistical test **114**. In one embodiment, for example, assume the statistical test function **112** is designed to implement a multiple structural change (maxF) test. For example, in order to have a 3-digit precision, the simulated data generator **320** may need to generate a sufficient number of data sets to calculate approximately 1,000,000 statistics for each point in a defined grid of points.

[0092] FIG. 4 illustrates an example of an operational environment **400**. The operational environment **400** may illustrate the operation of portions of the automated statistical test system **100**, such as the statistic simulator component **122-2**, for example.

[0093] As shown in FIG. 4, the statistic simulator component **122-2** may include a simulated statistic generator **420**. The simulated statistic generator **420** may receive simulated data **330** generated by the simulated data component **122-1**, and use (e.g., call) the statistical test function **112** to generate a set of simulated statistics **430** for a statistical test **114** with the simulated data **330**. As with the simulated data **330**, the simulated statistics **430** may be stored in the simulation database **340**, or a separate database entirely.

[0094] The statistic simulator component **122-2** may generate the simulated statistics **430** in different ways using various types of computer systems, including a centralized computing system and a distributed computing system. The statistic simulator component **122-2** may specify and control a particular computer system used for simulation through the simulation control engine **124**.

[0095] The statistic simulator component **122-2** may generate the simulated statistics using an exemplary procedure, as follows:

```

PROC HPSIMULATE
  data=scbpParms /* table containing simulation parameters */
  datadist=(COPYTONODES);
  MODULE name=SCBP
  ext=tkscbp /* TK Extension to plug-in */
  var=(T mmax NQ Q1 Q20 NEPS EPS1 - EPS50) /* variables */
  task=0 /* Task : Simulation */
  taskParmN=(1000000 /*number of replications*/
    6000000 /*random seed */ );
  OUTPUT out=scbpSimulation;
  PERFORMANCE nnodes=200 nthreads=6;
RUN.

```

The statistic simulator component **122-2** is not limited to this example.

[0096] FIG. 5 illustrates an example of an operational environment **500**. The operational environment **500** may illustrate operation of portions of the automated statistical test system **100**, such as the simulation control engine **124** of the statistical test component **122-2**, for example.

[0097] As shown in FIG. 5, the simulation control engine **124** may include a message interface **520**. The message interface **520** may receive the simulated data **330** from the

simulated data generator **122-1**, or retrieve the simulated data **330** from the simulation database **340**, and generate a simulation request **530**. The simulation request **530** may be a request to generate simulated statistics **430** from the simulated data **330** using the statistical test function **112**.

[0098] The simulation request **530** may include various types of information about the statistical test **114**, as well as information about a computing environment suitable for generating the simulated statistics **430**. Examples of computing environment information may include without limitation a name, description, speed requirements, power requirements, operating system requirements, database requirements, computing parameters, communications parameters, security parameters, and so forth. Depending on a particular statistical test **114**, the computing environment information may specify a configuration for a computer system having different combinations of computation resources, such as a number of servers, server types, processor circuits, processor cores, processing threads, memory units, memory types, and so forth. For example, the computer environment information may request a single computer with a single processor and a single thread, a single computer with a single processor and multiple threads, a single computer with multiple processors (or processing cores) each with a single thread, a single computer with multiple processors (or processing cores) each with multiple threads, multiple computers each with a single processor and a single thread, multiple computers each with a single processor and multiple threads, multiple computers with multiple processors each with a single thread, and multiple computers with multiple processors each with multiple threads, or any combination thereof.

[0099] A computing environment for a statistical test simulation may be particularly important when a simulation for a particular statistical test needs a larger set of data, such as in the gigabyte or terabyte range. Enumeration of all possible points could lead to a relatively large grid of points **M**. Continuing with our previous example of a multiple structural change (maxF) test, in order to have 3-digit precision, the simulated data generator **320** may need to generate a sufficient number of data sets to simulate approximately 1,000,000 statistics for each point in a defined grid of points. Assuming a number of variables is limited to less than 20, a possible number of structural changes is limited to less than 19, and a number of observations is 2,000 to approximate an asymptotic case, a defined grid of points for the maxF test would contain approximately 103,780 points (parameter vectors). To simulate 1,000,000 statistics for each of 103,780 points on a single processor, at roughly 0.001 seconds per statistic, would take approximately 1,200 days. Alternatively, executing 1,000,000 statistics for each of 103,780 points on 1200 processors, at roughly 0.001 seconds per statistic, would take approximately 1 day. For a computational task of this size, the message interface **520** may generate a simulation request **530** with computer environment information specifying a need for distributed computations in a distributed computing environment having multiple computers with multiple processors each with multiple threads operating in a parallel processing manner.

[0100] In one embodiment, the simulation control engine **124** may distribute portions of the simulated data **330** across various parts of a distributed computing environment, and control generation of simulated statistics **430** within the distributed computing environment, through use of one or

more software classes **522-v**. In object-oriented programming, a software class may be referred to as an extensible template for creating objects, providing initial values for state (e.g., member variables) and implementations of behavior (e.g., member functions, methods). In many computer programming languages, a class name may be used as a name for a class (e.g., the template itself), the name for the default constructor of the class (e.g., a subroutine that creates objects), and as the type of objects generated by the type. Typically, when an object is created by a constructor of the class, the resulting object may be called an instance of the class, and the member variables specific to the object may be called instance variables, to contrast with the class variables shared across the entire class.

[0101] As shown in FIG. 5, the software classes **522** are specifically designed to perform simulations of a statistical test **114** in a distributed computing environment. The software classes **522** may include at least a base software class **522-1** for a statistical test **114** and a virtual software class **522-2** for managing the simulation of a statistical test. In one embodiment, for example, a base software class **522-1** may be implemented as a TK-extension class. In one embodiment, for example, a virtual software class **522-2** may be implemented as a virtual TK-extension class (TKVRT). Embodiments, however, are not limited to these examples.

[0102] The base software class **522-1** may include an extensible template to create objects, provide initial values for states, and implementations of behavior for use by a software module to perform a statistical test. The virtual software class **522-2** may include an extensible template to create objects, provide initial values for states, and implementations of behavior for use by the separate software module having a base software class **522-1** for the statistical test, the base software class **522-1** to comprise a child of the virtual software class **522-2**. The virtual software class **522-2** may be used to extend the base software class **522-1** when used with a particular computing system, such as a distributed computing system. This allows standard statistical test code using the base software class **522-1** to take advantage of parallel processing algorithms implemented by the distributed computing environment, without having to make modifications to the base software class **522-1**. The software classes **522** may be described in more detail with reference to FIGS. 8-11, *infra*.

[0103] FIG. 6 illustrates a diagram for a computing system **600**. The computing system **600** may be representative of a computing system suitable for implementing the automated statistical test system **100**.

[0104] As shown in FIG. 6, the computing system **600** includes a computing environment **606** designed for processing large amounts of data for many different types of applications, such as for scientific, technical or business applications that require a greater number of computer processing cycles. The computing environment **606** may include different types of computing systems, such as a centralized computing system **608** and a distributed computing system **610**. Client devices **602-e** can interact with the computing environment **606** through a number of ways, such as over a network **604**. The network **604** may comprise a public network (e.g., the Internet), a private network (e.g., an intranet), or some combination thereof.

[0105] One or more data stores **660** are used to store the data to be processed by the computing environment **606** as well as any intermediate or final data generated by the

computing system in non-volatile memory. However in certain embodiments, the configuration of the computing environment **606** allows its operations to be performed such that intermediate and final data results can be stored solely in volatile memory (e.g., RAM), without a requirement that intermediate or final data results be stored to non-volatile types of memory (e.g., disk).

[0106] This can be useful in certain situations, such as when the computing environment **606** receives ad hoc queries from a user and when responses, which are generated by processing large amounts of data, need to be generated on-the-fly (e.g., in real time). In this non-limiting situation, the computing environment **606** is configured to retain the processed information within memory so that responses can be generated for the user at different levels of detail as well as allow a user to interactively query against this information.

[0107] A client device **602** may implement portions of the automated statistical test system **100**, such as the simulation subsystem **120**, for example. When the simulation subsystem **120** executes, and the statistic simulator component **122-2** initiates simulation operations, the simulation control engine **124** of the statistic simulator component **122-2** may generate a simulation request **530** and send the simulation request **530** to the computing environment **606** via the network **604**. The computing environment **606** may receive the simulation request **530**, and when the simulation request **530** indicates a need for centralized computations, the computing environment **606** may forward the simulation request to the centralized computing system **608** for simulation operations. When the simulation request **530** indicates a need for distributed computations (e.g., parallel processing operations), the computing environment **606** may forward the simulation request **530** to the distributed computing system **610** for simulation operations. The computing systems **608**, **610** may be integrated with, or capable of interaction with, a database management system (DBMS) **612** used to control and manage interaction with the data stores **660**. The data stores **660** may include, for example, the simulation database **340**, as well as other data needed for a given simulation.

[0108] FIG. 7 illustrates a diagram of a distributed computing system **610**. The distributed computing system **610** may include one or more client devices, such as client device **602**, and two or more data processing nodes **702**, **704**. The nodes **702**, **704** may have any of the computer system configurations as described with reference to FIG. 5.

[0109] The statistic simulator component **112-2** may simulate statistics with the distributed computing system **610** via the simulation control engine **124**. In one embodiment, the distributed computing system **610** may comprise multiple data processing nodes each having multi-core data processors, with at least one of the data processing nodes designated as a control data processing node ("control node") and multiple data processing nodes designated as worker data processing nodes ("worker node").

[0110] The client device **602** may couple to a central process, or control node **702**, which, in turn, is coupled to one or more worker nodes **704**. In general, each of the nodes of the distributed computing system **610**, including the control node **702**, and worker nodes **704-1**, **704-2**, and **704-f**, may include a distributed computing engine (DCE) **706** that executes on a data processor associated with that node and interfaces with buffer memory **708** also associated with that

node. The DCE 706 may comprise an instance of the distributed computing engine 124 of the statistical test component 122-2 of the simulation subsystem 120. Each of the nodes may also optionally include an interface to the DBMS 612 and the data stores 660, or local implementations of both (not shown).

[0111] In various embodiments, the control node 702 may manage operations in one or more of the worker nodes 704. More particularly, the control node 702 may be arranged to receive and process a simulation request 530 from the client device 602 when distributed computations are to be performed with data stored in one or more of the worker nodes 704.

[0112] In various embodiments, one or more of the components of distributed computing system 610 may be collocated, including the client device 602, control node 702, and one or more worker nodes 704. However, more generally, none of the components of distributed computing system 610 need be collocated. Furthermore, in some embodiments, more than one node of the distributed computing system 610 may be arranged to assume the role of the control node. Thus, in some scenarios, the component designated as the control node 702 may assume the role of a worker node, while one of the worker nodes 704-1 to 704-f may assume the role of the control node 702.

[0113] In various embodiments, in operation a simulation request 530 may be received by the control node 702 to simulate data and/or statistics for a statistical test, as described previously with respect to FIG. 1. For example, the client device 602 may generate a simulation request 530 to perform a statistical test simulation, which is processed by the control node 702 to construct work requests to be performed by one or more worker nodes 704.

[0114] In particular embodiments, a simulation request 530 generated by client device 602 may be received with a name for the distributed computing system 610 to process the simulation request 530. Accordingly, when the distributed computing system 610 is designated, the simulation request 530 is transmitted to control node 702.

[0115] Consistent with the present embodiments, when the control node 702 receives a simulation request 530 sent from the client device 602, the control node 702 may unpack the simulation request 530, parse the simulation request 530, and establish a flow of execution steps to perform an operation such as an simulating statistics using one or more worker nodes 704 of the distributed computing system 610.

[0116] As illustrated in FIG. 7, the distributed computing system 610 may further include a communication protocol such as the message passing interface (MPI) 710. When the control node 702 establishes a flow of execution for a simulation request 530, the control node 702 may distribute the execution steps to worker nodes 704-1 to 704-f via the message passing interface 710. Subsequently, results may be returned from one or more worker nodes 704-1 to 704-f to the control node 702 via the message passing interface 710.

[0117] In various embodiments, each of multiple worker nodes 704-1 to 704-f may contain a respective partition of data to be processed according to the compute request. The control node 702 may establish an execution flow in which messages are sent to multiple different worker nodes 704-1 to 704-f. Each worker node 704-1 to 704-f may subsequently load and execute a specified simulation function for the partition of data contained by that worker node.

[0118] When each of the worker nodes 704-1 to 704-f, that receives a message to execute a simulation function from control node 702, completes execution of its specified simulation function on its partition of data, the worker node 704 may return results to the control node 702 through the message passing interface 710. The results may subsequently be returned from the control node 702 to the client device 602 that generated the simulation request 530.

[0119] Although FIG. 7 illustrates a distributed database network 172 that comprises a control node 702 and multiple worker nodes 704-f, more general embodiments include any network in which an interface is provided so that a client device may initiate the execution of a compute request within a group of foreign machines, utilize resources of the foreign machines, including memory, input/output functionality, loading of images, launching of threads, and/or utilize a distributed database structure to send and receive message instructions and results.

[0120] FIG. 8 illustrates one example of a logic flow 800. The logic flow 800 may be representative of some or all of the operations executed by one or more embodiments described herein, such as the statistical test component 122-2 of the simulation subsystem 120 of the automated statistical test system 100.

[0121] In the illustrated embodiment shown in FIG. 8, the logic flow 800 may generate simulated data for a statistical test, the statistics of the statistical test based on parameter vectors to follow a probability distribution of a known or unknown form at block 802. For example, the simulated data component 122-1 may generate simulated data 330 for a statistical test 114, the statistical test 114 based on parameter vectors (points) to follow a probability distribution.

[0122] The logic flow 800 may simulate statistics for the parameter vectors from the simulated data with a distributed computing system comprising multiple nodes each having one or more processors capable of executing multiple threads, the simulation to occur by distribution of portions of the simulated data across the multiple nodes of the distributed computing system at block 804. For example, the simulated data generator 320 of the statistic simulator component 122-2 may simulate statistics for parameter vectors from the simulated data 330, where each parameter vector to comprise a single point in a grid of points. The simulation may be performed using a distributed computing system 610 comprising multiple nodes 702, 704, each having one or more processors capable of executing multiple threads. The simulation may occur by distribution of portions of the simulated data 330 across the multiple nodes 702, 704 of the distributed computing system 610.

[0123] The logic flow 800 may control task execution on the distributed portions of the simulated data on each node of the distributed computing system with a virtual software class arranged to coordinate task and sub-task operations across the nodes of the distributed computing system at block 806. For example, the simulation control engine 124 of the statistical test component 122-2 may control task execution to simulate statistics 430 from the distributed portions of the simulated data 330 on each node 702, 704 of the distributed computing system 610 with a virtual software class 522-2 arranged to assist in coordinating task and sub-task operations across the nodes 702, 704 of the distributed computing system 610.

[0124] FIG. 9 illustrates one example of a logic flow 900. The logic flow 900 may be representative of some or all of

the operations executed by one or more embodiments described herein, such as the simulation control engine **124** of the statistical test component **122-2** of the simulation subsystem **120** of the automated statistical test system **100**, on the distributed computing system **610**. More particularly, logic flow **900** illustrates the simulation control engine **124** creating an instance of a virtual software class **522-2** on one or more nodes of the distributed computing system **610**.

[**0125**] In some cases, simulation tasks may be implemented by multiple nodes **702**, **704** arranged in soloist architecture or a general/captain architecture. In a soloist architecture, simulations may be performed by a centralized computing system **608**. In a general/captain architecture, simulations may be performed by a distributed computing system **610**, where a control node **702** is designated as a general node, and one or more worker nodes **704** may be designated as captain nodes.

[**0126**] As shown in FIG. **9**, the logic flow **900** may perform initializing and parsing operations at block **902**. A call to an instance of software class `tksimDoAnalysis` may be made to initiate task analysis at block **904**. A subroutine named `DoAnalysis()` to perform the task analysis may be executed at block **906**. Control is passed at point A.

[**0127**] When in a general/captain mode, control is passed at point B to the general node, a subroutine for task initialization may be executed at block **910**. At general start, a subroutine named `ManageInformation(): Message Loop` may be executed at block **912**. A test whether the task is analysis is performed at diamond **914**. If the test is not passed, various clean up procedures are called and general processing terminates. If the test is passed, subroutines `TaskManager()`, `Zathread()`, `Launcher()` and `DoAnalysis()` are executed in a recursive manner at block **916**. Control is passed at point C. Control is returned to the general node at point D.

[**0128**] The `ManageInformation(): Message Loop` executed at block **912** may broadcast instructions to one or more captain nodes. The captain nodes perform operations similar to the general node for portions of the simulation. For instance, at captain start, a subroutine named `ManageInformation(): Message Loop` may be executed at diamond **922**. A test whether the task is analysis is performed at diamond **922**. If the test is not passed, various clean up procedures are called and captain processing terminates. If the test is passed, subroutines `TaskManager()`, `Zathread()`, `Launcher()` and `DoAnalysis()` are executed in a recursive manner at block **924**. Control is passed at point E. Control is returned to the captain node at point F.

[**0129**] FIG. **10** illustrates one example of a logic flow **1000**. The logic flow **1000** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the simulation control engine **124** of the statistical test component **122-2** of the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **1000** interoperates with the logic flow **900** at the various control locations A-F.

[**0130**] As shown in the logic flow **1000**, when control is passed at control location A from the logic flow **900**, a determination is made as to whether task analysis is to be performed in a soloist architecture or a general/captain architecture at diamond **1032**. If a soloist architecture, then subroutines `CreateParentTKVRTInstance()` and `tkvrtGridInitialize()` are executed at block **1036**. A loop starts to execute subroutines `ExecuteTheThreads(str, TASK_`

`ANALYSIS)` and `tkvrtGridSummarize()` at block **1038**. Control is passed at point A. If not a soloist architecture, then a determination is made as to whether task analysis is to be performed in a general/captain architecture at diamond **1034**. If a general/captain architecture, then control is passed at control location B to the logic flow **900**.

[**0131**] When control is passed at control location C from the logic flow **900**, the general node may execute a subroutine `GridTask(str, TASK_ANALYSIS)` at block **1040**, a subroutine `MPI_Bcast(TASK_ANALYSIS)` at block **1042**, and a `CreateParentTKVRTInstance()` and `tkvrtGridInitialize()` at block **1044**. A loop starts to execute subroutines `ExecuteTheThreads(str, TASK_ANALYSIS)` and `tkvrtGridSummarize()` at block **1046**. Once the loop completes, the general node executes a subroutine `MPI_Bcast(TASK_LOCALSTOP,)` at block **1048**. Parameters `TASK_ANALYSIS` and/or `TASK_LOCALSTOP` are passed to the block **1050**, and control is passed at control location D to the logic flow **900**.

[**0132**] Certain subroutines executed by the general node are designed to interoperate with subroutines executed by the captain node to coordinate completion of tasks and sub-tasks. For instance, when the general node executes subroutines `CreateParentTKVRTInstance()` and `tkvrtGridInitialize()` at block **1044**, and the loop at block **1046**, messages and parameters may be exchanged in similar subroutines executed by the captain node at corresponding blocks **1056**, **1058**, respectively, to coordinate task and sub-task completion. Such communication between general node and captain nodes may be necessary for some complex algorithms; however, for algorithms in which the tasks and sub-tasks are independent, no such communication is needed and execution cost is saved.

[**0133**] When control is passed at control location E from the logic flow **900**, the captain node may start a loop to execute subroutines `GridTask(str, TASK_UNKNOWN)` and `MPI_Bcast(task,)` at block **1050**. A determination is made as to whether analysis is complete at diamond **1052** using the `TASK_ANALYSIS` parameter. If the `TASK_ANALYSIS` parameter is evaluated as `TRUE`, the subroutines at blocks **1056**, **1058** are executed, and control is passed back to block **1050**. If the `TASK_ANALYSIS` parameter is evaluated as `FALSE`, a determination is made as to whether a local stop has occurred at diamond **1054** using the `TASK_LOCALSTOP` parameter. If the `TASK_LOCALSTOP` parameter is evaluated as `TRUE`, control is passed at control location F. If the `TASK_LOCALSTOP` parameter is evaluated as `FALSE`, control is passed back to block **1050**.

[**0134**] FIG. **11** illustrates one example of a logic flow **1100**, which shows how to finish the tasks and sub-tasks in parallel in the multithread environment. The logic flow **1100** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the simulation control engine **124** of the statistical test component **122-2** of the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **1100** illustrates certain operations for subroutines executed at blocks **1038**, **1046** and **1058** of the logic flow **1000**.

[**0135**] As shown in the logic flow **1100**, when the subroutine `ExecuteTheThreads()` is executed at blocks **1038**, **1046** and **1058** of the logic flow **1000**, thread execution **1170** executes subroutines `InitializeParentThread()` and `tkvrtInitialize(parentInst)` at block **1172**. The thread execution **1170**

then starts a Loop for all child to execute subroutines threadsInitializeChildThreads(.) and tkvrtInitialize(childInst) at block 1174. The thread execution 1170 then starts an event loop to execute subroutines InitializeChildThreads(.) and tkvrtInitialize(childInst) at block 1176. The thread execution 1170 then executes subroutines AccumulateChildThreads(.) and tkvrtSummarize(parentInst) at block 1178.

[0136] In one embodiment, the simulation control engine 124 may control thread execution 1170 for each node 702, 704 of the distributed computing system 610 with a various instances of a virtual software class 522-2. The virtual software class 522-2 may be arranged to control task operations across the nodes 702, 704 of the distributed computing system 610 while reducing dependency between tasks and sub-tasks. The logic flow 1100 illustrates an example for a virtual software class 522-2 called TKVRT extension 1180.

[0137] In various embodiments, the simulation control engine 124 may pass or receive one or more virtual software class parameters for each instance of a virtual software class, the one or more parameters comprising at least one of input/output parameters, input/output tables, or a pointer to list all instances of virtual software class parameters. For instance, with respect to TKVRT extension 1180, the simulation control engine 124 may pass or receive one or more virtual software class parameters for each instance of TKVRT, including tkvrtParmsPtr, input/output parameters, input/output tables, and a pointer to list all instances of tkvaParmPtrs. The TKVRT extension 1180 may also include several subroutines as used in logic flow 900, 1000.

[0138] In one embodiment, the simulation control engine 124 may initialize a parent thread with parent parameters with a first instance of the virtual software class TKVRT extension 1180, which includes tkvrtInitialize(parentInst) as shown in block 1184.

[0139] In one embodiment, the simulation control engine 124 may initialize a child thread with child parameters with a first instance of the virtual software class TKVRT extension 1180, which includes tkvrtInitialize(childInst) as also shown in block 1184.

[0140] In one embodiment, the simulation control engine 124 may analyze work results of a child thread with a second instance of the virtual software class TKVRT extension 1180, which includes tkvrtAnalyze(childInst) as shown in block 1186.

[0141] In one embodiment, the simulation control engine 124 may summarize work results of a child thread to a parent thread with a third instance of the virtual software class TKVRT extension 1180, which includes tkvrtSummarize(parentInst) as shown in block 1188.

[0142] In one embodiment, the simulation control engine 124 may initialize a grid with parent parameters with a fourth instance of the virtual software class TKVRT extension 1180, which includes tkvrtGridInitialize(parentInst) as shown in block 1190.

[0143] In one embodiment, the simulation control engine 124 may summarize a grid with parent parameters with a fifth instance of the virtual software class TKVRT extension 1180, which includes tkvrtGridSummarize(parentInst) as shown in block 1192.

[0144] It may be appreciated that these are merely a few example subroutines for the TKVRT extension 1180, and others exist as well. Embodiments are not limited in this context.

[0145] FIG. 12 illustrates one example of a logic flow 1200. The logic flow 1200 may be representative of some or all of the operations executed by one or more embodiments described herein, such as the simulation control engine 124 of the statistical test component 122-2 of the simulation subsystem 120 of the automated statistical test system 100. More particularly, the logic flow 1200 illustrates distribution algorithms for use with the distributed computing system 610.

[0146] As shown in FIG. 12, the logic flow 1200 may generate simulated data for a statistical test, the statistics of the statistical test based on parameter vectors to follow a probability distribution at block 1202. For example, the simulated data component 122-1 may generate simulated data 330 for a statistical test 114, the statistics of the statistical test 114 based on parameter vectors to follow a probability distribution of a known or unknown form.

[0147] The logic flow 1200 may simulate statistics for the parameter vectors from the simulated data, each parameter vector to comprise a single point in a grid of points, with a distributed computing system comprising multiple nodes each having one or more processors capable of executing multiple threads, the simulation to occur through distribution of portions of the simulated data or simulated statistics across the multiple nodes of the distributed computing system in accordance with a column-wise or column-wise-by-group distribution algorithm at block 1204. For example, the simulated statistic generator 420 of the statistic simulator component 122-2 may simulate statistics for the parameter vectors from the simulated data 330. Each parameter vector for the statistical test 114 may comprise a single point in a grid of points, with the grid of points to be used for interpolation. The simulation may be performed with a distributed computing system 610 comprising multiple nodes 702, 704. Each node 702, 704 may have one or more processors capable of executing multiple threads. The simulation control engine 124 of the statistic simulator component 122-2 may control simulation of the statistical test 114 by distributing portions of the simulated data 330 and/or simulated statistics 430 across the multiple nodes 702, 704 of the distributed computing system 610 in accordance with a column-wise or column-wise-by-group distribution algorithm. A column-wise or column-wise-by-group distribution algorithm may be described in more detail with reference to FIGS. 13-17, *infra*.

[0148] The logic flow 1200 may create a computational representation arranged to generate an approximate probability distribution for each point in the grid of points from the simulated statistics, the approximate probability distribution to comprise an empirical cumulative distribution function (CDF) at block 1206. For example, the code generator component 124 may create a computational representation 130, such as a DLL file. The computational representation 130 may be arranged to generate an approximate probability distribution 132 for each point in the grid of points from the simulated statistics 430. The approximate probability distribution 132 may comprise an empirical CDF, for example.

[0149] FIG. 13 illustrates an example of a simulated data structure 1300. The simulated data structure 1300 may be a software data structure arranged to store simulated data 330 and/or simulated statistics 430 in the simulation database 340.

[0150] The statistic simulator component 122-2 may generate the simulated data structure 1300. In one embodiment, the statistic simulator component 122-2 may generate the simulated data structure 1300 as a table. The simulated data structure 1300 may include an ordered arrangement of rows 1302-g and columns 1304-h to form multiple cells 1306-i. A cell 1306 may contain a simulation of a simulated statistic 430 (or simulated data 330) for a point in the grid of points, where each row 1302 represents a simulation of the simulated statistic 430 (or simulated data 330), and each column 1304 represents a point in the grid of points.

[0151] When populated, the simulated data structure 1300 may have a defined data storage size for a given statistical test 114. For instance, with the maxF test, the simulated data structure 1300 may comprise 1,000,000 rows and 103,780 columns, which gives the simulated data structure 1300 a data storage size of approximately 800 Gigabytes (GB).

[0152] FIG. 14 illustrates an example of an operational environment 1400. The operational environment 1400 shows distributing portions of the simulated data structure 1300 as column-based work units for the distributed computing system 610.

[0153] The simulation control engine 124 of the statistic simulator component 122-2 may control simulation of the statistical test 114 by distributing portions of the simulated data structure 1300 across the multiple nodes 702, 704 of the distributed computing system 610 in accordance with a column-wise distribution algorithm. For instance, the simulation control engine 124 may distribute the simulated data structure 1300 by column across multiple worker nodes 704 of the distributed computing system 610.

[0154] The DCE 706 of the control node 702 may distribute one or more columns 1304-h of the simulated data structure 1300 to one or more worker nodes 704 via the message passing interface 710. As shown in FIG. 14, the DCE 706 may distribute columns 1304-1, 1304-2 . . . 1304-h of the simulated data structure 1300 as work units to the worker nodes 704-1, 704-2 . . . 704-f, respectively. A worker node 704 may process its assigned work unit, such as sorting each column 1304 and/or calculating quantiles for the statistical test 114. The worker nodes 704 may pass their processed work units, or pointers to the processed work units, to the DCE 706 via the message passing interface 710. The DCE 706 may reassemble the processed work units into an output file to form a new version of the simulated data structure 1300.

[0155] In one embodiment, the new version of the simulated data structure 1300 may include an ordered arrangement of rows and columns, each row to represent a point in the grid of points and each column to represent a quantile for each point in the grid of points. In the case where the worker nodes 704 are tasked to calculate quantiles for the statistical test 114, the worker nodes 704 may pass back a defined number of quantiles as established for the statistical test 114. For instance, with the maxF test, the original simulated data structure 1300 may comprise 1,000,000 rows and 103,780 columns, which gives the original simulated data structure 1300 a data storage size of approximately 800 Gigabytes (GB). Assume the worker nodes 704 are to calculate 10,001 quantiles for the maxF test. In this case, the new simulated data structure 1300 may comprise 10,001 columns and 103,780 rows, which gives the new simulated data structure 1300 a reduced data storage size of approximately 8 GB.

[0156] In one embodiment, the statistic simulator component 122-2 may generate quantiles using the distributed computing system 610 in accordance with an exemplary procedure, as follows:

```
PROC HPSIMULATE
  data=scbpSimulation /* output of simulation with group head */
  datadist=(COLUMNWISEBY);
  MODULE name=SCBP
  ext=tkscbp /* TK Extension to plug-in */
  var=(c:) /* all columns */
  task=1 /* Task : Post-processing */;
  OUTPUT out=scbpQuantiles;
  PERFORMANCE nnodes=200 nthreads=6;
RUN.
```

Embodiments are not limited this example.

[0157] FIG. 15 illustrates an example of a simulated data structure 1500. The simulated data structure 1500 may be a software data structure arranged to store simulated data 330 and/or simulated statistics 430 in the simulation database 340.

[0158] The statistic simulator component 122-2 may generate the simulated data structure 1500. In one embodiment, the statistic simulator component 122-2 may generate the simulated data structure 1500 as a table. The simulated data structure 1500 may include an ordered arrangement of rows 1502-j and columns 1504-k to form multiple cells 1506-m. A cell 1506 may contain a simulation of a simulated statistic 430 (or simulated data 330) for a point in the grid of points, where each row 1502 represents a simulation of the simulated statistic 430 (or simulated data 330), and each column 1504 represents a point in the grid of points. Additionally, the simulated data structure 1500 may be organized into column groups 1508-n. For instance, a first column group 1508-1 may include six columns for parameter vector 4, and a second column group 1508-2 may include five columns for parameter vector 5, and so forth.

[0159] As with simulated data structure 1300, the simulated data structure 1500 may have a defined data storage size for a given statistical test 114. For instance, with the maxF test, the simulated data structure 1500 may comprise 1,000,000 rows and 103,780 columns, which gives the simulated data structure 1500 a data storage size of approximately 800 Gigabytes (GB).

[0160] FIG. 16 illustrates an example of an operational environment 1600. The operational environment 1600 shows distributing portions of the simulated data structure 1500 as column-group-based work units for the distributed computing system 610.

[0161] The simulation control engine 124 of the statistic simulator component 122-2 may control simulation of the statistical test 114 by distributing portions of the simulated data structure 1500 across the multiple nodes 702, 704 of the distributed computing system 610 in accordance with a column-wise-by-group distribution algorithm. For instance, the simulation control engine 124 may distribute the simulated data structure 1500 by groups of columns (or column groups) across multiple worker nodes 704 of the distributed computing system 610. Distributing the simulated data structure 1500 may make it easier to calculate the simulated statistic 430 for each point in the grid of points relative to the column-wise distribution algorithm.

[0162] The simulation control engine 124 may perform column group distribution according to column groups

1508-n defined in a control row of the simulated data structure **1500**. The control row may include various identifiers or parameters to control distribution. In one embodiment, for example, the control row may include a group identifier to identify corresponding columns in a group, a restriction identifier to identify corresponding columns that do not need to be distributed, and a universal identifier to identify corresponding columns that need to be distributed across all worker nodes. It may be appreciated that other identifiers and parameters may be used as desired for a given implementation. Embodiments are not limited in this context.

[0163] The DCE **706** of the control node **702** may distribute one or more column groups **1508-n** of the simulated data structure **1500** to one or more worker nodes **704** via the message passing interface **710**. As shown in FIG. 16, the DCE **706** may distribute columns **1508-1**, **1508-2** . . . **1508-n** of the simulated data structure **1500** as work units to the worker nodes **704-1**, **704-2** . . . **704-f**, respectively. A worker node **704** may process its assigned work unit, such as calculating the statistics for the statistical test **114**, based on the column groups, and then calculating quantiles for the statistical test **114**. The worker nodes **704** may pass their processed work units, or pointers to the processed work units, to the DCE **706** via the message passing interface **710**. The DCE **706** may reassemble the processed work units into an output file to form a new version of the simulated data structure **1500**.

[0164] In one embodiment, the new version of the simulated data structure **1500** may include an ordered arrangement of rows and columns, each row to represent a point in the grid of points and each column to represent a quantile for each point in the grid of points. In the case where the worker nodes **704** calculate quantiles for the statistical test **114**, as with the simulated data structure **1300**, the worker nodes **704** may pass back a defined number of quantiles as established for the statistical test **114**. For instance, with the WDmaxF test, the original simulated data structure **1500** may comprise 1,000,000 rows and 103,780 columns of maxF test statistics, which gives the original simulated data structure **1500** a data storage size of approximately 800 Gigabytes (GB). Assume the worker nodes **704** are to calculate 10,001 quantiles for the WDmaxF test. In this case, the new simulated data structure **1500** may comprise 10,001 columns and 103,780 rows, which gives the new simulated data structure **1500** a reduced data storage size of approximately 8 GB.

[0165] FIG. 17 illustrates an example of a simulated data structure **1700**. The simulated data structure **1700** may illustrate an example of the new versions of the simulated data structures **1300**, **1500**. As described with reference to FIGS. 13-16, new versions of the simulated data structures **1300**, **1500** may each include an ordered arrangement of rows **1702-p** and columns **1704-q**, each row **1702** to represent a point in the grid of points and each column **1704** to represent a quantile of the grid of points. Simulated data structure **1700** is transposed relative to the simulated data structures **1300**, **1500**, in that the simulated data structures **1300**, **1500** have columns representing points in a grid of points, while the simulated data structure **1700** has columns representing quantiles.

[0166] FIG. 18 illustrates one example of a logic flow **1800**. The logic flow **1800** may be representative of some or all of the operations executed by one or more embodiments

described herein, such as the statistic simulator component **122-2** of the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **1800** illustrates curve fitting algorithms for use with a grid of points.

[0167] As shown in FIG. 18, the logic flow **1800** may generate simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution at block **1802**. For example, the simulated data component **122-1** may generate simulated data **330** for a statistical test **114**, the statistical test **114** based on parameter vectors to follow a probability distribution of known or unknown form. Alternatively, the simulated data component **122-1** may receive simulated data **330** for a statistical test **114** from an external source.

[0168] The logic flow **1800** may simulate statistics for the parameter vectors from the simulated data, each parameter vector to comprise a single point in a grid of points at block **1804**. For instance, the statistic simulator component **122-2** may generate simulated statistics **430** for the parameter vectors from the simulated data **330**, each parameter vector to comprise a single point in a grid of points.

[0169] The logic flow **1800** may calculate quantiles for the parameter vectors from the simulated data at block **1806**. For instance, the statistic simulator component **122-2** may calculate quantiles saved in the simulated data structure **1700** for the parameter vectors from the simulated data **330**.

[0170] The logic flow **1800** may fit an estimated CDF curve to quantiles for each point in the grid of points using a monotonic cubic spline interpolation technique in combination with a transform to satisfy a defined level of precision at block **1808**. For instance, the statistic simulator component **122-2** may construct an estimated CDF curve for each point in the grid of points using a monotonic cubic spline interpolation technique in combination with a transform to interpolate quantiles in the simulated data structure **1700** in order to satisfy a precision level of interest.

[0171] Once the simulation control engine **124** generates the simulated data structure **1700** with quantiles for the statistical test **114**, the statistic simulator component **122-2** may use the quantiles to fit an estimated CDF curve for each point in the grid of points. The statistic simulator component **122-2** may fit an estimated CDF for each point according to a given level of precision. In general, reducing a level of precision results in a corresponding reduction in a number of curve parameters needed to fit the estimated CDF curve.

[0172] As previously described with reference to FIG. 2, the statistic simulator component **122-2** may simulate statistics for all given parameter vectors (p) for a statistical test (T) from the simulated data **330**. In accordance with Equation (1), the empirical CDF $\hat{T}(p, x)$ may have a precision of approximately $1/\sqrt{N}$, where N is the sample size, or the number of simulated statistics, for the given parameter vector p . For example, when $N=1,000,000$, the precision is about 0.001. However, the statistic simulator component **122-2** may generate an estimated CDF curve with much fewer curve parameters than N .

[0173] The statistic simulator component **122-2** may select a number of curve parameters to fit an estimated CDF curve for each point in the grid of points to provide a given level of precision. For instance, assume that a precision level is set as 0.0005, and that a monotonic cubic spline interpolation technique is used to fit the curve. On average, approxi-

mately 20 curve parameters can achieve a curve $C(c(p), x)$ as set forth in Equation (2), as follows:

$$\max_x |C(c(p), x) - \tilde{T}(p, x)| \leq 0.0005 \quad \text{Equation (2)}$$

where $c(p)$ denotes the point-dependent curve parameters.

[0174] In some cases, however, a number of curve parameters may be reduced through combination of a monotonic cubic spline interpolation technique and a transform. In one embodiment, for example, the statistic simulator component 122-2 may combine a monotonic cubic spline interpolation technique with a beta transformation. A beta transformation is a transform performed in accordance with a normalized incomplete beta function, the normalized incomplete beta function comprising a nonnegative function whose derivative is completely positive. In one embodiment, a beta function may comprise a CDF of a beta distribution. A beta distribution is a family of continuous probability distributions defined on the interval [0, 1] parameterized by two positive shape parameters, denoted by α and β , that appear as exponents of the random variable and control the shape of the distribution.

[0175] Assume the monotonic cubic spline interpolation technique fits a first estimated CDF curve with a first number of knots to give a first level of precision (0.0005), each knot comprising an x value and a y value for a two-dimensional coordinate system. The monotonic cubic spline interpolation technique spaces the x values at regular intervals along the x -axis as it is monotonic. As such, more knots are needed to accurately fit the curve. The monotonic cubic spline interpolation technique may be combined with a beta transformation to transform the x values to reduce the first number of knots to a second number of knots that gives approximately the first level of precision (0.0005), where the second number of knots is lower than the first number of knots. Applying the beta transformation causes the x values to be placed at irregular intervals, which reduces the number of knots.

[0176] Combining a monotonic cubic spline interpolation technique with a transform, such as the beta transformation, results in fewer curve parameters needed for a same or similar level of precision. For instance, in the previous example, the use of the monotonic cubic spline interpolation technique reduced a number of curve parameters from 1,000,000 simulated statistics to approximately 20 curve parameters. By combining the monotonic cubic spline interpolation technique with a beta transformation, the number of curve parameters may be further reduced from 20 curve parameters to 12 curve parameters, for a same or similar level of precision (e.g., 0.0005).

[0177] Once a number of curve parameters are selected, the statistic simulator component 122-2 may fit an estimated CDF curve for each point in the grid of points independently from other points in the grid of points using the selected number of curve parameters to provide a given level of precision. Fitting an estimated CDF curve for each point independently significantly reduces computational resources needed for curve-fitting operations. For instance, in a simple case that the point is one dimensional, rather than fitting estimated CDF curves for all points in the grid of points simultaneously to build an actual three-dimensional surface, the statistic simulator component 122-2 fits an estimated

curve for each point in sequence or parallel, and then combines the estimated curves to form an approximate three-dimensional surface.

[0178] Once curve-fitting operations are finished, the statistic simulator component 122-2 may generate a simulated data structure with information for a set of fitted CDF curves for the grid of points. Continuing with the maxF test example, the simulated data structure may have a data storage size calculated as 8 GB/10,001*12=10 megabytes (MB). As indicated with the maxF test example, a data storage size for each version of a simulated data structure reduces from 800 GB to 8 GB to 10 MB. This results in a significantly smaller data storage size needed for the computational representation 130.

[0179] In one embodiment, the statistic simulator component 122-2 may perform curve-fitting operations in accordance with the following exemplary procedure:

```

PROC HPSIMULATE
    data=scbpQuantiles /* output of quantiles */
    datadist=(ROUNDROBIN);
    MODULE name=fittedf
    ext=tkdens /* TK Extension to plug-in */
    var=(key1 - key3 q0 - q10000) /* keys and quantiles */
    task=0 /* Task : Fit CDF curves */
    taskParmN=( /*nKeys=*/3 /*maxParm=*/32 /*maxIter=*/10000
    /*precision=*/0.0005 /*maxModels=*/1 /*weightTails=*/0
    /*weightA=*/-4.605 /*weightB=*/5.685 /*transType=*/1
    /*transGridL=*/-2.0 /*transGridU=*/2.0 /*transGridS=*/0.1 );
    OUTPUT out=scbpFitCDFCurves;
    PERFORMANCE mnodes=200 nthreads=6;
RUN.

```

Embodiments are not limited to this example.

[0180] FIG. 19 illustrates an operational environment 1900. The operational environment 1900 shows operations for the code generator component 122-3 to generate interpolation code to interpolate statistics for a statistical test 114.

[0181] The simulated data component 122-1 may generate simulated data 330 for a statistical test 114, the statistics of the statistical test 114 based on parameter vectors to follow a probability distribution of a known or unknown form. The statistic simulator component 122-2 may generate simulated statistics 430 for the parameter vectors from the simulated data 330, each parameter vector to comprise a single point in a grid of points. The code generator component 122-3 may remove selective points from the grid of points to form a subset of points, and generate interpolation code to interpolate a statistic of the statistical test 114 on any point.

[0182] As shown in FIG. 19, the code generator component 122-3 may receive a simulated data structure 1910. The simulated data structure 1910 may include information for a set of fitted CDF curves for the grid of points, as described with reference to FIG. 18. The code generator component 122-3 may include an interpolation code generator 1920 to execute an interpolation function 1922.

[0183] In various embodiments, the interpolation code generator 1920 may generate interpolation source code 1930 from the simulated data structure 1910 and a pair of interpolation functions 1922, 1924.

[0184] The first interpolation function 1922 may be arranged to call a second interpolation function comprising an instance of the virtual software class. The interpolation function 1922 may be an instance of a base software class 522-1 designed to call an instance of a virtual software class 522-2, where the base software class 522-1 is a child of the

virtual software class **522-2**. In one embodiment, for example, a base software class **522-1** may be implemented as a TK-extension class for interpolating statistics of the statistical test **114**, and a virtual software class **522-2** may be implemented as a virtual TK-extension class (TKICDF). Embodiments, however, are not limited to this example.

[0185] The second interpolation **1924** may be an instance of the virtual software class **522-2**. In one embodiment, the interpolation function **1924** may implement a monotonic cubic spline interpolation technique. In one embodiment, the interpolation function **1924** may implement a monotonic cubic spline interpolation technique in combination with a transform, such as the beta transformation, for example. The beta transformation may comprise a transform with a normalized incomplete beta function (the cumulative distribution function of beta distribution), the normalized incomplete beta function to comprise a nonnegative function whose derivative is completely positive.

[0186] Alternatively, the interpolation code generator **1920** may utilize a single interpolation function with some or all of the characteristics of both interpolation functions **1922**, **1924**. Embodiments are not limited in this context.

[0187] In some cases, the interpolation code generator **1920** may have an integrated compiler **1932**. The interpolation code generator **1920** may generate the interpolation source code **1930**, and use the compiler **1932** to compile the interpolation source code **1930** in order to generate an interpolation executable code **1940**. Alternatively, the compiler **1932** may be separate from the code generator component **122-3** (e.g., part of an operating system).

[0188] In one embodiment, the interpolation code generator **1920** may generate the interpolation source code **1930** in accordance with the following exemplary procedure:

```

PROC HPSIMULATE
    data=schpFitCDFCurves /* output of fitted CDF curves */
    datadist=(ROUNDROBIN);
    MODULE name=getCCode
    ext=tkdens /* TK Extension to plug-in */
    var=(key1 - key3 fit) /* keys and fitting parameters */
    task=1 /* Task : Generate source code */
    taskParmN=( /*nKeys=*/3 /*bitflags=*/0 0 0 )
    taskParmS=( /*OutputPath=*/"u:\temp",
                /*TK-ExtensionFileName=*/"imaxf");
    OUTPUT out=schpIndexTableMaxF;
    PERFORMANCE nnodes=0 nthreads=1;
RUN.

```

Embodiments are not limited to this example.

[0189] FIG. 20 illustrates one example of a logic flow **2000**. The logic flow **2000** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the code generator component **122-3** of the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **2000** illustrates code generation operations for use with a grid of points.

[0190] As shown in FIG. 20, the logic flow **2000** may generate simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution, at block **2002**. For instance, the simulated data component **122-1** may generate simulated data **330** for a statistical test **114**, the statistical test **114** based on parameter vectors to follow a probability distribution of a known or unknown form.

[0191] The logic flow **2000** may simulate statistics for the parameter vectors from the simulated data, each parameter vector to comprise a single point in a grid of points, at block

2004. For instance, the statistic simulator component **122-2** may generate simulated statistics **430** for the parameter vectors from the simulated data **330**, each parameter vector to comprise a single point in a grid of points.

[0192] The logic flow **2000** may remove selective points from the grid of points to form a subset of points at block **2006**. For instance, the code generator component **122-3** may remove selective points from the grid of points to form a subset of points. The code generator component **122-3** may receive a simulated data structure **1910** with information for estimated CDF curves of the subset of points.

[0193] The logic flow **2000** may generate interpolation code to interpolate a statistic of the statistical test on any point at block **2008**. For instance, the code generator component **122-3** may generate interpolation source code **1930** or interpolation executable code **1940** to interpolate a statistic of the statistical test **114** on any point in the grid of points to form an estimated CDF curve. The interpolation code may include, among other types of information, the simulated data structure **1910**, index tables for the simulated data structure **1910**, and a first interpolation function **1922** designed to call a second interpolation function **1924**.

[0194] The interpolation source code **1930** may be used to interpolate a CDF for any given point *p* for a statistical test **114**. Assume the simulation subsystem **120** is executed to simulate and fit CDFs on *M* points. Those *M* points construct a grid (or mesh), which is contained in the interpolation source code **1930** as generated by the code generator component **122-3** of the simulation subsystem **120**. The compiler **1932** may compile the interpolation source code **1930** into interpolation executable code **1940**, such as a DLL, for example. The DLL may be used to interpolate a CDF for any given point *p* of the statistical test, regardless of whether *p* is a point within the grid of points *M* or outside of the grid of points *M*.

[0195] FIG. 21A illustrates an operational environment **2100**. The operational environment **2100** shows operations for the code generator component **122-3** to generate a computational representation **130** for a statistical test **114**.

[0196] As shown in FIG. 21A, the code generator component **122-3** may include a CDF code generator **2120**. The CDF code generator **2120** may receive a simulated data structure **1910** and interpolation source code **1930** from the interpolation code generator **1920**. The simulated data structure **1910** and the interpolation source code **1930** may be integrated or separate from each other. The simulated data structure **1910** may include information for a set of fitted CDF curves for the grid of points, as described with reference to FIG. 18. The interpolation source code **1930** may interpolate a statistic of the statistical test **114** on any point.

[0197] The CDF code generator **2120** may create a computational representation **130** arranged to generate an approximate probability distribution **132** for each point in the grid of points from the simulated data structure **1910**. For instance, the CDF code generator **2120** may generate CDF source code **2130** and/or CDF executable code **2140** via the compiler **2132**. The compiler **2132** may be integrated with, or separate from, the CDF code generator **2120**. The computational representation **130** may include the interpolation source code **1930**. The computational representation **130** may also include a set of H files, data C files, function C files, and a build script.

[0198] FIG. 21B illustrates one example of a logic flow **2150**. The logic flow **2150** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the CDF code generator **2120** of the code generator component **122-3** of the simulation

subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **2150** illustrates code generation operations to generate a computational representation **130**.

[0199] As shown in FIG. **21B**, the logic flow **2150** may receive a simulated data structure **1910** with information for a set of fitted CDF curves for the grid of points as input **2160**. A process **2170** may generate source code for a computational representation **130**, as implemented in generating source code **2172** by incorporating template files, data, and instructions into the corresponding type of files. For instance, the CDF code generator **2120** may generate CDF source code **2130** with the simulated data structure **1910** and interpolation source code **1930**. The logic flow **2150** may output various types of source code files and logic as output **2180**. For instance, the CDF code generator **2120** may generate source code files for CDF source code **2130**.

[0200] The CDF source code **2130** may include, for example, one or more H files **2182**. An H file **2182** may contain data structures and interface functions for the usage of a set of data and the interpolation based on the set of data. The CDF source code **2130** may include, for example, one or more data C files **2184**. A data C file **2184** may contain all fitted CDF curves saved in a data structure and functions of using such data structure. The CDF source code **2130** may include, for example, one or more function C files **2186**. A function C file contains a function for the interpolation based on a given set of data, such as data in the simulated data structure **1910**, for example, the set of fitted CDF curves.

[0201] The CDF source code **2130** may also include logic implemented in the form of one or more scripts **2188**. For instance, the CDF source code **2130** may include a build script or make file that specifies how to build a software library.

[0202] FIG. **22** illustrates an operational environment **2200**. The operational environment **2200** shows operations for the evaluation component **122-4** to reduce a data storage size for a computational representation **130**.

[0203] As shown in FIG. **22**, the evaluation component **122-4** may comprise a data reduction generator **2220**. The data reduction generator **2220** may receive as input a computational representation **130** arranged to generate an approximate probability distribution **132** for each point in a grid of points from simulated statistics **430** for a statistical test **114**. The computational representation **130** may include a simulated data structure **1910** with information for estimated CDF curves.

[0204] The data reduction generator **2220** may evaluate the simulated data structure **1910** to determine whether any points in the grid of points is removable from the simulated data structure **1910** given a target level of precision. The data reduction generator **2220** may reduce the simulated data structure in accordance with the evaluation to produce a reduced simulated data structure **2210**. The reduced simulated data structure may reduce a data storage size for the computational representation **130**.

[0205] The data reduction generator **2220** may implement a parallel adaptive grid enhancement (PAGE) function **2222** arranged to implement a PAGE algorithm. In one embodiment, the data reduction generator **2220** may receive selection of a precision parameter to represent a target level of precision for the simulated data structure **1910**. The data reduction generator **2220** may remove points from the simulated data structure **1910** in accordance with the selected level of precision utilizing the PAGE algorithm. The PAGE algorithm may be described in more detail with reference to FIGS. **24-27**, infra.

[0206] FIG. **23** illustrates one example of a logic flow **2300**. The logic flow **2300** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the data reduction generator **2220** of the evaluation component **122-4** of the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **2300** illustrates data reduction operations to reduce a data storage size for a computational representation **130**.

[0207] As shown in FIG. **23**, the logic flow **2300** may receive a computational representation arranged to generate an approximate probability distribution for statistics of a statistical test, the computational representation to include a simulated data structure with information for estimated cumulative distribution function (CDF) curves for one or more parameter vectors of the statistical test, each parameter vector to comprise a single point in a grid of points, at block **2302**. For instance, the data reduction generator **2220** may receive as input a computational representation **130** arranged to generate an approximate probability distribution **132** for each point in a grid of points from simulated statistics **430** for a statistical test **114**. The computational representation **130** may include a simulated data structure **1910** with information for estimated CDF curves.

[0208] The logic flow **2300** may evaluate the simulated data structure to determine whether any points in the grid of points are removable from the simulated data structure given a target level of precision at block **2304**. For example, the data reduction generator **2220** may evaluate the simulated data structure **1910** to determine whether any points in the grid of points are removable from the simulated data structure **1910** given a target level of precision.

[0209] The logic flow **2300** may reduce the simulated data structure in accordance with the evaluation to produce a reduced simulated data structure having a smaller data storage size relative to the simulated data structure, the reduced simulated data structure to reduce a data storage size for the computational representation at block **2306**. For example, the data reduction generator **2220** may reduce the simulated data structure **1910** in accordance with the evaluation to produce a reduced simulated data structure **2210**, where the simulated data structure **2210** has a smaller data storage size as compared to the simulated data structure **1910**. The reduced simulated data structure may in turn reduce a data storage size for the computational representation **130**.

[0210] FIG. **24** illustrates one example of a logic flow **2400**. The logic flow **2400** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the data reduction generator **2220** of the evaluation component **122-4** of the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **2400** illustrates data reduction operations to reduce a data storage size for a computational representation **130** utilizing a PAGE algorithm.

[0211] In general, the logic flow **2400** may receive a computation representation **130** with a simulated data structure **1910** containing information for estimated CDF curves, and evaluate the simulated data structure **1910** to determine whether any points in the grid of points are removable from the simulated data structure given a target level of precision. The logic flow **2400** may perform the evaluation using a PAGE algorithm. The logic flow **2400** may then reduce the simulated data structure **1910** using evaluation results to produce a reduced simulated data structure **2210**.

[0212] As shown in FIG. **24**, the logic flow **2400** may receive various inputs for a PAGE algorithm, such as an

interpolation grid G_0 with M points at **2402**, an interpolation grid G_2 with N points at **2404**, and an input table of N rows at **2406**. Each row of the input table may contain K keys and Q quantiles. The interpolation grid G_0 and/or the interpolation grid G_2 may be examples of an interpolation executable code **1940**. The input table at **2406** may be an example of a simulated data structure **1910**.

[0213] The logic flow **2400** may receive selection of a precision parameter to represent a target level of precision for the simulated data structure. The precision parameter may be automatically selected by the data reduction generator **2220** based on a defined set of rules. Alternatively, the precision parameter may be selected by a user. Once selected, the PAGE algorithm may receive as input the precision parameter, along with other control parameters, for example, the type of interpolation method, as indicated at **2408**.

[0214] The logic flow **2400** may remove points from the simulated data structure in accordance with a selected level of precision utilizing the PAGE algorithm. The PAGE algorithm may be used to identify a set of candidate points for potential removal from a simulated data structure. In one embodiment, for instance, the PAGE algorithm may execute at **2410** and output a candidate reduction data set using the interpolation grids G_0 , G_2 , the input table, and the one or more control parameters. The candidate reduction data set may be stored in a first output table **1** as indicated at **2412**. The output table **1** may include evaluation information. The evaluation information may include, for example, a defined number of rows N , with each row to include one or more each of K keys, Q explanation errors on quantiles, one or more evaluation criteria, F fit parameters, and/or one or more flags to indicate if a point p is to remain in an interpolation grid G_1 .

[0215] The logic flow **2400** may perform a DATA operation **2414** to extract one or more rows from the output table **1** at **2412** based on the evaluation information to construct a second output table **2** at **2416**. For instance, output table **2** is a subset of output table **1**, and it contains the rows that should be included in the interpolation grid G_1 and columns of keys and fit parameters. Output table **2** may be an example of a reduced simulated data structure **2210**. The logic flow **2400** may utilize the code generator component **122-3** at **2418** to generate the interpolation grid G_1 at **2420** based on the output table **2** at **2416**. The interpolation grid G_1 may be an example of an interpolation executable code **1940**.

[0216] In one embodiment, the PAGE algorithm may be arranged to generate the candidate reduction data set using a “jackknife” evaluation technique. A jackknife evaluation technique provides information regarding whether a point may be approximated by its neighbors for a given level of precision. This information may be used to determine those points that cannot be removed from the grid of points for the given level of precision. Once needed points are identified, the remaining points may be stored in the candidate reduction data set. For instance, the jackknife operation may provide information on a relationship between precision and grid size. Table 1 illustrates results from a jackknife evaluation technique on all 103,780 points on the grid of points, with each point having 10,001 quantiles, for a maxF test:

TABLE 1

Quantile	Jackknife Result
100%	0.445721510
99%	0.007458065
95%	0.000650852
90%	0.000596543

TABLE 1-continued

Quantile	Jackknife Result
75%	0.000532891
50%	0.000477936
25%	0.000435499
10%	0.000401377
5%	0.000382148
1%	0.000346780
0%	0.000270918

Table 1 illustrates that less than 1% points cannot be explained well by its neighbors when the precision requirement is 0.0075.

[0217] In one embodiment, a jackknife evaluation technique may be performed in accordance with the following exemplary procedure:

```

PROC HPSIMULATE
  data=scbpQuantiles /* output of quantiles */
  datadist=(ROUNDROBIN);
  MODULE name=evaluation
  ext=tkdens /* TK Extension to plug-in */
  var=(key1 - key3 q0 - q10000) /* keys and quantiles */
  task=2 /* Task : Evaluate performance */
  taskParmN=( /*nKeys=*/3 /*EvalType=*/1 /*weightTails=*/0
    /*weightA=*/-4.605 /*weightB=*/5.685
    /*interpolationMethod=*/1 /*interpolationMethodParm=*/5
  )
  taskParmS=( /*tkExtension=*/ “imaxf” );
  OUTPUT out=scbpEvaluationJackknife;
  PERFORMANCE nnodes=200 nthreads=6;
RUN.

```

Embodiments are not limited to this example.

[0218] The PAGE algorithm may use results from the jackknife evaluation technique as a basis for selectively removing points from the grid of points, estimating an approximation error for interpolation, and storing the removed points in the candidate reduction data set based on the approximation error. The PAGE algorithm may then evaluate each point in the candidate reduction data set against a set of evaluation criterion until a precision parameter is satisfied.

[0219] In general, the PAGE algorithm determines, given some target level of precision, whether an original interpolation grid G_2 could be reduced into a smaller interpolation grid G_1 , without deleting any points from an interpolation grid G_0 . The smaller interpolation grid may result in a smaller data storage size for the computational representation **130** (e.g., DLL). An example for reducing a data storage size for the computational representation **130** may be illustrated with the following exemplary procedure:

```

PROC HPSIMULATE
  data=scbpQuantiles /* output of quantiles */
  datadist=(ROUNDROBIN);
  MODULE name=PAGE
  ext=tkdens /* TK Extension to plug-in */
  dependent
  var=(key1 - key3 q0 - q10000) /* keys and quantiles */
  task=3 /* Task : Shrink the DLL size */
  taskParmN=( /*targetPrecision=*/0.0007 )
  taskParmS=( /*G2 tkExtension=*/ “imaxf”
    /*G0 tkExtension=*/ “imaxf0” );

```

-continued

```

OUTPUT out=scbpPAGE_G1;
PERFORMANCE nnodes=200 nthreads=6;
RUN.

```

Embodiments are not limited to this example.

[0220] After using a PAGE algorithm according to different precisions, a grid size with corresponding levels of precision for the maxF test may be shown in Table 2 as follows:

TABLE 2

	Precision				
	0.0050	0.0025	0.0010	0.0007	0.0005
Grid Size (# Points)	7,868	9,778	13,766	17,202	103,780
% of Original Grid	7.6%	9.4%	13.3%	16.6%	100.0%

Note that the original grid (e.g., simulated data structure **1910**) had 103,780 points for a precision level of 0.0005 ($\geq \max|-\tilde{T}|$). As indicated by Table 2, a data storage size for the simulated data structure **1910** may be substantially reduced when a level of precision is reduced. For instance, at a precision level of 0.0050, the number of points may be reduced from 103,780 points to 7,868 points, which is 7.6% of the simulated data structure **1910**. In this manner, an informed design decision may be made for the interpolation source code **1930** and/or the computational representation **130** regarding tradeoffs between a level of precision and data storage size, as desired for a given implementation. Embodiments are not limited in this context.

[0221] In some cases, it may take significant time and computational resources to simulate all points with an original set of statistics (e.g., 1 million statistics for the maxF test). To reduce time and conserve computational resources, a reduced number of statistics (e.g., 20,000 statistics for the maxF test) could be used for a single point, and then the PAGE algorithm may be used on the simulated points to find final grid points. The original set of statistics (e.g., 1,000,000) may then be simulated for only the final grid points. This could be accomplished using a defined set of criteria.

[0222] For the maxF test, for example, 20,000 statistics on each of 103,780 points may be simulated, and 10,001 quantiles on each of 103,780 points may be generated. Assume CDFs are fitted with a precision of 0.0020. The average number of curve parameters for different precisions are shown in Table 3, as follows:

TABLE 3

	Precision			
	0.0050	0.0025	0.0020	0.0010
Avg. # of curve Parameters	7.261	12.081	18.877	109.592

[0223] Code and a DLL may be generated, and the PAGE algorithm may be applied to the DLL to generate Table 4, as follows:

TABLE 4

Precision	0.0050	0.0045	0.0040	0.0035	0.0030	0.0025	0.0020
Percentage of Points	10.6%	12.2%	14.9%	19.2%	27.3%	46.1%	87.7%

[0224] Using the results shown in Table 4, assume the points corresponding to precision of 0.0030 are selected. The original set of statistics (e.g., 1,000,000 statistics) may be simulated on each of the selected points. The defined number of quantiles (e.g., 10,001 quantiles) on each of selected points may be generated. The CDFs may be fitted with a precision of 0.0005. Finally code and DLL may be generated for the selected points.

[0225] Since all points with 1,000,000 statistics are available, the PAGE algorithm can do another evaluation, the results of which are shown in Table 5 as follows:

TABLE 5

Quantile	Estimates
100% Max	0.002834907
99%	0.000847933
95%	0.000661086
90%	0.000603617
75% Q3	0.000530835
50% Median	0.000479984
25% Q1	0.000442317
10%	0.000411247
5%	0.000394015
1%	0.000361853
0% Min	0.000265525

[0226] Various aspects of the evaluation component **122-4** in general, and the data reduction generator **2220** and PAGE algorithm in particular, may be described with reference to FIGS. **25-27**, infra.

[0227] FIG. **25** illustrates one example of a logic flow **2500**. The logic flow **2500** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the data reduction generator **2220** of the evaluation component **122-4** of the simulation subsystem **120** of the automated statistical test system **100**.

[0228] The logic flow **2500** illustrates evaluation operations performed in accordance with an exemplary PAGE algorithm. In general, the PAGE algorithm determines, given some target level of precision, whether an original interpolation grid G_2 could be reduced into a smaller interpolation grid G_1 , without deleting any points from an interpolation grid G_0 . In this example, the PAGE algorithm is implemented by the distributed computing system **610** utilizing a general/captain architecture.

[0229] As shown in FIG. **25**, the logic flow **2500** may initialize an output table on a captain node at block **2502**. The output table may store a candidate reduction data set. The logic flow **2500** may perform a jackknife operation on interpolation grid G_2 with N points to find the P points not meeting the control parameters at **2504**.

[0230] The logic flow **2500** may call a subroutine MPI_Allgather for execution by a general node and the captain node at block **2506**. The logic flow **2500** may form an interpolation grid G_1 and update flags at **2508**. The interpolation grid G_1 may include the interpolation grid G_0 plus P points.

[0231] The logic flow **2500** may interpolate all quantiles through the interpolation grid G_1 against a set of evaluation criterion until the precision parameter is satisfied. For instance, the logic flow **2500** may evaluate N points on the interpolation grid G_1 at **2510**. The logic flow **2500** may call subroutines `MPI_Reduce` and `MPI_Bcast` on the general node and/or the captain node to broadcast a maximum criterion and the points V to achieve a maximum criterion at **2512**. The logic flow **2500** may test whether the maximum criterion is less than or equal to a defined precision level at **2514**. If the maximum criterion is less than or equal to the defined precision level, then the general node may call the subroutine `MPI_Bcast` to indicate a parameter `qDONE` is set to a value of 1 at **2516**. The PAGE algorithm then terminates.

[0232] If the maximum criterion is greater than the defined precision level, then the general node and/or the captain node may call the subroutine `MPI_Bcast` to indicate a parameter `qDONE` is set to a value of 0 and the point V at **2518**. The captain node may update the interpolation grid G_1 to include the interpolation grid G_1 plus the points V and update the flag at **2520**. Operations at **2510**, **2512**, **2514**, **2518** and **2520** may be repeated until the maximum criterion is less than or equal to a defined precision level at **2514**. The PAGE algorithm then terminates.

[0233] FIG. 26 illustrates one example of a logic flow **2600**. The logic flow **2600** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the simulation subsystem **120** of the automated statistical test system **100**. More particularly, the logic flow **2600** illustrates procedure for the simulation subsystem **120** to generate a computational representation **130**.

[0234] As shown in FIG. 26, the logic flow **2600** may simulate statistics by repeating, for p equals 1 to P , simulating S statistics on point p , where S is set to 20,000 and P equals a number of all potential points (or parameter vectors), at block **2602**. Block **2602** may output S by P statistics at **2614**.

[0235] The logic flow **2600** may generate quantiles by repeating, for p equals 1 to P , generating Q quantiles on point p , where Q is set to 10,001, at block **2604**. Block **2604** may output Q by P quantiles at **2626**.

[0236] The logic flow **2600** may fit CDFs by repeating, for p equals 1 to P , fitting a curve to Q quantiles on point p with at most F curve parameters, where F is set to 128, at block **2606**. Block **2606** may output F by P curve parameters at **2618**.

[0237] The logic flow **2600** may generate C code using all P points for grid G_2 and selected points for grid G_0 at block **2608**. Block **2608** may output two C files, four H files and two build scripts, at **2620**.

[0238] The logic flow **2600** may build a TK-Extension using a SDSGUI to build two DLLs at block **2610**. Block **2610** may output a `tkGrid2.dll` and a `tkGrid0.dll` at **2622**.

[0239] The logic flow **2600** may run PAGE algorithm for different levels of precisions. Block **2612** outputs a table of number of points versus a given level of precision at **2624**. Control is then passed to control location G .

[0240] FIG. 27 illustrates one example of a logic flow **2700**. The logic flow **2700** may be representative of some or all of the operations executed by one or more embodiments described herein, such as the simulation subsystem **120** of the automated statistical test system **100**. More particularly,

the logic flow **2700** illustrates procedure for the simulation subsystem **120** to reduce a data storage size for a computational representation **130**.

[0241] As shown in FIG. 27, the logic flow **2700** may receive control from control location G , and select a proper number of points for the computational representation **130** at **2702**. The proper number of points may be selected by data reduction generator **2220**, and it may be an example of a reduced simulated data structure **2210**.

[0242] The logic flow **2700** may simulate statistics by repeating, for p equals 1 to B , simulating S statistics on point p , where S is set to 1,000,000 and B equals the number of selected points (or parameter vectors), at block **2704**. Block **2704** may output S by B statistics at **2714**.

[0243] The logic flow **2700** may generate quantiles by repeating, for p equals 1 to B , generating Q quantiles on point p , where Q is set to 10,001, at block **2706**. Block **2706** may output Q by B quantiles at **2716**.

[0244] The logic flow **2700** may fit CDFs by repeating, for p equals 1 to B , fitting a curve to Q quantiles on point p with at most F curve parameters, where F is set to 128, at block **2708**. Block **2708** may output F by P curve parameters at **2718**.

[0245] The logic flow **2700** may generate C code using all B points for grid G_1 at block **2710**. Block **2710** may output one C file, two H files and one build script, at **2720**.

[0246] The logic flow **2700** may build a TK-Extension using a SDSGUI to build one DLL at block **2712**. Block **2712** may output a `tkGrid1.dll` at **2722**. The `tkGrid1.dll` may be an example of an interpolation executable code **1940**.

[0247] FIG. 28A illustrates a block diagram for a statistical test subsystem **140**. The statistical test subsystem **140** is part of the automated statistical test system **100**. The statistical test subsystem **140** may, for example, generate statistical significance values for results of a statistical test using an approximate probability distribution.

[0248] As shown in FIG. 28A, the statistical test subsystem **140** may include a statistical test application **2820** having various components **2822-s**. The statistical test application **2820** may include a data handler component **2822-1**, a statistical test component **2822-2**, and a significance generator component **2822-3**. The statistical test application **2820** may include more or less components **2822-s** for other implementations.

[0249] The data handler component **2822-1** may be generally arranged to handle data sets for use in a statistical test **114**. For instance, the data handler component **2822-1** may receive a real data set **2810** from a client device **602**. The real data set **2810** may represent actual data for analysis by the statistical test **114**, such as sets of collected business or enterprise data, as opposed to simulated data **330** used to generate approximate probability distributions **132** for the statistical test **114**. In one embodiment, for example, the real data set **2810** may comprise data representing one or more physical phenomena, such as occurrences of heads or tails in a coin flip, sales of a number of shoes in Asia, or a percentage increase or decrease in a financial portfolio. In one embodiment, for example, the real data set **2810** may comprise data representing one or more measurable phenomena, which may include both physical and non-physical phenomena. An example of non-measurable phenomena may include without limitation digital data from an electronic device, such as a sensor, computer, or characters on a display. Embodiments are not limited in this context.

[0250] The statistical test component **2822-2** may be generally arranged to perform the statistical test using the real data set **2810**. The statistical test component **2822-2** may receive a computation representation **130** from, for example, the simulation subsystem **120**. The statistical test component **2822-2** may also receive the statistical test function **112** for the statistical test **114**. As previously described, the computational representation **130** may be arranged to generate an approximate probability distribution **132** for each point in a grid of points from simulated statistics **430** for the statistical test **114**, statistics of the statistical test **114** to follow a probability distribution of a known or unknown form. The approximate probability distribution function **132** may comprise an empirical CDF, the empirical CDF to have a first level of precision relative to the probability distribution of the known or unknown form based on a sample size of the simulated statistics.

[0251] The statistical test component **2822-2** may generate a set of statistics **2824** for the statistical test **114** using the real data set **2810** and the statistical test function **112**.

[0252] The significance generator component **2822-3** may be generally arranged to generate a set of statistical significance values **2830** for the statistics **2824** generated by the statistical test component **2822-2** using the approximate probability distribution **132** of the computational representation **130**. The set of statistical significance values may be in the form of one or more p-values.

[0253] A p-value may generally represent a probability of obtaining a given test statistic from observed or measurable data, such as a test statistic obtained or evaluated from the real data set **2810**. More particularly, a p-value may represent a probability of obtaining a test statistic evaluated from the real data set **2810** that is at least as “extreme” as one that was actually observed, assuming the null hypothesis is true. For instance, assume a statistical test **114** involves rolling a pair of dice once and further assumes a null hypothesis that the dice are fair. An exemplary test statistic may comprise “the sum of the rolled numbers” and is one-tailed. When the dice are rolled, assume a result where each rolled dice finally lands and presents a side with a number **6**. In this case, the test statistic is the sum of the rolled numbers from both dice, which would be **12** ($6+6=12$). A p-value for this particular result or outcome is a probability of $1/36$, or approximately **0.028**. The p-value of **0.028** represents the highest test statistic out of $6 \times 6 = 36$ possible outcomes. If a significance level of **0.05** is assumed, then this result would be deemed significant since **0.028** is lower (or more extreme) value than **0.05**. As such, the observed result of **12** from the rolled dice would amount to evidence that could be used to reject the null hypothesis that the dice are fair.

[0254] Once p-values are generated, the significance generator component **2822-3** may use the p-values in a number of different ways. For instance, the significance generator component **2822-3** may present the p-values in a user interface view on an electronic display, an example of which is described with reference to FIG. **28B**, *infra*. A user may then determine whether a null hypothesis for the statistical test **114** is rejected based on the p-values.

[0255] Additionally or alternatively, this determination may be automatically made by the statistical application **2820**. For instance, the significance generator component **2822-3** may compare a p-value to a defined threshold value. The significance generator component **2822-3** may then determine whether a null hypothesis for the statistical test

114 is rejected based on a comparison of a p-value to a defined threshold value. The significance generator component **2822-3** may then display a conclusion from the results on the electronic display.

[0256] FIG. **28B** illustrates a user interface view **2850**. The user interface view **2850** illustrates an exemplary user interface presenting output of a statistical test **114** in the form of a Bai and Perron’s multiple structural change test as executed by the statistical test application **2820**.

[0257] This example illustrates how to use Bai and Perron’s multiple structural change tests and the p-values generated from a HPSIMULATE procedure. It uses the following notations:

[0258] t : a time index

[0259] y : a dependent variable

[0260] x : an independent variable

[0261] ϵ : an innovation

[0262] i. i. d.: independent and identically distributed

[0263] $N(0,1)$: a standard normal distribution with mean 0 and variance 1

[0264] H_0 : a null hypothesis

[0265] H_1 : an alternative hypothesis

[0266] m : a number of break points in the data

[0267] $\sup F_{l+1II}$: a sequential test for multiple structural change proposed by Bai and Perron, where l is the number of break points in the null hypothesis and $l+1$ in the alternative hypothesis

[0268] As shown in a DATA operation **2852**, labeled in the user interface view as “data one,” the data generating process (DGP) has two break points at time indices **60** and **140**. Precisely, the structural change model is as follows:

$$y_t = \begin{cases} 2 + x_t + \epsilon_t, & t \leq 59 \\ 3 + 2x_t + \epsilon_t, & 60 \leq t \leq 139, \epsilon_t \sim i.i.d.N(0, 1) \\ 3 + 2.9x_t + \epsilon_t, & t \geq 140 \end{cases}$$

[0269] In a PROC operation **2854**, labeled in the user interface view **2850** as “proc autoreg,” a BP=(M=3) option is set in the AUTOREG procedure to apply Bai and Perron’s multiple structural change tests on the data. The user interface view **2850** shows the result of $\sup F_{l+1II}$ tests in a table **2856** annotated as “Bai and Perron’s Multiple Structural Change Tests, $\sup F(1+1II)$ Tests,” which sequentially checks the null hypothesis H_0 : $m=l$ versus the alternative null hypothesis H_1 : $m=l+1$ for $l=0, 1, 2, 3$, where m is the number of break points in the data. A statistic for each test is shown in a column **2858** and a corresponding p-value, interpolated from the DLL generated by the HPSIMULATE procedure, is shown in a column **2860**. If 15% is selected as a defined threshold value (e.g., a significance threshold), by comparing p-values to 15%, the null hypothesis H_0 : $m=0$ and H_0 : $m=1$; are rejected. However, the null hypothesis of H_0 : $m=2$ cannot be rejected. According to one interpretation of these tests, there exists at least 2 break points in the data.

[0270] For the $\sup F_{l+1II}$ test, in literature, critical values for only four significance levels, namely 1%, 2.5%, 5%, and 10%, are available on some parameter vectors. Hence, a user can only make decision at those four significance levels on the finite parameter vectors by comparing the test statistics, based on the real data set, with the critical values available in literature. However, with the support of HPSIMULATE

system and the DLL generated from it, the user can make decision at any significance level of interest (e.g., 15% here) on any parameter vector.

[0271] FIG. 29 illustrates one example of a logic flow 2900. The logic flow 2900 may be representative of some or all of the operations executed by one or more embodiments described herein, such as the statistical test subsystem 140 of the automated statistical test system 100.

[0272] As shown in FIG. 29, the logic flow 2900 may receive a computational representation arranged to generate an approximate probability distribution for statistics of a statistical test based on a parameter vector, statistics of the statistical test to follow a probability distribution at block 2902. The probability distribution, for example, may comprise a probability distribution of a known or an unknown form. The logic flow 2900 may receive a real data set from a client device, the real data set to comprise data representing at least one measurable phenomenon or physical phenomenon at block 2904. The logic flow 2900 may generate statistics for the statistical test using the real data set on the parameter vector at block 2906. The logic flow 2900 may generate the approximate probability distribution of the computational representation on the parameter vector at block 2908. The logic flow 2900 may generate a set of statistical significance values for the statistics through interpolation at block 2910 by using the approximate probability distribution of the computational representation, the set of statistical significance values comprising one or more p-values, each p-value to represent a probability of obtaining a given test statistic from the real data set, at block 2906.

[0273] FIG. 30 illustrates a block diagram of a centralized system 3000. The centralized system 3000 may implement some or all of the structure and/or operations for the automated statistical test system 100 in a single computing entity, such as entirely within a single device 3020.

[0274] The device 3020 may comprise any electronic device capable of receiving, processing, and sending information for the automated statistical test system 100. Examples of an electronic device may include without limitation an ultra-mobile device, a mobile device, a personal digital assistant (PDA), a mobile computing device, a smart phone, a telephone, a digital telephone, a cellular telephone, eBook readers, a handset, a one-way pager, a two-way pager, a messaging device, a computer, a personal computer (PC), a desktop computer, a laptop computer, a notebook computer, a netbook computer, a handheld computer, a tablet computer, a server, a server array or server farm, a web server, a network server, an Internet server, a work station, a mini-computer, a main frame computer, a supercomputer, a network appliance, a web appliance, a distributed computing system, multiprocessor systems, processor-based systems, consumer electronics, programmable consumer electronics, game devices, television, digital television, set top box, wireless access point, base station, subscriber station, mobile subscriber center, radio network controller, router, hub, gateway, bridge, switch, machine, or combination thereof. The embodiments are not limited in this context.

[0275] The device 3020 may execute processing operations or logic for the automated statistical test system 100 using a processing component 3030. The processing component 3030 may comprise various hardware elements, software elements, or a combination of both. Examples of hardware elements may include devices, logic devices,

components, processors, microprocessors, circuits, processor circuits, circuit elements (e.g., transistors, resistors, capacitors, inductors, and so forth), integrated circuits, application specific integrated circuits (ASIC), programmable logic devices (PLD), digital signal processors (DSP), field programmable gate array (FPGA), memory units, logic gates, registers, semiconductor device, chips, microchips, chip sets, and so forth. Examples of software elements may include software components, programs, applications, computer programs, application programs, system programs, software development programs, machine programs, operating system software, middleware, firmware, software modules, routines, subroutines, functions, methods, procedures, software interfaces, application program interfaces (API), instruction sets, computing code, computer code, code segments, computer code segments, words, values, symbols, or any combination thereof. Determining whether an embodiment is implemented using hardware elements and/or software elements may vary in accordance with any number of factors, such as desired computational rate, power levels, heat tolerances, processing cycle budget, input data rates, output data rates, memory resources, data bus speeds and other design or performance constraints, as desired for a given implementation.

[0276] The device 3020 may execute communications operations or logic for the automated statistical test system 100 using communications component 3040. The communications component 3040 may implement any well-known communications techniques and protocols, such as techniques suitable for use with packet-switched networks (e.g., public networks such as the Internet, private networks such as an enterprise intranet, and so forth), circuit-switched networks (e.g., the public switched telephone network), or a combination of packet-switched networks and circuit-switched networks (with suitable gateways and translators). The communications component 3040 may include various types of standard communication elements, such as one or more communications interfaces, network interfaces, network interface cards (NIC), radios, wireless transmitters/receivers (transceivers), wired and/or wireless communication media, physical connectors, and so forth. By way of example, and not limitation, communication media 3012, 3042 include wired communications media and wireless communications media. Examples of wired communications media may include a wire, cable, metal leads, printed circuit boards (PCB), backplanes, switch fabrics, semiconductor material, twisted-pair wire, co-axial cable, fiber optics, a propagated signal, and so forth. Examples of wireless communications media may include acoustic, radio-frequency (RF) spectrum, infrared and other wireless media.

[0277] The device 3020 may communicate with other devices 3010, 3050 over a communications media 3012, 3042, respectively, using communications information 3014, 3044, respectively, via the communications component 3040. The devices 3010, 3050 may be internal or external to the device 3020 as desired for a given implementation. An example for the devices 3010 may be one or more client devices used to access results from the automated statistical test system 100.

[0278] FIG. 31 illustrates a block diagram of a distributed system 3100. The distributed system 3100 may distribute portions of the structure and/or operations for the automated statistical test system 100 across multiple computing entities. Examples of distributed system 3100 may include

without limitation a client-server architecture, a S-tier architecture, an N-tier architecture, a tightly-coupled or clustered architecture, a peer-to-peer architecture, a master-slave architecture, a shared database architecture, and other types of distributed systems. The embodiments are not limited in this context.

[0279] The distributed system 3100 may comprise a client device 3110 and a server device 3150. In general, the client device 3110 and the server device 3150 may be the same or similar to the client device 3020 as described with reference to FIG. 30. For instance, the client device 3110 and the server device 3150 may each comprise a processing component 3130 and a communications component 3140 which are the same or similar to the processing component 3030 and the communications component 3040, respectively, as described with reference to FIG. 30. In another example, the devices 3110, 3150 may communicate over a communications media 3112 using communications information 3114 via the communications components 3140.

[0280] The client device 3110 may comprise or employ one or more client programs that operate to perform various methodologies in accordance with the described embodiments. In one embodiment, for example, the client device 3110 may implement a client application 3116 to configure, control or otherwise manage the automated statistical test system 100. The client application 3116 may also be used to view results from the automated statistical test system 100, such as statistical significance values or null hypothesis results. The client application 3116 may be implemented as a thin-client specifically designed to interoperate with the automated statistical test system 100. Alternatively, the client application 3116 may be a web browser to access the automated statistical test system 100 via one or more web technologies. Embodiments are not limited in this context.

[0281] The server device 3150 may comprise or employ one or more server programs that operate to perform various methodologies in accordance with the described embodiments. In one embodiment, for example, the server device 3150 may implement the automated statistical test system 100, and any interfaces needed to permit access to the automated statistical test system 100, such as a web interface. The server device 3150 may also control authentication and authorization operations to enable secure access to the automated statistical test system 100 via the media 3112 and information 3114.

[0282] FIG. 32 illustrates an embodiment of an exemplary computing architecture 3200 suitable for implementing various embodiments as previously described. In one embodiment, the computing architecture 3200 may comprise or be implemented as part of an electronic device. Examples of an electronic device may include those described with reference to FIG. 31, among others. The embodiments are not limited in this context.

[0283] As used in this application, the terms “system” and “component” are intended to refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution, examples of which are provided by the exemplary computing architecture 3200. For example, a component can be, but is not limited to being, a process running on a processor, a processor, a hard disk drive, multiple storage drives (of optical and/or magnetic storage medium), an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a server and

the server can be a component. One or more components can reside within a process and/or thread of execution, and a component can be localized on one computer and/or distributed between two or more computers. Further, components may be communicatively coupled to each other by various types of communications media to coordinate operations. The coordination may involve the uni-directional or bi-directional exchange of information. For instance, the components may communicate information in the form of information communicated over the communications media. The information can be implemented as information allocated to various signal lines. In such allocations, each message is a signal. Further embodiments, however, may alternatively employ data messages. Such data messages may be sent across various connections. Exemplary connections include parallel interfaces, serial interfaces, and bus interfaces.

[0284] The computing architecture 3200 includes various common computing elements, such as one or more processors, multi-core processors, co-processors, memory units, chipsets, controllers, peripherals, interfaces, oscillators, timing devices, video cards, audio cards, multimedia input/output (I/O) components, power supplies, and so forth. The embodiments, however, are not limited to implementation by the computing architecture 3200.

[0285] As shown in FIG. 32, the computing architecture 3200 comprises a processing unit 3204, a system memory 3206 and a system bus 3208. The processing unit 3204 can be any of various commercially available processors, including without limitation an AMD® Athlon®, Duron® and Opteron® processors; ARM® application, embedded and secure processors; IBM® and Motorola® DragonBall® and PowerPC® processors; IBM and Sony® Cell processors; Intel® Celeron®, Core (2) Duo®, Itanium®, Pentium®, Xeon®, and XScale® processors; and similar processors. Dual microprocessors, multi-core processors, and other multi-processor architectures may also be employed as the processing unit 3204.

[0286] The system bus 3208 provides an interface for system components including, but not limited to, the system memory 3206 to the processing unit 3204. The system bus 3208 can be any of several types of bus structure that may further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. Interface adapters may connect to the system bus 3208 via a slot architecture. Example slot architectures may include without limitation Accelerated Graphics Port (AGP), Card Bus, (Extended) Industry Standard Architecture ((E)ISA), Micro Channel Architecture (MCA), NuBus, Peripheral Component Interconnect (Extended) (PCI(X)), PCI Express, Personal Computer Memory Card International Association (PCMCIA), and the like.

[0287] The computing architecture 3200 may comprise or implement various articles of manufacture. An article of manufacture may comprise a computer-readable storage medium to store logic. Examples of a computer-readable storage medium may include any tangible media capable of storing electronic data, including volatile memory or non-volatile memory, removable or non-removable memory, erasable or non-erasable memory, writeable or re-writable memory, and so forth. Examples of logic may include executable computer program instructions implemented using any suitable type of code, such as source code,

compiled code, interpreted code, executable code, static code, dynamic code, object-oriented code, visual code, and the like. Embodiments may also be at least partly implemented as instructions contained in or on a non-transitory computer-readable medium, which may be read and executed by one or more processors to enable performance of the operations described herein.

[0288] The system memory 3206 may include various types of computer-readable storage media in the form of one or more higher speed memory units, such as read-only memory (ROM), random-access memory (RAM), dynamic RAM (DRAM), Double-Data-Rate DRAM (DDRDRAM), synchronous DRAM (SDRAM), static RAM (SRAM), programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), flash memory, polymer memory such as ferroelectric polymer memory, ovonic memory, phase change or ferroelectric memory, silicon-oxide-nitride-oxide-silicon (SONOS) memory, magnetic or optical cards, an array of devices such as Redundant Array of Independent Disks (RAID) drives, solid state memory devices (e.g., USB memory, solid state drives (SSD) and any other type of storage media suitable for storing information. In the illustrated embodiment shown in FIG. 32, the system memory 3206 can include non-volatile memory 3210 and/or volatile memory 3212. A basic input/output system (BIOS) can be stored in the non-volatile memory 3210.

[0289] The computer 3202 may include various types of computer-readable storage media in the form of one or more lower speed memory units, including an internal (or external) hard disk drive (HDD) 3214, a magnetic floppy disk drive (FDD) 3216 to read from or write to a removable magnetic disk 3218, and an optical disk drive 3220 to read from or write to a removable optical disk 3222 (e.g., a CD-ROM or DVD). The HDD 3214, FDD 3216 and optical disk drive 3220 can be connected to the system bus 3208 by a HDD interface 3224, an FDD interface 3226 and an optical drive interface 3228, respectively. The HDD interface 3224 for external drive implementations can include at least one or both of Universal Serial Bus (USB) and IEEE 1394 interface technologies.

[0290] The drives and associated computer-readable media provide volatile and/or nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For example, a number of program modules can be stored in the drives and memory units 3210, 3212, including an operating system 3230, one or more application programs 3232, other program modules 3234, and program data 3236. In one embodiment, the one or more application programs 3232, other program modules 3234, and program data 3236 can include, for example, the various applications and/or components of the automated statistical test system 100.

[0291] A user can enter commands and information into the computer 3202 through one or more wire/wireless input devices, for example, a keyboard 3238 and a pointing device, such as a mouse 3240. Other input devices may include microphones, infra-red (IR) remote controls, radio-frequency (RF) remote controls, game pads, stylus pens, card readers, dongles, finger print readers, gloves, graphics tablets, joysticks, keyboards, retina readers, touch screens (e.g., capacitive, resistive, etc.), trackballs, trackpads, sensors, styluses, and the like. These and other input devices are often connected to the processing unit 3204 through an input device interface 3242 that is coupled to the system bus 3208, but can be connected by other interfaces such as a parallel port, IEEE 1394 serial port, a game port, a USB port, an IR interface, and so forth.

[0292] A monitor 3244 or other type of display device is also connected to the system bus 3208 via an interface, such as a video adaptor 3246. The monitor 3244 may be internal or external to the computer 3202. In addition to the monitor 3244, a computer typically includes other peripheral output devices, such as speakers, printers, and so forth.

[0293] The computer 3202 may operate in a networked environment using logical connections via wire and/or wireless communications to one or more remote computers, such as a remote computer 3248. The remote computer 3248 can be a workstation, a server computer, a router, a personal computer, portable computer, microprocessor-based entertainment appliance, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer 3202, although, for purposes of brevity, only a memory/storage device 3250 is illustrated. The logical connections depicted include wire/wireless connectivity to a local area network (LAN) 3252 and/or larger networks, for example, a wide area network (WAN) 3254. Such LAN and WAN networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which may connect to a global communications network, for example, the Internet.

[0294] When used in a LAN networking environment, the computer 3202 is connected to the LAN 3252 through a wire and/or wireless communication network interface or adaptor 3256. The adaptor 3256 can facilitate wire and/or wireless communications to the LAN 3252, which may also include a wireless access point disposed thereon for communicating with the wireless functionality of the adaptor 3256.

[0295] When used in a WAN networking environment, the computer 3202 can include a modem 3258, or is connected to a communications server on the WAN 3254, or has other means for establishing communications over the WAN 3254, such as by way of the Internet. The modem 3258, which can be internal or external and a wire and/or wireless device, connects to the system bus 3208 via the input device interface 3242. In a networked environment, program modules depicted relative to the computer 3202, or portions thereof, can be stored in the remote memory/storage device 3250. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers can be used.

[0296] The computer 3202 is operable to communicate with wire and wireless devices or entities using the IEEE 802 family of standards, such as wireless devices operatively disposed in wireless communication (e.g., IEEE 802.11 over-the-air modulation techniques). This includes at least Wi-Fi (or Wireless Fidelity), WiMax, and Bluetooth™ wireless technologies, among others. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices. Wi-Fi networks use radio technologies called IEEE 802.11x (a, b, g, n, etc.) to provide secure, reliable, fast wireless connectivity. A Wi-Fi network can be used to connect computers to each other, to the Internet, and to wire networks (which use IEEE 802.3-related media and functions).

[0297] FIG. 33 illustrates a block diagram of an exemplary communications architecture 3300 suitable for implementing various embodiments as previously described. The communications architecture 3300 includes various common communications elements, such as a transmitter, receiver, transceiver, radio, network interface, baseband processor, antenna, amplifiers, filters, power supplies, and so forth. The

embodiments, however, are not limited to implementation by the communications architecture **3300**.

[0298] As shown in FIG. 33, the communications architecture **3300** comprises includes one or more clients **3302** and servers **3304**. The clients **3302** may implement the client device **3110**. The servers **3304** may implement the server device **950**. The clients **3302** and the servers **3304** are operatively connected to one or more respective client data stores **3308** and server data stores **3310** that can be employed to store information local to the respective clients **3302** and servers **3304**, such as cookies and/or associated contextual information.

[0299] The clients **3302** and the servers **3304** may communicate information between each other using a communication framework **3306**. The communications framework **3306** may implement any well-known communications techniques and protocols. The communications framework **3306** may be implemented as a packet-switched network (e.g., public networks such as the Internet, private networks such as an enterprise intranet, and so forth), a circuit-switched network (e.g., the public switched telephone network), or a combination of a packet-switched network and a circuit-switched network (with suitable gateways and translators).

[0300] The communications framework **3306** may implement various network interfaces arranged to accept, communicate, and connect to a communications network. A network interface may be regarded as a specialized form of an input output interface. Network interfaces may employ connection protocols including without limitation direct connect, Ethernet (e.g., thick, thin, twisted pair 10/100/1000 Base T, and the like), token ring, wireless network interfaces, cellular network interfaces, IEEE 802.11a-x network interfaces, IEEE 802.16 network interfaces, IEEE 802.20 network interfaces, and the like. Further, multiple network interfaces may be used to engage with various communications network types. For example, multiple network interfaces may be employed to allow for the communication over broadcast, multicast, and unicast networks. Should processing requirements dictate a greater amount speed and capacity, distributed network controller architectures may similarly be employed to pool, load balance, and otherwise increase the communicative bandwidth required by clients **3302** and the servers **3304**. A communications network may be any one and the combination of wired and/or wireless networks including without limitation a direct interconnection, a secured custom connection, a private network (e.g., an enterprise intranet), a public network (e.g., the Internet), a Personal Area Network (PAN), a Local Area Network (LAN), a Metropolitan Area Network (MAN), an Operating Missions as Nodes on the Internet (OMNI), a Wide Area Network (WAN), a wireless network, a cellular network, and other communications networks.

[0301] FIG. 34 illustrates an embodiment of a storage medium **3400**. The storage medium **3400** may comprise an article of manufacture. In one embodiment, the storage medium **3400** may comprise any non-transitory, physical, or hardware computer readable medium or machine readable medium, such as an optical, magnetic or semiconductor storage. The storage medium may store various types of computer executable instructions **3402**, such as instructions to implement one or more of the logic flows as described herein. Examples of a computer readable or machine readable storage medium may include any tangible media capable of storing electronic data, including physical memory, hardware memory, volatile memory or non-volatile memory, removable or non-removable memory, erasable or

non-erasable memory, writeable or re-writeable memory, and so forth. Examples of computer executable instructions may include any suitable type of code, such as assembly code, source code, compiled code, interpreted code, executable code, static code, dynamic code, object-oriented code, visual code, compressed code, uncompressed code, and the like. The embodiments are not limited in this context.

[0302] The computer executable instructions **3402** may be implemented using one or more different types of programming languages. A programming language is an artificial language designed to communicate instructions to a machine, particularly a computer. Programming languages can be used to create programs that control the behavior of a machine and/or to express algorithms. Many programming languages have computation specified in an imperative form (e.g., as a sequence of operations to perform), while other languages utilize other forms of program specification such as the declarative form (e.g., the desired result is specified, not how to achieve it). The description of a programming language is usually split into the two components of syntax (form) and semantics (meaning). Some languages are defined by a specification document (e.g. the C programming language is specified by an ISO Standard), while other languages (e.g., Perl) have a dominant implementation that is treated as a reference.

[0303] In one embodiment, for example, the computer executable instructions **3402** may be implemented in a specific programming language as developed by SAS Institute, Inc., Cary, N.C. For instance, the computer executable instructions **3402** may be implemented in a procedure referred to as HPSIMULATE, which is a procedure suitable for execution within a SAS programming language and computing environment. In such embodiments, the computer executable instructions **3402** may follow syntax and semantics associated with HPSIMULATE. However, embodiments are not limited to HPSIMULATE, and further, do not need to necessarily follow the syntax and semantics associated with HPSIMULATE. Embodiments are not limited to a particular type of programming language.

[0304] The HPSIMULATE procedure dynamically loads a TK-extension to perform statistical simulation and other tasks, such as post-processing, optimization, and other tasks. In one embodiment, the HPSIMULATE procedure may perform statistical simulation in distributed computing and multi-thread environment.

[0305] The HPSIMULATE may have a syntax as follows:

```
PROC HPSIMULATE
DATA = SAS-data-set
DATADIST = ( COPYONGENERAL | COPYTONODES |
ROUNDROBIN | DEFAULT | INSLICES | COLUMNWISE |
COLUMNWISEBY )
NAMELEN <= number>
NOCLPRINT <= number>
DEBUG$ <= number>
NTRIES = number
NOPRINT;
MODULE
EXT = name
TASK = number
DEPENDENT | CONTROLPARALLEL
TASKPARMV | VARPARM | VAR = ( variable-list )
TASKPARMN | NUMBERPARM | TASKPARM = (
number-list )
TASKPARMS | STRINGPARM = ( quoted-string-list )
NAME = name;
OUTPUT
OUT | OUT1 = SAS-data-set
OUT2 = SAS-data-set
```

-continued

OUT3 = SAS-data-set
OUT4 = SAS-data-set
OUT5 = SAS-data-set
OUT6 = SAS-data-set
OUT7 = SAS-data-set
OUT8 = SAS-data-set
OUT9 = SAS-data-set
REG REGSTART = number;
PERFORMANCE
NODES = number
NTHREADS = number.

The options in gray font are some unnecessary options to run the HPSIMULATE procedure, or reserved for future usage. [0306] A set of statements and options used with the HPSIMULATE procedure are summarized in the following Table 6:

TABLE 6

Description	Statement	Option
Data Set Options		
Specify the input data set	HPSIMULATE	DATA=
Specify how the data are distributed on grid	HPSIMULATE	DATADIST=
Write results to an output data set	OUTPUT	OUT=
Grid Control Options		
Specify the number of captains	PERFORMANCE	NODES=
Specify the number of threads	PERFORMANCE	NTHREADS=
Task Control Options		
Specify the TK-extension to execute the tasks	MODULE	EXT=
Specify the task ID to be executed	MODULE	TASK=
Specify whether the task needs to control communication between threads and between nodes	MODULE	DEPENDENT
Specify the variable names in input data set	MODULE	TASKPARMV=
Specify the number parameters	MODULE	TASKPARMN=
Specify the string parameters	MODULE	TASKPARMS=
Specify the name of the module	MODULE	NAME=

[0307] The HPSIMULATE procedure may use the following statement:

[0308] PROC HPSIMULATE options.

[0309] The HPSIMULATE statement may use a first option, as follows:

[0310] DATA=SAS-data-set.

The DATA option specifies the input data set containing parameters for simulation or data for other tasks. If the DATA option is not specified, PROC HPSIMULATE uses the most recently created SAS data set.

[0311] The HPSIMULATE statement may use a second option, as follows:

[0312] DATADIST=(options)

The second option specifies how data is distributed on a distributed computing system. The second option may have a set of options as shown in Table 7, as follows:

TABLE 7

Option	Description
COPYONGENERAL	Make a copy on general.
COPYTONODES	Make a copy of data set to each captain so that each captain has all data. This is the default option.

TABLE 7-continued

Option	Description
ROUNDROBIN	Distribute the data to captains row-wisely according to round-robin rule.
DEFAULT	Distribute the data to captains row-wisely according to first-come-first-serve rule.
INSLICES	Distribute the data to captains in slices.
COLUMNWISE	Distribute the data to captains column-wisely and evenly.
COLUMNWISEBY	Distribute the data to captains column-wisely according to the groups defined in the first row of data: (1) the group ID must be integer; (2) negative ID indicating the corresponding columns need not be distributed; and (3) zero ID indicating the columns must be distributed to all captains.

[0313] The HPSIMULATE procedure may have a module statement as follows:

[0314] MODULE options.

The MODULE statement specifies the TK-extension and parameters for the task to be executed. The MODULE statement may use seven options, as follows:

```
EXT= name
TASK= number
DEPENDENT | CONTROLPARALLEL
TASKPARMV | VARPARM | VAR =( variable-list )
TASKPARMN | NUMBERPARM | TASKPARM = ( number-list )
TASKPARMS | STRINGPARM = ( quoted-string-list )
NAME= name
```

[0315] The EXT option specifies the name of the TK-extension to execute the task. The TK-extension can focus on the task-oriented calculation since the data I/O, communication between client and grid and on grid, and multi-threading are all left to the HPSIMULATE procedure. The TK-extension is dynamically loaded in the procedure. The EXT=option must be specified. The TK-extension must follow some protocol defined in a virtual TK-extension which includes the structures of instance and factory of functions; in other words, any user specified TK-extension is the “child” of that virtual TK-extension which is called TKVRT and introduced later in the Details section.

[0316] The TASK option specifies the task ID to be executed. The TK-extension understands the task ID and executes the right task. By default, TASK=option is set to zero.

[0317] The DEPENDENT|CONTROLPARALLEL option specifies whether the task needs to control communication between threads and between nodes.

[0318] The TASKPARMV|VARPARM|VAR option specifies the variables in the input data set. For example, if the input data set contains parameters for the simulation, the variables are the names of parameters; if the input data set is for post-processing, the variables define the columns of data to be dealt with. The TASKPARMV option should be specified. If an input data set is not needed, a dummy data set and a dummy variable name may be specified.

[0319] The TASKPARMN|NUMBERPARM|TASKPARM option specifies the number parameters for the task. For example, the number of simulations, the random seed to start, the optimization grid.

[0320] The TASKPARMS|STRINGPARM option specifies the string parameters for the task. For example, the output folder, the output file name or prefix and suffix.

[0321] The NAME option specifies a name of the module.

[0322] The HPSIMULATE procedure may include an output statement, as follows:

[0323] OUTPUT OUT=SAS-data-set

The OUTPUT statement creates an output SAS data set as specifies by the following OUT option:

[0324] OUT=SAS-data-set

The OUT option names the output SAS data set containing the task-dependent results which might be simulated statistics or the quantiles.

[0325] The HPSIMULATE procedure may include a performance statement, called PERFORMANCE. The PERFORMANCE statement is a common statement supported in a high performance architecture (HPA) bridge. Only some options used in the HPSIMULATE procedure are listed as follows:

[0326] NODES=number

The NODES option specifies a number of captains. If NODES=0 is specified, the procedure is executed on client side and no distributed computing environment computers are involved.

[0327] NTHREADS=number

The NTHREADS option specifies the number of threads to be used in each computer.

[0328] The HPSIMULATE procedure is based, in part, on the HPLOGISTICS procedure. The framework of the HPLOGISTICS procedure may implement all data input/output, communication between client computers **602** and the distributed computing system **610**, or general and captain nodes of the distributed computing system **610**, and multi-threading details. A framework extended on the framework of the HPLOGISTICS procedure is shown in FIGS. **9-11**. The framework is flexible to support any simple and complex algorithm. In this manner, a client application may plug-in its own tasks, like simulation or estimation. A user's TK-extension should follow some protocol defined in a virtual TK-extension which includes structures of instance and factory of functions. In other words, any user specified TK-extension is a "child" of that virtual TK-extension which is called TKVRT.

[0329] For the virtual TK-extension TKVRT, the user-specified TK-extension should be a “child” of the TKVRT TK-extension. The TKVRT defines the following public structures related to input parameters and output result:

```
struct TKVRT_COLUMN                                     /* Column name element */
{
    int                                         type;
    int                                         namelen;
    char                                       name[TKVRT_MAXNAME];
    tkvrtColumnPtr                           next;
};

struct TKVRT_DATA                                      /* Matrix in memory or
                                                         utility file on disk
                                                         with column names*/
{
    TKBoolean                                QinMemory;
    int64_t                                  nRow;
    int64_t                                  curRow;
    int64_t                                  nColumn;
    tkvrtColumnPtr                          colHead;
    tkvrtColumnPtr                          colTail;
    double                                   *mat;
    tkrecUtFilePtr                           fid;
    TKPoolh                                    Pool;
};

struct TKVRT_PARMS                                    /* Parameters */
{
    long          nCaptains;                  /* is the number of captains */
    long          captainID;                   /* is the current captain ID */
    long          nThreads;                    /* is the number of threads */
    long          threadID;                    /* is the current thread ID*/
    long          task;                        /* is the task id */
    char          taskFlag[5];                /* is the task flag */
    long          nTaskParm;                  /* is the number of input parameters */
    double        *taskParmList;              /* is the list of input number parameters */
    long          nTaskParmStr;               /* is the number of input string parameters */
    char          **taskParmStrList;          /* is the list of input string parameters */
    long          *taskParmStrLenList;         /* is the list of the length of input string parameters */
    long          nInputData;                 /* is the number of input data sets */
    tkvrtDataPtr   inputDataList;             /* is the list of input data sets */
    long          nOutputParm;                /* is the number of output number parameters */
}
```

-continued

int64_t	sOutputParm;	/* is the size of allocated memory for output number parameters */
double	*outputParmList;	/* is the list of output number parameters */
long	nOutputInt64Parm;	/* is the number of output integer parameters */
int64_t	sOutputInt64Parm;	/* is the size of allocated memory for output integer parameters */
int64_t	*outputInt64ParmList;	/* is the list of output integer parameters */
long	nOutputParmStr;	/* is the number of output string parameters */
char	**outputParmStrList;	/* is the list of output string parameters */
long	*outputParmStrLenList;	/* is the list of the length of output string parameters */
long	nOutputData;	/* is the number of output data sets */
tkvrtDataPtr	outputDataList;	/* is the list of output data sets */
TKPoolh	taskPool;	/* is the memory Pool */
TKMemPtr	userPtr;	/* is the pointer to anything else */
TKMemPtr	userPtr1;	/* is the pointer to anything else */
TKMemPtr	userPtr2;	/* is the pointer to anything else */
TKMemPtr	userPtr3;	/* is the pointer to anything else */
TKMemPtr	userPtr4;	/* is the pointer to anything else */

The function Set up Thread Work(.) in tksimt.c may provide details on how the parameter structures are initialized.

[0330] The TKVRT also declares following public functions:

TKStatus	(*ValueGet)	(tkvrtInstPtr, int, TKMemPtr, TKMemSize *);
TKStatus	(*ValueSet)	(tkvrtInstPtr, int, TKMemPtr);
TKStatus	(*DestroyInstance)	(tkvrtInstPtr *);
TKStatus	(*ResetInstance)	(tkvrtInstPtr);
TKStatus	(*Initialize)	(tkvrtInstPtr);
TKStatus	(*Analyze)	(tkvrtInstPtr);
TKStatus	(*Summarize)	(tkvrtInstPtr);
TKStatus	(*GridInitialize)	(tkvrtInstPtr);
TKStatus	(*GridSummarize)	(tkvrtInstPtr, TKMemPtr);

The TKVRT are implemented in tkvrt.h, tkvrtmem.h, tkvrtph, and tkvrt.c. An example of the child of TKVRT is TKSCBP, which are implemented in tkscbp.h, tkscbph.h, and tkscbp.c, and is used to simulate multiple structural change tests' statistics and generate the quantiles for constructing the empirical CDFs.

[0331] Some embodiments may be described using the expression “one embodiment” or “an embodiment” along with their derivatives. These terms mean that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment. Further, some embodiments may be described using the expression “coupled” and “connected” along with their derivatives. These terms are

not necessarily intended as synonyms for each other. For example, some embodiments may be described using the terms “connected” and/or “coupled” to indicate that two or more elements are in direct physical or electrical contact with each other. The term “coupled,” however, may also mean that two or more elements are not in direct contact with each other, but yet still co-operate or interact with each other.

[0332] It is emphasized that the Abstract of the Disclosure is provided to allow a reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein,” respectively. Moreover, the terms “first,” “second,” “third,” and so forth, are used merely as labels, and are not intended to impose numerical requirements on their objects in all situations.

[0333] Some systems may use an open-source framework for storing and analyzing big data in a distributed computing environment. For example, some systems may use Hadoop® for applications in which the simulated functions depend on

given fixed data that are supplied externally to the algorithm, and that these data can be read from distributed file systems, such as Hadoop®. This could apply, for example, if subsets of the data on different nodes correspond to different cases to be simulated. In that case, different nodes can do the simulations for the subcases corresponding to the data that they read locally, without need to pass data across the network. To help make that process work, the system could adopt a map-reduce-like pattern for controlling which nodes do which simulations.

[0334] Some systems may use cloud computing, which can enable ubiquitous, convenient, on-demand network access to a shared pool of configurable computing resources (e.g., networks, servers, storage, applications and services) that can be rapidly provisioned and released with minimal management effort or service provider interaction. Some grid systems may be implemented as a multi-node cluster. Some systems may use a massively parallel processing (MPP) database architecture. Some systems may be used in conjunction with complex analytics (e.g., high-performance analytics, complex business analytics, and/or big data analytics) to solve complex problems quickly.

[0335] What has been described above includes examples of the disclosed architecture. It is, of course, not possible to describe every conceivable combination of components and/or methodologies, but one of ordinary skill in the art may recognize that many further combinations and permutations are possible. Accordingly, the described architecture is intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims.

1. An article of manufacture comprising a non-transitory computer-readable storage medium containing instructions that, when executed, cause a system to:

generate simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution;

simulate statistics for the parameter vectors from the simulated data, each parameter vector represented with a single point in a grid of points;

remove selective points from the grid of points to form a subset of points; and

generate interpolation code to interpolate a statistic of the statistical test on any point.

2. The article of claim 1, the statistics of the statistical test based on parameter vectors to follow a probability distribution of an unknown form.

3. The article of claim 1, the statistics of the statistical test based on parameter vectors to follow a probability distribution of a known form.

4. The article of claim 1, further comprising instructions that, when executed, enable a system to receive a simulated data structure with information for estimated CDF curves of the subset of points.

5. The article of claim 4, further comprising instructions that, when executed, enable a system to generate the interpolation code of a software class of a virtual software class, the interpolation code to include the simulated data structure, index tables for the simulated data structure, and a first interpolation function.

6. The article of claim 5, the first interpolation function arranged to call a second interpolation function comprising an instance of the virtual software class.

7. The article of claim 6, the second interpolation function arranged to interpolate the estimated CDF curve using a monotonic cubic spline interpolation technique.

8. The article of claim 7, the second interpolation function arranged to interpolate the estimated CDF curve using the monotonic cubic spline interpolation technique with a beta transformation.

9. The article of claim 8, the beta transformation to comprise a transform performed in accordance with a normalized incomplete beta function, the normalized incomplete beta function comprising a nonnegative function whose derivative is positive.

10. The article of claim 1, further comprising instructions that, when executed, enable a system to:

receive a simulated data structure having information for a set of fitted CDF curves for the grid of points, and generate the interpolation code from the simulated data structure.

11. The article of claim 10, further comprising instructions that, when executed, enable a system to create a computational representation arranged to generate an approximate probability distribution for each point in the grid of points from the simulated statistics, the computational representation to include the interpolation code, the computational representation to comprise a set of H files, data C files, function C files, or a build script.

12. An apparatus, comprising:

processor circuitry;

a simulated data component for execution by the processor circuitry to generate simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution;

a statistic simulator component for execution by the processor circuitry to simulate statistics for the parameter vectors from the simulated data, each parameter vector represented with a single point in a grid of points; and

a code generator component for execution by the processor circuitry to remove selective points from the grid of points to form a subset of points, and generate interpolation code to interpolate a statistic of the statistical test on any point.

13. The apparatus of claim 12, the statistics of the statistical test based on parameter vectors to follow a probability distribution of an unknown form.

14. The apparatus of claim 12, the statistics of the statistical test based on parameter vectors to follow a probability distribution of a known form.

15. The apparatus of claim 12, the code generator component to receive a simulated data structure with information for estimated CDF curves of the subset of points.

16. The apparatus of claim 15, the code generator component to generate the interpolation code of a software class of a virtual software class, the interpolation code to include the simulated data structure, index tables for the simulated data structure, and a first interpolation function.

17. The apparatus of claim 16, the first interpolation function arranged to call a second interpolation function comprising an instance of the virtual software class.

18. The apparatus of claim 17, the second interpolation function arranged to interpolate the estimated CDF curve using a monotonic cubic spline interpolation technique.

19. The apparatus of claim **18**, the second interpolation function arranged to interpolate the estimated CDF curve using the monotonic cubic spline interpolation technique with a beta transformation.

20. The apparatus of claim **19**, the beta transformation to comprise a transform performed in accordance with a normalized incomplete beta function, the normalized incomplete beta function comprising a nonnegative function whose derivative is completely positive.

21. The apparatus of claim **12**, the code generator component to receive a simulated data structure having information for a set of fitted CDF curves for the grid of points, and generate the interpolation code from the simulated data structure.

22. The apparatus of claim **21**, the code generator component to create a computational representation arranged to generate an approximate probability distribution for each point in the grid of points from the simulated statistics, the computational representation to include the interpolation code, the computational representation to comprise a set of H files, data C files, function C files, or a build script.

23. A computer-implemented method, comprising:
generating simulated data for a statistical test, statistics of the statistical test based on parameter vectors to follow a probability distribution;
simulating statistics for the parameter vectors from the simulated data, each parameter vector represented with a single point in a grid of points;
removing selective points from the grid of points to form a subset of points; and
generating, by circuitry, interpolation code to interpolate a statistic of the statistical test on any point.

24. The computer-implemented method of claim **23**, the statistics of the statistical test based on parameter vectors to follow a probability distribution of an unknown form.

25. The computer-implemented method of claim **23**, the statistics of the statistical test based on parameter vectors to follow a probability distribution of a known form.

26. The computer-implemented method of claim **23**, comprising receiving a simulated data structure with information for estimated CDF curves of the subset of points.

27. The computer-implemented method of claim **26**, comprising generating the interpolation code of a software class of a virtual software class, the interpolation code to include the simulated data structure, index tables for the simulated data structure, and a first interpolation function.

28. The computer-implemented method of claim **27**, the first interpolation function arranged to call a second interpolation function comprising an instance of the virtual software class.

29. The computer-implemented method of claim **28**, the second interpolation function arranged to interpolate the estimated CDF curve using a monotonic cubic spline interpolation technique.

30. The computer-implemented method of claim **29**, the second interpolation function arranged to interpolate the estimated CDF curve using the monotonic cubic spline interpolation technique with a beta transformation.

31. The computer-implemented method of claim **30**, the beta transformation to comprise a transform performed in accordance with a normalized incomplete beta function, the normalized incomplete beta function comprising a nonnegative function whose derivative is completely positive.

32. The computer-implemented method of claim **23**, comprising:
receiving a simulated data structure having information for a set of fitted CDF curves for the grid of points; and
generating the interpolation code from the simulated data structure.

33. The computer-implemented method of claim **23**, comprising creating a computational representation arranged to generate an approximate probability distribution for each point in the grid of points from the simulated statistics, the computational representation to include the interpolation code, the computational representation to comprise a set of H files, data C files, function C files, or a build script.

* * * * *