




(86) Date de dépôt PCT/PCT Filing Date: 2016/01/22
(87) Date publication PCT/PCT Publication Date: 2016/07/28
(85) Entrée phase nationale/National Entry: 2017/07/21
(86) N° demande PCT/PCT Application No.: JP 2016/051900
(87) N° publication PCT/PCT Publication No.: 2016/117697
(30) Priorité/Priority: 2015/01/23 (JP2015-011811)

(51) Cl.Int./Int.Cl. *H04L 12/70* (2013.01),
G06F 9/46 (2006.01), *H04L 12/717* (2013.01)
(71) Demandeur/Applicant:
NEC CORPORATION, JP
(72) Inventeurs/Inventors:
GOKURAKUJI, JUNICHI, JP;
OOHIRA, MAYO, JP;
SHINOZAWA, HIROKAZU, JP
(74) Agent: SMART & BIGGAR

(54) Titre : METHODE DE GESTION ET D'ORCHESTRATION DE VIRTUALISATION DE FONCTIONS RESEAU ET
SYSTEME DE GESTION ET ORCHESTRATION DE VIRTUALISATION DE FONCTIONS RESEAU, ET
PROGRAMME
(54) Title: NETWORK FUNCTIONS VIRTUALIZATION MANAGEMENT AND ORCHESTRATION METHOD, NETWORK
FUNCTIONS VIRTUALIZATION MANAGEMENT AND ORCHESTRATION SYSTEM, AND PROGRAM

FIG. 11



(57) **Abrégé/Abstract:**

The present invention makes it possible to distinguish, in terms of management, instances generated on the basis of a descriptor. In the present invention, a VNF descriptor (VNFD) comprises an information element with which it is possible to distinguish, by name, instances generated on the basis of the VNFD. The information element includes a virtual machine (VM) name information element, which describes a naming convention related to the VM.



ABSTRACT

In the present invention, distinction of an instance created based on a descriptor is made possible, in terms of management. An information element that allows an instance created based on a VNF descriptor (VNFD) to be distinguished by name is provided in the VNFD. 5 The information element includes an information element of a VM name that describes a naming rule for a virtual machine (VM).

DESCRIPTION

TITLE

NETWORK FUNCTIONS VIRTUALIZATION MANAGEMENT AND
ORCHESTRATION METHOD, NETWORK FUNCTIONS
5 VIRTUALIZATION MANAGEMENT AND ORCHESTRATION SYSTEM,
AND PROGRAM

FIELD

[0001]

(CROSS-REFERENCE TO RELATED APPLICATIONS)

10 The present invention is based upon and claims the benefit of the
priority of Japanese Patent Application No. 2015-011811 (filed on
January 23, 2015), the disclosure of which is incorporated herein in its
entirety by reference.

The present invention relates to a network management and
15 orchestration technology. More specifically, the invention relates to a
method, a system, and a program suitable for being applied to network
functions virtualization (Network Functions Virtualization)
management and orchestration.

BACKGROUND

20 [0002]

There is known NFV (Network Functions Virtualization) or the
like configured to implement a network apparatus and so on in software,
using a virtualization technology that virtualizes hardware resources
(computing, storage, network functions and so on) of a server by a
25 virtual machine (VM: Virtual Machine) implemented on a virtualization
layer (Virtualization Layer) such as a hypervisor (HyperVisor) on the
server. The NFV is implemented, based on a MANO (Management &
Orchestration) architecture, for example. FIG. 1 is a diagram cited
from Figure 5.1 (The NFV-MANO architectural framework with
30 reference points) on page 23 of Non-Patent Literature 1.

[0003]

Referring to FIG. 1, VNF (Virtualized Network Function)
corresponds to an application or the like running on a virtual machine
(VM) on a server, and implements a network function in software. As

VNF, MME (Mobility Management Entity), S-GW (Serving Gateway), P-GW (PDN Gateway), and so forth on EPC (Evolved Packet Core) that is a core network of LTE (Long Term Evolution) network may be implemented by software (virtual machine). In the example of FIG. 1,
5 a management function referred to as EM (Element Manager: element management) is provided for each VNF, for example.

[0004]

NFVI (Network Function Virtualization Infrastructure) that constitutes an implementation infrastructure of each VNF is an
10 infrastructure that allows hardware resources of a physical machine (server) such as computing, storage, and network functions to be flexibly handled as virtualized hardware resources such as virtualized computing, virtualized storage, virtualized network, and so on which have been virtualized using a virtualization layer such as a hypervisor.

15 [0005]

NFV MANO (Management & Orchestration) includes an NFV-Orchestrator (NFVO), a VNF-manager (VNFM), and a Virtualized Infrastructure Manager (VIM).

[0006]

20 The NFV-Orchestrator (NFVO) performs orchestration of NFVI resources and lifecycle management (such as Instantiation, Scaling, Termination, and Update of each NS instance) of NSs (Network Services). The NFV-Orchestrator also performs management of an NS catalog (NSD/VLD/VNFFGD) and a VNF catalog (VNFD/VM
25 images/manifest files, etc.), and includes a repository of NS instances and a repository of the NFVI resources.

[0007]

The VNF-Manager (VNFM) performs VNF lifecycle management (such as instantiation, update, query, scaling, termination, etc.) and
30 event notification.

[0008]

The virtualized Infrastructure Manager (VIM) performs control of the NFVI (such as computing, storage, network resource management, fault monitoring of the NFVI being the implementation infrastructure of

the NFV, and monitoring of resource information) through the virtualization layer.

[0009]

OSS (Operations Support Systems) are a generic term for systems
5 (such as apparatuses, software, and schemes) necessary for telecommunications carriers (carriers) to construct and manage services, for example. BSS (Business Support systems) are a generic term for information systems (such as apparatuses, software, and schemes) to be used for accounting for and charging of a usage charge and handling of a
10 customer by the telecommunications carriers.

[0010]

The NS Catalogue (NS catalog: an NS Catalogue in FIG. 1) represents repository of network Services. NS Catalogue supports creation and management of NS deployment templates (Network Service
15 Descriptor (NSD), Virtual Link Descriptor (VLD), and VNF Forwarding Graph Descriptor (VNFFGD)).

[0011]

The VNF catalog (VNF catalog: a VNF Catalogue in FIG. 1) represents repository of VNF packages. The VNF catalog supports
20 creation and management of each VNF package of a VNF Descriptor (VNFD), a software image, a manifest file and so forth.

[0012]

The NFV instance repository (NFV instance Repository: NFV Instances in FIG. 1) holds information of all VNF instances and
25 Network Service instances. Each VNF instance and each NS instance are represented respectively by a VNF record and by an NS record. Those records are updated during a lifecycle of the respective instances, reflecting changes resulting from execution of NS lifecycle management operations and/or VNF lifecycle management operations.

30 [0013]

The NFVI resources repository (NFVI Resources Repository: NFVI Resources in FIG. 1) holds information on available (available)/reserved (reserved)/allocated (allocated) resources as extracted by the VIM across operator's infrastructure domains.

[0014]

Referring to FIG. 1, a reference point Os-Nfvo is a reference point between the OSS (Operation Service Systems)/BSS (Business Service Systems) and the NFVO, and is used for forwarding a lifecycle management request of each network service, a VNF lifecycle management request, state information associated with NFV, exchange of policy management information, and so on.

[0015]

A reference point Vnfm-Vi is used for a resource allocation request from the VNFM and exchange of virtualized resource configuration and state information.

[0016]

A reference point Ve-Vnfm-em is used between the EM and the VNFM for VNF instantiation, VNF instance retrieval, VNF instance update, VNF instance termination, VNF instance scaling-out/in, VNF instance scaling-up/down, forwarding of configuration and events from the EM to the VNFM, and notification of configuration and events regarding the VNF from the VNFM to the VNF, and so on.

[0017]

A reference point Ve-Vnfm-Vnf is used between the VNF and the VNFM for VNF instantiation, VNF instance retrieval, VNF instance update, VNF instance termination, VNF instance scaling-out/in, VNF instance scaling-up/down, forwarding of configuration and events from the VNF to the VNFM, and notification of configuration and events regarding the VNF from the VNFM to the VNF, and so on.

[0018]

A reference point Nf-Vi is used for VM allocation with indication of compute/storage resource, update of VM resources allocation, VM migration, VM termination, creation and removal of connection between VMs, etc., virtual resources allocation in response to a resource allocation request, forwarding of virtual resource state information, exchange of configuration and state information of hardware resources, and so on.

[0019]

A reference point Vn-Nf indicates an execution environment to be provided to the VNF by the NFVI.

[0020]

A reference point Nfvo-Vnfm is used for a resource-related request (of validation, reservation (reservation), or allocation, etc.) by the VNF-manager (VNFM) and forwarding of configuration information to the VNFM, and collection of VNF state information.

[0021]

A reference point Nfvo-Vi is used for a resource reservation request and a resource allocation request from the NFVO, and exchange of virtual resource configuration and state information (for details, reference may be made to Non-Patent Literature 1).

[0022]

FIG. 2 is cited from Figure 6.2 (Information elements in different context) on page 40 of Non-Patent Literature 1. An instantiation input parameter is input.

[0023]

Referring to FIG. 2, a network service descriptor (Network Service Descriptor: NSD) is a network service deployment template for referencing other descriptors that describe components constituting a network service (NS).

[0024]

A VNF descriptor (VNF Descriptor: VNFD) is a deployment template that describes a VNF in terms of deployment and operational behavior requirements.

[0025]

The VNFD is mainly used by the VNFM in VNF instantiation (instantiation) and VNF instance lifecycle management. The VNFD is used for a network service and management and orchestration of virtualized resources on the NFVI (automation of deployment/setting/management of a computer system/middleware/service) by the NFVO. The VNFD also contains connectivity, interface and KPIs requirements that can be used by NFV-MANO functional blocks to establish appropriate Virtual Links

within the NFVI between its VNFC instances, or between a VNF instance and the endpoint interface to the other network functions.

[0026]

A VNF Forwarding Graph Descriptor (VNFFGD) is a deployment
5 template that describes a network service topology or a part of the topology by referring to the VNFs, PNFs, and Virtual Links connecting those VNFs and PNFs.

[0027]

A virtual link descriptor (Virtual Link Descriptor: VLD) is a
10 deployment template that describes resource requirements necessary for links between the VNFs, between the PNFs, and between NS endpoints (endpoints) that can be used by the NFVI.

[0028]

A physical network function descriptor (Physical Network
15 Function Descriptor: PNFD) describes connectivity (connectivity), interface and KPIs requirements of a virtual link, for a function of an attached physical network. The PNFD is needed when a physical device is incorporated into an NS, and facilitates addition of a network.

[0029]

20 The NSD, the VNFFGD, and the VLD are included in the NS catalog (Network Service Catalogue in FIG. 2), and the VNFD is included in the VNF catalogue (VNF Catalogue in FIG. 2) as the VNF package.

[0030]

25 An NS or a VNF instantiation operation is performed from the OSS/BSS or the VNFM to the NFVO. As a result of the instantiation operation, each record indicating a newly created instance is created. Each record to be created based on information to be given by each descriptor and additional runtime information related to a component
30 instance provides data for modeling a network service (NS) instance state, for example.

[0031]

As types of the instance records (of NFV Instances) to be created, there may be listed the following types, for example:

- Network Service Record (NSR);
- VNFFG Record (VNFFGR);
- Virtual Link Record (VLR);
- VNF (Virtualized Network Function) Record (VNFR); and
- 5 - PNF (Physical Network Function) Record (PNFR).

[0032]

Information elements of the NSR, the VNFR, the VNFFGR, and the VVLR provide a data item group necessary for modeling states of an NS instance, a VNF instance, a VNFFG instance, and a VL instance.

10 [0033]

The PNF Record (PNFR) indicates an instance related to a pre-existing PNF which is part of an NS and contains a set of runtime attributes regarding PNF information (including connectivity relevant to the NFVO). An overview of each element of the NFV is summarized
15 as lists in Tables 1 and 2.

[0034]

[Table 1]

Functional Entity	Description
OSS/BSS	Comprehensively performs operations/business support. A plurality of EMSs and Orchestrator are deployed on a low-order layer of OSS/BSS.
Orchestrator	- Orchestration across a plurality of VIMs - Management of NS(Network Service) deployment templates and VNF packages - Management of instantiation and lifecycle management of NSs - Management of instantiation of VNFM - Management of VNF instantiation in coordination with VNFM - Validation and authorization of NFVI resource request from VNFM - Management of integrity and visibility of NS instances through their lifecycle - Management of relationship between NS instances and VNF instances, using NFV instances Repository - Topology management of NS instances - Automated management of NS instances
VNF-Manager	Performs VNF lifecycle management * and event notification management. * Instantiation, Auto-Scaling, Auto-Healing, Update, and so on
Virtualized Infrastructure Manager (VIM)	Performs resource management and control of NFV infrastructure as follows: - Management of computing, storage, and network resources - Resource allocation in response to a request - Monitoring of a fault state of NFV Infrastructure - Monitoring of resource information of NFV Infrastructure

[0035]

[Table 2]

Functional Entity	Description
Service VND and Infrastructure Description	Defines information templates that become necessary for deploying each Network Service and each VNF - NSD: a template that describes requirements and constraint conditions necessary for deployment of the NS - VLD: describes resource requirements of a logical link connecting VNFs or connecting PNFs that constitute NS - VNFGD: a template that describes a logical topology for and assignment of NS - VNFD: a template that describes requirements and constraint conditions necessary for deploying VNF - PNFD: describes, for a physical network function, connectivity, external interface, and KPIs requirements of aVL.
NS Catalogue	- Repository of NSs - Management of NS deployment templates (NSD, VLD, VNFGD)
VNF Catalogue	- Describes repository of each VNF. - Management of each VNF package (VNFD, software images, manifest files, etc.)
NFV Instances Repository	- Holds instance information of all the VNFs and all the NSs. - Information on each instance is described in Record. - Record is updated according to lifecycle of each instance.
NFVI Resources Repository	- Holds information of NFVI resources (NFVI resources as abstracted by VIM across operator's Infrastructure Domains) that are available/reserved/allocated, for abstraction
VNF	Refers to a virtualized Network Function and refers to a VM (e.g., MME, SGW, PGW or the like) in which an EPC application is installed, being configured with VNF.
EMS	Performs management of FCAPS (FCAPS: Fault, Configuration, Accounting, Performance and Security) of VNF.
NFVI	A resource infrastructure in which VNF is executed. Comprises computing, a storage, and a network. Physical resources are abstracted by hypervisor and abstracted resources are managed and controlled by VIM and are provided to VNF.

CITATION LIST

NON-PATENT LITERATURE

[0036]

NON-PATENT LITERATURE 1

- 5 ETSI GS NFV-MAN 001 V1.1.1 (2014-12) Network Functions
Virtualisation (NFV); Management and Orchestration
http://www.etsi.org/deliver/etsi_gs/NFV-MAN/001_099/001/01.01.01_60/gs_NFV-MAN001v010101p.pdf

SUMMARY

10 TECHNICAL PROBLEM

[0037]

An analysis by the inventor of the present invention will be given below.

[0038]

- 15 An example of a relationship among VNF, VNFCs (VNF
Components) and VDU (Virtualization Deployment Unit) will be
described, with reference to FIG. 3. FIG. 3 schematically illustrates
an example where VNFC is set for each logical interface in a VNF
obtained by virtualizing an S-GW (Serving gateway). Each VDU is an
20 entity used for an information model configured to support description
of partial or whole deployment and operational behaviors of the VNF.
VNFI configured to provide an implementation infrastructure of the
VNF includes a virtual computing, a virtual storage, and a virtual
network, each virtualized on a virtualization layer such as a hypervisor.
25 There is provided a virtual machine on a virtualization layer (where the
virtual machine includes a virtual CPU (Central Processing Unit), a
virtual memory, a virtual storage, and a guest OS (Operating System)),
with an application being executed on the guest OS. Compute, Storage,
and Network below the virtualization layer schematically represent
30 hardware resources such as a CPU, a storage, and a network interface
controller (Network Interface Controller: NIC). Vn-Nf represents an
execution environment to be provided to the VNF by the NFVI.

[0039]

In FIG. 3, where SGW is constituted by VNF, VNFC is configured

for each logical interface, logical interfaces S11, Gx, and S5/S8-C with respect to C-Plane (Control Plane) are collectively defined as one VDU (VM), and logical interfaces S1U, S5/S8-U, and S12 with respect to U-Plane are collectively defined as one VDU (VM). C in S5/S8-C represents a control plane (Control Plane). U in the S1U and S5/S8-U represents a user plane (User-plane).

[0040]

In EPC, S11 is a control plane interface between MME and SGW, S5/S8 is a user plane interface between SGW and PGW, S1U is an interface between eNodeB (evolved NodeB) and Core Network, Gx is an interface between PGW and PCRF (Policy and Charging Rules Function), S11 is an interface between MME and S-GW, S12 is an interface between UTRAN (Universal Terrestrial Radio Access Network) and S-GW.

[0041]

When congestion of control signals occurs, VMs corresponding to S11, Gx, and S5/S8-C (in which C represents a control plane (Control Plane)), for example, are added (increased) (Scaled-out).

[0042]

When congestion of data signals occurs, a VM corresponding to S1U, and S5/S8-U (in which U represents a user plane (User-Plane)) are added (increased) (Scaled-out).

[0043]

FIG. 4 is a diagram illustrating a logical relationship among respective descriptors (cited from FIG. 6.4 on page 60 of Non-Patent Literature 1). FIG. 4 illustrates relationships between internal virtual links (internal Virtual Links) and external virtual links (external Virtual Links). FIG. 4 also illustrates relationships of connection points (Connection Points) among VNFs, VNFCs, and VLS (Virtual Links) in a network service (NS).

[0044]

FIG. 5 is a diagram schematically illustrating a structure (hierarchical structure, or a tree structure) of a VNF descriptor (VNFD) in Non-Patent Literature 1 with respect to a standard specification of NFV-MANO (reference may be made to Non-Patent Literature 1). FIG.

6 is a diagram obtained by citing 6.3.1.1 (vnfd base information elements) on page 44 of Non-Patent Literature 1, and is a diagram illustrating basic information elements of the VNF descriptor (VNFD) that is the deployment template describing a VNF in terms of deployment and operational behavior requirements (requirements).
[0045]

An entry (element) whose type is a leaf (Leaf) in FIG. 6 and so on designates a leaf (end node) in a template of a tree structure (hierarchical structure), and indicates an element including no other element. Generally, the leaf element is an empty element or a text. Element (Element Tree) includes a child node (having an ID).
[0046]

Regarding VNFD that is a root (root) element of the template, the there are defined on the same layer as VNFD following information items that define requirements and constraint conditions for VNF:
VDU (Virtualized Deployment Unit);
virtual link (Virtual Link) (0 to N);
connection points (Connection Points) (1 to N); and
deployment flavor (Deployment Flavor) (1 to N), where N is an integer not less than 1.
[0047]

FIG. 7(A) is a diagram illustrating VDU base elements (vdu base elements) defined in a form of a table (6.3.1.2.1 in Non-Patent Literature 1). VDU includes one or more VNFCs as child nodes, as information defining requirements and constraint conditions for the VDU constituting VNF. Information elements of VNFC are illustrated in FIG. 7(B) (reference may be made to 6.3.1.2.1.1 in Non-Patent Literature 1). VNFC includes one or more connection points (Connection point) as leaf elements. Information elements of connection point (Connection point) are illustrated in FIG. 7(C) (reference may be made to 6.3.1.2.1.2 in Non-Patent Literature 1).
[0048]

For VDU, requirements and constraint conditions for various resources to be used by VDU (VDU information on CPUs, virtual

switches, security, hypervisor, PCIe (PCI express), reliability and availability (reliability and availability), and storage (see FIG. 8(A): reference may be made to 6.3.1.2.10 in Non-Patent Literature 1), network interface, and so on, for example) are defined. As illustrated
5 in FIG. 9(A), the template (descriptor) of the storage includes a storage requirement (storage requirement), an rdma (Remote Direct Memory Access)-support-bandwidth, and so on, as leaf elements. Herein, information elements of the storage are illustrated, as an example. With respect to information elements such as CPUs, virtual switches,
10 security, hypervisor, PCIe (PCE express), and reliability and availability, Non-Patent Literature 1 may be referred to as necessary.
[0049]

Templates for virtual link (Virtual Link), connection point (Connection Point), deployment flavor (Deployment Flavor), and
15 Constituent VDU in the VNF descriptor (VNFD) in FIG. 5 are respectively illustrated in FIG. 8(B), FIG. 8(C), FIG. 9(A), and FIG. 9(B). Regarding the virtual link (Virtual Link), connection point (Connection Point), deployment flavor (Deployment Flavor), and Constituent VDU, reference may be made respectively to 6.3.1.3. in
20 Non-Patent Literature 1, 6.3.1.4 in Non-Patent Literature 1, 6.3.1.5 in Non-Patent Literature 1, and 6.3.1.5.1 in Non-Patent Literature 1.
[0050]

In carrier's operations using a dedicated hardware-based network apparatus (Network Appliance), name mapping and management may be
25 performed for each hardware apparatus so that the following data, for example, may be immediately determined, in order to streamline operation and management and to identify a corresponding portion of a fault at a time of the fault:

- which station house (building);
- 30 - communication node; and
- function.

[0051]

To take an example, a name "Osaka SGW001-U-Plane001" assigned to a hardware apparatus of a gateway, a network apparatus, or

the like indicates a U-Plane (User-Plane) function "001" of a service gateway (SGW) "SGW001" of "Osaka building".

[0052]

There is a similar need for an NFV architecture as well. It is important to manage which type of VNF/VNFC (VNF Component) instance (VM: Virtual Machine) is running on which hardware that is separated from software by virtualization (findings by the inventors of the present invention).

[0053]

In the standard specification for NFV described with reference to FIG. 6 and so on, for example, with respect to VNF descriptor (VNFD), VDU, and VNFC, an ID can be given for each VNFD, for each VDU, and for each VNFC, as illustrated in FIG. 6, FIG. 7(A), and FIG. 7(B), respectively.

[0054]

However, in terms of the standard specification for NFV, a name (VM Name) cannot be given for each VM (instance). In VNF descriptor (VNFD) according to the standard specification for NFV described with reference to FIG. 6 and so on, for example, it is possible to incorporate up to the following:

- VNF ID, such as "SGW", may be given for VNF; and
- VNFC ID may be given as VNFC.

[0055]

However, which node of SGWs or which instance of a GWU (gateway unit) cannot be specified (according to findings by the inventors of the present invention).

[0056]

With respect to the VNF descriptor in the above-mentioned standard specification, when a plurality of virtual machines (VMs) are generated at a time of addition (creation) of virtual machines VM on a server for auto scaling (scaling-out), for example, a same VNFC ID is given to the plurality of virtual machines (VMs), thus leading to a situation where distinction among instances cannot be made, in terms of management (findings by the inventors of the present invention).

[0057]

Accordingly, the present invention has been devised in view of the above-mentioned problem, and it is an object of the present invention to provide a network functions virtualization management and orchestration method, a network functions virtualization management and orchestration system, and a program that allow distinction of an instance created based on a descriptor, in terms of management.

SOLUTION TO PROBLEM

[0058]

10 According to one aspect of the present invention, there is provided a method comprising: a step of receiving information of a template from a storage unit; and a step of creating an instance based on the information of the template, wherein an information element that allows the instance to be distinguished by name is provided in the
15 template that is stored in the storage unit. The information element that allows the instance to be distinguished by name includes an information element that gives a naming rule for a name of the instance. According to the present invention, there is provided a network functions virtualization (NFV) management and orchestration method
20 comprising: providing, in a VNF (Virtualized Network Function) descriptor (VNFD), for example, an information element that gives a naming rule for a name of an instance, to allow an instance that is created based on information of the VNFD to be distinguished by name.
[0059]

25 According to another aspect of the present invention, there is provided a system including input means that receives information of a template from a storage unit; and creation means that creates an instance based on the information of the template, wherein the template includes an information element that allows an instance created based
30 on the information of the template to be distinguished by name. The information element that allows an instance to be distinguished by name includes an information element that gives a naming rule for the name of the instance. According to the present invention, there is provided a system (NFV-MANO) including means that receives, for example, a

VNF (Virtualized Network Function) descriptor (VNFD) with an information element that gives a naming rule for a name of an instance and means that creates an instance based on information of the VNFD.

[0060]

5 According to yet another aspect of the present invention, there is provided a program causing a computer to execute

 a processing of receiving, from a storage unit, a template including an information element that allows an instance created based on information of the received template to be distinguished by name;

10 and

 a processing of creating the instance based on the information of the received template.

 The information element that allows an instance to be distinguished by name includes an information element that gives a naming rule for the name of the instance. According to the present invention, there is provided a program causing a computer to execute a processing of receiving, for example, a VNF (Virtualized Network Function) descriptor (VNFD) with an information element that gives a naming rule for a name of an instance and a processing of creating the instance based on information of the VNFD. According to the present invention, there is provided a non-transitory computer readable recording medium, such as a magnetic disk or a semiconductor memory storing the computer program therein.

ADVANTAGEOUS EFFECTS OF INVENTION

25 [0061]

 According to the present invention, distinction of an instance created based on the template (descriptor) is made possible, in terms of management.

BRIEF DESCRIPTION OF THE DRAWINGS

30 [0062]

 [FIG. 1]

 FIG. 1 is a diagram illustrating NFV-MANO of an NFV architecture (cited from FIG. 5.1 in Non-Patent Literature 1).

 [FIG. 2]

FIG. 2 is a diagram illustrating templates and instance records according to Non-Patent Literature (cited from FIG. 6.2 in Non-Patent Literature 1).

[FIG. 3]

5 FIG. 3 is a diagram illustrating a relationship among a VNF, VNFCs, and VDUs.

[FIG. 4]

FIG. 4 is a diagram schematically illustrating a logical relationship among descriptors (cited from FIG. 6.4 in Non-Patent Literature 1).

10 [FIG. 5]

FIG. 5 is a diagram schematically illustrating a structure of a VNF descriptor (vnfd).

[FIG. 6]

FIG. 6 is a diagram illustrating information elements in a table of the
15 VNF descriptor (vnfd) (cited from 6.3.1.1 in Non-Patent Literature 1).

[FIG. 7]

FIG. 7(A) is a diagram illustrating information elements of VDU, FIG. 7(B) is a diagram illustrating information elements of VNFC, and FIG. 7(C) is a diagram illustrating information elements of Connection point
20 (respectively cited from 6.3.1.2.1, 6.3.1.2.1.1, and 6.3.1.2.1.2 in Non-Patent Literature 1).

[FIG. 8]

FIG. 8(A) is a diagram illustrating VDU information elements related to storage, FIG. 8(B) is a diagram illustrating information elements of
25 each VNF internal Virtual Link, and FIG. 8(C) is a diagram illustrating information elements of Connection points (respectively cited from 6.3.1.2.10 in Non-Patent Literature 1).

[FIG. 9]

FIG. 9(A) is a diagram illustrating information elements of deployment
30 flavor (Deployment Flavor) and FIG. 9(B) is a diagram illustrating information elements of each constituent VDU (respectively cited from 6.3.1.5 and 6.3.1.5.1 in Non-Patent Literature 1).

[FIG. 10]

FIG. 10 is a diagram illustrating information elements of a VNF

descriptor (vnfd) in an exemplary embodiment.

[FIG. 11]

FIG. 11 is a diagram schematically illustrating a structure of the VNF descriptor (vnfd) in the exemplary embodiment.

5 [FIG. 12]

FIG. 12 is a diagram illustrating an example of scaling-out of VMs in the exemplary embodiment.

[FIG. 13]

FIG. 13 is a diagram illustrating NFV-MANO configured to process the
10 descriptor in the exemplary embodiment.

MODES

[0063]

According to one of some exemplary embodiments, a VNF (Virtualized Network Function) descriptor (VNFD) includes an entry
15 (information element) of a VM name that describes a naming rule for a virtual machine (VM) on the same layer (immediately below a VNFD root) as information elements of an identifier (ID) and a VDU (Virtualized Deployment Unit), for example. An instance (virtual machine (VM) or the like) that is created based on the descriptor may be
20 distinguished by name. This enables distinction among instances (VMs or the like) in terms of management.

[0064]

As described above, in the standard specification for NFV, with respect to VNFD, VDU, and VNFC, an ID can be given for VNFD, for
25 VDU, and for VNFC, as illustrated in FIG. 6, FIG. 7(A), and FIG. 7(B), respectively. However, a name cannot be given for VM (instance), for example, as a result of which, when congestion (processing congestion due to a load that has exceeded capability of VM), a fault, or the like occurs and scaling-out (such as addition of a VM) is performed, for
30 example, distinction cannot be made among of VMs (instances), in terms of management. A similar problem may occur in the case of VNF or VDU as well.

[0065]

In order to solve this type of problem, according to the present

exemplary embodiment, as illustrated in FIG. 10, for example, an information element (VM name) that gives a naming rule for a VM name is provided as a type of leaf (Leaf), for example, on the same layer as entries such as an identifier (ID (identifier)), a vendor (Vendor), a version (Version), and a VDU located on a layer immediately below a root, for example, in a VDN descriptor (VNFD).

[0066]

FIG. 11 is a diagram illustrating a structure of a VNF descriptor in the exemplary embodiment illustrated in FIG. 10 and corresponds to FIG. 5 described above.

[0067]

Referring to FIG. 11, the VNF descriptor (vnfd) includes information elements (entries) of one to N (N being an integer equal to 1 or more) virtual machine names (VM names) on the same layer as a vdu, a Virtual Link, Connection Points, and a Deployment Flavor. These information elements (VM names) are connected as end nodes (Leaves) in a structure of the VNF descriptor. NNFV-MANO (see FIG. 2) generates each VM name based on the naming rule of the VM name for the VM in the descriptor, using an instantiation operation.

[0068]

FIG. 12 is a diagram illustrating a specific example of the present exemplary embodiment. FIG. 12 illustrates respective names (a physical server name, a VDU name, and a logical node name) of a physical machine PM (Physical Machine), a virtual machine VM (Virtual Machine), and an application (APL) on the virtual machine, corresponding to servers before and after scaling-out (where two servers are added). The following describes a case where NFV-MANO executes auto scale-out, as a result of detection of a fault, congestion, or the like, in a server apparatus having

a physical server name: PM01,
a VDU name: OsakaSGW001 U-Plane001, and
a logical node name: OsakaSGW001 U-Plane001.

[0069]

One of the two servers to be added is one having a physical server

name: PM02 and a VM name (VDU name) of OsakaSGW001 U-Plane002.
The other of the two servers to be added is the one having
a physical server name : PM03 and
a VM name (VDU name) of OsakaSGW001 U-Plane003.

5 These VM names are each created as an instance name (VDU
name) by instantiation by NFV-MANO according to the description of
the information element of the VM name (VM names) that has defined
the naming rule for the VM.

[0070]

10 To take an example, the naming rule for the VM set in the
information element of the VM name (VM name) of the VNF descriptor
is set to "OsakaSGW001 U-Plane" && "++integer-value". Then, the
initial value of the integer-value is set to 0. At a time of instantiation,
for example, the "integer-value" following the character string
15 (character string) of the "Osaka SGW001 U-Plane" is auto-incremented
(automatically incremented by 1) due to "++integer-value" in the rule, a
resulting integer value is converted to a character string of three
decimal digits (such as "002"), and the character string of "002" is
concatenated to the character string of "OsakaSGW001 U-Plane) using
20 an operator "&&", thereby generating the VDU name of "OsakaSGW001
U-Plane002" or the like.

[0071]

 Therefore, the names of "OsakaSGW001 U-Plane002" and
"OsakaSGW001 U-Plane003" are respectively assigned to second and
25 third, VMs added by auto scaling (auto-scale V-MANO). That is,
according this exemplary embodiment, distinction can be made, in terms
of management.

[0072]

 An operator ++ in the "++integer-value" of the instruction rule is
30 given as the simplest example among examples of naming rule for the
auto-increment (in which on syntax of the naming rule is arbitrary).
Naturally, the present invention is not limited to such a naming rule.
To take an example, in place of the "OsakaSGW001 U-Plane"
"++integer-value", an instruction of inserting a text code of a "building

name" in place of a field of "Osaka" as an argument (variable) of the naming rule may be embedded. When orchestration is performed, NFVO may select a building or the like with sufficient resources (resources), for example. In that case, it may be so arranged that an instruction of automatically inserting "building name" is specified as the naming rule, and NFVO gives VM name (VDU name) by referring to repository information of NFVI and VNF that NFVO manages at the time of the orchestration.

[0073]

FIG. 13 is a diagram illustrating NFV-MANO (in FIG. 2) configured to execute a process of loading the VNF descriptor (vnfd) in this exemplary embodiment described with reference to FIGs. 10 and 11 and generating an NFV instance. The process may be implemented in NFVO, VNFN, or the like of NFV-MANO as a program. In this case, a processor (CPU (Central Processing Unit)), not shown, which constitutes NFVO, VNFN, or the like of the NFV-MANO loads the program stored in a semiconductor memory, an HDD (Hard Disk Drive), or the like into a main memory, and executes the program, thereby implementing a VNF descriptor loading process from the storage unit and an NFV instance creation process.

[0074]

NFV-MANO 100 includes a descriptor input unit 101 configured to receive the VNF descriptor (vnfd) (including an information element of a VM name) in this exemplary embodiment illustrated in FIG. 10 and so on, an instantiation input parameter input unit 102 configured to receive an instantiation input parameter, an instantiation execution unit 103 configured to execute an instantiation operation, and an instance record output unit 104 configured to output an instance record. The instance record and data are stored in an instance record storage unit 112.

[0075]

For example, from OSS/BSS or VNFN to NFVO, NS (Network Service) or VNF instantiation operation is executed. The instantiation input parameter is used to customize network service NS or VNF to

specific instantiation, for example. As the instantiation input parameter, information for identifying a deployment flavor (Deployment Flavor) to be used, and VNF and PNF to be incorporated by the instantiation operation are referred to. The instantiation execution unit 103 creates records (NSR, VNFR, VLR, VNFFGR and so forth) indicating a newly created instance. Each record created based on information given by each descriptor and additional runtime information related to a component instance, provides a data group necessary for modeling a state of a network service (NS) instance, VNF instance, VNFFG instance, or VL (Virtual Link) instance. Distinction among instances such as a plurality of VMs (VDUs) that have been created can be made by names (such as VDU names).
[0076]

In the above-mentioned exemplary embodiment, the description has been given, using, as an example, virtual machines (VMs) instantiated based on information on the descriptor or the like. With respect to VNF, VNFC, and VDU as well, by including an information element for setting a name (naming rule) to be associated with an instance to be created, distinction among instances (VNF, VNFC, and VDU) created based on the descriptor is made possible, in terms of management.
[0077]

Each disclosure of the above-listed Non-Patent Literature is incorporated herein by reference. Modification and adjustment of each exemplary embodiment or each example are possible within the scope of the overall disclosure (including the claims) of the present invention and based on the basic technical concept of the present invention. Various combinations and selections of various disclosed elements (including each element in each claim, each element in each example, each element in each drawing, and so on) are possible within the scope of the claims of the present invention. That is, the present invention naturally includes various variations and modifications that could be made by those skilled in the art according to the overall disclosure including the claims and the technical concept.

REFERENCE SIGNS LIST

[0078]

100 NFV-MANO

101 descriptor input unit

5 102 instantiation input parameter input unit

103 instantiation execution unit

104 instance record output unit

111 descriptor storage unit

112 instance record storage unit

10

CLAIMS:

1. A network functions virtualization management and orchestration method comprising:

a step of receiving information of a template from a storage unit;

5 and

a step of creating an instance based on the information of the template, wherein

an information element that allows an instance created based on the information of the template to be distinguished by name is provided
10 in the template that is stored in the storage unit.

2. The network functions virtualization management and orchestration method according to claim 1, wherein the information element that allows the instance to be distinguished by name includes an information element that gives a naming rule for a name of the instance.

15 3. A network functions virtualization management and orchestration method, comprising:

providing, in a VNF (Virtualized Network Function) descriptor (VNFD), an information element that gives a naming rule for a name of an instance, to allow an instance created based on information of the
20 VNFD to be distinguished by name.

4. The network functions virtualization management and orchestration method according to claim 3, comprising:

providing an information element of a VM name that describes a naming rule for a virtual machine (VM) on a same layer as information
25 elements of an ID (Identifier) and a VDU (Virtualized Deployment Unit) of the VNFD, to allow a plurality of instances created based on the VNFD to be distinguished by name.

5. A network functions virtualization management and orchestration system, comprising:

30 input means that receives information of a template from a storage unit; and

creation means that creates an instance based on the information of the template,

wherein the template includes an information element that allows

an instance created based on the information of the template to be distinguished by name.

6. The network functions virtualization management and orchestration system according to claim 5, wherein the information element that allows the instance to be distinguished by name includes an information element that gives a naming rule for the name of the instance.

7. A network functions virtualization management and orchestration system comprising:

10 means that receives a VNF (Virtualized Network Function) descriptor (VNFD) including an information element that gives a naming rule for a name of an instance; and

means that creates an instance based on information of the VNFD.

8. The network functions virtualization management and orchestration system according to claim 7, wherein an information element of a VM name that describes a naming rule for a virtual machine (VM) is provided in the VNFD on a same layer as information elements of an ID (Identifier) and a VDU (Virtualized Deployment Unit) of the VNFD, to allow a plurality of instances created based on the VNFD to be distinguished by name.

9. A program causing a computer to execute:

a processing of receiving, from a storage unit, a template including an information element that allows an instance created based on information of the received template to be distinguished by name; and

a processing of creating an instance based on the information of the received template.

10. The program according to claim 9, wherein the information element that allows the instance to be distinguished by name includes an information element that gives a naming rule for the name of the instance.

11. A program causing a computer to execute:

a processing of receiving a VNF (Virtualized Network Function) descriptor (VNFD) with an information element that gives a naming rule

for a name of an instance; and

a processing of creating an instance based on information of the VNFD.

12. The program according to claim 11, wherein an information
5 element of a VM name that describes a naming rule for a virtual machine
(VM) is provided in the VNFD on a same layer as information elements
of an ID and a VDU (Virtualized Deployment Unit), to allow the
instance created based on the VNFD to be distinguished by name.

FIG. 1





FIG. 2



Network Service Descriptor(NSD)
 Virtual Link Descriptor(VLD)
 VNF Forwarding Graph Descriptor(VNFFGD)
 VNF Descriptor (VNFD)
 Physical Network Function Descriptor(PNFD)

Network Service Record (NSR)
 VNFFG Record (VNFFGR)
 Virtual Link Record (VLR)
 VNF Record (VNFR)
 PNF Record (PNFR)

FIG. 3




FIG. 4




FIG. 5




FIG. 6

• vnfd base information elements

Identifier	Type	Cardinality	Description
Id	Leaf	1	ID (e.g., name) of this VNFD.
Vendor	Leaf	1	The vendor generating this VNFD.
descriptor_version	Leaf	1	Version of the VNF Descriptor
Version	Leaf	1	Version of VNF software, described by the descriptor under consideration
Vdu	Element	1...N	This describes a set of elements related to a particular VDU, see section 6.3.1.2
virtual_link	Element	0...N	Represents the type of network connectivity mandated by the VNF vendor between two or more Connection Points, see section 6.3.1.3
connection_point	Element	1...N	This element describes an external interface exposed by this VNF enabling connection with a VL, see section 6.3.1.4. NOTE: The connection between the VNF and the VL is expressed by the VLD referencing this Connection Point. The Connection Point may also be attached to internal Virtual Vinks (vnfd:virtual_link:id).
lifecycle_event	Leaf	0...N	Defines VNF functional scripts/workflows for specific lifecycle events (e.g., initialization, termination, graceful shutdown, scaling out/in, update/upgrade, VNF state management related actions to support service continuity)
Dependency	Leaf	0...N	Describe dependencies between VDUs. Defined in terms of source and target VDU, i.e., target VDU "depends on" source VDU. In other words sources VDU must exists before target VDU can be initiated/deployed,
monitoring_parameter	Leaf	0...N	Monitoring parameters, which can be tracked for this VNF. Can be used for specifying different deployment flavours for the VNF in a VNFD, and/or to indicate different levels of VNF service availability. These parameters can be an aggregation of the parameters at VDU level e.g., memory-consumption, CPU-utilisation, bandwidth-consumption etc. They can be VNF specific as well such as calls-per-second (cps), number-of-subscribers, no-of-rules, flows-per-second, VNF downtime, etc. One or more of these parameters could be influential in determining the need to scale.
deployment_flavour	Element	1...N	Represents the assurance parameter(s) and its requirement for each deployment flavour of the VNF being described, see section 6.3.1.5
auto_scale_policy	Leaf	0...N	Represents the policy meta data, which may include the criteria parameter and action-type. The criteria parameter should be a supported assurance parameter (vnf:monitoring_parameter). Example of such a descriptor could be Criteria parameter → calls-per-second Action-type → scale-out to a different flavour ID, if exists
manifest_file	Leaf	0...1	The VNF package may contain a file that lists all files in the package. This can be useful for auditing purposes or for enabling some security features on the package.
manifest_file_security	Leaf	0...N	The manifest file may be created to contain a digest of each file that it lists as part of the package. This digest information can form the basis of a security mechanism to ensure the contents of the package meet certain security related properties. If the manifest file contains digests of the files in the package, then the manifest file should also note the particular hash algorithm used to enable suitable verification mechanisms. Examples of suitable hash algorithms include, but are not limited to SHA-256, SHA-384, SHA-512, and SHA-3. In conjunction with an appropriate security signing mechanism, which may include having a security certificate as part of the VNF package, the digest information can be used to help ensure the contents of the VNF package have not been tampered with.

FIG. 7

(A) nfd:vdu vbase elements

Identifier	Type	Cardinality	Description
id	Leaf	1	A unique identifier of this VDU within the scope of the VNFD, including version functional description and other identification information. This will be used to refer to VDU when defining relationships between them.
vm_image	Leaf	0...1	This provides a reference to a VM image. NOTE: A cardinality of zero allows for creating empty virtualisation containers as per [NFVSWA001].
computation_requirement	Leaf	1	Describe the required computation resources characteristics (e.g., processing power, number of virtual CPUs, etc.), including Key Quality Indicators (KQIs) for performance and reliability/availability.
virtual_memory_resource_element	Leaf	1	This represents the virtual memory needed for the VDU
virtual_network_bandwidth_resource	Leaf	1	This represents the requirements in terms of the virtual network bandwidth needed for the VDU
lifecycle_event	Leaf	0...N	Defines VNF component functional scripts/workflows for specific lifecycle events (e.g. initialization, termination, graceful shutdown, scaling out/in)
constraint	Leaf	0...1	Placeholder for other constraints.
high_availability	Leaf	0...1	Defines redundancy model to ensure high availability examples include: - ActiveActive: Implies that two instance of the same VDU will co-exists with continuous data synchronization. - ActivePassive: Implies that two instance of the same VDU will co-exists without any data synchronization.
scale_in_out	Leaf	0...1	Defines minimum and maximum number of instances which can be created to support scale out/in.
vnfc	Element	1...N	Contains information that is distinct for each VNFC created based on this VDU.
monitoring_parameter	Leaf	0...N	Monitoring parameter, which can be tracked for a VNFC based on this VDU Examples include: memory-consumption, CPU-utilisation, bandwidth-consumption, VNFC downtime, etc.

(B) VNFC (vnfd:vdu:vnfc)

Identifier	Type	Cardinality	Description
id	Leaf	1	Unique VNFC identification within the namespace of a specific VNF.
connection_point	Element	1...N	Describes network connectivity between a VNFC instance (based on this VDU) and an internal Virtual Link.

(C) Connection Point (vnfd:vdu:vnfc:connection_point)

Identifier	Type	Cardinality	Description
id	Leaf	1	ID of the Connection Point.
virtual_link_reference	Reference	1	References an internal Virtual Link (vnfd:virtual_link:id, see section 6.3.1.3) to which other VNFCs can connect.
type	Leaf	1	This may be, for example, a virtual port, a virtual NIC address, a physical port, a physical NIC address or the endpoint of an IP VPN enabling network connectivity.

FIG. 8

(A) vnfd:vdv information elements related to storage

storage_requirement	Leaf	0...1	Required storage characteristics (e.g. size), including Key Quality Indicators (KQIs) for performance and reliability/availability.
rdma_support_bandwidth	Leaf	0...1	The VDU may have been developed, optimized or tested with a storage supporting RDMA over a given bandwidth.

(B) VNF internal Virtual Link (vnfd:virtual_link)

Identifier	Type	Cardinali ty	Description
id	Leaf	1	Unique identifier of this internal Virtual Link
connectivity_type	Leaf	1	Connectivity type (e.g., E-Line, E-LAN or E-Tree).
connection_points_references	Reference	2...N	References to Connection Points (vnfd:vdv:vnfc:connection_point:id, vnfd:connection_point:id), e.g., of type E-Line, E-Tree, or E-LAN.
root_requirement	Leaf	1	Describes required throughput of the link (e.g., bandwidth of E-Line, root bandwidth of E-Tree, and aggregate capacity of E_LAN)
leaf_requirement	Leaf	0...1	Describes required throughput of leaf connections to the link (for E-Tree and E-LAN branches)
qos	Leaf	0...N	Describes the QoS options to be supported on the VL e.g., latency, jitter etc.
test_access	Leaf	0...1	Describes the test access facilities to be supported on the VL (e.g., none, passive monitoring, or active (intrusive) loopbacks at endpoints

(C) Connection Point (vnfd:connection_point)

Identifier	Type	Cardinali ty	Description
id	Leaf	1	ID of the Connection Point.
virtual_link_reference	Reference	0...1	References an internal Virtual Link (vnfd:virtual_link:id, see section 6.3.1.3) to which other VDUs, NFs, and other types of endpoints can connect.
type	Leaf	1	This may be for example a virtual port, a virtual NIC address, a physical port, a physical NIC address or the endpoint of an IP VPN enabling network connectivity.

FIG. 9

(A) Deployment flavour element (vnfd:deployment_flavour)

Identifier	Type	Cardinality	Description
id	Leaf	1	ID of the VNF flavour
flavour_key	Leaf	1	Monitoring parameter & its value against which this flavour is being described. The parameters should be present as a vnfd:monitoring_parameter, see section 6.3.1.1. An example is a flavour of a virtual PGW could be described in terms of the parameter "calls per second" There could be a flavour describing what it takes to support a VPGW with 10k calls per second.
constraint	Leaf	0...N	Constraint that this deployment flavour can only meet the requirements on certain hardware
constituent_vdu	Element	1...N	Represents the characteristics of a constituent flavour element, see section 6.3.1.6. Examples include Control-plane VDU & Data-plane VDU & Load Balancer VDU Each needs a VDU element to support the deployment flavour of 10k calls-per-sec of vPGW, Control-plane VDU may specify 3 VMs each with 4 GB vRAM, 2 vCPU, 32 GB virtual storage etc. Data-plane VDU may specify 2 VMs each with 8 GB vRAM, 4 vCPU, 64 GB virtual storage etc.

(B) Constituent VDU (vnfd:deployment_flavour:constituent_vdu)

Identifier	Type	Cardinality	Description
vdu_reference	Reference	1	References a VDU which should be used for this deployment flavour by vnfd:vdu:id, see section 6.3.1.2.1.
number_of_instances	Leaf	1	Number of VDU instances required
constituent_vnfc	Reference	1...N	References VNFCs which should be used for this deployment flavour by vnfd:vdu:vnfc:id

FIG. 10

VNFD Vnfd base information elements

Identifier	Type	Cardinality	Description
Id	Leaf	1	ID (e.g., name) of this VNFD.
Vendor ...	Leaf	1	The vendor generating this VNFD.
descriptor_version	Leaf	1	Version of the VNF Descriptor
Version	Leaf	1	Version of VNF software, described by the descriptor under consideration
vdu	Element	1..N	This describes a set of elements related to a particular VDU.
...			
VM name	Leaf	1...N	NAMING RULE FOR VM

FIG. 11




FIG. 12




FIG. 13




FIG. 11

