



(86) Date de dépôt PCT/PCT Filing Date: 2012/05/25
(87) Date publication PCT/PCT Publication Date: 2012/12/06
(45) Date de délivrance/Issue Date: 2021/02/23
(85) Entrée phase nationale/National Entry: 2013/11/25
(86) N° demande PCT/PCT Application No.: US 2012/039684
(87) N° publication PCT/PCT Publication No.: 2012/166644
(30) Priorités/Priorities: 2011/05/27 (US61/490,737);
2011/06/13 (US61/496,347); 2011/07/06 (US13/176,834)


(51) Cl.Int./Int.Cl. A62C 37/00 (2006.01)

(72) Inventeur/Inventor:
SHIPMAN, BUDDY CLAYTON, US

(73) Propriétaire/Owner:
VICTAULIC COMPANY, US

(74) Agent: BERESKIN & PARR LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : ENTRETOISE EN X ET RACCORDEMENT SOUPLE POUR TETES D'EXTINCTION
(54) Title: X-BRACE VALVE AND FLEXIBLE CONNECTION FOR FIRE SPRINKLERS



(57) Abrégé/Abstract:

A fire sprinkler head (12) has a valve (42) with an X-brace latch (54), and includes a flexible conduit (14). A sprinkler nozzle (16) is secured to a first end of the flexible conduit (14). The sprinkler nozzle (16) includes a first fitting (28), a sprinkler orifice (20) and fusible element (22). A second fitting (40) is secured to the second end of the flexible conduit (14) and includes the valve (42). The valve (42) has a valve element (44) which is moveable from a latched position to an unlatched position. A flexible link (56) extends from the sprinkler nozzle (16) to the X-brace valve latch (54). Breaking of the fusible element (22) releases the flexible link (56) to move from the latched position to the unlatched position, releasing the valve (42) for flow there-through.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(10) International Publication Number

WO 2012/166644 A1

(43) International Publication Date
6 December 2012 (06.12.2012)

(51) International Patent Classification:

A62C 37/14 (2006.01)

(21) International Application Number:

PCT/US2012/039684

(22) International Filing Date:

25 May 2012 (25.05.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/490,737	27 May 2011 (27.05.2011)	US
61/496,347	13 June 2011 (13.06.2011)	US
13/176,834	6 July 2011 (06.07.2011)	US

(72) Inventor; and

(71) Applicant : SHIPMAN, Buddy, Clayton [US/US]; 742 Ridge Hollow Drive, Heath, TX 75032 (US).

(74) Agent: KUBASTA, Kelly, J.; Klemchuk Kubasta LLP, 8150 N. Central Expressway; Tenth Floor, Dallas, TX 75206 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: X-BRACE AND FLEXIBLE CONNECTION FOR FIRE SPRINKLERS




FIG. 2

(57) Abstract: A fire sprinkler head (12) has a valve (42) with an X-brace latch (54), and includes a flexible conduit (14). A sprinkler nozzle (16) is secured to a first end of the flexible conduit (14). The sprinkler nozzle (16) includes a first fitting (28), a sprinkler orifice (20) and fusible element (22). A second fitting (40) is secured to the second end of the flexible conduit (14) and includes the valve (42). The valve (42) has a valve element (44) which is moveable from a latched position to an unlatched position. A flexible link (56) extends from the sprinkler nozzle (16) to the X-brace valve latch (54). Breaking of the fusible element (22) releases the flexible link (56) to move from the latched position to the unlatched position, releasing the valve (42) for flow there-through.

**X-BRACE VALVE AND FLEXIBLE CONNECTION FOR FIRE
SPRINKLERS**

TECHNICAL FIELD OF THE INVENTION

[0001] The present invention relates in general to fire sprinkler systems, and in particular to fire sprinkler heads used for sprinkler systems.

CROSS-REFERENCE TO RELATED APPLICATION

[0002] The present application claims the benefit under 35 U.S.C. § 120 of U.S. Non-Provisional Patent Application Serial No. 13/176,834 filed July 6, 2011 and entitled "X-Brace Valve And Flexible Connection For Fire Sprinklers," and further claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application Serial No. 61/496,347, filed June 13, 2011 and entitled "Sprinkler Hose Assembly," and U.S. Provisional Patent Application Serial No. 61/490,737, filed May 27, 2011 and entitled "Corrosion Resistant Straight or Flexible Dry Fire Sprinkler Tube With X-Brace".

BACKGROUND OF THE INVENTION

[0003] Prior art conventional dry barrel sprinklers for use in commercial fire sprinkler systems are sold to fire system installers in fixed lengths. The installer has to first install branch line piping for a sprinkler system and then measure a suitable length for dry barrel fire sprinklers for installation. An installer will order fire sprinklers for the installation according to the lengths measured. Delivery typically takes seven to ten business days, which delays installation and completion of construction projects. Longer delays occur if mistakes are made in measuring and the fire sprinklers have to be reordered in a different length.

[0004] Dry fire sprinkler systems often deteriorate rapidly due to condensation being trapped in such systems. With rigid dry sprinkler systems, an increased number of fittings is often required to route rigid piping from a branch line to a desired fire sprinkler head location. This increase in the number of fittings results

in providing additional places where condensation may collect without being able to drain. Additionally, dry fire sprinkler systems are filled with air or inert gas which is expelled during operation of such sprinkler systems. The response time for expelling air from the system and providing water to a fire zone is critical for containing a fire. With additional piping and fittings required for routing dry fire sprinkler systems, the volume required for evacuation and filling with water is increased.

SUMMARY OF THE INVENTION

[0005] A novel X-brace valve and flexible connection for fire sprinklers are disclosed. The X-brace is preferably included in a flexible fire sprinkler head, but may also be used in rigid sprinkler installations. The flexible fire sprinkler head is preferably a pendent dry fire sprinkler head, which has a flexible body structure, constructed of corrugated or braided hose similar to that commonly used for plumbing household clothes washing machines. A sprinkler nozzle secured to a first end of the conduit, which is preferably provided by a flexible hose. The sprinkler nozzle has a first fitting, a sprinkler orifice and fusible element. The fusible element is preferably provided by a fluid filled glass bulb which will break when ambient temperatures reach a predetermined temperature. A second fitting is secured to a second end of the flexible conduit, and a valve is mounted to the second fitting. The valve includes a valve element which is pivotally mounted to the second fitting and moveable from a latched position to an unlatched position. A flexible link extends from the sprinkler nozzle to the valve latch. Breaking of the fusible element releases the flexible link to move from the latched position to the unlatched position, releasing the valve to open for passing flow there-through. The flexible link provides a spring biased plunger having a plug which fits in the sprinkler orifice to seal against fluid flow there-through. Tension from the spring pulls the rod, or plunger, from within an X-brace valve latch which releases the valve element to open and pass water through the valve.

[0005a] In accordance with one aspect of invention, there is provided a fire sprinkler head comprising: a flexible conduit having a first end and a second end; a sprinkler nozzle secured to said first end of said flexible conduit, said sprinkler nozzle having an element which opens when exposed to temperatures above a preselected temperature to permit fluid flow through the sprinkler nozzle; a fitting secured to said second end of said flexible conduit, wherein said fitting is configured for securing to a sprinkler branch line; a valve disposed proximate to said second

end, said valve having a valve element which is moveable from a latched position to a released position, wherein said valve element prevents fluid flow through said valve when in said latched position and said valve element does not prevent fluid flow through said valve when in said released position; a flexible link extending between said sprinkler nozzle and said valve, wherein opening of said element causes said flexible link to in turn cause the valve element to move from said latched position to said released position; a plurality of slider locks, each of said slider locks having a lock pin and a brace arm, with said lock pins being slidably secured to respective ones of said brace arms such that said lock pins have open and closed positions relative to said brace arms, wherein said slider locks are arranged to be angularly aligned about a brace eye, each said lock pin having a follower end which extends into said brace eye when disposed in the open position and a protuberant end disposed on an opposite end of said lock pin that retains said valve element in said latched position when said lock pins are in the closed position; a link pin mounted to said flexible link and extending into said brace eye, engaging said follower ends of said lock pins to secure said lock pins in said closed positions; and wherein said lock pins have bias members urging said follower ends to protrude into said brace eye.

[0005b] In accordance with another aspect of invention, there is provided a flexible dry sprinkler head comprising: a flexible conduit having a first end and a second end, the flexible conduit being configured to couple to a fluid supply; a sprinkler nozzle mounted at the first end of the flexible conduit; and a valve disposed proximate to the second end of the flexible conduit and having an open state and a closed state, the valve configured to allow fluid from the fluid supply to flow through the conduit when the valve is in the open state and to prevent fluid from the fluid supply from flowing through the conduit when the valve is in the closed state.

[0005c] In accordance with another aspect of invention, there is provided a flexible dry sprinkler head comprising: a flexible conduit having a first end and a second end, the flexible conduit being configured to be coupled to a fluid supply; a sprinkler nozzle mounted at the first end of the flexible conduit, the sprinkler nozzle including an element that breaks when exposed to predetermined temperatures; a valve disposed proximate to the second end of the conduit and having an open state and a closed state, the valve configured to allow fluid from the fluid supply to flow through the conduit when the valve is in the open state and to prevent fluid from the fluid supply to flow through the conduit when the valve is in the closed state; and a flexible link extending within the conduit between the sprinkler nozzle and the valve, wherein the sprinkler nozzle, valve and flexible link are configured such that breaking of the element causes the flexible link to allow the valve to move from the closed state to the open state.

DESCRIPTION OF THE DRAWINGS

[0006] For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying Drawings in which FIGS. 1 through 7 show various aspects for x-brace valve and flexible connection for fire sprinklers devices made according to the present invention, as set forth below:

FIG. 1 is a side elevation view and partial cut-away view of a dry flexible fire sprinkler head made according to the present invention;

FIG. 2 is a sectional view of the flexible fire sprinkler head of FIG. 1, taken along section line 2-2 of FIG. 1, and shows a frontal elevation view of an X-brace valve latch in an unlatched position;

FIG. 3 is a side elevation view of slider lock of the X-brace latch of FIG. 2, and shows the slider lock in a released position;

FIG. 4 is a sectional view of the flexible fire sprinkler head of FIG. 1, taken along section line 2-2 of FIG. 1, and shows frontal elevation view of the X-brace valve latch in a latched position;

FIG. 5 is a side elevation view of a slider lock of the X-brace latch of FIG. 4, and shows the slider lock in a latched position;

FIG. 6 is an exploded view of the slider lock of FIG. 5; and

FIG. 7 is a side elevation view of an alternative lock pin.

DETAILED DESCRIPTION OF THE INVENTION

[0007] Referring to the Figures, FIG. 1 is a side elevation view and partial cut-away view of a dry flexible fire sprinkler head 12 made according to the present invention. The sprinkler head 12 has a conduit 14, which is provided a flexible conduit such as that formed with an outer cover of braided metal. A sprinkler nozzle 16 is mounted to a first end of the flexible conduit 14 and a connector fitting 32 is mounted to a second end of the conduit 14. The sprinkler nozzle 16 preferably includes a fitting 18, a sprinkler orifice, and a fusible element 22, such as a fluid filled glass bulb as is conventionally used in other fire sprinkler heads. The fusible element 22 breaks when exposed to a predetermined temperature. A diffuser 26, or spray plate, and support arms 28 are also provided. The connector fitting 32 is preferably secured to the second end of the flexible conduit 14 with an elbow fitting 40 there-between. The connector fitting 32 preferably connects the sprinkler head 12 to a pipe T 34 in a sprinkler branch line 36. A connector coupling 38 secures the fitting 32 to the pipe T 34. A valve 42 is preferably provided between the fitting 32 and the flexible conduit 14. The valve 42 is preferably a swing check valve, such as a clapper valve, and includes a swing-type valve element 44, or clapper, mounted by means of a pivot 46 for angularly moving to engage a seal 48 against a seal seat 50. An X-brace valve latch 54 is provided for securing the valve element 44 in a latched position until the sprinkler head 12 is opened for flow by means of the fusible element 22 breaking in response to exposure to high temperatures.

[0008] A flexible link 56 extends from the valve latch 54 to the sprinkler nozzle 16. A first end of the flexible link 56 has a link pin 58 for fitting into the valve latch 54 as described herein-below to secure the valve latch 54 in a latched

position. A second end of the flexible link 56 has a plug adapter 60 for securing the flexible link 56 to the sprinkler plug 24, such that removal of the sprinkler plug 24 due to breaking of the fusible element 22 will allow downward movement of the flexible link 56. An intermediate portion 62 of the flexible link 56 connects the plug adapter 60 to the link pin 58. Centralizer braces 64 are shown for centering the flexible link 56 within the flexible conduit 14. A bias member 66 is preferably provided by a torsion spring which is connected between the fitting 18 and the orifice 20 and the flexible link 56. A coupler 68 secures the flexible link 56 to a run out end of the bias member 66, which is preferably provided by a torsion spring. The bias member 66 provides a motive force for moving the flexible link 56 to pull the link pin 58 from engaging within the valve latch 54. A portion of the fitting 40 adjacent the valve latch 54 preferably has an undercut 70. The undercut 70 may be provided by a circumferentially extending groove, or by apertures formed radially into a first end of the fitting 40 to extend along a circumference of the fitting 40, in an angularly spaced, diametrically opposed arrangement.

[0009] FIG. 2 is a sectional view of the flexible sprinkler head 12 of FIG. 1, taken along section line 2-2 of FIG. 1, and shows a frontal elevation view of an X-brace type valve latch 54 in an unlatched position. FIG. 3 is a side elevation view of a slider lock 72 of FIG. 2, and shows the lock pin 74 in a released position. The valve latch 54 is shown having eight slider locks 72 arranged with respective longitudinal axes 86 in an angularly spaced alignment, with the longitudinal axes disposed equal angular distances about a central point of a brace eye 94. When the brace eye 94 is engaged by the flexible link 56, it is coaxial with a centrally disposed, longitudinal axis of the flexible link 56 and the link pin 58. The brace eye 94 defines a centrally disposed section of the valve latch 54, defined within a

link pin guide 96 to which first ends of the brace arms 88 are fixedly secured. The slider locks 72 each preferably have a brace arm 88 and a lock pin 74. In some embodiments, the brace arms 88 may be integrally formed as part of the valve element 44. The lock pins 74 have an elongate stem 80, with a follower end 82 and a protuberant end 84. Preferably, the follower end 82 and the protuberant end 84 are of a round shapes. Spaced apart from the protuberant end 84 is a fixed shoulder 78. A bias member 76 is preferably provided by a wound coil spring for extending between the fixed shoulder 78 and a stop 92 provided on the brace arm 88, such that the lock pin 74 is urged to move away from the protuberance end 82 toward the follower end 82. The brace arms 88 further include retainers 90 for slidably securing the lock pins 74 to the brace arms 88 for reciprocating along respective ones of the longitudinal axes 86. When the link pin 58 is not disposed within the brace eye 94, the lock pins 74 are free to move toward follower ends 82 of respective ones of the slider locks 72 and the associated brace arms 88, such that follower ends 82 protrude into the brace eye 94.

[0010] FIG. 4 is a sectional view of the flexible sprinkler head 12 of FIG. 1, taken along section line 2-2 of FIG. 1, and shows a frontal elevation view of the X-brace valve latch 54 in a latched position. FIG. 5 is a side elevation view and FIG. 6 is an exploded view of a brace arm 88 and lock pin 74 of the X-brace latch 54 of FIG. 4, and shows the lock pin 74 in the latched position. The flexible link 56 is shown in an initial position, as shown in FIG. 1, with the link pin 58 engaged within the brace eye 94 of the valve latch 54. The link pin 58 being engaged within the brace eye 94 pushes the lock pins 74 of respective ones of the slider locks 72 radially outward from the brace eye 94, which moves the protuberant portions 84 to radially extend into the undercut 70 and secure the valve element 44 in a closed

position. When the link pin 58 is removed from within the brace eye 94, the bias members 76 will urge the lock pins to move from latched positions, shown in FIGS. 4 and 5, into the released positions shown in FIGS. 2 and 3, and the valve element 44 will open under the force of fluid pressure within the sprinkler branch line 36.

[0011] FIG. 6 is a side elevation view of an alternative lock pin 100. The lock pin 100 has a bias member 102 provided by a wound coil spring. The lock pin 100 preferably has an elongate stem 106, a follower end 108 and a protuberant end 110. The follower end 108 and the protuberant end 110 are preferably rounded ends. A fixed shoulder 104 is provided spaced apart from the protuberant end 110, for receiving the bias member 102 there-between.

[0012] Vent holes 98 are preferably provided in the fitting 18 and the elbow fitting 40, such that moisture will drain from within the flexible sprinkler head 12. In other embodiments, nitrogen or another inert gas may be sealed within the flexible sprinkler head 12 to prevent moisture from being retained within the sprinkler head 12, rather than providing the vent holes 98.

[0013] The X-brace valve element of the present invention may also be used in wet sprinkler installations, and in rigid sprinkler heads. For rigid sprinkler heads, flexible link 56 may be replaced by a rigid link such as a solid rod or a rigid tube, and the flexible conduit 14 replaced with a rigid tubular member, such as a pipe or tubing.

[0014] The present invention provides advantages of a flexible sprinkler head for use in dry fire sprinkler installations. An X-brace configuration locks a valve element in a latched position, until a fusible element breaks and then a bias member pulls a flexible link from within the X-brace configuration to release the valve element to open and allow water flow through the flexible sprinkler head.

[0015] Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

1. A flexible dry sprinkler head comprising:
 - a flexible conduit having a first end and a second end, the flexible conduit being configured to be coupled to a fluid supply;
 - a sprinkler nozzle mounted at the first end of the flexible conduit, the sprinkler nozzle including an element that breaks when exposed to predetermined temperatures;
 - a valve disposed proximate to the second end of the conduit and having an open state and a closed state, the valve configured to allow fluid from the fluid supply to flow through the conduit when the valve is in the open state and to prevent fluid from the fluid supply to flow through the conduit when the valve is in the closed state; and
 - a flexible link extending within the conduit between the sprinkler nozzle and the valve,wherein the sprinkler nozzle, valve and flexible link are configured such that breaking of the element causes the flexible link to allow the valve to move from the closed state to the open state.
2. The flexible dry sprinkler head of claim 1, wherein the flexible conduit includes a corrugated hose.
3. The flexible dry sprinkler head of claim 2, wherein the flexible conduit includes an outer cover of braided metal.
4. The flexible dry sprinkler head of any one of claims 1-3, wherein the flexible conduit is capable of being bent at a right angle.
5. The flexible dry sprinkler head of any one of claims 1-4, wherein the valve comprises a valve element that is moveable from a latched position to a released position, the valve element maintaining the valve in the closed state when the valve element is in the latched position and allowing the valve to be in the open position when the valve element is in the released position.

6. The flexible dry sprinkler head of claim 5, wherein the flexible link has a first end portion that interfaces with the valve element.
7. The flexible dry sprinkler head of claim 6, when the first end portion maintains the valve element in the latched position.
8. The flexible dry sprinkler head of claim 7, wherein breaking of the element causes the flexible link to move toward the sprinkler nozzle, which disengages the first end portion from the valve element.
9. The flexible dry sprinkler head of claim 8, wherein the flexible link has a second end portion that is coupled to the sprinkler nozzle.
10. The flexible dry sprinkler head of any one of claims 1-9, further comprising at least one brace provided in the flexible conduit between the sprinkler nozzle and the valve that centers the flexible link within the flexible conduit.
11. The flexible dry sprinkler head of any one of claims 1-10, further comprising a bias member that is connected to the flexible link and that biases the flexible link toward the sprinkler nozzle.
12. The flexible dry sprinkler head of any one of claims 1-10, further comprising a bias member that is connected to the flexible link, wherein breaking of the element causes the bias member to pull on the flexible link.

1/4




FIG. 1

2/4




FIG. 2




FIG. 3

REPLACEMENT SHEET

3/4




FIG. 4




FIG. 5

4/4




FIG. 6




FIG. 7

