



US010837377B2

(12) **United States Patent**  
**Sueoka et al.**

(10) **Patent No.:** **US 10,837,377 B2**

(45) **Date of Patent:** **Nov. 17, 2020**

(54) **METHOD OF IMPLEMENTING CONTROL LOGIC OF COMPRESSION IGNITION ENGINE**

(58) **Field of Classification Search**  
CPC .. F02D 41/0002; F02D 37/02; F02D 41/0057; F02D 41/26; F02D 41/3041;  
(Continued)

(71) Applicant: **Mazda Motor Corporation**, Hiroshima (JP)

(56) **References Cited**

(72) Inventors: **Masanari Sueoka**, Hiroshima (JP); **Atsushi Inoue**, Aki-gun (JP); **Keiji Maruyama**, Hiroshima (JP); **Takuya Ohura**, Hiroshima (JP); **Tomohiro Nishida**, Hiroshima (JP); **Yusuke Kawai**, Hiroshima (JP); **Tetsuya Chikada**, Higashihiroshima (JP); **Tatsuhiko Tokunaga**, Aki-gun (JP)

U.S. PATENT DOCUMENTS

6,968,825 B2 11/2005 Hitomi et al.  
2009/0194081 A1 8/2009 Ito et al.

FOREIGN PATENT DOCUMENTS

JP 4082292 B2 4/2008  
JP 6249667 B2 12/2017

OTHER PUBLICATIONS

Urushihara T et al., "A Study of a Gasoline-fueled Compression Ignition Engine ~ Expansion of HCCI Operation Range Using SI Combustion as a Trigger of Compression Ignition," SAE International, Apr. 11, 2005, 9 pages.

(Continued)

(73) Assignee: **Mazda Motor Corporation**, Hiroshima (JP)

*Primary Examiner* — Audrey K Bradley  
*Assistant Examiner* — Edward Bushard

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 31 days.

(74) *Attorney, Agent, or Firm* — Alleman Hall Creasman & Tuttle LLP

(21) Appl. No.: **16/411,896**

(22) Filed: **May 14, 2019**

(65) **Prior Publication Data**  
US 2019/0360409 A1 Nov. 28, 2019

(57) **ABSTRACT**


(30) **Foreign Application Priority Data**  
May 22, 2018 (JP) ..... 2018-098137

A method of implementing control logic of a compression ignition engine is provided. The engine includes an injector, a variable valve operating mechanism, an ignition plug, at least one sensor, and a processor. The processor outputs the signal to the ignition plug in a specific operating state so that unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside a combustion chamber. The method includes determining a geometric compression ratio  $\epsilon$  of the engine, and determining control logic defining a valve opening angle CA of an intake valve. The valve opening angle CA (deg) is determined so that the following expression is satisfied, if the geometric compression ratio  $\epsilon$  is  $\epsilon < 14$ ,  $-40\epsilon + 800 + D \leq CA \leq 60\epsilon - 550 + D$ . Here, D

(Continued)

(51) **Int. Cl.**  
**F02D 41/00** (2006.01)  
**F01L 1/22** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **F02D 41/0002** (2013.01); **F01L 1/22** (2013.01); **F02D 37/02** (2013.01);  
(Continued)



is a correction term according to the engine speed NE (rpm),  
 $D=3.3 \times 10^{-10} NE^3 - 1.0 \times 10^{-6} NE^2 + 7.0 \times 10^{-4} NE$ .

**12 Claims, 26 Drawing Sheets**

- (51) **Int. Cl.**  
*F02D 37/02* (2006.01)  
*F02D 41/26* (2006.01)  
*F02D 41/30* (2006.01)  
*F02P 9/00* (2006.01)
- (52) **U.S. Cl.**  
 CPC ..... *F02D 41/0057* (2013.01); *F02D 41/26*  
 (2013.01); *F02D 41/3041* (2013.01); *F02P*  
*9/00* (2013.01); *F02D 2041/001* (2013.01)
- (58) **Field of Classification Search**  
 CPC ..... F02D 2041/001; F02D 13/0215; F02D  
 2200/101; F02D 13/0261; F02D 41/006;

F02D 41/0007; F02D 41/1475; F02D  
13/0234; F02D 41/30; F02D 41/0077;  
F02D 9/00; F01L 1/22; F02P 9/00; F02P  
5/1502; Y02T 10/144; Y02T 10/47; Y02T  
10/18; F02B 37/16; F02B 31/06

See application file for complete search history.

(56) **References Cited**

OTHER PUBLICATIONS

Gentz, G et al., "Spark Assist for CA50 Control and Improved  
Robustness in a Premixed LTGC Engine—Effects of Equivalence  
Ratio and Intake Boost," SAE International, Apr. 3, 2018, 19 pages.  
European Patent Office, Extended European Search Report Issued in  
Application No. 19174790.6, dated Sep. 18, 2019, Germany, 25  
pages.






FIG. 2




FIG. 3




FIG. 4





FIG. 5

FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12

FIG. 13






FIG. 14




FIG. 15





FIG. 16

FIG. 17






FIG. 18



FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25





FIG. 26



**METHOD OF IMPLEMENTING CONTROL  
LOGIC OF COMPRESSION IGNITION  
ENGINE**

TECHNICAL FIELD

The technology disclosed herein relates to a method of implementing control logic of a compression ignition engine.

BACKGROUND OF THE DISCLOSURE

It is known that combustion by compressed self ignition in which a mixture gas combusts instantly without flame propagation maximizes fuel efficiency since the combustion period minimized. However, various problems must be solved for automobile engines with regard to the combustion by compressed self ignition. For example, since the operating state and environmental conditions vary greatly in the automotive application, a stable compressed self ignition is a major problem. The combustion by compressed self ignition has not yet been put to practical use for the automobile engine. In order to solve this problem, for example, JP4,082,292B2 proposes that an ignition plug ignite the mixture gas, when it is difficult for the compressed self ignition to occur because of a low combustion-chamber temperature. By igniting the mixture gas immediately before the compression top dead center, the pressure around the ignition plug increases to facilitate the compressed self ignition.

Unlike the technology disclosed in JP4,082,292B2 in which the compressed self ignition is assisted by the ignition of the ignition plug, the present applicant instead proposes SPCCI (SPark Controlled Compression Ignition) combustion which is a combination of SI (Spark Ignition) combustion and CI (Compression Ignition) combustion. SI combustion is combustion accompanied by the flame propagation initiated by forcibly igniting the mixture gas inside the combustion chamber. CI combustion is combustion initiated by the mixture gas inside the combustion chamber carrying out the compressed self ignition. SPCCI combustion is combustion in which, when the mixture gas inside the combustion chamber is forcibly ignited to start the combustion by flame propagation, the unburnt mixture gas inside the combustion chamber combusts by the compression ignition because of a pressure buildup due to the heat generation and the flame propagation of the SI combustion. Since SPCCI combustion includes CI combustion, it is one form of "combustion by compression ignition."

CI combustion takes place when the in-cylinder temperature reaches an ignition temperature defined by the composition of the mixture gas. Fuel efficiency can be maximized, if the in-cylinder temperature reaches the ignition temperature near a compression top dead center and CI combustion takes place. The in-cylinder temperature increases according to the increase in the in-cylinder pressure. The in-cylinder pressure in SPCCI combustion is a result of two pressure buildups: a pressure buildup by the compression work of the piston in a compression stroke, and a pressure buildup caused by the heat generation of the SI combustion.

Here, the compression work of the piston is defined by an effective compression ratio. If the effective compression ratio is too low, the pressure buildup by the compression work of the piston is small. In this case, unless the flame propagation in the SPCCI combustion progresses and the pressure buildup caused by the heat generation of the SI combustion increases considerably, the in-cylinder temperature cannot be raised to the ignition temperature. As a result,

since a small amount of mixture gas is ignited by the compressed self ignition, and a large amount of mixture gas combusts by the flame propagation, the combustion period becomes longer and fuel efficiency decreases. That is, in order to stabilize the CI combustion in the SPCCI combustion to maximize fuel efficiency, it is necessary to have the effective compression ratio above a certain value.

Meanwhile, if CI combustion takes place near a compression top dead center because of a high in-cylinder temperature at a compression starting timing due to a high ambient temperature, etc., the in-cylinder pressure excessively increases to create excessive combustion noise. In this case, the combustion noise can be reduced if the ignition timing is retarded. However, if the ignition timing is retarded, since the CI combustion takes place when the piston falls considerably in the expansion stroke, fuel efficiency is lowered. Since the pressure buildup caused by the heat generation of the SI combustion can be utilized in the SPCCI combustion, it is effective to lower the effective compression ratio to reduce the pressure buildup by the compression work of the piston in order to achieve both reduced combustion noise and improved fuel efficiency. Thus, combustion noise can be kept suitable, without lowering fuel efficiency.

In order for a design engineer to put to practical use an engine which performs the SPCCI combustion, he/she needs to determine, depending on each engine operating state, the minimum effective compression ratio at which the CI combustion is stabilized, and additionally needs to raise the effective compression ratio within a permissible combustion noise range and determine the effective compression ratio without the combustion noise becoming excessively large. Therefore, the design engineer can put to practical use the engine with maximum fuel efficiency by maximizing the ratio in the CI combustion within the SPCCI combustion, while suppressing the combustion noise to a tolerable level.

However, since the SPCCI combustion is a new combustion system in the art, no one has found the suitable range for the effective compression ratio until now.

The engine effective compression ratio is determined based on the geometric compression ratio and a valve opening period (valve opening angle) of an intake valve. When implementing engine control logic for performing the SPCCI combustion, the design engineer needs to determine a range of the valve opening angle.

Since the maximum in-cylinder pressure increases as the geometric compression ratio increases, the strength of engine components needs to be raised, which results in an increase in weight, and an increase in mechanical resistance loss. Meanwhile, in terms of thermal efficiency, a larger expansion ratio which is determined based on the geometric compression ratio is desirable. Since the maximum in-cylinder pressure varies by the heat balance based on the combustion mode or the stroke capacity even if the geometric compression ratio is same, the optimal geometric compression ratio for the new combustion system of SPCCI combustion has been unknown until now.

SUMMARY OF THE DISCLOSURE

The present inventors diligently examined SPCCI combustion, and as a result, succeeded in determining a suitable range of a valve opening angle within a range of a geometric compression ratio where the SPCCI combustion occurs. The present inventors came to invent a method of implementing control logic of a compression ignition engine based on this knowledge.

3

Specifically, the technology disclosed herein relates to the method of implementing the control logic of the compression ignition engine.

The engine includes an injector configured to inject fuel to be supplied in a combustion chamber, a variable valve operating mechanism configured to change a valve timing of an intake valve, an ignition plug configured to ignite a mixture gas inside the combustion chamber, at least one sensor configured to measure a parameter related to an operating state of the engine, and a processor configured to output a signal to the injector, the variable valve operating mechanism, and the ignition plug, according to control logic corresponding to the operating state of the engine, in response to the measurement of the at least one sensor.

The processor outputs the signal to the ignition plug in a specific operating state defined by an engine load and an engine speed so that unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber.

The method includes the steps of determining a geometric compression ratio  $\epsilon$  of the engine, and determining the control logic defining a valve opening angle CA of the intake valve. When determining the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the geometric compression ratio  $\epsilon$  is  $\epsilon < 14$ ,

$$-40\epsilon + 800 + D \leq CA \leq 60\epsilon - 550 + D \tag{a}$$

where D is a correction term according to the engine speed NE (rpm),

$$D = 3.3 \times 10^{-10} NE^3 - 1.0 \times 10^{-6} NE^2 + 7.0 \times 10^{-4} NE.$$

The ignition plug ignites the mixture gas inside the combustion chamber in response to the signal from the processor. The combustion starts by flame propagation and then the unburnt mixture gas combusts by self-ignition to complete the combustion. That is, this engine performs SPCCI (Spark Controlled Compression Ignition) combustion.

When implementing the control logic of the engine, the design engineer first determines the geometric compression ratio  $\epsilon$  of the engine. When the geometric compression ratio is set  $\epsilon < 14$ , the design engineer determines the valve opening angle CA of the intake valve so that the expression (a) is satisfied. By setting the opening angle so as to satisfy the expression (a), the engine can keep the combustion noise within the allowable range while performing stable CI (compression ignition) combustion in the SPCCI combustion which is a combination of SI (spark ignition) combustion and the CI combustion, even under various conditions with different situations of the combustion chamber. Operating the engine for performing the SPCCI combustion according to the control logic maximizes fuel efficiency.

The index for determining the valve opening angle CA of the intake valve, which is available when implementing the control logic of the engine for performing the SPCCI combustion has been unknown until now. The design engineer had to repeatedly conduct experiments, etc. under various conditions while changing the valve opening angle CA of the intake valve to various timings so as to determine the valve opening angle CA corresponding to the operating state of the engine.

The method of defines the relationship between the geometric compression ratio  $\epsilon$  of the engine and the valve opening angle CA of the intake valve in order to achieve suitable SPCCI combustion. The design engineer can put to practical use the engine for performing the SPCCI combustion,

4

by determining the valve opening angle CA within the range in which the relationship is satisfied. The design engineer can put to practical use the engine for performing the SPCCI combustion with very few man-hours.

When implementing the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the geometric compression ratio  $\epsilon$  is  $14 \leq \epsilon < 16$ .

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 290 + D \tag{b}$$

Thus, with the engine for performing the SPCCI combustion, fuel efficiency is maximized. In addition, the design engineer can put to practical use the engine with fewer man-hours than the conventional one.

When determining the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the geometric compression ratio  $\epsilon$  is  $16 \leq \epsilon < 16.3$ .

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq 290 + D \tag{c}$$

or

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D \tag{d}$$

Similar to the above, with the engine for performing SPCCI combustion, fuel efficiency is maximized. In addition, the design engineer can put to practical use the engine with fewer man-hours than the conventional one.

When implementing the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the geometric compression ratio  $\epsilon$  is  $16.3 \leq \epsilon$ .

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq 290 + D \tag{e}$$

or

$$-12.162\epsilon + 403.24 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D \tag{f}$$

Similar to the above, with the engine for performing the SPCCI combustion, fuel efficiency is maximized. In addition, the design engineer can put to practical use the engine with fewer man-hours than the conventional one.

When implementing the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the fuel is a low octane fuel, and if the geometric compression ratio  $\epsilon$  is  $\epsilon < 12.7$ .

$$-40(\epsilon + 1.3) + 800 + D \leq CA \leq 60(\epsilon + 1.3) - 550 + D \tag{g}$$

Thus, the engine using the low octane fuel also can maximize fuel efficiency. In addition, the design engineer can put to practical use the engine with man-hours fewer than the conventional one.

By determining a valve close timing IVC of the intake valve so as to satisfy both of the expressions (a) and (g) if the geometric compression ratio  $\epsilon$  is  $\epsilon < 12.7$ , the design engineer can set the control logic suitable for both of the engine using a high octane fuel and the engine using low octane fuel. Even if the octane number of the fuel is different depending on each destination, the design engineer can set the control logic collectively, which reduces the man-hours.

When implementing the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the fuel is the low octane fuel, and if the geometric compression ratio  $\epsilon$  is  $12.7 \leq \epsilon < 14.7$ .

$$-0.7246(\epsilon + 1.3)^2 + 6.7391(\epsilon + 1.3) + 287.68 + D \leq CA \leq 290 + D \tag{h}$$

When implementing the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the fuel is the low octane fuel, and if the geometric compression ratio  $\epsilon$  is  $14.7 \leq \epsilon < 15$ .

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq 290+D \quad (i)$$

or

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+287.68+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D \quad (j)$$

When implementing the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied, if the fuel is the low octane fuel, and if the geometric compression ratio  $\epsilon$  is  $15 \leq \epsilon$ .

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq 290+D \quad (k)$$

or

$$-12.162(\epsilon+1.3)+403.24+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D \quad (l)$$

The valve close timing IVC of the intake valve may change as the operating state of the engine changes, and the valve opening angle CA (deg) is determined for each operating state so as to satisfy the expressions (a) to (l).

Thus, the engine can stably perform the SPCCI combustion in various operating states.

The engine may operate in a low-load operating state where the load is a given load or lower, according to the control logic.

In general CI combustion, the ignitability degrades when the engine load is low. In this regard, in the SPCCI combustion, the SI combustion is performed at the start of the combustion, and the CI combustion starts using the heat released by the SI combustion. The ignitability of the SPCCI combustion does not degrade even when the engine load is low.

The engine may operate in a minimum load operating state according to the control logic. That is, the engine may perform the SPCCI combustion in the minimum load operating state.

The geometric compression ratio  $\epsilon$  of the engine may be set to satisfy  $10 \leq \epsilon < 21$ . Thus, the geometric compression ratio  $\epsilon$  can be suitably set.

The engine may have a first mode in which the processor outputs a signal to each of the injector and the variable valve operating mechanism so that an air-fuel ratio (A/F) that is a weight ratio of air contained in the mixture gas inside the combustion chamber to the fuel becomes leaner than a stoichiometric air fuel ratio, and outputs a signal to the ignition plug so that the unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber, and a second mode in which the processor outputs a signal to each of the injector and the variable valve operating mechanism so that a gas-fuel ratio (G/F) that is a weight ratio of the entire mixture gas inside the combustion chamber to the fuel becomes leaner than the stoichiometric air fuel ratio, and the A/F becomes the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio, and outputs a signal to the ignition plug so that the unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber.

In the first mode, the engine makes the A/F of the mixture gas leaner than the stoichiometric air fuel ratio, which

improves the fuel efficiency of the engine. On the other hand, in the second mode, the engine makes the G/F leaner than the stoichiometric air fuel ratio and makes the A/F the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio. By the G/F becoming lean, fuel efficiency improves. Further, by introducing exhaust gas recirculation (EGR) gas into the combustion chamber, the combustion stability of the SPCCI combustion increases.

In such an engine, the valve close timing IVC of the intake valve is determined so as to satisfy any one of expressions (a) to (h). Thus, the engine can perform the SPCCI combustion that is a combination of the SI combustion and the CI combustion stably in both the first mode and the second mode.

The engine may be provided with an EGR system configured to introduce burnt gas into the combustion chamber. The processor may output a signal to the EGR system and the ignition plug so that a heat amount ratio used as an index related to a ratio of an amount of heat generated when the mixture gas combusts by flame propagation to the entire amount of heat generated when the mixture gas inside the combustion chamber combusts, becomes a target heat amount ratio defined corresponding to the operating state of the engine.

The heat amount ratio of the SPCCI combustion is less than 100%. The heat amount ratio of the combustion mode where the combustion completes only by flame propagation without the combustion by compression ignition (i.e., SI combustion) is 100%.

If the heat amount ratio is increased in the SPCCI combustion, the ratio of the SI combustion increases, which is advantageous in reducing combustion noise. Whereas, if the heat amount ratio is lowered in the SPCCI combustion, the ratio of the CI combustion increases, which is advantageous in improving fuel efficiency. The heat amount ratio changes by changing the temperature of the combustion chamber and/or the ignition timing. For example, when the temperature inside the combustion chamber is high, the CI combustion starts at an early timing, and the heat amount ratio becomes low. Further, when the ignition timing is advanced, the SI combustion starts at an early timing, and the heat amount ratio becomes high. By the processor outputting the signal to the EGR system and the ignition plug so that the heat amount ratio becomes the target heat amount ratio defined corresponding to the operating state of the engine, both of the reduction of the combustion noise and the improvement of the fuel efficiency can be achieved.

The processor may output a signal to the EGR system and the ignition plug so that the heat amount ratio becomes higher when the load of the engine is higher.

When the engine load increases, the amount of fuel supplied into the combustion chamber increases and the temperature inside the combustion chamber becomes high. By increasing the heat amount ratio of the SPCCI combustion when the engine load is high, combustion noise is reduced.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view illustrating a configuration of an engine.

FIG. 2 is a view illustrating a configuration of a combustion chamber, where an upper portion corresponds to a plan view of the combustion chamber, and a lower portion is a cross-sectional view taken along a line II-II.

FIG. 3 is a plan view illustrating a configuration of the combustion chamber and an intake system.

FIG. 4 is a block diagram illustrating a configuration of an engine control device.

FIG. 5 is a graph illustrating a waveform of SPCCI combustion.

FIG. 6 illustrates maps of the engine, where an upper portion is a map when the engine is warm, a middle figure is a map when the engine is half warm, and a lower portion is a map when the engine is cold.

FIG. 7 illustrates the details of the map when the engine is warm.

FIG. 8 illustrates charts of a fuel injection timing, an ignition timing, and a combustion waveform in each operating range of the map of FIG. 7.

FIG. 9 illustrates a layer structure of the engine map.

FIG. 10 is a flowchart illustrating a control process according to a layer selection of the map.

An upper graph of FIG. 11 is a graph illustrating a relationship between an engine load and a valve open timing of an intake valve in Layer 2, and a lower graph thereof is a graph illustrating a relationship between an engine speed and the valve open timing of the intake valve in Layer 2.

An upper graph of FIG. 12 is a graph illustrating a relationship between the engine load and the valve open timing of the intake valve in Layer 3, a middle figure thereof is a graph illustrating a relationship between the engine load and a valve close timing of an exhaust valve in Layer 3, and a lower graph thereof is a graph illustrating a relationship between the engine load, and an overlap period of the intake valve and the exhaust valve in Layer 3.

FIG. 13 is a flowchart illustrating a process of an operation control of the engine executed by an ECU.

FIG. 14 illustrates a relationship between the engine load and a target SI ratio.

FIG. 15 is a graph illustrating an occurring range of the SPCCI combustion versus an EGR rate in Layer 2.

FIG. 16 is one example of a matrix image utilized in order to determine a relationship between a geometric compression ratio and a valve close timing of the intake valve where the SPCCI combustion is possible in Layer 2.

An upper graph of FIG. 17 illustrates a relationship between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 2 when a high octane fuel is used, and a lower graph thereof illustrates a relationship between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 2 when a low octane fuel is used.

FIG. 18 is a graph illustrating a range where the SPCCI combustion is stabilized versus a gas air-fuel ratio (G/F) in Layer 3.

FIG. 19 is one example of a matrix image utilized in order to determine the relationship between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 3.

An upper graph of FIG. 20 illustrates a relationship between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 3 when the high octane fuel is used, and a lower graph thereof illustrates a relationship between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 3 when the low octane fuel is used.

An upper graph of FIG. 21 illustrates a relationship between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 2 and Layer 3 when the high octane fuel is used, and a lower graph thereof illustrates a relationship

between the geometric compression ratio and the valve close timing of the intake valve where the SPCCI combustion is possible in Layer 2 and Layer 3 when the low octane fuel is used.

FIG. 22 is a flowchart illustrating a procedure of a method of implementing control logic of a compression ignition engine.

An upper graph of FIG. 23 illustrates a relationship between the geometric compression ratio and a valve opening angle of the intake valve where the SPCCI combustion is possible in Layer 2 when the high octane fuel is used, and a lower graph thereof illustrates a relationship between the geometric compression ratio and the valve opening angle of the intake valve where the SPCCI combustion is possible in Layer 2 when the low octane fuel is used.

An upper graph of FIG. 24 illustrates a relationship between the geometric compression ratio and the valve opening angle of the intake valve where the SPCCI combustion is possible in Layer 3 when the high octane fuel is used, and a lower graph thereof illustrates a relationship between the geometric compression ratio and the valve opening angle of the intake valve where the SPCCI combustion is possible in Layer 3 when the low octane fuel is used.

An upper graph of FIG. 25 illustrates a relationship between the geometric compression ratio and the valve opening angle of the intake valve where the SPCCI combustion is possible in Layer 2 and Layer 3 when the high octane fuel is used, and a lower graph thereof illustrates a relationship between the geometric compression ratio and the valve opening angle of the intake valve where the SPCCI combustion is possible in Layer 2 and Layer 3 when the low octane fuel is used.

FIG. 26 is a flowchart illustrating a procedure of the method of implementing the control logic of the compression ignition engine.

#### DETAILED DESCRIPTION OF THE DISCLOSURE

Hereinafter, one embodiment of a method of implementing control logic of a compression ignition engine will be described in detail with reference to the accompanying drawings. The following description is one example of the engine and the method of implementing the control logic.

FIG. 1 is a view illustrating a configuration of the compression ignition engine. FIG. 2 is a view illustrating a configuration of a combustion chamber of the engine. FIG. 3 is a view illustrating a configuration of the combustion chamber and an intake system. Note that in FIG. 1, an intake side is the left side in the drawing, and an exhaust side is the right side in the drawing. In FIGS. 2 and 3, the intake side is the right side in the drawings, and the exhaust side is the left side in the drawings. FIG. 4 is a block diagram illustrating a configuration of a control device of the engine.

An engine 1 is a four-stroke engine which operates by a combustion chamber 17 repeating an intake stroke, a compression stroke, an expansion stroke, and an exhaust stroke. The engine 1 is mounted on an automobile with four wheels. The automobile travels by operating the engine 1. Fuel of the engine 1 is gasoline in this example. The fuel may be a liquid fuel containing at least gasoline. The fuel may be gasoline containing, for example, bioethanol.  
(Engine Configuration)

The engine 1 includes a cylinder block 12 and a cylinder head 13 placed thereon. A plurality of cylinders 11 are

formed inside the cylinder block **12**. In FIGS. **1** and **2**, only one cylinder **11** is illustrated. The engine **1** is a multi-cylinder engine.

A piston **3** is slidably inserted in each cylinder **11**. The pistons **3** are connected with a crankshaft **15** through respective connecting rods **14**. Each piston **3** defines the combustion chamber **17**, together with the cylinder **11** and the cylinder head **13**. Note that the term “combustion chamber” may be used in a broad sense. That is, the term “combustion chamber” may refer to a space formed by the piston **3**, the cylinder **11**, and the cylinder head **13**, regardless of the position of the piston **3**.

As illustrated in the lower part of FIG. **2**, a lower surface of the cylinder head **13**, i.e., a ceiling surface of the combustion chamber **17**, is comprised of a slope **1311** and a slope **1312**. The slope **1311** is a rising gradient from the intake side toward an injection axial center **X2** of an injector **6** which will be described later. The slope **1312** is a rising gradient from the exhaust side toward the injection axial center **X2**. The ceiling surface of the combustion chamber **17** is a so-called “pent-roof” shape.

An upper surface of the piston **3** is bulged toward the ceiling surface of the combustion chamber **17**. A cavity **31** is formed in the upper surface of the piston **3**. The cavity **31** is a dent in the upper surface of the piston **3**. The cavity **31** has a shallow pan shape in this example. The center of the cavity **31** is offset at the exhaust side with respect to a center axis **X1** of the cylinder **11**.

A geometric compression ratio  $\epsilon$  of the engine **1** is set so as to satisfy  $10 \leq \epsilon < 30$ , and preferably satisfy  $10 \leq \epsilon < 21$ . The engine **1** which will be described later performs SPCCI (Spark Controlled Compression Ignition) combustion that is a combination of SI (Spark Ignition) combustion and CI (Compression Ignition) combustion in a part of operating ranges. The SPCCI combustion controls the CI combustion using heat generated and a pressure buildup by the SI combustion. The engine **1** is the compression ignition engine. However, in this engine **1**, the temperature of the combustion chamber **17**, when the piston **3** is at a compression top dead center (i.e., compression end temperature), does not need to be increased. In the engine **1**, the geometric compression ratio can be set comparatively low. The low geometric compression ratio becomes advantageous in a reduction of cooling loss and mechanical loss. For engines using regular gasoline (a low octane fuel of which the octane number is about 91), the geometric compression ratio of the engine **1** is 14-17, and for those using high octane gasoline (a high octane fuel of which the octane number is about 96), the geometric compression ratio is 15-18.

An intake port **18** is formed in the cylinder head **13** for each cylinder **11**. As illustrated in FIG. **3**, each intake port **18** has a first intake port **181** and a second intake port **182**. The intake port **18** communicates with the corresponding combustion chamber **17**. Although the detailed illustration of the intake port **18** is omitted, it is a so-called “tumble port.” That is, the intake port **18** has such a shape that a tumble flow is formed in the combustion chamber **17**.

Each intake valve **21** is disposed in the intake ports **181** and **182**. The intake valves **21** open and close a channel between the combustion chamber **17** and the intake port **181** or **182**. The intake valves **21** are opened and closed at given timings by a valve operating mechanism. The valve operating mechanism may be a variable valve operating mechanism which varies the valve timing and/or valve lift. In this example, as illustrated in FIG. **4**, the variable valve operating mechanism has an intake-side electric S-VT (Sequential-Valve Timing) **23**. The intake-side electric S-VT **23** con-

tinuously varies a rotation phase of an intake cam shaft within a given angle range. The valve open timing and the valve close timing of the intake valve **21** vary continuously. Note that the electric S-VT may be replaced with a hydraulic S-VT, as the intake valve operating mechanism.

An exhaust port **19** is also formed in the cylinder head **13** for each cylinder **11**. As illustrated in FIG. **3**, each exhaust port **19** also has a first exhaust port **191** and a second exhaust port **192**. The exhaust port **19** communicates with the corresponding combustion chamber **17**.

Each exhaust valve **22** is disposed in the exhaust ports **191** and **192**. The exhaust valves **22** open and close a channel between the combustion chamber **17** and the exhaust port **191** or **192**. The exhaust valves **22** are opened and closed at a given timing by a valve operating mechanism. The valve operating mechanism may be a variable valve operating mechanism which varies the valve timing and/or valve lift. In this example, as illustrated in FIG. **4**, the variable valve operating mechanism has an exhaust-side electric SVT **24**. The exhaust-side electric S-VT **24** continuously varies a rotation phase of an exhaust cam shaft within a given angle range. The valve open timing and the valve close timing of the exhaust valve **22** change continuously. Note that the electric S-VT may be replaced with a hydraulic S-VT, as the exhaust valve operating mechanism.

The intake-side electric S-VT **23** and the exhaust-side electric S-VT **24** adjust length of an overlap period where both the intake valve **21** and the exhaust valve **22** open. If the length of the overlap period is made longer, the residual gas in the combustion chamber **17** can be purged. Moreover, by adjusting the length of the overlap period, internal EGR (Exhaust Gas Recirculation) gas can be introduced into the combustion chamber **17**. An internal EGR system is comprised of the intake-side electric S-VT **23** and the exhaust-side electric S-VT **24**. Note that the internal EGR system may not be comprised of the S-VT.

The injector **6** is attached to the cylinder head **13** for each cylinder **11**. Each injector **6** directly injects fuel into the combustion chamber **17**. The injector **6** is one example of a fuel injection part. The injector **6** is disposed in a valley part of the pent roof where the slope **1311** and the slope **1312** meet. As illustrated in FIG. **2**, the injection axial center **X2** of the injector **6** is located at the exhaust side of the center axis **X1** of the cylinder **11**. The injection axial center **X2** of the injector **6** is parallel to the center axis **X1**. The injection axial center **X2** of the injector **6** and the center of the cavity **31** are in agreement with each other. The injector **6** faces the cavity **31**. Note that the injection axial center **X2** of the injector **6** may be in agreement with the center axis **X1** of the cylinder **11**. In such a configuration, the injection axial center **X2** of the injector **6** and the center of the cavity **31** may be in agreement with each other.

Although the detailed illustration is omitted, the injector **6** is comprised of a multi nozzle-port type fuel injection valve having a plurality of nozzle ports. As illustrated by two-dot chain lines in FIG. **2**, the injector **6** injects the fuel so that the fuel spreads radially from the center of the combustion chamber **17**. The injector **6** has ten nozzle ports in this example, and the nozzle port is disposed so as to be equally spaced in the circumferential direction.

The injectors **6** are connected to a fuel supply system **61**. The fuel supply system **61** includes a fuel tank **63** configured to store fuel, and a fuel supply passage **62** which connects the fuel tank **63** to the injector **6**. In the fuel supply passage **62**, a fuel pump **65** and a common rail **64** are provided. The fuel pump **65** pumps fuel to the common rail **64**. The fuel pump **65** is a plunger pump driven by the crankshaft **15** in

## 11

this example. The common rail **64** stores fuel pumped from the fuel pump **65** at a high fuel pressure. When the injector **6** is opened, the fuel stored in the common rail **64** is injected into the combustion chamber **17** from the nozzle ports of the injector **6**. The fuel supply system **61** can supply fuel to the injectors **6** at a high pressure of 30 MPa or higher. The pressure of fuel supplied to the injector **6** may be changed according to the operating state of the engine **1**. Note that the configuration of the fuel supply system **61** is not limited to the configuration described above.

An ignition plug **25** is attached to the cylinder head **13** for each cylinder **11**. The ignition plug **25** forcibly ignites a mixture gas inside the combustion chamber **17**. The ignition plug **25** is disposed at the intake side of the center axis **X1** of the cylinder **11** in this example. The ignition plug **25** is located between the two intake ports **181** and **182** of each cylinder. The ignition plug **25** is attached to the cylinder head **13** so as to incline downwardly toward the center of the combustion chamber **17**. As illustrated in FIG. 2, the electrode of the ignition plug **25** faces the inside of the combustion chamber **17** and is located near the ceiling surface of the combustion chamber **17**. Note that the ignition plug **25** may be disposed at the exhaust side of the center axis **X1** of the cylinder **11**. Moreover the ignition plug **25** may be disposed on the center axis **X1** of the cylinder **11**.

An intake passage **40** is connected to one side surface of the engine **1**. The intake passage **40** communicates with the intake port **18** of each cylinder **11**. Gas introduced into the combustion chamber **17** flows through the intake passage **40**. An air cleaner **41** is disposed in an upstream end part of the intake passage **40**. The air cleaner **41** filters fresh air. A surge tank **42** is disposed near the downstream end of the intake passage **40**. Part of the intake passage **40** downstream of the surge tank **42** constitutes independent passages branched from the intake passage **40** for each cylinder **11**. The downstream end of each independent passage is connected to the intake port **18** of each cylinder **11**.

A throttle valve **43** is disposed between the air cleaner **41** and the surge tank **42** in the intake passage **40**. The throttle valve **43** adjusts an introducing amount of the fresh air into the combustion chamber **17** by adjusting an opening of the throttle valve.

A supercharger **44** is also disposed in the intake passage **40**, downstream of the throttle valve **43**. The supercharger **44** boosts gas to be introduced into the combustion chamber **17**. In this example, the supercharger **44** is a mechanical supercharger driven by the engine **1**. The mechanical supercharger **44** may be a root, Lysholm, vane, or a centrifugal type.

An electromagnetic clutch **45** is provided between the supercharger **44** and the engine **1**. The electromagnetic clutch **45** transmits a driving force from the engine **1** to the supercharger **44** or disengages the transmission of the driving force between the supercharger **44** and the engine **1**. As will be described later, an ECU **10** switches the disengagement and engagement of the electromagnetic clutch **45** to switch the supercharger **44** between ON and OFF.

An intercooler **46** is disposed downstream of the supercharger **44** in the intake passage **40**. The intercooler **46** cools gas compressed by the supercharger **44**. The intercooler **46** may be of a water cooling type or an oil cooling type, for example.

A bypass passage **47** is connected to the intake passage **40**. The bypass passage **47** connects an upstream part of the supercharger **44** to a downstream part of the intercooler **46** in the intake passage **40** so as to bypass the supercharger **44** and the intercooler **46**. An air bypass valve **48** is disposed in

## 12

the bypass passage **47**. The air bypass valve **48** adjusts a flow rate of gas flowing in the bypass passage **47**.

The ECU **10** fully opens the air bypass valve **48** when the supercharger **44** is turned OFF (i.e., when the electromagnetic clutch **45** is disengaged). The gas flowing through the intake passage **40** bypasses the supercharger **44** and is introduced into the combustion chamber **17** of the engine **1**. The engine **1** operates in a non-supercharged state, i.e., a natural aspiration state.

When the supercharger **44** is turned ON, the engine **1** operates in a supercharged state. The ECU **10** adjusts an opening of the air bypass valve **48** when the supercharger **44** is turned ON (i.e., when the electromagnetic clutch **45** is engaged). A portion of the gas which passed through the supercharger **44** flows back toward upstream of the supercharger **44** through the bypass passage **47**. When the ECU **10** adjusts the opening of the air bypass valve **48**, a supercharging pressure of the gas introduced into the combustion chamber **17** changes. Note that the term "supercharging" as used herein refers to a situation where the pressure inside the surge tank **42** exceeds an atmospheric pressure, and "non-supercharging" refers to a situation where the pressure inside the surge tank **42** becomes below the atmospheric pressure.

In this example, a supercharging system **49** is comprised of the supercharger **44**, the bypass passage **47**, and the air bypass valve **48**.

The engine **1** has a swirl generating part which generates a swirl flow inside the combustion chamber **17**. As illustrated in FIG. 3, the swirl generating part has a swirl control valve **56** attached to the intake passage **40**. Among a primary passage **401** coupled to the first intake port **181** and a secondary passage **402** coupled to the second intake port **182**, the swirl control valve **56** is disposed in the secondary passage **402**. The swirl control valve **56** is an opening control valve which is capable of choking a cross section of the secondary passage **402**. When the opening of the swirl control valve **56** is small, since an intake flow rate of air flowing into the combustion chamber **17** from the first intake port **181** is relatively large, and an intake flow rate of air flowing into the combustion chamber **17** from the second intake port **182** is relatively small, the swirl flow inside the combustion chamber **17** becomes stronger. On the other hand, when the opening of the swirl control valve **56** is large, since the intake flow rates of air flowing into the combustion chamber **17** from the first intake port **181** and the second intake port **182** become substantially equal, the swirl flow inside the combustion chamber **17** becomes weaker. When the swirl control valve **56** is fully opened, the swirl flow will not occur. Note that the swirl flow circulates counterclockwise in FIG. 3, as illustrated by white arrows (also see white arrows in FIG. 2).

An exhaust passage **50** is connected to the other side surface of the engine **1**. The exhaust passage **50** communicates with the exhaust port **19** of each cylinder **11**. The exhaust passage **50** is a passage through which exhaust gas discharged from the combustion chambers **17** flows. Although the detailed illustration is omitted, an upstream part of the exhaust passage **50** constitutes independent passages branched from the exhaust passage **50** for each cylinder **11**. The upper end of the independent passage is connected to the exhaust port **19** of each cylinder **11**.

An exhaust gas purification system having a plurality of catalytic converters is disposed in the exhaust passage **50**. Although illustration is omitted, an upstream catalytic converter is disposed inside an engine bay. The upstream catalytic converter has a three-way catalyst **511** and a GPF

(Gasoline Particulate Filter) **512**. The downstream catalytic converter is disposed outside the engine bay. The downstream catalytic converter has a three-way catalyst **513**. Note that the exhaust gas purification system is not limited to the illustrated configuration. For example, the GPF may be omitted. Moreover, the catalytic converter is not limited to those having the three-way catalyst. Further, the order of the three-way catalyst and the GPF may suitably be changed.

Between the intake passage **40** and the exhaust passage **50**, an EGR passage **52** which constitutes an external EGR system is connected. The EGR passage **52** is a passage for recirculating part of the exhaust gas to the intake passage **40**. The upstream end of the EGR passage **52** is connected between the upstream catalytic converter and the downstream catalytic converter in the exhaust passage **50**. The downstream end of the EGR passage **52** is connected to an upstream part of the supercharger **44** in the intake passage **40**. EGR gas flowing through the EGR passage **52** flows into the upstream part of the supercharger **44** in the intake passage **40**, without passing through the air bypass valve **48** of the bypass passage **47**.

An EGR cooler **53** of water cooling type is disposed in the EGR passage **52**. The EGR cooler **53** cools the exhaust gas. An EGR valve **54** is also disposed in the EGR passage **52**. The EGR valve **54** adjusts a flow rate of the exhaust gas flowing through the EGR passage **52**. By adjusting the opening of the EGR valve **54**, an amount of the cooled exhaust gas, i.e., a recirculating amount of external EGR gas can be adjusted.

In this example, an EGR system **55** is comprised of the external EGR system and the internal EGR system. The external EGR system can supply exhaust gas to the combustion chamber **17** that is a lower temperature than the internal EGR system.

The control device of the compression ignition engine includes the ECU (Engine Control Unit) **10** for operating the engine **1**. The ECU **10** is a controller based on a well-known microcomputer, and as illustrated in FIG. **4**, includes a processor (e.g., a central processing unit (CPU)) **101** which executes a computer program, memory **102** which, for example, is comprised of a RAM (Random Access Memory) and/or a ROM (Read Only Memory), and stores the program and data, and an input/output bus **103** which inputs and outputs an electrical signal. The ECU **10** is one example of a control part.

As illustrated in FIGS. **1** and **4**, various kinds of sensors SW1-SW17 are connected to the ECU **10**. The sensors SW1-SW17 output signals to the ECU **10**. The sensors include the following sensors:

Airflow sensor SW1: Disposed downstream of the air cleaner **41** in the intake passage **40**, and measures a flow rate of fresh air flowing through the intake passage **40**;

First intake-air temperature sensor SW2: Disposed downstream of the air cleaner **41** in the intake passage **40**, and measures the temperature of fresh air flowing through the intake passage **40**;

First pressure sensor SW3: Disposed downstream of the connected position of the EGR passage **52** in the intake passage **40** and upstream of the supercharger **44**, and measures the pressure of gas flowing into the supercharger **44**;

Second intake-air temperature sensor SW4: Disposed downstream of the supercharger **44** in the intake passage **40** and upstream of the connected position of the bypass passage **47**, and measures the temperature of gas flowed out of the supercharger **44**;

Second pressure sensor SW5: Attached to the surge tank **42**, and measures the pressure of gas downstream of the supercharger **44**;

Pressure indicating sensors SW6: Attached to the cylinder head **13** corresponding to each cylinder **11**, and measures the pressure inside each combustion chamber **17**;

Exhaust temperature sensor SW7: Disposed in the exhaust passage **50**, and measures the temperature of the exhaust gas discharged from the combustion chamber **17**;

Linear O<sub>2</sub> sensor SW8: Disposed upstream of the upstream catalytic converter in the exhaust passage **50**, and measures the oxygen concentration of the exhaust gas;

Lambda O<sub>2</sub> sensor SW9: Disposed downstream of the three-way catalyst **511** in the upstream catalytic converter, and measures the oxygen concentration of the exhaust gas;

Water temperature sensor SW10: Attached to the engine **1** and measures the temperature of coolant;

Crank angle sensor SW11: Attached to the engine **1** and measures the rotation angle of the crankshaft **15**;

Accelerator opening sensor SW12: Attached to an accelerator pedal mechanism and measures the accelerator opening corresponding to an operating amount of the accelerator pedal;

Intake cam angle sensor SW13: Attached to the engine **1** and measures the rotation angle of an intake cam shaft;

Exhaust cam angle sensor SW14: Attached to the engine **1** and measures the rotation angle of an exhaust cam shaft;

EGR pressure difference sensor SW15: Disposed in the EGR passage **52** and measures a pressure difference between the upstream and the downstream of the EGR valve **54**;

Fuel pressure sensor SW16: Attached to the common rail **64** of the fuel supply system **61**, and measures the pressure of fuel supplied to the injector **6**; and

Third intake-air temperature sensor SW17: Attached to the surge tank **42**, and measures the temperature of gas inside the surge tank **42**, i.e., the temperature of intake air introduced into the combustion chamber **17**.

The ECU **10** determines the operating state of the engine **1** based on the signals of at least one of the sensors SW1-SW17, and calculates a control amount of each device according to the control logic defined beforehand. The control logic is stored in the memory **102**. The control logic includes calculating a target amount and/or the control amount by using a map stored in the memory **102**.

The ECU **10** outputs electrical signals according to the calculated control amounts to the injectors **6**, the ignition plugs **25**, the intake-side electric S-VT **23**, the exhaust-side electric S-VT **24**, the fuel supply system **61**, the throttle valve **43**, the EGR valve **54**, the electromagnetic clutch **45** of the supercharger **44**, the air bypass valve **48**, and the swirl control valve **56**.

For example, the ECU **10** sets a target torque of the engine **1** based on the signal of the accelerator opening sensor SW12 and the map, and determines a target supercharging pressure. The ECU **10** then performs a feedback control for adjusting the opening of the air bypass valve **48** based on the target supercharging pressure and the pressure difference before and after the supercharger **44** obtained from the signals of the first pressure sensor SW3 and the second pressure sensor SW5 so that the supercharging pressure becomes the target supercharging pressure.

Moreover, the ECU **10** sets a target EGR rate (i.e., a ratio of the EGR gas to the entire gas inside the combustion chamber **17**) based on the operating state of the engine **1** and the map. The ECU **10** then determines a target EGR gas amount based on the target EGR rate and an inhaled air amount based on the signal of the accelerator opening sensor

SW12, and performs a feedback control for adjusting the opening of the EGR valve 54 based on the pressure difference before and after the EGR valve 54 obtained from the signal of the EGR pressure difference sensor SW15 so that the external EGR gas amount introduced into the combustion chamber 17 becomes the target EGR gas amount.

Further, the ECU 10 performs an air-fuel ratio feedback control when a given control condition is satisfied. For example, the ECU 10 adjusts the fuel injection amount of the injector 6 based on the oxygen concentration of the exhaust gas which is measured by the linear O<sub>2</sub> sensor SW8 and the lambda O<sub>2</sub> sensor SW9 so that the air-fuel ratio of the mixture gas becomes a desired value.

Note that the details of other controls of the engine 1 executed by the ECU 10 will be described later.  
(Concept of SPCCI Combustion)

The engine 1 performs combustion by compressed self ignition under a given operating state, mainly to improve fuel consumption and emission performance. The combustion by self ignition varies largely at the timing of the self ignition, if the temperature inside the combustion chamber 17 before a compression starts is nonuniform. Thus, the engine 1 performs the SPCCI combustion which is a combination of the SI combustion and the CI combustion.

The SPCCI combustion is combustion in which the ignition plug 25 forcibly ignites the mixture gas inside the combustion chamber 17 so that the mixture gas carries out the SI combustion by flame propagation, and the temperature inside the combustion chamber 17 increases by the heat generation of the SI combustion and the pressure inside the combustion chamber 17 increases by the flame propagation so that the unburnt mixture gas carries out the CI combustion by self ignition.

By adjusting the heat amount of the SI combustion, the variation in the temperature inside the combustion chamber 17 before a compression starts can be absorbed. By the ECU 10 adjusting the ignition timing, the mixture gas can be self-ignited at a target timing.

In the SPCCI combustion, the heat release of the SI combustion is slower than the heat release in the CI combustion. As illustrated in FIG. 5, the waveform of the heat release rate of SI combustion in the SPCCI combustion is smaller in the rising slope than the waveform in the CI combustion. In addition, the SI combustion is slower in the pressure fluctuation (dp/dθ) inside the combustion chamber 17 than the CI combustion.

When the unburnt mixture gas self-ignites after the SI combustion is started, the waveform slope of the heat release rate may become steeper. The waveform of the heat release rate may have an inflection point X at a timing of starting the CI combustion.

After the start in the CI combustion, the SI combustion and the CI combustion are performed in parallel. Since the CI combustion has a larger heat release than SI combustion, the heat release rate becomes relatively large. However, since the CI combustion is performed after a compression top dead center, the waveform slope of the heat release rate does not become too steep. The pressure fluctuation in the CI combustion (dp/dθ) also becomes comparatively slow.

The pressure fluctuation (dp/dθ) can be used as an index representing combustion noise. As described above, since the SPCCI combustion can reduce the pressure fluctuation (dp/dθ), it is possible to avoid excessive combustion noise. Combustion noise of the engine 1 can be kept below a tolerable level.

The SPCCI combustion is completed when the CI combustion is finished. The CI combustion is shorter in the

combustion period than SI combustion. The end timing of the SPCCI combustion becomes earlier than the SI combustion.

The heat release rate waveform of the SPCCI combustion is formed so that a first heat release rate part Q<sub>SI</sub> formed by the SI combustion and a second heat release rate part Q<sub>CI</sub> formed by the CI combustion continue in this order.

Here, a SI ratio is defined as a parameter indicative of a characteristic of the SPCCI combustion. The SI ratio is defined as an index related to a ratio of the amount of heat generated by the SI combustion to the entire amount of heat generated by the SPCCI combustion. The SI ratio is a ratio of heat amount generated by the two different combustion modes. If the SI ratio is high, the ratio of the SI combustion is high, and if the SI ratio is low, the ratio in the CI combustion is high. Alternatively, the SI ratio may be defined as a ratio of the amount of heat generated by the SI combustion to the amount of heat generated by the CI combustion. That is, in a waveform 801 illustrated in FIG. 5,

$$SI \text{ ratio} = Q_{SI} / Q_{CI}$$

Here,

Q<sub>SI</sub>: Area of SI combustion; and

Q<sub>CI</sub>: Area of CI combustion.

The engine 1 generates a strong swirl flow inside the combustion chamber 17 when performing the SPCCI combustion. The term "strong swirl flow" may be defined as a flow having a swirl ratio of four or higher, for example. The swirl ratio can be defined as a value obtained by dividing an integrated value of intake flow lateral angular velocities by an engine angular velocity, where the intake flow lateral angular velocity is measured for every valve lift, and the measured values are integrated to obtain the integrated value. Although illustration is omitted, the intake flow lateral angular velocity can be obtained based on measurement using known rig test equipment.

When the strong swirl flow is generated in the combustion chamber 17, the swirl flow is stronger in an outer circumferential part of the combustion chamber 17 and is relatively weaker in a central part. By the whirlpool resulting from a velocity gradient at the boundary between the central part and the outer circumferential part, turbulence energy becomes higher in the central part. When the ignition plug 25 ignites the mixture gas in the central part, the combustion speed of the SI combustion becomes higher by the high turbulence energy.

Flame of the SI combustion is carried by the strong swirl flow inside the combustion chamber 17 and propagates in the circumferential direction. The CI combustion is performed from the outer circumferential part to the central part in the combustion chamber 17.

When the strong swirl flow is generated in the combustion chamber 17, the SI combustion can fully be performed before the start in the CI combustion. Thus, the generation of combustion noise can be reduced, and the variation in the torque between cycles can be reduced.

(Engine Operating Range)

FIGS. 6 and 7 illustrate maps according to the control of the engine 1. The maps are stored in the memory 102 of the ECU 10. The maps include three kinds of maps, a map 501, a map 502, and a map 503. The ECU 10 uses a map selected from the three kinds of maps 501, 502, and 503 according to a wall temperature of the combustion chamber 17 and an intake air temperature, in order to control the engine 1. Note that the details of the selection of the three kinds of maps 501, 502, and 503 will be described later.

The first map **501** is a map when the engine **1** is warm. The second map **502** is a map when the engine **1** is half warm. The third map **503** is a map when the engine **1** is cold.

The maps **501**, **502**, and **503** are defined based on the load and the engine speed of the engine **1**. The first map **501** is roughly divided into three areas depending on the load and the engine speed. For example, the three areas include a low load area **A1**, a middle-to-high load area (**A2**, **A3**, and **A4**), and a high speed area **A5**. The low load area **A1** includes idle operation, and covers areas of a low engine speed and a middle engine speed. The middle-to-high load area (**A2**, **A3**, and **A4**) are higher in the load than the low load area **A1**. The high speed area **A5** is higher in the engine speed than the low load area **A1** and the middle-to-high load area (**A2**, **A3**, and **A4**). The middle-to-high load area (**A2**, **A3**, and **A4**) is divided into a middle load area **A2**, a high-load middle-speed area **A3** where the load is higher than the middle load area **A2**, and a high-load low-speed area **A4** where the engine speed is lower than the high-load middle-speed area **A3**.

The second map **502** is roughly divided into two areas. For example, the two areas include a low-to-middle speed area (**B1**, **B2**, and **B3**) and a high speed area **B4** where the engine speed is higher than the low-to-middle speed area (**B1**, **B2**, and **B3**). The low-to-middle speed area (**B1**, **B2**, and **B3**) is divided into a low-to-middle load area **B1** corresponding to the low load area **A1** and the middle load area **A2**, a high-load middle-speed area **B2**, and a high-load low-speed area **B3**.

The third map **503** has only one area **C1**, without being divided into a plurality of areas.

Here, the low speed area, the middle speed area, and the high speed area may be defined by substantially equally dividing the entire operating range of the engine **1** into three areas in the engine speed direction. In the example of FIGS. **6** and **7**, the engine speed is defined to be a low speed if the engine speed is lower than the engine speed **N1**, a high speed if the engine speed is higher than or equal to the engine speed **N2**, and a middle speed if the engine speed is higher than or equal to the engine speed **N1** and lower than the engine speed **N2**. For example, the engine speed **N1** may be about 1,200 rpm, and the engine speed **N2** may be about 4,000 rpm.

Moreover, the low load area may be an area including an operating state with the light load, the high load area may be an area including an operating state with full load, and the middle load area may be an area between the low load area and the high load area. Moreover, the low load area, the middle load area, and the high load area may be defined by substantially equally dividing the entire operating range of the engine **1** into three areas in the load direction.

The maps **501**, **502**, and **503** in FIG. **6** illustrate the states and combustion modes of the mixture gas in the respective areas. A map **504** in FIG. **7** corresponds to the first map **501**, and illustrates the state and combustion mode of the mixture gas in each area of the map, the opening of the swirl control valve **56** in each area, and a driving area and a non-driving area of the supercharger **44**. The engine **1** performs the SPCCI combustion in the low load area **A1**, the middle load area **A2**, the high-load middle-speed area **A3**, the high-load low-speed area **A4**, the low-to-middle load area **B1**, the high-load middle-speed area **B2**, and the high-load low-speed area **B3**. The engine **1** performs the SI combustion in other areas, specifically, in the high speed area **A5**, the high speed area **B4**, and the area **C1**.

(Operation of Engine in Each Area)

Below, the operation of the engine **1** in each area of the map **504** in FIG. **7** will be described in detail with reference to the fuel injection timing and the ignition timing which are illustrated in FIG. **8**. The horizontal axis in FIG. **8** is a crank angle. Note that reference numerals **601**, **602**, **603**, **604**, **605**, and **606** in FIG. **8** correspond to the operating states of the engine **1** indicated by the reference numerals **601**, **602**, **603**, **604**, **605**, and **606** in the map **504** of FIG. **7**, respectively.

(Low load Area)

The engine **1** performs the SPCCI combustion when the engine **1** operates in the low load area **A1**.

The reference numeral **601** in FIG. **8** indicates fuel injection timings (reference numerals **6011** and **6012**), an ignition timing (reference numeral **6013**), and a combustion waveform (i.e., a waveform indicating a change in the heat release rate with respect to the crank angle: reference numeral **6014**), when the engine **1** operates in the operating state **601** in the low load area **A1**. The reference numeral **602** indicates fuel injection timings (reference numerals **6021** and **6022**), an ignition timing (reference numeral **6023**), and a combustion waveform (reference numeral **6024**), when the engine **1** operates in the operating state **602** in the low load area **A1**. The reference numeral **603** indicates fuel injection timings (reference numerals **6031** and **6032**), an ignition timing (reference numeral **6033**), and a combustion waveform (reference numeral **6034**), when the engine **1** operates in the operating state **603** in the low load area **A1**. The operating states **601**, **602**, and **603** have the same engine speed, but different loads. The operating state **601** has the lowest load (i.e., light load), the operating state **602** has the second lowest load (i.e., low load), and the operating state **603** has the maximum load among these states.

In order to improve the fuel efficiency of the engine **1**, the EGR system **55** introduces the EGR gas into the combustion chamber **17**. For example, the intake-side electric S-VT **23** and the exhaust-side electric S-VT **24** are provided with a positive overlap period where both the intake valve **21** and the exhaust valve **22** are opened near an exhaust top dead center. A portion of the exhaust gas discharged from the combustion chamber **17** into the intake port **18** and the exhaust port **19** is re-introduced into the combustion chamber **17**. Since the hot exhaust gas is introduced into the combustion chamber **17**, the temperature inside the combustion chamber **17** increases. Thus, it becomes advantageous to stabilize the SPCCI combustion. Note that the intake-side electric S-VT **23** and the exhaust-side electric S-VT **24** may be provided with a negative overlap period where both the intake valve **21** and the exhaust valve **22** are closed.

Moreover, the swirl generating part forms the strong swirl flow inside the combustion chamber **17**. The swirl ratio is four or higher, for example. The swirl control valve **56** is fully closed or at a given opening (closed to some extent). As described above, since the intake port **18** is the tumble port, an inclined swirl flow having a tumble component and a swirl component is formed in the combustion chamber **17**.

The injector **6** injects fuel into the combustion chamber **17** a plurality of times during the intake stroke (reference numerals **6011**, **6012**, **6021**, **6022**, **6031**, and **6032**). The mixture gas is stratified by the multiple fuel injections and the swirl flow inside the combustion chamber **17**.

The fuel concentration of the mixture gas in the central part of the combustion chamber **17** is denser or richer than the fuel concentration in the outer circumferential part. For example, the air-fuel ratio (A/F) of the mixture gas in the central part is 20 or higher and 30 or lower, and the A/F of

the mixture gas in the outer circumferential part is 35 or higher. Note that the value of the A/F is a value when the mixture gas is ignited, and the same applies to the following description. Since the A/F of the mixture gas near the ignition plug 25 is set 20 or higher and 30 or lower, generation of raw NO<sub>x</sub> during the SI combustion can be reduced. Moreover, since the A/F of the mixture gas in the outer circumferential part is set to 35 or higher, the CI combustion stabilizes.

The A/F of the mixture gas is leaner than the stoichiometric air fuel ratio throughout the combustion chamber 17 (i.e., excess air ratio  $\lambda > 1$ ). For example, the A/F of the mixture gas is 30 or higher throughout the combustion chamber 17. Thus, the generation of raw NO<sub>x</sub> can be reduced to improve the emission performance.

When the engine load is low (i.e., in the operating state 601), the injector 6 performs the first injection 6011 in the first half of an intake stroke, and performs the second injection 6012 in the second half of the intake stroke. The first half of the intake stroke may be a first half of an intake stroke when the intake stroke is equally divided into two, and the second half of the intake stroke may be the rest. Moreover, an injection amount ratio of the first injection 6011 to the second injection 6012 may be 9:1, for example.

In the operating state 602 where the engine load is higher, the injector 6 initiates the second injection 6022 which is performed in the second half of an intake stroke at a timing advanced from the second injection 6012 in the operating state 601. By advancing the second injection 6022, the mixture gas inside the combustion chamber 17 becomes more homogeneous. The injection amount ratio of the first injection 6021 to the second injection 6022 may be 7:3 to 8:2, for example.

In the operating state 603 where the engine load is even higher, the injector 6 initiates the second injection 6032 which is performed in the second half of an intake stroke at a timing further advanced from the second injection 6022 in the operating state 602. By further advancing the second injection 6032, the mixture gas inside the combustion chamber 17 becomes further homogeneous. The injection amount ratio of the first injection 6031 to the second injection 6032 may be 6:4, for example.

After the fuel injection is finished, the ignition plug 25 ignites the mixture gas in the central part of the combustion chamber 17 at a given timing before a compression top dead center (reference numerals 6013, 6023, and 6033). The ignition timing may be during a final stage of the compression stroke. The compression stroke may be equally divided into three, an initial stage, a middle stage, and a final stage, and this finale stage may be used as the final stage of the compression stroke described above.

As described above, since the mixture gas in the central part has the relatively high fuel concentration, the ignitability improves and the SI combustion by flame propagation stabilizes. By the SI combustion being stabilized, the CI combustion begins at a suitable timing. Thus, the controllability in the CI combustion improves in the SPCCI combustion. Further, the generation of the combustion noise is reduced. Moreover, since the A/F of the mixture gas is made leaner than the stoichiometric air fuel ratio to perform the SPCCI combustion, the fuel efficiency of the engine 1 can be significantly improved. Note that the low load area A1 corresponds to Layer 3 described later. Layer 3 extends to the light load operating range and includes a minimum load operating state.

(Middle-to-High Load Area)

When the engine 1 operates in the middle-to-high load area, the engine 1 also performs the SPCCI combustion, similar to the low load area.

The reference numeral 604 in FIG. 8 indicates, in the middle-to-high load area, fuel injection timings (reference numerals 6041 and 6042), an ignition timing (reference numeral 6043), and a combustion waveform (reference numeral 6044), when the engine 1 operates in the operating state 604 in the middle load area A2. The reference numeral 605 indicates a fuel injection timing (reference numeral 6051), an ignition timing (reference numeral 6052), and a combustion waveform (reference numeral 6053), when the engine 1 operates in the operating state 605 in the high-load low-speed area A4.

The EGR system 55 introduces the EGR gas into the combustion chamber 17. For example, the intake-side electric S-VT 23 and the exhaust-side electric S-VT 24 are provided with a positive overlap period where both the intake valve 21 and the exhaust valve 22 are opened near an exhaust top dead center. Internal EGR gas is introduced into the combustion chamber 17. Moreover, the EGR system 55 introduces the exhaust gas cooled by the EGR cooler 53 into the combustion chamber 17 through the EGR passage 52. That is, the external EGR gas with a lower temperature than the internal EGR gas is introduced into the combustion chamber 17. The external EGR gas adjusts the temperature inside the combustion chamber 17 to a suitable temperature. The EGR system 55 reduces the amount of the EGR gas as the engine load increases. The EGR system 55 may not recirculate the EGR gas containing the internal EGR gas and the external EGR gas during the full load.

Moreover, in the middle load area A2 and the high-load middle-speed area A3, the swirl control valve 56 is fully closed or at a given opening (closed to some extent). In the combustion chamber 17, the strong swirl flow with the swirl ratio of four or higher is formed. On the other hand, in the high-load low-speed area A4, the swirl control valve 56 is open.

The air-fuel ratio (A/F) of the mixture gas is the stoichiometric air fuel ratio (A/F $\approx$ 14.7:1) throughout the combustion chamber 17. Since the three-way catalysts 511 and 513 purify the exhaust gas discharged from the combustion chamber 17, the emission performance of the engine 1 is improved. The A/F of the mixture gas may be set within a purification window of the three-way catalyst. The excess air ratio  $\lambda$  of the mixture gas may be 1.0 $\pm$ 0.2. Note that when the engine 1 operates in the high-load middle-speed area A3 including the full load (i.e., the maximum load), the A/F of the mixture gas may be set at the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio (i.e., the excess air ratio  $\lambda$  of the mixture gas is  $\lambda < 1$ ) throughout the combustion chamber 17.

Since the EGR gas is introduced into the combustion chamber 17, a gas-fuel ratio (G/F) which is a weight ratio of the entire gas to the fuel in the combustion chamber 17 becomes leaner than the stoichiometric air fuel ratio. The G/F of the mixture gas may be 18:1 or higher. Thus, generation of a so-called "knock" is avoided. The G/F may be set 18:1 or higher and 30:1 or lower. Alternatively, the G/F may be set 18:1 or higher and 50:1 or lower.

When the engine 1 operates in the operating state 604, the injector 6 performs a plurality of fuel injections (reference numerals 6041 and 6042) during an intake stroke. The injector 6 may perform the first injection 6041 in the first half of the intake stroke and the second injection 6042 in the second half of the intake stroke.

Moreover, when the engine **1** operates in the operating state **605**, the injector **6** injects fuel in an intake stroke (reference numeral **6051**).

The ignition plug **25** ignites the mixture gas at a given timing near a compression top dead center after the fuel is injected (reference numerals **6043** and **6052**). The ignition plug **25** may ignite the mixture gas before the compression top dead center when the engine **1** operates in the operating state **604** (reference numeral **6043**). The ignition plug **25** may ignite the mixture gas after the compression top dead center when the engine **1** operates in the operating state **605** (reference numeral **6052**).

Since the A/F of the mixture gas is set to the stoichiometric air fuel ratio and the SPCCI combustion is performed, the exhaust gas discharged from the combustion chamber **17** can be purified using the three-way catalysts **511** and **513**. Moreover, the fuel efficiency of the engine **1** improves by introducing the EGR gas into the combustion chamber **17** and making the mixture gas leaner. Note that the middle-to-high load areas **A2**, **A3**, and **A4** correspond to Layer **2** described later. Layer **2** extends to the high load area and includes the maximum load operating state.

(Operation of Supercharger)

Here, as illustrated in the map **504** of FIG. **7**, the supercharger **44** is OFF in part of the low load area **A1** and part of the middle load area **A2** (see S/C OFF). In detail, the supercharger **44** is OFF in an area on the lower engine speed side in the low load area **A1**. In an area on the higher speed side in the low load area **A1**, the supercharger **44** is ON in order to secure a required intake filling amount for the increased speed of the engine **1**. Moreover, the supercharger **44** is OFF in a partial area on the lower load and lower engine speed side in the middle load area **A2**. In the area on the higher load side in the middle load area **A2**, the supercharger **44** is ON in order to secure a required intake filling amount for the increased fuel injection amount. Moreover, the supercharger **44** is ON also in the area on the higher speed side in the middle load area **A2**.

Note that in each area of the high-load middle-speed area **A3**, the high-load low-speed area **A4**, and the high speed area **A5**, the supercharger **44** is entirely ON (see S/C ON). (High Speed Area)

When the speed of the engine **1** increases, a time required for changing the crank angle by  $1^\circ$  becomes shorter. Thus, it becomes difficult to stratify the mixture gas inside the combustion chamber **17**. When the speed of the engine **1** increases, it also becomes difficult to perform the SPCCI combustion.

Therefore, the engine **1** performs not the SPCCI combustion but the SI combustion when the engine **1** operates in the high speed area **A5**. Note that the high speed area **A5** extends entirely in the load direction from the low load to the high load.

The reference numeral **606** of FIG. **8** indicates a fuel injection timing (reference numeral **6061**), an ignition timing (reference numeral **6062**), and a combustion waveform (reference numeral **6063**), when the engine **1** operates in the high speed area **A5** in the operating state **606** where the load is high.

The EGR system **55** introduces the EGR gas into the combustion chamber **17**. The EGR system **55** reduces the amount of the EGR gas as the load increases. The EGR system **55** may not recirculate the EGR gas during full load.

The swirl control valve **56** is fully opened. No swirl flow occurs in the combustion chamber **17**, but only a tumble

flow occurs. By fully opening the swirl control valve **56**, it is possible to increase the filling efficiency, and reduce the pumping loss.

Fundamentally, the air-fuel ratio (A/F) of the mixture gas is the stoichiometric air fuel ratio (A/F $\approx$ 14.7:1) throughout the combustion chamber **17**. The excess air ratio  $\lambda$  of the mixture gas may be set to  $1.0\pm 0.2$ . Note that the excess air ratio  $\lambda$  of the mixture gas may be lower than 1 when the engine **1** operates near full load.

The injector **6** starts the fuel injection during an intake stroke. The injector **6** injects fuel all at once (reference numeral **6061**). By starting the fuel injection in the intake stroke, the homogeneous or substantially homogeneous mixture gas is formed inside the combustion chamber **17**. Moreover, since a longer vaporizing time of the fuel can be secured, unburnt fuel loss can also be reduced.

After the fuel injection is finished, the ignition plug **25** ignites the mixture gas at a suitable timing before a compression top dead center (reference numeral **6062**).

(Layer Structure of Map)

As illustrated in FIG. **9**, the maps **501**, **502**, and **503** of the engine **1** illustrated in FIG. **6** are comprised of a combination of three layers, Layer **1**, Layer **2**, and Layer **3**.

Layer **1** is a layer used as a base layer. Layer **1** extends throughout the operating range of the engine **1**. Layer **1** corresponds to the entire third map **503**.

Layer **2** is a layer which is superimposed on Layer **1**. Layer **2** corresponds to a portion of the operating range of the engine **1**. For example, Layer **2** corresponds to the low-to-middle speed area **B1**, **B2**, and **B3** of the second map **502**.

Layer **3** is a layer which is superimposed on Layer **2**. Layer **3** corresponds to the low load area **A1** of the first map **501**.

Layer **1**, Layer **2**, and Layer **3** are selected according to the wall temperature of the combustion chamber **17** and the intake air temperature.

When the wall temperature of the combustion chamber **17** is higher than a given first wall temperature (e.g.,  $80^\circ\text{C}$ .) and the intake air temperature is higher than a given first intake air temperature (e.g.,  $50^\circ\text{C}$ .), Layer **1**, Layer **2**, and Layer **3** are selected, and the first map **501** is formed by superimposing Layer **1**, Layer **2**, and Layer **3**. In the low load area **A1** in the first map **501**, the top Layer **3** therein becomes effective, in the middle-to-high load areas **A2**, **A3**, and **A4**, the top Layer **2** therein becomes effective, and in the high speed area **A5**, Layer **1** becomes effective.

When the wall temperature of the combustion chamber **17** is lower than the given first wall temperature and higher than a given second wall temperature (e.g.,  $30^\circ\text{C}$ .), and the intake air temperature is lower than the given first intake air temperature and higher than a given second intake air temperature (e.g.,  $25^\circ\text{C}$ .), Layer **1** and Layer **2** are selected. By piling up the Layer **1** and Layer **2**, the second map **502** is formed. The low-to-middle speed area **B1**, **B2**, and **B3** in second map **502**, the top Layer **2** therein becomes effective, and in the high speed area **B4**, Layer **1** becomes effective.

When the wall temperature of the combustion chamber **17** is lower than the given second wall temperature and the intake air temperature is lower than the given second intake air temperature, only Layer **1** is selected to form the third map **503**.

Note that the wall temperature of the combustion chamber **17** may be replaced, for example, by temperature of the coolant of the engine **1** measured by the water temperature sensor **SW10**. Alternatively, the wall temperature of the combustion chamber **17** may be estimated based on the

temperature of the coolant, or other measurements. The intake air temperature is measurable, for example, by the third intake-air temperature sensor SW17 which measures the temperature inside the surge tank 42. Alternatively, the temperature of the intake air introduced into the combustion chamber 17 may be estimated based on various kinds of measurements.

As described above, the SPCCI combustion is performed by generating the strong swirl flow inside the combustion chamber 17. Since the flame propagates along the wall of the combustion chamber 17 during the SI combustion, the flame propagation of the SI combustion is influenced by the wall temperature. If the wall temperature is low, the flame of the SI combustion is cooled to delay the timing of compression ignition.

Since the CI combustion of the SPCCI combustion is performed in the area from the outer circumferential part to the central part of the combustion chamber 17, it is influenced by the temperature in the central part of the combustion chamber 17. If the temperature in the central part is low, the CI combustion becomes unstable. The temperature in the central part of the combustion chamber 17 depends on the temperature of the intake air introduced into the combustion chamber 17. That is, when the intake air temperature is higher, the temperature in the central part of the combustion chamber 17 becomes higher, and when the intake air temperature is lower, the temperature in the central part becomes lower.

When the wall temperature of the combustion chamber 17 is lower than the given second wall temperature and the intake air temperature is lower than the given second intake air temperature, the stable SPCCI combustion cannot be performed. Thus, only Layer 1 which performs the SI combustion is selected, and the ECU 10 operates the engine 1 based on the third map 503. By the engine 1 performing the SI combustion in the entire operating range, the combustion stability can be secured.

When the wall temperature of the combustion chamber 17 is higher than the given second wall temperature and the intake air temperature is higher than the given second intake air temperature, the stable SPCCI combustion of the mixture gas having substantially stoichiometric air fuel ratio (i.e.,  $\lambda \approx 1$ ) can be carried out. Thus, in addition to Layer 1, Layer 2 is selected, and the ECU 10 operates the engine 1 based on the second map 502. By the engine 1 performing the SPCCI combustion in a portion of the operating ranges, the fuel efficiency of the engine 1 improves.

When the wall temperature of the combustion chamber 17 is higher than the given first wall temperature and the intake air temperature is higher than the given first the intake air temperature, the stable SPCCI combustion of the mixture gas leaner than the stoichiometric air fuel ratio can be carried out. Thus, in addition to Layer 1 and Layer 2, Layer 3 is selected, and the ECU 10 operates the engine 1 based on the first map 501. By the engine 1 performing the SPCCI combustion of the lean mixture gas in a portion of the operating ranges, the fuel efficiency of the engine 1 further improves.

Next, one example of control related to the layer selection of the map executed by the ECU 10 will be described with reference to a flowchart of FIG. 10. First, at Step S1 after the control is started, the ECU 10 reads the signals of the sensors SW1-SW17. At the following Step S2, the ECU 10 determines whether the wall temperature of the combustion chamber 17 is 30° C. or higher and the intake air temperature is 25° C. or higher. If the determination at Step S2 is YES, the control shifts the process to Step S3, and on the other

hand, if NO, the control shifts the process to Step S5. The ECU 10 selects only Layer 1 at Step S5. The ECU 10 operates the engine 1 based on the third map 503. The control then returns the process.

At Step S3, the ECU 10 determines whether the wall temperature of the combustion chamber 17 is 80° C. or higher and the intake air temperature is 50° C. or higher. If the determination at Step S3 is YES, the control shifts the process to Step S4, and on the other hand, if NO, the control shifts the process to Step S6.

The ECU 10 selects Layer 1 and Layer 2 at Step S6. The ECU 10 operates the engine 1 based on the second map 502. The control then returns the process.

The ECU 10 selects Layer 1, Layer 2, and Layer 3 at Step S4. The ECU 10 operates the engine 1 based on the first map. The control then returns the process.

(Valve Timing of Intake Valve and Exhaust Valve)

FIG. 11 illustrates one example of a change in the valve open timing IVO of the intake valve 21 when the ECU 10 controls the intake-side electric S-VT 23 according to the control logic set for Layer 2. The upper graph of FIG. 11 (i.e., a graph 1101) illustrates a change of the valve open timing IVO of the intake valve 21 (vertical axis) versus the engine load (horizontal axis). The solid line corresponds to a case where the speed of the engine 1 is a relatively low first engine speed, and a broken line corresponds to a case where the speed of the engine 1 is a relatively high second engine speed (first engine speed < second engine speed).

The lower graph of FIG. 11 (i.e., a graph 1102) illustrates a change of the valve open timing IVO of the intake valve 21 (vertical axis) versus the speed of the engine 1 (horizontal axis). The solid line corresponds to a case where the engine load is a relatively low first load, and the broken line corresponds to a case where the engine load is a relatively high second load (first load < second load).

In the graph 1101 and the graph 1102, the valve open timing IVO of the intake valve 21 is advanced as it goes upward and the positive overlap period where both the intake valve 21 and the exhaust valve 22 open becomes longer. Therefore, the amount of the EGR gas introduced into the combustion chamber 17 increases.

In Layer 2, the engine 1 operates with the A/F of the mixture gas at the stoichiometric air fuel ratio or the substantially stoichiometric air fuel ratio, and the G/F leaner than the stoichiometric air fuel ratio. When the engine load is low, the fuel supply amount decreases. As illustrated in the graph 1101, when the engine load is low, the ECU 10 sets the valve open timing IVO of the intake valve 21 at a timing on the retard side. Thus, the amount of the EGR gas introduced into the combustion chamber 17 is regulated to secure the combustion stability.

Since the fuel supply amount increases when the engine load increases, the combustion stability improves. The ECU 10 sets the valve open timing of the intake valve 21 at a timing on the advance side. The pumping loss of the engine 1 can be lowered by increasing the amount of the EGR gas introduced into the combustion chamber 17.

When the engine load further increases, the temperature inside the combustion chamber 17 further increases. Then, the amount of the internal EGR gas is reduced and the amount of the external EGR gas is increased so that the temperature inside the combustion chamber 17 does not become too high. Therefore, the ECU 10 sets the valve open timing of the intake valve 21 again at a timing on the retard side.

When the engine load further increases and the supercharger 44 starts boosting, the ECU 10 sets the valve open

timing of the intake valve **21** again at a timing on the advance side. Since the positive overlap period where both the intake valve **21** and the exhaust valve **22** open is provided, the residual gas in the combustion chamber **17** can be purged.

Note that when the engine speed is high and low, the tendency of the change in the valve open timing of the intake valve **21** is almost the same.

As illustrated in the graph **1102**, when the engine speed is low, the flow inside the combustion chamber **17** becomes weaker. Since the combustion stability falls, the amount of the EGR gas introduced into the combustion chamber **17** is regulated. The ECU **10** sets the valve open timing of the intake valve **21** at a timing on the retard side.

Since the flow inside the combustion chamber **17** becomes strong when the engine speed increases, the amount of the EGR gas introduced into the combustion chamber **17** can be increased. The ECU **10** sets the valve open timing of the intake valve **21** at a timing on the advance side.

When the engine speed further increases, the ECU **10** sets the valve open timing of the intake valve **21** at a timing on the retard side according to the engine speed. Thus, the amount of gas introduced into the combustion chamber **17** is maximized.

FIG. **12** illustrates one example of a change in the valve open timing IVO of the intake valve **21**, the valve close timing EVC of the exhaust valve **22**, and an overlap period O/L of the intake valve **21** and the exhaust valve **22**, when the ECU **10** controls the intake-side electric S-VT **23** and the exhaust-side electric S-VT **24** according to the control logic set for Layer **3**.

The upper graph of FIG. **12** (i.e., a graph **1201**) illustrates a change in the valve open timing IVO of the intake valve **21** (vertical axis) versus the engine load (horizontal axis). The solid line corresponds to a case where the engine speed is a relatively low third engine speed, and the broken line corresponds to a case where the engine speed is relatively high fourth engine speed (third engine speed < fourth engine speed).

The middle figure of FIG. **12** (i.e., a graph **1202**) illustrates a change in the valve close timing EVC of the exhaust valve **22** (vertical axis) versus the engine load (horizontal axis). The solid line corresponds to a case where the engine speed is at the third engine speed, and the broken line corresponds to a case where the engine speed is at the fourth engine speed.

The lower graph of FIG. **12** (i.e., a graph **1203**) illustrates a change in the overlap period O/L of the intake valve **21** and the exhaust valve **22** (vertical axis) versus the engine load (horizontal axis). The solid line corresponds to a case where the engine speed is at the third engine speed, and the broken line corresponds to a case where the engine speed is at the fourth engine speed.

In Layer **3**, the engine **1** operates by carrying out the SPCCI combustion of the mixture gas with the A/F leaner than the stoichiometric air fuel ratio. When the engine load is low, the fuel supply amount decreases. Thus, the ECU **10** regulates the amount of gas introduced into the combustion chamber **17** so that the A/F of the mixture gas does not become too low. As illustrated in the graph **1201**, the ECU **10** sets the valve open timing IVO of the intake valve **21** at a timing on the retard side of an exhaust top dead center. The valve close timing of the intake valve **21** becomes after an intake bottom dead center, so-called "late close". Moreover, when the engine load is low, the ECU **10** regulates the amount of the internal EGR gas introduced into the com-

5 bustion chamber **17**. As illustrated in the graph **1202**, the ECU **10** sets the valve close timing EVC of the exhaust valve **22** at a timing on the advance side. The valve close timing EVC of the exhaust valve **22** approaches an exhaust top dead center.

Since the fuel supply amount increases when the engine load increases, the ECU **10** does not regulate the amount of gas introduced into the combustion chamber **17**. Moreover, in order to stabilize the SPCCI combustion of the mixture gas leaner than the stoichiometric air fuel ratio, the ECU **10** increases the amount of the internal EGR gas introduced into the combustion chamber **17**. The ECU **10** sets the valve open timing IVO of the intake valve **21** at a timing on the advance side of an exhaust top dead center. Moreover, the ECU **10** sets the valve close timing EVC of the exhaust valve **22** at a timing on the retard side of the exhaust top dead center. As a result, as illustrated in the graph **1203**, when the engine load increases, the overlap period where both the intake valve **21** and the exhaust valve **22** open becomes longer.

When the engine load further increases, the ECU **10** reduces the amount of the internal EGR gas introduced into the combustion chamber **17** so that the temperature inside the combustion chamber **17** does not become too high. The ECU **10** brings the valve close timing EVC of the exhaust valve **22** closer to an exhaust top dead center. Thus, the overlap period of the intake valve **21** and the exhaust valve **22** becomes shorter. Moreover, when the engine load is high and the engine speed is high, the ECU **10** sets the valve open timing of the intake valve **21** on the retard side more than when the engine speed is low. Thus, the amount of gas introduced into the combustion chamber **17** is maximized.

Note that in the low load area surrounded by a one-dot chain line in FIG. **12**, the engine **1** may perform a reduced-cylinder operation in order to improve fuel efficiency. When performing the reduced-cylinder operation, the amount of gas and the internal EGR gas introduced into the combustion chamber **17** are not regulated. As illustrated by a two-dot chain line in the graphs **1201** and **1202**, the ECU **10** may set the valve open timing of the intake valve **21** at a timing on the advance side and the valve close timing of the exhaust valve **22** at a timing on the retard side. (Engine Control Logic)

FIG. **13** is a flowchart illustrating the control logic of the engine **1**. The ECU **10** operates the engine **1** according to the control logic stored in the memory **102**. For example, the ECU **10** determines the operating state of the engine **1** based on the signals of the sensors SW1-SW17, and performs calculations for adjusting properties in the combustion chamber **17**, the injection amount, the injection timing, and the ignition timing so that the combustion in the combustion chamber **17** becomes combustion at the SI ratio according to the operating state.

The ECU **10** first reads the signals of the sensors SW1-SW17 at Step S131. Subsequently, at Step S132, the ECU **10** determines the operating state of the engine **1** based on the signals of the sensors SW1-SW17, and sets a target SI ratio (i.e., a target heat amount ratio). The target SI ratio is set according to the operating state of the engine **1**.

FIG. **14** schematically illustrates one example of a setting of the target SI ratio. When the engine load is low, the ECU **10** sets the target SI ratio low, and on the other hand, when the engine load is high, it sets the target SI ratio high. When the engine load is low, both the reduction of combustion noise and the improvement in fuel efficiency can be achieved by increasing the ratio in the CI combustion to the SPCCI combustion. When the engine load is high, it becomes

advantageous for the reduction of the combustion noise by increasing the ratio of the SI combustion to the SPCCI combustion.

Returning to the flowchart of FIG. 13, the ECU 10 sets the target in-cylinder properties for achieving the target SI ratio setting based on the combustion model stored in the memory 102 at the following Step S133. For example, the ECU 10 sets a target temperature, a target pressure, and target properties in the combustion chamber 17. At Step S134, the ECU 10 sets an opening of the EGR valve 54, an opening of the throttle valve 43, an opening of the air bypass valve 48, an opening of the swirl control valve 56, and phase angles of the intake-side electric S-VT 23, and the exhaust-side electric S-VT 24 (i.e., a valve timing of the intake valve 21 and a valve timing of the exhaust valve 22), which are required for achieving the target in-cylinder properties. The ECU 10 sets the control amounts of these devices based on the map stored in the memory 102. The ECU 10 outputs signals to the EGR valve 54, the throttle valve 43, the air bypass valve 48, the swirl control valve (SCV) 56, the intake-side electric S-VT 23, and the exhaust-side electric S-VT 24 based on the control amount setting. By each device operating based on the signal of the ECU 10, the properties in the combustion chamber 17 become the target properties.

The ECU 10 further calculates predicted values or estimated values of the properties in the combustion chamber 17 based on the control amount setting of each device. The predicted property value is a predicted value of the property in the combustion chamber 17 before the intake valve 21 is closed. The predicted property value is used for setting of the fuel injection amount during the intake stroke as will be described later. The estimated property value is an estimated value of the property in the combustion chamber 17 after the intake valve 21 is closed. The estimated property value is used for setting of the fuel injection amount during a compression stroke, and setting of the ignition timing, as will be described later. The estimated property value is also used for calculation of a property error of comparison with an actual combustion state.

At Step S135, the ECU 10 is sets a fuel injection amount in the intake stroke based on the predicted property value. When performing a divided injection during the intake stroke, the ECU 10 sets the injection amount of each injection. Note that when fuel is not injected in the intake stroke, the injection amount of fuel is zero. At Step S136, the ECU 10 outputs a signal to the injector 6 so that the injector 6 injects fuel into the combustion chamber 17 at given injection timing(s).

At Step S137, the ECU 10 is sets a fuel injection amount in a compression stroke based on the estimated property value and the injection result of the fuel in the intake stroke. Note that when fuel is not injected in the compression stroke, the injection amount of fuel is zero. At Step S138, the ECU 10 outputs a signal to the injector 6 so that the injector 6 injects fuel into the combustion chamber 17 at an injection timing based on the preset map.

At Step S139, the ECU 10 sets an ignition timing based on the estimated property value and the injection result of the fuel in the compression stroke. At Step S1310, the ECU 10 outputs a signal to the ignition plug 25 so that the ignition plug 25 ignites the mixture gas inside the combustion chamber 17 at the set ignition timing.

By the ignition plug 25 igniting the mixture gas, the SI combustion or the SPCCI combustion is performed inside the combustion chamber 17. At Step S1311, the ECU 10 reads the change in the pressure inside the combustion chamber 17 measured by the pressure indicating sensor

SW6, and based on the change, the ECU 10 determines a combustion state of the mixture gas inside the combustion chamber 17. At Step S1312, the ECU 10 compares the measurement result of the combustion state with the estimated property values estimated at Step S134, and calculates an error between the estimated properties value and the actual properties. The calculated error is used for the estimation at Step S134 in the subsequent cycles. The ECU 10 adjusts the openings of the throttle valve 43, the EGR valve 54, the swirl control valve 56, and/or the air bypass valve 48, and the phase angles of the intake-side electric S-VT 23 and the exhaust-side electric S-VT 24 so as to eliminate the property error. Thus, the amount of the fresh air and the EGR gas introduced into the combustion chamber 17 are adjusted.

If the ECU 10 estimates that the temperature inside the combustion chamber 17 will be lower than the target temperature again based on the estimated property values, it advances, at Step S138, the injection timing in the compression stroke more than the injection timing based on the map so that the advancing of the ignition timing becomes possible. On the other hand, if ECU 10 estimates that the temperature inside the combustion chamber 17 will be higher than the target temperature based on the estimated property values, it retards, at Step S138, the injection timing in the compression stroke more than the injection timing based on the map so that the retarding of the ignition timing becomes possible.

That is, if the temperature inside the combustion chamber 17 is low, a self-ignition timing  $\theta_{CI}$  (see FIG. 5) of the unburnt mixture gas is delayed after the SI combustion begins by jump-spark ignition, which deviates the SI ratio from the target SI ratio. In this case, an increase in the unburnt fuel and a decrease in emission performance will be caused.

Thus, when the ECU 10 estimates that the temperature inside the combustion chamber 17 will be lower than the target temperature, it advances the injection timing, and advances the ignition timing at Step S1310. Since the heat release which is sufficient for the SI combustion becomes possible by the start of the SI combustion is made earlier, it can prevent that the self-ignition timing  $\theta_{CI}$  of the unburnt mixture gas is delayed when the temperature inside the combustion chamber 17 is low. As a result, the SI ratio approaches the target SI ratio.

On the other hand, when the temperature inside the combustion chamber 17 is high, the unburnt mixture gas will carry out the self ignition shortly after SI combustion begins by the jump-spark ignition, which deviates the SI ratio from the target SI ratio. In this case, the combustion noise increases.

Thus, when the ECU 10 estimates that the temperature inside the combustion chamber 17 will be higher than the target temperature, it retards the injection timing, and retards the ignition timing at Step S1310. Since the start of SI combustion is delayed, when the temperature inside the combustion chamber 17 is high, it can be prevented that the self-ignition timing  $\theta_{CI}$  of the unburnt mixture gas becomes early. As a result, the SI ratio approaches the target SI ratio.

The control logic of the engine 1 is configured to adjust the SI ratio by using a property setting device including the throttle valve 43, the EGR valve 54, the air bypass valve 48, the swirl control valve 56, the intake-side electric S-VT 23, and the exhaust-side electric S-VT 24. By adjusting the properties in the combustion chamber 17, a rough adjustment of the SI ratio is possible. The control logic of the engine 1 is also configured to adjust the SI ratio by adjusting the injection timing and the ignition timing of fuel. By

adjusting the injection timing and the ignition timing, a difference between the cylinders can be corrected, and a fine adjustment of the self-ignition timing can be performed, for example. By adjusting the SI ratio by two steps, the engine 1 can achieve the target SPCCI combustion accurately

The ECU 10 also outputs signals to at least the EGR system 55 and the ignition plug 25 so that the actual SI ratio by combustion becomes the target SI ratio. Moreover, as described above, when the engine load is high, since the ECU 10 makes the target SI ratio higher than when the load is low, it then outputs the signals to at least the EGR system 55 and the ignition plug 25 when the engine load is high so that the SI ratio becomes higher than when the load is low.

Note that the control of the engine 1 executed by the ECU 10 is not limited to the control logic based on the combustion model described above.

(Method of Implementing Control Logic of Engine)

When implementing the control logic of the engine 1 for performing the SPCCI combustion described above, the parameter related to the control amount of each device is set. For example, if the device is the ignition plug 25, ignition energy and the ignition timing corresponding to the operating state of the engine 1 are set. If the device is the intake-side electric S-VT 23, the valve timing of the intake valve 21 corresponding to the operating state of the engine 1 is set. Below, the setting of the valve timing of the intake valve 21 in the method of implementing the control logic of the engine 1 will be described with reference to the drawings.

(1) Implementing Method According to Valve Close Timing of Intake Valve

In the engine 1 for executing the SPCCI combustion, in order to reduce the combustion noise and achieve the stable SPCCI combustion, the present inventors found out that it was necessary to adjust the temperature inside the combustion chamber 17 to a suitable temperature at the start timing in the CI combustion (00: see FIG. 5). That is, when the temperature inside the combustion chamber 17 is low, the ignitability in the CI combustion falls. When the temperature inside the combustion chamber 17 is high, the combustion noise increases.

The temperature inside the combustion chamber 17 at the start timing  $\theta_{CI}$  in the CI combustion is mainly related to the effective compression ratio of the engine 1. The effective compression ratio of the engine 1 is determined by the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21. In order to put the engine for executing the SPCCI combustion into practical use, the present inventors newly found that a suitable IVC range existed within a range of the geometric compression ratio  $\epsilon$  where the SPCCI combustion may occur. The technology disclosed herein is novel in that a given relationship was found out between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21, where the given relationship is required in order to put to practical use the engine which performs the unique combustion mode that is the SPCCI combustion. In addition, a relational expression between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21, which will be described later, is also novel.

Further, the technology disclosed herein is also novel in that, when implementing the control logic of the engine 1 for executing the SPCCI combustion, the valve close timing IVC of the intake valve 21 is set based on the relationship between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21.

The engine 1 switches between "Layer 2" where the SPCCI combustion is performed with the A/F of the mixture gas being made at the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio and the G/F being made leaner than the stoichiometric air fuel ratio, and "Layer 3" where the SPCCI combustion is performed with the A/F of the mixture gas being made leaner than the stoichiometric air fuel ratio. The relationship between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21 in Layer 2 differs from the relationship between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21 in Layer 3.

(1-1) Relationship Between Geometric Compression Ratio and Valve Close Timing of Intake Valve in Layer 2

FIG. 15 illustrates the characteristic of SPCCI combustion. For example, FIG. 15 illustrates the occurring range of the SPCCI combustion against the EGR rate (horizontal axis) in a case where the engine 1 carries out the SPCCI combustion of the mixture gas of which the A/F is the stoichiometric air fuel ratio and the G/F is leaner than the stoichiometric air fuel ratio, similar to Layer 2. The vertical axis in this graph is a crank angle corresponding to a combustion center of gravity, where the combustion center of gravity advances as it goes upward in this graph.

The occurring range of the SPCCI combustion is illustrated by a hatched range in this graph. The occurring range of the SPCCI combustion is located between a line of "advancing limit" and a line of "retarding limit." If the combustion center of gravity advances beyond the "advancing limit" line, combustion becomes abnormal, which means that the SPCCI combustion does not occur. Similarly, if the combustion center of gravity retards beyond the "retarding limit" line, self ignition does not occur, which means that the SPCCI combustion does not occur.

The one-dot chain line in this graph illustrates the combustion center of gravity of combustion corresponding to MBT (Minimum advance for Best Torque). Here, the combustion center of gravity of combustion corresponding to MBT is simply referred to as "MBT." MBT is advanced as the EGR rate increases.

In terms of the improvement in the fuel efficiency, it is desirable to bring the combustion center of gravity of the SPCCI combustion closer to the MBT. As the EGR rate increases, the occurring range of the SPCCI combustion is advanced, but the interval between the "advancing limit" line and the "retarding limit" line becomes narrower, which narrows the occurring range of the SPCCI combustion.

When the engine load is low (when "light load"), the occurring range of the SPCCI combustion is on the advance side. Therefore, as illustrated by a both-ends arrow in FIG. 15, the SPCCI combustion corresponding to the MBT can be achieved by adjusting the EGR rate within a certain width, and adjusting the combustion center of gravity to the advance side or the retard side.

When the engine load increases, the amount of air introduced into the combustion chamber 17 must be increased corresponding to the increase in the fuel supply amount. When the EGR rate is increased corresponding to the increase in the air amount, a large amount of the EGR gas must be introduced into the combustion chamber 17. However, because of the limit of the supercharging capability of the supercharger 44, it is difficult to introduce both the large amount of air and the large amount of the EGR gas into the combustion chamber 17. Therefore, when the engine load increases, the occurring range of the SPCCI combustion becomes on the retard side. If bringing the combustion center of gravity of the SPCCI combustion closest to the

MBT when the engine load is high, the SPCCI combustion must be performed at a point Y in FIG. 15. The point Y corresponds to the operating state of the engine 1 with the maximum load where the SPCCI combustion of the mixture gas with the A/F being at the stoichiometric air fuel ratio is possible. When the engine 1 operates with the maximum load, it is difficult to achieve the SPCCI combustion corresponding to the MBT by adjusting the EGR rate or the combustion center of gravity.

The engine 1 operates over a wide operating range from the low load to the high load in Layer 2. In Layer 2, the state where the engine 1 operates with the maximum load corresponds to the operating state at the limit where the SPCCI combustion can occur. In Layer 2, upon determining the relationship between  $\epsilon$  and IVC so that the temperature of the combustion chamber 17 at the start timing ( $\theta_{CI}$ ) in the CI combustion becomes the given temperature, it is necessary to set the relationship based on the temperature inside the combustion chamber 17 when the engine 1 operates with the maximum load.

In order to obtain the temperature inside the combustion chamber 17 when the engine 1 operates with the maximum load, the present inventors performed the SPCCI combustion in an actual engine 1, and used measurements acquired from the engine 1. For example, the present inventors measured various parameters when the engine 1 operates with the maximum load in Layer 2, and estimated an actual temperature inside the combustion chamber 17 at  $\theta_{CI}$  based on the measured parameter. The present inventors used an average value of a plurality of estimated temperatures as a reference temperature Tth1. If the temperature of the combustion chamber 17 at  $\theta_{CI}$  is the reference temperature Tth1, the SPCCI combustion can be achieved in Layer 2.

Here, as described above,  $\theta_{CI}$  can be adjusted by adjusting the ignition timing in the SPCCI combustion. However, while the engine 1 operates with the maximum load in Layer 2, it becomes impossible to adjust  $\theta_{CI}$  even if the ignition timing is adjusted when the temperature inside the combustion chamber 17 at  $\theta_{CI}$  exceeds the reference temperature Tth1. On the other hand, if the temperature inside the combustion chamber 17 at  $\theta_{CI}$  is the reference temperature Tth1 or lower, the ignition timing is adjusted (e.g., the ignition timing is advanced) to raise the temperature inside the combustion chamber 17 at  $\theta_{CI}$  to the reference temperature Tth1, thereby achieving the SPCCI combustion.

Therefore, in order to achieve SPCCI combustion in Layer 2, the relationship between  $\epsilon$  and IVC so that the temperature of the combustion chamber 17 at  $\theta_{CI}$  does not exceed the reference temperature Tth1 is required.

Thus, as conceptually illustrated in FIG. 16, the present inventors performed an estimation of the temperature of the combustion chamber 17 at  $\theta_{CI}$  by using a model of the engine 1, while changing the values of the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21 in a matrix comprised of the two parameters of  $\epsilon$  and IVC. A combination of  $\epsilon$  and IVC where the temperature of the combustion chamber 17 becomes the reference temperature Tth1 or lower can achieve the SPCCI combustion in Layer 2. As illustrated in FIG. 16, when the geometric compression ratio  $\epsilon$  is high and the valve close timing IVC of the intake valve 21 approaches an intake bottom dead center, the temperature of the combustion chamber 17 during CI combustion exceeds the reference temperature Tth1.

Note that FIG. 16 illustrates the matrix where IVC is set after the intake bottom dead center. Although illustration is omitted, the present inventors also acquired a combination

of and IVC where the temperature becomes the reference temperature Tth1 or lower, by performing an estimation of the temperature of the combustion chamber 17 at  $\theta_{CI}$ , similarly for the matrix where IVC is set before the intake bottom dead center.

A graph 1701 of the upper graph in FIG. 17 illustrates approximations (approx.) (I) and (II) calculated based on the combination of  $\epsilon$  and IVC. The horizontal axis of the graph 1701 is the geometric compression ratio  $\epsilon$ , and the vertical axis is the valve close timing IVC (deg.aBDC) of the intake valve 21. Although illustration is omitted, the present inventors plotted on the graph 1701 the combination of  $\epsilon$  and IVC where the temperature becomes the reference temperature Tth1 or lower, and determined the approximations (I) and (II) based on the plots.

The graph 1701 corresponds to a case where the engine speed is 2,000 rpm. The approximations (I) and (II) are as follows.

$$IVC = -0.4288\epsilon^2 + 31.518\epsilon - 379.88 \quad \text{Approximation (I):}$$

$$IVC = 1.9163\epsilon^2 - 89.935\epsilon + 974.94 \quad \text{Approximation (II):}$$

In the graph 1701, the combination of  $\epsilon$  and IVC on the left side of the approximations (I) and (II) and  $\epsilon=17$ , the temperature of the combustion chamber 17 during the CI combustion becomes the reference temperature Tth1 or lower. In this combination, it is possible to carry out the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio and the G/F being leaner than the stoichiometric air fuel ratio.

The relationship between  $\epsilon$  and IVC described above is a relationship based on the maximum temperature of the combustion chamber 17 in Layer 2.

On the other hand, in Layer 2, also while the engine 1 operates with the light load, the relationship between  $\epsilon$  and IVC must be defined so that the temperature of the combustion chamber 17 becomes the given temperature.

The temperature of the combustion chamber 17 when the SPCCI combustion is performed is a result of two pressure buildups of a pressure buildup by the compression work of the piston 3 in a compression stroke, and the pressure buildup caused by the heat generation of the SI combustion. The compression work of the piston 3 is determined by the effective compression ratio. If the effective compression ratio is too low, the pressure buildup by the compression work of the piston 3 decreases. Unless the pressure buildup, which is caused by the heat generation of the SI combustion after the flame propagation in the SPCCI combustion progresses, increases considerably, the in-cylinder temperature cannot be raised to an ignition temperature. As a result, since the amount of the mixture gas which is ignited by the compressed self ignition is little, and most of the mixture gas burn by flame propagation, the combustion period becomes longer and fuel efficiency decreases. In order to stabilize the CI combustion in the SPCCI combustion and maximize fuel efficiency, it is necessary to maintain the effective compression ratio above a certain value. Therefore, the relationship between  $\epsilon$  and IVC must be determined accordingly.

Similarly, the present inventors measured various parameters when the actual engine 1 operates with the light load, and estimated an actual temperature inside the combustion chamber 17 at  $\theta_{CI}$  based on the measured parameters. The present inventors used an average value of a plurality of estimated temperatures as a reference temperature Tth2.

If the temperature inside the combustion chamber 17 at  $\theta_{CI}$  is the reference temperature Tth2 or higher while the engine 1 operates with the light load, the SPCCI combustion

can be achieved by delaying the ignition timing. However, since the temperature of the combustion chamber 17 is too low if the temperature at  $\theta_{CI}$  is lower than the reference temperature  $T_{th2}$ , the SPCCI combustion cannot be achieved even if the ignition timing is advanced.

Thus, in order to achieve the SPCCI combustion in Layer 2, a relationship between and IVC so that the temperature of the combustion chamber 17 at  $\theta_{CI}$  becomes the reference temperature  $T_{th2}$  or higher is required.

The present inventors performed an estimation of the temperature of the combustion chamber 17 during CI combustion by using a model of the engine 1, while changing the values of the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve 21 in a matrix comprised of two parameters of  $\epsilon$  and IVC, similarly to the matrix illustrated in FIG. 16. In this matrix, the combination of  $\epsilon$  and IVC where the temperature of the combustion chamber 17 becomes the reference temperature  $T_{th2}$  or higher can achieve the SPCCI combustion in Layer 2.

In the graph 1701 of FIG. 17, approximations (III) and (IV) calculated based on the combination of  $\epsilon$  and IVC where the temperature becomes the reference temperature  $T_{th2}$  or higher are also illustrated. The approximations (III) and (IV) are as follows.

$$IVC = -0.4234\epsilon^2 + 22.926\epsilon - 167.84 \quad \text{Approximation (III):}$$

$$IVC = 0.4234\epsilon^2 - 22.926\epsilon + 207.84 \quad \text{Approximation (IV):}$$

In the graph 1701, the combination of  $\epsilon$  and IVC on the right side of the approximations (III) and (IV), the temperature of the combustion chamber 17 during CI combustion becomes the reference temperature  $T_{th2}$  or higher. In this combination, the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio and the G/F being leaner than the stoichiometric air fuel ratio is possible.

As seen in FIG. 17, the relationship between  $\epsilon$  and IVC is substantially vertically symmetrical with respect to  $IVC = \text{about } 20 \text{ deg.aBDC}$ .  $IVC = 20 \text{ deg.aBDC}$  corresponds to a valve close timing (i.e., the best IVC) at which the amount of gas introduced into the combustion chamber 17 becomes the maximum when the engine speed is 2,000 rpm. Moreover,  $IVC = 120 \text{ deg.aBDC}$  is a retarding limit of the valve close timing IVC of the intake valve 21, and  $IVC = -80 \text{ deg.aBDC}$  is an advancing limit of the valve close timing IVC of the intake valve 21.

The combination of  $\epsilon$  and IVC within a range surrounded by the approximations (I), (II), (III), and (IV) in FIG. 17 is a combination which can put to practical use the engine 1 for executing the SPCCI combustion in Layer 2. In other words, the combination of  $\epsilon$  and IVC outside this range cannot put the engine 1 to practical use for executing the SPCCI combustion in Layer 2.

The design engineer has to determine IVC within the  $\epsilon$ -IVC valid range hatched in FIG. 17, upon determining the valve close timing IVC of the intake valve 21 when the engine 1 operates in Layer 2.

For example, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 17$ , the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 22.926\epsilon + 207.84 \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 167.84 \quad (1)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $17 \leq \epsilon < 20$ , the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 379.88 \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 167.84 \quad (2)$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 207.84 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 974.94 \quad (3)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 30$ , the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 379.88 \leq IVC \leq 120 \quad (4)$$

or

$$-80 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 974.94 \quad (5)$$

By setting the valve close timing IVC of the intake valve 21 based on the relational expressions (1) to (5), the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio and the G/F being leaner than the stoichiometric air fuel ratio is achieved. Note that the valve close timing IVC is set for each operating state which is determined by the load and the engine speed in Layer 2. The example illustrated by the solid line in FIG. 17 is the  $\epsilon$ -IVC valid range when the engine speed is 2,000 rpm, as described above. If the engine speed changes, the  $\epsilon$ -IVC valid range also changes. As the engine speed increases, the best IVC is retarded.

For example, when the engine speed is 3,000 rpm, the best IVC is about 22 deg.aBDC. As illustrated by broken lines in FIG. 17, the  $\epsilon$ -IVC valid range when the engine speed is 3,000 rpm can be obtained by parallelly translating the  $\epsilon$ -IVC valid range when the engine speed is 2,000 rpm to the retard side by about 2 deg.

Therefore, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 17$ , when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 22.926\epsilon + 209.84 \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 165.84 \quad (1^{-1})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $17 \leq \epsilon < 20$ , when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 377.88 \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 165.84 \quad (2^{-1})$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 209.84 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 976.94 \quad (3^{-1})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 30$ , the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 377.88 \leq IVC \leq 120 \quad (4^{-1})$$

or

$$-80 \leq IVC \leq 1.9163\epsilon^2 - 87.935\epsilon + 976.94 \quad (5^{-1})$$

Moreover, when the engine speed is 4,000 rpm, the best IVC is about 28 deg.aBDC. As illustrated by one-dot chain lines in FIG. 17, the  $\epsilon$ -IVC valid range when the engine

35

speed is 4,000 rpm is obtained by parallelly translating the  $\epsilon$ -IVC valid range when the engine speed is 2,000 rpm to the retard side by about 8 deg.

Therefore, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 17$ , when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 22.926\epsilon + 215.84 \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 159.84 \quad (1^{-2})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $17 \leq \epsilon < 20$ , when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 371.88 \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 159.84 \quad (2^{-2})$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 215.84 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 982.94 \quad (3^{-2})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon \leq 30$ , the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 371.88 \leq IVC \leq 120 \quad (4^{-2})$$

or

$$-80 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 982.94 \quad (5^{-2})$$

If a correction term C according to the engine speed NE (rpm) of the engine 1 is set as the following,

$$C = 3.3 \times 10^{-10} NE^3 - 1.0 \times 10^{-6} NE^2 + 7.0 \times 10^{-4} NE$$

the relational expression of  $\epsilon$  and IVC in Layer 2 can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 17$ ,

$$0.4234\epsilon^2 - 22.926\epsilon + 207.84 + C \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 167.84 + C \quad (1^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $17 \leq \epsilon < 20$ ,

$$0.4288\epsilon^2 + 31.518\epsilon - 379.88 + C \leq IVC \leq -0.4234\epsilon^2 + 22.926\epsilon - 167.84 + C \quad (2^{-3})$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 207.84 + C \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 974.94 + C \quad (3^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $20 \leq \epsilon \leq 30$ ,

$$-0.4288\epsilon^2 + 31.518\epsilon - 379.88 + C \leq IVC \leq 120 \quad (4^{-3})$$

or

$$-80 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 974.94 + C \quad (5^{-3})$$

The design engineer determines the valve close timing IVC based on the  $\epsilon$ -IVC valid range determined for every engine speed of the engine 1. As a result, the design engineer can set the valve timing of the intake valve 21 in Layer 2 as illustrated in FIG. 11.

(1-2) Change in  $\epsilon$ -IVC Valid Range by Difference of Octane Number

The graph 1701 in FIG. 17 is a relationship between  $\epsilon$  and IVC when the fuel is the high octane fuel (octane number is about 96). A graph 1702 illustrated in the lower graph is a relationship between  $\epsilon$  and IVC when the fuel is the low octane fuel (octane number is about 91). According to the examination of the present inventors, when the fuel was the

36

low octane fuel, it was found that the  $\epsilon$ -IVC valid range shifts by 1.3 compression ratios toward the lower compression ratio from the  $\epsilon$ -IVC valid range of the high octane fuel.

Accordingly, upon determining the valve close timing IVC in the engine 1 of the low octane fuel, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 15.7$ , when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 21.826\epsilon + 178.75 \leq IVC \leq -0.4234\epsilon^2 + 21.826\epsilon - 138.75 \quad (6)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $15.7 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2 + 34.859\epsilon - 377.22 \leq IVC \leq -0.4234\epsilon^2 + 21.826\epsilon - 138.75 \quad (7)$$

or

$$0.4234\epsilon^2 - 21.826\epsilon + 178.75 \leq IVC \leq 1.9211\epsilon^2 - 85.076\epsilon + 862.01 \quad (8)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon \leq 30$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2 + 34.859\epsilon - 377.22 \leq IVC \leq 120 \quad (9)$$

or

$$-80 \leq IVC \leq 1.9211\epsilon^2 - 85.076\epsilon + 862.01 \quad (10)$$

The cross-hatched range in the graph 1702 of FIG. 17 is an overlapping range of the  $\epsilon$ -IVC valid range of the high octane fuel and the  $\epsilon$ -IVC valid range of the low octane fuel. The design engineer can set the control logic which suits both the engine 1 using the high octane fuel and the engine 1 using the low octane number fuel, if IVC is determined within the overlapping range of the two valid ranges. Even if the octane number of fuel differs for every destination of this product, the design engineer can collectively implement the engine control logic. This package design has an advantage which lessens the design time and labor.

Note that although illustration is omitted, the  $\epsilon$ -IVC valid range is parallelly translated to the retard side also in the engine 1 of the low octane number fuel, when the engine speed increases. If the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 15.7$  in the engine 1 of the low octane number fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 21.826\epsilon + 180.75 \leq IVC \leq -0.4234\epsilon^2 + 21.826\epsilon - 136.75 \quad (6^{-1})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $15.7 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2+34.859\epsilon-375.22\leq IVC\leq-0.4234\epsilon^2+21.826\epsilon-136.75 \quad (7^{-1})$$

or

$$0.4234\epsilon^2-21.826\epsilon+180.75\leq IVC\leq 1.9211\epsilon^2-85.076\epsilon+864.01 \quad (8^{-1})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7\leq\epsilon\leq 30$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2+34.859\epsilon-375.22\leq IVC\leq 120 \quad (9^{-1})$$

or

$$-80\leq IVC\leq 1.9211\epsilon^2-85.076\epsilon+864.01 \quad (10^{-1})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $10\leq\epsilon<15.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.4234\epsilon^2-21.826\epsilon+186.75\leq IVC\leq-0.4234\epsilon^2+21.826\epsilon-130.75 \quad (6^{-2})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $15.7\leq\epsilon<18.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2+34.859\epsilon-369.22\leq IVC\leq-0.4234\epsilon^2+21.826\epsilon-130.75 \quad (7^{-2})$$

or

$$0.4234\epsilon^2-21.826\epsilon+186.75\leq IVC\leq 1.9211\epsilon^2-85.076\epsilon+870.01 \quad (8^{-2})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7\leq\epsilon\leq 30$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2+34.859\epsilon-369.22\leq IVC\leq 120 \quad (9^{-2})$$

or

$$-80\leq IVC\leq 1.9211\epsilon^2-77.076\epsilon+870.01 \quad (10^{-2})$$

If the correction term C according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and IVC in Layer 2 in the engine 1 of the low octane fuel can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10\leq\epsilon<15.7$ ,

$$0.4234\epsilon^2-21.826\epsilon+178.75+C\leq IVC\leq-0.4234\epsilon^2+21.826\epsilon-138.75+C \quad (6^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $15.7\leq\epsilon<18.7$ ,

$$-0.5603\epsilon^2+34.859\epsilon-377.22+C\leq IVC\leq-0.4234\epsilon^2+21.826\epsilon-138.75+C \quad (7^{-3})$$

or

$$0.4234\epsilon^2-21.826\epsilon+178.75+C\leq IVC\leq 1.9211\epsilon^2-85.076\epsilon+862.01+C \quad (8^{-3})$$

If the geometric compression ratio is  $18.7\leq\epsilon\leq 30$ ,

$$-0.5603\epsilon^2+34.859\epsilon-377.22+C\leq IVC\leq 120 \quad (9^{-3})$$

or

$$-80\leq IVC\leq 1.9211\epsilon^2-85.076\epsilon+862.01+C \quad (10^{-3})$$

(1-3) Relationship Between Geometric Compression Ratio and Valve Close Timing of Intake Valve in Layer 3

FIG. 18 illustrates the characteristic of the SPCCI combustion when the engine 1 carries out the SPCCI combustion of the mixture gas where the A/F is leaner than the stoichiometric air fuel ratio, similar to Layer 3. FIG. 18 illustrates a range where the SPCCI combustion is stable with respect to the G/F (horizontal axis). The vertical axis in this graph is a crank angle corresponding to a combustion center of gravity, and the combustion center of gravity is advanced as it goes upward in this graph.

The range where the SPCCI combustion is stabilized is a range surrounded by a curve in this graph. When the engine load is low, the range where the SPCCI combustion is stabilized is located at upper left in FIG. 18. When the engine load increases, the range where the SPCCI combustion is stabilized moves downwardly in FIG. 18.

FIG. 18 also illustrates a range where discharge of raw  $\text{NO}_x$  can be reduced. The range where the discharge of raw  $\text{NO}_x$  can be reduced is located at lower right in FIG. 18. This range has a triangular shape in FIG. 18. If the A/F is leaner than the stoichiometric air fuel ratio, raw  $\text{NO}_x$  cannot be purified by the three-way catalyst. In Layer 3, the engine 1 must satisfy both securing of the stability of the SPCCI combustion and reduction of the discharge of raw  $\text{NO}_x$ .

As seen in this graph, if the engine load is high, an overlapping area of the range where the combustion stability is secured and the range where the discharge of raw  $\text{NO}_x$  can be reduced increases. On the other hand, if the engine load is low, the overlapping area of the range where the combustion stability is secured and the range where the discharge of raw  $\text{NO}_x$  can be reduced decreases.

Regarding Layer 3, the state where the engine 1 operates with the light load corresponds to a limit of the operating state where the SPCCI combustion can occur. Regarding Layer 3, upon determining the relationship between  $\epsilon$  and IVC so that the temperature of the combustion chamber 17 at the start timing ( $\theta_{CI}$ ) of the CI combustion becomes the given temperature, it is necessary to be set based on the temperature inside the combustion chamber 17 when the engine 1 operates with the light load.

Similar to above, using the actual engine 1, the present inventors measured various parameters when operating the engine 1 with the light load in Layer 3, and estimated an actual temperature inside the combustion chamber 17 at  $\theta_{CI}$  based on the measured parameters. Then, an average value of a plurality of estimated temperatures was determined as a reference temperature Tth3. If the temperature of the combustion chamber 17 at  $\theta_{CI}$  is the reference temperature Tth3, the SPCCI combustion can be achieved in Layer 3. This reference temperature Tth3 corresponds to the minimum temperature. If the temperature inside the combustion chamber 17 at  $\theta_{CI}$  is the reference temperature Tth3 or higher while the engine 1 operates with the light load, the SPCCI combustion can be achieved by delaying the ignition timing. However, if the temperature inside the combustion chamber 17 at  $\theta_{CI}$  is lower than the reference temperature Tth3, the SPCCI combustion cannot be achieved even if the ignition timing is advanced.

Therefore, in order to achieve the stable SPCCI combustion in Layer 3, the relationship between  $\epsilon$  and IVC so that the temperature inside the combustion chamber 17 at  $\theta_{CI}$  becomes the reference temperature Tth3 or higher is required.

Thus, as conceptually illustrated in FIG. 19, the present inventors estimated the temperature of the combustion chamber 17 during the CI combustion by using the model of the engine 1, while changing the values of IVC and O/L in a matrix of the valve close timing IVC of the intake valve 21 and the overlap period O/L of the intake valve 21 and the exhaust valve 22, for every geometric compression ratio  $\epsilon$  ( $\epsilon 1, \epsilon 2 \dots$ ) (reference numeral 1901). As hatched in the matrix of the reference numeral 1901, a combination of IVC and O/L where the temperature becomes the reference temperature Tth3 or higher can achieve the SPCCI combustion in Layer 3.

Moreover, in order to reduce the discharge of raw  $\text{NO}_x$ , the G/F of the mixture gas must be made a given value or higher. As illustrated by a reference numeral 1902 in FIG. 19, the present inventors estimated the G/F by using the model of the engine 1, while changing the values of the valve close timing IVC and the overlap period O/L in the matrix comprised of the two parameters of IVC and O/L. As oblique lines are drawn in the matrix of the reference numeral 1902, the combination of IVC and O/L where the G/F becomes the given value or higher can reduce the discharge of raw  $\text{NO}_x$ .

Then, the present inventors determined the relationship between  $\epsilon$  and IVC which can achieve both the stability of the SPCCI combustion and the reduction of raw  $\text{NO}_x$  discharge, by overlapping the combination of IVC and O/L where the temperature becomes the reference temperature Tth3 or higher which is illustrated by the reference numeral 1901, and the combination of IVC and O/L where the G/F becomes the given value or higher which is illustrated by the reference numeral 1902. That is, in the matrix of a reference numeral 1903, a cross-hatched range is the combination of  $\epsilon$  and IVC which can achieve both the stability of the SPCCI combustion and the reduction of  $\text{NO}_x$  discharge.

Note that although illustration is omitted, the present inventors acquired a combination of IVC and O/L where the temperature becomes the reference temperature Tth3 or higher and a combination of IVC and O/L where the G/F becomes the given value or higher by estimating the temperature of the combustion chamber 17 and the G/F during the CI combustion, similarly for the matrix where the valve close timing of the intake valve 21 is set before the intake bottom dead center.

FIG. 20 illustrates approximations (V) and (VI) calculated based on the combinations of  $\epsilon$  and IVC. The horizontal axis in FIG. 20 is the geometric compression ratio  $\epsilon$ , and the vertical axis is the valve close timing IVC (deg. aBDC) of the intake valve 21.

The upper graph 2001 of FIG. 20 corresponds to a case when the engine speed is 2,000 rpm. The approximations (V) and (VI) are as follows.

$$IVC=0.9949\epsilon^2+41.736\epsilon-361.16 \quad \text{Approximation (V):}$$

$$IVC=0.9949\epsilon^2-41.736\epsilon+401.16 \quad \text{Approximation (VI):}$$

In FIG. 20, the combinations of  $\epsilon$  and IVC on the right side of the approximations (V) and (VI) have the temperature of the combustion chamber 17 during CI combustion becoming the reference temperature Tth3 or higher, thereby achieving the SPCCI combustion of the mixture gas with the A/F being leaner than the stoichiometric air fuel ratio.

In Layer 3, the relationship between  $\epsilon$  and IVC described above is a relationship based on the minimum temperature of the combustion chamber 17 which can achieve the SPCCI combustion when the engine 1 operates with the light load.

On the other hand, if the temperature inside the combustion chamber 17 is too high, the CI combustion begins before the start of the SI combustion and the SPCCI combustion cannot be performed, regardless of Layer 2 or Layer 3.

Here, the concept of the SPCCI combustion is such that, as described above, when the ignition plug 25 ignites the mixture gas, the mixture gas around the ignition plug 25 starts the SI combustion, and, after that, surrounding mixture gas carries out the CI combustion. From the examinations by experiments, etc. which the present inventors conducted until now, it was found that the self ignition of the mixture gas occurred when the surrounding temperature of the mixture gas which self-ignites exceeds a given reference temperature Tth4, and this reference temperature Tth4 was not necessarily in agreement with a mean temperature of the entire combustion chamber 17. From this knowledge, if the mean temperature inside the combustion chamber 17 at a compression top dead center reaches the reference temperature Tth4, it is thought that the CI combustion will begin before the SI combustion begins, and in this case, the SPCCI combustion cannot be performed.

Thus, the present inventors estimated the temperature of the combustion chamber 17 at the compression top dead center by using the model of the engine 1, while changing the values of the valve close timing IVC and the overlap period O/L in the matrix of the valve close timing IVC of the intake valve 21, and the overlap period O/L of the intake valve 21 and the exhaust valve 22, for every geometric compression ratio  $\epsilon$  ( $\epsilon 1, \epsilon 2 \dots$ ), similar to the matrix of the reference numeral 1901 of FIG. 19. The combination of IVC and O/L where the temperature inside the combustion chamber 17 at the compression top dead center exceeds the reference temperature Tth4 cannot achieve the SPCCI combustion, but the combination of IVC and O/L being the reference temperature Tth4 or lower can achieve the SPCCI combustion.

FIG. 20 illustrates approximations (VII) and (VIII) calculated based on the combination of  $\epsilon$  and IVC where the temperature inside the combustion chamber 17 at the compression top dead center becomes the reference temperature Tth4 or lower. The approximations (VII) and (VIII) are as follows.

$$IVC=-4.7481\epsilon^2+266.75\epsilon-3671.2 \quad \text{Approximation (VII):}$$

and

$$IVC=4.7481\epsilon^2-266.75\epsilon+3711.2 \quad \text{Approximation (VIII):}$$

In FIG. 20, the combination of  $\epsilon$  and IVC on the left side the approximations (VII) and (VIII) can avoid that the CI combustion begins before the SI combustion, and achieves the SPCCI combustion.

As seen in FIG. 20, also in Layer 3, the relationship between  $\epsilon$  and IVC is substantially vertically symmetrical with respect to  $IVC=20$  deg.aBDC. Moreover,  $IVC=75$  deg.aBDC is a retarding limit of the valve close timing of the intake valve 21 set in consideration of the amount of gas introduced into the combustion chamber 17 when the engine 1 operates in Layer 3. Similarly,  $IVC=-35$  deg.aBDC is an advancing limit of the valve close timing of the intake valve 21 set in consideration of the amount of gas introduced into the combustion chamber 17.

41

When determining the valve close timing IVC of the intake valve **21** in the case where the engine **1** operates in Layer **3**, the design engineer must determine IVC within the  $\epsilon$ -IVC valid range surrounded by the approximations (V), (VI), (VII), and (VIII) in FIG. **20** (the hatched range in FIG. **20**).

For example, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 20$ , when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 41.736\epsilon + 401.16 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 361.16 \quad (11)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 25$ , when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-35 \leq IVC \leq 75 \quad (12)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $25 \leq \epsilon \leq 30$ , when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-4.7481\epsilon^2 + 266.75\epsilon - 3671.2 \leq IVC \leq 75 \quad (13)$$

or

$$-35 \leq IVC \leq 4.7481\epsilon^2 - 266.75\epsilon + 3711.2 \quad (14)$$

By setting the valve close timing IVC of the intake valve **21** based on the relational expressions (11) to (14), the SPCCI combustion of the mixture gas with that the A/F being leaner than the stoichiometric air fuel ratio carries is achieved. Note that the valve close timing IVC is set for each operating state which is determined by the load and the engine speed in Layer **3**.

The example illustrated by a solid line in FIG. **20** is the  $\epsilon$ -IVC valid range when the engine speed is 2,000 rpm, as described above. If the engine speed changes, the  $\epsilon$ -IVC valid range also changes. When the engine speed increases, the  $\epsilon$ -IVC valid range is also parallelly translated to the retard side, similarly in FIG. **20**. Therefore, if the geometric compression ratio is set as  $10 \leq \epsilon < 20$ , when the engine speed is 3,000 rpm (see a broken line), the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 41.736\epsilon + 403.16 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 359.16 \quad (11^{-1})$$

If the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 25$ , when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-33 \leq IVC \leq 77 \quad (12^{-1})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $25 \leq \epsilon \leq 30$ , when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-4.7481\epsilon^2 + 266.75\epsilon - 3669.2 \leq IVC \leq 77 \quad (13^{-1})$$

or

$$-33 \leq IVC \leq 4.7481\epsilon^2 - 266.75\epsilon + 3713.2 \quad (14^{-1})$$

If the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 20$ , when the engine speed is 4,000 rpm (see one-dot chain line), the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

42

$$0.9949\epsilon^2 - 41.736\epsilon + 409.16 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 353.16 \quad (11)$$

If the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 25$ , when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-27 \leq IVC \leq 83 \quad (12^{-2})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $25 \leq \epsilon \leq 30$ , when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-4.7481\epsilon^2 + 266.75\epsilon - 3663.2 \leq IVC \leq 83 \quad (13^{-2})$$

or

$$-27 \leq IVC \leq 4.7481\epsilon^2 - 266.75\epsilon + 3719.2 \quad (14^{-2})$$

If the correction term C according to the engine speed NE (rpm) of the engine **1** is used similar to the above, the relational expression of  $\epsilon$  and IVC in Layer **3** can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 20$ ,

$$0.9949\epsilon^2 - 41.736\epsilon + 401.16 + C \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 361.16 + C \quad (11^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $20 \leq \epsilon < 25$ ,

$$-35 + C \leq IVC \leq 75 + C \quad (12^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $25 \leq \epsilon \leq 30$ ,

$$-4.7481\epsilon^2 + 266.75\epsilon - 3671.2 + C \leq IVC \leq 75 + C \quad (13^{-3})$$

or

$$-35 + C \leq IVC \leq 4.7481\epsilon^2 - 266.75\epsilon + 3711.2 + C \quad (14^{-3})$$

The design engineer determines the valve close timing IVC based on the  $\epsilon$ -IVC valid range determined for every engine speed of the engine **1**. As a result, the design engineer can set the valve timing of the intake valve **21** in Layer **3** as illustrated in FIG. **12**.

Moreover, the lower graph **2002** of FIG. **20** is a relationship between  $\epsilon$  and IVC when the fuel is the low octane fuel.

Upon determining the valve close timing IVC in the engine **1** of the low octane fuel, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 18.7$ , when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 39.149\epsilon + 348.59 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 308.59 \quad (15)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon < 23.7$  in the engine **1** of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-35 \leq IVC \leq 75 \quad (16)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $23.7 \leq \epsilon \leq 30$  in the engine **1** of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-3.1298\epsilon^2 + 172.48\epsilon - 2300 \leq IVC \leq 75 \quad (17)$$

or

$$-35 \leq IVC \leq 3.1298\epsilon^2 - 172.48\epsilon + 2340 \quad (18)$$

The cross-hatched range in the lower graph **2002** of FIG. **20** is an overlapping range of the  $\epsilon$ -IVC valid range of the high octane fuel and the  $\epsilon$ -IVC valid range of the low octane fuel. Similar to the above, the design engineer can set the control logic which suits both the engine **1** using the high octane fuel and the engine **1** using the low octane fuel by determining IVC within the overlapping range of the two occurring ranges.

Note that although illustration is omitted, if the engine speed increases, the  $\epsilon$ -IVC valid range is parallelly translated to the retard side also in the engine **1** of the low octane fuel. If the geometric compression ratio  $\epsilon$  is set as  $10 < \epsilon < 18.7$  in the engine **1** of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 39.149\epsilon + 350.59 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 306.59 \quad (15^{-1})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon < 23.7$  in the engine **1** of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-33 \leq IVC \leq 77 \quad (16^{-1})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $23.7 \leq \epsilon \leq 30$  in the engine **1** of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-3.1298\epsilon^2 + 172.48\epsilon - 2298 \leq IVC \leq 77 \quad (17^{-1})$$

or

$$-33 \leq IVC \leq 3.1298\epsilon^2 - 172.48\epsilon + 2342 \quad (18^{-1})$$

If the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 18.7$  in the engine **1** of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 39.149\epsilon + 356.59 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 300.59 \quad (15^{-2})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon < 23.7$  in the engine **1** of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-27 \leq IVC \leq 83 \quad (16^{-2})$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $23.7 \leq \epsilon \leq 30$  in the engine **1** of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-3.1298\epsilon^2 + 172.48\epsilon - 2292 \leq IVC \leq 83 \quad (17^{-2})$$

or

$$-27 \leq IVC \leq 3.1298\epsilon^2 - 172.48\epsilon + 2348 \quad (18^{-2})$$

If the correction term C according to the engine speed NE (rpm) of the engine **1** is used similar to the above, the relational expression of  $\epsilon$  and IVC in Layer **3**, in the engine **1** of the low octane fuel can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 18.7$ ,

$$0.9949\epsilon^2 - 39.149\epsilon + 348.59 + C \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 308.59 + C \quad (15^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $18.7 \leq \epsilon < 23.7$ ,

$$-35 + C \leq IVC \leq 75 + C \quad (16^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $23.7 \leq \epsilon \leq 30$ ,

$$-3.1298\epsilon^2 + 172.48\epsilon - 2300 + C \leq IVC \leq 75 + C \quad (17^{-3})$$

or

$$-35 + C \leq IVC \leq 3.1298\epsilon^2 - 172.48\epsilon + 2340 + C \quad (18^{-3})$$

(1-4) Relationship Between Geometric Compression Ratio and Valve Close Timing of Intake Valve in Layers **2** and **3**

FIG. **21** illustrates a relationship between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve **21** where the SPCCI combustion is possible in both Layer **2** and Layer **3**. This relational expression is obtained from the  $\epsilon$ -IVC valid range of FIG. **17** and the  $\epsilon$ -IVC valid range of FIG. **20**.

When the ECU **10** selects Layer **3** according to the temperature, etc. of the engine **1**, the low-load operating range of the engine **1** is switched from Layer **2** to Layer **3**. If the valve close timing IVC of the intake valve **21** is set so that the SPCCI combustion is possible in both Layer **2** and Layer **3**, it is possible to continuously perform the SPCCI combustion even when the map of the engine **1** is switched from Layer **2** to Layer **3**.

An upper graph **2101** of FIG. **21** is a relationship between  $\epsilon$  and IVC when the fuel is the high octane fuel. A lower graph **2102** is a relationship between  $\epsilon$  and IVC when the fuel is the low octane fuel.

If the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 17$  in the engine **1** of the high octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 41.736\epsilon + 401.16 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 361.16 \quad (19)$$

If the geometric compression ratio  $\epsilon$  is set as  $17 \leq \epsilon \leq 30$  in the engine **1** of the high octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 379.88 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 361.16 \quad (20)$$

or

$$0.9949\epsilon^2 - 41.736\epsilon + 401.16 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 974.94 \quad (21)$$

By setting the valve close timing IVC of the intake valve **21** based on the relational expressions (19) to (21), the SPCCI combustion of the mixture gas with the A/F being leaner than the stoichiometric air fuel ratio can be carried out, and the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio, and the G/F being leaner than the stoichiometric air fuel ratio can be carried out.

Note that the valve close timing IVC is set for each operating state which is determined by the load and the engine speed in Layer **2** and Layer **3**.

As illustrated by a broken line, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 17$  in the engine **1** of the high octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

45

$$0.9949\epsilon^2 - 41.736\epsilon + 403.16 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 359.16 \quad (19^{-1})$$

If the geometric compression ratio  $\epsilon$  is set as  $17 \leq \epsilon \leq 30$  in the engine 1 of the high octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 377.88 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 359.16 \quad (20^{-1})$$

or

$$0.9949\epsilon^2 - 41.736\epsilon + 403.16 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 976.94 \quad (21^{-1})$$

Similarly, as illustrated by a one-dot chain line, if the geometric compression ratio is set as  $10 \leq \epsilon < 17$  in the engine 1 of the high octane number fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 41.736\epsilon + 409.16 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 353.16 \quad (19^{-2})$$

If the geometric compression ratio  $\epsilon$  is set as  $17 \leq \epsilon \leq 30$  in the engine 1 of the high octane number fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.4288\epsilon^2 + 31.518\epsilon - 371.88 \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 353.16 \quad (20^{-2})$$

or

$$0.9949\epsilon^2 - 41.736\epsilon + 409.16 \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 982.94 \quad (21^{-2})$$

If the correction term C according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and IVC in Layer 2 and Layer 3 can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 17$ ,

$$0.9949\epsilon^2 - 41.736\epsilon + 401.16 + C \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 361.16 + C \quad (19^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $17 \leq \epsilon \leq 30$ ,

$$-0.4288\epsilon^2 + 31.518\epsilon - 379.88 + C \leq IVC \leq -0.9949\epsilon^2 + 41.736\epsilon - 361.16 + C \quad (20^{-3})$$

or

$$0.9949\epsilon^2 - 41.736\epsilon + 401.16 + C \leq IVC \leq 1.9163\epsilon^2 - 89.935\epsilon + 974.94 + C \quad (21^{-3})$$

Here, if the geometric compression ratio  $\epsilon$  determined to be lower than 17, the design engineer can determine IVC based on the relational expression (19<sup>-3</sup>). Since the selection range of IVC is wide, a degree of freedom in the design becomes high.

Moreover, as illustrated in the lower graph 2102 of FIG. 21, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 15.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 39.149\epsilon + 348.59 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 308.59 \quad (22)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $15.7 \leq \epsilon \leq 30$  in the engine 1 of the low octane fuel, when the

46

engine speed is 2,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2 + 34.859\epsilon - 377.22 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 308.59 \quad (23)$$

or

$$0.9949\epsilon^2 - 39.149\epsilon + 348.59 \leq IVC \leq 1.9211\epsilon^2 - 85.076\epsilon + 862.01 \quad (24)$$

Although illustration is omitted, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 15.7$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 39.149\epsilon + 350.59 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 306.59 \quad (22^{-1})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $15.7 \leq \epsilon \leq 30$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2 + 34.859\epsilon - 375.22 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 306.59 \quad (23^{-1})$$

or

$$0.9949\epsilon^2 - 39.149\epsilon + 350.59 \leq IVC \leq 1.9211\epsilon^2 - 85.076\epsilon + 864.01 \quad (24^{-1})$$

Although illustration is similarly omitted, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 15.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$0.9949\epsilon^2 - 39.149\epsilon + 356.59 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 300.59 \quad (22^{-2})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $15.7 \leq \epsilon \leq 30$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve close timing IVC (deg.aBDC) so that the following expression is satisfied.

$$-0.5603\epsilon^2 + 34.859\epsilon - 369.22 \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 300.59 \quad (23^{-2})$$

or

$$0.9949\epsilon^2 - 39.149\epsilon + 356.59 \leq IVC \leq 1.9211\epsilon^2 - 85.076\epsilon + 870.01 \quad (24^{-2})$$

If the correction term C according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and IVC in Layer 2 and Layer 3 in the engine 1 of the low octane fuel can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 15.7$ ,

$$0.9949\epsilon^2 - 39.149\epsilon + 348.59 + C \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 308.59 + C \quad (22^{-3})$$

If the geometric compression ratio  $\epsilon$  is  $15.7 \leq \epsilon \leq 30$ ,

$$-0.5603\epsilon^2 + 34.859\epsilon - 377.22 + C \leq IVC \leq -0.9949\epsilon^2 + 39.149\epsilon - 308.59 + C \quad (23^{-3})$$

or

$$0.9949\epsilon^2 - 39.149\epsilon + 348.59 + C \leq IVC \leq 1.9211\epsilon^2 - 85.076\epsilon + 862.01 + C \quad (24^{-3})$$

Note that although illustration is omitted, the design engineer may determine IVC within an overlapping range of

the  $\epsilon$ -IVC valid range of the upper graph **2101** and the  $\epsilon$ -IVC valid range of the lower graph **2102** of FIG. **21**. Similar to the above, the design engineer can set the control logic which suits both the engine **1** using the high octane fuel and the engine **1** using the low octane fuel by determining IVC within the overlapping range of the two occurring ranges.

(1-5) Procedure of Method of Implementing Control Logic

Next, a procedure of the method of implementing the control logic of the engine **1** for executing the SPCCI combustion will be described with reference to a flowchart illustrated in FIG. **22**. The design engineer can execute each step using a computer. The computer stores information on the  $\epsilon$ -IVC valid range illustrated in FIGS. **17**, **20**, and **21**.

At Step **S221** after the procedure starts, the design engineer first sets the geometric compression ratio  $\epsilon$ . The design engineer may input the set value of the geometric compression ratio  $\epsilon$  into the computer.

At the following Step **S222**, the design engineer sets the valve opening angle of the intake valve **21**, and the valve opening angle of the exhaust valve **22**. This corresponds to determining the cam shapes of the intake valve **21** and the exhaust valve **22**. The design engineer may input the set values of the valve opening angles of the intake valve **21** and the exhaust valve **22** into the computer. Thus, a hardware configuration of the engine **1** can be set at Steps **S221** and **S222**.

At Step **S223**, the design engineer sets the operating state comprised of the load and the engine speed, and at the following Step **S224**, the design engineer selects IVC based on the  $\epsilon$ -IVC valid range (FIGS. **17**, **20**, and **21**) stored in the computer.

Then, at Step **S225**, the computer determines whether the SPCCI combustion can be achieved based on IVC set at Step **S224**. If the determination at Step **S225** is YES, this procedure shifts to Step **S226**, and the design engineer determines the control logic of the engine **1** so that the SPCCI combustion is performed in the operating state set at Step **S223**. On the other hand, if the determination at Step **S225** is NO, this procedure shifts to Step **S227**, and the design engineer determines the control logic of the engine **1** so that the SI combustion is performed in the operating state set at Step **S223**. Note that at Step **S227**, the design engineer may again set the valve close timing IVC of the intake valve **21** in consideration of performing the SI combustion.

As described above, the method of implementing the control logic of the compression ignition engine disclosed herein determines the relationship between the engine geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve **21**. The design engineer can determine the valve close timing IVC of the intake valve **21** within the range where the relationship is satisfied. The design engineer can implement the control logic of the engine **1** by less time and labor compared with the conventional arts.

(2) Method of Implementing Control Logic According to Valve Opening Angle of Intake Valve

As described above, the valve close timing IVC of the intake valve **21** can be set based on the relationship between the geometric compression ratio  $\epsilon$  and the valve close timing IVC of the intake valve **21**.

The present inventors further found that, as a result of repeating further diligent examinations, a given relationship was required between the geometric compression ratio  $\epsilon$  and the closed-valve period (valve opening angle) CA of the intake valve **21**, in order to put to practical use the engine for executing the SPCCI combustion.

As described above, the engine **1** switches the layer between Layer **2** and Layer **3**. Here, the relationship between

the geometric compression ratio  $\epsilon$  and the valve opening angle CA of the intake valve **21** in Layer **2** differs from the relationship between the geometric compression ratio  $\epsilon$  and the valve opening angle CA of the intake valve **21** in Layer **3**.

(2-1) Relationship Between Geometric Compression Ratio and Valve Opening Angle of Intake Valve in Layer **2**

As described above, the engine **1** operates over the wide operating range from the low load to the high load in Layer **2**. In the operating range on the higher load side, in order to achieve the SPCCI combustion in Layer **2**, the relationship between  $\epsilon$  and IVC so that the temperature of the combustion chamber **17** at  $\theta_{CT}$  does not exceed the reference temperature Tth1 is required.

Thus, the present inventors created a matrix of the valve close timing IVC of the intake valve **21** and the overlap period O/L of the intake valve **21** and the exhaust valve **22**, for every geometric compression ratio  $\epsilon$  ( $\epsilon_1, \epsilon_2 \dots$ ), and in this matrix, estimated the temperature of the combustion chamber **17** during the CI combustion by using the model of the engine **1**, while changing the values of IVC and O/L. When this estimated result becomes the reference temperature Tth1 or lower, the combination of IVC and O/L can achieve the SPCCI combustion in Layer **2**.

Thus, the present inventors obtained a relationship between the geometric compression ratio  $\epsilon$ , the valve close timing IVC of the intake valve **21**, and the overlap period O/L of the intake valve **21** and the exhaust valve **22**, which can achieve the SPCCI combustion in Layer **2**. According to this relation, when the combination of  $\epsilon$  and IVC is determined, the range of O/L where the temperature becomes the reference temperature Tth1 or lower can be determined. As already described, in Layer **2**, the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion within the operating range on the higher load side is as expressed in the approximations (I) and (II) in FIG. **17**.

That is, when the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion in Layer **2** is selected based on FIG. **17**, the range of O/L corresponding to this combination can be determined through this relation.

The magnitude of the overlap period O/L is determined based on the valve close timing EVC of the exhaust valve **22** and the valve open timing IVO of the intake valve **21**. Here, assumed that EVC and IVO were set symmetrically with respect to an exhaust top dead center (symmetrical in the direction of the crank angle), the present inventors obtained the range of IVO corresponding to the range of O/L.

For example, if O/L is 70 deg, EVC becomes 35 deg.aTDC and IVO becomes 35 deg.bTDC. Then, the valve opening period of the intake valve **21**, i.e., the valve opening angle CA, can be determined by using the obtained IVO, and IVC used for the determination of O/L.

In this way, the present inventors acquired the combination of  $\epsilon$  and CA by converting the combination of  $\epsilon$  and IVC where the temperature becomes the reference temperature Tth1 or lower.

A graph **2301** in the upper graph of FIG. **23** illustrates the approximations (A) and (B) calculated based on the combination of  $\epsilon$  and CA. The horizontal axis of the graph **2301** is the geometric compression ratio  $\epsilon$ , and the vertical axis is the valve opening angle CA (deg) of the intake valve **21**. Although illustration is omitted the present inventors plotted, on the graph **1701**, the combination of  $\epsilon$  and CA where the temperature becomes the reference temperature Tth1 or lower, and determined the approximations (A) and (B) based on the plots.

The graph 2301 corresponds to a case when the engine speed is 2,000 rpm. The approximations (A) and (B) are as follows.

$$CA = -3.9394\epsilon^2 + 159.53\epsilon - 1314.9 \quad \text{Approximation (A):}$$

$$CA = 0.9096\epsilon^2 - 47.634\epsilon + 745.28 \quad \text{Approximation (B):}$$

In the graph 2301, when the combination of  $\epsilon$  and CA is on the left side of the approximations (A) and (B), the temperature of the combustion chamber 17 during the CI combustion becomes the reference temperature Tth1 or lower. This combination can carry out the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio, and the G/F being leaner than the stoichiometric air fuel ratio.

The relationship between  $\epsilon$  and CA described above is a relationship based on the maximum temperature of the combustion chamber 17 in Layer 2.

Moreover, as described above, in Layer 2, in order to achieve the SPCCI combustion when the engine 1 operates with the light load, the relationship between  $\epsilon$  and IVC so that the temperature of the combustion chamber 17 at  $\theta_{CT}$  becomes the reference temperature Tth2 or higher is required.

Thus, the present inventors created a matrix of the valve close timing IVC of the intake valve 21, and the overlap period O/L of the intake valve 21 and the exhaust valve 22, for every geometric compression ratio  $\epsilon$  ( $\epsilon_1, \epsilon_2 \dots$ ), and in this matrix, estimated the temperature of the combustion chamber 17 during CI combustion by using the model of the engine 1, while changing the values of IVC and O/L. The combination of IVC and O/L where this estimated result becomes the reference temperature Tth2 or higher can achieve the SPCCI combustion in Layer 2.

Thus, the present inventors obtained the relationship between the geometric compression ratio  $\epsilon$ , the valve close timing IVC of the intake valve 21, and the overlap period O/L of the intake valve 21 and the exhaust valve 22, which can achieve the SPCCI combustion in Layer 2. According to this relation, when the combination of  $\epsilon$  and IVC is determined, the range of O/L where the temperature becomes the reference temperature Tth2 or higher can be determined. As already described, in Layer 2, the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion within the operating range on the light-load side is as expressed by the approximations (III) and (IV) in FIG. 17.

That is, when the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion in Layer 2 is selected based on FIG. 17, the range of O/L corresponding to this combination can be determined through this relation.

The magnitude of the overlap period O/L is determined based on the valve close timing EVC of the exhaust valve 22 and the valve open timing IVO of the intake valve 21. The present inventors obtained the range of IVO corresponding to the range of O/L, by assuming that EVC and IVO were set symmetrically with respect to an exhaust top dead center (symmetrical in the direction of the crank angle). Thus, the valve opening period of the intake valve 21, i.e., the valve opening angle CA, can be determined by using the obtained IVO, and IVC used for the determination of O/L.

In this way, the present inventors acquired the combination of  $\epsilon$  and CA by converting the combination of  $\epsilon$  and IVC where the temperature becomes the reference temperature Tth2 or higher.

In the graph 2301 of the upper graph in FIG. 23, the approximations (C) and (D) calculated based on the combination of  $\epsilon$  and CA where the temperature becomes the

reference temperature Tth2 or higher are also illustrated. The approximations (C) and (D) are as follows.

$$CA = -0.4234\epsilon^2 + 22.926\epsilon + 42.164 \quad \text{Approximation (C):}$$

$$CA = 0.4234\epsilon^2 - 22.926\epsilon + 417.84 \quad \text{Approximation (D):}$$

In the graph 2301, when the combination of  $\epsilon$  and CA is on the right side of the approximations (C) and (D), the temperature of the combustion chamber 17 during the CI combustion becomes the reference temperature Tth2 or higher. This combination can carry out the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio and the G/F being leaner than the stoichiometric air fuel ratio.

As seen in FIG. 23, the relationship between  $\epsilon$  and CA is substantially vertically symmetrical with respect to CA=about 230 deg. CA=230 deg corresponds to the valve close timing (the best IVC described above) at which IVC=20 deg.aBDC, i.e., the amount of gas introduced into the combustion chamber 17 becomes the maximum, when the engine speed is 2,000 rpm.

In FIG. 23, the combination of  $\epsilon$  and CA within the range surrounded by the approximations (A), (B), (C), and (D) is the combination which can put to practical use the engine 1 for executing the SPCCI combustion in Layer 2. In other words, other combinations of  $\epsilon$  and CA outside this range cannot put to practical use the engine 1 for executing the SPCCI combustion in Layer 2.

The design engineer must determine CA within the  $\epsilon$ -CA valid range which is hatched in FIG. 23, upon determining the valve opening angle CA of the intake valve 21 when the engine 1 operates in Layer 2.

For example, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 16$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 22.926\epsilon + 417.84 \leq CA \leq 0.4234\epsilon^2 + 22.926\epsilon + 42.164 \quad (25)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $16 \leq \epsilon < 20$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 42.164 \quad (26)$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 417.84 \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 \quad (27)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 \leq CA \quad (28)$$

or

$$CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 \quad (29)$$

By setting the valve close timing IVC of the intake valve 21 based on the relational expressions (25) to (29), the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio, and the G/F being leaner than the stoichiometric air fuel ratio is achieved. Note that the valve close timing IVC is set for each operating state which is determined by the load and the engine speed in Layer 2. The example illustrated by solid lines in FIG. 23 is the  $\epsilon$ -CA valid range when the engine speed is 2,000 rpm, as described above. If the engine speed changes, the  $\epsilon$ -CA valid range

51

also changes. When the engine speed increases, the best IVC is retarded, and as a result, the corresponding CA is also retarded.

For example, when the engine speed is 3,000 rpm, CA corresponding to the best IVC is about 232 deg. As illustrated by broken lines in FIG. 23, the  $\epsilon$ -CA valid range when the engine speed is 3,000 rpm is obtained by parallelly translating the  $\epsilon$ -CA valid range when the engine speed is 2,000 rpm to the retard side by about 2 deg.

Therefore, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 16$ , when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 22.926\epsilon + 419.84 \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 44.164 \quad (25')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $16 \leq \epsilon < 20$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1312.9 \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 44.164 \quad (26')$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 419.84 \leq CA \leq -0.9096\epsilon^2 - 47.634\epsilon + 747.28 \quad (27')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1312.9 \leq CA \quad (28')$$

or

$$CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 747.28 \quad (29')$$

Moreover, when the engine speed is 4,000 rpm, CA corresponding to the best IVC is about 238 deg. As illustrated by broken lines in FIG. 23, the  $\epsilon$ -CA valid range when the engine speed is 3,000 rpm is obtained by parallelly translating the  $\epsilon$ -CA valid range when the engine speed is 2,000 rpm to the retard side by about 8 deg.

Therefore, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 16$ , when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$0.4234\epsilon^2 - 22.926\epsilon + 425.84 \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 50.164 \quad (25'')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $16 \leq \epsilon < 20$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1306.9 \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 50.164 \quad (26'')$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 425.84 \leq CA \leq -0.9096\epsilon^2 - 47.634\epsilon + 753.28 \quad (27'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon$ , the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1306.9 \leq CA \quad (28'')$$

or

$$CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 753.28 \quad (29'')$$

If a correction term D according to the engine speed NE (rpm) of the engine 1 is determined as  $D = 3.3 \times 10^{-1} NE^3 -$

52

$1.0 \times 10^{-6} NE^2 + 7.0 \times 10^{-4} NE$ , the relational expression of  $\epsilon$  and CA in Layer 2 can be expressed as follows. The valve opening angle CA (deg) is determined so that the following expression is satisfied:

5 if the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 16$ ,

$$0.4234\epsilon^2 - 22.926\epsilon + 417.84 + D \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 42.164 + D \quad (25^{(3)})$$

or if the geometric compression ratio  $\epsilon$  is  $16 \leq \epsilon < 20$ ,

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq -0.4234\epsilon^2 + 22.926\epsilon + 42.164 + D \quad (26^{(3)})$$

or

$$0.4234\epsilon^2 - 22.926\epsilon + 417.84 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D \quad (27^{(3)})$$

Further, if the design engineer determines the geometric compression ratio  $\epsilon$  as  $20 \leq \epsilon$ ,

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \quad (28^{(3)})$$

or

$$CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D \quad (29^{(3)})$$

The design engineer determines the valve opening angle CA based on the  $\epsilon$ -CA valid range determined for every engine speed of the engine 1. As a result, the design engineer can set the valve timing of the intake valve 21 in Layer 2 as illustrated in FIG. 11.

(2-2) Change in  $\epsilon$ -CA Valid Range by Difference of Octane Number

The graph 2301 of FIG. 23 is a relationship between  $\epsilon$  and CA when the fuel is the high octane number fuel (octane number is about 96). A graph 2302 illustrated in the lower graph is a relationship between  $\epsilon$  and CA when the fuel is the low octane fuel (octane number is about 91). According to the examination by the present inventors, when the fuel was the low octane fuel, it was found that the  $\epsilon$ -CA valid range shifts by 1.3 compression ratios toward the lower compression ratio from the  $\epsilon$ -CA valid range of the high octane fuel.

Accordingly, upon determining the valve opening angle CA in the engine 1 of the low octane fuel, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 14.7$ , when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$0.4234(\epsilon+1.3)^2 - 22.926(\epsilon+1.3) + 417.84 \leq CA \leq -0.4234(\epsilon+1.3)^2 + 22.926(\epsilon+1.3) + 42.164 \quad (30)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $14.7 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2 + 159.53(\epsilon+1.3) - 1314.9 \leq CA \leq -0.4234(\epsilon+1.3)^2 + 22.926(\epsilon+1.3) + 42.164 \quad (31)$$

or

$$0.4234(\epsilon+1.3)^2 - 22.926(\epsilon+1.3) + 417.84 \leq CA \leq 0.9096(\epsilon+1.3)^2 - 47.634(\epsilon+1.3) + 745.28 \quad (32)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines

the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9 \leq CA \quad (33)$$

or

$$CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28 \quad (34)$$

The cross-hatched range in the graph 2302 of FIG. 23 is an overlapping range of the  $\epsilon$ -CA valid range of the high octane fuel and the  $\epsilon$ -CA valid range of the low octane fuel. The design engineer can set the control logic which suits both the engine 1 using the high octane fuel and the engine 1 using the low octane fuel by determining CA within the overlapping range of the two occurring ranges. The design engineer can collectively implement the engine control logic even if the octane number of fuel differs for every destination. The package design has an advantage which lessens the design time and labor.

Note that although illustration is omitted, also in the engine 1 of the low octane fuel, when the engine speed increases, the  $\epsilon$ -CA valid range is parallelly translated to the retard side.

Accordingly, upon determining the valve opening angle CA in the engine 1 of the low octane fuel, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 14.7$ , when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$0.4234(\epsilon+1.3)^2-22.926(\epsilon+1.3)+419.84 \leq CA \leq -0.4234(\epsilon+1.3)^2+22.926(\epsilon+1.3)+44.164 \quad (30')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $14.7 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1312.9 \leq CA \leq -0.4234(\epsilon+1.3)^2+22.926(\epsilon+1.3)+44.164 \quad (31')$$

or

$$0.4234(\epsilon+1.3)^2-22.926(\epsilon+1.3)+419.84 \leq CA \leq -0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+747.28 \quad (32')$$

Further, upon determining the valve opening angle CA, if the geometric compression ratio  $\epsilon$  is set as  $10 \leq \epsilon < 14.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$0.4234(\epsilon+1.3)^2-22.926(\epsilon+1.3)+425.84 \leq CA \leq -0.4234(\epsilon+1.3)^2+22.926(\epsilon+1.3)+50.164 \quad (30'')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $14.7 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1306.9 \leq CA \leq -0.4234(\epsilon+1.3)^2+22.926(\epsilon+1.3)+50.164 \quad (31'')$$

or

$$0.4234(\epsilon+1.3)^2-22.926(\epsilon+1.3)+425.84 \leq CA \leq -0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+753.28 \quad (32'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon$  in the engine 1 of the low octane fuel, when the

engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1306.9 \leq CA \quad (33'')$$

or

$$CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+753.28 \quad (34'')$$

If the correction term D according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and CA in Layer 2 in the engine 1 of the low octane fuel can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $10 \leq \epsilon < 14.7$ ,

$$0.4234(\epsilon+1.3)^2-22.926(\epsilon+1.3)+417.84+D \leq CA \leq -0.4234(\epsilon+1.3)^2+22.926(\epsilon+1.3)+42.164+D \quad (30''')$$

If the geometric compression ratio  $\epsilon$  is  $14.7 \leq \epsilon < 18.7$ ,

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq -0.4234(\epsilon+1.3)^2+22.926(\epsilon+1.3)+42.164+D \quad (31''')$$

or

$$0.4234(\epsilon+1.3)^2-22.926(\epsilon+1.3)+417.84+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D \quad (32''')$$

If the geometric compression ratio  $\epsilon$  is  $18.7 < \epsilon$ ,

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \quad (33''')$$

or

$$CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D \quad (34''')$$

(2-3) Relationship Between Geometric Compression Ratio and Valve Opening Angle of Intake Valve in Layer 3

As described above, regarding Layer 3, the state where the engine 1 operates with the light load corresponds to the operating state at the limit where the SPCCI combustion can occur. In the operating range on the light-load side, in order to achieve the stable SPCCI combustion in Layer 3, the relationship between  $\epsilon$  and IVC so that the temperature inside the combustion chamber 17 at  $\theta_{CI}$  becomes the reference temperature Tth3 or higher is required.

Therefore, the present inventors performed the examination described above.

First, the present inventors estimated the temperature of the combustion chamber 17 during the CI combustion by using the model of the engine 1, while changing the values of IVC and O/L in the matrix (see FIG. 19) of the valve close timing IVC of the intake valve 21, and the overlap period O/L of the intake valve 21 and the exhaust valve 22, for every geometric compression ratio  $\epsilon$  ( $\epsilon_1, \epsilon_2 \dots$ ). The combination of IVC and O/L where this estimated result becomes the reference temperature Tth3 or lower can achieve the stable SPCCI combustion in Layer 3.

Then, the present inventors estimated the G/F by using the model of the engine 1 in the matrix comprised of the two parameters of IVC and O/L, in order to reduce the discharge of raw NO<sub>x</sub>. The combination of IVC and O/L where the G/F becomes the given value or higher can reduce the discharge of raw NO<sub>x</sub>.

Then, the present inventors overlapped the combination of IVC and O/L where the temperature becomes the reference temperature Tth3 or higher with the combination of IVC and O/L where the G/F becomes the given value or higher to determine the relationship between  $\epsilon$  and IVC which can achieve both the stability of the SPCCI combustion and the reduction of raw NO<sub>x</sub> discharged.

Here, the relationship between  $\epsilon$  and IVC is based on the combination of IVC and O/L. According to this relation, if the combination of  $\epsilon$  and IVC is determined, the range of O/L where the temperature becomes the reference temperature  $T_{th3}$  or lower and the G/F becomes the given value or higher can be determined.

Moreover, as already described, in Layer 3, the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion within the operating range on the light-load side is as expressed by the approximations (V) and (VI) in FIG. 20.

That is, if the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion in Layer 3 is selected based on FIG. 20, the range of O/L corresponding to this combination can be determined through this relation.

The magnitude of the overlap period O/L is determined based on the valve close timing EVC of the exhaust valve 22 and the valve open timing IVO of the intake valve 21. The present inventors obtained the range of IVO corresponding to the range of O/L, by assuming that EVC and IVO were set symmetrically with respect to an exhaust top dead center (symmetrical in the direction of the crank angle). Thus, the valve opening period of the intake valve 21, i.e., the valve opening angle CA, can be determined by using the obtained IVO, and IVC used for the determination of O/L.

In this way, the present inventors acquired the combination of  $\epsilon$  and CA, by converting the combination of  $\epsilon$  and IVC where the temperature becomes the reference temperature  $T_{th3}$  or lower and the G/F becomes the given value or higher.

FIG. 24 illustrates the approximations (E), (F), (G), (H), (I), and (J) calculated from the combination of  $\epsilon$  and CA. The horizontal axis in FIG. 24 is the geometric compression ratio  $\epsilon$ , and the vertical axis is the valve opening angle CA (deg) of the intake valve 21.

An upper graph 2401 of FIG. 24 corresponds to a case where the engine speed is 2,000 rpm. Both the approximations (E) and (F) are effected when  $\epsilon < 14$ , and they are as follows.

$CA = 60\epsilon - 550$  Approximation (E): 40

$CA = -40\epsilon + 800$  Approximation (F):

Moreover, both approximations (G) and (H) are effected when  $14 \leq \epsilon < 16.3$ , and they are as follows.

$CA = 290$  Approximation (G): 45

$CA = -0.7246\epsilon^2 + 6.7391\epsilon + 287.68$  Approximation (H):

Moreover, both the approximations (I) and (J) are effected when  $16.3 \leq \epsilon < 20$ , and they are as follows.

$CA = 290$  Approximation (I): 50

$CA = -12.162\epsilon + 403.24$  Approximation (J): 55

In FIG. 24, the combination of  $\epsilon$  and CA between a boundary connecting the approximations (E), (G), and (I), and a boundary connecting the approximations (F), (H), and (J) achieves the SPCCI combustion of the mixture gas with the temperature of the combustion chamber 17 during the CI combustion becoming the reference temperature  $T_{th3}$  or higher, and the A/F being leaner than the stoichiometric air fuel ratio.

The relationship between  $\epsilon$  and CA described above is a relation, in Layer 3, based on the minimum temperature of the combustion chamber 17 which can achieve the SPCCI combustion when the engine 1 operates with the light load.

Moreover, the approximations (G) and (I) correspond to the retarding limit of IVC and the maximum value of O/L, respectively.

On the other hand, regardless of Layer 2 and Layer 3, if the temperature inside the combustion chamber 17 is too high, the CI combustion begins before the start of the SI combustion, and thereby the SPCCI combustion cannot be performed.

Moreover, as described above, in Layer 3, if the mean temperature inside the combustion chamber 17 at a compression top dead center reaches the reference temperature  $T_{th4}$ , it is thought that the CI combustion will begin before the SI combustion begins, and in this case, the SPCCI combustion cannot be performed.

Thus, the present inventors created a matrix of the valve close timing IVC of the intake valve 21 and the overlap period O/L of the intake valve 21 and the exhaust valve 22, for every geometric compression ratio  $\epsilon$  ( $\epsilon_1, \epsilon_2 \dots$ ), and in this matrix, estimated the temperature of the combustion chamber 17 at a compression top dead center by using the model of the engine 1, while changing the values of IVC and O/L. The combination of IVC and O/L where this estimated result becomes the reference temperature  $T_{th4}$  or lower can achieve the SPCCI combustion in Layer 3.

Thus, the present inventors obtained a relationship of the geometric compression ratio  $\epsilon$ , the valve close timing IVC of the intake valve 21, and the overlap period O/L of the intake valve 21 and the exhaust valve 22, which can achieve the SPCCI combustion in Layer 3. According to this relation, if the combination of  $\epsilon$  and IVC is determined, the range of O/L where the temperature becomes the reference temperature  $T_{th4}$  or lower can be determined. As already described, the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion in Layer 3 is as expressed by the approximations (VII) and (VIII) in FIG. 20.

That is, when the combination of  $\epsilon$  and IVC which can perform the SPCCI combustion in Layer 3 is selected based on FIG. 20, the range of O/L corresponding to this combination can be determined through this relation.

The magnitude of the overlap period O/L is determined based on the valve close timing EVC of the exhaust valve 22 and the valve open timing IVO of the intake valve 21. The present inventors obtained the range of IVO corresponding to the range of O/L, by assuming that EVC and IVO were set symmetrically with respect to an exhaust top dead center (symmetrical in the direction of the crank angle). Thus, the valve opening period of the intake valve 21, i.e., the valve opening angle CA, can be determined by using the obtained IVO, and IVC used for the determination of O/L.

In this way, the present inventors acquired the combination of  $\epsilon$  and CA by converting the combination of  $\epsilon$  and IVC where the temperature becomes the reference temperature  $T_{th4}$  or lower.

In the graph 2401 of the upper graph in FIG. 24, the approximations (M) and (N) calculated based on the combination of  $\epsilon$  and CA where the temperature becomes the reference temperature  $T_{th4}$  or lower are also illustrated. The approximation (M) and (N) are as follows.

$CA = 5\epsilon + 112.5$  Approximation (M):

$CA = 1.8571\epsilon^2 - 112.216 + 1834.6$  Approximation (N):

Moreover, the approximations (M) and (N) are connected by the approximations (O) and (P).

$CA = 32.5\epsilon - 602.5$  Approximation (O):

$\epsilon = 25$  Approximation (P)

For example, the approximations (M) and (O) are connected at  $\epsilon=26$ , and the approximations (O) and (P), and the approximations (P) and (N) are connected at  $\epsilon=25$ .

In FIG. 24, the combination of  $\epsilon$  and CA on the left side of the approximations (M), (N), (O), and (P) can avoid that the CI combustion begins before the SI combustion, thereby achieving the SPCCI combustion.

Moreover, in the graph 2401 of the upper graph in FIG. 24, approximations (K) and (L) which constitute the boundary connecting the approximations (I) and (M), and the boundary connecting the approximations (J) and (N) are also illustrated. The approximations (K) and (L) are as follows.

$$CA = -4.1176\epsilon + 372.35 \quad \text{Approximation (K):}$$

$$CA = -1.7647\epsilon + 195.29 \quad \text{Approximation (L):}$$

The approximation (K) corresponds to a retarding limit of the valve close timing of the intake valve 21 set in consideration of the amount of gas introduced into the combustion chamber 17 when the engine 1 operates in Layer 3, and the approximation (L) corresponds to an advancing limit of the valve close timing of the intake valve 21 set in consideration of the amount of gas introduced into the combustion chamber 17.

Upon determining the valve close timing IVC of the intake valve 21 when the engine 1 operates in Layer 3, the design engineer must determine CA within the  $\epsilon$ -CA valid range (the hatched range in FIG. 24) surrounded by the approximations (E), (F), (G), (H), (I), (K), (L), (M), (O), and (P) in FIG. 20.

For example, if the geometric compression ratio  $\epsilon$  is set as  $13.5 \leq \epsilon < 14$ , when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40\epsilon + 800 \leq CA \leq 60\epsilon - 550 \quad (35)$$

If the geometric compression ratio  $\epsilon$  is set as  $14 \leq \epsilon < 16.3$ , when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 \leq CA \leq 290 \quad (36)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $16.3 \leq \epsilon < 20$ , when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-12.162\epsilon + 403.24 \leq CA \leq 290 \quad (37)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 25$ , when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-1.7647\epsilon + 195.29 \leq CA \leq -4.1176\epsilon + 372.35 \quad (38)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $25 \leq \epsilon \leq 28.5$ , when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$5\epsilon + 112.5 \leq CA \leq -4.1176\epsilon + 372.35 \quad (39)$$

or

$$-1.7647\epsilon + 195.29 \leq CA \leq 1.8571\epsilon^2 - 112.21\epsilon + 1834.6 \quad (40)$$

By setting the valve opening angle CA of the intake valve 21 based on the relational expressions (35) to (40), the SPCCI combustion of the mixture gas with the A/F being leaner than the stoichiometric air fuel ratio is achieved. Note

that the valve opening angle CA is set for each operating state which is determined by the load and the engine speed in Layer 3.

The example illustrated by the solid line in FIG. 24 is the  $\epsilon$ -CA valid range when the engine speed is 2,000 rpm, as described above. If the engine speed changes, the  $\epsilon$ -CA valid range also changes. If the engine speed increases, the  $\epsilon$ -CA valid range is also parallelly translated to the retard side in FIG. 24.

For example, if the geometric compression ratio  $\epsilon$  is set as  $13.5 \leq \epsilon < 14$ , when the engine speed is 3,000 rpm (see a broken line), the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40\epsilon + 802 \leq CA \leq 60\epsilon - 548 \quad (35')$$

If the geometric compression ratio  $\epsilon$  is set as  $14 \leq \epsilon < 16.3$ , when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246\epsilon^2 + 6.7391\epsilon + 289.68 \leq CA \leq 292 \quad (36')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $16.3 \leq \epsilon < 20$ , when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-12.162\epsilon + 405.24 \leq CA \leq 292 \quad (37')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 25$ , when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-1.7647\epsilon + 197.29 \leq CA \leq -4.1176\epsilon + 374.35 \quad (38')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $25 \leq \epsilon \leq 28.5$ , when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$5\epsilon + 114.5 \leq CA \leq -4.1176\epsilon + 374.35 \quad (39')$$

or

$$-1.7647\epsilon + 197.29 \leq CA \leq 1.8571\epsilon^2 - 112.21\epsilon + 1836.6 \quad (40')$$

If the geometric compression ratio  $\epsilon$  is set as  $13.5 \leq \epsilon < 14$ , when the engine speed is 4,000 rpm (see a one-dot chain line), the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40\epsilon + 808 \leq CA \leq 60\epsilon - 542 \quad (35'')$$

If the geometric compression ratio  $\epsilon$  is set as  $14 \leq \epsilon < 16.3$ , when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246\epsilon^2 + 6.7391\epsilon + 295.68 \leq CA \leq 298 \quad (36'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $16.3 \leq \epsilon < 20$ , when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-12.162\epsilon + 411.24 \leq CA \leq 298 \quad (37'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $20 \leq \epsilon < 25$ , when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-1.7647\epsilon + 203.29 \leq CA \leq -4.1176\epsilon + 380.35 \quad (38'')$$

59

Further, if the geometric compression ratio  $\epsilon$  is set as  $25 \leq \epsilon \leq 28.5$ , when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$5\epsilon + 120.5 \leq CA \leq -4.1176\epsilon + 380.35 \quad (39'')$$

or

$$-1.7647\epsilon + 203.29 \leq CA \leq 1.8571\epsilon^2 - 112.21\epsilon + 1842.6 \quad (40'')$$

If the correction term D according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and CA in Layer 3 can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $13.5 \leq \epsilon < 14$ ,

$$-40\epsilon + 800 + D \leq CA \leq 60\epsilon - 550 + D \quad (35^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $14 \leq \epsilon < 16.3$ ,

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 290 + D \quad (36^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $16.3 \leq \epsilon < 20$ ,

$$-12.162\epsilon + 403.24 + D \leq CA \leq 290 + D \quad (37^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $20 \leq \epsilon < 25$ ,

$$-1.7647\epsilon + 195.29 + D \leq CA \leq -4.1176\epsilon + 372.35 + D \quad (38^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $25 \leq \epsilon \leq 28.5$ ,

$$5\epsilon + 112.5 + D \leq CA \leq -4.1176\epsilon + 372.35 + D \quad (39^{(3)})$$

or

$$-1.7647\epsilon + 195.29 + D \leq CA \leq 1.8571\epsilon^2 - 112.21\epsilon + 1834.6 + D \quad (40^{(3)})$$

The design engineer determines the valve opening angle CA based on the  $\epsilon$ -CA valid range determined for every engine speed of the engine 1. As a result, the design engineer can set the valve timing of the intake valve 21 in Layer 3, as illustrated in FIG. 12.

Moreover, a lower graph 2402 of FIG. 24 is a relationship between  $\epsilon$  and CA when the fuel is the low octane fuel.

Upon determining the valve opening angle CA, if the geometric compression ratio  $\epsilon$  is set as  $12.2 \leq \epsilon < 12.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40(\epsilon + 1.3) + 800 \leq CA \leq 60\epsilon - 550 \quad (41)$$

If the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246(\epsilon + 1.3)^2 + 6.7391(\epsilon + 1.3) + 287.68 \leq CA \leq 290 \quad (42)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $15.3 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-12.162(\epsilon + 1.3) + 403.24 \leq CA \leq 290 \quad (43)$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon < 23.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-1.7647(\epsilon + 1.3) + 195.29 \leq CA \leq -4.1176(\epsilon + 1.3) + 372.35 \quad (44)$$

60

Further, if the geometric compression ratio  $\epsilon$  is set as  $23.7 \leq \epsilon < 27.2$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$5(\epsilon + 1.3) + 112.5 \leq CA \leq -4.1176(\epsilon + 1.3) + 372.35 \quad (45)$$

or

$$-1.7647(\epsilon + 1.3) + 195.29 \leq CA \leq 1.8571(\epsilon + 1.3)^2 - 112.21(\epsilon + 1.3) + 1834.6 \quad (46)$$

The cross-hatched range in the lower graph 2402 of FIG. 24 is an overlapping range of the  $\epsilon$ -CA valid range of the high octane fuel and the  $\epsilon$ -CA valid range of the low octane fuel. Similar to the above, the design engineer can set the control logic which suits both the engine 1 using the high octane fuel and the engine 1 using the low octane fuel by determining CA within the overlapping range of the two occurring ranges.

Note that although illustration is omitted, also in the engine 1 of the low octane fuel, when the engine speed increases, the  $\epsilon$ -CA valid range is parallelly translated to the retard side.

Upon determining the valve opening angle CA, if the geometric compression ratio  $\epsilon$  is set as  $12.2 \leq \epsilon < 12.7$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40(\epsilon + 1.3) + 802 \leq CA \leq 60\epsilon - 548 \quad (41')$$

If the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246(\epsilon + 1.3)^2 + 6.7391(\epsilon + 1.3) + 289.68 \leq CA \leq 292 \quad (42')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $15.3 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-12.162(\epsilon + 1.3) + 405.24 \leq CA \leq 292 \quad (43')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon < 23.7$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-1.7647(\epsilon + 1.3) + 197.29 \leq CA \leq -4.1176(\epsilon + 1.3) + 374.35 \quad (44')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $23.7 \leq \epsilon \leq 27.2$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$5(\epsilon + 1.3) + 114.5 \leq CA \leq -4.1176(\epsilon + 1.3) + 374.35 \quad (45')$$

or

$$-1.7647(\epsilon + 1.3) + 197.29 \leq CA \leq 1.8571(\epsilon + 1.3)^2 - 112.21(\epsilon + 1.3) + 1836.6 \quad (46')$$

If the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve

61

opening angle CA (deg) so that the following expression is satisfied.

$$-40(\epsilon+1.3)+808 \leq CA \leq 60\epsilon-542 \quad (41'')$$

If the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+295.68 \leq CA \leq 298 \quad (42'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $15.3 \leq \epsilon < 18.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-12.162(\epsilon+1.3)+411.24 \leq CA \leq 298 \quad (43'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $18.7 \leq \epsilon < 23.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-1.7647(\epsilon+1.3)+203.29 \leq CA \leq -4.1176(\epsilon+1.3)+380.35 \quad (44'')$$

Further, if the geometric compression ratio  $\epsilon$  is set as  $23.7 \leq \epsilon \leq 27.2$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$5(\epsilon+1.3)+120.5 \leq CA \leq -4.1176(\epsilon+1.3)+380.35 \quad (45'')$$

or

$$-1.7647(\epsilon+1.3)+203.29 \leq CA \leq 1.8571(\epsilon+1.3)^2-112.21(\epsilon+1.3)+1842.6 \quad (46'')$$

If the correction term D according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and CA in Layer 3 in the engine 1 of the low octane fuel can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $12.2 \leq \epsilon < 12.7$ ,

$$-40(\epsilon+1.3)+800+D \leq CA \leq 60\epsilon-550+D \quad (41^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $12.7 \leq \epsilon < 15$ ,

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+287.68+D \leq CA \leq 290+D \quad (42^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $15.3 \leq \epsilon < 18.7$ ,

$$-12.162(\epsilon+1.3)+403.24+D \leq CA \leq 290+D \quad (43^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $18.7 \leq \epsilon < 23.7$ ,

$$-1.7647(\epsilon+1.3)+195.29+D \leq CA \leq -4.1176(\epsilon+1.3)+372.35+D \quad (44^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $23.7 \leq \epsilon \leq 27.2$ ,

$$5(\epsilon+1.3)+112.5+D \leq CA \leq -4.1176(\epsilon+1.3)+372.35+D \quad (45^{(3)})$$

or

$$-1.7647(\epsilon+1.3)+195.29+D \leq CA \leq 1.8571(\epsilon+1.3)^2-112.21(\epsilon+1.3)+1834.6+D \quad (46^{(3)})$$

(2-4) Relationship Between Geometric Compression Ratio and Valve Opening Angle of Intake Valve in Layers 2 and 3

FIG. 25 illustrates a relationship between the geometric compression ratio  $\epsilon$  and the valve opening angle CA of the intake valve 21 where the SPCCI combustion is possible in

62

both Layer 2 and Layer 3. This relational expression is obtained from the  $\epsilon$ -CA valid range of FIG. 23 and the  $\epsilon$ -CA valid range of FIG. 24.

When the ECU 10 selects Layer 3 according to the temperature, etc. of the engine 1, the low-load operating range of the engine 1 is switched from Layer 2 to Layer 3. If the valve opening angle CA of the intake valve 21 is set so that the SPCCI combustion is possible in both Layer 2 and Layer 3, it becomes possible to continuously perform the SPCCI combustion even when the map of the engine 1 is switched from Layer 2 to Layer 3.

An upper graph 2501 of FIG. 25 is a relationship between  $\epsilon$  and CA when the fuel is the high octane fuel. A lower graph 2502 is a relationship between  $\epsilon$  and CA when the fuel is the low octane fuel.

If the geometric compression ratio  $\epsilon$  is set as  $13.5 \leq \epsilon < 14$  in the engine 1 of the high octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40\epsilon+800 \leq CA \leq 60\epsilon-550 \quad (47)$$

If the geometric compression ratio  $\epsilon$  is set as  $14 \leq \epsilon < 16$  in the engine 1 of the high octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246\epsilon^2+6.7391\epsilon+287.68 \leq CA \leq 290 \quad (48)$$

If the geometric compression ratio  $\epsilon$  is set as  $16 \leq \epsilon < 16.3$  in the engine 1 of the high octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2+159.53\epsilon-1314.9 \leq CA \leq 290 \quad (49)$$

or

$$-0.7246\epsilon^2+6.7391\epsilon+287.68 \leq CA \leq -0.9096\epsilon^2-47.634\epsilon+745.28 \quad (50)$$

If the geometric compression ratio  $\epsilon$  is set as  $16.3 \leq \epsilon$  in the engine 1 of the high octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2+159.53\epsilon-1314.9 \leq CA \leq 290 \quad (51)$$

or

$$-12.162\epsilon+403.24 \leq CA \leq -0.9096\epsilon^2-47.634\epsilon+745.28 \quad (52)$$

By setting the valve opening angle CA of the intake valve 21 based on the relational expressions (47) to (52), the SPCCI combustion of the mixture gas with the A/F being leaner than the stoichiometric air fuel ratio can be carried out, and the SPCCI combustion of the mixture gas with the A/F being the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio, and the G/F being leaner than the stoichiometric air fuel ratio can be carried out.

Note that the valve opening angle CA is set for each operating state which is determined by the load and the engine speed in Layer 2 and Layer 3.

As illustrated by a broken line, if the geometric compression ratio  $\epsilon$  is set as  $13.5 \leq \epsilon < 14$  in the engine 1 of the high octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40\epsilon+802 \leq CA \leq 60\epsilon-548 \quad (47')$$

63

If the geometric compression ratio  $\epsilon$  is set as  $14 \leq \epsilon < 16$  in the engine 1 of the high octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246\epsilon^2 + 6.7391\epsilon + 289.68 \leq CA \leq 292 \quad (48')$$

If the geometric compression ratio  $\epsilon$  is set as  $16 \leq \epsilon < 16.3$  in the engine 1 of the high octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1312.9 \leq CA \leq 292 \quad (49')$$

or

$$-0.7246\epsilon^2 + 6.7391\epsilon + 289.68 \leq CA \leq -0.9096\epsilon^2 - 47.634\epsilon + 747.28 \quad (50')$$

If the geometric compression ratio  $\epsilon$  is set as  $16.3 \leq \epsilon$  in the engine 1 of the high octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1312.9 \leq CA \leq 292 \quad (51')$$

or

$$-12.162\epsilon + 405.24 \leq CA \leq -0.9096\epsilon^2 - 47.634\epsilon + 747.28 \quad (52')$$

Similarly, as illustrated by a one-dot chain line, if the geometric compression ratio is set as  $13.5 \leq \epsilon < 14$  in the engine 1 of the high octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40\epsilon + 808 \leq CA \leq 60\epsilon - 542 \quad (47'')$$

If the geometric compression ratio  $\epsilon$  is set as  $14 \leq \epsilon < 16$  in the engine 1 of the high octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246\epsilon^2 + 6.7391\epsilon + 295.68 \leq CA \leq 298 \quad (48'')$$

If the geometric compression ratio  $\epsilon$  is set as  $16 \leq \epsilon < 16.3$  in the engine 1 of the high octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1306.9 \leq CA \leq 298 \quad (49'')$$

or

$$-0.7246\epsilon^2 + 6.7391\epsilon + 295.68 \leq CA \leq -0.9096\epsilon^2 - 47.634\epsilon + 753.28 \quad (50'')$$

If the geometric compression ratio  $\epsilon$  is set as  $16.3 \leq \epsilon$  in the engine 1 of the high octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394\epsilon^2 + 159.53\epsilon - 1306.9 \leq CA \leq 298 \quad (51'')$$

or

$$-12.162\epsilon + 411.24 \leq CA \leq -0.9096\epsilon^2 - 47.634\epsilon + 753.28 \quad (52'')$$

If the correction term D according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the

64

relational expression of  $\epsilon$  and CA in Layer 2 and Layer 3 can be expressed as follows. If the geometric compression ratio  $\epsilon$  is  $13.5 \leq \epsilon < 14$ ,

$$-40\epsilon + 800 + D \leq CA \leq 60\epsilon - 550 + D \quad (47^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $14 \leq \epsilon < 16$ ,

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 290 + D \quad (48^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $16 \leq \epsilon < 16.3$ ,

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq 290 + D \quad (49^{(3)})$$

or

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D \quad (50^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $16.3 \leq \epsilon$ ,

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq 290 + D \quad (51^{(3)})$$

or

$$-12.162\epsilon + 403.24 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D \quad (52^{(3)})$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $12.2 \leq \epsilon < 12.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40(\epsilon + 1.3) + 800 \leq CA \leq 60(\epsilon + 1.3) - 550 \quad (53)$$

If the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 14.7$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246(\epsilon + 1.3)^2 + 6.7391(\epsilon + 1.3) + 287.68 \leq CA \leq 290 \quad (54)$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $14.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon + 1.3)^2 + 159.53(\epsilon + 1.3) - 1314.9 \leq CA \leq 290 \quad (55)$$

or

$$-0.7246(\epsilon + 1.3)^2 + 6.7391(\epsilon + 1.3) + 287.68 \leq CA \leq -0.9096(\epsilon + 1.3)^2 - 47.634(\epsilon + 1.3) + 745.28 \quad (56)$$

If the geometric compression ratio  $\epsilon$  is set as  $15 \leq \epsilon$  in the engine 1 of the low octane fuel, when the engine speed is 2,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon + 1.3)^2 + 159.53(\epsilon + 1.3) - 1314.9 \leq CA \leq 290 \quad (57)$$

or

$$-12.162(\epsilon + 1.3) + 403.24 \leq CA \leq 0.9096(\epsilon + 1.3)^2 - 47.634\epsilon + 745.28 \quad (58)$$

Although illustration is omitted, if the geometric compression ratio  $\epsilon$  is set as  $12.2 \leq \epsilon < 12.7$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40(\epsilon + 1.3) + 802 \leq CA \leq 60(\epsilon + 1.3) - 548 \quad (53')$$

If the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 14.7$  in the engine 1 of the low octane fuel, when the engine speed

65

is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+289.68 \leq CA \leq 292 \quad (54')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $14.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1312.9 \leq CA \leq 292 \quad (55')$$

or

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+289.68 \leq CA \leq -0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+747.28 \quad (56')$$

If the geometric compression ratio  $\epsilon$  is set as  $15 \leq \epsilon$  in the engine 1 of the low octane fuel, when the engine speed is 3,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1312.9 \leq CA \leq 292 \quad (57')$$

or

$$-12.162(\epsilon+1.3)+405.24 \leq CA \leq -0.9096(\epsilon+1.3)^2-47.634\epsilon+747.28 \quad (58')$$

Although illustration is similarly omitted, if the geometric compression ratio  $\epsilon$  is set as  $12.2 \leq \epsilon < 12.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-40(\epsilon+1.3)+808 \leq CA \leq 60(\epsilon+1.3)-542 \quad (53'')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $12.7 \leq \epsilon < 14.7$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+295.68 \leq CA \leq 298 \quad (54'')$$

Moreover, if the geometric compression ratio  $\epsilon$  is set as  $14.7 \leq \epsilon < 15$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1306.9 \leq CA \leq 298 \quad (55'')$$

or

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+295.68 \leq CA \leq -0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+753.28 \quad (56'')$$

If the geometric compression ratio  $\epsilon$  is set as  $15 \leq \epsilon$  in the engine 1 of the low octane fuel, when the engine speed is 4,000 rpm, the design engineer determines the valve opening angle CA (deg) so that the following expression is satisfied.

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1306.9 \leq CA \leq 298 \quad (57'')$$

or

$$-12.162(\epsilon+1.3)+411.24 \leq CA \leq -0.9096(\epsilon+1.3)^2-47.634\epsilon+753.28 \quad (58'')$$

If the correction term D according to the engine speed NE (rpm) of the engine 1 is used similar to the above, the relational expression of  $\epsilon$  and CA in Layer 2 and Layer 3 in the engine 1 of the low octane fuel can be expressed as follows.

66

If the geometric compression ratio  $\epsilon$  is  $12.2 \leq \epsilon < 12.7$ ,

$$-40(\epsilon+1.3)+800+D \leq CA \leq 60(\epsilon+1.3)-550+D \quad (53^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $12.7 \leq \epsilon < 14.7$ ,

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+287.68+D \leq CA \leq 290+D \quad (54^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $14.7 \leq \epsilon < 15$ ,

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq 290+D \quad (55^{(3)})$$

or

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+287.68+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D \quad (56^{(3)})$$

If the geometric compression ratio  $\epsilon$  is  $15 \leq \epsilon$ ,

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq 290+D \quad (57^{(3)})$$

or

$$-12.162(\epsilon+1.3)+403.24+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634\epsilon+745.28+D \quad (58^{(3)})$$

Note that although illustration is omitted, the design engineer may determine CA within the overlapping range of the  $\epsilon$ -CA valid range of the upper graph 2501 and the  $\epsilon$ -CA valid range of the lower graph 2502 of FIG. 25. Similar to the above, the design engineer can set the control logic which suits both the engine 1 using the high octane fuel and the engine 1 using the low octane fuel by determining CA within the overlapping range of the two occurring ranges.

(2-5) Procedure of Method of Implementing Control Logic

Next, a procedure of the method of implementing the control logic of the engine 1 for executing the SPCCI combustion will be described with reference to the flowchart illustrated in FIG. 26. The design engineer can perform each step using a computer. The computer stores information on the  $\epsilon$ -CA valid range illustrated in FIGS. 23, 24, and 25.

At Step S261 after the procedure starts, the design engineer first sets the geometric compression ratio  $\epsilon$ . The design engineer may input the set value of the geometric compression ratio  $\epsilon$  into the computer.

At the following Step S262, the design engineer sets the valve opening angle of the exhaust valve 22. This corresponds to determining the cam shape of the exhaust valve 22. The design engineer may input the set value of the valve opening angle of the exhaust valve 22 into the computer. Thus, a hardware configuration of the engine 1 can be set at Steps S261 and S262.

At Step S263, the design engineer sets the operating state comprised of the load and the engine speed, and at the following Step S264, the design engineer selects CA based on the  $\epsilon$ -CA valid range (FIGS. 23, 24, and 25) stored in the computer.

Then, at Step S265, the computer determines whether the SPCCI combustion can be achieved based on CA set at Step S264. If the determination at Step S265 is YES, this procedure shifts to Step S266, and the design engineer determines the control logic of the engine 1 so that the SPCCI combustion is performed in the operating state set at Step S263. On the other hand, if the determination at Step S265 is NO, this procedure shifts to Step S267, and the design engineer determines the control logic of the engine 1 so that SI combustion is performed in the operating state set at Step S263. Note that at Step S267, the design engineer may again

set the valve opening angle CA of the intake valve 21 in consideration of performing the SI combustion.

As described above, the method of implementing the control logic of the compression ignition engine disclosed herein determines the relationship between the engine geometric compression ratio  $\epsilon$  and the valve opening angle CA of the intake valve 21. The design engineer can determine the valve opening angle CA of the intake valve 21 within the range where the relationship is satisfied. The design engineer can implement the control logic of the engine 1 by less time and labor compared with the conventional arts.

Other Embodiments

Note that the application of the technology disclosed herein is not limited to the engine 1 having the configuration described above. The engine 1 may adopt various configurations.

For example, the engine 1 may be provided with a turbocharger, instead of the mechanical supercharger 44.

It should be understood that the embodiments herein are illustrative and not restrictive, since the scope of the invention is defined by the appended claims rather than by the description preceding them, and all changes that fall within metes and bounds of the claims, or equivalence of such metes and bounds thereof, are therefore intended to be embraced by the claims.

DESCRIPTION OF REFERENCE CHARACTERS

- 1 Engine
- 10 ECU (Control Part)
- 17 Combustion Chamber
- 23 Intake-side Electric S-VT (Variable Valve Operating Mechanism)
- 25 Ignition Plug (Ignition Part)
- 44 Supercharger
- 55 EGR System
- 6 Injector (Fuel Injection Part)
- SW1 Airflow Sensor
- SW2 First Intake-air Temperature Sensor
- SW3 First Pressure Sensor
- SW4 Second Intake-air Temperature Sensor
- SW5 Second Pressure Sensor
- SW6 Pressure Indicating Sensor
- SW7 Exhaust Temperature Sensor
- SW8 Linear O<sub>2</sub> Sensor
- SW9 Lambda O<sub>2</sub> Sensor
- SW10 Water Temperature Sensor
- SW11 Crank Angle Sensor
- SW12 Accelerator Opening Sensor
- SW13 Intake Cam Angle Sensor
- SW14 Exhaust Cam Angle Sensor
- SW15 EGR Pressure Difference Sensor
- SW16 Fuel Pressure Sensor
- SW17 Third Intake-air Temperature Sensor

What is claimed is:

1. A method of implementing control logic of a compression ignition engine, the engine comprising:
  - an injector configured to inject fuel to be supplied in a combustion chamber;
  - a variable valve operating mechanism configured to change a valve timing of an intake valve;
  - an ignition plug configured to ignite a mixture gas inside the combustion chamber;
  - at least one sensor configured to measure a parameter related to an operating state of the engine; and

a processor configured to output a signal to the injector, the variable valve operating mechanism, and the ignition plug, according to control logic corresponding to the operating state of the engine, in response to the measurement of the at least one sensor, the processor outputting the signal to the ignition plug in a specific operating state defined by an engine load and an engine speed so that unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber,

the method comprising the steps of:  
determining a geometric compression ratio  $c$  of the engine; and

determining the control logic defining a valve opening angle CA of the intake valve, utilized by the processor to generate a signal to the injector, the variable valve operating mechanism, and the ignition plug,

wherein, when determining the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied:

if the geometric compression ratio  $\epsilon$  is  $\epsilon < 14$ ,

$$-40\epsilon + 800 + D \leq CA \leq 60\epsilon - 550 + D$$

and if the geometric compression ratio  $\epsilon$  is  $14 \leq \epsilon < 16$ ,

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 290 + D$$

and if the geometric compression ratio  $\epsilon$  is  $16 \leq \epsilon < 16.3$ ,

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq 290 + D$$

or

$$-0.7246\epsilon^2 + 6.7391\epsilon + 287.68 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D$$

and if the geometric compression ratio  $\epsilon$  is  $16.3 \leq \epsilon$ ,

$$-3.9394\epsilon^2 + 159.53\epsilon - 1314.9 + D \leq CA \leq 290 + D$$

or

$$-12.162\epsilon + 403.24 + D \leq CA \leq 0.9096\epsilon^2 - 47.634\epsilon + 745.28 + D,$$

where D is a correction term according to the engine speed NE (rpm),

$$D = 3.3 \times 10^{-10} NE^3 - 1.0 \times 10^{-6} NE^2 + 7.0 \times 10^{-4} NE.$$

2. The method of claim 1, wherein a valve close timing of the intake valve changes as the operating state of the engine changes, and wherein the valve opening angle CA (deg) is determined for each operating state.

3. The method of claim 1, wherein the engine operates in a low-load operating state where the load is a given load or lower, according to the control logic.

4. The method of claim 1, wherein the engine has:  
a first mode in which the processor outputs a signal to each of the injector and the variable valve operating mechanism so that an air-fuel ratio (A/F) that is a weight ratio of air contained in the mixture gas inside the combustion chamber to the fuel becomes leaner than a stoichiometric air fuel ratio, and outputs a signal to the ignition plug so that the unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber, and  
a second mode in which the processor outputs a signal to each of the injector and the variable valve operating mechanism so that a gas-fuel ratio (G/F) that is a weight ratio of the entire mixture gas inside the combustion chamber to the fuel becomes leaner than the stoichiometric

metric air fuel ratio, and the A/F becomes the stoichiometric air fuel ratio or richer than the stoichiometric air fuel ratio, and outputs a signal to the ignition plug so that the unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber.

5. The method of claim 1, wherein the engine is provided with an exhaust gas recirculation (EGR) system configured to introduce burnt gas into the combustion chamber, and

wherein the processor outputs a signal to the EGR system and the ignition plug so that a heat amount ratio used as an index related to a ratio of an amount of heat generated when the mixture gas combusts by flame propagation to the entire amount of heat generated when the mixture gas inside the combustion chamber combusts, becomes a target heat amount ratio defined corresponding to the operating state of the engine.

6. The method of claim 1, wherein the processor outputs a signal to the EGR system and the ignition plug so that the heat amount ratio becomes higher when the load of the engine is higher.

7. A method of implementing control logic of a compression ignition engine using low octane fuel, the engine comprising:

an injector configured to inject fuel to be supplied in a combustion chamber;

a variable valve operating mechanism configured to change a valve timing of an intake valve;

an ignition plug configured to ignite a mixture gas inside the combustion chamber;

at least one sensor configured to measure a parameter related to an operating state of the engine; and

a processor configured to output a signal to the injector, the variable valve operating mechanism, and the ignition plug, according to a control logic corresponding to the operating state of the engine, in response to the measurement of the at least one sensor, the processor outputting the signal to the ignition plug in a specific operating state defined by an engine load and an engine speed so that unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber, the method comprising the steps of:

determining that the fuel is a low octane fuel, determining a geometric compression ratio  $\epsilon$  of the engine; and

determining control logic defining a valve opening angle CA of the intake valve, utilized by the processor to generate a signal to the injector, the variable valve operating mechanism, and the ignition plug,

wherein, when determining the control logic, the valve opening angle CA (deg) is determined so that the following expression is satisfied:

if the geometric compression ratio  $\epsilon$  is  $\epsilon < 12.7$ ,

$$-40(\epsilon+1.3)+800+D \leq CA \leq 60(\epsilon+1.3)-550+D$$

and if the geometric compression ratio  $\epsilon$  is  $12.7 \leq \epsilon < 14.7$ ,

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+287.68+D \leq CA \leq 290+D$$

and if the geometric compression ratio  $\epsilon$  is  $14.7 \leq \epsilon < 15$ ,

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq 290+D$$

or

$$-0.7246(\epsilon+1.3)^2+6.7391(\epsilon+1.3)+287.68+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D$$

and if the geometric compression ratio  $\epsilon$  is  $15 \leq \epsilon$ ,

$$-3.9394(\epsilon+1.3)^2+159.53(\epsilon+1.3)-1314.9+D \leq CA \leq 290+D$$

or

$$-12.162(\epsilon+1.3)+403.24+D \leq CA \leq 0.9096(\epsilon+1.3)^2-47.634(\epsilon+1.3)+745.28+D,$$

where D is a correction term according to the engine speed NE (rpm),

$$D=3.3 \times 10^{-10}NE^3-1.0 \times 10^{-6}NE^2+7.0 \times 10^{-4}NE.$$

8. The method of claim 7, wherein a valve close timing of the intake valve changes as the operating state of the engine changes, and wherein the valve opening angle CA (deg) is determined for each operating state.

9. The method of claim 7, wherein the engine operates in a low-load operating state where the load is a given load or lower, according to the control logic.

10. The method of claim 7, wherein the engine has: a first mode in which the processor outputs a signal to each of the injector and the variable valve operating mechanism so that an air-fuel ratio (A/F) that is a weight ratio of air contained in the mixture gas inside the combustion chamber to the fuel becomes leaner than a stoichiometric air fuel ratio, and outputs a signal to the ignition plug so that the unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber, and

a second mode in which the processor outputs a signal to each of the injector and the variable valve operating mechanism so that a gas-fuel ratio (G/F) that is a weight ratio of the entire mixture gas inside the combustion chamber to the fuel becomes leaner than the stoichiometric air fuel ratio, and the A/F becomes the stoichiometric air fuel ratio, and outputs a signal to the ignition plug so that the unburnt mixture gas combusts by self ignition after the ignition plug ignites the mixture gas inside the combustion chamber.

11. The method of claim 7, wherein the engine is provided with an exhaust gas recirculation (EGR) system configured to introduce burnt gas into the combustion chamber, and

wherein the processor outputs a signal to the EGR system and the ignition plug so that a heat amount ratio used as an index related to a ratio of an amount of heat generated when the mixture gas combusts by flame propagation to the entire amount of heat generated when the mixture gas inside the combustion chamber combusts, becomes a target heat amount ratio defined corresponding to the operating state of the engine.

12. The method of claim 7, wherein the processor outputs a signal to the EGR system and the ignition plug so that the heat amount ratio becomes higher when the load of the engine is higher.

\* \* \* \* \*