

(19)



INTELLECTUAL PROPERTY
OFFICE OF SINGAPORE

(11) Publication number:

SG 188074 A1

(43) Publication date:

28.03.2013

(51) Int. Cl:

;

(12)

Patent Application

(21) Application number: 2012083937

(71) Applicant:

INDIAN INSTITUTE OF TECHNOLOGY
HAUZ KHAS NEW DELHI 110016 IN
SIMPRI INVESTMENT LIMITED P.O BOX
3476 GENERAL POST OFFICE HONG
KONG CN

(22) Date of filing: 14.05.2010

(30) Priority: IN 1001/DEL/2009 15.05.2009

(72) Inventor:

ANOOP CHAWLA DEPARTMENT OF
MECHANICAL ENGINEERING, INDIAN
INSTITUTE OF TECHNOLOGY, DELHI,
NEW DELHI 110016 IN
SUDIPTO MUKHERJEE DEPARTMENT
OF MECHANICAL ENGINEERING,
INDIAN INSTITUTE OF TECHNOLOGY,
DELHI, NEW DELHI 110016 IN

(54) **Title:**

HINGE JOINT SYSTEM

(57) **Abstract:**

Abstract HINGE JOINT SYSTEM The present invention relates to a hinge joint mechanism. The hinge joint mechanism comprises a fixed component including a plurality of curved portions and at least one straight portion; a movable component including a plurality of curved portions and a plurality of straight portions; said hinge joint mechanism provides a relative rotation between the two surfaces of the hinge joints to rotate the movable component by a desired amount relative to the fixed component. The hinge joint mechanism of the invention provides a proper sealing in the joints to avoid liquid or any such kind of material to move across it. Figure 3.

Abstract
HINGE JOINT SYSTEM

The present invention relates to a hinge joint mechanism. The hinge joint mechanism comprises a fixed component including a plurality of curved portions and at least one straight portion; a movable component including a plurality of curved portions and a plurality of straight portions; said hinge joint mechanism provides a relative rotation between the two surfaces of the hinge joints to rotate the movable component by a desired amount relative to the fixed component. The hinge joint mechanism of the invention provides a proper sealing in the joints to avoid liquid or any such kind of material to move across it.

Figure 3.

HINGE JOINT SYSTEM

Technical Field

The present disclosure relates to a hinge mechanism and more specifically to a hinged component.

Background

Various types of Hinge Joints have been developed in the art. They provide a simple, efficient method of allowing two or more components to move about one another in a designated manner. Their simple construction and efficient performance, makes the hinge joints to be found in many everyday products, building structures, vehicles, and complex systems.

Perhaps the most common or well-known type of hinged joints comprises a movable member, such as a door or a lid, coupled to a stationary base or receiver capable of receiving the movable member and allowing the movable member to come to rest within the base or receiver. This fitting incorporates a hole to receive a pin therein which is affixed to a lock bar. The ends of the lock bar bend inwardly to press against the frame and the door for door locking purposes.

Moreover such pin based hinge joints fail to provide proper sealing in the joints to make them completely intact with each other.

Profiled hinged joints are also known in the art. Said joints have fixed member and movable member that is capable of partially rotating in the slot of the fixed member as disclosed in US4315345. The fixed member is having a hollow circular bead portion connected to the flange. This invention also does not restrict assembly / disassembly in non-axial directions.

The bead member is partially surrounded by a shell which protrudes from the flange. The gap between the shell and the bead member forms a slot in which the movable member rotates around the bead member. Said design does not provide any sealing properties as the slot in which the movable part rotates is not an enclosed structure preventing leakage.

Moreover, other similar kinds of hinge joints fail to gain widespread acceptance either because of their relatively complicated nature, their appearance or inability to provide the necessary degree of desired protection.

Summary

To obviate the aforesaid drawback, the present disclosure seeks to overcome these by providing a hinge joint mechanism with relatively better sealing across the joint and simpler construction because of a reduced number of components.

Therefore, it is an object of the present disclosure to provide a hinge mechanism with simple construction and said mechanism provides relative rotation between the two surfaces of the hinge joints such that movable part can rotate by a desired amount relative to fixed part.

To achieve said objectives the present disclosure provides a hinge joint mechanism comprising a fixed component includes a plurality of curved portions and at least one straight portion; a movable component includes a plurality of curved portion and a plurality of straight portions; wherein said hinge joint mechanism provides a relative rotation between the two surfaces of the hinge joints to rotate the movable component by a desired amount relative to the fixed component.

Brief description of the accompanying drawings:

The invention, together with its objects and advantages thereof may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify substantially like elements in the several figures and in which:

Figure 1 shows hinge joint mechanism in its open position.

Figure 2 shows hinge joint mechanism in its closed position.

Figure 3 shows hinge joint mechanism description in open position according to the present invention.

Figure 4 shows hinge joint mechanism description in closed position according to the present invention.

Figure 5 shows the operation of hinge joint position at first stage.

Figure 6 shows the operation of hinge joint position at second stage.

Figure 7 shows the operation of hinge joint position at third stage.

Figure 8 shows the operation of hinge joint position at fourth stage.

Figure 9 shows the operation of hinge joint position at fifth stage.

Detailed description of the invention

For the purpose of promoting an understanding of the principles of the invention, reference will now be made to the embodiment illustrated in the drawings and

specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended, such alterations and further modifications in the illustrated bag, and such further applications of the principles of the disclosure as illustrated therein being contemplated as would normally occur to one skilled in the art to which the disclosure relates.

The hinge mechanism of the present disclosure provides a proper sealing in the joints to avoid liquid or any such kind of material to move across it.

Figure 1 shows a hinge joint mechanism in its open position. The hinge mechanism contains two parts attached to (or integral to) two surfaces. A fixed part **101** and a movable part **102**.

Figure 2 shows a hinge joint mechanism in its closed position. The hinge mechanism contains two parts attached to (or integral to) two surfaces. A fixed part **101** and a movable part **102**.

Figure 3 shows hinge joint mechanism description in open position according to the present invention. The fixed part consists of two curved portions **301** and **302** and a straight portion **303**. Similarly, the movable part also consists of two curved portions **304** and **305** and two straight portions **306** and **307**.

Figure 4 shows hinge joint mechanism description in closed position according to the present invention. The fixed part consists of two curved portions **301** and **302** and a straight portion **303**. Similarly, the movable part also consists of two curved portions **304** and **305** and two straight portions **306** and **307**.

Figure 5 shows the operation of joint in the first stage. In the first stage of motion, the convex surface of the curved portion **304** of the movable part meshes with the concave surface of the curved surface **301** of the fixed part, convex surface of the curved portion **305** of the movable part meshes with concave

surface of the curved portion **302** of the fixed part, and straight portion **306** of the connecting convex segments of the movable part meshes with straight portion **303** of the concave zone of the fixed part.

Figure 6 shows the operation of joint in the second stage. In the second stage of motion, the convex zone of the curved portion **304** of the movable part meshes with the concave zone of the curved portion **301** of the fixed part and convex zone of the curved portion **305** of the movable part meshes with the concave zone of the curved portion **302** of the fixed part.

Figure 7 shows the operation of joint in the third stage. In the third stage of motion the convex zone of the curved portion **304** of the movable part meshes with the concave zone of the curved portion **301** of the fixed part and the convex zone of the curved portion **305** of the movable part meshes with the concave zone of the curved portion **302** of the fixed part. In addition the convex zone of the curved portion **301** contacts the concave zone of the curved portion **305**.

Figure 8 shows the operation of joint in the fourth stage. In the fourth stage of motion, the convex zone of the curved portion **301** of the fixed part meshes with the concave zone of the curved portion **305** of the movable part and convex zone of the curved portion **304** of movable part meshes with the concave zone of the curved portion **301** of the fixed part.

Figure 9 shows the operation of joint in the fifth stage. In the fifth stage of motion, the concave zone of the curved portion **305** of the movable part meshes with the convex zone of the curved portion **301** of the fixed part and the convex zone of the movable part (304) meshes with the concave zone of the fixed part (301); and the surface **303** of the fixed part contacts the surface **307** of the moving part.

Different zones of the fixed component and movable component mesh at a plurality of different angular positions during a hinge motion.

Further, the aforementioned sequence of motion stages results in a rotation between fixed part and movable part thereby causing a movement between the two surfaces **101** and **102** about the centre of rotation (CR) of hinge joint. This hinge joint also allows a predefined level of rotation. Beyond the predefined level of rotation (i.e. 180^0), this rotation hinge point is self locked because in extreme position of the joint curved portion **301** of the fixed part and straight part **303** of the fixed part restrict further movement of curved portion **304** of the movable part and straight part **306** of the movable part respectively.

In the other extreme position of the joint curved portion **302** of the fixed part and straight part **303** of fixed part restrict further movement of straight part **306** and **307** of movable part respectively.

Further, movable part and fixed part can be assembled or disassembled only in axial direction of hinge. The hinge can be optionally be used along with a lock in the locked and unlocked positions.

The hinge mechanism of the present disclosure is used in various appliances/equipment. Said hinge mechanism is used in a container and more particularly in a transport container.

All documents cited in the description are incorporated herein by reference. The present disclosure is not to be limited in scope by the specific embodiments and examples which are intended as illustrations of a number of aspects of the disclosure and any embodiments which are functionally equivalent are within the scope of this invention. Those skilled in the art will know, or be able to ascertain using no more than routine experimentation, many equivalents to the specific embodiments of the described herein.

We claim:

1. A hinge joint mechanism comprising
 - a fixed component includes a plurality of curved portions and at least one straight portion;
 - a movable component includes a plurality of curved portion and a plurality of straight portions;

said hinge joint mechanism provides a relative rotation between the two surfaces of the hinge joints to rotate the movable component by a desired amount relative to the fixed component.

2. The hinge joint mechanism as claimed in claim 1, wherein the movable component rotates with respect to the fixed component as long as the curved portion of the movable component meshes with the curved portion of the fixed component thereby interlocking the movable component and the fixed component.
3. The hinge joint mechanism as claimed in claim 1, wherein the meshing surface of the movable component comprises at least one convex zone and at least one concave zone.
4. The hinge joint mechanism as claimed in claim 1, where the meshing surface of the fixed component comprises at least one convex zone and at least one concave zone.
5. The hinge joint mechanism as claimed in claim 1, wherein the meshing surface of the movable and fixed components comprise a plurality of contiguous zones of different curvatures with or without the same centre of curvatures.
6. The hinge mechanism as claimed in claim 5, wherein said meshing surface optionally includes a surface of infinite curvature.
7. The hinge joint mechanism as claimed in claim 1, wherein different zones of the fixed component and movable component mesh at a plurality of different angular positions during a hinge motion.
8. The hinge joint mechanism as claimed in claim 1, wherein the rotation is limited to a predetermined level depending on the meshing surfaces having different local radius of curvature in different meshing zones.

9. The hinge joint mechanism as claimed in claim 1, wherein the movable portion and the fixed portion are assembled or disassembled only in a substantially axial direction of the hinge joint.

10. The hinge joint mechanism as claimed in the preceding claims is used in a transport container.




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9