



(43) International Publication Date
13 September 2012 (13.09.2012)

(51) International Patent Classification:
A21B 1/48 (2006.01)

(21) International Application Number:
PCT/US2012/028526

(22) International Filing Date:
9 March 2012 (09.03.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13/044,370 9 March 2011 (09.03.2011) US

(71) Applicant (for all designated States except US):
UNITHERM FOOD SYSTEMS, INC. [US/US]; 502 Industrial Road, Bristow, OK 74010 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HOWARD, David** [US/US]; 502 Industrial Road, Bristow, OK 74010 (US).

(74) Agents: **ROSSLER, Paul, E.** et al.; Gable Gotwals, 100 West 5th Street, 10th Floor, Tulsa, OK 74103-4217 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: AIRFLOW PATTERN FOR SPIRAL OVEN




Fig. 8A

(57) Abstract: An improved spiral oven (10) and method for its use includes the step of using a forward/reversing fan (11) to produce a first airflow (40) and a second inverted airflow (50) in the cooking chamber (15). The proportion of time each airflow occurs may be unbalanced within an oven residence time or cook cycle, and either airflow may begin the cycle. The first airflow creates a flow across the cook belt (25) predominantly at the top and bottom tiers, whereas the second airflow creates this flow predominantly in the middle tiers. A braking resistor allows the fan (11) to quickly changeover between full-forward and full-reverse directions. Because of the reversing airflow pattern, the product cooks more evenly across the cook belt (25).

AIRFLOW PATTERN FOR SPIRAL OVEN

FIELD OF THE INVENTION

This invention relates generally to spiral ovens which are used to cook large quantities of food in commercial food preparation processes. More particularly, the invention relates to apparatuses and methods to create airflow patterns within the cook chamber of a spiral oven in order to effectively and uniformly heat the product being cooked and produce a desired final, cooked product appearance across the cook belt.

BACKGROUND OF THE INVENTION

Consistently creating a final, cooked product appearance that resembles one typically created in a residential oven has proven to be a far more difficult problem to solve in spiral ovens than it is in linear ovens. Linear ovens cook food using an airflow process known as impingement cooking. In impingement cooking, hot vertical airflow impinges directly upon each individual product flowing along the cook belt of the oven. Impingement cooking produces an acceptable "browned" appearance but comes at the price of increased floor space requirements. For example, a 600-foot (~ 183 m) cook belt requires 600 feet (~ 183 m) of linear oven.

Spiral ovens solve the floor space problem associated with high volume capacity cooking. A 600-foot (~ 183 m) cook belt, for example, can be compressed into a 20' x 20' x 20' (~ 6 m x 6 m x 6 m) box. However, compressing the cook belt creates problems for the heat transfer system needed to cook the product. In a linear oven, the upper surface of each product is exposed to the impingement cooking system. In a spiral oven, indirect cooking methods must be used because the upper (lower) surface of product within the spiral is hidden by the layer of cook belt and product suspended above (below) it. As a result, a product cooked in a spiral oven in no way resembles the color of the product illustrated on the package in which the product is sold. For example, a microwaveable-ready meal of macaroni-and-cheese or au gratin potatoes may appear on the package as having a golden brown finish. The actual product finish is white and anemic-looking. Microwaving by the consumer to heat the product will not change the color.

Prior art spiral ovens (see FIGS. 1 to 4) have adopted various ways to uniformly distribute and transfer heat to the product being cooked on the belt. One prior art spiral oven (FIG. 1) employs a thermal coil arrangement at one end of the oven and a fan and vent system arranged to create airflow both vertically through the belt mesh of the spiral conveyor and horizontally through the side-links of the conveyor. The fan operates in a single direction of

rotation. An example of this airflow system and method is found in JBT FoodTech's (Chicago, Illinois) Stein GYROCOMPACT® II-1000 Oven.

Another prior art spiral oven (FIG. 2) employs a first, lower section cooking zone in which heat is provided by horizontal airflow and a second, upper section cooking zone in which high-velocity hot air impinges vertically on the product being conveyed. The fan operates in a single direction of rotation. An example of this airflow system and method is found in CFS's (The Netherlands) COOKSTAR® three-zone, double-spiral cooker.

Yet another prior art spiral oven (FIG. 3) employs a cylindrical fan and air circulation system arranged to circulate air around all sides of the spiral conveyor and create airflow both horizontally across the conveyor and vertically upward through the belt mesh of the spiral conveyor. The fan operates in a single direction of rotation. An example of this airflow system and method is found in Heat and Control, Inc.'s (Hayward, California) Model SO Twin Drum Spiral Oven.

A final prior art spiral oven (FIG. 4) employs a fan and air circulation system arranged to provide an airflow pattern that impinges upon the outer edge of the belt and flows horizontally across and vertically through the belt mesh of the spiral conveyor. The fan operates in a single direction of rotation. An example of this airflow system and method is found in Unitherm Food Systems, Inc.'s (Bristow, Oklahoma) spiral oven.

All prior art spiral ovens are designed to provide a substantially uniform airflow across the cook belt because conventional wisdom in the art of spiral oven design holds that a non-uniform airflow across the belt is not desirable and must be avoided.

SUMMARY OF THE INVENTION

A method of heating a food product being conveyed on a cook belt in a spiral oven includes the steps of producing a first and second airflow between an upper and lower portion of the cooking chamber of the oven, with the second airflow being inverted relative to the first. A
5 desired cooking effect is achieved by alternating between the two airflows during a cook residence cycle. A desired effect may also be achieved by operating the spiral oven with the first airflow occurring for a different amount of time than the second airflow during the cook residence cycle. The addition of ducting or shielding can also be used in combination with the alternating first and second airflows. The first airflow also creates a horizontal flow across the
10 cook belt predominantly at the top and bottom tiers, whereas the second airflow creates this horizontal flow predominantly in the middle tiers. The cycle can start with either the first airflow or the second airflow.

Fan speed can be controlled to increase or decrease the airflow patterns within the spiral oven. The forward/reversing fan can be prevented from running at its maximum speed when
15 operating in the reverse direction and a braking resistor can be used so that the fan can quickly changeover between the full-forward and full-reverse directions. Because of the reversing airflow pattern, the product cooks more evenly across the cook belt than with the prior art methods.

An improved spiral oven made according to this invention has a forward/reversing fan
20 located in an upper portion of the spiral oven and means for distributing the air produced by the fan within a cooking chamber of the spiral oven. The fan alternates between a first direction of rotation and a second direction of rotation during a timed cycle "T". The first direction of rotation may represent a greater proportion of the timed cycle T than the second direction, or the proportion of time between the two directions may be substantially even. Additionally, the first
25 or second direction of rotation can begin the cycle. Further, the cycle can begin at the halfway point (or some other proportion of) the forward or reverse timed cycle. A braking resistor can be placed in communication with the fan motor.

Objects of this invention are to (1) provide an airflow pattern within the cook chamber of a spiral oven that accounts for the unbalanced loading of product as the cook belt traverses bends
30 within the spiral oven; (2) transfer the appropriate amount of heat to each product across the cook belt regardless of where the product is located on the belt; (3) provide uniformity of color development of product across the cook belt without degrading the CPET tray that each product may be contained within; (4) reduce or eliminate temperature differences between product

located on the inside, middle and outside portions of the cook belt; and (5) provide a system and method of reversing airflow that existing ovens can take advantage of through relatively low cost retrofits.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a prior art spiral oven that employs a thermal coil arrangement at one end of the oven and a fan and vent system arranged to create airflow vertically through the belt mesh of the spiral conveyor and horizontally through the side links of the conveyor. The fan operates in a single direction of rotation.

FIG. 2 is a prior art spiral oven that employs a first, lower section cooking zone in which heat is provided by horizontal airflow and a second, upper section cooking zone in which high-velocity hot air impinges vertically on the product being conveyed. The fan operates in a single direction of rotation.

FIG. 3 is a prior art spiral oven that employs a cylindrical fan and vent system arranged to circulate air around all sides of the spiral conveyor and create airflow horizontally across the conveyor and vertically upward through the belt mesh of the conveyor. The fan operates in a single direction of rotation.

FIG. 4 is a prior art spiral oven that employs a fan and vent system arranged to provide an airflow pattern that impinges upon the outer edge of the belt and flows horizontally across and vertically through the belt mesh of the conveyor. The fan operates in a single direction of rotation.

FIG. 5 illustrates the typical product spacing or loading of product entering the inlet side of a spiral oven and prior to the product encountering the first bend in the conveyor. The product is loaded into individual trays spaced substantially equidistant from one another across the belt.

FIG. 6 illustrates the product spacing as the product of FIG. 5 traverses the first bend of a spiral oven. The belt collapses toward the inside of the bend and the product spacing significantly changes as a result. Product located toward the inside of the belt moves closer together, thereby allowing less heat transfer, and product located toward the outside of the belt moves farther apart, thereby allowing more heat transfer.

FIG. 7 illustrates the finish color of product as it exits a prior art spiral oven like those in FIGS. 1 to 4 whose cook belt has been uniformly loaded and exposed to unidirectional airflow that is intended to be uniform across the belt. Product located toward the outside of the spiral cook belt has a much darker finish than product located toward the inside of the cook belt.

FIGS. 8A & B illustrate the airflow pattern created by a preferred embodiment of a spiral oven made and operated according to this invention. The oven includes a forward/reversing fan and vent system that provides an airflow pattern that is not uniform across the conveyor belt. The fan reverses its direction of rotation during certain time intervals to produce an inverted

airflow (*see* FIG. 8B). Fan rotation in the forward direction may occur for a different amount of time than fan rotation in the reverse direction. Either direction may start the cycle.

FIG. 9 illustrates the finish color of product as it exits the spiral oven of FIGS. 8A & B. Because the reversing and inverted airflow pattern accounts for the uneven product spacing, it creates a substantially uniform temperature of the finished product across the belt. Therefore, the product exiting the oven has a substantially same, golden brown finish.

List of element numbers used in FIGS. 8A to 9.

	10	Spiral oven cooking system	25	Cook belt
	11	Forward/reversing fan	27	Inlet opening side to 10
10	13	Heating elements	29	Outlet opening side to 10
	15	Cooking chamber	31	Inner edge of 25 (toward center of oven)
	17	Air cones or corner nozzles	33	Outer edge of 25 (toward walls of oven)
	19	Injection ring	40	Forward airflow pattern
	21	Fan motor	50	Reverse or inverted airflow pattern
15	23	Fan blades		

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A spiral oven made according to this invention creates a controlled airflow pattern that better reflects the heat transfer demands of the product being cooked in the oven. Because the product to be cooked is loaded uniformly across the width of the cook belt, prior art spiral ovens (see e.g. FIGS. 1 to 4) are designed to provide a unidirectional airflow pattern within the cooking chamber and, therefore, a substantially uniform airflow across the belt. The width of the cook belt in most commercial spiral ovens ranges between 12 and 42 inches (~ 31 cm and 61 cm).

Regardless of the width of the cook belt, a loading pattern must be determined relative to the size of the tray in which the product or meal to be cooked is placed. Consider a 40-inch wide (~ 102 cm) cook belt loaded with trays that are 7 inches wide (~ 18 cm), 10 inches long (~ 25 cm), and 2 inches deep (~ 5 cm) (see FIG. 5). The trays are typically CPET trays used for microwaveable-ready meals. If the cook belt is loaded four trays across, with the trays arranged short side leading, the longitudinal centerline of the first or inside tray is located about 5.9 inches (~ 15 cm) from the inner edge of the belt (see FIG. 5). The longitudinal centerline of the second tray is located about 15.3 inches (~ 38.9 cm) from the inner edge and the longitudinal centerline of the third tray is located about 24.7 inches (~ 62.7 cm) from the inner edge. The fourth or outside tray is located about 34.1 inches (~ 86.6 cm) from the inner edge (5.9 inches [~ 15 cm] from the outer edge). In actual practice, the tray spacing may not be this precise, but the idea is to present products for cooking which are spaced substantially equidistant from one another on the cook belt. Each row of trays across the cook belt is also spaced substantially equidistant from the adjacent row of trays across the belt.

If the cook belt is loaded five trays across, then the longitudinal centerline of the first tray is located about 4-1/3 inches (~ 11 cm) from the inner edge of the belt. The longitudinal centerline of the fifth tray is located about 35-2/3 inches (~ 90 cm) from the inner edge. Because of this equal spacing or product loading, the uniform airflow being provided should result in equal air to and around each product and, therefore, substantially uniform heat transfer effects.

Although the above is how all prior art spiral ovens are designed to operate (and do operate), spiral ovens do not cook uniformly across the belt because a uniform airflow pattern does not take into account what happens to the product as it traverses around a spiraled cook belt. At the entrance of the spiral oven, the cook belt is a straight run and product loading across the belt is substantially equal as described above. However, once the product arrives at the first bend of the cook belt, the product spacing changes.

Referring now to FIG. 6, in order for the cook belt to spiral about within the interior space of the oven, the belt must collapse along its inside edge as it traverses the bend and, conversely, expand along its outside edge. This change in the cook belt results in compressed spacing of the trays located toward the inner edge of the belt and expanded spacing of the trays located toward the outer edge. Because there are no straight runs of the cook belt within the cook chamber, this changed and unequal spacing remains throughout the cook residence time. Therefore, the innermost product is shielded from the uniform airflow by the adjacent product and the outermost product is exposed to more space and airflow. Although equal air may be delivered, the deflection of the air created by the changed and unequal spacing affects the heat transfer and energy being absorbed by each product. As the products continue to progress through the oven, the outermost product experiences a lot more air and heat transfer than does the innermost product. The end result is a variation in color and browning of about two whole shades, with product located toward the inner edge of the cook belt having a white or anemic finish and product located nearer the outer edge of the cook belt having a browner finish (see FIG. 7).

Referring now to FIGS. 8A & 8B, an improved spiral oven cook system 10 uses a forward/reversing (bidirectional) fan 11 to deliver air in two different directions 40, 50 throughout a resident cook cycle, preferably in a non-even pattern. Heating elements 13 located above the fan 11 provide heated cooking medium, which is delivered into the cooking chamber 15 by way of a ducting system such as airflow cones or corner nozzles 17. The corner nozzles 17 may include deflectors (not shown) or other means for completing or partially blocking airflow. The cooking chamber may also include impingement nozzles (not shown) located directly above the cook belt. Similar to the corner nozzles 17, the impingement nozzles may also include deflectors or other means for closing the nozzles. Steam may also be introduced into the cooking chamber 15 by way of an injection ring 19 positioned between the fan 11 and the heating elements 13. Alternatively, or in addition to, steam can be injected into the cooking chamber by way of a second steam injection ring (not shown) located toward the bottom of the cooking chamber 15.

Fan 11 includes a fan motor 21 preferably equipped with a braking resistor (not shown) in order to allow fan 11 to quickly changeover between full speed forward and full speed reverse.

The importance of a quick changeover between forward and reverse is discussed below. Additionally, the blades 23 of fan 11, if being used to retrofit an existing oven, will most likely require a higher pitch than the blades of a standard forward fan typically used in spiral ovens.

The product to be cooked is loaded in trays T, which are spaced substantially evenly across the cook belt 25. The cook belt 25 is substantially a straight run on the conveyor inlet and outlet opening sides 27; 29. As is typical in spiral ovens, cook belt 25 continuously conveys the product P in trays upwardly in the cooking chamber 15 in a spiral pattern. At the same time, the fan 11, when in the forward direction, circulates the heated cooking medium within the cooking chamber 15 in a forward airflow pattern 40 (see FIG. 8A). In this airflow pattern 40, fan 11 draws the heated cooking medium upwardly from the cooking chamber 15 and the medium then flows back into the cooking chamber 15 downwardly along or toward the outer edge 33 of the cook belt 25 by way of the nozzles 17. When fan 11 is operating in the reverse direction, reverse or inverted airflow pattern 50 results (see FIG. 8B). In this airflow pattern 40, fan 11 draws the heated cooking medium upwardly along the outer edge 33 of the cook belt 25 and through the nozzles 17 and then flows the medium downwardly through the center of the cook belt 23, that is, along or toward the inner edge 31 of the cook belt 25. As the airflow pattern switches between a forward pattern 40 and reverse pattern 50, the products P are indirectly cooked as they travel upwardly through the cooking chamber 15

By providing a first, forward airflow 40 for a predetermined time "T1" and a second, inverted airflow 50 for a predetermined time "T2", heat transfer and color development are better matched to the unequal loading that occurs when cook belt 25 has collapsed toward its inner edge 31 to traverse a bend. As the experimental results below demonstrate, the temperature difference between the inside-most finished product and the outside-most finished product generally decreased as first airflow time T1 increased to about 80% of the total airflow cycle time, "T". Because the non-uniform, inverted airflow pattern 40, 50 accounts for the uneven product spacing, it creates a substantially uniform temperature gradient of product across the belt. Therefore, all of the product across the cook belt has a substantially same, golden brown finish (see FIG. 9). Variation in color and browning across the belt was limited to about one-half or less of a shade difference.

Depending on the desired cook results, airflows 40 and 50 may be practiced with the addition of ducting and shielding in the spiral oven. The addition of ducting and shielding may be arranged so as to achieve a more consistent cooked product across the belt with a substantially balanced airflow between airflows 40 and 50.

Experimental Results

Reversing Fan Testing and Implementation Procedure General

A forward/reversing (bidirectional) fan was used on a Unitherm Food Systems, Inc's spiral oven ("the Unitherm spiral oven") similar to the one illustrated in FIGS. 8A & 8B to investigate the benefits of reversing the direction of airflow multiple times during the cooking process. Testing was first performed without heat, in order to compare airflow volume between a standard spiral oven (unidirectional) fan and a forward/reversing fan made according to this invention. Then, testing was performed at typical operating temperatures to determine the effects of reversing fan speed and forward-and-reverse balance on actual product.

From preliminary testing on, and experience with, spiral ovens, the inventor had learned there is a general temperature gradient across the width of the cook belt due to the net direction of airflow during circulation. A standard spiral oven fan draws air from the center of the drum and delivers the air to the cook chamber through nozzles directed toward the cook belt. The typical nozzle arrangement in combination with this airflow creates a temperature gradient, with higher temperatures experienced toward the outside of the cook belt (*i.e.*, toward the walls of the oven) and gradually cooler temperatures experienced toward the inside of the belt (*i.e.*, toward the center of the oven). Although this temperature gradient can be minimized through the use of several techniques, for certain products those same techniques compromise desirable attributes such as browning. The forward/reversing fan was implemented as a way to ensure the hottest air is not always delivered to the same location on the cook belt, therefore minimizing the temperature gradient across the belt while at the same time improving browning performance across the belt.

Preliminary Considerations

Upon selecting a fan blade for the forward/reversing fan, it was determined that the maximum fan flow volume of a forward/reversing fan when operating in the reverse direction and equipped with a same diameter and pitch fan blade as a standard blade, is only about 60% that of a forward-direction fan. Therefore, a fan blade with a higher pitch than a standard fan blade was selected to minimize this differential so that a seamless retrofit to an existing Unitherm spiral oven like that shown in FIG. 4 could be achieved. However, in a spiral oven built according to this invention, the fan pitch can be selected to suit the diameter of the fan. Similarly, fan speed can be controlled to increase or decrease airflow patterns. Therefore, the selected pitch angle is the one appropriate to a fan diameter and speed relevant to the desired airflow pattern. For example, selecting a different pitch angle, in turn, forces a change in the fan

speed required to get the same or similar desired airflow pattern. The pitch angle could be in the range of 5 to 90%.

Other considerations in implementing a forward/reversing fan included minimizing the time needed to changeover from full-speed forward rotation to full-speed reverse rotation. Decreased changeover time is desirable to minimize the amount of time in the cooking chamber that cooked product experiences no forced airflow ("dead time"). During preliminary testing, different ramp rates in the motor drives were tried as well as the use of a braking resistor to quickly slow the rotation of the forward/reversing fan. The braking resistor proved best in decreasing and minimizing the changeover time between full-speed forward and reverse rotation.

Another consideration was the nozzle configuration. The Unitherm spiral oven included corner nozzles located toward and about the walls of the oven and directed inward and impingement nozzles located directly over the cook belt. To ensure that product throughout an oven residence cycle experienced generally the same airflow conditions, the impingement nozzles located over the belt would need to be closed fully so that the same hot air movement is experienced by product on the top tier regardless of whether a forward or reverse fan cycle occurs. For example, if the impingement nozzles located over the belt were open, the nozzles would deliver hot air directly to product on the top tier of the cook belt during the forward fan cycle but not during the reverse fan cycle. Additionally, the corner nozzles are typically fitted with deflector shields (during standard fan operation) to prevent air from being delivered directly near the outer edge of the belt. Therefore, a different nozzle configuration might prove beneficial for use with a forward/reversing fan. Those different configurations and their results are discussed below in reference to hot oven testing.

Cold Oven Testing

An initial discovery was that the forward/reversing fan with the higher pitched fan blades could not run at the same speed as a standard fan with its standard pitched fan blades. An adjustment was made through pulley ratios that allowed the forward/reversing fan to operate at its motor's designed operating speed. This had positive improvements to overall air velocity and volume. Cold airflow measurement revealed the pressure naturally developed in the cooking chamber produced nearly identical flow rates for the two styles of fan blades (standard and reversing). The pulley ratio for the standard fan gave a full speed of 1235 rpm, while the pulley ratio for the forward/reversing fan provided 864 rpm. Measureable horizontal airflow across the cook belt with the forward/reversing fan in the standard (forward) rotation was predominantly at the top and bottom sections of the tiers of the belt. When the fan direction was reversed,

measurable airflow was detected in the middle-to-upper tier ranges, which provides a new location within the cooking chamber experiencing measurable airflow.

Hot Oven Testing

Hot oven testing was performed at typical operating temperatures ranging from 350° F –
5 417° F (~ 177° C – 214° C). Fan speeds ranging from 864 to 950 rpm were tested. All tests
were done with measurements gathered from the outside, center, and inside sections of the cook
belt. Reversing cycles were set at a predetermined cycle time (*e.g.* 4 minutes or 240 seconds),
and each cycle consisted of one forward-direction timed cycle and one reverse-direction timed
cycle. For example, a 240 second, 75:25 reversing cycle meant the fan rotated in the forward
10 direction for 180 seconds and in the reverse direction for 60 seconds.

The hot oven testing made use of temperature data logging probes and fell into one of
four categories: (1) aluminum blocks (for a damping effect); (2) open-air; (3) client test product,
namely, macaroni & cheese and scalloped potatoes in CPET trays, as it traversed through the
oven; and (4) product temperatures taken one minute after exiting the oven in addition to a
15 browning color test of the top surface of the product. This last category of testing used a client's
conventional test methods for determining the quality of the cooked product and variation in
color across the cook belt.

The first test was performed with the corner nozzle deflectors in place to direct air from
the nozzles slightly away from the outer edge of the belt (*i.e.*, toward the oven wall). A
20 residence cycle was run with temperature probes in blocks and the forward/reversing fan in full
forward direction, in full reverse direction, then in a split of 50% forward and 50% reverse
balance (a 50:50 forward-reverse split). Table 1 presents the results.

The results generally indicate (1) the forward only direction mimicked what was seen
with a standard fan, with the outer edge of the cook belt having the highest temperature; (2) the
25 reverse only direction had a much higher temperature reading on the inside edge of the belt, and
(3) the 50:50 forward-reverse split had a lower but still significantly higher temperature on the
inside edge of the belt. From this test it was concluded that the deflectors on the corner nozzles
provided a dampened forward airflow at the outside of the cook belt compared to the reversing
airflow coming down the center of the drum (and along the inside of the belt). Therefore, the
30 deflectors were removed for all subsequent testing, leaving open nozzles in the corners of the
oven.

Table 1. Baseline Probe Temperature Differences in °F for Forward Only, Reverse Only, and 50:50 Forward/Reverse Cycle with Corner Nozzle (Bottom Hole, Top Slot) Deflectors Directing Air away from Outside Edge of Cook Belt and Impingement Deflectors Fully Closed.

Reversals and Cycle Time	Fan Setting	Temp. (°F)	Humidity (%)	Fan Speed (% max / rpm)	Residence Time (min.)	Probe Temperature			Range in Probe Temp.
						Outside Probe	Center Probe	Inside Probe	
–	Forward only	415	55	100 / 1202	39	–	–	–	–
0 reversals	Forward only	350	0	79 / 950	8	181	173	174	8
				78 / 936		182	162	165	20
240 sec.	Reverse only	350	0	78 / 936	8	156	175	211	-55
						157	176	207	-50
4 reversals 240 sec.	50:50 w/ reverse start	350	0	78 / 936	8	168	173	194	-26
	50:50 w/ forward start	350	0	78 / 936	8	165	170	188	-23
	50:50 w/ forward start	350	0	78 / 936	8	164	169	180	-16

5

A series of tests were then performed in which the percentage balance of forward/reverse time was adjusted. The results of those tests are shown in Table 2. With the oven configuration determined, a 50/50 split still resulted in a higher inside belt temperature, albeit less than with the deflectors in place. Forward rotation time was increased for a given cycle until a temperature

10

Table 2. Baseline Probe Temperature Differences in °F for Various Forward/Reverse Fan Settings with Corner Nozzle Deflectors Open and Impingement Deflectors Fully Closed.

Reversals and Cycle Time	Fan Setting	Temp. (°F)	Humidity (%)	Fan Speed (% max / rpm)	Residence Time (min.)	Probe Temperature			Range in Probe Temp.
						Outside Probe	Center Probe	Inside Probe	
Large blocks to match large trays									
4 w/ fwd. start 240 sec.	50:50	350	0	78 / 936	8	164	169	180	-16
	75:25	350	0	78 / 936	8	172	173	182	-10
						170	162	187	-25
						167	166	184	-18
	80:20	350	0	78 / 936	8	182	173	176	9
						167	163	169	-6
						169	165	170	-5
	16 w/ fwd. start 240 sec.	81.25: 18.75	350	0	78 / 936	8	170	165	169
173							166	171	7
Open-Air Measurement									
16 w/ fwd. start 263 sec.	81:19	385	0	78 / 936	35	320	310	328	-18
				70 / 840		316	302	315	14
Small blocks to match small trays									
7 w/ rev. start 234 sec.	70:30	395	0	70 / 840	27	289	284	297	-13
	75:25					290	286	296	-10
	80:20					290	282	296	-14

- 5 probe differential of less than 7°F (~ -14° C) was achieved at an oven temperature of 350°F (~ 177° C) (with a balance of about 81% forward time and 19% reverse time). A similar test was conducted with open-air temperature measurements. The results shown in Table 2 provided a baseline starting point for product testing.

10 Product testing was performed with macaroni & cheese in CPET trays and au gratin potatoes, also in CPET trays. Selected oven temperature and residence time were selected to replicate the temperature and residence time used by the client when cooking those particular products. Temperature probes were buried in the center of the product to monitor temperature

throughout the residence cycle. Incremental product temperature data were collected after exiting the oven. Tables 3 and 4 present the results. Note that in some tests the cycle started with a reverse airflow and in others the cycle started with a forward airflow. The conclusion was that product temperature and browning (color) difference were minimized at a fan direction
 5 balance of 80% forward rotation and 20% reverse direction within an oven residence cycle.

Table 3. Product Temperatures of Macaroni & Cheese Cooked in Small and Large Trays under Replicated Client Oven Temperatures and Residence Cycle Time.

Reversals and Cycle Time	Fan Setting	Temp. (°F)	Humidity (%)	Fan Speed (% max / rpm)	Residence Time (min.)	Time after Exit (min.)	Probe Temperature			Range in Probe Temp.
							Outside Probe	Center Probe	Inside Probe	
Large trays										
10 w/ rev. start 234 sec.	60:40	417	0	70 / 840	39	-	192	169	188	19
	80:20						183	173	165	18
	65:35	395					162	159	163	-4
Small trays										
7 w/ rev. start 234 sec.	65:35	395	0	70 / 840	27	-	156	164	169	-13
	70:30						160	155	165	-10
	80:20		40	100 / 864	27		187	180	179	8
7 w/ fwd start 234 sec.	80:20	395	40	100 / 864	27	-	183	180	180	3
						1	187	183	182	5
						2	184	183	181	3
						3	178	181	179	2
						4	172	179	175	7
Small blocks to match small trays										
7 w/ fwd. start 234 sec.	80:20	395	0	100 / 864	27	-	300	291	298	9
			40				302	295	302	7

Table 4. Product Temperatures of Au Gratin Potatoes Cooked in Large Tray under Replicated Client Oven Temperatures and Residence Cycle Time.

5 Product Entering Oven at Halfway Point of Forward Cycle.

Reversals and Cycle Time	Fan Setting	Temp. (°F)	Humidity (%)	Fan Speed (% max / rpm)	Residence Time (min.)	Time after Exit (min.)	Probe Temperature			Range in Probe Temp.
							Outside Probe	Center Probe	Inside Probe	
About 10 234 sec.	80:20	395	40	100 /864	38	–	176	172	179	-7

Another test using client product was performed at Unitherm, Inc.'s test facility (Bristow, Oklahoma) with scalloped potatoes in CPET trays using the client's standard temperature measurement methods and browning/color visual approval. This test used a 40% water vapor in addition to the oven temperature cooking. A forward/reverse cycle percentage of 70:30 was selected for a starting point. The product temperature differentials observed across the cook belt are not solely the result of the cook conditions. Product characteristics, which are beyond the experimenter's control, are a source of variance, even within a single lane of product on the cook belt.

Table 5 presents the temperature data of product cooked in the Unitherm test oven prior to its retrofit with the forward/reversing fan. The temperature of the cooked product was taken approximately one minute after leaving the oven. The variation in product temperature across the belt, as measured by the range in temperatures, is about 10% of the average product temperature, with product travelling in the inside lanes about 15° F (~ –9° C) cooler on average than product travelling in the outside lane.

Table 5. Scalloped Potato Product Temperature Data in °F for Non-Reversing Fan Operating at 1235 rpm, Oven Temperature at 385°F (~ 196°C), Humidity 40% and Residence Time of 32 minutes.

Sample	Product Temperature by Lane (1 = outside lane, 4 = inside lane)				Lane 1 – 4 Δ Temp.	Total Range	Coefficient of Variation (%)
	1	2	3	4			
A	165.8	151.8	160.5	156.6	9.2	14.0	8.8
B	169.8	146.8	160.1	147.8	22.0	23.0	14.7
C	165.4	161.6	157.4	142.3	23.1	23.1	14.7
D	169.1	158.0	159.3	145.7	23.4	23.4	14.8
E	160.3	151.0	157.7	151.0	9.3	9.3	6.0
F	155.5	148.5	152.5	147.6	7.9	7.9	5.2
G	164.1	156.6	161.9	151.5	12.6	12.6	7.9
H	162.0	157.6	159.8	146.7	15.3	15.3	9.8
Average	164.0	154.0	158.6	148.6	15.4	15.4	9.9

Tables 6 & 7 present the temperature data of product cooked in the test oven after its retrofit with the forward/reversing fan. As before, the temperature of the cooked product was taken approximately one minute after leaving the oven. The coefficient of variation in product temperature across the belt, as calculated by the range in product temperatures relative to the average product temperature, is about half that experienced in the forward only fan arrangement (about 4 to 5% compared to 10% with the forward only fan). Similarly, the difference in product temperature between product travelling in the inside lane and outside lane is about half that experienced in the forward only fan arrangement (about 4 to 8° F [~ -16 to -13° C] compared to 15° F [$\sim -9^\circ$ C]). Within the forward/reversing fan arrangement, variation in product temperature increased as total residence time decreased. For example, a 36 minute residence time resulted in about a 4% coefficient of variation whereas a 38 minute residence resulted in about a 5% coefficient of variation. However, in both cases, color was a 3 to 4, closer to a 4, with the inside lane darkest by a half shade and middle lanes the lightest. In other words, the shading difference was limited to about a half shade or less.

Table 6. Scalloped Potato Product Temperature Data in °F for 70/30 Forward/Reversing Fan Cycle at 864 rpm, Oven Temperature at 395° F ($\sim 202^\circ$ C), Humidity 40% and Residence Time of 38 minutes.

10 cycles of 228 seconds each (160 seconds forward / 68 seconds reverse)

Sample	Product Temperature by Lane (1 = outside lane, 4 = inside lane)				Lane 1 – 4 Δ Temp.	Total Range	Coefficient of Variation (%)
	1	2	3	4			
A	185.6	181.1	183.0	184.0	1.6	4.5	2.5
B	185.1	183.8	182.4	178.6	6.5	6.5	3.6
C	178.3	175.8	173.6	176.1	2.2	4.7	2.7
D	183.8	167.3	176.0	177.1	6.7	16.5	9.4
Average	183.2	177.0	178.8	179.0	4.2	6.2	3.5

Changes were then made in an attempt to decrease browning. Fan speed was decreased to 778 rpm and residence time was increased one minute to 37 minutes. Table 8 presents the results. Color was again a 3 to 4, closer to a 4, with the inside lane darkest by a half shade and middle lanes the lightest. The cooked product was considered the best looking cooked product in comparison to the previous tests, with product on the inside lane being darker than in the previous runs. However, the trays started to slightly deform at these settings. For example, the long side of some of the trays, most likely those travelling on the inside lane, began to droop. Therefore, experiments were made to the forward/reverse balance adjustment.

Table 7. Scaloped Potato Product Temperature Data in °F for 70/30 Forward/Reversing Fan Cycle at 864 rpm, Oven Temperature at 395° F (~ 202° C), Humidity 40% and Residence Time of 36 minutes.

9 cycles of 240 seconds each (168 seconds forward / 72 seconds reverse)

Sample	Product Temperature by Lane (1 = outside lane, 4 = inside lane)				Lane 1 – 4 Δ Temp.	Total Range	Coefficient of Variation (%)
	1	2	3	4			
A	174.9	161.9	169.6	164.6	10.3	13.0	7.7
B	173.6	172.5	170.5	169.9	3.7	3.7	2.2
C	173.0	159.9	169.0	163.4	9.6	13.1	7.9
Average	173.8	164.8	169.7	166.0	7.9	9.1	5.4

Table 8. Scaloped Potato Product Temperature Data in °F for 70/30 Forward/Reversing Fan Cycle at 778 rpm, Oven Temperature at 395° F (~ 202° C), Humidity 40% and Residence Time of 37 minutes.

9 cycles of 247 seconds each (173 seconds forward / 74 seconds reverse)

Sample	Product Temperature by Lane (1 = outside lane, 4 = inside lane)				Lane 1 – 4 Δ Temp.	Total Range	Coefficient of Variation (%)
	1	2	3	4			
A	175.7	162.6	176.1	176.1	-0.4	13.5	7.8
B	169.9	153.1	164.3	159.8	10.1	16.8	10.4
Average	172.8	157.9	170.2	168.0	4.9	15.0	8.9

Tables 9 and 10 present the results of changing the forward/reverse balance to about 70:30. Given the same residence time, temperature variability increased as the amount of forward rotation slightly increased to 72% from 70% of the total cycle. In these tests, the color had improved between the inside and outside (about a 3-4 closer to a 4), middle two lanes were 3, but the outside lane was clearly hotter. Testing was concluded here.

Table 9. Scaloped Potato Product Temperature Data in °F for 70/30 Forward/Reversing Fan Cycle at 864 rpm, Oven Temperature at 390° F (~ 199° C), Humidity 40% and Residence Time of 37 minutes.

9 cycles of 247 seconds each (173 seconds forward / 74 seconds reverse)

Sample	Product Temperature by Lane (1 = outside lane, 4 = inside lane)				Lane 1 – 4 Δ Temp.	Total Range	Coefficient of Variation (%)
	1	2	3	4			
A	177.5	165.8	169.9	164.5	13.0	13.0	7.7
B	172.4	166.7	169.9	168.3	4.1	5.7	3.4
C	167.3	160.5	165.0	162.0	5.3	6.8	4.2
D	180.0	167.3	163.7	169.3	10.7	16.3	9.6
Average	174.3	165.1	167.1	166.0	8.3	9.2	5.5

Table 10. Scalloped Potato Product Temperature Data in °F for 72/28 Forward/Reversing Fan Cycle at 864 rpm, Oven Temperature at 390° F (~ 199° C), Humidity 40% and Residence Time of 37 minutes.

9 cycles of 247 seconds each (178 seconds forward / 69 seconds reverse)

Sample	Product Temperature by Lane (1 = outside, 4 = inside lane)				Lane 1 – 4 Δ Temp.	Total Range	Coefficient of Variation (%)
	1	2	3	4			
A	184.5	170.4	175.8	171.4	13.1	14.1	8.0
B	182.4	166.3	171.7	169.7	12.7	16.1	9.3
Average	183.5	168.4	173.8	170.6	12.9	15.1	8.7

A person of ordinary skill in the art would understand that the addition of ducting or shielding in the spiral oven could allow balanced or more balanced forward-reverse cycles to be run yet still achieve substantially the same or similar result as the unbalanced forward-reverse cycles tested here.

Additional System Changes

The operating program for the UNITHERM™ spiral oven retrofitted with the forward/reversing fan was modified to accommodate the reversing fan option. The modified algorithm allowed a user to select a desired residence time and a forward/reverse fan direction balance based on percentage. The algorithm then automatically determined a cycle time and forward/reverse intervals to ensure that for a given residence time, all product experienced the same quantity of forward and reverse airflow throughout its cook process. The determined cycle time is the anticipated minimum time for one direction of rotation to be considered effective.

Additionally, it was found that during the change of direction of the fan blade, temperatures could fluctuate until the airflow re-stabilized. A moving average temperature display was integrated so that a temperature more representative of an oven cycle temperature was displayed. Lastly, a breaking resistor was determined to be a permanent addition to the reversing fan implementation because reducing the time taken to reverse rotation proved beneficial by greatly reducing dead time.

While preferred embodiments of a spiral oven cooking system equipped with a forward/reversing fan and a method for its use have been described in detail, changes can be made in the details of its construction and use without departing from the scope of its claims.

WHAT IS CLAIMED IS:

1. A method of heating a food product being conveyed on a cook belt in a spiral oven, the method comprising the steps of:

producing a first airflow in a first rotational direction flowing between an
upper and lower portion of a cooking chamber of a spiral oven; and

producing a second airflow in a second rotational direction flowing
between the upper and lower portion of the cooking chamber;

the second rotational direction being inverted relative to that of the first rotational
direction.

2. A method according to claim 1 further comprising the first and second airflow occurring during a total timed cycle "T"; the total timed cycle T being equal to an amount of time "T1" in which the first airflow occurs and an amount of time "T2" in which the second airflow occurs.

3. A method according to claim 2 further comprising the total timed cycle T starting with the second airflow.

4. A method according to claim 2 further comprising the amount of time T1 and T2 being unequal amounts of time.

5. A method according to claim 2 further comprising the amount of time T1 being greater than 50% of the total timed cycle T.

6. A method according to claim 5 further comprising the amount of time T1 being in a range of about 60% to 90% of the total timed cycle T.

7. A method according to claim 1 further comprising a horizontal airflow across the cook belt resulting from the first airflow being predominantly at a top and bottom portion of the spiral oven and a horizontal airflow across the cook belt resulting from the second airflow being predominantly in a middle portion of the spiral oven.

8. A method according to claim 1, an average range in final temperature measured across the cook belt of the spiral oven being no greater than about 10% of the total average product temperature.
- 5 9. A method according to claim 1 further comprising the first and second airflows being produced by a forward/reversing fan.
- 10 10. A method according to claim 9 further comprising the step of preventing the forward/reversing fan from running at its maximum speed when operating in the reverse direction.
11. A method according to claim 9 further comprising the step of running the forward/reversing fan at a same rpm regardless of a direction of rotation of the forward/reversing fan.
- 15 12. A method according to claim 9 further comprising the step of using a braking resistor to changeover a direction of rotation of the forward/reversing fan to an opposite direction of rotation.
- 20 13. A method of heating a food product being conveyed on a cook belt in a spiral oven, the method comprising the steps of:
- uniformly loading onto the cook belt a row of product to be cooked in the spiral oven; and
- exposing the row of product as it travels through the spiral oven to a first airflow and a second airflow, the second airflow being an inverted airflow relative to the first airflow;
- 25
- controlling the exposure of the row of product to the first and second airflows by using at least one of an amount of time the row of product is exposed to the first airflow and to the second airflow, ducting of at least one of the first and second airflows, and
- 30
- shielding of at least one of the first and second airflows.

14. A method according to claim 13 further comprising the first airflow and the second airflow each occurring a predetermined number of times during a total residence time of the row of product in the spiral oven.
- 5 15. A method according to claim 13 further comprising the step of controlling a speed of a fan producing at least one of the first and second airflows.
- 10 16. An improved spiral oven having a least one fan located in an upper portion of the spiral oven and means for distributing air produced by the at least one fan within a cooking chamber of the spiral oven, the improvement comprising the at least one fan being a forward/reversing fan and alternating between a first direction of rotation and a second direction of rotation during a timed cycle "T".
- 15 17. A spiral oven according to claim 16 further comprising a braking resistor in communication with a motor of the forward/reversing fan.
- 20 18. An improved spiral oven according to claim 16, the first direction of rotation representing a different proportion of the timed cycle T than the second direction of rotation.

Fig. 1
(PRIOR ART)





Fig. 2
(PRIOR ART)



2/8




Fig. 3
(PRIOR ART)





Fig. 4
(PRIOR ART)

*Fig. 5*




Fig. 6





Fig. 7






Fig. 8B




Fig. 9

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2012/028526

A. CLASSIFICATION OF SUBJECT MATTER
INV. A21B1/48
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 797 758 A2 (FMC TECHNOLOGIES [US] JOHN BEAN TECHNOLOGIES CORP [US]) 20 June 2007 (2007-06-20)	1-6,8, 13-15
Y	abstract; figure 1 paragraphs [0002], [0021] - [0023] -----	9-12, 16-18
X	WO 84/01266 A1 (PRO TECH AB [SE]) 12 April 1984 (1984-04-12) abstract; figures 1,2 page 1, lines 20-36 page 2, line 34 - page 3, line 15 page 7, lines 15-19 -----	1-3,7,13
Y	CH 548 161 A (SCHALK FRANZ) 30 April 1974 (1974-04-30) abstract; figure 1 column 3, lines 46-56 -----	9-12, 16-18
	-/-	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

9 August 2012

Date of mailing of the international search report

17/08/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Moreno Rey, Marcos

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2012/028526

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98/12926 A1 (KAAK JOHAN H B [NL]; PASCH LOTHAR [NL]) 2 April 1998 (1998-04-02) abstract page 3, line 31 - page 4, line 1 page 9, line 29 - page 10, line 12 -----	1-18
A	FR 2 390 102 A1 (DEBAG DEUTSCHE BACKOFENBAU [DE]) 8 December 1978 (1978-12-08) page 6, line 35 - page 7, line 6 -----	1-18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2012/028526

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 1797758	A2	20-06-2007	BR PI0605299 A 09-10-2007
		EP 1797758 A2	20-06-2007
		US 2007131215 A1	14-06-2007

WO 8401266	A1	12-04-1984	DK 261684 A 28-05-1984
		EP 0136286 A1	10-04-1985
		NO 842123 A	28-05-1984
		SE 8205564 A	30-03-1984
		WO 8401266 A1	12-04-1984

CH 548161	A	30-04-1974	AT 326063 B 25-11-1975
		CH 548161 A	30-04-1974

WO 9812926	A1	02-04-1998	AT 205051 T 15-09-2001
		AU 4402297 A	17-04-1998
		DE 69706548 D1	11-10-2001
		EP 0928137 A1	14-07-1999
		NL 1004136 C2	31-03-1998
		WO 9812926 A1	02-04-1998

FR 2390102	A1	08-12-1978	BE 866714 A1 01-09-1978
		DE 2720237 B1	02-02-1978
		FR 2390102 A1	08-12-1978
		IT 1107285 B	25-11-1985
		NL 7804864 A	07-11-1978
