



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
30.04.2008 Bulletin 2008/18

(51) Int Cl.:
B65B 19/28 (2006.01) B65B 61/26 (2006.01)

(21) Application number: **07119020.1**

(22) Date of filing: **22.10.2007**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR
Designated Extension States:
AL BA HR MK RS

(72) Inventors:
• **Bovina, Stefano**
40121 Bologna (IT)
• **Strazzari, Simone**
40057 Granarolo dell'Emilia (IT)
• **Minarelli, Alessandro**
40053 Bazzano (IT)

(30) Priority: **23.10.2006 IT BO20060726**

(71) Applicant: **G.D SOCIETÀ PER AZIONI**
40133 Bologna (IT)

(74) Representative: **Jorio, Paolo et al**
Studio Torta S.r.l.
Via Viotti, 9
10121 Torino (IT)

(54) **Packet printing unit**

(57) A printing unit (1) for packets (2), having: a printing conveyor (6) for feeding the packets (2) successively along a printing path (P), and having a number of pockets (12), each for housing a respective packet (2); an input station (7); an output station (8); and a printing station (16) located along the printing conveyor (6), between the input station (7) and the output station (8), and having a printing device (17) for printing a code on the outer sur-

face of each packet (2) on the printing conveyor (6); the printing conveyor (6) has a belt (9) looped about at least two end pulleys (10) and supporting a number of gripping members (13), each extending perpendicularly to the belt (9) and defining a wall of a respective pocket (12) which is narrowest along straight portions (T2, T4) of the printing path (P), and widest along curved portions (T1, T3, T5) of the printing path (P).




Fig.1

Description

[0001] The present invention relates to a packet printing unit.

[0002] The present invention may be used to advantage for printing progressive alphanumeric codes on the outer surface of packets of cigarettes, to which the following description refers purely by way of example.

[0003] On some packing lines for producing packets of cigarettes, each packet of cigarettes must be printed or marked with a progressive code by which to determine, for example, when and/or where the packet was produced.

[0004] Patent US6098533A1 describes a conveyor for stabilizing packets of cigarettes coming off a packing machine, and in which each packet is fed along a stabilizing path and through a printing station by two opposite, facing conveyor belts, which partly engage respective opposite minor lateral surfaces of the packet; and a laser printing unit is set up at the printing station to print a progressive code on a portion of one of the minor lateral surfaces of the packet left exposed by the respective conveyor belt.

[0005] The printing unit described in US6098533A1 is cheap and easy to produce and of good overall performance, but fails to ensure precise location of the actual printing on each packet, on account of the packets advancing side by side, with no mechanical stops by which to position the packets accurately.

[0006] Patent Application US2001032932A1 describes laser printing a progressive code on the outer surface of packets of cigarettes. The packets of cigarettes are advanced on a conveyor (preferably a vertical drying drum) having grippers which engage each packet, leaving a portion of the packet exposed, and on which a laser printer fitted to the conveyor prints the progressive code.

[0007] The printing unit described in Patent Application US2001032932A1 is complicated and expensive to produce, by featuring a rotary drum having a number of pockets performing various cam-controlled movements. Moreover, being extremely bulky and heavy, installing the printing unit along the output belt conveyor of a packing machine involves enormous mechanical complications. As a result, it can be integrated in a new packing machine at the design stage, but can only be installed on an existing packing machine at the expense of enormous mechanical complications.

[0008] It is an object of the present invention to provide a packet printing unit designed to eliminate the aforementioned drawbacks, and which at the same time is cheap and easy to produce.

[0009] According to the present invention, there is provided a packet printing unit as claimed in the accompanying Claims.

[0010] A non-limiting embodiment of the present invention will be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a schematic view in perspective, with parts removed for clarity, of a printing unit, for printing packets of cigarettes, in accordance with the present invention;

Figure 2 shows a plan view, with parts removed for clarity, of the Figure 1 printing unit for printing packets of cigarettes.

[0011] Number 1 in Figure 1 indicates as a whole a printing unit for printing a progressive code (normally an alphanumeric code and/or a bar code) on the outer surface of packets 2 of cigarettes.

[0012] Packets 2 of cigarettes are fed to printing unit 1 by an input belt conveyor 3, which receives a succession of packets 2 of cigarettes, arranged in a line, from a packing machine (not shown); and, from printing unit 1, the packets 2 of cigarettes are fed onto an output belt conveyor 4, which feeds a succession of packets 2 of cigarettes, arranged in a line, to a cellophaning machine (not shown).

[0013] Printing unit 1 comprises a frame 5 resting on the floor on feet and supporting a horizontal printing conveyor 6, which feeds packets 2 of cigarettes along a printing path P extending between an input station 7 at an output end of input conveyor 3, and an output station 8 at an input end of output conveyor 4.

[0014] Printing conveyor 6 comprises an endless belt 9 looped about two horizontal end pulleys 10a, 10b mounted to rotate about respective vertical central axes of rotation 11. Preferably, one end pulley 10 is powered to rotate continuously about its central axis of rotation 11, while the other end pulley 10 is idle. Path P therefore comprises a curved, arc-shaped initial portion T1 extending about end pulley 10a; a straight intermediate portion T2 extending between end pulley 10a and end pulley 10b; a curved, semicircular intermediate portion T3 extending about end pulley 10b; a straight intermediate portion T4 extending between end pulley 10b and end pulley 10a; and a curved, arc-shaped end portion T5 extending about end pulley 10b.

[0015] A number of pockets 12 are defined along belt 9, each for housing a respective packet 2 of cigarettes. More specifically, each pocket 12 receives a respective packet 2 of cigarettes from input conveyor 3 at input station 7, and releases respective packet 2 of cigarettes to output conveyor 4 at output station 8. Belt 9 supports a number of gripping members 13, each of which extends perpendicularly to belt 9 and defines a wall of a respective pocket 12. In other words, each pocket 12 is defined and bounded by two successive, side by side gripping members 13.

[0016] For obvious geometric reasons, each two successive, side by side gripping members 13 are parallel to each other along straight portions T2 and T4 of printing path P, and are inclined with respect to each other (i.e. converge towards the central axis of rotation 11 of corresponding end pulley 10) along curved portions T1, T3 and T5 of printing path P, so that each pocket 12 is nar-

rowest along straight portions T2 and T4 of printing path P, and widest along curved portions T1, T3 and T5 of printing path P.

[0017] In a preferred embodiment, printing conveyor 6 comprises a supporting member 14 located beneath printing conveyor 6 and having a horizontal top wall 15, on which packets 2 of cigarettes, pushed along by pockets 12 of printing conveyor 6, slide.

[0018] Printing unit 1 also comprises a printing station 16 located along printing conveyor 6, between input station 7 and output station 8, and in particular along straight intermediate portion T2 of printing path P between end pulley 10a and end pulley 10b. Printing station 16 comprises a printing device 17 for printing a code on the outer surface of each packet 2 of cigarettes advanced by printing conveyor 6, and which may, for example, be defined by a laser printing device.

[0019] Printing unit 1 also comprises a control station 18 located along straight portion T2 of printing path P, downstream from printing station 16, and which comprises an optical control device 19 for checking the code printed on each packet 2 of cigarettes. Control device 19 is connected to a central control unit 20, which receives the signals acquired by control device 19, and determines whether or not the code printed on each packet 2 of cigarettes is to specifications, i.e. whether the code printed on each packet 2 of cigarettes contains any flaws.

[0020] It is important to note that input station 7 and output station 8 are located at curved portions T1 and T5 of printing path P, along which pockets 12 of printing conveyor 6 are widest and so permit easy insertion or withdrawal of each packet 2 of cigarettes with respect to the corresponding pocket 12. In a preferred embodiment, input station 7 and output station 8 are both located about the same end pulley 10a. Output station 8 may obviously be located about end pulley 10b, in which case, printing path P would be shorter. Printing station 16 and control station 18, on the other hand, are located along straight intermediate portion T2 of printing path P, along which pockets 12 of printing conveyor 6 are narrowest and so retain packets 2 of cigarettes in precise predetermined positions.

[0021] Finally, printing unit 1 comprises a pick-off station 21 located along straight intermediate portion T4 of printing path P, downstream from control station 18, and which comprises a pick-off device 22 operated by central control unit 20 to remove packets 2 of cigarettes from pockets 12 of printing conveyor 6.

[0022] During normal operation of printing unit 1, central control unit 20 activates pick-off device 22 to remove any packets 2 of cigarettes with flawed printed codes from pockets 12 of printing conveyor 6. When requested by the operator, central control unit 20 may also activate pick-off device 22 to remove sample packets 2 of cigarettes from pockets 12 of printing conveyor 6. In other words, by means of a control device (keyboard or similar), central control unit 20 may be requested by the operator to remove sample packets 2 of cigarettes, for random

checking, from printing conveyor 6.

[0023] Pick-off device 22 comprises a curved profile 23 located along straight intermediate portion T4 of printing path P, and over which belt 9 of printing conveyor 6 runs to locally curve belt 9 inwards and locally widen pockets 12; and a push member 24 (normally pneumatic or mechanical) located at an intermediate portion of curved profile 23 and activated by central control unit 20 to push a packet 2 of cigarettes out of respective pocket 12 and onto a pick-off path 25 terminating in a bin 26, which may be divided into different compartments for sample and flawed packets 2 of cigarettes.

[0024] In a preferred embodiment, input conveyor 3 and output conveyor 4 extend perpendicularly to printing path P, and therefore to belt 9 of printing conveyor 6, to insert/remove packets 2 of cigarettes into/from pockets 12 quickly and easily.

[0025] In a different embodiment not shown, printing conveyor 6 comprises more than two (normally no more than three or four) end pulleys 10.

[0026] Printing unit 1 as described above has numerous advantages, by featuring no complex mechanical devices, such as cams or similar, and so being cheap and easy to produce. Pockets 12, in fact, are cyclically widened and narrowed simply by the movement of belt 9, with no other mechanical movements necessary.

[0027] Printing unit 1 as described above also ensures extremely precise location of the actual printing on each packet 2 of cigarettes, by virtue of packets 2 of cigarettes being fed through printing station 16 inside pockets 12 and therefore in a known, predetermined location in space.

[0028] Finally, being extremely compact and lightweight, printing unit 1 as described above may be installed easily along a packing machine output belt conveyor, and therefore connected to an existing packing machine at very low installation cost.

[0029] Given its numerous advantages, printing unit 1 as described above may also be used to advantage for printing codes or similar on packets 2 other than packets 2 of cigarettes, such as cartons of cigarettes, boxes, or food product packages.

Claims

1. A printing unit (1) for packets (2), comprising:

a printing conveyor (6) for feeding the packets (2) successively along a printing path (P), and comprising a number of pockets (12), each for housing a respective packet (2);
an input station (7) defining the start of the printing path (P), and where the packets (2) are fed into the pockets (12) on the printing conveyor (6);
an output station (8) defining the end of the printing path (P), and where the packets (2) are re-

moved from the pockets (12) on the printing conveyor (6); and
 a printing station (16) located along the printing conveyor (6), between the input station (7) and the output station (8), and comprising a printing device (17) for printing a code on the outer surface of each packet (2) on the printing conveyor (6);

the printing unit (1) being **characterized in that:**

the printing conveyor (6) comprises a belt (9) looped about at least two end pulleys (10) and supporting a number of gripping members (13), each extending perpendicularly to the belt (9) and defining a wall of a respective pocket (12) which is narrowest along straight portions (T2, T4) of the printing path (P), and widest along curved portions (T1, T3, T5) of the printing path (P); the input station (7) and output station (8) are located along respective curved portions (T1, T3, T5) of the printing path (P); and
 the printing station (16) is located along a first straight portion (T2) of the printing path (P).

2. A printing unit (1) as claimed in Claim 1, wherein the input station (7) and output station (8) are located about the same end pulley (10) and along respective curved portions (T1, T5) of the printing path (P).

3. A printing unit (1) as claimed in Claim 1 or 2, and comprising a control station (18) located along the first straight portion (T2) of the printing path (P), downstream from the printing station (16), and which comprises an optical control device (19) for checking the code printed on each packet (2).

4. A printing unit (1) as claimed in Claim 1, 2 or 3, and comprising a pick-off station (21) located along a second straight portion (T4) of the printing path (P), downstream from the control station (18), and which comprises an activatable pick-off device (22) for removing packets (2) from the pockets (12) on the printing conveyor (6).

5. A printing unit (1) as claimed in Claim 4, and comprising a central control unit (20) which activates the pick-off device (22) to remove sample packets (2) from the pockets (12) on the printing conveyor (6).

6. A printing unit (1) as claimed in Claim 4, and comprising:

a control station (18) located along the first straight portion (T2) of the printing path (P), downstream from the printing station (16), and

which comprises an optical control device (19) for checking the code printed on each packet (2); and

a central control unit (20) connected to the control device (19), and which activates the pick-off device (22) to remove packets (2) with flawed printed codes from the pockets (12) on the printing conveyor (6).

7. A printing unit (1) as claimed in Claim 4, 5 or 6, wherein the pick-off device (22) comprises a curved profile (23) located along the second straight portion (T4) of the printing path (P), and over which the belt (9) of the printing conveyor (6) runs to locally curve the belt (9) inwards and locally widen the pockets (12).


8. A printing unit (1) as claimed in Claim 7, wherein the pick-off device (22) comprises a push member (24) located at an intermediate portion of the curved profile (23) and activated to push a packet (2) out of the respective pocket (12), and feed the packet (2) onto a pick-off path (25).

9. A printing unit (1) as claimed in one of Claims 1 to 8, wherein the printing path (P) extends along a horizontal plane, and the printing conveyor (6) comprises a supporting member (14) located beneath the printing conveyor (6) and having a horizontal top wall (15) on which the packets (2), pushed along by the pockets (12) of the printing conveyor (6), slide.

10. A printing unit (1) as claimed in one of Claims 1 to 9, wherein the packets (2) are fed to the pockets (12) of the printing conveyor (6) at the input station (7) by an input conveyor (3) extending perpendicularly to the printing path (P).

11. A printing unit (1) as claimed in one of Claims 1 to 10, wherein the packets (2) are removed from the pockets (12) of the printing conveyor (6) at the output station (8) by an output conveyor (4) extending perpendicularly to the printing path (P).

Fig.1






Fig. 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 07 11 9020

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A,D	US 2001/032932 A1 (FOCKE HEINZ [DE] ET AL) 25 October 2001 (2001-10-25) * abstract * * figure 5 * * column 2, paragraph 28 - column 3, paragraph 33 *	1-11	INV. B65B19/28 B65B61/26
A,D	US 6 098 533 A (POLLONI ROBERTO [IT] ET AL) 8 August 2000 (2000-08-08) * abstract * * figure 1 *	1-11	
A	US 6 158 193 A (FOCKE HEINZ [DE] ET AL) 12 December 2000 (2000-12-12) * abstract * * figures 1,5 *	1-11	
			TECHNICAL FIELDS SEARCHED (IPC)
			B65B
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 30 January 2008	Examiner Damiani, Alberto
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 07 11 9020

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-01-2008

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 2001032932	A1	25-10-2001	BR	0100231 A		28-08-2001
			CN	1319538 A		31-10-2001
			DE	10004022 A1		02-08-2001
			EP	1122171 A1		08-08-2001
			JP	2001233310 A		28-08-2001

US 6098533	A	08-08-2000	DE	19924449 A1		16-12-1999
			GB	2337974 A		08-12-1999
			IT	B0980350 A1		03-12-1999

US 6158193	A	12-12-2000	BR	9900825 A		14-12-1999
			CN	1234359 A		10-11-1999
			DE	59912692 D1		01-12-2005
			EP	0941775 A2		15-09-1999
			JP	11292033 A		26-10-1999

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 6098533 A1 [0004] [0005]
- US 2001032932 A1 [0006] [0007]