

**(57) Abstract:** An apparatus for in-field configuration of a seismic device such as a seismic sensor may include a memory module having data for configuring the seismic device, a location sensor determining a location parameter for the seismic sensor, an alignment member aligning the location sensor with the seismic sensor, and a communication device transmitting the determined location parameter to a selected external device. It is emphasized that this abstract is provided to comply with the rules requiring an abstract which will allow a searcher or other reader to quickly ascertain the subject matter of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. 37 CFR 1.72(b).

**TITLE:                    CONFIGURATION TOOL AND METHODS FOR  
                             SEISMIC DATA ACQUISITION**

**BACKGROUND OF THE DISCLOSURE**

**[001]** Oil companies conduct seismic surveying to lower risk and to reduce costs of locating and developing new oil and gas reserves. Seismic surveying is, therefore, an up-front cost with intangible return value. Consequently, minimizing the cost of seismic surveying and obtaining quality results in minimum time are important aspects of the seismic surveying process.

**[002]** Seismic surveys are conducted by deploying a large array of seismic sensors over a terrain of interest. These arrays may cover over 50 square miles and may include 2000 to 5000 seismic sensors. An energy source such as buried dynamite may be discharged within the array to impart a shockwave into the earth. The resulting shock wave is an acoustic wave that propagates through the subsurface structures of the earth. A portion of the wave is reflected after encountering underground discontinuities, such as oil and gas reservoirs. These reflections are then sensed at the surface by the sensor array and recorded as seismic data. Such sensing and recording are referred to herein as seismic data acquisition. This seismic data is then processed to generate a three dimensional map, or seismic image, of the

subsurface structures. The map may be used to make decisions about drilling locations, reservoir size and pay zone depth.

**[003]** Seismic data acquisition systems may include a relatively large number of seismic data acquisition units. These seismic data acquisition units may need to be configured in a particular manner in order to properly acquire seismic data. The present disclosure addresses the need for in-field configuration of seismic data acquisition units.

## SUMMARY OF THE DISCLOSURE

**[004]** In aspects, the present disclosure provides an apparatus for configuring a seismic device positioned in a geographical area of interest. In one embodiment, the apparatus includes data associated with the seismic device, a memory module configured to store the data, a processor configured to retrieve the data from the memory module, and a communication device operatively coupled to the processor. The communication device may be configured to transmit the retrieved data to the seismic device. In embodiments, the data may include: a configuration file, an acquisition parameter, and / or an operational parameter. In embodiments, the data may include processor-executable instructions. In one aspect, the seismic device may be a sensor station, and the communication device may be configured to transmit the retrieved data to the sensor station. In aspects, the apparatus may include at least one location sensor that determines at least one location parameter for the seismic device. Exemplary location parameters include, but are not limited to: an x-coordinate, a y-coordinate, elevation, z-coordinate, inclination, tilt and / or azimuth. The processor may communicate with the at least one location sensor to received the measured location parameter(s). In arrangements, the at least one location sensor may be: an orientation sensor; a compass, or a GPS device. In embodiments, the apparatus may include an alignment member receiving the at least one location sensor. The alignment member may be configured to align the at least one location sensor with the seismic device. In embodiments, the apparatus may include a hand-held device configured to receive the memory module and / or the processor. The communication device may use: a wireless transmission media and / or one or more wires.

**[005]** In aspects, the present disclosure provides a method for configuring a seismic device in the field. One exemplary method includes positioning the

seismic device in a geographical area of interest; and configuring the seismic device using data associated with the seismic device. The data for configuring the seismic device may include: a configuration file, an acquisition parameter, and / or an operational parameter. In embodiments, the data may include processor executable instructions. In aspects, the seismic device may be a sensor station.

**[006]** The method may also include determining at least one location parameter for the seismic device; and transmitting the determined at least one location parameter to the seismic device. The at least one location sensor may be: an orientation sensor, a compass, or a GPS device. The method may include aligning the at least one location sensor with the seismic device. In embodiments, the method may further include transporting a processor to the geographical area of interest. The processor may be programmed to configure the seismic device while being positioned proximate to the seismic device. In embodiments, the method may also include transporting a memory module to the geographical area of interest, the memory module including the data associated with the seismic device. The method may further include using: a wireless media and / or one or more wires to transmit data.

**[007]** In aspects, the present disclosure provides methods and devices that provide accurate measurements of a specified orientation, position or coordinate for seismic devices such as sensor units. In one aspect, the present disclosure provides orientation measurement systems and devices for determining one or more parameters of interest associated with a seismic sensor. These parameters may include location parameters such as latitude, longitude, azimuth, inclination / tilt and elevation. In one embodiment, an configuration tool performing such a function includes a location sensor that measures one or more location parameters for the seismic sensor and an alignment member that aligns the location sensor with the seismic sensor. Exemplary location sensors include compasses and GPS devices. The

location parameter measurements made by the location sensor are transmitted via a communication device to a selected external device. The external device may be a processor positioned in a hand-held device received by the alignment member. In such an arrangement, the processor can include a communication device that transmits location parameters to a sensor station associated with the seismic sensor. In other arrangements, the location sensor can communicate directly with the sensor station associated with the seismic sensor.

**[008]** In embodiments, the configuration tool can be formed as a generally tubular member that has a pod removably connected at one end. The pod may be formed to receive the location sensor and other associated devices such as a power source and data transmission device. The pod when not attached from the tubular member can be worn by a user, and / or mounted on a vehicle or any other suitable structure. The communication devices can use either a wireless transmission media or data conductors such as metal wires or optical fibers.

**[009]** It should be understood that examples of the more important features of the disclosure have been summarized rather broadly in order that detailed description thereof that follows may be better understood, and in order that the contributions to the art may be appreciated. There are, of course, additional features of the disclosure that will be described hereinafter and will form the subject of the claims appended hereto.

## BRIEF DESCRIPTION OF THE DRAWINGS

**[0010]** The novel features of this disclosure, as well as the disclosure itself, will be best understood from the attached drawings, taken along with the following description, in which similar reference characters refer to similar parts, and in which:

**FIG. 1** schematically illustrates a cable seismic data acquisition system;

**FIG. 2** schematically illustrates a wireless seismic data acquisition system;

**FIG. 3A** shows a schematic representation of the system of **FIG. 2** in more detail;

**FIG. 3B** shows one embodiment of a wireless station unit having an integrated seismic sensor;

**FIG. 3C** illustrates a multi-component sensor for use in one embodiment of the present disclosure;

**FIG. 4** is a schematic representation of a wireless station unit incorporating circuitry to interface with an analog output sensor unit; and

**FIG. 5** illustrates one embodiment of a configuration tool made in accordance with the present disclosure.

## DETAILED DESCRIPTION OF THE DISCLOSURE

**[0011]** In aspects, the present disclosure relates to devices and methods for determining location parameters for seismic devices used during seismic data acquisition and / or configuring seismic devices in the field. The present disclosure is susceptible to embodiments of different forms. There are shown in the drawings, and herein will be described in detail, specific embodiments of the present disclosure with the understanding that the present disclosure is to be considered an exemplification of the principles of the disclosure, and is not intended to limit the disclosure to that illustrated and described herein.

**[0012]** **FIG. 1** depicts a typical cable-based seismic data acquisition system **100**. The typical system **100** includes an array (string) of spaced-apart seismic sensor units **102**. Each string of sensors is typically coupled via cabling to a data acquisition device (field box) **103**, and several data acquisition devices and associated string of sensors are coupled via cabling **110** to form a line **108**, which is then coupled via cabling **110** to a line tap or (crossline unit) **104**. Several crossline units and associated lines are usually coupled together and then to a central controller **106** housing a main recorder (not shown). One sensor unit **102** that is in use today is a velocity geophone used to measure acoustic wave velocity traveling in the earth. Other sensor units **102** that may be used are acceleration sensors (accelerometers) for measuring acceleration associated with the acoustic wave. In embodiments, each sensor unit may comprise a single sensor element or more than one sensor element for multi-component seismic sensor units.

**[0013]** The sensors **102** are usually spaced at least on the order of tens of meters, e.g., 13.8 - 220.0 feet. Each of the crossline units **104** may perform some signal processing and then store the processed signals as seismic information for later retrieval. The crossline units **104** are each coupled, either in parallel or in series with one of the units **104a** serving as an interface with between the central controller **106** and all crossline units **104**.



[0014] Referring to **FIG. 2** there is schematically shown a wireless seismic data acquisition system. The system **200** includes a central controller **202** in direct communication with each of a number of wireless sensor stations **208** forming an array (spread) **210** for seismic data acquisition. Each sensor station **208** may include one or more sensors **212** for sensing seismic energy. Direct communication as used herein refers to individualized data flow as depicted in **FIG. 2** by dashed arrows. The data flow may be bi-directional to allow one or more of: transmitting command and control instructions from the central controller **202** to each wireless sensor station **208**; exchanging quality control data between the central controller **202** and each wireless sensor station **208**; and transmitting status signals, operating conditions and/or selected pre-processed seismic information from each wireless sensor station **208** to the central controller **202**. The communication may be in the form of radio signals transmitted and received at the central controller **202** via a suitable antenna **204**. The term “seismic devices” includes any device that is used in a seismic spread, including, but not limited to, sensors, sensor stations, receivers, transmitters, power supplies, control units, etc. As used herein the term “wireless” or “cableless” is intended to describe an arrangement wherein communication or data transfer between a sensor station **208** and a central controller **202** does not utilize wire conductors. There can be, of course, cables and wires that connects the sensor station **208** and local components such as the sensing devices or external batteries. Thus, in general, a wireless or cableless seismic device is one that does not utilize wires or cables to communicate with a central control unit. In one embodiment, each sensor station **208** has a single sensor and a cable connected between one station and one sensor.

[0015] The controller **202**, the central station computer (CSC) **490** and a central server **492** exert control over the constituent components of the system **200** and direct both human and machine activity during the operation of the system **200**. The server **492** can be programmed to manage data and activities over the span of the seismic campaign, which can include daily

shooting sequences, updating the shots acquired, tracking shooting assets, storing seismic data, pre-processing seismic data and broadcasting corrections. Of course, a single controller can be programmed to handle most if not all of the above described functions. For example, the CSC **490** can be positioned in or integral with the controller **202**. Moreover, in some applications it may be advantageous to position the controller **202** and CSC **490** in the field, albeit in different locations, and the server **492** at a remote location.

**[0016]** **Figure 3A** is a schematic representation of the system **200** in more detail. The central controller **202** includes a computer **300** having a processor **302** and a memory **303**. An operator can interface with the system **200** using a keyboard **306** and mouse or other input **308** and an output device such as a monitor **310**. Communication between remotely-located system components in the spread **210** and the central controller **202** is accomplished using a central transmitter-receiver (transceiver) unit **312** disposed in the central controller **202** along with an antenna **314**.

**[0017]** The central controller **202** communicates with each wireless sensor station **208**. Each wireless sensor station **208** shown includes a wireless station unit **316**, an antenna **318** compatible with the antenna **314** used with the central controller **202**, and a sensor unit **320** responsive to acoustic energy traveling in the earth co-located with a corresponding wireless sensor station. Co-located, as used herein, means disposed at a common location with one component being within a few feet of the other. Therefore, each sensor unit **320** can be coupled to a corresponding wireless station unit by a relatively short cable **322**, e.g., about one meter in length, or coupled by integrating a sensor unit **320** with the wireless station unit **316** in a common housing **324** as shown in **Figure 3B**. In certain situations, the expected in-field service time may exceed the power capacity of internal battery sources (e.g., battery **422** of **Figure 4**). In certain embodiments, an external battery **323** can be connected to the sensor station **208** via a suitable cable **325**.

The external battery **323** increases the amount of power available to the sensor station **208** and thereby increases the in-field service life of the sensor station **208**.

**[0018]** One sensor for use in a sensor unit **320** may be a multi-component sensor **326** as shown in **Figure 3C**. The multi-component sensor shown includes a three-component accelerometer sensor incorporating micro electro-mechanical systems (MEMS) technology and application-specific integrated circuits (ASIC) as found in the Vectorseis sensor module available from ION Geophysical Corporation, Houston, Texas. The present disclosure, however, does not exclude the option of using velocity sensors such as a conventional geophone or using a pressure sensor such as a conventional hydrophone. Any sensor unit capable of sensing seismic energy will provide one or more advantages of the present disclosure. Furthermore, the present disclosure is useful using a single sensor unit **320** as shown, or the sensor unit **320** might include multiple sensors connected in a string.

**[0019]** **Figure 4** is a schematic representation of a wireless station unit **400** according to the present disclosure that operates as a data recorder incorporating circuitry to interface with an analog output sensor unit (not shown). The wireless station unit **400** is an acquisition device that includes a sensor interface **402** to receive an output signal from the sensor unit. The sensor interface **402** shown includes a protection circuit, switch network, a preamplifier, a test oscillator, and ADC and digital filtering circuits to pre-process the received signal. The sensor interface **402** is controlled in part by a field programmable gate array (FPGA) and/or an ASIC controller circuit **404**. An on-board local processor **406** processes the signal to create storable information indicative of the seismic energy sensed at the sensor unit. The processor **406** may also include software, algorithms, and instructions for performing any required task. Moreover, the processor **406** may be configured to utilize configuration data files or other uploadable files that instruct the processor **406** to operate in a specified manner; e.g., during

data acquisition. Such configuration data files will be discussed in greater detail below. The information can be in digital form for storage in a storage device **408**, also referred to herein as a memory unit. The memory unit can be removable as shown at **408** and/or dedicated **408a** with a coupling **410** for providing access to the stored information and/or for transferring the stored information to an external storage unit **411**. The coupling **410** may be a cable coupling as shown or the coupling might be an inductive coupling or an optical coupling. Such couplings are known in the art and thus are not described in detail. The memory **408**, **408a** can be a nonvolatile memory of sufficient capacity for storing information for later transfer or transmission. The memory might be in the form of a memory card, removable miniature hard disk drive, an Electrically-Erasable Programmable Read Only Memory (EEPROM) or the like.

**[0020]** Interface with the central controller **202** is accomplished with a communication device such as an on-board transmitter-receiver circuit **412**, and an antenna **414** selected for the desired transmitting/receiving frequency to provide direct communication with the remotely-located central controller **202**. The transmitter/receiver circuit **412** shown is a direct conversion receiver/synthesizer/transmitter circuit and can alternatively be implemented as software-defined radio transceiver. Alternatively, the transmitter/receiver circuit **412** might be any suitable circuit providing transceiver functions such as a transceiver utilizing superheterodyne technology, for example. Location parameters (e.g., latitude, longitude, azimuth, inclination, azimuth, etc.) associated with a particular wireless sensor station help to correlate data acquired during a survey. These parameters are determined prior to a survey using a selected sensor location and nominal sensor orientation and the parameters can be adjusted according to the present disclosure. The location parameters are stored in a memory **303**, **408** either in the central controller or in the station unit **400**. In one embodiment, the wireless sensor station includes a global positioning system (GPS) receiver **434** and associated antenna **436**. The GPS receiver in this embodiment is shown

coupled to the processor **406** and to a clock circuit **338** to provide location parameters such as position and location data for correlating seismic information and for synchronizing data acquisition.

**[0021]** Local power is provided by a power supply circuit **420** that includes an on-board rechargeable battery **422**. The battery **422** might be of any suitable chemistry and might be nickel-metal hydride (NMH), a lithium-ion or lithium-polymer rechargeable battery of adequate size for the particular application. The battery provides an output to a power supply **424** to condition and regulate power to downstream circuits and the power supply output is coupled to a power control circuit **426** for distributing power to various local components. The power circuit **420** further includes a charging device **428** and charger interface **430** for coupling the charging device **428** to an external power source **431**. A charge indicator **432** provides an indication of amount of charge and/or charging time remaining for the power circuit **420**. Such indicators are somewhat common and further description is not necessary here.

**[0022]** As described above, the external equipment interacts with the sensor station **208** to, in part, retrieve data from the memory module **408** and to charge the rechargeable batteries **323**, **422**. In one embodiment, a single cable **400** includes a data conductor that transmits data between the external equipment and the memory module **408** and other components of the sensor station **208** and a power conductor that transfers electrical power from an external source to the power circuit **420**. The cable **440**, which can be formed of metal wire or optical fibers, provides a consolidated connection device for operatively connecting the sensor station **208** to one or more external devices. The sensor station **208** can also include one or more external batteries.

**[0023]** Another optional feature is a wake up circuit **444** that allows the wireless station unit to control power consumption from the battery

throughout different operating modes. The wake up circuit **444** can be triggered by a number of specified sources; such as the radio receiver **412**, the clock **438**, a motion sensor or environmental condition sensor (not shown). Still another optional feature is a wireless station unit **400** that includes a motion sensor **440** to detect unwanted movement of the station unit or to detect around the station unit, in which a proximity sensor might be used. Such unwanted movement might be caused by wildlife interfering with the unit, soil movement or the like.

**[0024]** Location parameters, which include latitude, longitude, azimuth, inclination, elevation, heading (*e.g.*, relative to north), tilt relative to gravity, etc., associated with a particular sensor unit **320** help to correlate data acquired during a survey. These parameters may be determined prior to a survey and are stored in a memory **303**, **408** in the central controller and / or in the station unit **400**. The sensor units **320** can be affected by their orientation in all three dimensions. Thus, if a measured orientation of a given sensor unit **320** is inaccurate or has been omitted, then the accuracy of the recorded data can be compromised. As will be described in greater detail below, embodiments of the present disclosure provide an efficient method of determining and recording location parameters such as orientation data for sensor units **320**.

**[0025]** Referring now to **Fig. 5**, an configuration tool **500** can be used to configure the sensor station **208**, the sensors **102** (**Fig. 1**), the field boxes **103** (**Fig. 1**), or any other seismic device. This configuration may include transmitting one or more location parameters to the sensor station **208**. The location parameters include, but are not limited to, heading, x and y coordinates, inclination / tilt and azimuth and elevation. This configuration may also include transmitting one or more processor executable instructions that may be used by the sensor station **208** to control one or more functions of the sensor station **208**.

**[0026]** In one embodiment, the configuration tool **500** for configuring seismic devices includes an orientation sensor **502** and an alignment member **504**. The orientation sensor **502** measures one or both of heading and tilt angle of a sensor unit **320** that has been placed into the ground. Exemplary orientation sensors include digital compasses, devices that can provide a measurement relative to a selected reference such as magnetic north, accelerometers, magnetometers, etc. Digital compasses are used in certain embodiment because such devices can provide accuracy to within 2.5 degrees. The alignment member **504** in one non-limiting embodiment is a tubular member that engages the sensor unit **320** with an end cap **506**. The end cap **506** is formed such that the sensor unit **320** slides into the end cap **506** only when a preset angular alignment exists between the end cap **506** and the sensor unit **320**. For example, in embodiments where a cable **508** extends out of the sensor unit **320**, the end cap **506** can have a slot **510** formed to receive a fitting **512** associated with the cable **508**. When the fitting **512** slides into the slot **510**, the sensor unit **320** and the alignment member **504** are aligned in the desired manner. In other arrangements, the alignment member **504** and the sensor unit **320** can utilize pins, grooves, and other known mechanisms for causing a desired alignment there between.

**[0027]** In other embodiments, the alignment member **504** can be configured to actively determine the angular offset of the sensor unit **320** relative to a preset reference point. That is, instead of manipulating the alignment member **504** and / or the sensor unit **320** until a desired physical relative orientation exists, the alignment member **504** can include one or more sensors (not shown) that determine the angular orientation of the sensor unit **320**. The determined angular orientation is then correlated with a heading reading for the orientation sensor **502**.

**[0028]** It will be appreciated that the physical mating of the orientation sensor **502** with the sensor unit **320** increases the accuracy of the measured location parameters pertaining to the sensor unit **320** in at least two ways.

First, because the configuration tool **500** is positioned directly over the sensor unit **320**, longitude and latitude measurements are assured of being as representative as possible of the true location of the sensor unit **320**. Additionally, because of physical connection between the configuration tool **500** and the sensor unit **320**, human error that could arise in measuring a heading of the sensor unit **320** using a hand-held device are also eliminated.

**[0029]** In embodiments, the configuration tool **500** can include a pod **520** that houses the orientation sensor **502**. The pod **520** can include associated support equipment such as a power supply **522** and a data transmission device **524**. The data transmission device **524** in one embodiment wirelessly transmits heading data from the orientation sensor **502** to a processing unit **530** and /or the station unit **316** associated with the sensor unit **320**. In other embodiments, the data transmission device **524** can use electrical and /or fiber optic conductors for data transmission.

**[0030]** The processing unit **530** is configured to store, transmit and receive data. In one configuration, the processing unit **530** can be portable digital assistant (PDA) which is a small hand-held device equipped with a microprocessor that is used for storing and organizing electronic data. In some arrangements, the processing unit can include a GPS device. In other arrangements, a GPS device can be a separate unit.

**[0031]** In embodiments, the pod **520** has a coupling end **526** that connects to an end of the alignment member **504** and a cradle portion **532** that supports the processing unit **530**. Advantageously, the coupling end **526** can be detached from the alignment member **504** and attached to a mounting element (not shown) on a vehicle or other mobile platform. Alternatively, the pod **520** when not connected to the alignment member **504** can be worn on the person. It will be appreciated that the pod **520** can operate as a self-contained navigation device that can be easily deployed by ground personnel



in the field. It should be appreciated that compasses and GPS devices are merely illustrative of the types of sensors that can be integrated into a pod **520** or supported by the pod **520**.

**[0032]** In an exemplary mode of deployment, each wireless sensor station **208** is transported to a predetermined spread location. This can be done utilizing a pod **520** having a GPS device and orientation sensor and that is detached from the alignment member **504**. It should be appreciated that the detached pod **520** having such instruments may provide the user with precise information as to position (e.g., x, y coordinates) and heading, which can allow the user to readily navigate over survey area. Upon arriving at the location, the location parameters (e.g., latitude, longitude, azimuth, inclination, elevation, etc.) associated with the particular sensor unit **320** are determined using the configuration tool **500**. For instance, once the sensor unit **320** has been planted in the ground, the alignment member **504** is fitted onto the sensor unit **320**. While in this position, the orientation device **502**, such as a digital compass, obtains an accurate azimuth reading and wireless transmits that information via a wireless data link **540** to the processing unit **530**. Alternatively or additionally, the information is transmitted to the station unit **316** via a suitable wireless data link **542**. The wireless data link **542** may use radio signals, BLUE TOOTH technology, infrared signals or any other suitable wireless communication methodology. Additionally, the GPS device determines coordinates, which is also recorded in the processing unit **530**. In arrangements where the location parameter data is transmitted to the processing unit **530**, the processing unit **530** can thereafter transmit that location parameter data to the station unit **316** via a suitable wireless data link **544**. The location parameter data may be stored in trace headers for each wireless station unit **316**. It should be appreciated that this automated nature of obtaining, recording and transferring location parameter data can provide more precise results when seismic data is processed.

**[0033]** As noted above, the configuration tool **500** may be used to perform

in-field configuration of the station unit **316**. In one embodiment, the configuration tool **500** may include a memory module (not shown) storing processor executable instructions that configures the station unit **316** to operate in a specified manner during the course of a given seismic data acquisition activity. For example, the configuration tool **500** may load the station unit **316** with processor executable instructions that enables the station unit **316** to acquire seismic data in accordance with a pre-determined seismic data acquisition plan (e.g., a shot plan). In one arrangement, the configuration tool **500** may load the station unit **316** with one or more configuration data files. During seismic data acquisition, one or more of these loaded configuration data files may be utilized by the station unit **316** to control the in-field behavior or operation of the station unit **316**. The operation or behavior may be related to functions that include, but are not limited to, the measuring of seismic energy, the writing of data indicative of the measured seismic energy to a data storage medium, the response of the station unit **316** to an event or condition that may impact a functional aspect of the station unit **316** (i.e., an “out-of-norm” condition or event), and the protocols or method the station unit **316** uses to communication with other external devices. In some embodiments, the configuration data files may include acquisition parameters such as sample rates, record lengths, filter configurations, etc. The configuration data files may also include operational parameters such as alarm set points for low battery power, maximum operating temperature, maximum noise, etc. Thus, a station unit **316** may be configured to report one or more of these conditions such as low battery levels, excessive noise, once a preset threshold value for such a condition has been reached. Other operational parameters may include available communication frequencies that may be in a “look-up” table. The station unit **316** may reference the “look-up” table to select the most suitable frequency for signal transmission. Still another operational parameter may include a “shot template” that enables the station unit **316** to determine whether or not to change operating states to prepare for a given shot. For example, the

“shot template” may be a mathematical expression or geometric shape that may be referenced by the station unit **316** to determine whether to record seismic data from a source that is to be activated. In some embodiments, the CSC **490** (**Fig. 2**) may transmit a signal that instructs the sensor stations **208** to select one configuration data file from a plurality of different configuration data files. Thus, the sensor stations **208** may be effectively reconfigured as desired while in the field.

**[0034]** It should be understood that the **Fig. 5** embodiment is merely illustrative. For example, in certain embodiments, an inductive coupling or mating electrical or fiber optic contacts can be used to transmit or exchange data between the various sensors and processing units. Additionally, in certain other embodiments, a compass and a GPS device can be integrated into a single device or integrated into a single processing unit. In still other embodiments, the processing unit is not physically mated with the orientation device. For example, as described in co-pending application U.S. Serial No. 11/760,078, navigation devices can be used to provide a “heads-up” navigation to the user. Such devices can be worn in an ear piece or eye wear. In such embodiments, the compass device can transmit data via wire or wireless to the “heads-up” navigation devices worn by the user.

**[0035]** In embodiments, the configuration tool **500** may include additional equipment of enhanced the ability of field personnel to navigate the terrain, maintain accurate logs of the equipment in the field, develop, and accurately position equipment. For example, the configuration tool **500** may include a device configured to read bar codes or an RFID reader that is configured to scan hardware and assign some property to it (*e.g.*, location, condition, associated hardware, etc.). Another device may be an imaging device such as a digital camera. For example, images of a deployed receiver, or other piece of equipment, may be used to develop a photographic log. Such a log may be useful for 4D applications to, for instance, replicate positions, as well as general quality control, *e.g.* a receiver may be planted in an undesirable

location. The configuration tool **500** may also be configured to receive data relating to property permitting. The permit process can often involve talking to land owners and marking out boundaries. This process could be administered by a permit agent and a database having permitting-related information. In embodiments, the configuration tool **500** may include instructions and databases used to evaluate field crew operational metrics (e.g., productivity metrics). For example, the configuration tool **500** may be configured to collect selected data that may be useful identifying the occurrence of operational delays and bottlenecks in daily crew workflows. Events and tasks that may be contributing to such difficulties may be may be logged and time-stamped for later evaluation.

**[0036]** The foregoing description is directed to particular embodiments of the present disclosure for the purpose of illustration and explanation. It will be apparent, however, to one skilled in the art that many modifications and changes to the embodiment set forth above are possible without departing from the scope of the disclosure. It is intended that the following claims be interpreted to embrace all such modifications and changes.

## THE CLAIMS

We Claim:

1. An apparatus for configuring a seismic device positioned in a geographical area of interest, comprising:
  - data associated with the seismic device;
  - a memory module configured to store the data;
  - a processor configured to retrieve the data from the memory module;and
  - a communication device operatively coupled to the processor, the communication device transmitting the retrieved data to the seismic device.
2. The apparatus of claim 1 wherein the data includes one of: (i) a configuration file, (ii) an acquisition parameter, (iii) an operational parameter.
3. The apparatus of claim 1 wherein the data includes processor-executable instructions.
4. The apparatus of claim 1 wherein the seismic device is a sensor station, and wherein the communication device is configured to transmit the retrieved data to the sensor station.
5. The apparatus of claim 1 further comprising at least one location sensor determining at least one location parameter for the seismic device, the processor being in communication with the at least one location sensor;
6. The apparatus of claim 5 wherein the at least one location sensor is one of: (i) an orientation sensor; (ii) a compass, (iii) a GPS device.
7. The apparatus of claim 5 further comprising an alignment member receiving the at least one location sensor, the alignment member aligning the at least one location sensor with the seismic device.

8. The apparatus of claim 5 wherein the at least one location parameter is one of: (i) x-coordinate, (ii) y-coordinate, (iii) elevation, (iv) z-coordinate, (v) inclination (vi) tilt and (vii) azimuth.
9. The apparatus of claim 1 further comprising a hand-held device configured to receive one of: (i) the memory module, and (ii) the processor.
10. The apparatus of claim 1 wherein the communication device uses one of: (i) a wireless transmission media, and (ii) one or more wires.
11. A method for configuring a seismic device, comprising:  
positioning the seismic device in a geographical area of interest; and  
configuring the seismic device using data associated with the seismic device.
12. The method of claim 11 wherein the data includes one of: (i) a configuration file, (ii) an acquisition parameter, and (iii) an operational parameter.
13. The method of claim 11 wherein the data includes processor-executable instructions.
14. The method of claim 11 wherein the seismic device is a sensor station.
15. The method of claim 11 further comprising:  
determining at least one location parameter for the seismic device;  
and  
transmitting the determined at least one location parameter to the seismic device.

16. The method of claim 15 wherein the at least one location sensor is one of: (i) an orientation sensor; (ii) a compass, (iii) a GPS device.

17. The method of claim 15 further comprising aligning the at least one location sensor with the seismic device.

18. The method of claim 11 further comprising transporting a processor to the geographical area of interest, the processor being programmed to configure the seismic device; and positioning the processor proximate to the seismic device.

19. The method of claim 11 further comprising transporting a memory module to the geographical area of interest, the memory module including the data associated with the seismic device.

20. The method of claim 9 wherein the transmitting is performed using one of: (i) a wireless media, and (ii) one or more wires.




FIG. 1










FIG. 2

3/5





**FIG. 4**

5/5




FIG. 5