



(51) International Patent Classification:

G06T 19/00 (2011.01) G06F 3/048 (2006.01)

G06T 7/11 (2017.01) G06T 19/20 (2011.01)

G06T 7/70 (2017.01)

(21) International Application Number:

PCT/KR2019/007720

(22) International Filing Date:

26 June 2019 (26.06.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/690,813 27 June 2018 (27.06.2018) US

16/274,054 12 February 2019 (12.02.2019) US

(71) Applicant: SAMSUNG ELECTRONICS CO., LTD.

[KR/KR]; 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do 16677 (KR).

(72) Inventors: KOCHARLAKOTA, Sridhar; 665 Clyde

Avenue, Mountain View, California 94043 (US). SON-ASATH, Moiz; 665 Clyde Avenue, Mountain View, California 94043 (US).

(74) Agent: LEE, Keon-Joo et al.; Mihwa Bldg., 16, Daehak-ro


9-gil, Chongro-gu, Seoul 03079 (KR).

(81) Designated States (unless otherwise indicated, for every

kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,

(54) Title: APPARATUS AND METHOD FOR AUGMENTED REALITY

[Fig. 2]



(57) Abstract: A method for providing a personalized augmented reality (AR) display includes obtaining, at an augmented reality apparatus, image data of a camera field of view, the camera field of view covering a field of view of an externally oriented camera of the augmented reality apparatus, identifying a first object in the camera field of view based on the image data, and mapping a position of the first object relative to an augmented reality (AR) field of view. The method further includes determining, based on the identity of the first object, whether the first object is an augmentation target, and responsive to determining that the first object is the augmentation target, displaying, on the internally-facing display, an item of AR content associated with the augmentation target in the AR field of view.

OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

Description

Title of Invention: APPARATUS AND METHOD FOR AUGMENTED REALITY

Technical Field

- [1] This disclosure relates generally to communication technology. More specifically, this disclosure relates to an apparatus and method for augmented reality.

Background Art

- [2] Portable networked devices with displays, such as tablets and smartphones have, within the course of little over a decade, gone from being luxury items to supplanting desktop computers, fax machines and landline telephones as the default device for personal and business communications. The smartphone's dominance as the primary communication interface for millions of people is reflected by the frequency with which many users check their devices and the steady rise in screen time among users.
- [3] In addition to the emergence of portable networked devices as a dominant communication medium, the past decade has also witnessed the emergence of new display technologies, including virtual reality (VR) and augmented reality (AR), which harness the possibilities of small form processors and lightweight displays to provide displays which supplant or augment the feed of visual information to viewers' eyes from the physical world.
- [4] The ubiquity of portable devices, such as smartphones and the emergence of new display technologies, such as AR and VR present numerous opportunities and technological challenges associated with improving the functionality of smartphones and other portable devices as tools for communication by incorporating AR and VR technologies.
- [5] The above information is presented as background information only to assist with an understanding of the present disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the present disclosure.

Disclosure of Invention

Technical Problem

- [6] This disclosure has been made to address at least the above problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of this disclosure is to provide an apparatus and a method for augmented reality.

Solution to Problem

- [7] In a first embodiment, a method for providing a personalized augmented reality (AR) display includes obtaining, at an augmented reality apparatus, image data of a camera

field of view, the camera field of view covering a field of view of an externally oriented camera of the augmented reality apparatus, identifying a first object in the camera field of view based on the image data, and mapping a position of the first object relative to an augmented reality (AR) field of view, the AR field of view covering a portion of the camera field of view in which augmented reality (AR) content can be displayed on an internally-facing display of the augmented reality apparatus. The method further includes determining, based on the identity of the first object, whether the first object is an augmentation target, and responsive to determining that the first object is the augmentation target, displaying, on the internally-facing display, an item of AR content associated with the augmentation target in the AR field of view.

- [8] In a second embodiment, an augmented reality apparatus includes an externally oriented camera covering a camera field of view, the camera field of view including a field of view of the externally oriented camera, an internally-facing display providing an augmented reality (AR) field of view, the AR field of view including a portion of the camera field of view in which AR content can be displayed on the internally-facing display of the augmented reality apparatus, a processor and a memory containing instructions, which when executed by the processor, cause the processor to implement a personalized communication augmented reality (PCAR) framework. The PCAR is configured to obtain image data of the camera field of view, identify a first object in the camera field of view based on the image data, map a position of the first object in the camera field of view relative to the AR field of view, determine, based on the identity of the first object, whether the first object is an augmentation target, and responsive to determining that the first object is the augmentation target, display, on the internally-facing display, an item of AR content associated with the augmentation target in the AR field of view.

- [9] In a third embodiment, a non-transitory computer-readable medium includes program code, which when executed by a processor, causes an augmented reality apparatus to obtain image data of a camera field of view, the camera field of view including a field of view of an externally oriented camera of the augmented reality apparatus, identify a first object in the camera field of view based on the image data, and map a position of the first object relative to an augmented reality (AR) field of view, the AR field of view in a portion of the camera field of view in which augmented reality (AR) content can be displayed on an internally-facing display of the augmented reality apparatus. The non-transitory computer-readable medium further includes program code, which when executed by the processor, causes the augmented reality apparatus to determine, based on the identity of the first object, whether the first object is an augmentation target, and responsive to determining that the first object is the augmentation target,

display, on the internally-facing display, an item of AR content associated with the augmentation target in the AR field of view.

[10] Other technical features may be readily apparent to one skilled in the art from the following Figures, descriptions, and claims.

[11] Before undertaking the DETAILED DESCRIPTION below, it may be advantageous to set forth definitions of certain words and phrases used throughout this patent document. The term "couple" and its derivatives refer to any direct or indirect communication between two or more elements, whether or not those elements are in physical contact with one another. The terms "transmit," "receive," and "communicate," as well as derivatives thereof, encompass both direct and indirect communication. The terms "include" and "comprise," as well as derivatives thereof, mean inclusion without limitation. The term "or" is inclusive, meaning and/or. The phrase "associated with," as well as derivatives thereof, means to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, have a relationship to or with, or the like. The term "controller" means any device, system or part thereof that controls at least one operation. Such a controller may be implemented in hardware or a combination of hardware and software and/or firmware. The functionality associated with any particular controller may be centralized or distributed, whether locally or remotely. The phrase "at least one of," when used with a list of items, means that different combinations of one or more of the listed items may be used, and only one item in the list may be needed. For example, "at least one of: A, B, and C" includes any of the following combinations: A, B, C, A and B, A and C, B and C, and A and B and C.

[12] Moreover, various functions described below can be implemented or supported by one or more computer programs, each of which is formed from computer readable program code and embodied in a computer readable medium. The terms "application" and "program" refer to one or more computer programs, software components, sets of instructions, procedures, functions, objects, classes, instances, related data, or a portion thereof adapted for implementation in a suitable computer readable program code. The phrase "computer readable program code" includes any type of computer code, including source code, object code, and executable code. The phrase "computer readable medium" includes any type of medium capable of being accessed by a computer, such as read only memory (ROM), random access memory (RAM), a hard disk drive, a compact disc (CD), a digital video disc (DVD), or any other type of memory. A "non-transitory" computer readable medium excludes wired, wireless, optical, or other communication links that transport transitory electrical or other signals. A non-transitory computer readable medium includes media where data can be

permanently stored and media where data can be stored and later overwritten, such as a rewritable optical disc or an erasable memory device.

- [13] Definitions for other certain words and phrases are provided throughout this patent document. Those of ordinary skill in the art should understand that in many if not most instances, such definitions apply to prior as well as future uses of such defined words and phrases.

Brief Description of Drawings

- [14] For a more complete understanding of this disclosure and its advantages, reference is now made to the following description, taken in conjunction with the accompanying drawings, in which:
- [15] Figure 1 illustrates an example of an electronic device for implementing apparatuses and methods for augmented reality according to certain embodiments of this disclosure;
- [16] Figure 2 illustrates an example of an architecture incorporating a personalized communication augmented reality (PCAR) framework according to some embodiments of this disclosure;
- [17] Figure 3 illustrates an example of an augmented reality apparatus according to one or more embodiments of this disclosure;
- [18] Figure 4 illustrates an example of fields of view at an AR apparatus according to some embodiments of this disclosure;
- [19] Figure 5 illustrates an example of fields of view at an AR apparatus according to various embodiments of this disclosure;
- [20] Figure 6 illustrates an example of a PCAR database schema according to certain embodiments of this disclosure;
- [21] Figure 7 illustrates aspects of image recognition using binary image descriptors, according to various embodiments of the present disclosure;
- [22] Figures 8A, 8B, 8C, 8D, 8E, and 8F illustrate aspects of augmented reality-based communication according to certain embodiments of this disclosure;
- [23] Figures 9A, 9B, 9C, and 9D illustrate aspects of augmented reality-based communication according to various embodiments of this disclosure;
- [24] Figure 10 illustrates operations of a method of operating a PCAR framework in a normal mode, according to some embodiments of this disclosure;
- [25] Figure 11 illustrates operations of a method of operating a PCAR framework in an augmentation mode, according to at least one embodiment of this disclosure;
- [26] Figure 12 illustrates operations of a method for performing augmented reality-based communications according to certain embodiments of this disclosure; and
- [27] Figure 13 illustrates operations of methods for performing augmented reality-based

communications according to various embodiments of this disclosure.

- [28] Throughout the drawings, like reference numerals will be understood to refer to like parts, components, and structures.

Mode for the Invention

- [29] Figures 1 through 13, discussed below, and the various embodiments used to describe the principles of this disclosure in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the disclosure. Those skilled in the art will understand that the principles of this disclosure may be implemented in any suitably arranged wireless communication system.

- [30] Figure 1 illustrates a non-limiting example of a device for augmented reality-based communication according to some embodiments of this disclosure. The embodiment of device 100 illustrated in Figure 1 is for illustration only, and other configurations are possible. However, suitable devices come in a wide variety of configurations, and Figure 1 does not limit the scope of this disclosure to any particular implementation of a device. For example, device 100 may be implemented, without limitation, as a smartphone, a wearable smart device (such as a smart watch), a tablet computer, or as a head-mounted display.

- [31] As shown in the non-limiting example of Figure 1, the device 100 includes a communication unit 110 that may include, for example, a radio frequency (RF) transceiver, a Bluetooth® transceiver, or WI-FI® transceiver, etc., transmit (TX) processing circuitry 115, a microphone 120, and receive (RX) processing circuitry 125. The device 100 also includes a speaker 130, a main processor 140, an input/output (I/O) interface (IF) 145, input/output device(s) 150, and a memory 160. The memory 160 includes an operating system (OS) program 161 and one or more applications 162.

- [32] Applications 162 can include games, social media applications, applications for geotagging photographs and other items of digital content, virtual reality (VR) applications, augmented reality (AR) applications, operating systems, device security (e.g., anti-theft and device tracking) applications or any other applications which access resources of device 100, the resources of device 100 including, without limitation, speaker 130, microphone 120, input/output devices 150, and additional resources 180. According to some embodiments, applications 162 include applications which can consume image data from physical objects in a field of view of a camera of electronic device 100 and provide AR or VR content through a display of device 100, or a display of a separate device.

- [33] The communication unit 110 may receive an incoming RF signal, for example, a near field communication signal such as a Bluetooth® or Wi-Fi™ signal. The communication unit 110 can down-convert the incoming RF signal to generate an intermediate

frequency (IF) or baseband signal. The IF or baseband signal is sent to the RX processing circuitry 125, which generates a processed baseband signal by filtering, decoding, or digitizing the baseband or IF signal. The RX processing circuitry 125 transmits the processed baseband signal to the speaker 130 (such as for voice data) or to the main processor 140 for further processing (such as for web browsing data, online gameplay data, notification data, or other message data). Additionally, communication unit 110 may contain a network interface, such as a network card, or a network interface implemented through software.

[34] The TX processing circuitry 115 receives analog or digital voice data from the microphone 120 or other outgoing baseband data (such as web data, e-mail, or interactive video game data) from the main processor 140. The TX processing circuitry 115 encodes, multiplexes, or digitizes the outgoing baseband data to generate a processed baseband or IF signal. The communication unit 110 receives the outgoing processed baseband or IF signal from the TX processing circuitry 115 and up-converts the baseband or IF signal to an RF signal for transmission.

[35] The main processor 140 can include one or more processors or other processing devices and execute the OS program 161 stored in the memory 160 in order to control the overall operation of the device 100. For example, the main processor 140 could control the reception of forward channel signals and the transmission of reverse channel signals by the communication unit 110, the RX processing circuitry 125, and the TX processing circuitry 115 in accordance with well-known principles. In some embodiments, the main processor 140 includes at least one microprocessor or microcontroller.

[36] The main processor 140 is also capable of executing other processes and programs resident in the memory 160. The main processor 140 can move data into or out of the memory 160 as required by an executing process. In some embodiments, the main processor 140 is configured to execute the applications 162 based on the OS program 161 or in response to inputs from a user or applications 162. Applications 162 can include applications specifically developed for the platform of device 100, or legacy applications developed for earlier platforms. Additionally, main processor 140 can be manufactured to include program logic for implementing methods for monitoring suspicious application access according to certain embodiments of the present disclosure. The main processor 140 is also coupled to the I/O interface 145, which provides the device 100 with the ability to connect to other devices such as laptop computers and handheld computers. The I/O interface 145 is the communication path between these accessories and the main processor 140.

[37] The main processor 140 is also coupled to the input/output device(s) 150. The operator of the device 100 can use the input/output device(s) 150 to enter data into the

device 100. Input/output device(s) 150 can include keyboards, head mounted displays (HMD), touch screens, mouse(s), track balls or other devices capable of acting as a user interface to allow a user to interact with electronic device 100. In some embodiments, input/output device(s) 150 can include a touch panel, a (digital) pen sensor, a key, or an ultrasonic input device.

[38] Input/output device(s) 150 can include one or more screens, which can be a liquid crystal display, light-emitting diode (LED) display, an optical LED (OLED), an active matrix OLED (AMOLED), or other screens capable of rendering graphics.

[39] The memory 160 is coupled to the main processor 140. According to certain embodiments, part of the memory 160 includes a random access memory (RAM), and another part of the memory 160 includes a Flash memory or other read-only memory (ROM). Although Figure 1 illustrates one example of a device 100. Various changes can be made to Figure 1.

[40] For example, according to certain embodiments, device 100 can further include a separate graphics processing unit (GPU) 170.

[41] According to certain embodiments, electronic device 100 includes a variety of additional resources 180 which can, if permitted, be accessed by applications 162. According to certain embodiments, additional resources 180 include an accelerometer or inertial motion unit 182, which can detect movements of the electronic device along one or more degrees of freedom. Additional resources 180 include, in some embodiments, a dynamic vision sensor (DVS) 184, one or more cameras 186 of electronic device 100.

[42] Although Figure 1 illustrates one example of a device 100 for performing semi-dense depth estimation, various changes may be made to Figure 1. For example, the device 100 could include any number of components in any suitable arrangement. In general, devices including computing and communication systems come in a wide variety of configurations, and Figure 1 does not limit the scope of this disclosure to any particular configuration. While Figure 1 illustrates one operational environment in which various features disclosed in this patent document can be used, these features could be used in any other suitable system.

[43] Figure 2 illustrates an example of an architecture 200 incorporating a personalized communication augmented reality (PCAR) framework according to some embodiments of this disclosure. The embodiment of the architecture 200 shown in Figure 2 is for illustration only and other embodiments could be used without departing from the scope of the present disclosure.

[44] For ease of explanation, in the non-limiting example of Figure 2, architecture 200 adheres to a client-host model between host platform 201 and client platform 205, with the components of a PCAR framework 220 implemented as software on a logical layer

between an AR application layer 230 and an OS/device layer 210. Other embodiments, such as embodiments utilizing a peer-to-peer relationship (as opposed to a host-client) between entities, or where the components of PCAR framework 220 are implemented as hardware, or a combination of hardware and software, are possible and within the contemplated scope of this disclosure.

- [45] According to certain embodiments, host platform 201 comprises a database server, which is communicatively connected (for example, via the internet, a wireless network, or an intranet) to client platform 205. As one non-limiting example, host platform 201 comprises networked computer, such as a database server running an instance of MySQL to host a PCAR database 203.
- [46] According to various embodiments, PCAR database 203 comprises, at a minimum, a repository of information associating items of augmented reality (AR) content with identifiers of objects. According to some embodiments, PCAR database 203 also includes data corresponding to a schema comprising object signatures (for example, identifiers of a particular object - for example, a chair at a known location), a user identifier (for example, an ID of a user who created an association between item(s) of AR content and an object, visibility data (for example, data specifying the permissions of other user to view the AR content whose association was created by a user identified in the user identifier field, object location, and the expiration time of the association between the item of AR content and the object.
- [47] In certain embodiments, the associations between item(s) of AR content and objects are determined by a user (for example, as shown in Figures 8A through 8F of this disclosure). In various embodiments, the logic for creating associations between objects and item(s) of content reside within the AR apparatus itself. As a non-limiting example, a PCAR service running on client platform 205 could use information of the client platform itself (for example, an international mobile equipment identifier (IMEI) associated with client platform, or system information, such as an identifier of the operating system) to create associations between objects (for example, a charger for the device) and item(s) of AR content. As one example, a PCAR service for client platform 205 may receive from a PCAR database 203, information associating an item of AR content provided by a mobile carrier for client platform 205 with an object. As an example, an item of AR content comprising an advertisement for an upgraded mobile service plan may be presented when the client platform 205 receives image data associated with the charger or power supply for client platform 205. In this example, the itemAR content is selected to be associated with the object based on a piece of information regarding the client platform, such as the identity of the wireless carrier to which the client platform is a subscriber.
- [48] In various embodiments according to this disclosure, the associations between items

of AR content and objects are driven by, and pushed out, by host platform 201 in conjunction with PCAR database 203. Thus, certain embodiments according to this disclosure support communications between client devices (for example, as shown in Figures 8A through 8F), as well as end-to-end communications between a host platform 201 and 203. In some embodiments according to this disclosure, host platform 201 receives information (for example, from network access points, such as Wi-Fi routers or ZigBee transceivers) regarding the identity of devices within visual range of an object which is an augmentation target. Based on this information, host platform 201 pushes out association information maintained in PCAR database 203 to some or all of the identified devices. As an illustrative example, the augmentation shown to users in Figures 9A through 9D of this disclosure may be selected on device information obtained by host platform 201. As one example, the information regarding the television set shown in Figures 9A through 9D might, based on device identity information, only be pushed out to devices manufactured by the maker of the television.

[49] As shown in the non-limiting example of Figure 2, client platform 205 comprises one or more electronic devices (for example, a head mounted display and a smartphone, or electronic device 100 of Figure 1) which are communicatively connected to host platform 201. In this illustrative example, on the client side, architecture 200 comprises three logical layers - a device / operating system (OS) layer 210, a middle layer comprising PCAR framework 220, and an AR application layer 230.

[50] In certain embodiments according to this disclosure, device / OS layer 210 comprises the hardware, software or combination of hardware and software of client platform 205 which obtains image data 215 and location data 217.

[51] In some embodiments, image data 215 comprises data output by from one or more externally-oriented sensors (for example, a CMOS video camera or a dynamic vision sensor (DVS), configured to produce a comparatively less data-intensive representation of a field of view by capturing changes in the intensity of received light at the pixels of the sensor). As used in this disclosure, the term "externally-oriented" encompasses directions away from a direction of projection of a display for presenting AR content in an AR apparatus. As a non-limiting example, for an AR device to be worn over a user's eyes, a display in the AR device projecting content towards the user's eyes would be "internally-oriented" or "internally facing," while a camera of the device pointed at the world in front of the user, would be "externally oriented." In some embodiments, the one or more sensors generating image data 215 may be components of an augmented reality apparatus (for example, a headset, "smart glasses" or a smartphone).

[52] In some embodiments, location data 217 comprises positioning data (for example, data assigning a specific geospatial coordinate to a sensor), as well as metadata of a

specific location (for example, data associating a particular geospatial location and altitude with a particular room in a building, as well as attributes of the location, such as the presence of IoT devices or other devices with which an AR apparatus can communicate). In the non-limiting example of Figure 2, location data 217 may be obtained from a GPS sensor, an IMU (for example, IMU 182 in Figure 1), and a communication unit (for example, communication unit 110 in Figure 1) for communicating with networked devices at a particular location.

- [53] According to various embodiments, data from device / OS layer 210, such as image data 215 and location data 217 are provided to PCAR framework 220.
- [54] According to various embodiments, PCAR framework 220 catalyzes improvements in the functionality of certain electronic devices, such as smartphones or devices with head mounted displays, such as "smart glasses," by allowing users to communicate by assigning items of virtual reality or augmented reality content to locations and objects (including, without limitation, native objects) within the physical world. As used in this disclosure, the term "native object" encompasses an object whose form or appearance has not been modified, for example, by affixing a sticker with a QR code, to enhance its recognition and identification in a set of digital image data. As discussed elsewhere herein, embodiments according to the present disclosure facilitate the creation, assignment and management of AR and VR content by AR apparatus users, thereby allowing commonly-used devices, such as smartphones, to operate as platforms for managed AR and VR based communication between users. As such, embodiments as disclosed and claimed, extend the functionality of AR from being a technology merely allowing users of AR apparatus to consume content (for example, by seeing AR content created and selected for a general audience, such as AR content associated with a landmark viewed through an AR apparatus), to being a technology which allows users of AR apparatus to consume, produce, and manage content, thereby allowing AR apparatus to function as a tool for communication.
- [55] Referring to the non-limiting example of Figure 2, PCAR framework 220 comprises signature engine 225, object recognition engine 227, and augmentation engine 229. In this non-limiting example, each of signature engine 225, object recognition engine 227 and augmentation engine 229 are implemented as program code executed by a processor of client platform 205. In certain embodiments, the components of PCAR framework may be implemented as hardware (for example, by an image recognition processor) or across multiple computing platforms (for example, a cloud based platform connected by an API to the client platform 205).
- [56] According to certain embodiments, object recognition engine 227 obtains image data from covering a field of view of an externally-oriented camera or other visual sensor (for example, a DVS sensor, such as DVS sensor 184 in Figure 1) trained on a field of

view in which objects which can be recognized as augmentation objects may be found. In certain embodiments, object recognition engine 227 processes the image data to detect features in the image data. According to various embodiments, the object recognition engine 227 performs object recognition using a binary descriptor based object recognition technique, including, for example, the binary robust independent elementary features (BRIF), binary robust invariant scalable keypoints (BRISK), fast retina keypoints (FREAK), or oriented fast and rotated BRIEF (ORB). According to various embodiments, object recognition engine 227 identifies one or more objects within the field of view of an externally facing sensor (such as an CMOS camera or DVS sensor) and provides a descriptor or other data associated with the identification of the first object to augmentation engine 229 or signature engine 225.

[57] According to various embodiments, signature engine 225 receives descriptors of recognized objects in a field of view (for example, a camera field of view of an AR apparatus operating as client platform 205) from object recognition engine 227. In certain embodiments, object recognition engine 227 operates continuously, and continuously scans image data from a field of view for objects to recognize. According to some embodiments, object recognition engine 227 may, to conserve battery or other resources, suspend or reduce its operation when a threshold condition (for example, it stops recognizing unique objects at a given location) is met. Additionally, in various embodiments, signature engine 225 also receives location data 217 from one or more entities (such as a GPS sensor, or wireless communication unit). According to various embodiments, signature engine 225 generates, for each object associated with a descriptor generated by object recognition engine 227, and location data 217, a signature for the object. In certain embodiments, signature engine 225 generates the signature based on just the descriptor generated by object recognition engine 227. According to various embodiments, the signature may be unique. According to some embodiments, a signature consists of a hash of the descriptor and location. In the non-limiting example of Figure 2, signature engine 225 periodically performs comparisons of generated signatures against signatures maintained in a PCAR database 203 maintained on host platform 201. According to various embodiments, when a match between a signature at client platform 205 and host platform 201 is determined, signature engine 225 receives augmentation data. According to various embodiments, augmentation data encompasses, at a minimum, data associated with an AR display, the AR display being associated with the object for which a signature match was determined.

[58] In various embodiments according to this disclosure, PCAR framework 220 includes augmentation engine 229. In certain embodiments, augmentation engine 229 supports at least two modes of operation comprising a normal mode, and an augmentation mode. In some embodiments, PCAR framework 220 allows the client platform 205 to

simultaneously operate in both normal mode and augmentation mode. In certain embodiments, client platform 205 may operate exclusively in either a normal mode or an augmentation mode. According to the non-limiting example of Figure 2, in the normal mode, augmentation engine 229 receives augmentation data for objects which have been recognized, and whose signature matches a signature associated with an AR augmentation in PCAR database 203. In certain embodiments, augmentation engine 229 receives outputs from object recognition engine 227, including, for example, data indicating the location of features of the object (for example, corners, legs, etc.) In various embodiments, augmentation engine 229 provides an AR application data comprising, or based on, the augmentation data and the data from object recognition engine 227. In various embodiments according to this disclosure, in normal mode, augmentation engine 229 also receives certain inputs provided through AR application (for example, an input indicating that an item of AR content has been viewed), which are passed through signature engine 225 to PCAR database 203.

[59] Referring to the non-limiting example of Figure 2, in an augmentation mode, augmentation engine 229 receives inputs from AR application 230 for associating an item of AR content with a recognized object in a field of view of a sensor communicatively connected to client platform 205. In certain embodiments, the augmentation engine formats the received inputs according to a schema of PCAR database 203 into augmentation data, which is further associated with an object signature for the recognized object (for example, a signature generated by signature engine 225) and passed to PCAR database 203.

[60] As shown in the non-limiting example of Figure 2, in architecture 200, client platform 205 also comprises an AR application 230. According to certain embodiments, AR application 230 provides AR content for display on an internally-facing display of client platform 205 (for example, an AR apparatus communicatively connected to host platform 201). In some embodiments, the internally-facing display of client platform 205 provides an AR field of view, which comprises a portion of a camera field of view of a camera or other sensor providing image data 215. In certain embodiments, the AR field of view is a subset of the camera field of view. In certain embodiments, the AR field of view comprises an area of overlap with the camera field of view. In various embodiments, the AR field of view is co-extensive with the camera field of view. In some embodiments, the camera field of view is a subset of the AR field of view. In certain embodiments, AR application 230 displays both the AR content and a visual identification (for example, a box or callout) around the recognized object that is the augmentation target with which the AR content is associated. According to various embodiments, AR application 230 provides a user interface for assigning AR content to the augmentation target.

- [61] Figure 3 illustrates an example of an augmented reality (AR) apparatus 300 according to one or more embodiments of this disclosure. According to various embodiments, AR apparatus may function as a client device (for example, client platform 205 in Figure 2) in communicative contact with a host system (for example, host platform 201 in Figure 2) which maintains one or more databases of object signatures and augmentation data associated with object signatures. According to some embodiments, AR apparatus 300 may operate as an accessory device to another device (for example, a smartphone), which in turn acts as a client device to a host system maintaining associations between object signatures and augmentation data. In certain embodiments, associations between object signatures and augmentation data may be maintained across a variety of peer devices, rather than according to a host-client architecture.
- [62] Referring to the non-limiting example of Figure 3, AR apparatus 300 includes an externally oriented camera 305. For the purposes of explaining this non-limiting example, the arrow 301 is provided. Arrow 301 points externally, towards a field of view away from the direction of projection of an internal-facing display of AR apparatus 300. According to various embodiments, externally oriented camera 305 is an RGB digital video camera (for example, a camera using a CMOS sensor). According to some embodiments, externally oriented camera 305 is a camera capable of detecting light at wavelengths outside the visible range of the human eye (for example, infrared). In certain embodiments, externally oriented camera 305 is a dynamic vision sensor (DVS), which provides an event stream of changes in the intensity of light received at pixels of a sensor of the DVS. In this non-limiting example, externally-oriented camera 305 generates image data, either as an event stream or as discrete image frames, which are passed to a PCAR framework (for example, PCAR framework 220 in Figure 2).
- [63] Referring to the non-limiting example of Figure 3, AR apparatus 300 includes an externally oriented camera 305. For the purposes of explaining this non-limiting example, the arrow 301 is provided. Arrow 301 points externally, towards a field of view away from the direction of projection of an internal-facing display of AR apparatus 300. According to various embodiments, externally oriented camera 305 is an RGB digital video camera (for example, a camera using a CMOS sensor). According to some embodiments, externally oriented camera 305 is a camera capable of detecting light at wavelengths outside the visible range of the human eye (for example, infrared). In certain embodiments, externally oriented camera 305 is a dynamic vision sensor (DVS), which provides an event stream of changes in the intensity of light received at pixels of a sensor of the DVS. In this non-limiting example, externally-oriented camera 305 generates image data, either as an event stream or as discrete image frames, which

are passed to a PCAR framework (for example, PCAR framework 220 in Figure 2).

- [64] According to various embodiments, AR apparatus 300 includes second camera 309. In some embodiments, second camera 309 is an externally-oriented camera of the same type as externally-oriented camera 305, thereby forming a stereoscopic pair which can generate image data comprising depth estimation. In certain embodiments, second camera 309 is an externally-oriented camera with a different sensor type than externally-oriented camera 305. For example, in some embodiments, to extend battery life and minimize processor usage, externally-oriented camera 305 is a DVS sensor, and second camera 309 is a CMOS type camera, which, while less efficient than a DVS sensor, can provide additional image data (for example, data regarding colors and elements of a scene whose brightness may not change at a level detectable by a DVS sensor) that is useful for object recognition. According to various embodiments second camera 309 is an internally-facing camera, which tracks the motion of a user's eyes, and by implication, the direction of the user's gaze. Gaze tracking can be used to support foveal rendering of items of AR content, which can conserve battery and processor resources by rendering items of AR content away from a viewer's gaze at lower resolutions.
- [65] According to certain embodiments, AR apparatus 300 includes processor 311 and memory 313. In certain embodiments, memory 313 contains program code, which when executed by processor 311, causes AR apparatus 300 to execute an AR application (for example, AR application 230 in Figure 2), or one or more components of a PCAR framework (for example, PCAR framework 220 in Figure 2).
- [66] Referring to the non-limiting example of Figure 3, AR apparatus 300 includes an inertial measurement unit 315, which generates location data associated with the motion of AR apparatus 300 along one or more degrees of freedom. In certain embodiments, data output from IMU 315 may be used for positioning (for example, to confirm a geospatial position of AR apparatus 300), or to obtain image stabilization data (for example, data indicating the direction and periodicity of a camera shake) to facilitate object recognition.
- [67] In some embodiments, AR apparatus 300 includes input/output interface 317. According to various embodiments, I/O interface 317 provides communicative connectivity between AR apparatus 300 and at least one other electronic device, such as a smartphone, or computer to which AR apparatus 300 is an accessory device. According to certain embodiments, I/O interface 317 connects AR apparatus over a network to a host platform providing a PCAR database. I/O interface is, in certain embodiments, a wireless communication interface, such as a Bluetooth transceiver, or communication hardware supporting communications over one or more longer range wireless systems (for example, communication unit 110 in Figure 1).

- [68] Figure 4 illustrates an example of fields of view at an AR apparatus according to some embodiments of this disclosure. The example of fields of view shown in Figure 4 is for illustration only and other examples could be depicted without departing from the scope of the present disclosure.
- [69] Referring to the non-limiting example of Figure 4, an AR apparatus 400 is shown. AR apparatus 400 comprises an externally-oriented camera 405, which is a camera trained on a field of view (*e.g.*, a "camera field of view") comprising a set of viewing angles which have a component which points away from the direction from an internally-facing display of the AR apparatus and an intended viewing location 415 (represented in this example by a viewer's eye). In some embodiments, externally-oriented camera 405 gathers image data from the camera field of view. AR apparatus 400 recognizes objects in the camera field of view, and a PCAR framework running on AR apparatus provides items of AR content (represented by arrow 417) associated with the recognized objects to internally-facing display 410 to be presented towards intended viewing location 415.
- [70] According to various embodiments, internally-facing display 410 is at least partially transparent, thereby allowing light from external objects located along viewing angles within a field of view in which AR content can be displayed (*e.g.*, an "AR field of view") to pass through internally-facing display 410 to intended viewing location 415. In this non-limiting example, light from tree 419 (represented by arrow 421) passes through display 410 to intended viewing location. Thus, the view at intended viewing location includes both light from tree 419, as well as one or more items of AR content associated with tree 419.
- [71] Figure 5 illustrates an example of fields of view at an AR apparatus according to various embodiments of this disclosure. The example of fields of view shown in Figure 5 is for illustration only and other examples could be depicted without departing from the scope of the present disclosure.
- [72] Referring to the non-limiting example of Figure 5, a scene 500 is shown from a viewing point along an internally-facing direction relative to an AR apparatus 505. In this illustrative example, scene 500 includes first tree 501a, second tree 501b, house 502 and stream 503.
- [73] According to certain embodiments, AR apparatus 505 includes an externally-oriented camera covering a range of view angles defining a camera field of view 507, which includes first tree 501a, house 502 and part of stream 503. Further, AR apparatus 505 includes an internally-facing display 509. In this non-limiting example, internally-facing display 509 is at least partially transparent, and permits light from first tree 501a and house 502 to pass to the viewing point. According to some embodiments, internally-facing display 509 comprises one or more regions in which items of AR

content (for example, notification 511 and object frame 513) can be displayed. In the non-limiting example of Figure 5, the portions of internally-facing display 509 cover a range of viewing angles which defines an AR field of view 515.

[74] Referring to the non-limiting example of Figure 5, a PCAR framework operating on AR apparatus 505 recognizes house 502 from image data of camera field of view 507, determines (for example, based on a signature comparison) that house 502 is an augmentation target, and responsive to determining that house 502 is an augmentation target, displays AR content comprising object frame 513, which identifies house 502 as a recognized object, and notification 511, which is associated with house 502.

[75] Note that, depending on the design objectives, the relative proportions of camera field of view 507 and AR field of view 515 may change. Additionally, depending on applications, the proportions of AR field of view relative to internally-facing display 509 might change. In certain embodiments, such as, for example, an AR apparatus to be used in connection with active pursuits, such as skiing or mountain biking, it may make sense for camera field of view 507 to extend significantly beyond AR field of view 515. In such embodiments, an externally-oriented camera may be able to identify hazards in a user's peripheral vision and provide AR content (for example, a warning regarding a vehicle rapidly approaching from the side). In some embodiments, it may be appropriate for AR field of view 515 to comprise a relatively small portion of display 509, so as to avoid distractions. In various embodiments, it may be appropriate for camera field of view 507 to comprise a subset of AR field of view 515. For example, in embodiments where the AR apparatus is a headset intended for use in applications involving small, near field details (for example, surgery), the externally-oriented camera may provide a magnified view of a small area, which is surrounded by an AR field of view in which multiple pieces of AR content (for example, a patient's vital signs) can be presented.

[76] Figure 6 illustrates an example of a PCAR database schema 600 according to certain embodiments of this disclosure. The embodiment of the PCAR database schema 600 shown in Figure 6 is for illustration only and other examples could be depicted without departing from the scope of the present disclosure.

[77] Referring to the non-limiting example of Figure 6, in certain embodiments, associations between objects which can be identified based on image data from AR apparatus and augmentation data used to generate items of AR content, as well as user-managed attributes of items of AR content are maintained in a PCAR database (for example, PCAR database 203 in Figure 2) on a host platform. In some embodiments, a PCAR database is a relational database utilizing a schema, such as schema 600. In certain embodiments, PCAR database is a columnar database, or other suitable structure for storing and managing associations between objects, augmentation data,

and items of AR content.

- [78] According to certain embodiments, values of an object signature 605 field serve as a primary key (PK) of database schema 600. In some embodiments, an object signature comprises a unique identifier of an object associated with one or more items of augmentation data used to generate items of AR content. In some embodiments, an object signature is a unique identifier of a particular instance of an object (for example, a refrigerator in a particular location, such as a house). In certain embodiments, the object signature comprises a unique identifier of an object for which there may be multiple instances (for example, a particular model of television, or a model of car). In the illustrative example of Figure 6, the object signatures are assigned numbers for objects (for example, signature 607, which corresponds to the assigned number "1"). In certain embodiments, to enhance security, signatures may correspond to an alphanumeric string (for example, a hash of descriptors of an object and other associated data), or an encryption thereof.
- [79] In the non-limiting example of Figure 6, schema 600 includes a "User ID" field 610, the values of which correspond to identifiers of a user who created an association between an object having an object signature and augmentation data. For example, the User ID "Martha" is associated with the object signature "2," identifying Martha as the creator and manager of an item of an item of AR content, the item of AR content being associated with "Virtual Object" augmentation data 609.
- [80] According to various embodiments, schema 600 includes an Augmentation Data field 615. In certain embodiments, the values of augmentation data field 615 comprise pointers to locations where data for an item of AR content are stored. For example, the "Text and Web Content Item" augmentation data 617 associated with object signature 607 may correspond to images and text stored at location at an edge caching server, the address of which is provided to an AR application (for example, AR application 230 in Figure 2), and which the AR application accesses to assemble an item of AR content for display on the AR apparatus. In some embodiments, augmentation data may comprise an actual item of AR content (for example, a video to be played at an AR apparatus).
- [81] In certain embodiments according to this disclosure, schema 600 includes a visibility field 620, which is an attribute of the association between an object (as identified by its object signature) and one or more items of augmentation data. As shown in the non-limiting example of Figure 6, values in visibility field 620 correspond to identifiers of users who can access the augmentation data associated with a particular object signature. For example, visibility value 619 specifies that "Martha" is the user with permission to see item(s) of AR content based on augmentation data 617, in response to an AR apparatus associated with Martha recognizing, based on obtained image data,

an object having object signature 607.

- [82] As shown in the non-limiting example of Figure 6, schema 600 also includes object location field 625, whose values specify a location, or set of locations associated with an object having a particular object signature value. According to various embodiments, object location data can be used to distinguish between objects which are generic augmentation targets (for example, any instance of a particular model of automobile), and objects which are specific augmentation targets (for example, a specific instance of a recognized refrigerator at a particular location, which is a user's or viewer's "home fridge."). For example, object location value 627 indicates that the object associated with object signature 607 is located indoors at a specific set of GPS coordinates. In this way, a PCAR database or a PCAR framework utilize object location 627 in determining whether to present an item of AR content based on augmentation data 617 in response to recognizing an object having object signature 607. If the PCAR database or PCAR framework determines that the recognized object is outside or at a different GPS location, the item of AR content will not be presented. As another example, object location value 629 is equal to "anywhere," indicating that there are no location-based constraints on presenting an item of AR content based on augmentation data 609.
- [83] In various embodiments, schema 600 includes expiration time field 630, the values of which specify the duration an item of AR content associated with the augmentation target having a given object signature is to be available for viewing. As an example, expiration time value 631 specifies that item(s) of AR content based on augmentation data 617 are to be available until read by a user specified in visibility field 620. As another example, expiration time value 633 is "indefinite", indicating that AR content based on augmentation data 609 will be persistently available to "John" and "Ted" in response to recognizing objects having object signature.
- [84] While not shown in the illustrative example of Figure 6, schema 600 can include other fields, such as fields indicating a relationship (for example, a hierarchical, or parent-child relationship) between object signatures. For example, a particular chest of drawers may be associated with a first object signature. At the same time, a drawer, or other sub-component of the chest of drawers, may be associated with a second object signature. A relationship field of schema 600 may include values specifying a parent-child relationship between the chest of drawers, and a particular dresser. In this way, AR communications utilizing the chest of drawers as an augmentation target may be more nuanced and effective. For example, a first user may associate an AR item with the chest of drawers, the AR item comprising a note saying that a second user has clean laundry, which is in a particular drawer within the chest of drawers. Further, the database entry associating the item of AR content with the chest of drawers may

include a value in a relationship field specifying a particular drawer, which may also be associated with a second item of AR content.

- [85] Figure 7 illustrates aspects of image recognition using binary image descriptors, according to various embodiments of the present disclosure. The example of the image recognition shown in Figure 7 is for illustration only and other examples could be depicted without departing from the scope of the present disclosure.
- [86] Certain embodiments according to this disclosure recognize objects from image data obtained over a camera field of view by recognizing three dimensional feature points (also referred to as "smart feature points") within the image data of a scene. According to certain embodiments, three dimensional feature points comprise characteristic features (for example, corners and relationships between corners) of objects which can be reliably found within image data obtained at an AR apparatus. Various embodiments according to this disclosure recognize three dimensional feature points of objects (including objects which are augmentation targets) by using binary image descriptors.
- [87] Referring to the non-limiting example of Figure 7, a three dimensional feature space 700 is shown. According to various embodiments, three dimensional feature space 700 is a three dimensional section of the physical world covered by the field of view of an externally-facing camera of an AR apparatus. According to various embodiments, a recognition engine (for example, object recognition engine 227 in Figure 2) or other image analysis process, obtains image data comprising patches associated with points in the feature space, such as points 701a, 701b and 701c shown in Figure 7. In certain embodiments, the image patches are selected based on a visual scanning / search algorithm of the recognition engine. In various embodiments, the image patches are selected based on existing knowledge regarding the feature space, such as a map of known features of the space based on previously obtained image data.
- [88] As shown in the non-limiting example of Figure 7, image patch 705 is obtained from image data obtained at point 701a. According to various embodiments, a binary representation of image patch 705 is obtained by image intensity data at points of a sampling pattern. As shown by graphic 710, in this illustrative example, the sampling pattern comprises a 3x3 grid which includes sampling points 715a, 715b and 715c. According to various embodiments, a representative slice of the visual information contained in patch 705 can be encoded as a binary string or binary vector, by comparing the intensity value of a predetermined set of pairs of sampling points within the sampling pattern. In the non-limiting example of Figure 7, in the predetermined set of pairs of sampling points is represented through lines connecting a given sampling point to certain other sampling points. In certain embodiments, where a given sampling point of a sampling point pair in a patch has the higher intensity value of the sampling

point pair, a "1" is written to the binary string. Similarly, if the sampling point has a lower intensity value than a conjugate sampling point of the sampling point pair, a "0" is written to the binary string of binary vector. By repeating this comparison across the predetermined set of sampling vectors, a binary string or binary vector 715 representing the patch is generated.

- [89] According to certain embodiments, binary vector 715 can be rapidly compared against other binary vectors describing features of objects to be recognized (also known as "binary descriptors") by calculating the Hamming distance (for example, a value representing the number of divergent or similar values between two binary vectors) or by applying an exclusive OR ("XOR") operation to values of a binary vector encoding information from an image patch (for example, binary vector 715) and a binary vector representing a feature of a recognizable object. Where a hamming distance or value of an XOR operation is within an acceptable range, the image patch is recognized as a feature of an object. In certain embodiments, by iteratively encoding and comparing patches of image data obtained across feature space 700, objects within the space can be recognized the purposes of AR based communication.
- [90] Figures 8A through 8F illustrate aspects of augmented reality-based communication according to certain embodiments of this disclosure. In the illustrative examples of Figures 8A-8F, a method of communication according to this disclosure is shown from the perspective of an AR field of view of an apparatus (for example, AR apparatus 300 in Figure 3) implementing a PCAR framework (for example, PCAR framework 220 in Figure 2).
- [91] Referring to the non-limiting example of Figure 8A, the portion of a scene 800 visible within the AR field view of an AR apparatus is shown at an initial time, such as immediately after the wearer of the AR apparatus enters the room containing the elements of scene 800. According to certain embodiments, the elements of the scene, such as refrigerator 805 are visible from light within the scene passing through a clear display (for example, display 410 in Figure 4) of the AR apparatus. While not depicted in the non-limiting example of Figure 8A, in addition to allowing light from the scene to pass through the display, the AR apparatus is also obtaining image data of a camera field of view of one or more externally-oriented cameras and processing the image data to identify objects within the camera field of view.
- [92] Referring to the non-limiting example of Figure 8B, elements of an AR field of view of scene 800 are illustrated. In this non-limiting example, two items of AR content - first highlighting frame 810a and second highlighting frame 810b are depicted in a portion of the AR field of view at locations of the display coinciding with the position of refrigerator 805 and second refrigerator 815. According to certain embodiments, the AR apparatus, or a PCAR framework implemented on a device connected to the AR

apparatus, has identified, based on binary descriptors of the refrigerators in image data from an externally-oriented apparatus, the refrigerators. Further, having identified the refrigerators, the AR apparatus has performed a calculation to map the location of refrigerator 805 to a location, or a coordinate representing a location, in the AR field of view. Additionally, according to certain embodiments, the AR apparatus is in an augmentation mode, and has determined that refrigerator 805 and second refrigerator 815 are augmentation targets, which can be associated with an item of AR content (for example, a note or message) to communicate with other AR apparatus users.

[93] In certain embodiments, the AR apparatus's identification of objects within scene 800 can be assisted by data provided by the PCAR framework and/or the objects themselves. In one non-limiting example, the PCAR framework can provide an AR apparatus with additional object information (for example, an identification of objects near the current location of the AR apparatus). This additional object information can be used to provide notifications to a user of the AR apparatus when a predetermined condition (for example, a proximity value to the object) is satisfied. Thus, in one example, a user of an AR apparatus may, upon entering the room of scene 800, receive a message notifying him of refrigerator 805 being an augmentation target. Additionally, in instances where an item of AR content has already been associated with refrigerator 805, the additional object notification may be more specific, such as a message of the form "Message for you on the refrigerator." Through the use of such additional object information, computing and battery resources of an apparatus may be conserved, potentially less image data needs to be received to recognize an object if a user is given an indication of the object to be recognized.

[94] Additionally, in certain embodiments, objects within scene 800 themselves may broadcast or otherwise provide an AR apparatus of their identity, as well as additional object information. For example, refrigerator 805, may, in some embodiments, include a Bluetooth Low Energy transmitter, or LED beacon which emits a signal informing AR apparatus that it is an augmentation target, or that a piece of AR content is associated with refrigerator 805. Here, the object itself provides additional assistance as to the presence of augmentation targets and/or associations between items of AR content and the object, thereby potentially reducing the amount of image data an AR apparatus must process to find augmentation targets within scene 800.

[95] Turning to the non-limiting example of Figure 8C, which illustrates elements of scene 800 within an AR field of view. In this illustrative example, a user (identified as "John") has provided an input (for example, a verbal command or eye gesture) initiating the process of creating an association between an augmentation target (in this case, refrigerator 805) and one or more items of AR content. According to certain embodiments, John's input triggers the display of option menu 820, which presents

various user-selectable parameters of an association between the augmentation target and one or more items of AR content. As shown in this non-limiting example, the user-selectable parameters comprise a type 821 of AR content to be associated with the augmentation target, users 823 to whom the selected AR item(s) of AR content will be visible, and an expiration or duration time 825 for the association between the augmentation target and the item(s) of AR content. In certain embodiments, the user-selectable parameters of option menu 820 may map to one or more fields of a PCAR database schema (for example, schema 600 shown in Figure 6).

[96] Turning to the non-limiting example of Figure 8D, which illustrates an input window 830 presented to the user in response to a selection of parameters further defining the association between the augmentation target and an item of AR content. In this illustrative example, the user "John" has selected the values "TEXT" from type 821, "JEN" from users 823, and "UNTIL READ" from time 825, and has been presented with input window 830, which allows a user to input textual data to be provided as part of an item of AR content associated with an augmentation target. In this non-limiting example, the user "John" inputs text describing food which has been left for a user specified by a value of users 823 in option menu 820. In various embodiments according to this disclosure, after the user creating the association between an augmentation target and an item of AR content (in this case, a message to be seen by certain users who look at refrigerator 805 through AR apparatus connected to a PCAR database), the text inputted through input window 830, along with values for the parameters inputted via option menu 820, as well as location, and user profile information, is transmitted to a platform hosting a database (for example, PCAR database 203 in Figure 2) of associations between augmentation targets, items of AR content, and parameters of the associations.

[97] Figure 8E illustrates elements of scene 800 in the AR field of view of an AR apparatus associated with the user "Jen" selected by the user "John" via option menu 820. In this non-limiting example, the PCAR framework of Jen's AR apparatus is operating in a "normal" mode, and has identified refrigerator 805 as an augmentation target. According to various embodiments, the PCAR framework on Jen's device recognizes refrigerator 805 as an augmentation target using the same object recognition technique as a PCAR framework on John's device (for example, object recognition based on comparing binary descriptors of patches of image data against binary descriptors of features). According to certain embodiments, Jen's device may recognize refrigerator 805 as an augmentation target using a different method, such as by recognizing a visually coded link to a reference in a PCAR database (for example, a QR code) on the refrigerator, or detecting an identifying signal from the refrigerator (for example, an IR beacon on the refrigerator transmitting an identification code).

Having determined that refrigerator 805 is an augmentation target, the PCAR framework on Jen's device generates an object signature associated with refrigerator 805.

- [98] In this illustrative example, the object signature generated at Jen's device matches an object signature for refrigerator 805 maintained at a PCAR database. Further, Jen's user profile matches a value associated with a permission to view the AR content associated with the object signature. As such, Jen receives data associated with an item of AR content (for example, the text of John's message, as well as information specifying how long the image is to be presented. Based on the received data, an item of AR content 840 is presented on a display of Jen's AR apparatus. In this non-limiting example, Jen is presented with a second option window 845, which allows her to choose between either marking John's message as having been read, or responding to John's original message.
- [99] Figure 8F illustrates elements of scene 800 within the AR field of view of the AR apparatus associated with the user "Jen". In this non-limiting example, Jen selected "Respond" in second option window 845, and has composed a response message 850 (for example, an email or text message) to be sent to John in response. As shown above, certain embodiments according to the present disclosure enhance the functionality of smartphones and other AR apparatus by allowing AR to be used as either a standalone communication tool, or as a complement to other communication tools, such as text and email.
- [100] Figures 9A through 9D illustrate aspects of augmented reality-based communication according to various embodiments of this disclosure. The embodiments of the augmented reality-based communication shown in Figures 9A through 9D are for illustration only and other embodiments could be used without departing from the scope of the present disclosure.
- [101] The non-limiting example of Figure 9A illustrates elements of a scene 900 visible in the AR field of view of an AR apparatus associated with a first user, Mary. In this non-limiting example, the elements of scene 900 visible in the AR field of view include television 905.
- [102] The non-limiting example of FIG. 9B illustrates elements of scene 900 visible in the AR field of view of the AR apparatus associated with the user Mary. In this non-limiting example, Mary's AR apparatus has, based on image data of an externally-oriented camera of the AR apparatus, identified television 905 as both a television and an augmentation target, and having mapped the position of television 905 relative to the AR field of view, displays, highlighting frame 910 around television 905 on an internally-facing display of Mary's AR apparatus.
- [103] Figure 9C illustrates elements of scene 900 visible in the AR field of view of Mary's

apparatus. In this non-limiting example, in response to an input from Mary (for example, an affirmative input, such as a voice command, or an implied input, such as gaze tracking data indicating showing Mary looking at the augmentation target in a way that satisfies a specified criteria, such as a temporal threshold), a second item of AR content 915a is presented on an internally facing display (for example, a display like display 410 in Figure 4). According to certain embodiments, the second item of AR content 915a may be based, at least in part, on data (for example, data maintained in a PCAR database) provided by a PCAR database in response to a match between an object signature of television 905 and descriptors of the television maintained in the PCAR database. In this non-limiting example, the second item of AR content 915a is based, at least in part, on a user profile data accessible to an AR application (for example, AR application 230 in Figure 2) operating on Mary's AR apparatus. In various embodiments, such user profile data defines one or more presentation parameters (for example, a choice of language and personalization parameters, such as a name or photograph) of the second item of AR content 920. In the illustrative example of Figure 9D, the presentation parameters drawn from a user profile associated with Mary include her name 917 and the use of English as the language for presenting the message regarding the television set in her AR field of view.

[104] Figure 9D illustrates elements of scene 900 visible in the AR field of view of a second user, "Lars". As illustrated by this non-limiting example, creating associations between augmentation targets and items of AR content according to embodiments of the present disclosure can provide an efficient and easily extensible method of personalized communications. In this non-limiting example, an AR apparatus associated with second user Lars, has, identified television 905 as an augmentation target, and presented a first item of AR content associated with the augmentation target on an internally-facing display of Lars's AR apparatus. Based on Lars's response to the first item of AR content, a second item of AR content 915b is displayed. According to various embodiments, second item of AR content 915b is based on the same data received from a PCAR database as second item of AR content 915a in Figure 9C. Using the same information from a PCAR database, an AR application on Lars's AR apparatus can use information in Lars's user profile to apply different presentation parameters to substantially change the appearance of second item of AR content 915b relative to second item of AR content 915a. In this non-limiting example, information in Lars's user profile provides presentation parameters changing both the addressee 919 of the message, but also switching the language of the message text to German.

[105] Figure 10 illustrates operations of a method 1000 of operating a PCAR framework in a normal mode of operation. According to certain embodiments, a "normal mode of operation" of a PCAR encompasses a mode of operation in which the PCAR is

"listening" or "looking" for items of AR content associated with identified augmentation targets in image data obtained from a camera field of view of an apparatus. In some embodiments, a "normal" mode of operation operates in parallel with an "augmentation mode," in which a PCAR framework is creating or updating an association between an augmentation target and an item of AR content. In certain embodiments, a "normal" mode of operation operates as an alternative to an "augmentation mode." While the flow chart depicts a series of sequential steps, unless explicitly stated, no inference should be drawn from that sequence regarding specific order of performance, performance of steps or portions thereof serially rather than concurrently or in an overlapping manner, or performance of the steps depicted exclusively without the occurrence of intervening or intermediate steps. The process depicted in the example depicted is implemented by a processor in, for example, an electronic device.

- [106] Referring to the non-limiting example of Figure 10, method 1000 includes operation 1010, wherein a PCAR framework (for example, PCAR framework 220 in Figure 2) receives location data and image data from sensors connected to an AR apparatus (for example, image data from externally-oriented camera 405 in Figure 4 and location data from a GPS sensor or IMU 315 in Figure 3). According to various embodiments, image data is received by a camera field of view object recognition engine (for example object recognition engine 227 in Figure 2) and location data is received at the PCAR framework by a signature engine (for example, signature engine 225 in Figure 2).
- [107] According to various embodiments, at operation 1015, the PCAR framework performs an initial determination of whether there are any augmentations associated with the user device at a current device location (as determined from location data received in operation 1010). According to certain embodiments, the determination performed at operation 1015 comprises sending a query to a host platform (for example host platform 201 in Figure 2) which maintains an index or other data structure associating locations, user devices and items of AR content. In certain embodiments, if the outcome of the determination at operation 1015 is negative, method 1000 loops back to operation 1010. If, however, the PCAR determines that there is an item of AR content associated with an augmentation target and visible to viewing devices with the user's profile and current device location, method 1000 proceeds to operation 1020.
- [108] In certain embodiments according to the present disclosure, at operation 1020, one or more components (for example, an augmentation engine, such as augmentation engine 229 in Figure 2 and an object recognition engine, such as object recognition engine 227 in Figure 2) determines whether there are objects within a given sensor range (for example, the field of view of an externally-oriented camera of an AR apparatus) which

comprise augmentation targets. According to various embodiments, the determination of whether there are augmentation targets, and in particular, augmentation targets associated with items of AR content for the present user is performed by applying one or more object recognition algorithms to image data from the externally-oriented camera. In certain embodiments, the determination of whether there are augmentation targets associated with AR content for a present user may be assisted by the augmentation target itself. For example, the augmentation target may have one or more surfaces with a coded medium (for example, a barcode or QR code), bypassing the need for recognition of the object as the augmentation target. As another example, the augmentation target may also have a beacon (for example, a flashing infrared beacon) advertising itself as an augmentation target.

[109] In the non-limiting example of Figure 10, if, at operation 1020, the PCAR cannot find objects in the relevant sensor range(s) which are augmentation targets, method 1000 reverts back to operation 1010. When the PCAR, or a module thereof, such as an augmentation engine, finds objects within the relevant sensor range(s) which are augmentation targets, method 1000 proceeds to operation 1025.

[110] In various embodiments according to the present disclosure, at operation 1025, responsive to finding object(s) within the relevant sensor range(s) (for example, the range of an IR beacon, or within a camera field of view of an externally-oriented camera of an AR apparatus), the PCAR interacts with one or more of a PCAR database (or other repository or data structure maintaining data storing associations between augmentation targets and items of AR content) and an AR application (for example, AR application 230 in Figure 2) to display one or more items of AR content associated with an augmentation target found in operation 1020. According to some embodiments, the item of AR content is a highlighting frame (for example, first highlighting frame 810a in Figure 8C). In various embodiments, the item of AR content displayed at operation 1025 comprises a communicative piece of content (for example, second item of AR content 915a in Figure 9C).

[111] Referring to the non-limiting example of Figure 10, at operation 1030, the PCAR framework provides information regarding the present user's interaction to the device(s) maintaining the PCAR database to update the data defining the association between the augmentation target and the item(s) of AR content. For example, the PCAR framework may provide information indicating that a particular item of AR content (for example, item of AR content 840 in Figure 8E) has been read or responded to. Based on the provided information, and the specified parameters of the association between augmentation target and item of AR content (for example, display settings specifying that the item of content is to be displayed until read) the PCAR database may be updated (for example, by canceling or deleting the association between the

augmentation target and item of AR content).

- [112] Figure 11 illustrates operations of a method 1100 of operating a PCAR framework in an augmentation mode, according to at least one embodiment of this disclosure. While the flow chart depicts a series of sequential steps, unless explicitly stated, no inference should be drawn from that sequence regarding specific order of performance, performance of steps or portions thereof serially rather than concurrently or in an overlapping manner, or performance of the steps depicted exclusively without the occurrence of intervening or intermediate steps. The process depicted in the example depicted is implemented by a processor in, for example, an electronic device. Further, while the operations of method 1100 are described with reference to an exemplary embodiment in which the operations are carried out by a PCAR framework on an electronic device, in certain embodiments, performance of the operations of method 1100 may be distributed across multiple computing platforms.
- [113] Referring to the non-limiting example of Figure 11, at operation 1110, an augmentation mode of a PCAR framework is activated, and an object recognition engine (for example, object recognition engine 227 in Figure 2) is activated. Such activation may be in responses to a received input (for example, a user input). In this way, the PCAR framework is configured to recognize augmentation targets within a relevant sensor range (for example, the field of view of an externally-oriented camera, or the transmission range of a BLUETOOTH® Low Energy ("BLE") beacon on a predetermined augmentation target).
- [114] According to various embodiments, at operation 1115, the PCAR framework recognizes one or more objects as augmentation targets (for example, through comparisons of binary representations of image data patches against binary descriptors of defined features) based on image or other data provided to the PCAR. Responsive to recognizing objects that are augmentation targets, the PCAR maps the objects' location in the image data to positions with an AR field of view (for example, AR field of view 515 in Figure 5) and displays one or more items of AR content comprising selectable overlays of the augmentation targets, and method 1100 proceeds to operation 1120. If, however, the PCAR framework does not recognize any objects, in certain embodiments, method 1100 reverts back to operation 1110. In various embodiments, when reverting to operation 1110, the PCAR framework switches back to "normal" mode, until a fresh input enabling the augmentation mode is received.
- [115] In the non-limiting example of Figure 11, at operation 1120, a user may select
- [116] In the non-limiting example of Figure 11, at operation 1120, a selection input is received. According to certain embodiments, the selection input selects an object associated with an overlay marker as an augmentation target to be associated with one or more pieces of AR content. According to various embodiments, selection input may be

provided by a user, such as through a verbal input processed by a speech recognition algorithm implemented on an AR apparatus or device (for example, a smartphone) communicatively connected thereto. In certain embodiments, the selection input may be provided through a gaze or gesture (for example, a nod) detected by one or more sensors (for example, an internally-facing camera) of an AR apparatus. If a selection input is received by the PCAR framework (for example, within a specified period of time), method 1100 proceeds to operation 1125. If a user selection is not received, or not received within a specified period of time, method 1100 reverts to operation 1110.

- [117] In certain embodiments, at operation 1125, the PCAR framework obtains (for example, by generating a new signature, or retrieving a previously stored signature) an object signature for the object selected in operation 1120 as an augmentation target to be associated with one or more items of AR content. In various embodiments, at operation 1125, the PCAR framework also obtains (for example, by receiving user inputs, such as via option menu 820 in Figure 8C, or from a user profile) parameters (for example, text or images to be displayed) further defining the association between the selected augmentation target and the item of AR content. At operation 1125, the object signature, and the parameters defining the association between the augmentation target and the item of AR content are provided to a PCAR management entity (for example, host platform 201 in Figure 2).
- [118] Referring to the non-limiting example of Figure 11, at operation 1130, the PCAR management entity (for example, a server maintaining a PCAR database) updates a PCAR database to include the association between the selected augmentation target and an item of AR content, and the parameters thereof, created at operation 1125.
- [119] Figure 12 illustrates operations of a method 1200 for performing augmented reality-based communications according to certain embodiments of this disclosure. While the flow chart depicts a series of sequential steps, unless explicitly stated, no inference should be drawn from that sequence regarding specific order of performance, performance of steps or portions thereof serially rather than concurrently or in an overlapping manner, or performance of the steps depicted exclusively without the occurrence of intervening or intermediate steps. The process depicted in the example depicted is implemented by a processor in, for example, an electronic device.
- [120] Referring to the non-limiting example of Figure 12, at operation 1210, a processor (for example, processor 311 in Figure 3) obtains image data of a camera field of view (for example, camera field of view 507 in Figure 5) from an externally-oriented camera (for example, externally-oriented camera 405 in Figure 4).
- [121] According to various embodiments, at operation 1215, an object in the camera field of view (for example, house 502 in Figure 5) is identified (for example, based on an analysis of binary descriptors of patches of image data, as described with reference to

Figure 7) based on the image data obtained at operation 1210.

- [122] As shown in the non-limiting example of Figure 12, at operation 1220, the position of the object identified in operation 1215 is mapped to a position of an AR field of view (for example, the location of object frame 513 in Figure within AR field of view 515 is determined based on a mapping of camera field of view 507 to AR field of view 515).
- [123] According to some embodiments, at operation 1225, a determination of whether the object identified at operation 1215 is an augmentation target is performed. In certain embodiments, this determination is performed by comparing an object signature of the object identified at operation 1215 against a set of object signatures (for example, object signatures maintained in a PCAR database utilizing database schema 600 in Figure 6). In various embodiments, the determination of whether an object comprises an augmentation target is based on whether the object belongs to a defined class of objects which can be augmentation targets (for example, non-transitory items, such as buildings or pieces of furniture).
- [124] Referring to the non-limiting example of Figure 12, at operation 1230, responsive to determining that the object identified at operation 1215 comprises an augmentation target, an item of AR content associated with the augmentation target is displayed on an internally-facing display in the AR field of view of the AR apparatus. For example, the item of AR content may be a frame or overlay which can be selected (for example, first highlighting frame 810a in Figure 8B). In certain embodiments, the item of AR content may be a pre-associated item of AR content (for example, item of content 840 in Figure 8E).
- [125] Figure 13 illustrates operations 1300 of methods for performing augmented reality-based communications according to various embodiments of this disclosure. Depending on embodiments, operations within operations 1300 may be performed in addition to the operations of method 1200 in Figure 2, or as substitutions or alternatives to operations of method 1200. While the flow chart depicts a series of sequential steps, unless explicitly stated, no inference should be drawn from that sequence regarding specific order of performance, performance of steps or portions thereof serially rather than concurrently or in an overlapping manner, or performance of the steps depicted exclusively without the occurrence of intervening or intermediate steps. The process depicted in the example depicted is implemented by a processor in, for example, an electronic device.
- [126] Referring to the non-limiting example of Figure 13, at operation 1310, a PCAR framework (for example, PCAR framework 220 in Figure 2) or module thereof identifies, a parent object to another object in the camera field of view based on image data received from an externally-oriented camera of an AR apparatus. According to

various embodiments, the PCAR framework recognizes the first object separately from its parent object (for example, the PCAR recognizes a distinctive car wheel and a car), and derives the parent-child relationship from additional information provided in a PCAR database or object descriptor database (for example, data associating a particular kind of wheel with a specific model car). According to some embodiments, the PCAR framework recognizes the first object as a feature of the parent object and based on this recognition, identifies the parent-child relationship between the objects.

- [127] In certain embodiments, the PCAR frame identifies a first object based on a comparison of one or more binary descriptors of image data representing the first object (for example, image data patch 705 in Figure 7) against binary descriptors of features of the first object.
- [128] According to various embodiments, at operation 1320, an item of AR content is displayed at a location in the AR field of view, which has been determined not to obstruct either a view of an object which is an augmentation target (for example, house 502 in Figure 5), or another item of AR content (for example, notification 511 in Figure 5). In certain embodiments, the determination of non-obstructing locations within the AR field of view is based on a mapping of the locations of objects in a camera field of view to an AR field of view (for example, as performed by operation 1220 in Figure 12). According to certain embodiments, the placement of items of AR content within an AR field of view is determined based on an analysis of the image data from the camera field of view, as well as stored contextual information regarding objects in the camera field of view. According to certain embodiments, the stored contextual information regarding objects includes information identifying the location and size of essential features of an object. In this way, items of AR content can be displayed in a way in which essential features of a scene are not occluded by items of AR content. As one non-limiting example, a movie poster which is an augmentation target may comprise the images of the actors, the film's title, and fine print identifying the studio, producers and other stakeholders in the project. The stored contextual information may include rules regarding the placement of AR content regarding the elements of the augmentation target, including, without limitation, proximity requirements for items of AR content associated with elements of the augmentation target. Additionally, the stored contextual information may include rules about feature visibility (for example, rules specifying that covering faces with AR content is impermissible, but covering text is permitted). In this way, certain embodiments according to this disclosure can present AR content associated with augmentation targets in a way that is contextually aware, and uncluttered.
- [129] In some embodiments according to this disclosure, at operation 1325, the position of an item of AR content is displayed on an internally-facing display of an AR apparatus

at a location based on the mapped position of the first object relative to the AR field of view (for example highlighting frame 810b in Figure 8B is displayed at a location based on the mapped position of second refrigerator 815 in the AR field of view).

[130] In the non-limiting example of Figure 13, at operation 1330, the item of AR content associated with the augmentation target to be displayed is selected, at least in part, based on information in a user profile of an AR apparatus (for example, second item of AR content 915b in Figure 9D is, in certain embodiments, selected for display based on information in a user profile identifying a present user of an AR apparatus as a German speaker named "Lar.")

[131] None of the description in this application should be read as implying that any particular element, step, or function is an essential element that must be included in the claim scope. The scope of patented subject matter is defined only by the claims.

Claims

- [Claim 1] A method for providing a personalized augmented reality (AR) display, the method comprising:
obtaining, at an augmented reality apparatus, image data of a camera field of view, the camera field of view comprising a field of view of an externally oriented camera of the augmented reality apparatus;
identifying a first object in the camera field of view based on the image data;
mapping a position of the first object relative to an augmented reality (AR) field of view, the AR field of view comprising a portion of the camera field of view in which augmented reality (AR) content can be displayed on an internally-facing display of the augmented reality apparatus;
determining, based on the identity of the first object, whether the first object comprises an augmentation target; and
responsive to determining that the first object comprises the augmentation target, displaying, on the internally-facing display, an item of AR content associated with the augmentation target in the AR field of view.
- [Claim 2] The method of claim 1, wherein the item of AR content associated with the augmentation target comprises at least one of visual content previously assigned to the augmentation target or a user interface (UI) for assigning AR content to the augmentation target.
- [Claim 3] The method of claim 1, wherein the item of AR content is displayed on the internally-facing display at a location in the AR field of view based on the mapped position of the first object relative to the AR field of view.
- [Claim 4] The method of claim 3, wherein the item of AR content is displayed on the internally-facing display, at a location in the AR field of view determined not to obstruct at least one of the first object or a second item of AR content in the AR field of view.
- [Claim 5] The method of claim 1, further comprising:
identifying, based on the image data, a parent object to the first object in the camera field of view,
wherein the first object comprises at least one of a surface of the parent object or a part of the parent object.
- [Claim 6] The method of claim 1, wherein the first object is identified based on a

comparison of one or more binary descriptors of the image data to an object model.

[Claim 7] The method of claim 1, wherein the item of AR content associated with the augmentation target is selected based on a user profile of a user of the augmented reality apparatus.

[Claim 8] An augmented reality apparatus comprising:
an externally oriented camera covering a camera field of view, the camera field of view comprising a field of view of the externally oriented camera;
an internally-facing display providing an augmented reality (AR) field of view, the AR field of view comprising a portion of the camera field of view in which AR content can be displayed on the internally-facing display of the augmented reality apparatus;
a processor; and
a memory containing instructions, which when executed by the processor, cause the processor to implement a personalized communication augmented reality (PCAR) framework configured to:
obtain image data of the camera field of view,
identify a first object in the camera field of view based on the image data,
map a position of the first object in the camera field of view relative to the AR field of view,
determine, based on the identity of the first object, whether the first object comprises an augmentation target, and
responsive to determining that the first object comprises the augmentation target, display, on the internally-facing display, an item of AR content associated with the augmentation target in the AR field of view.

[Claim 9] The augmented reality apparatus of claim 8, wherein the item of AR content associated with the augmentation target comprises at least one of visual content previously assigned to the augmentation target or a user interface (UI) for assigning AR content to the augmentation target.


[Claim 10] The augmented reality apparatus of claim 8, wherein the PCAR is further configured to display the item of AR content on the internally-facing display at a location in the AR field of view based on the mapped position of the first object relative to the AR field of view.

[Claim 11] The augmented reality apparatus of claim 10, wherein the PCAR is further configured to display the item of AR content on the internally


facing display at a location in the AR field of view determined not to obstruct at least one of the first object or a second item of AR content in the AR field of view.

- [Claim 12] The augmented reality apparatus of claim 8, wherein the PCAR is further conFigured to:
identify, based on the image data, a parent object to the first object in the camera field of view,
wherein the first object comprises at least one of a surface of the parent object or a part of the parent object.
- [Claim 13] The augmented reality apparatus of claim 8, wherein the PCAR is further conFigured to identify the first object based on a comparison of one or more binary descriptors of the image data to an object model.
- [Claim 14] The augmented reality apparatus of claim 8, wherein the item of AR content associated with the augmentation target is selected based on a user profile of a user of the augmented reality apparatus.


[Fig. 1]




[Fig. 2]




[Fig. 3]



[Fig. 4]



[Fig. 5]




[Fig. 6]


600

605 Object Signature	610 User ID	615 Augmentation Data	620 Visibility	625 Object Location	630 Expiration Time
607 1	John	Text, Web Content Item	Martha 619	{GPS Coordinates / Indoor}	Until Read 631
617					627
635 2	Martha	Virtual Object	John, Ted	Any place	6:00 a.m. - 6:00 p.m. 633
609					629
	Ted	Video	Anyone	{GPS Coordinates / Indoor}	Indefinite


[Fig. 7]




[Fig. 8A]




[Fig. 8B]




[Fig. 8C]




[Fig. 8D]




[Fig. 8E]




[Fig. 8F]




[Fig. 9A]




[Fig. 9B]




[Fig. 9C]




[Fig. 9D]




[Fig. 10]




[Fig. 11]



[Fig. 12]



[Fig. 13]



INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR2019/007720**A. CLASSIFICATION OF SUBJECT MATTER****G06T 19/00(2011.01)i, G06T 7/11(2017.01)i, G06T 7/70(2017.01)i, G06F 3/048(2006.01)i, G06T 19/20(2011.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G06T 19/00; G06F 3/0482; G06F 3/14; G06T 11/60; G06T 15/00; G09G 5/00; G06T 7/11; G06T 7/70; G06T 19/20

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords: personalized augmented reality (PCAR), camera field of view, augmented reality (AR), field of view, internally-facing display, augmentation target, parent object, user profile

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2012-0092372 A1 (JUNG HEE RYU et al.) 19 April 2012 See paragraph [0011]; claims 1-2; and figure 2.	1-14
Y	US 2016-0086384 A1 (HERE GLOBAL B.V.) 24 March 2016 See paragraphs [0059]-[0060], [0092]; and figures 3-4.	1-14
Y	US 2018-0088746 A1 (MICROSOFT TECHNOLOGY LICENSING, LLC) 29 March 2018 See paragraph [0129]; and figure 4.	5-6, 12-13
A	US 2012-0001901 A1 (SUN-HYUNG PARK) 05 January 2012 See paragraphs [0010], [0028].	1-14
Y	US 2010-0315418 A1 (WOON TACK WOO) 16 December 2010 See paragraphs [0057], [0059].	1-14



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"D" document cited by the applicant in the international application

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 October 2019 (10.10.2019)

Date of mailing of the international search report

10 October 2019 (10.10.2019)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea



Facsimile No. +82-42-481-8578

Authorized officer

AHN, Jeong Hwan

Telephone No. +82-42-481-8633



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR2019/007720

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2012-0092372 A1	19/04/2012	AU 2011-211601 A1 AU 2011-211601 B2 CN 104221056 A CN 104221056 B EP 2533214 A2 JP 05383930 B2 JP 2013-518337 A KR 10-0985737 B1 US 8947458 B2 WO 2011-096668 A2 WO 2011-096668 A3	23/08/2012 30/01/2014 17/12/2014 22/12/2017 12/12/2012 08/01/2014 20/05/2013 06/10/2010 03/02/2015 11/08/2011 10/11/2011
US 2016-0086384 A1	24/03/2016	EP 2791908 A1 EP 2791908 B1 US 10127734 B2 US 2013-0147837 A1 US 2018-0082485 A1 US 9230367 B2 US 9858723 B2 WO 2013-087352 A1	22/10/2014 21/08/2019 13/11/2018 13/06/2013 22/03/2018 05/01/2016 02/01/2018 20/06/2013
US 2018-0088746 A1	29/03/2018	None	
US 2012-0001901 A1	05/01/2012	CN 102395036 A EP 2402906 A2 EP 2402906 A3 JP 05260705 B2 JP 2012-014690 A KR 10-1295714 B1 KR 10-2012-0002261 A	28/03/2012 04/01/2012 22/04/2015 14/08/2013 19/01/2012 16/08/2013 05/01/2012
US 2010-0315418 A1	16/12/2010	EP 2267595 A2 EP 2267595 A4 KR 10-0963238 B1 KR 10-2009-0087332 A US 8823697 B2 WO 2009-102138 A2 WO 2009-102138 A3	29/12/2010 14/05/2014 10/06/2010 17/08/2009 02/09/2014 20/08/2009 12/11/2009