



US00RE36654E

United States Patent [19] **Conner et al.**

[11] E **Patent Number: Re. 36,654**
[45] **Reissued Date of Patent: *Apr. 11, 2000**

[54] **STACKED LCD COLOR DISPLAY**

[75] Inventors: **Arlie R. Conner; Paul E. Gulick**, both of Tualatin, Oreg.

[73] Assignee: **In Focus Systems, Inc.**, Wilsonville, Oreg.

[*] Notice: This patent is subject to a terminal disclaimer.

[21] Appl. No.: **08/692,300**
[22] Filed: **Aug. 5, 1996**

Related U.S. Patent Documents

Reissue of:

[64] Patent No.: **5,050,965**
Issued: **Sep. 24, 1991**
Appl. No.: **07/445,769**
Filed: **Nov. 22, 1989**

U.S. Applications:

[63] Continuation of application No. 08/125,646, Sep. 21, 1993, abandoned, which is a continuation-in-part of application No. 07/402,134, Sep. 1, 1989, Pat. No. 4,917,465, application No. 07/378,997, Jul. 12, 1989, Pat. No. 4,952,036, application No. 07/363,099, Jun. 7, 1989, Pat. No. 4,966,441, and application No. 07/329,938, Mar. 28, 1989, abandoned.

[51] **Int. Cl.**⁷ **G02F 1/1335; G02F 1/1347**
[52] **U.S. Cl.** **349/6; 349/8; 349/62; 349/80; 349/97; 349/112; 349/117; 349/180; 349/181**
[58] **Field of Search** **349/6, 8, 62, 80, 349/97, 112, 117, 180, 181**

[56] **References Cited**

U.S. PATENT DOCUMENTS

2,586,635	2/1952	Fernseler	359/63
3,703,329	11/1972	Castellano	359/53
3,785,721	1/1974	Harsch	359/64
3,811,751	5/1974	Myer	359/63
3,863,246	1/1975	Treka et al.	359/63

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0098070	11/1984	European Pat. Off.	
259058	9/1988	European Pat. Off.	
0311405	4/1989	European Pat. Off.	350/334
2250458	5/1975	France	
3034181	3/1982	Germany	

(List continued on next page.)

OTHER PUBLICATIONS

"Liquid Crystal Displays Take a New Twist," Electronic Products, Aug. 15, 1990, pp. 58-62 by D. Lieberman.

G.H. Heilmer and L.A. Zanoni, "Guest Host Interactions in Nematic Liquid Crystals, A New Electro-Optic Effect," Aug. 1, 1968, Applied Physics Letter, vol. 13, No. 3, pp. 91, 92.

Donald L. White and Gary N. Taylor, "New Absorptive Mode Reflective Liquid-Crystal Display Device," Nov. 1974, Journal of Appl. Physics, vol. 45, No. 11, pp. 4718-4723.

Kawacki et al., "Light Scattering Characteristics in Nematic-Cholesteric Mixtures with Positive Dielectric Anisotropy," Jul. 1978, Japan Journal of Appl. Physics, pp. 1245-1250.

Uchida et al., "Bright Dichroic Guest-Host LCS's Without a Polarizer," 1981 Proceeding of the SID, vol. 22/1, pp. 41-46.

K. Sato, "Novel Multicolored Liquid Crystal Display Without Color Fitter," 1989 Japan Display, pp. 392-395.

C. Lijimn et al., "640x400 Pixels Multicolor STN-LCD Using Birefringence Effect," 1989 Japan Display, pp. 300-302.


(List continued on next page.)

Primary Examiner—Huy Mai
Attorney, Agent, or Firm—Stoel Rives LLP

[57] **ABSTRACT**

A color display is formed by stacking two or more birefringent elements that are tuned to provide different spectral characteristics, and operating each of the elements independently.

82 Claims, 17 Drawing Sheets



U.S. PATENT DOCUMENTS

3,876,287	4/1975	Sprokel	359/54	4,722,593	2/1988	Shimazaki	359/63
3,915,554	10/1975	Maezawa	359/63	4,723,840	2/1988	Humbert et al.	359/53
4,006,968	2/1977	Ernstoff et al.	359/66	4,726,663	2/1988	Buzak et al.	359/54
4,044,546	8/1977	Koike	359/63	4,736,332	4/1988	Crease	359/65
4,068,926	1/1978	Nakamura et al.	359/64	4,745,406	5/1988	Hayashi et al.	359/62
4,084,213	4/1978	Kirchner et al.	359/64	4,756,604	7/1988	Nakatsuka et al.	359/53
4,097,128	6/1978	Matsumoto et al.	359/53	4,758,818	7/1988	Vatne	359/53
4,097,130	6/1978	Cole, Jr.	359/53	4,759,612	7/1988	Nakatsuka et al.	359/64
4,099,855	7/1978	Wisbey et al.	359/53	4,763,993	8/1988	Vogeley et al.	359/54
4,110,792	8/1978	Long et al.	359/53	4,770,500	9/1988	Kalmanash et al.	359/53
4,116,544	9/1978	Soref	359/63	4,770,525	9/1988	Umeda et al.	359/53
4,127,322	11/1978	Jacobson et al.	359/53	4,773,032	9/1988	Uehara et al.	359/64
4,137,524	1/1979	Chen et al.	359/63	4,786,146	11/1988	Ledebuhr	359/53
4,171,874	10/1979	Bigelow et al.	359/53	4,786,147	11/1988	Clere et al.	359/63
4,232,948	11/1980	Shanks	359/64	4,796,978	1/1989	Tanaka et al.	359/53
4,239,349	12/1980	Scheffer	359/64	4,812,034	3/1989	Mochizuki et al.	359/53
4,241,339	12/1980	Ushivama	359/53	4,813,770	3/1989	Clere et al.	359/63
4,251,137	2/1981	Knop et al.	359/64	4,832,461	5/1989	Yamagichi et al.	359/53
4,257,682	3/1981	Suzuki et al.	359/64	4,838,655	6/1989	Hunahata et al.	359/63
4,258,387	3/1981	Lemelson et al.	359/53	4,838,661	6/1989	McKee et al.	359/63
4,272,162	6/1981	Togashi et al.	359/54	4,839,634	6/1989	More et al.	359/53
4,299,447	11/1981	Soltan et al.	359/63	4,842,374	6/1989	Ledebuhr	359/63
4,317,115	2/1982	Kawakami et al.	359/54	4,842,379	6/1989	Oishi et al.	350/347 G
4,349,817	9/1982	Hoffman et al.	359/63	4,844,569	7/1989	Wada et al.	350/335
4,394,069	7/1983	Kaye	359/53	4,848,877	7/1989	Miller	359/53
4,398,805	8/1983	Cole	359/53	4,850,681	7/1989	Yamanobe et al.	359/64
4,403,216	9/1983	Yokoi	359/53	4,859,037	8/1989	Iwashita et al.	359/53
4,408,839	10/1983	Wiener-Avnear	359/63	4,867,536	9/1989	Pidosoy et al.	359/53
4,411,496	10/1983	Nonomura et al.	359/53	4,874,228	10/1989	Aho et al.	359/53
4,416,514	11/1983	Plummer	359/53	4,877,309	10/1989	Takamatsu	359/53
4,426,133	1/1984	Funada et al.	359/63	4,886,343	12/1989	Johnson	359/94
4,427,741	1/1984	Aizawa et al.	359/53	4,889,412	12/1989	Clere et al.	359/63
4,443,065	4/1984	Funada et al.	359/53	4,909,606	3/1990	Wade et al.	359/63
4,466,702	8/1984	Wiener-Avnear et al.	359/54	4,927,240	5/1990	Stolov et al.	350/335
4,487,480	12/1984	Nonomura et al.	359/63	5,122,887	6/1992	Mathewson	359/53
4,487,481	12/1984	Suzawa	359/63				
4,527,864	7/1985	Dir	359/53				
4,547,043	10/1985	Penz	359/94				
4,548,479	10/1985	Yeh	359/53				
4,549,174	10/1985	Funada et al.	359/63				
4,556,286	12/1985	Uchida et al.	359/64				
4,571,456	2/1986	Paulsen et al.	359/64				
4,579,422	4/1986	Simoni et al.	359/53				
4,580,876	4/1986	Stolov et al.	350/335 X				
4,597,636	7/1986	Hoshikawa	359/53				
4,604,706	8/1986	Fisher, Jr. et al.	359/64				
4,608,558	8/1986	Amstutz et al.	359/99				
4,610,507	9/1986	Kamamori et al.	359/64				
4,613,207	9/1986	Ferguson	359/53				
4,617,562	10/1986	Klotz	359/63				
4,630,894	12/1986	Cremers	359/53				
4,634,229	1/1987	Amstutz et al.	359/99				
4,649,264	3/1987	Carson	359/64				
4,650,286	3/1987	Koda et al.	359/64				
4,651,148	3/1987	Takeda et al.	359/64				
4,652,088	3/1987	Kando et al.	359/54				
4,652,101	3/1987	Grunwald	359/94				
4,653,861	3/1987	Kando et al.	359/54				
4,653,865	3/1987	Kando et al.	359/64				
4,659,182	4/1987	Aizawa	359/63				
4,659,183	4/1987	Suzawa	359/63				
4,664,482	5/1987	Kando et al.	359/63				
4,671,634	6/1987	Kizaki et al.	359/63				
4,680,579	7/1987	Ott	359/53				
4,693,562	9/1987	Hasegawa et al.	359/63				
4,697,884	10/1987	Amatutz et al.	359/53				
4,701,028	10/1987	Clere et al.	359/53				
4,711,313	12/1987	Iida et al.	359/53				
4,715,686	12/1987	Iwashita et al.	359/53				
4,720,804	1/1988	Moore	359/53				
				3501210	7/1986	Germany	
				3721751	12/1989	Germany	
				110296	8/1975	Japan	
				110297	8/1975	Japan	
				53-37051	4/1978	Japan	
				55049	5/1978	Japan	
				59162	5/1979	Japan	
				159415	12/1980	Japan	
				61176531	5/1981	Japan	
				121076	9/1981	Japan	
				140320	11/1981	Japan	
				195624	7/1982	Japan	
				23012	4/1983	Japan	
				224376	12/1983	Japan	
				189317	10/1984	Japan	
				219719	12/1984	Japan	
				60-169827	9/1985	Japan	
				60-189730	9/1985	Japan	
				0194426	10/1985	Japan	350/335
				238815	11/1985	Japan	
				100725	5/1986	Japan	
				61157928	6/1986	Japan	
				125328	6/1987	Japan	
				0153832	7/1987	Japan	350/337
				164024	7/1987	Japan	
				62-257123	11/1987	Japan	
				49736	3/1988	Japan	
				63-49736	3/1988	Japan	
				63-198023	4/1988	Japan	
				144326	6/1988	Japan	
				234225	9/1988	Japan	
				77807	10/1988	Japan	
				264731	11/1988	Japan	
				286819	11/1988	Japan	
				124823	2/1989	Japan	

44417	2/1989	Japan .	
147432	3/1989	Japan .	
0147430	6/1989	Japan	350/337
594185	8/1977	Switzerland .	
1501211	2/1978	United Kingdom .	
1501212	2/1978	United Kingdom .	
2048506	12/1980	United Kingdom .	
2110863	6/1983	United Kingdom .	
213937	2/1984	United Kingdom .	
1390925	1/1985	United Kingdom .	
215704	9/1985	United Kingdom .	

OTHER PUBLICATIONS

- B. Lyot, "Comptes Rendus," 1993, vol. 197, pp. 1592-1595.
- Mitsuo Nagatu and Hiroshi Wada, "Neutralized Supertwisted Nematic LCD: Principle and Characteristics," Nov. 1988, The Transactions of the IEICE, vol. E71, No. 11, pp. 1080-1085.
- Terry J. Scheffer, "New Multicolor Liquid Crystal Displays That Use a Twisted Nematic Electro-Optical Cell," Nov. 1973, J. Appl. Phys., vol. 44, No. 11, pp. 4799-4803.
- Y. Kotani et al., "Effect of Various Parameters on Matrix Display Characteristics of SBE Liquid Crystal Cells," Japan Display 1986, pp. 384-386.
- G. Assouline et al., "Two Color Crystal Liquid Display," Nov. 18, 1971, Electronics Letters, vol. 7, No. 23, pp. 699-700.
- Tatsuo Uchida, "Multicolored Liquid Crystal Display," May/June 1984, Optical Engineering, vol. 23, No. 3, pp. 247-252.
- M.F. Schiekel and K. Fahrenschom, "Deformation of Nematic Liquid Crystals with Vertical Orientation in Electrical Fields," Appl. Phys. Letter vol. 19, No. 10, 1971, pp. 391-393.
- Y. Yamagishi et al., "A Multicolored Nematic Cholesteric Liquid Crystal," 1988 IEEE CH-2678-1/88/0000-0204, pp. 204-207.
- A. Mochizuki, "New Nematic-Cholesteric LCD Using Hysteresis Behavior," 1985, Proceedings of the SID, vol. 26/4, pp. 243-248.
- T.J. Scheffer, "Liquid Crystal Color Displays," pp. 45-78.
- T.J. Scheffer and J. Nehring, "A New Highly Multiplexable Liquid Crystal Display," Nov. 15, 1984, Appl. Phys. Letter 45 (10), pp. 1021-1023.
- T.J. Scheffer and J. Nehring, "Investigation of the Electro-Optical Properties of 270 + Nematic Layer in the Birefringence Mode," Oct. 15, 1985, J. Appl. Phys., pp. 3022-3031, vol. 58, No. 8.
- H. Mada and S. Kobayashi, "Electro-Optical Properties of Twisted Nematic Liquid Crystals: An Application to Voltage Controllable Color Information (*) (**)," Revue de Physique Appliquee, Tome 10, Mai 1975, pp. 147-151.
- J. Roberts, "T.V. Image With Liquid Crystal Display," Oct. 1978, Biennial Display Research Conference, pp. 52-55.
- Y. Takahashi, T. Uchida and M. Wade, "The Effect of Various Parameters of TN-LCD's," Mol. Cryst. Liq. Cryst., 1981, vol. 66, pp. 171-182.
- Scheffer, T.J. "Liquid Color Crystal Displays," (1976), pp. 45-78.
- Matsumoto, Schoichi et al., "A Single-Cell High-Quality Black & White ST LCD," Electron Device Engineering Laboratory Toshiba Corp., pp. 3-7.
- Mochizuki, A., "A Nematic-Cholesteric Bistable Liquid Crystal Display for Projectors," SPIE vol. 760 Large Screen Projection Displays (1987) pp. 74-77.
- Uchida, Tatsuo, "Color LCSs: Technical Developments," Japan Display '83, pp. 202-205.
- K. Kinugawa et al., "640 x400 Pixel LCD Using Highly Twisted Birefringence Effect With Low Pretilt Angle," STD 86, Digest, pp. 122-125.
- Scheffer, T.J. et al., "A New, Highly Multiplexable Liquid Crystal Display," Appl. Phys. Lett. 45 (10), Nov., 1984, pp. 1021-1023.
- Kinugawa, Kiyoshige, et al., "640 x400 Pixel LCD Using Highly Twisted Birefringence Effect," SID 86 Digest, pp. 122-125.
- C.M. Waters et al., "Highly Multiplexable Dyed LCDs," Proceedings of the SID, vol. 25/4, 1984, pp. 261-264.
- P. Palffy-Muhoray, et al., "Orientational Order in Binary Mixtures of Nematic Liquid Crystals," Liquid Crystals and Ordered Fluids, vol. 4, pp. 615-641.
- T. Shimomura et al., "Voltage Controllable Color Formation With a Twisted Nematic Liquid Crystal Cell," Japan J. Appl. Phys., vol. 14 (1975), No. 7, pp. 1093-1094.
- "Light-Activated Liquid Crystal Light Valve for Projection Displays," IBM Technical Disclosure Bulletin, vol. 28, No. 4, Sep. 1985, pp. 1664-1666.
- S. Matsumoto et al., "New Multicolor Liquid-Crystal Display," Toshiba Review, No. 108, Mar./Apr. 1977, pp. 32-35.
- S. Sato et al., "Frequency Color Display by Nematic Liquid Crystals," Japan J. Appl. Phys., vol. 13, (1974), No. 3, pp. 559-560.
- A. Aviram et al., "Multicolor Display," IBM Technical Disclosure Bulletin, vol. 15, No. 8, Jan. 1973, pp. 2538-2539.
- "New Electro-Optical Effect: Optical Activity of Electric-Field-Induced Twisted-Nematic Liquid Crystal," Electronics Letters, Feb. 5, 1976, vol. 12, No. 3, pp. 70-71.
- V.A. Tsvetkov et al., "Picture Logic and Liquid Crystals," Sov. J. Quant. Electron., vol. 4, No. 8, Feb. 1975, pp. 989-993.
- H. Mada et al., "Surface Order Parameter of 4-n-Heptyl-4'-Cyanobiphenyl," Mol. Cryst. Liq. Cryst., 1981, vol. 66, pp. 57-61.
- H. Ibrahim et al., "On the Molecular Polarizability of Nematic Liquid Crystals," Mol. Cryst. Liq. Cryst. 1981, vol. 66, pp. 189-198.
- S. Chandrasekhar et al., "Theory of Birefringence of Nematic Liquid Crystals," Liquid Crystals, pp. 291-315.
- Y. Kotani et al., "Effect of Various Parameters on Matrix Display Characteristics of SBE Liquid Crystal Cells," Japan Display, 1986, pp. 384-386.
- T.J. Scheffer et al., "24 x80 Character LCD Panel Using the Supertwisted Birefringence Effect," SID 85 Digest, pp. 120-123.
- K. Asano et al., "SBE Liquid Crystal Displays with Improved Response Time," Japan Display, 1986, pp. 392-395.
- M. Akatsuka et al., "Electro-Optical Properties of Supertwisted Nematic Display Obtained by Rubbing Technique," Japan Display, 1986, pp. 400-40.
- F. Leenhouts et al., Electro-Optics of Supertwisted Displays: Dependence on Liquid Crystal Material Parameters, Japan Display, 1986, pp. 388-391.
- C.M. Waters et al., "Design of Highly Multiplexed Liquid Crystal Dye Displays," Mol. Cryst. Liq. Cryst., 1985, vol. 123, pp. 303-319.
- M. Schadt et al., "Voltage-Dependent Optical Activity of a Twisted Nematic Liquid Crystal," Applied Phys. Ltrs. vol. 18, No. 4, Feb. 1971, pp. 127-128.

- R.A. Soref et al., "Electrically Controlled Birefringence of Thin Nematic Films," *J. Appl. Phys.*, vol. 43, No. 5, May 1972, pp. 2029–2036.
- I. Haller et al., "Liquid Scattering Spectrum of a Nematic Liquid," *Mol. Cryst. Liq. Cryst.* 1971, vol. 12, pp. 277–287.
- Y. Inagaki et al., "Dependence of the Electrically Controlled Birefringence on Applied Frequency in a Nematic Liquid Crystal," *Mol. Cryst. Liq. Cryst.*, 1981, vol. 67, pp. 69–76.
- B. Cvikič et al., "on Form Birefringence of Some Smectic Liquid Crystals," *Mol. Cryst. Liq. Cryst.*, 1971, vol. 12, pp. 267–276.
- IBM Corp., "Twisted Nematic Liquid Crystal Replacement For Overhead Transparency", IBM Technical Disclosure Bulletin, vol. 29, No. 11, Apr. 1987.
- Kawasaki, Kazuo, "High-Density Performance Black and White Supertwisted Nematic LCD," *SID 87 Digest*, pp. 391–394.
- Yamagishi, Y., et al., "A Multicolor Projection Display Using Nematic-Cholesteric Liquid Crystal," 1988 IEEE pp. 204–207.
- Jones, Mitt, "NEC Breaks New Ground with First Color Portable," *PC Magazine*, Oct. 31, 1989, pp. 33–36.
- Pryce, Dave, "Special Report," *EDN Magazine*, Oct. 12, 1989, pp. 103–114.

FIG. 1 Prior Art





FIG. 2 Prior Art









FIG. 7




FIG. 8




FIG. 9




FIG. 18




FIG. 10





FIG. 11






FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17









FIG. 19A




FIG. 19B




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 28




FIG. 27




FIG. 30




FIG. 29




FIG. 31




FIG. 32






FIG. 33








FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40

STACKED LCD COLOR DISPLAY

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

RELATED APPLICATION DATA

[The present invention] *This application is a continuation of Reissue application No. 08/125,646, filed on Sep. 21, 1993, now abandoned, which is a continuation-in-part of application Ser. Nos. 07/402,134 filed Sept. 1, 1989, now U.S. Pat. No. 4,917,465, 07/378,997 filed July 12, 1989, now U.S. Pat. No. 4,952,036, 07/363,099 filed June 7, 1989, now U.S. Pat. No. 4,966,441, and 07/329,938 filed Mar. 28, 1989, now abandoned. These applications are assigned to the present assignee and are incorporated herein by reference.*

FIELD OF THE INVENTION

The present invention relates to systems for displaying color images, and more particularly relates to such systems wherein the image is formed by passing light through a plurality of birefringent optical elements.

BACKGROUND AND SUMMARY OF THE INVENTION

Much effort has been made in recent years to develop low power color displays. Such efforts have generally employed LCD panels in one of three configurations. In the first configuration, a plurality of differently colored LCD panels are stacked and illuminated with white light. As the light passes through the stacked layers, pixels in each panel act as controllable color filters, selectively coloring the light exiting the display. U.S. Pat. No. 3,703,329 is representative of such systems and shows a stack of three panels, variously dyed to individually produce the colors yellow, cyan and magenta. Together the panels cooperate, using subtractive color, to produce all eight primary colors. A related system is shown in U.S. Pat. No. 4,416,514. In this system, differently dyed polarizers (yellow, magenta and cyan) are interposed in a series of twisted nematic cells. By varying the voltage applied to each cell, the twist angle of the liquid crystal molecules changes, imparting a variable rotation to the light exiting the cell. The colored polarizers cooperate with this controllably twisted light to select desired colors.

While such stacked cell systems can provide a full color display, they typically have certain drawbacks. One is parallax, inherent in any stacked optical system. Another is poor brightness, due to absorption of light by the dye in dyed cell systems, and due to blockage of cross polarized light by polarizers in systems that rely on polarization rotation to differentiate colors.

The second approach uses only a single LCD panel, but uses it in conjunction with a mosaic color filter. The mosaic filter typically has a plurality of red, green and blue filter elements, each aligned with a pixel in the LCD panel. By controlling the transmissivity of pixels in the LCD panel, the display can pass light through selected areas of the color mosaic filter.

While the color mosaic technique addresses certain shortcomings of the stacked panel approach, it introduces certain problems of its own. One is that brightness is limited because less than a third of the active pixel area transmits light for any given color.

Another shortcoming of the color mosaic approach is that pixel density must be increased by a factor of three to obtain the same resolution as the stacked cell approach. That is, to provide a color display with a horizontal resolution of 640 colored pixels, for example, the LCD panels must have 1920 pixels, 640 for each of the red, green and blue filter elements. This introduces fabrication problems that decrease yields and increase panel costs. Further, the finite width of the gap between pixels must remain, even though the pitch has decreased, so the actual pixel "aperture ratio" can be decreased dramatically. (Some small format thin film transistor (TFT) displays have a total open aperture area of only 45% of the total display surface due to row and column lines and transistor area, etc.)

The third approach is birefringence color. In such systems, the birefringent operating mode of certain material is exploited to produce color, as opposed to reliance on colored dyes in guest-host type cells or reliance on rotation of light through known twist angles in twisted nematic cells.

Birefringent color systems typically take two forms: those relying on passive birefringent layers to impart a birefringent effect to a liquid crystal cell (as shown in U.S. Pat. No. 4,232,948), and those in which the liquid crystal material itself exhibits a birefringent effect (sometimes called "electrically controlled birefringence" or "tunable birefringence"). In the latter instance, the degree of birefringence is a function of the voltage applied to the liquid crystal material. By switching the applied voltage to different values, different colors can be produced. Color displays relying on this principle are shown in U.S. Pat. Nos. 3,785,721, 3,915,554 and 4,044,546.

During recent years, so called "supertwisted" or "highly twisted" nematic cells have become popular in many applications. Such cells are described, inter alia, in U.S. Pat. Nos. 4,697,884 and 4,634,229, and in Scheffer et al, "A New, Highly Multiplexable Liquid Crystal Display," Appl. Phys. Lett. 45 (1), Nov. 15, 1984, pp. 1021-1023, and Kinugawa et al, "640x400 Pixel LCD Using Highly Twisted Birefringence Effect With Low Tilt Angle," 1986 SID Digest, pp. 122-125. The '884 and '229 patents are incorporated herein by reference.

Supertwisted nematic (STN) cells generally function in a birefringent mode. However, unlike earlier birefringent cells, STN cells exhibit a bistable behavior wherein they switch rapidly from a deselect state to a select state and back again as the excitation (RMS) voltage crosses a switching threshold. The select and deselect voltage regions can be made quite close to one another, such as 1.20 volts and 1.28 volts, permitting the cells to be multiplexed at high rates. FIG. 1 shows the transmission of a representative STN cell (with a particular polarizer orientation) as a function of applied voltage, illustrating the steepness of the switching function. Note that this curve shows the overall photopic "brightness" and does not reveal any coloration of the liquid crystal in the select and deselect states.

It is the multiplexibility of STN cells that makes them particularly desirable. This multiplexibility is achieved without active elements (i.e. drive transistors on each pixel, etc.) and without exotic alignment and liquid crystal operating modes (i.e. ferroelectric, phase-change, hysteresis, etc.). Thus, STN provides an inexpensive direct-multiplexed display type requiring only M+N drivers to operate a display comprised of MxN pixels.

There is an inverse-squared relationship between the number of display lines to be "addressed" and the difference between display "on" and "off" driving voltages (RMS

average). As the number of display lines increases, the difference in driving voltage must decrease. To illustrate, a multiplex rate of 100:1 can be achieved with approximately a 10% difference in driving voltages, and a MUX rate of 240:1 can be achieved with approximately a 6% difference in driving voltages. Theoretically, arbitrarily high MUX rates can be achieved if the driving voltage difference is made small enough.

The main drawback to STN is the optical operating mode—birefringence. That is, the only way to distinguish pixels driven by the “on” voltage from those driven by the “off” voltage is the difference in birefringence between the two pixels. (As noted, for high information content displays, the difference in driving voltages is minute and decreases rapidly with an increase in the number of display lines that must be driven.) To distinguish the difference in pixel birefringence, polarizers are used—one to polarize the entering light to a known polarization, and one to select only one polarization of exiting light for examination. Depending on the state of the pixels, the light oriented to pass through the exit polarizer will be one of two colors. For best contrast, the polarizers are usually arranged so that these two colors are yellow and blue. (Actually, only one color can be selected by orientation of the polarizers—and this color can only be selected from a relatively small spectrum of colors. There is very little design freedom in varying the color in the second state—it is essentially a function of the first color.)

FIG. 2 shows the transmission characteristics of a representative yellow/blue mode STN cell (with associated polarizers) when the cell is in its select and deselect states. As can be seen, when the cell is “selected” (by applying an excitation voltage of 1.56 volts), the transmission spectrum has a maximum at 400 nanometers, a minimum at 600 nanometers, and an intermediate value at 500 nanometers. When the cell is “deselected” (by reducing the excitation voltage to 1.41 volts), the transmission spectrum includes a null at 400 nanometers, a maximum at 500 nanometers, and an intermediate value at 600 nanometers. Light exiting the cell/polarizer combination in the select state is thus principally blue, and light exiting in the deselect state is green plus yellow plus red, which appears as yellow to the human observer.

Unlike TN cells and cells operating in other modes, a birefringent STN cell cannot be operated in a black/white mode. The reason is that black requires all wavelengths of light to be linearly cross-polarized with the exit polarizer to effect complete light blockage, and true white requires all wavelengths of light to be linearly polarized parallel with the exit polarizer to effect complete light passage. The birefringent operating mode, by definition, prevents such results since different wavelengths of light are polarized differently during passage through the material. Thus, STN cells are unavoidably colored. However, this drawback has been tolerated in order to achieve the high multiplexibility that STN provides.

In order to eliminate the birefringence color, some manufacturers have incorporated various compensation layers in display assemblies. One such compensation layer is a second birefringent cell of opposite twist than the first to counteract the wavelength dependence in the cell’s behavior. Another type of compensation layer, sometimes used in conjunction with the above-mentioned blue/yellow mode STN LCDs, is a polarizer that has been dyed to pass cross-polarized light in the blue and red portions of the spectrum in order to make the yellow state of the LCD “whiter.” This still yields a blue/white LCD, instead of the desired black/white. However, this color limitation is usually accepted in order to achieve the high multiplex ratio.

While the birefringence of STN cells unavoidably produces colors, the colors so produced are generally considered too limited in range and too inferior in quality to be suitable for use in color displays. Far preferred are the rich colors that can be achieved with guest-host cells, or TN cells with dyed filters.

In accordance with the present invention, a color display system is formed by operating a plurality of birefringent cells in cooperation with one or more colored polarizers, thereby complementing and correcting the birefringence colors and yielding a brighter display.

In a preferred embodiment, a plurality of STN birefringent panels are tuned to different subtractive primary colors (i.e. yellow, cyan and magenta) and stacked. Interposed between the panels, and sandwiched about the stack, are polarizers, at least one of which is colored. In some embodiments, this assembly is illuminated by a collimated light source and the resulting image is focused onto a projection screen for viewing. In other embodiments, optics are provided to permit direct wide angle viewing of the display without parallax effects.

The foregoing and additional features and advantages of the present invention will be more readily apparent from the following detailed description, which proceeds with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the transmission characteristics of a representative STN cell as a function of applied voltage.

FIG. 2 shows the transmission spectrum of a representative STN cell when operated in its select state (with an excitation voltage of 1.56 volts) and in its deselect state (with an excitation voltage of 1.41 volts).

FIG. 3 is a schematic diagram of a display subassembly according to one embodiment of the present invention.

FIGS. 4–6 are spectral photometer plots showing ideal light transmission characteristics for three liquid crystal panels used in the display subassembly of FIG. 3 when in their selected and deselected states.

FIGS. 7–9 are spectral photometer plots showing the actual light transmission characteristics of three Kyocera liquid crystal panels used in the display subassembly of FIG. 3 when in their selected and deselected states.

FIG. 10 is a chromaticity diagram illustrating the performance of the Kyocera panels when in their selected and deselected states.

FIG. 11 is a diagram showing the eight basic colors achieved by operating yellow, cyan and magenta panels in their various combinations.

FIG. 12 details the construction of a display assembly incorporating three panels according to the present invention.

FIG. 13 shows a first projection system according to the present invention.

FIG. 14 is a perspective view of an integrated assembly including a display assembly and associated optics to facilitate use with an overhead projector.

FIG. 15 shows a second projection system according to the present invention.

FIG. 16 shows a self contained color display using a display subassembly according to the present invention with associated projection optics.

FIG. 17 shows a first direct view display system according to the present invention.

5

FIG. 18 shows the spectral distribution of a backlight that may be used with the display system of FIG. 17.

FIG. 19 shows a second direct view display system according to the present invention.

FIG. 20 shows a third direct view display system according to the present invention.

FIGS. 21 and 22 show a fourth direct view display system according to the present invention.

FIG. 23 shows a portable computer employing a direct view display according to the present invention.

FIG. 24 shows a laptop computer employing a direct view display according to the present invention.

FIG. 25 is a view of a portable computer including a direct view display according to one embodiment of the present invention.

FIG. 26 is a perspective view of the portable computer of FIG. 25.

FIG. 27 is a view of a portable computer including a direct view display according to another embodiment of the present invention.

FIG. 28 is a perspective view of the portable computer of FIG. 27.

FIG. 29 is a view of a portable computer including a direct view display according to yet another embodiment of the present invention.

FIG. 30 is a perspective view of the portable computer of FIG. 29.

FIG. 31 shows a display stand that permits a display subassembly to be backlit for direct viewing.

FIG. 32 shows a display system employing two light sources and two optical paths according to the present invention.

FIG. 33 shows a display system employing one light source and two optical paths according to the present invention.

FIG. 34 shows a computer with a roll-up screen according to the present invention.

FIG. 35 shows a display subassembly using a thin film transistor (TFT) LCD panel in conjunction with an STN panel.

FIG. 36 shows a display subassembly using a TFT panel, an STN panel, and a color shutter.

FIG. 37 shows a display subassembly using two panels.

FIG. 38 illustrates a possible color gamut produced by one of the panels of FIG. 37.

FIG. 39 illustrates the gamut of FIG. 38 after being analyzed with a blue polarizer.

FIG. 40 illustrates the spectral characteristics of two possible polarizers used in the display subassembly of FIG. 37.

DETAILED DESCRIPTION

To provide an enabling disclosure without unduly lengthening this specification, applicants incorporate by reference the disclosures of U.S. Pat. Nos. 4,549,174, 4,652,101, 4,709,990, 4,763,993 and 4,832,461 which teach certain concepts useful in the construction of a device according to the present invention.

Before proceeding, it may be helpful to first review certain principles of color optics. The primary light colors are generally considered to be red, green and blue. White light is composed of all three primaries. White light with red filtered therefrom (i.e. removed) is termed cyan; white light

6

with green filtered therefrom is termed magenta; and white light with blue filtered therefrom is termed yellow. These latter colors, cyan, magenta and yellow, are sometimes termed subtractive primary colors, since they denote the absence of one of the primary colors.

Filters selectively attenuate (or "absorb") light of certain colors and pass light of other colors relatively unattenuated. A red filter, for example, attenuates blue and green light and lets red light pass. Similarly, a blue filter attenuates red and green light and lets blue light pass. Finally, a green filter attenuates red and blue light and lets green light pass. Filters of the primary colors thus subtract two primary colors and let the third pass.

Filters of the subtractive primary colors subtract one primary color and let the two others pass. For example, a cyan filter attenuates red light and lets blue and green light pass. Similarly, a magenta filter attenuates green light and lets blue and red light pass. Finally, a yellow filter attenuates blue light and lets green and red light pass.

These properties are summarized in Table I.

TABLE I

Filter	Absorbs	Passes
Red	Green, Blue	Red
Green	Red, Blue	Green
Blue	Red, Green	Blue
Yellow	Blue	Green, Red
Cyan	Red	Blue, Green
Magenta	Green	Blue, Red

Again, although somewhat counter-intuitive, it should be remembered that a blue filter does not absorb blue light. It passes blue light and blocks light of other colors.

It should further be noted that the human eye is more sensitive to certain wavelengths of light than to others. The eye's normal daytime response (termed "photopic" response) typically peaks at about 554 nanometers and diminishes to near negligible values around 400 and 700 nanometers.

For convenience of discussion, the optical spectrum is generally segregated into the red, green and blue portions by dividing lines at 500 and 600 nanometers. (For physiological reasons, a precise dividing line cannot be defined.) Using these boundaries, the human eye perceives 55% of the energy in white light from the green portion of the spectrum (500 to 600 nm.), 30% from the red portion (above 600 nm.), and only 15% from the blue portion (below 500 nm.). Perfect green, red and blue filters thus transmit 55%, 30% and 15% of white light, respectively (photopically). Since yellow, cyan and magenta are combinations of these colors, it can be seen that perfect yellow, cyan and magenta filters transmit 85%, 70% and 45% of white light, respectively.

The LCD panels used in the illustrated embodiments are supertwisted nematic LCD panels that are controllably colored by exploitation of the birefringence effect. As mentioned in the Background discussion, birefringence is an optical phenomenon in which light oriented along one axis of the material propagates at a different speed than light oriented along another axis. This asymmetry results in different wavelengths of light having different polarizations when they exit the material. Polarizers can be used to analyze the elliptically polarized light exiting the panel to select colors. Prior art uses of birefringence to control color in LCD panels are discussed in U.S. Pat. Nos. 3,876,287, 4,097,128, 4,127,322, 4,394,069, 4,759,612 and 4,786,146, the disclosures of which are incorporated by reference.

Display Subassembly

Turning now to FIG. 3, there is shown a basic display subassembly 10 according to one embodiment of the present invention. The illustrated subassembly includes four LCD panels 12, 14, 16, 18 sandwiched alternately between five polarizers 20, 22, 24, 26 and 28. An optional retardation film layer 30 is also shown.

In the illustrated subassembly 10, the birefringent properties of the panels 12–18 are “tuned” (by choosing the thickness (d) of the liquid crystal layer and its optical refractive index anisotropy (Δn)) to yield a desired coloration. For example, the birefringent properties of the first panel 12 are tuned so that incoming green light (which has been polarized by the entrance polarizer 20) propagates through the liquid crystal material in such a manner that the orientation of its principal axis upon leaving the cell is orthogonal to the exiting polarizer 22 when the panel 12 is in its deselected (i.e. deenergized) state. The panel 12 and polarizers 20 and 22 thus act as a magenta filter when the panel is deselected. The tuning of panel 12, and the orientations of the associated polarizers, are also selected so that, when the panel is in its selected (i.e. energized) state, green light is passed, together with red and blue light, to yield a substantially “white” color. (For expository convenience, panel 12 is sometimes called the “magenta” panel and is said to controllably absorb green light. It will be recognized, however, that this and the other panels must be operated in conjunction with associated front and back polarizers to achieve the desired coloring effect.)

The illustrated second panel 14 is similarly tuned to operate as a yellow filter (i.e. absorbing blue) when in its deselected state and to pass all wavelengths of light (i.e. white light) when in its selected state. It is sometimes termed the “yellow” panel. The illustrated fourth panel 18 is similarly tuned to operate as a cyan filter.

The illustrated third panel 16 is an optional “black” panel that may be included to increase contrast. Its construction may take any of a number of forms, as discussed below.

As mentioned earlier, it is the thickness (d) of the liquid crystal layer and its optical refractive index anisotropy (Δn) that principally determine each panel’s spectral response for a given twist angle ψ . While the panel’s response is determined by a complex formula, the response can be roughly approximated as dependent on the ratio $\Delta n d / \psi$. In the illustrated embodiment, these ratios have the values shown in Table II:

TABLE II

Panel	$\Delta n d / \psi$	ψ
Magenta	0.19	4.19 (rad.)
Yellow	0.23	3.84
Cyan	0.25	4.19

It will be recognized that the $\Delta n d / \psi$ ratios referenced in Table II can be achieved with any number of cell thicknesses. The choice of cell thickness is a tradeoff between several factors, including the panel’s response time and uniformity. The response time of the panel generally increases with the panel thickness. Consequently, to achieve a fast response time, it is desirable to use a thin panel. However, as the cell thickness decreases, small fabrication errors, such as a 1μ change in cell thickness over the width of a panel, yields a relatively large variation in panel color behavior and switching threshold voltage. To insure color uniformity, it is desirable to use a thick panel so fabrication

errors are kept to a small percentage of the total liquid crystal thickness. As a compromise between these considerations, a cell thickness of 6 to 12μ may be used.

Spectral photometer plots showing the light transmission qualities of ideal panels 12, 14 and 18 (again, considered in conjunction with their associated polarizers) are provided in FIGS. 4, 5 and 6, respectively. Panels suitable for use as panels 12, 14 and 18 are available from Kyocera of Hayato, Japan as part numbers KC-6448ASTP-SC-M, KC-6448ASTP-SC-Y and KC-6448ASTP-SC-C, respectively, or may be fabricated using known techniques. Spectral photometer plots showing the actual behavior of the Kyocera panels are provided in FIGS. 7–9. The plot for the magenta panel in FIG. 7 was made with a red entrance polarizer. The plot for the cyan panel in FIG. 9 was made with a blue exit polarizer. (As can be seen from these curves, neither the passage of light of the desired color nor the attenuation of light of undesired colors is perfect, but the resulting effect is more than adequate to provide saturated colors throughout the human visual area.) A chromaticity diagram illustrating performance of the Kyocera panels in their selected and deselected states is provided in FIG. 10.

Each of panels 12–18 comprises a plurality of pixels that can be individually energized to change the spectral distribution of the light that is permitted to pass therethrough. By selecting corresponding pixels in the three colored panels, light of any color can be transmitted through the display subassembly 10. To transmit a pixel of green light, for example, a pixel in the yellow panel 14 is deselected to absorb blue light and the correspondingly positioned pixel in the cyan panel 18 is deselected to absorb red light. By superimposing the spectral transmission curves of these two pixels, it will be recognized that the remaining, transmitted light has a peak in the region of the spectrum the eye perceives as green. (The magenta panel 12 is left selected (i.e. white transmitting) in this example and thus has no relevant filtering effect.)

The color blue can be similarly achieved by deselecting corresponding pixels in the cyan and magenta panels, and red can be achieved by deselecting corresponding pixels in the yellow and magenta panels. If it is desired to absorb all light and thus produce a black pixel on the image plane, pixels in all three panels are deselected. FIG. 11 shows the eight basic colors achieved by operating a yellow/cyan/magenta series of panels in their various combinations.

Polarizers are needed to analyze the light passing through the liquid crystal panels in order to achieve perceptible contrast. In prior art systems, the polarizers are typically neutral (i.e., dyed black by iodine). In the present invention, colored polarizers (which are “leaky”) can be used in certain positions to pass more light, improving the brightness and allowing color balance improvements.

The first panel 12 is illustrated as being “magenta.” Light entering it is polarized by the first polarizer 20. Normally, all colors of light orthogonal to the axis of polarizer 20 would be absorbed by the black dye of a conventional, neutral polarizer, resulting in an immediate loss of 50% (theoretical) of the light. (In actual practice, the loss of a neutral polarizer is about 55–58%.) This loss can be cut dramatically if the first polarizer is dyed magenta. Such a polarizer still passes the white light parallel to the polarizer’s axis, but additionally passes blue and red light orthogonal to its axis. This additional blue and red light is permitted to pass further into the display subassembly and ultimately contributes to the overall brightness of the resulting display, instead of being absorbed by the first polarizer as is normally the case. The

losses normally associated with this first polarizer are thus cut by about two thirds. Display brightness improves commensurately.

(In an alternative embodiment, the entrance polarizer **20** may be dyed red. While theoretically not as advantageous as a magenta polarizer, a red polarizer is easier to realize and still offers a substantial improvement in brightness, passing about 59% of the incident light, as opposed to 45% or less for a neutral polarizer.)

The same benefit can be achieved at the exiting end of the sandwiched display subassembly **10**. The last panel **18** in the subassembly is illustrated as being cyan. By dyeing the polarizer **28** adjacent thereto cyan, the blue and green light that would normally be absorbed thereby is allowed to leak through and pass out of the display subassembly, again improving display brightness.

(Again, the exit polarizer **28** may be dyed blue instead of cyan. A blue polarizer passes about 56% of the incident light, still yielding a significant improvement in brightness over a neutral polarizer.)

Conventional neutral polarizers can be used at the positions (**22**, **24**, **26**) intermediate the liquid crystal panels and a significant improvement in display brightness is still achieved by virtue of the two colored polarizers described above. The use of neutral intermediate polarizers also assures that there is no birefringence interaction between panels (i.e. the deselected or selected nature of the Δn of the center panel makes no difference to the passage of light and total birefringence of the adjacent panels).

In other embodiments, the polarizers at the intermediate positions in the subassembly may be colored. Care must be taken, however, not to interfere with the color-selective properties of the birefringent panels. For example, if a yellow colored polarizer is interposed between the magenta and yellow panels **12**, **14**, it will interfere with the color-selective properties of the magenta panel. As noted, the magenta panel itself does not absorb the undesired green light. Instead, its birefringence is tuned so that light propagating through the panel exits with the axis of its principal green component oriented orthogonally to the polarizer **22**, causing it to be blocked. If this polarizer **22** is colored yellow, it will leak green and red light, including the green light that is meant to be blocked. Consequently, use of a yellow polarizer between the magenta and yellow panels defeats the careful tuning of the first panel's birefringence.

An equally poor color choice for the first intermediate polarizer **22** is magenta. A magenta polarizer would permit blue and red light to enter the yellow panel **14** at an unexpected orientation. The yellow panel was tuned so that blue light entering at a known polarization would propagate and exit with a principal polarization that would be blocked by the exiting polarizer **24**. If the blue light enters the yellow panel **14** at an unexpected orientation, it will exit at an unexpected orientation and will not be blocked by the exiting polarizer. Consequently, use of a magenta colored polarizer **22** defeats the careful tuning of the yellow panel's birefringence.

Polarizer **22** should be colored, if at all, a color that both of the adjoining panels are intended to pass. In this case, since the magenta panel is intended to pass blue and red, and the yellow panel **14** is intended to pass green and red, the polarizer **22** should be colored the common color: red.

If the black panel **16** is omitted (together with associated retardation film **30** and polarizer **26**), similar logic would dictate that the polarizer **24** between the remaining yellow and cyan panels should be colored, if anything, green.

In embodiments including a black/white panel, such as panel **16** in FIG. **3**, the polarizers positioned adjacent thereto should be neutral (i.e. not colored) since any polarizer coloring would permit the black panel to leak light—an undesired effect.

To optimize display brightness, the dyed polarizers should exhibit a high degree of transmissivity to cross-polarized light in their "leaky" portion of the spectrum. In the illustrated embodiment, the polarizers each comprise a dyed 5 mil sheet of stretched polyvinyl alcohol. Table III specifies suitable dichroic dyes, which are available under various brand names from Crompton & Knowles, Atlantic, Ciba-Geigy and a variety of other dye suppliers.

TABLE III

POLARIZER	DYE
Magenta	Direct Red #81
Yellow	Direct Yellow #18
Cyan	Direct Blue #1

The foregoing discussion has described only one of many possible sequences of polarizers and panels. Others can be devised. For example, while the first polarizer **20** in the above example has been described as being magenta in order to achieve an improvement in brightness, an alternative embodiment with the same sequence of LCDs can here use a blue or red polarizer instead. A blue or red polarizer still provides some improvement in brightness since it leaks light that would be absorbed by a black polarizer. Of course, a black polarizer can also be used if desired. The basic LCD sequence itself can also be varied with corresponding changes in the associated polarizers. The basic sequences are set forth in Table IV:

TABLE IV

POL1	LCD1	POL2	LCD2	POL3	LCD3	POL4
Y/G/R/K	Y	G/K	C	B/K	M	M/R/B/K
M/R/B/K	M	R/K	Y	G/K	C	C/G/B/K
Y/G/R/K	Y	R/K	M	B/K	C	C/G/B/K

where Y is yellow, K is black, G is green, C is cyan, B is blue, M is magenta and R is red.

FIG. **12** illustrates in greater detail a display subassembly using just the magenta, yellow and cyan panels. The polarizers are magenta, black, black and cyan, respectively. Included in FIG. **12** are details of the relative alignment of the component panels and polarizers in an implementation using the Kyocera panels. The alignment angles are typically specified by the manufacturer and depend, inter alia, on the rubbing angles of the front and rear panel plates, the twist of the LCD molecules, and on various boundary layer phenomena associated with the liquid crystal material.

As noted, such a three panel subassembly can produce the color "black" (the absence of light) by deselection of each panel. Since the light passing through the subassembly is progressively stripped of its green, blue and red components, theoretically no light exits the subassembly. As a practical matter, however, the imperfect responses of the three panels permit some light of various colors to leak through at an attenuated level. The net result is a dark brown or grey color. While such an arrangement yields a contrast ratio of approximately 10:1—more than adequate for many applications—some applications require contrast ratios on the order of 100:1. To achieve such ratios, a fourth panel, such as the "black" panel **16** illustrated in FIG. **3**, may be

included in the subassembly. The characteristics of the black panel may be optimized for the intended application.

In one application, namely digital computer graphics using the RGBI standard, an "intensity" signal is used to differentiate each of the eight basic colors used in RGB systems into two colors, yielding a total of 16 colors. In such application, the black cell is optimized for maximum transmission when in the selected state. The contrast provided by the cell is of lesser importance. That is, a contrast range of 2:1; or even 1.5:1, will suffice to distinguish the 16 colors of the RGBI system.

In contrast, "full color" systems (i.e. television or high quality color computer graphics) require high contrast. To achieve the 256 or more colors that such systems require, an overall contrast ratio of 100:1 may be needed. Since the basic magenta/yellow/cyan (M/Y/C) subassembly delivers only a 10:1 contrast ratio, the black panel must provide a 10:1 ratio on its own. Thus, it must be optimized for blackest black. By cascading the two systems (M/Y/C and black), the contrast figures are multiplied, producing 100:1 overall white to black contrast, and allowing excellent grey shading and range of color. Of course, highly saturated primary colors still require M/Y/C contrast, but the black panel provides greater depth in the shadows and details in the highlights.

In the illustrated embodiment, the black panel 16 is a supertwisted nematic cell operated in conjunction with a retardation film 30 that tunes the cell for maximum contrast. In other embodiments, a double supertwisted nematic cell or even a twisted nematic cell may be used.

In actual practice, the "black" cell need not be black. A birefringent cell tuned to the blue end of the spectrum, for example, may be used since the human eye is relatively insensitive to blue light, yielding a relatively high photopic contrast ratio.

One advantage of the display subassembly of the present invention is the flexibility it affords in possible panel/polarizer sequences. If one sequence seems unworkable, a design can be optimized about another one. For example, if it is found that a good quality magenta polarizer cannot be obtained, then a design that does not require a magenta polarizer can be adopted.

It will be recognized that a display subassembly 10 according to the present invention can be used in a variety of applications, such as color projection systems and in direct view displays. A variety of such applications are detailed below.

Projection Systems

In a first projection system embodiment 32 of the invention, shown in FIG. 13, a display subassembly 10 is positioned on the transparent projection surface 34 of a conventional overhead projector 36. Such projectors typically include an illumination bulb 38 and a Fresnel lens 40 under the projection surface to produce light beams that pass through a transparency and converge onto a projection lens assembly 42. (Due to the short focal length and high power required of lens 40, it is often formed by cementing two or more lower powered Fresnel lenses together.)

When display subassembly 10 is used in such an embodiment, it is desirable to provide a Fresnel lens 44 to collimate the converging light from the projection surface 34 prior to illumination of the display subassembly. The light exiting the subassembly is then focused by a lens 46 (which is also desirably in Fresnel form) onto the projection lens assembly 42. (Lens 46 here serves the same purpose as the Fresnel lens 40 provided under the projection surface of the

projector in the projector's normal operation, namely to focus light towards the projection lens assembly 42.) An integrated assembly 47 including both the display subassembly 10 and the Fresnel lenses 44, 46 is shown in FIG. 14.

In a second projection system embodiment 48 of the invention, a portion of which is shown in FIG. 15, the collimating and focusing Fresnel lenses 44, 46 used in the FIG. 13 embodiment are omitted. Instead, the panels comprising the display subassembly are fabricated with different pixel spacings. The spacings on the various panels are selected so that corresponding pixels in the various panels are aligned with the converging light exiting the projection surface of the projector. By this arrangement, no accessory optics are required. Parallax effects are avoided since the internal optics of the display subassembly are designed to cooperate with the focused light used by the projector.

Projection technology may also be used to provide a self contained display in which an image is projected onto the rear of a viewing screen. A color monitor for a computer may be realized in this fashion. One such arrangement 50 is shown in FIG. 16. In this embodiment, a field lens 52 is used to collimate the light from bulb 54 prior to its passage through the display subassembly 10. The resulting image is projected by a second lens 56 onto a translucent medium 58 which can then be viewed from the opposite side by a user.

Direct View Systems

A display subassembly 10 according to the present invention can also be incorporated into a number of direct view display systems, such as color graphics displays for portable or laptop computers.

In direct view displays, it is usually desirable to backlight the display with substantially collimated light. On the viewing side of the display, it is desirable to provide exit optics that permit a wide viewing angle without parallax effects.

In a first direct view embodiment 60, shown in FIG. 17, the display subassembly 10 is backlit from a diffuse light source, such as a fluorescent light panel 62. In such embodiment, entrance and exit optic elements 64, 66 generally collimate the diffuse light prior to entrance into the display subassembly and scatter the approximately-collimated light exiting the display. Each of optic elements 64, 66 may comprise a plate having formed thereon a plurality of microlenses 68, one aligned to each pixel. Light incident on one of the microlenses on element 64 is directed substantially normal to the plane of the subassembly and thus passes through the pixels of the component panels in the proper alignment, regardless of its initial orientation. Collimated light exiting the subassembly 10 is dispersed by the microlenses on the exit optic element 66, thereby permitting the color image to be viewed from a wide range of angles without parallax effects. The interstitial areas 69 between the lenses on exit optic 66 may be colored black to minimize stray light and to improve perceived contrast.

In other versions of the FIG. 17 embodiment 60, the arrays of microlenses can be replaced by arrays of fiber optic collimator faceplates or lenticular lenses.

FIG. 18 shows the spectral distribution of a representative fluorescent backlight 62 that may be employed in the embodiment of FIG. 17. As is characteristic of fluorescent lighting, the spectrum has characteristic peaks corresponding to certain chemical components used in the light. These peaks (and the nulls) can be tailored to specific applications by changing the chemistry of the lamp.

In a second direct view embodiment 70, shown in FIG. 19, the backlit illumination can be collimated by a novel

arrangement employing a parabolic mirror **72** (desirably in Fresnel form). In this embodiment, a pair of linear light sources, such as fluorescent bulbs **74**, illuminate a generally flat mirrored surface **76** that has facets arranged to provide one axis of collimation. The angles of the facets vary with placement on the surface to simulate a sectioned parabolic reflector. Light reflected from this mirrored surface is substantially collimated. However, to remove any stray off-axis light, a microvenetian blind material **78**, such as Light Control Film marketed by 3M Corp, is desirably placed between the mirror and the display subassembly. This material is a thin plastic film containing closely spaced black microlouvers to absorb light misaligned with respect to the louvers. Substantial collimation of the illuminating light is thus achieved.

In the FIG. **19** embodiment **70**, a translucent light dispersing material **80**, such as a ground glass plate or a commercially available diffusion material (i.e. Rolux film manufactured by Rosco of Port Chester N.Y.) is mounted adjacent the exit side of the display subassembly **10** to display the resulting color image.

FIG. **20** shows a third direct view embodiment **82** of the invention. In this system, the display subassembly **10** is illuminated by a tungsten-halogen lamp **84** that operates in conjunction with a curved reflector **86**. The reflector is computer designed (using well known optical modeling programs or ray tracing techniques) to provide equal energy illumination to all regions of the display subassembly. A corrector plate **88**, mounted adjacent the display subassembly, provides a normalization of illumination angle, i.e. perpendicular to the assembly.

The lamp **84** in the FIG. **20** embodiment is desirably part of a removable module that also includes a shield **90** for preventing direct illumination of the display subassembly by the lamp. Again, a diffuser material **92** is mounted adjacent the exit side of the display subassembly to permit direct, wide angle viewing.

A fourth direct view embodiment **94** of the invention is shown in FIGS. **21** and **22** and includes fiber optic back-lighting of the display subassembly. In the illustrated system, a tungsten-halogen lamp **96** is again used, but this time is optically coupled to a bundle of optical fibers **98**. Each fiber terminates at a microlens **100** on a plate **102** of such microlenses. These microlenses can be arrayed in a rectangular pattern on the plate **102**, or can be arranged in a hexagonal pattern for higher density. In either event, the microlenses are matched to the dispersion patterns of the fiber so that light exiting the fibers is substantially collimated by the lenses. Again, a diffuser optic **104** is desirably positioned adjacent the exit side of the display subassembly.

In the FIG. **21, 22** embodiment, it is desirable that tolerance be provided for non-uniformities, and maximum use be made of all light, including paraxial rays. Fortunately, with the intimately contacting diffuser **104** on the top surface of the display subassembly, there is a reasonable "blur" tolerance. Some stray light can even be beneficial to "initialias" the jagged square pixels.

The above-described direct view displays may each be advantageously incorporated into a portable or laptop computer. "Portables" are generally considered to be computers that are sized for ready portability, but still require use of 120 volts AC from a wall outlet. They often take a suitcase-like form. "Laptops," on the other hand, generally rely on an internal rechargeable battery and often take a "clamshell" form.

FIG. **23** shows a portable computer **106** including a direct view display **108** according to the present invention. To

operate the computer, the case **112** is opened and the display is positioned for viewing. (In some portables, the display is coupled to the computer by a coiled cable and can be positioned where desired.) When the computer is no longer needed, the display is packed into the case, secure against abuse.

FIG. **24** shows a laptop computer **114** including a direct view display **108** according to the present invention. As can be seen, the display is coupled to the remainder of the computer by a hinge arrangement **115**. The laptop's internal rechargeable battery **105** powers both the computer and the display.

Again, to operate the computer **114**, the hinged display **108** is lifted, exposing it for viewing. When the computer is no longer needed, the hinged display is secured in its collapsed position, protecting it from abuse.

FIGS. **25-30** illustrate a variety of other portable computer designs that are adapted for use with a display subassembly according to the present invention. In FIGS. **25** and **26**, a computer **200** includes a display subassembly **10** mounted by a hinge **202** to the front top edge of a computer case **204**. When in use, the display subassembly **10** is illuminated by light reflected off a mirrored surface **206** from a lamp **208**. The lamp **208** is a point source (i.e. it has a relatively small physical extent, such as a small filament) and is fixedly attached to the body of the computer case **204**. The diverging light from this point source is collimated by a flat lens (not particularly shown in the figures) mounted adjacent the display subassembly.

To fold for storage, the display subassembly **10** on computer **200** pivots rearwardly into the body of the computer case, and the panel **210** to which the mirrored surface is attached folds down over the display, protecting it from abuse. The computer keyboard **212** slides into a recess **214** in the front portion of the computer case and a door **216** closes to secure the keyboard in place.

FIGS. **27** and **28** show a portable computer **218** in which the display subassembly **10** is illuminated by light reflected from a mirror **220** that slides out the back of the computer case **222**. Again, the illumination is provided by a point source, such as a tungsten-halogen bulb **224** that is mounted to the computer case **222** rather than to display subassembly itself.

In operation, the display subassembly is positioned in a substantially vertical orientation on a hinge **226** at the rear top portion of the case. To collapse for storage, the display subassembly folds forwardly and latches in place over the keyboard **228**. The mirror **220** is slid towards the case and locks with the mirrored surface adjacent the case's back side. (In another embodiment, the mirrored surface is small enough to be positioned entirely within the computer case. In still another embodiment, the illustrated mirror is hinged at point **230**, permitting it to be folded flat and slid entirely within the computer case.)

Again, a flat correction lens is desirably mounted on the rear of the display subassembly to collimate the light reflected from the mirror **220**.

FIGS. **29** and **30** show a portable computer **232** in which the display subassembly is directly illuminated from a point source **234**, without an intervening mirror. In this embodiment, the display subassembly **10** is again attached by a hinge **236**, this one in a cavity **240** in the front portion of the computer case **238**. In use, the display subassembly **10** is positioned substantially vertically and is illuminated by the point source **234**. To fold for storage, the display subassembly **10** folds rearwardly into the cavity and is held

secure by the keyboard **242**, which is inverted and latched into place to serve as a top cover.

FIG. **34** shows yet another computer **250** according to the present invention. In computer **250**, a point light source **252** is disposed within a case **254** and illuminates a display subassembly **256**, which fills an aperture formed in the case. An image formed by projection of light through this display subassembly is projected on a screen **258** positioned at the back of the computer case **254**. In the illustrated embodiment, the projection screen is flexible and is rolled for storage about a spring-loaded roller **260** disposed at the bottom rear portion of the computer case. To erect the screen for viewing, a screen support **262** is pivoted upwardly from its collapsed storage position to an upright position at the back of the computer. The unrolled screen can then be fastened to the screen support by one or more clips, or like means (not shown).

It will be recognized that in all of the foregoing embodiments, the pixel pitches on the various panels may be made different (as shown in FIG. **15**) to align the pixels with the orientation of the incoming light. By such a construction, it is not necessary to collimate or otherwise process the light prior to illumination of the stacked subassembly. (It will further be recognized that the invention can be practiced by simply illuminating a stack of uniformly pitched panels with uncollimated **55** light, although parallax effects may cause improper pixel registration, blur and false color edges.)

FIG. **31** shows a final embodiment **116** illustrating use of a display subassembly **10** according to the present invention in a direct view display. In this embodiment, the display subassembly is removably positioned on an illumination stand **118** for direct viewing. The illumination stand **118** has a light-transmitting surface **120** against which the display subassembly can rest, and an internal light source **122** for directing illumination therethrough. A small shelf **124** on which the display can be positioned is provided on the exterior of the stand.

The stand **118** is desirably collapsible to permit ready portability. This can be achieved with a hinge and bellows arrangement **126**. Small size can be maintained by using folded optics that include mirroring on the inside back wall **128** of the stand.

The stand may be provided with optics that emulate the optics of a conventional overhead projector. That is, these optics may focus light incident on the display **10** so that it converges on a point a short distance away. In the illustrated embodiment, these optics may comprise a Fresnel plate lens **130**. In such case, the Fresnel entrance optic **44** used in the FIG. **13** projection system embodiment may be used to collimate the focused light prior to its illumination of the display subassembly.

In this embodiment, the exit optic **132** is again a simple translucent dispersion medium to permit wide angle viewing of the collimated image.

It will be recognized that the viewing stand **118** advantageously permits an LCD display to be used either as a projection device for large audiences (i.e. as an "electronic transparency"), or as a single-user computer screen.

Systems with Split Optic Paths

While the foregoing discussions have been directed to display subassemblies comprised of single stacks of panels, additional advantageous results can sometimes be achieved by splitting the stack into two or more sub-stacks and illuminating each separately. One such arrangement is shown in FIG. **32**.

In the FIG. **32** arrangement **134**, the stacked panels are split into two sub-stacks to permit illumination by two different light sources. The first light source **136** is a tungsten-halogen incandescent lamp, which produces a spectrum that is strong in red, especially when the lamp's operating voltage is decreased, which may be desired to increase the lamp's life. The second light source **138** is a mercury arc-lamp, which produces a spectrum rich in deep blue light (430 nm), with a large amount of energy also in the mid-green (540 nm) portion of the spectrum. The complementary spectrums produced by these two light sources are advantageously combined in the embodiment of FIG. **32** to achieve good brightness, long lamp life and high color temperature "white."

As shown in FIG. **32**, light from the tungsten-halogen lamp **136** follows a first optical path that includes a holographic or dichroic mirror **139**. (This mirror may be designed to pass all of the spectrum except a narrow notch [20 or 30 nm] at 540 nm.) This filtered light continues on to illuminate a stacked assembly **140** that includes red- and green-controlling panels (i.e. "cyan" and "magenta"). (For clarity of presentation, the polarizers, collimator, and other optical elements used in this stack and elsewhere in the FIG. **32** embodiment are not illustrated. Following the logic discussed above, the entrance polarizer on the magenta panel may be red, the exit polarizer on the cyan panel may be green, and the intermediate polarizer may be neutral.) The light exiting the stacked assembly **140** is reflected off mirrors **142** and **144** and is directed to exit optics for projection or direct viewing. The tungsten-halogen light **136** thus provides illumination at the red and green portions of the spectrum, and the stacked assembly **140** controls these colors.

Light from the second, mercury arc-lamp **138** follows a second optical path towards a dichroic mirror **146**, which reflects green light up to mirror **139** (for additional illumination of the red/green control stack **140**) and passes blue light into a blue controlling (i.e. "yellow") LCD **148**. The light exiting this blue LCD continues to and through the mirror **144**, joining with the red and green light and continuing to the exit optics. A full color image is thus produced.

(It will be recognized that splitting the light in this fashion provides some design freedom, viz., that the red- and green-controlling panels can be tuned without regard to their blue performance [since they encounter no blue light] and the blue-controlling panel can be similarly tuned without regard to its red and green performance.)

If increased contrast is desired, a black/white panel may be included in either the first or second optical paths. Alternatively, an additional magenta (i.e. green controlling) cell may be included in the stack **140** since green is the dominant contributor to photopic brightness.

While the FIG. **32** embodiment provides different optical paths for different portions of the optical spectrum, in other embodiments the different optical paths can be dedicated to different polarizations of light. Such split-by-polarization systems offer improved brightness since the cross-polarized light that is filtered from single path systems is instead directed to a second path where it is utilized.

FIG. **33** shows a system **150** similar to that of FIG. **32**, except the FIG. **33** system uses a single light source **152**. Blue light from this light source is stripped off by a dichroic mirror **154**, reflected off a mirror **156**, collimated by a collimator **158**, and directed into a blue controlling LCD assembly **160**. Light exiting this LCD assembly is focused by a lens **162** through a blue-passing mirror **164** and into a lens **166** for projection onto a viewing screen.

The red/green light from lamp **152** passes through mirror **154**, is collimated by a collimator **168**, and illuminates a stack **170** that includes cyan and magenta panels (which control red and green light, respectively). The light exiting the stack **170** is again focused by a lens **172**, reflected off the mirror **164** and directed into the projection lens **166**.

Alternative Embodiments

While the foregoing description has focused on a single class of embodiments that incorporate supertwisted nematic panels, it will be recognized that a variety of other embodiments can be constructed using different display elements. Exemplary is the display **300** shown in FIG. **35**. In this display, a thin film transistor (TFT) liquid crystal panel **302** is operated in conjunction with an optical element **304** that exhibits an electrically controllable birefringent (ECB) effect. Thin films transistors are known in the art and disclosed, inter alia, in U.S. Pat. Nos. 4,821,092, 4,819,038, 4,816,885, 4,776,673, 4,743,099, 4,743,098, 4,723,838, 4,715,930, 4,654,117, 4,649,383, 4,636,038, 4,621,260, 4,599,246, 4,591,848, 4,581,619, 4,461,071, 4,386,352, 4,385,292, 4,299,447 and 3,824,003, the disclosures of which are incorporated herein by reference.

In the illustrated embodiment, a limited birefringence mode liquid crystal effect may be given to the TFT panel by adding a retardation film to the (90°) TN of a standard TFT-LCD and by selecting the polarization orientation appropriately.

In the preferred embodiment, the TFT is optimized for whitest white (instead of blackest black). The TFT is also tuned to broaden the dip in the spectral transmissivity curve and place it at the appropriate wavelength required by the stacked combination of panels. In some such embodiments, a double dip in this curve may be obtained by use of a retardation film. By providing several layers of retardation film, ideal "notch filter" performance may more nearly be achieved.

The ECB element may be a supertwisted nematic panel detailed earlier, or may comprise a conventional twisted nematic cell, or a great variety of other elements, such as electro-optic or electro-acoustic crystals. (STN cells have generally not been used in a classical electrically controlled birefringence mode due to the very restricted range of operating voltages dictated by multiplexability requirements. Rather, they have been operated in a bistable mode, operating in either the select or non-select states, not in between. The present invention exploits the voltage-dependent birefringence exhibited by STN cells within the narrow R.M.S. operating range between V_{select} and $V_{non-select}$ to achieve a broad range of intermediate birefringent colors.)

The TFT panel **302** and ECB panel **304** are sandwiched between three polarizers **306**, **308** and **310**. The subtractive coloration provided by each pixel in the ECB display element **304** is a function of the signal driving that pixel. The range of colors produced by this variable birefringence is augmented by one or more additional colors attainable by use of the TFT panel **302** to produce a full color display.

A related embodiment is shown in FIG. **36**. In this figure, a display subassembly **320** comprises a white/yellow mode STN (or DSTN) panel **322**, a thin film transistor panel **324** and a color shutter assembly **326** in stacked arrangement with associated polarizers. Color shutter assemblies are known in the art and are described, inter alia, in U.S. Pat. Nos. 4,758,818, 4,726,663, 4,652,087, 4,635,051, 4,611,889 and 4,582,396, the disclosures of which are incorporated herein by reference.

In the illustrated display subassembly **320**, the color shutter is operated in alternate frames to block red and green light, respectively (thus giving the appearance of cyan and magenta). The TFT provides a very fast switching speed. The STN cell **322** is relatively slower than the TFT, but the blue light it controls is relatively less perceptible to the human eye, so the slower response speed is of little significance.

The FIG. **36** embodiment is intended to lower the costs associated with making a high-information content full color LCD based display system. This embodiment requires only one (monochrome) TFT panel, as opposed to three that may otherwise be used to control red, green and blue.

The STN **322** may be grey-scaled, using a single bit plane of RAM, to 8 or 16 levels. It can provide sufficiently fast response time for moving images.

The TFT **324** is operated at twice the normal frame rate (i.e. greater than or equal to 120 Hz) and, along with the color shutter **326**, controls the red and green image fields sequentially. Both the color shutter and the TFT (with their associated polarizers) are tuned to leak blue all the time, thereby improving the color balance, especially when a tungsten-halogen lamp is used.

In still another embodiment of the present invention, two LCD panels may be stacked and operated independently to produce a full gamut of colors. A display assembly **330** according to this construction is shown in FIG. **37**. For expository convenience, the panels will be referenced as STN panels **332**, **334**, although again, a variety of other technologies can be used.

STN panels **332** and **334** are fabricated with a higher value of $\Delta n d$ than those STN panels illustrated earlier. An exemplary panel may have a 240 degree twist angle, with a $\Delta n d$ value of 1.4. The larger $\Delta n d$ value produces a wider variation in the voltage variable coloration effect. When a high information content, multiplex-addressed LCD panel is grey-scaled (either by PWM or multiple frame averaging), intermediate voltages (between V_{select} and $V_{non-select}$) can be attained on each pixel, despite the nearly-bistable switching behavior that characterizes STN cells.

Between neutral polarizers, the first panel **332** can obtain, for example, the color gamut shown in FIG. **38**. By using a blue (ideal characteristic, pure blue leakage only) polarizer, the gamut is as illustrated in FIG. **39**, instead.

As can be seen, the color gamut with the blue polarizer is shifted towards the blue, with the result that "yellow" cannot be obtained, but "white" is obtained instead. The "blue" may not be as pure as desired ideally, but human-factors experts suggest that a desaturated blue is better for communicating visual information.

If the first polarizer **336** is dyed blue, producing the color gamut shown in FIG. **39**, the second panel **334** needs only to be able to make yellow and white to make the full gamut of saturated primary and secondary colors. To be safe and insure a true black state, the leakages of the first and third polarizers **336**, **338** must not overlap, so rather than choose a yellow polarizer for polarizer **338**, it is somewhat preferable to choose an orange polarizer instead (FIG. **40**). Of course, by tuning the $\Delta n d$ of the LCD and, optionally, adding additional layers of birefringent material (such as retardation films), various birefringence colors can be made within each layer. A desirable display according to this embodiment has the following characteristics:

- 1) good white and black states (overall contrast $\geq 10:1$);
- 2) good color saturation (especially redness of red); and

3) extra good blue light transmission to counteract tungsten illuminant (to raise the color temperature, i.e. color correction).

By using various commercially available color polarizers, the display subassembly can be optimized for various purposes and with different performances for different needs.

Other possibly complimentary pairs of colors for polarizers **336** and **338** are cyan and red, green and red, green and violet, green and magenta, and perhaps green and blue.

The magenta formed by electrically controlled birefringence is generally poor, because the red edge is too soft and must be supplemented. Thus, a red polarizer is desirable, which provides excellent sharpness (i.e. steepness of edge between yellowish-green and red). The gamut of the first LCD **332** may thus be, inter alia, one of the following:

- a) red/magenta/white;
- b) red/yellow/white; or
- c) magenta/yellow/white.

In these cases, the second panel **334** should subtract red, at least, so cyan is its chief color and it may attain one of the following:

- d) cyan/magenta/white;
- e) green/cyan/white;
- f) cyan/green/yellow/white; or
- g) blue/cyan/white.

Preferred combinations include a+f, b+g or c+d, above. (a+e requires alternating red and green to make yellow; b+c is undesirable because it requires alternating red plus blue pixels to make magenta and cannot make blue; a+d cannot make green, b+d cannot make blue, etc.)

While the display subassembly **330** has been described as operating in a color subtractive mode, it will be recognized that the display may also be operated in an additive mode, either with adjacent pixels being operated together to add spatially, or with a single pixel in the stacked assembly being operated with alternate colors to add temporally.

If both liquid crystal panels **332**, **334** are tuned to produce four distinct shades of color, they can be operated co-jointly to product sixteen colors without the need for grey scaling.

Of the foregoing combinations, the presently preferred is to tune panel **332** to produce a color gamut extending from magenta, through yellow to white, and dye polarizer **336** red. Panel **334** can be tuned to produce a color gamut extending from cyan, through green and yellow to white, and polarizer **338** can be dyed green. Again, partial compensation can be used to optimize the various colors produced.

Concluding Remarks

It will be recognized that the use of colored polarizers with birefringent cells provides a great deal of design freedom. The reason is that a colored polarizer renders the response of a cell at certain wavelengths irrelevant. Taking as an example a magenta (green blocking) cell, the cell must normally be optimized for a number of factors: high transmissivity of blue light in both the select and deselect states, low transmissivity of green light in the select state but high transmissivity of green light in the deselect state, and high transmissivity of red light in both states. Such optimization typically requires a compromise of all factors. When used in conjunction with a magenta polarizer, however, the cell's transmissivity at blue and red becomes only a minor concern. The magenta-dyed polarizer causes the cell to pass blue and red regardless of the characteristics of the cell. With the importance of these factors minimized, the design of the

cell can focus on just one factor—high contrast between the select and deselect states for green—and no compromises need be made.

In optimizing the response of the cells, it is sometimes desirable to use additional optical components. For example, in order to tune the range of birefringence effects it is sometimes desirable to include retardation films adjacent the cells.

A birefringent cell, operated in conjunction with a neutral polarizer, exhibits a sinusoidal transmissivity versus wavelength curve, as was shown in FIG. 2. Taking again the example of a magenta (green blocking) cell, the cell's Δn is selected so the minimum of its sinusoidal curve falls somewhere in the green portion of the spectrum. This minimum, however, may be relatively narrow, permitting relatively large amounts of higher and lower wavelength green light to pass through the cell/polarizer combination. To broaden this "notch" in the transmissivity curve, a retardation film may be employed. While retardation films are generally used to tune the cell's characteristics (i.e. to move the dip in the curve up or down in wavelength), the film's action in reversing part of the cell's twist also serves to broaden the dip somewhat. Thus, the transmissivity curve of the magenta cell in its deselect state may be made to more nearly approximate the ideal (i.e. a rectangular notch that encompasses all of green—500 to 600 nm.).

While the display subassembly has been described as including single supertwisted liquid crystal panels, other types of birefringent optics, such as double supertwisted panels or single panels embodying other technologies (such as electro-optic [i.e. lithium tantalum niobate], acoustic-optic, or PET cells) can alternatively be used. A higher resolution display can be achieved by stacking two or more cells for each color, with the active lines on one cell overlapping active lines on the other, similar to the basic technique shown in U.S. Pat. No. 4,448,490, the disclosure of which is incorporated by reference. Faster switching times can be achieved by stacking several thin panels for each color, as disclosed in U.S. Pat. No. 4,547,043, the disclosure of which is incorporated by reference. The basic principles of the invention are also applicable to other display technologies, such as interference color systems.

In other embodiments, certain birefringent panels may be stacked without intervening polarizers. For example, two panels (with or without different Δn) may be stacked without an intermediate polarizer to produce white, yellow, green and cyan in the four combinations of select states. A green polarizer can be used on the outside layer, since green is common to all these colors. Such an embodiment is especially valuable for a white, magenta, cyan and blue combination, since overhead projection needs more blue throughput, which may be obtained by use of a "pure blue" polarizer.

In still other embodiments, if any of the LCD birefringence colors are not ideal, some attenuation of specific light wavelengths might enhance the color gamut and overall contrast. For example, two polarizers might be used together, or a weak color filter compensator (i.e. a conventional gelatin filter) might be added.

It will be recognized that known grey scaling techniques can readily be applied to the present invention to provide the full gamut of possible colors. In one such embodiment, grey scaling is applied to each of the three colored cells. In another embodiment, grey scaling is applied simply to a fourth (typically black) cell included in the stack. U.S. Pat. Nos. 4,840,462, 4,840,460, 4,818,078, 4,766,430, 4,743,

096, 4,709,995, 4,560,982, 4,508,427, 4,427,978 and 4,043, 640 teach various grey scaling techniques and are incorporated herein by reference.

It will further be recognized that the invention can be practiced with more or less panels than the three or four illustrated. For example, it is advantageous to provide laboratory instruments, such as oscilloscopes and analyzers, with displays formed by stacking two supertwisted birefringent panels with one or more colored polarizers. The display may take virtually any of the forms discussed above and still be suitable for inclusion in the instrument. While color gamut is compromised somewhat by such a two panel stack, brightness is increased and cost is reduced.

Finally, it will be recognized that many advantageous results can be achieved by conjointly operating several TFT panels, either in stacked or split-optic arrangement, rather than including a single TFT panel in a stack with other panels, as particularly discussed above. Some such embodiments, including certain of the split optic path embodiments, do not rely on exploitation of the birefringence effect. A number of such embodiments may be realized by substituting TFT panels for the STN panels in the illustrated embodiments. (In such embodiments, the neutral polarizers typically provided on a TFT panel by the manufacturer may be removed, any spectral deficiencies of the panel may be compensated for by retardation film [i.e. commercially available panels are particularly deficient in the blue portion of the spectrum, which deficiency can be alleviated by retardation film], and colored polarizers may be added to achieve the benefits discussed earlier.)

In view of the wide variety of embodiments to which the principles of our invention may be applied, it should be recognized that the illustrated embodiments are to be considered illustrative only and not as limiting the scope of the invention. Instead, we claim as our invention all such modifications as may come within the scope and spirit of the following claims and equivalents thereto.

We claim:

1. A method of producing a color display comprising: providing first and second optical assemblies, each assembly including a plurality of independently operable pixels, each of said pixels exhibiting a birefringent effect that varies in response to a signal applied thereto; stacking said assemblies with a pixel in the first assembly linearly aligned with a corresponding pixel in the second assembly; interposing a first polarizer between the assemblies and sandwiching the stack between a second and a third polarizer wherein said second and third polarizers are colored complementary colors; and applying a first dynamic signal to the pixels in the first assembly and applying a second dynamic signal to the pixels in the second assembly so as to selectively change the birefringent effect.
2. The method of claim 1 which includes providing a supertwisted nematic liquid crystal panel in each of said first and second optical assemblies.
3. The method of claim 1 which further includes enhancing display brightness by interposing a polarizer dyed a color other than black between the assemblies.
4. The method of claim 1 further comprising: applying said first dynamic signal to said pixels in the first assembly wherein said first dynamic signal changes selectively and periodically between more than two values so that said second dynamic signal differs from said first signal thereby producing more than two distinct birefringent effects.

5. The method of claim 1 wherein each assembly has a value of Δnd greater than $0.05 \mu m$ and is individually tuned to produce a different plurality of colors in cooperation with additional layers of birefringent material and said polarizers to produce a wider voltage variable coloration effect.

6. A display subassembly comprising:

first, second and third supertwisted nematic birefringent liquid crystal display panels;

first, second, third and fourth polarizers;

the first panel being positioned between the first and second polarizers, the second panel being positioned between the second and third polarizers and the third panel being positioned between the third and fourth polarizers;

the birefringence of the first, second and third panels, together with the polarizers adjacent thereto, cooperating to pass light of first, second and third colors, respectively, when the panels are in first states, and to pass substantially all colors of light when the panels are in second states;

each of said panels having a plurality of independently electronically operable pixels, said panels being stacked so that corresponding pixels in each of said panels are aligned; and

at least said first or said fourth polarizers is a color other than black so as to increase display brightness.

7. The display subassembly of claim 6 wherein said second polarizer colored a color common to said first and second colors of light passed by said first and second panels in the first state.

8. The display subassembly of claim 6 wherein said third polarizer is colored a color common to said second and third colors of light passed by said second and third panels in the first state.

9. The display subassembly of claim 6 in which the first, second and third colors are each subtractive primary colors.

10. A color display that can be operated to yield at least the colors black, white, red, green, blue, cyan, yellow and magenta comprising: an entrance and exit polarizer, each polarizer dyed a color other than black and at least a first and second birefringent subassembly disposed between said polarizers in a stacked relationship, each of said subassemblies defining a plurality of pixels, each of said pixels being independently operable to birefringently control passage of a portion of a spectrum of light passing therethrough, and wherein at least two of said subassemblies each includes a supertwisted nematic panel.

11. The display of claim 10 wherein said supertwisted nematic panels have substantially equal values of Δnd and a third neutral polarizer disposed between said first and second subassemblies.

12. The display of claim 11 in which the first and second subassemblies are stacked without an intervening polarizer.

13. The display of claim 11 in which the first and second subassemblies are stacked with an intervening polarizer therebetween.

14. The display of claim 13 in which the intervening polarizer is dyed a color other than black.

15. The display of claim 10 in which a supertwisted nematic panel in a first of the subassemblies has a different value of Δnd than a supertwisted panel in a second of the subassemblies.

16. The display of claim 15 in which the first and second subassemblies are stacked without an intervening polarizer.

17. The display of claim 15 in which the first and second subassemblies are stacked with an intervening polarizer therebetween.

23

18. The display of claim 17 in which said intervening polarizer is dyed a color other than black.

19. The display of claim 10 further comprising a third subassembly wherein, at least two of said three subassemblies include supertwisted nematic panels each with a substantially equal value of Δn_d .

20. The display of claim 10 further comprising a third subassembly wherein, each of said subassemblies includes a supertwisted nematic panel and each of said panels has a substantially equal value of Δn_d .

21. The display of claim 20 in which at least two of said subassemblies comprise a birefringent LCD panel and at least a passive compensation layer.

22. The display of claim 21 further comprising means for grey scaling said display to yield more than eight colors.

23. The display of claim 10 in which at least one of the subassemblies includes a passive compensation layer.

24. The display of claim 10 further comprising means for grey scaling said display to yield more than eight colors.

25. A color display method comprising the steps:

providing first and second display subassemblies, each of said assemblies including a supertwisted nematic birefringent panel, each of said panels defining a plurality of independently operable pixels, at least one of said display subassemblies additionally including a passive compensation layer to tune the color response thereof;

stacking said subassemblies with a first polarizer therebetween, said first polarizer being dyed a color other than a color intended to be blocked by said first subassembly;

sandwiching the stacked subassemblies between second and third polarizers;

operating pixels in each of the panels independently to birefringently control passage of a portion of a spectrum of light passing therethrough in cooperation with said first, second and third polarizers, wherein at least the eight colors black, white, red, green, blue, cyan, yellow and magenta may thereby be displayed; and

controllably grey scaling at least one of the supertwisted nematic panels to yield colors in addition to the aforesaid eight colors.

26. The method of claim 23 in which:

the providing step includes providing a third display subassembly, said third subassembly including a supertwisted nematic birefringent panel and a fourth polarizer;

the stacking step includes stacking said third subassembly with the first and second subassemblies whereby said third display subassembly is disposed between said third and fourth polarizers;

the operating step including operating pixels in the third panel to birefringently control passage of a portion of a spectrum of light passing therethrough in cooperation with said third and fourth polarizers; and

the grey scaling step including grey scaling each of the three supertwisted nematic panels.

27. The method of claim 26 in which the providing step includes providing first, second and third display subassemblies, each of said subassemblies including supertwisted nematic birefringent panels with the same values of Δn_d , and at least two of said subassemblies each including a passive compensation layer.

28. An accessory for use with a conventional overhead projector to project electronically generated color images therefrom, the projector having a bulb, a projection lens, and a projection surface having a Fresnel lens thereunder, the

24

Fresnel lens focusing light from the bulb into the projection lens, the accessory being adapted to rest on the projection surface and comprising:

first lens means for receiving converging white light from the projection surface of the projector and collimating said light;

second lens means for receiving collimated light and focusing said light into the projection lens;

a display subassembly positioned between the first and second lens means and illuminated by the collimated light, said subassembly including first, second, third and fourth polarizers and further including first, second and third transmissive liquid crystal birefringent display panels, the birefringence of said panels being tuned, respectively, to first, second and third subtractive complementary colors, each of said panels having a plurality of electronically operable pixels, said panels being stacked so that corresponding pixels in each of said panels are aligned with the direction of the collimated light, the first panel being positioned between the first and second polarizers, the second panel being positioned between the second and third polarizers and the third panel being positioned between the third and fourth polarizers.

29. The accessory of claim 28 in which the first polarizer is colored the first color.

30. The accessory of claim 29 in which the fourth polarizer is colored the third color.

31. The accessory of claim 28 in which the second polarizer is colored a color other than the first or second color or black.

32. The accessory of claim 28 in which:

the first polarizer is colored the first color;

the fourth polarizer is colored the third color;

the second polarizer is colored a color passed by both the first and second panels; and

the third polarizer is colored a color passed by both the second and third panels.

33. The accessory of claim 28 in which:

one of the panels is yellow;

one of the panels is cyan;

one of the panels is magenta;

the colors of the first and fourth polarizers are selected from the list: yellow, cyan, magenta and black; and

the colors of the second and third polarizers are selected from the list: red, green, blue and black;

wherein each of the polarizers is colored differently.

34. A method of projecting a colored image, comprising the steps:

providing first, second and third birefringent liquid crystal panels that include a plurality of independently selectable pixels, said panels being tuned to selectively pass first, second and third subtractive color primaries, respectively, when a signal is applied to each panel;

stacking said first, second and third panels so that corresponding pixels in each of said panels are aligned along an axis orthogonal thereto, said stacked panels forming a subassembly;

providing a first polarizer between the first and second panels;

providing a second polarizer between the second and third panels; and

sandwiching said subassembly and said first and second polarizers between a third polarizer, colored the first

subtractive primary color, and a fourth polarizer, colored the third subtractive primary color;

passing light through the subassembly in a direction parallel to the axis of alignment and selectively-controlling spectral portions of said light when a signal is applied to pixels on at least one of said panels;

focusing the light exiting the subassembly parallel to the axis of alignment into a projection lens; and

projecting the light exiting the projection lens onto a display screen.

35. The method of claim 34 which further includes the step of collimating the light parallel to the axis of alignment of the panels prior to passage into the subassembly.

36. A color display comprising:

first and second optics;

first, second and third display subassemblies disposed between said optics;

each of said display subassemblies including a liquid crystal panel defining a plurality of independently operable pixels wherein at least two of said three liquid crystal panels control color through use of a birefringence effect and wherein at least two of said display subassemblies have different values of Δn ;

first, second, third and fourth polarizers, at least one of said four polarizers dyed a color other than black;

said first display subassembly disposed between the first and second polarizers;

said second display subassembly disposed between the second and third polarizers; and

said third display subassembly disposed between the third and fourth polarizers.

37. The color display of claim 36 in which the liquid crystal panels each comprises supertwisted nematic liquid crystal panels.

38. The color display of claim 36 in which at least one of the display subassemblies includes:

a birefringent liquid crystal panel;

a first passive layer that minimizes the birefringent effect exhibited by the birefringent liquid crystal panel; and

a second passive layer that introduces a birefringent effect.

39. The color display of claim 36 in which at least one of said four polarizers is colored a color other than black.

40. The color display of claim 36 in which one of said display subassemblies operates, in conjunction with the polarizers adjacent thereto, to pass all colors of light in a first state and to pass all colors of light except blue in a second state.

41. The color display of claim 36 in which:

at least one of said four polarizers is colored a color other than black;

one of said display subassemblies operates, in conjunction with the polarizers adjacent thereto, to pass all colors of light in a first state and to pass all colors of light except blue in a second state.

42. The color display system of claim 41 in which said first optic comprises a Fresnel lens adapted to collimate converging light introduced thereto, and the second optic comprises a Fresnel lens adapted to cause said collimated light exiting therefrom to substantially converge.

43. A color display according to claim 42 that is operable to produce at least the colors black, white, red, green, blue, cyan, yellow and magenta.

44. The color display of claim 36 in which the first optic includes a mirror, and the second optic includes a translucent

screen having a back surface on which an image can be displayed and a front surface from which the image can be viewed, said screen being disposed about a spring loaded roller from which it can be unrolled for use and rolled for storage.

45. A method of producing a color display comprising the steps:

collimating illuminating light;

linearly polarizing said collimated light with a first polarizer;

passing said collimated polarized light through a first display subassembly that includes a liquid crystal panel with a plurality of independently operable pixels;

said passing step including elliptically polarizing the linearly polarized light so that different wavelengths of light are rotated to different angular orientations;

analyzing light exiting the first display subassembly with a second polarizer to attenuate therefrom wavelengths of light cross polarized relative to the second polarizer, said analyzing step thereby yielding linearly re-polarized light from which certain wavelengths have been attenuated;

passing said linearly re-polarized light through a second display subassembly that includes a liquid crystal panel with a plurality of independently operable pixels;

said second passing step including elliptically polarizing the linearly re-polarized light so that different wavelengths of light are rotated to different angular orientations;

analyzing light exiting the second display subassembly with a third polarizer to attenuate therefrom wavelengths of light cross polarized relative to the third polarizer, this analyzing step thereby yielding linearly polarized light from which additional wavelengths have been attenuated; and

converging the linearly polarized light from the third polarizer,

wherein:

the elliptical polarization effected during the first passing step differs from elliptical polarization effected during the second passing step due to different values of Δn exhibited by the first and second display subassemblies; and

at least one of said first, second or third polarizers is dyed a color other than black;

and the method further includes:

applying a first dynamic signal to a pixel in the first liquid crystal panel; and

applying a second dynamic signal different from the first dynamic signal to a pixel in the second liquid crystal panel.

46. The method of claim 45 which further includes independently varying the first and second dynamic signals among more than two values.

47. The method of claim 45 in which the passing steps each further includes passing light through a supertwisted nematic liquid crystal panel.

48. The method of claim 45 in which at least one of the passing steps includes passing light through:

a birefringent liquid crystal panel;

a first passive layer that minimizes the birefringent effect exhibited by the birefringent liquid crystal panel; and

a second passive layer that introduces a birefringent effect.

49. A color display comprising, in combination: first and second display subassemblies each having a net Δn_d value greater than $0.5 \mu\text{m}$, each including a liquid crystal panel defining a plurality of independently operable pixels, which exhibit a birefringent effect that varies in response to a signal applied thereto, said first subassembly having a net Δn_d value at least $0.05 \mu\text{m}$ greater than the net Δn_d value of the second subassembly;

- a first polarizer interposed between the two display subassemblies; and
- a second and a third polarizer sandwiched about the two display subassemblies wherein at least one of the first, second or third polarizers is colored a color other than black.

50. The color display of claim 49 in which the first and second liquid crystal panels are each supertwisted nematic liquid crystal panels.

51. The color display of claim 49 in which at least one of the first and second liquid crystal panels comprise:

- a birefringent liquid crystal panel;
- a first passive layer that minimizes the birefringent effect exhibited by the birefringent liquid crystal panel; and
- a second passive layer that introduces a birefringent effect.

52. The color display of claim 49 which further comprises:

- a third display subassembly having a net Δn_d value at least $0.05 \mu\text{m}$ greater than the net Δn_d values of the first and second panels; said third display subassembly including a liquid crystal panel and defining a plurality of independently operable pixels;
- a fourth polarizer; and
- said third display subassembly interposed between the third and fourth polarizers;

wherein:

- all three of the subassemblies have Δn_d values greater than $0.5 \mu\text{m}$.

53. A subtractive color display method that includes the steps:

- providing a birefringent display subassembly that includes a nematic liquid crystal cell and that defines a plurality of independently operable pixels, wherein a birefringent effect exhibited by one of said pixels varies in response to an electrical signal applied thereto;
- operating the display subassembly in conjunction with entrance and exit polarizers;
- linearly polarizing light entering the pixel by passing it through the entrance polarizer;
- elliptically polarizing said linearly polarized light as it passes through the pixel, whereby different wavelengths of light are oriented at different angular orientations when they exit the pixel, the elliptical polarization when a first electrical signal is applied to said pixel differing from the elliptical polarization when a second electrical signal is applied to said pixel;
- analyzing the elliptically polarized light exiting the pixel so that light oriented orthogonally to an axis of the exit polarizer is attenuated by the exit polarizer;

wherein:

- when the first electrical signal is applied to the pixel, the birefringence of the pixel orients a first wavelength of light orthogonally to the axis of the exit polarizer, thereby causing its attenuation by the exit polarizer; and

when the second electrical signal is applied to the pixel, the different birefringence of the pixel orients the first wavelength of light so that it is no longer oriented orthogonally to the axis of the exit polarizer, thereby permitting it to pass through the exit polarizer relatively less attenuated;

wherein the exit polarizer is dyed to pass wavelengths of light, other than the first wavelength, relatively unattenuated regardless of their orientation, thereby improving the transmission of said wavelengths of light and optimizing the resulting display brightness of the subtractive color display.

54. A subtractive color display method that includes the steps:

- providing a birefringent display subassembly that includes a nematic liquid crystal cell and that defines a plurality of independently operable pixels, wherein a birefringent effect exhibited by one of said pixels varies in response to an electrical signal applied thereto;
- operating the display subassembly in conjunction with entrance and exit polarizers;
- linearly polarizing light of a first wavelength entering the pixel by passing it through the entrance polarizer;
- elliptically polarizing light as it passes through the pixel, whereby different wavelengths of light are oriented at different angular orientations when they exit the pixel, the elliptical polarization when a first electrical signal is applied to said pixel differing from the elliptical polarization when a second electrical signal is applied to said pixel;
- analyzing the elliptically polarized light exiting the pixel so that light oriented orthogonally to an axis of the exit polarizer is attenuated by the exit polarizer,
- wherein:

- when the first electrical signal is applied to the pixel, the birefringence of the pixel orients the first wavelength of light orthogonally to the axis of the exit polarizer, thereby causing its attenuation by the exit polarizer; and

- when the second electrical signal is applied to the pixel, the different birefringence of the pixel orients the first wavelength of light so that it is no longer oriented orthogonally to the axis of the exit polarizer, thereby permitting it to pass through the exit polarizer relatively less attenuated;

wherein the entrance polarizer is dyed to pass wavelengths of light, other than the first wavelength, relatively unattenuated regardless of their orientation, thereby improving the transmission of said wavelengths of light and optimizing the resulting display brightness of the subtractive color display.

55. In a color display system comprising:

- a first, second and third polarizer;
- first and second cells comprising supertwisted nematic type liquid crystal material, said cells exhibiting a birefringent effect and having different values of Δn_d , said cells having a plurality of independently operable pixels and disposed in a stacked arrangement with said polarizers;
- said first polarizer interposed between said first and second cells and said second and third polarizers disposed outside the stacked arrangement adjacent to said first and second cells, respectively, whereby said first cell in cooperation with said first and second polarizers provides spectral response different from said second cell in cooperation with said first and third polarizers.

56. The color display system of claim 55 further comprising a passive compensation layer adjacent to one of said cells.

57. The color display system of claim 55 which further includes at least two polarizers adjacent different surfaces of the first and second portions, each of said two polarizers being dyed a color other than black.

58. A color display system comprising:

a first and second portion in stacked arrangement;

each portion including an optical element defining a plurality of independently operable pixels and exhibiting a birefringent effect that varies in response to an applied signal;

a first polarizer interposed between said first and second portion;

a second and third polarizer sandwiched about said stacked portions, said second and third polarizers colored a color other than black so that the leakage characteristics of said second and third polarizers do not overlap;

the first portion, in combination with said first and second polarizers, exhibits a first spectral response when driven with a first signal; and

the second portion, in combination with said first and third polarizers, exhibits a second spectral response when driven with the first signal.

59. The color display system of claim 58 in which the portions exhibit different spectral responses and different values of $\Delta n d$, each of which is greater than $0.50 \mu\text{m}$.

60. The color display system of claim 58 in which the different spectral responses are achieved by inclusion of a passive optical element in one of said portions.

61. The color display system of claim 60 in which the passive element is a retardation film.

62. A color display comprising:

first and second stacked birefringent display subassemblies, each having a supertwisted nematic liquid crystal panel defining a plurality of independently operable pixels, said first and second display subassemblies stacked so that corresponding pixels in each of said subassemblies are linearly aligned, at least one of said display subassemblies having a value of $\Delta n d$ greater than 1.05 micrometers;

a first polarizer disposed between said first and second subassemblies;

second and third polarizers sandwiched about said first and second subassemblies, said second and third polarizers colored different primary colors selected from the list: red, green and blue whereby each pair of corresponding pixels in the first and second display subassemblies can be cooperatively operated to produce all the colors comprising red, green, blue, yellow, magenta, cyan, black and white.

63. The color display of claim 62 wherein:

the first and second display subassemblies each includes a supertwisted nematic panel;

at least one of said display subassemblies exhibits a value of $\Delta n d$ greater than 1.05 micrometers; and

each pair of corresponding pixels in the first and second display subassemblies can be cooperatively operated to produce all the primary and secondary colors (red, green, blue, yellow, magenta and cyan), together with black and white;

wherein a true, eight color display can be produced with a stack of just two liquid crystal panels.

64. The color display of claim 63 wherein:

at least one of the display subassemblies exhibits a value of $\Delta n d$ greater than 1.15 micrometers.

65. A color liquid crystal display, comprising:

first and second subtractive LCD filters, each filter, comprising means for independently subtracting one of the primary colors (red, green, blue) from a polychromatic light beam without substantially affecting the other primary colors, each filter including:

an entrance selective polarizer for polarizing light of one of the primary colors while passing light of the other colors substantially unpolarized;

a LCD panel for selectively changing polarization of incident light; and

an exit selective polarizer for selectively blocking or passing the light of the same one of the primary colors, depending upon the polarization change imparted by the LCD panel, and passing light of the other colors.

66. The liquid crystal display of claim 65 in which:

the first subtractive LCD filter comprises a yellow filter for subtracting blue light; and

the second subtractive LCD filter comprises a magenta filter for subtracting green light.

67. The liquid crystal display of claim 66 in which the first-second polarizer comprises a red polarizer for polarizing green and blue light.

68. The liquid crystal display of claim 65 in which sequentially adjacent entrance and exit polarizers of the first and second filters comprise a single polarizer.

69. The liquid crystal display of any of claims 65–67 in which each LCD panel comprises a plurality of individually selectable regions.

70. The liquid crystal display of claim 65 in which the LCD panel employs a birefringence optical operating mode to selectively chance polarization of incident light.

71. The liquid crystal display of claim 65 in which the LCD panel includes a supertwisted nematic LCD cell.

72. Display apparatus comprising:

first and second liquid crystal display panels for imparting an effective polarization change to applied incident spectral radiant energy as an excitation voltage is applied to the liquid crystal display panel;

first, second, third and fourth polarizers; the first liquid crystal display panel being disposed between the first and second polarizers, the second liquid crystal display panel being disposed between the third and fourth polarizers;

the first and second polarizers characterized by selectively linearly polarizing the spectral radiant energy of a first primary color, while transmitting the spectral energy of second and third primary colors unaffected; the third and fourth polarizers selected to linearly polarize spectral radiant energy of the second primary color, while transmitting spectral radiant energy of the first and third primary colors unaffected; and

the first and second panels in cooperation with the selective polarizers adjacent thereto being operative, in combination, to block one of the primary colors, while transmitting the balance of incident spectral radiant energy unaffected when the panel is in a first state and for transmitting incident spectral radiant energy of all colors when the panel is in a second state.

73. The display apparatus of claim 72 in which each of said panels comprises an array of electronically controlled pixels, corresponding ones of said pixels in each of said panels being aligned along an axis or orthogonal to the panels.

31

74. The display apparatus of claim 72 in which the combination of the first panel and the first and second selective polarizers adjacent thereto is operative to linearly polarize spectral energy of a first primary color when the panel is in a second state, while transmitting the spectral energy for the second and third primary colors unpolarized. 5

75. The display apparatus of claim 72 in which the combination of the second panel and the third and fourth selective polarizers adjacent thereto is operative to linearly polarize the spectral energy of a second primary color when the panel is in a second state, while transmitting the spectral energy for the first and third primary colors unpolarized. 10

76. The display apparatus of claim 72 in which the first and second liquid crystal display panels employ a birefringence optical operating mode to impart effective polarization chances to incident spectral radiant energy. 15

77. The display apparatus of claim 72 in which the first and second liquid crystal display panels each include a supertwisted nematic LCD cell.

78. Display apparatus comprising:

first and second liquid crystal display panels for imparting an effective polarization change to applied incident spectral radiant energy as an excitation voltage is applied to the liquid crystal display panels;

first, second and third polarizers;

the first panel disposed between the first and second polarizers, the second panel disposed between the second and third polarizers;

the first polarizer being adapted to selectively linearly polarize spectral radiant energy corresponding to a first primary color, while transmitting spectral radiant energy of other colors substantially unaffected; 30

32

the second polarizer operative to selectively linearly polarize spectral radiant energy of both the first and second primary colors, while transmitting spectral radiant energy of other colors substantially unaffected; the third polarizer being selected to selectively linearly polarize the second primary color while transmitting other colors unpolarized; and

the first and second panels in cooperation with the selective polarizers adjacent thereto being operative, in combination, to block one of the primary colors while transmitting the balance of incident spectral radiant energy unaffected in a first state, and to pass incident spectral radiant energy of all colors in a second state.

79. The display apparatus of claim 78 in which each of said panels comprises an array of electronically controlled pixels, corresponding ones of said pixels in each of said panels being aligned along an axis or orthogonal to the panels.

80. The display apparatus of claim 78 in which the first liquid crystal display panel, in the second state, in combination with the first and second selective polarizers adjacent thereto, linearly polarizes the spectral energy of the first and second primary colors, while transmitting the spectral energy of the third primary color unpolarized.

81. The display apparatus of claim 78 in which the first and second liquid crystal display panels employ a birefringence optical operating mode to impart effective polarization changes to incident spectral radiant energy.

82. The display apparatus of claim 78 in which the first and second liquid crystal display panels each include a supertwisted nematic LCD cell.

* * * * *