



(22) Date de dépôt/Filing Date: 2014/03/14

(41) Mise à la disp. pub./Open to Public Insp.: 2014/09/14

(45) Date de délivrance/Issue Date: 2022/05/17

(30) Priorité/Priority: 2013/03/14 (US61/783,590)

(51) Cl.Int./Int.Cl. *A63C 1/00* (2006.01),
A43B 5/16 (2006.01), *A63C 1/38* (2006.01)


(72) Inventeurs/Inventors:
LABONTE, IVAN, CA;
CORBEIL, JEAN-FRANCOIS, CA

(73) Propriétaire/Owner:
BAUER HOCKEY LTD., CA

(74) Agent: SMART & BIGGAR LLP

(54) Titre : PATIN A GLACE

(54) Title: ICE SKATE



(57) Abrégé/Abstract:

An ice skate comprising a blade holder having U-shaped inner and outer members that are spaced apart to define a hollow space therebetween. The U-shaped outer member has an elongated blade-supporting base and front and rear pillars that are spaced apart in a longitudinal direction of the blade holder. At least part of the elongated blade-supporting base, front pillar and rear pillar is made of a composite material such as a fiber-matrix composite material. The ice skate also has a blade comprising a runner and a body made of composite material with a matrix and a plurality of fibers embedded in the matrix.

ABSTRACT

An ice skate comprising a blade holder having U-shaped inner and outer members that are spaced apart to define a hollow space therebetween. The U-shaped outer
5 member has an elongated blade-supporting base and front and rear pillars that are spaced apart in a longitudinal direction of the blade holder. At least part of the elongated blade-supporting base, front pillar and rear pillar is made of a composite material such as a fiber-matrix composite material. The ice skate also has a blade comprising a runner and a body made of composite material with a matrix and a
10 plurality of fibers embedded in the matrix.

ICE SKATE

Field of the invention

- 5 The invention generally relates to ice skates, including their blade holder and their blade.

Background of the invention

- 10 Ice skates include a skate boot for receiving a skater's foot and a blade holder connecting a blade to the skate boot. Many different types of skate boots, blade holders and blades have been developed in order to provide skates which can accommodate different skating maneuvers as well as to provide general advantages to skaters.

15

It is typically desirable from a skater's perspective to have a skate which is relatively lightweight. This is because heavier skates impose a larger physical burden during use and can incrementally result in tiring the skater. From a manufacturer's perspective, it is important to be able to provide such advantages at a reduced cost.

20

While changes can be made to the skate boot itself, the skate boot can only be optimized to a certain point before reaching a substantial "plateau" in comfort, performance, production cost, etc. As such, it is important to also consider the design of the blade holder and the blade which can largely affect a skater's

25

performance depending on the materials and design employed.

There is therefore an ongoing need in the industry to improve an ice skate, including its blade holder and its blade.

Summary of the invention

In accordance with an aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises an elongated blade-supporting base for supporting the blade. The blade holder also comprises a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder. The front pillar extends from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extends from the elongated blade-supporting base towards the rear portion of the skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar. The blade holder is responsive to a skating movement of the skater to undergo an elastic torsion of each of the front pillar and the rear pillar which induces an elastic flexion of the elongated blade-supporting base and the blade in a widthwise direction of the blade holder.

In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises an elongated blade-supporting base for supporting the blade. The blade holder also comprises a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder. The front pillar extends from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extends from the elongated blade-supporting base towards the rear portion of the skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar. A longitudinal spacing of the front pillar and the rear pillar is greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal

longitudinal dimension of the rear pillar. At least a front quarter and a rear quarter of the blade holder is free of any inter-pillar structure comparable to at least one of the front pillar and the rear pillar.

5 In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade
10 holder comprises an elongated blade-supporting base for supporting the blade. The blade holder also comprises a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder. The front pillar extends from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extends from the elongated blade-supporting base towards the rear portion of the
15 skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar. A longitudinal spacing of the front pillar and the rear pillar is greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal longitudinal dimension of the rear pillar. At least a front quarter and a rear quarter of the blade holder is free of any inter-pillar structure substantially limiting a widthwise
20 flexion of the elongated blade-supporting base while the skater skates.

In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving
25 toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises an elongated blade-supporting base for supporting the blade. The blade holder also comprises a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder. The front pillar extends from the elongated
30 blade-supporting base towards the front portion of the skate boot, the rear pillar extends from the elongated blade-supporting base towards the rear portion of the

skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar. A longitudinal spacing of the front pillar and the rear pillar is greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal longitudinal dimension of the rear pillar. The elongated blade-supporting base is
5 suspended only by the front pillar and the rear pillar.

In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving
10 toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises a U-shaped inner member and a U-shaped outer member spaced from the U-shaped inner member to define a hollow space between the U-shaped inner member and the U-shaped outer member. The U-shaped outer member
15 comprises an elongated blade-supporting base for supporting the blade. The U-shaped outer member also comprises a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder. The front pillar extends from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extends from the elongated blade-supporting base towards the rear portion of
20 the skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar.

In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for
25 receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises an elongated blade-supporting base for supporting the blade. The blade holder also comprises a front pillar and a rear pillar that are spaced apart in a
30 longitudinal direction of the blade holder. The front pillar extends from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar

extends from the elongated blade-supporting base towards the rear portion of the skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar. A longitudinal spacing of the front pillar and the rear pillar is greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal longitudinal dimension of the rear pillar. At least part of the elongated blade-supporting base, the front pillar, and the rear pillar is made of a composite material.

In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises an elongated blade-supporting base for supporting the blade. The elongated blade-supporting base comprises an external wall defining an interior cavity. The external wall comprises a composite material. The blade holder also comprises a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder. The front pillar extends from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extends from the elongated blade-supporting base towards the rear portion of the skate boot, and the elongated blade-supporting base extends from the front pillar to the rear pillar.

In accordance with another aspect of the invention, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The blade holder comprises an upper structure for facing the skate boot and an elongated blade-supporting base for supporting the blade. The blade holder also comprises a resilient element disposed between the upper structure and the elongated blade-supporting base and configured to deform when the elongated blade-supporting base moves relative to the upper structure while the skater skates.

In accordance with another aspect of the invention, there is provided a blade for an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater and a blade holder for holding the blade. The blade comprises a body for mounting to the blade holder. The body comprises a composite material. The composite material
5 comprises a matrix and a plurality of fibers embedded in the matrix. The blade also comprises an ice-contacting surface for contacting an ice surface on which the skater skates. The ice-contacting surface comprises an ice-contacting material different from the composite material.

10 In accordance with a broad aspect, the present invention provides a blade holder for an ice skate, the ice skate comprising: a skate boot for receiving a foot of a skater, the skate boot comprising a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot, the blade holder comprising an elongated
15 blade-supporting base; and a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder, the front pillar extending from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extending from the elongated blade-supporting base towards the rear portion of the skate boot, the elongated blade-supporting base extending from the front pillar to
20 the rear pillar; and wherein at least part of the elongated blade-supporting base, the front pillar and the rear pillar is made of a composite material.

The composite material may be a fiber-matrix composite material and the elongated blade-supporting base, the front pillar and the rear pillar may be made of the fiber-
25 matrix composite material.

The blade holder may comprise an ice skate blade mounted to the bottom blade portion of the elongated blade-supporting base of the blade holder.

30 In one variant, the bottom blade portion of the elongated blade-supporting base defines a recess and the ice skate blade has a top portion and a bottom portion

defining an ice-contacting surface, the top portion of the ice skate blade comprising a projection affixed into the recess of the bottom blade portion of the elongated blade-supporting base

- 5 In another variant, the bottom blade portion of the elongated blade-supporting base defines a projection and the ice skate blade has a top portion and a bottom portion defining an ice-contacting surface, the top portion of the ice skate blade comprising a recess in which the projection the bottom blade portion of the elongated blade-supporting base is affixed.

10

- In a further variant, the ice skate blade has a top portion and a bottom portion defining an ice-contacting surface, the top portion of the ice skate blade comprising a plurality of anchoring members such that the top portion of the ice skate blade is within the fiber-matrix composite material of the elongated blade-supporting base for
15 retaining the ice skate blade to the blade holder. The plurality of anchoring elements may comprise hooks, projections, channels or interlocking openings. The fiber-matrix composite material of the elongated blade-supporting base comprises layers of fibers and at least one layer of fibers is located within the anchoring elements such that the anchoring elements are embedded in the fiber-matrix composite
20 material of the elongated blade-supporting base.

- The blade holder may be responsive to a skating movement of the skater to undergo an elastic torsion of each of the front pillar and the rear pillar which induces an elastic flexion of the elongated blade-supporting base and the blade in a widthwise
25 direction of the blade holder.

- A longitudinal spacing of the front pillar and the rear pillar may be greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal longitudinal dimension of the rear pillar and at least a front quarter and a rear quarter of the
30 blade holder may be free of any inter-pillar structure comparable to at least one of the front pillar and the rear pillar. At least one of a front third and a rear third of the

blade holder may be free of any inter-pillar structure comparable to at least one of the front pillar and the rear pillar. Each of the front third and the rear third of the blade holder may be free of any inter-pillar structure comparable to at least one of the front pillar and the rear pillar.

5

The blade holder may be free of any inter-pillar structure comparable to at least one of the front pillar and the rear pillar.

10 A longitudinal spacing of the front pillar and the rear pillar may be greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal longitudinal dimension of the rear pillar and at least a front quarter and a rear quarter of the blade holder may be free of any inter-pillar structure substantially limiting a widthwise flexion of the elongated blade-supporting base while the skater skates.

15 At least one of a front third and a rear third of the blade holder may be free of any inter-pillar structure substantially limiting a widthwise flexion of the elongated blade-supporting base while the skater skates. Each of the front third and the rear third of the blade holder may be free of any inter-pillar structure substantially limiting a widthwise flexion of the elongated blade-supporting base while the skater skates.

20

the blade holder is free of any inter-pillar structure substantially limiting a widthwise flexion of the elongated blade-supporting base while the skater skates.

25 A longitudinal spacing of the front pillar and the rear pillar may be greater than a sum of a minimal longitudinal dimension of the front pillar and a minimal longitudinal dimension of the rear pillar and the elongated blade-supporting base may be suspended only by the front pillar and the rear pillar.

30 The elongated blade-supporting base, the front pillar and the rear pillar may be part of a U-shaped outer member and the blade holder may comprise a U-shaped inner member spaced from the U-shaped outer member to define a void between the U-

shaped inner member and the U-shaped outer member. The blade holder may comprise a resilient element disposed between the U-shaped inner member and the U-shaped outer member that is configured to deform when the U-shaped inner and outer members move relative to each other while the skater skates.

5

The blade holder may comprise a front member defining a front peripheral wall with an upper surface for facing a bottom portion of the front portion of the skate boot and a rear member defining a rear peripheral wall with an upper surface for facing a bottom portion of the rear portion of the skate boot. The U-shaped inner member comprising an elongated portion, a front portion extending upwardly from the elongated portion and having an upper end integrally formed with the front member and a rear portion extending upwardly from the elongated portion and having an upper end integrally formed with the rear member, and the front pillar has an upper end integrally formed with the front member and the rear pillar has an upper end integrally formed with the rear member. Each of the front and rear peripheral walls of the front and rear members may comprise apertures for affixing the blade holder to the bottom portion of the front and rear portions of the skate boot. The blade holder may comprise an intermediate member extending between the front and rear members, the intermediate member having an upper surface for facing a bottom portion of the intermediate portion of the skate boot, the front and rear peripheral walls of the front and rear members and the intermediate member defining a pedestal for facing the bottom portion of the skate boot. The elongated portion of the U-shaped inner member overlaps a portion of the elongated blade-supporting base. The elongated portion of the U-shaped inner member may contact a portion of the elongated blade-supporting base. The blade holder may comprise a resilient element disposed between the elongated portion of the U-shaped inner member and the elongated blade-supporting base.

The U-shaped inner member may comprise fiber-matrix composite material that offers less resilience than the fiber-matrix composite material of the U-shaped outer member. The fiber-matrix composite material of the U-shaped inner member may

comprise glass fibers or polypropylene fibers and the fiber-matrix composite material of the U-shaped outer member may comprise carbon fibers, graphite fibers or carbon graphite fibers.

- 5 The elongated blade-supporting base, the front pillar, the rear pillar, the elongated portion, front portion and rear portion of the U-shaped inner member, the front member or the rear member may comprise an external wall defining an interior cavity. The elongated blade-supporting base, the front pillar, the rear pillar or the elongated portion, front portion or rear portion of the U-shaped inner member may
10 comprise a filler in the interior cavity. The filler may comprise foam.

According to another broad aspect, the invention provides a blade holder for an ice skate, the ice skate comprising a skate boot for receiving a foot of a skater, the skate boot comprising a front portion for receiving toes of the foot, a rear portion for
15 receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot, the blade holder comprising: a U-shaped inner member; and a U-shaped outer member spaced from the U-shaped inner member to define a hollow space between the U-shaped inner member and the U-shaped outer member, the U-shaped outer member comprising: an elongated blade-supporting
20 base; and a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder, the front pillar extending from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extending from the elongated blade-supporting base towards the rear portion of the skate boot, the elongated blade-supporting base extending from the front pillar to the rear pillar;
25 and wherein at least part of the elongated blade-supporting base, the front pillar and the rear pillar is made of a composite material. The composite material may be a fiber-matrix composite material and the elongated blade-supporting base, the front pillar and the rear pillar may be made of the fiber-matrix composite material.

- 30 According to a further broad aspect, the invention provides a blade holder for an ice skate, the ice skate comprising a skate boot for receiving a foot of a skater, the skate

boot comprising a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot, the blade holder comprising: an elongated blade-supporting base; and a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder, the front pillar extending from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar extending from the elongated blade-supporting base towards the rear portion of the skate boot, the elongated blade-supporting base extending from the front pillar to the rear pillar; wherein the elongated blade-supporting base, the front pillar and the rear pillar comprise an external wall defining an interior cavity, the external wall being at least partially made of a composite material. The composite material may be a fiber-matrix composite material and the elongated blade-supporting base, the front pillar and the rear pillar may be made of the fiber-matrix composite material.

According to another broad aspect, the invention provides an ice skate blade extending along a longitudinal axis, the ice skate blade comprising: a body extending along the longitudinal axis and comprising a composite material, the composite material comprising a matrix and a plurality of fibers embedded in the matrix, the body comprising a bottom portion and a top portion for mounting to a blade holder; and a runner extending along the longitudinal axis and comprising a top portion and a bottom portion having an ice-contacting surface for contacting an ice surface on which a skater skates. Respective ones of the fibers may be oriented to be in tension when the blade deflects while the skater skates. Respective ones of the fibers may extend parallel or at an oblique angle to a longitudinal axis of the blade. At least a majority of the fibers may extend parallel or at an oblique angle to the longitudinal axis of the blade. A totality of the fibers may extend parallel or at an oblique angle to the longitudinal axis of the blade.

The runner is made of metallic material. For example, the runner may be made of stainless steel, carbon steel, tungsten carbide or titanium), of a strip of engineering plastic or a strip that is at least partially made of ceramic material (e.g. aluminum

titanate, aluminum zirconate, sialon, silicon nitride, silicon carbide, zirconia and partially stabilized zirconia or a combination of two or more of these materials).

In one variant, the bottom portion of the body defines a recess and the top portion of the runner comprises a projection affixed into the recess of the bottom portion of the body. In another variant, the bottom portion of the body defines a projection and the top portion of the runner comprises a recess in which the projection the bottom portion of the body is affixed. In a further variant, the top portion of the runner comprises a plurality of anchoring members such that the top portion of the runner is within the composite material of the body for retaining the runner to the body. The plurality of anchoring elements may comprise hooks, projections, channels or interlocking openings. The composite material of the body may comprise layers of fibers and at least one layer of fibers is located within the anchoring elements such that the anchoring elements are embedded in the composite material of the body.

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising: a one-piece component, comprising: a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a fiber-reinforced composite layer; and a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the fiber-reinforced composite layer. The skate further comprising a toe cap separately affixed to the one-piece component; wherein the one-piece component defines a plurality of voids extending laterally from a medial side of the skate to a lateral side of the skate; and wherein at least one of the voids occupies most of a height of the blade holder body.

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising: a skate boot configured to receive a foot of a user, the skate boot

comprising a body that comprises a medial side portion to face a medial side of the user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the body of the skate boot including fiber-reinforced composite material;
5 and a blade holder disposed below the skate boot and configured to hold a blade for engaging the ice, the blade holder comprising a body including fiber-reinforced composite material and an internal frame covered by the fiber-reinforced composite material of the body of the blade holder. The fiber-reinforced composite material of the body of the skate boot and the fiber-reinforced composite material of the body of
10 the blade holder are formed integrally with one another.

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising: a skate boot configured to receive a foot of a user, the skate boot comprising a body that comprises a medial side portion to face a medial side of the
15 user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the body of the skate boot including fiber-reinforced composite material; and a blade holder disposed below the skate boot and configured to hold a blade for engaging the ice, the blade holder comprising a body including fiber-reinforced
20 composite material. The fiber-reinforced composite material of the body of the skate boot and the fiber-reinforced composite material of the body of the blade holder are formed integrally with one another; and the fiber-reinforced composite material of the body of the blade holder defines a void extending laterally from a medial side of the skate to a lateral side of the skate.

25
According to another broad aspect, there is provided a skate for skating on ice, the skate comprising: a skate boot configured to receive a foot of a user, the skate boot comprising a body that comprises a medial side portion to face a medial side of the user's foot, a lateral side portion to face a lateral side of the user's foot, a heel
30 portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user; and a blade holder disposed below the skate boot and configured to hold

a blade for engaging the ice, the blade holder comprising a body and a blade-connecting mechanism that is configured to attach the blade to and detach the blade from the blade holder. At least part of the body of the skate boot and at least part of the body of the blade holder are formed integrally with one another.

5

According to another broad aspect, there is provided a blade holder for holding a blade of an ice skate, the ice skate comprising a skate boot for receiving a foot of a skater, the blade holder comprising: a first structural portion comprising a first polymeric material and defining at least part of a shape of the blade holder; and a
10 second structural portion comprising a second polymeric material different from the first polymeric material.

According to another broad aspect, there is provided a blade holder for holding a blade of an ice skate, the ice skate comprising a skate boot for receiving a foot of a
15 skater, the blade holder comprising: a first structural portion comprising a composite material and defining at least part of a shape of the blade holder; and a second structural portion comprising a polymeric material different from the composite material.

20 According to another broad aspect, there is provided a blade holder for holding a blade of an ice skate, the ice skate comprising a skate boot for receiving a foot of a skater, the blade holder comprising: a first structural portion comprising a first polymeric material and defining at least part of a shape of the blade holder; and a second structural portion comprising a second polymeric material different from the
25 first polymeric material. The first structural portion and the second structural portion of the blade holder are affixed to one another by molding of at least one of the first structural portion and the second structural portion of the blade holder.

According to another broad aspect, there is provided a blade for an ice skate, the ice
30 skate comprising a skate boot for receiving a foot of a skater and a blade holder for holding the blade, the blade holder comprising a blade-connecting mechanism to

attach the blade to and detach the blade from the blade holder without using mechanical fasteners, the blade comprising: a metallic member comprising a metallic material and including an ice-contacting surface for contacting ice; and a polymeric member comprising a polymeric material and connected to the metallic member. The blade comprises a connector including part of the polymeric material and configured to engage the blade-connecting mechanism of the blade holder.

According to another broad aspect, there is provided a method for manufacturing a skate for skating on ice, the method comprising: molding a one-piece component using a mold and at least one layer of fiber-reinforced composite material. The one-piece component comprising a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, an ankle portion to receive an ankle of the user, and a toe portion to enclose toes of the user's foot, the skate boot body including at least a first part of the at least one fiber-reinforced composite layer. The one-piece component further comprising a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the at least one fiber-reinforced composite layer. The method further comprising affixing a toe cap to the one-piece component.

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising a one-piece component. The one-piece component comprising a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a fiber-reinforced composite later. The one-piece component further comprising a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the fiber-

reinforced composite layer. The skate further comprising a toe cap separately affixed to the one-piece component.

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising a one-piece component. The one-piece component comprises a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a fiber-reinforced composite layer. The one-piece component comprises a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the fiber-reinforced composite layer. The skate comprises a toe cap separately affixed to the one-piece component. The one-piece component defines a plurality of voids at least one void extending laterally from a medial side of the skate to a lateral side of the skate. At least one of the voids occupies most of a height of the blade holder body

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising a one-piece component. The one-piece component comprises a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a fiber-reinforced composite layer. The one-piece component comprises a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the fiber-reinforced composite layer. The skate comprises a toe cap separately affixed to the one-piece component.

According to another broad aspect, there is provided a skate for skating on ice, the skate comprising a one-piece component. The one-piece component comprises a

skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a material layer. The one-piece component comprises a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the material layer. The skate comprises an injection-molded component distinct from the one-piece component and affixed to the one-piece component.

10

According to another broad aspect, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises: an elongated blade-supporting base for supporting the blade; and a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder, the front pillar being configured to extend from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar being configured to extend from the elongated blade-supporting base towards the rear portion of the skate boot, the elongated blade-supporting base extending from the front pillar to the rear pillar; wherein a longitudinal spacing of the front pillar and the rear pillar is greater than a minimal longitudinal dimension of the front pillar and greater than a minimal longitudinal dimension of the rear pillar. At least part of the blade holder is made of a composite material.

25

According to another broad aspect, there is provided a blade holder for holding a blade of an ice skate. The ice skate comprises a skate boot for receiving a foot of a skater. The skate boot comprises a front portion for receiving toes of the foot, a rear portion for receiving a heel of the foot, and an intermediate portion between the front portion and the rear portion of the skate boot. The blade holder comprises: an

30

elongated blade-supporting base for supporting the blade; and a front pillar and a rear pillar that are spaced apart in a longitudinal direction of the blade holder, the front pillar being configured to extend from the elongated blade-supporting base towards the front portion of the skate boot, the rear pillar being configured to extend
5 from the elongated blade-supporting base towards the rear portion of the skate boot, the elongated blade-supporting base extending from the front pillar to the rear pillar. A longitudinal spacing of the front pillar and the rear pillar is greater than a minimal longitudinal dimension of the front pillar and greater than a minimal longitudinal dimension of the rear pillar. The blade holder comprises an external wall defining an
10 interior cavity, the external wall being at least partially made of a composite material.

These and other aspects of the invention will now become apparent to those of ordinary skill in the art upon review of the following description of embodiments of the invention in conjunction with the accompanying drawings.

15

Brief description of the drawings

A detailed description of embodiments of the invention is provided below, by way of example only, with reference to the following drawings, in which:

20

Figure 1 is a perspective view of an ice skate in accordance with an embodiment of the invention;

Figure 2 is an exploded view of the ice skate of Figure 1;

25

Figure 3 is a side cross-sectional view of an ice skate blade holder of the ice skate;

Figure 4 is a bottom view of the ice skate blade holder;

Figure 5 is a front view of the ice skate blade holder;

- 5 Figure 6 is an enlarged cross-sectional view of the ice skate blade holder;

Figure 7 is a bottom view of the ice skate blade holder experiencing a rotational deformation at its front and rear pillars which induces a flexion of its blade-supporting base;

10

Figure 8 is a side cross-sectional view of a variant of the ice skate blade holder including an inter-pillar structure in accordance with another embodiment of the invention;

- 15 Figure 9 illustrates a composite material of the ice skate blade holder;

Figure 10 is a side view of an ice skate blade of the blade holder;

Figure 11 is a cross-sectional view of the ice skate blade;

20

Figure 12 is a cross-sectional view of a variant of the ice skate blade holder in accordance with another embodiment of the invention;

- 25 Figures 13A and 13B are side cross-sectional views of variants of the ice skate blade holder in accordance with other embodiments of the invention;

Figures 14A to 14F are bottom views of variants of an outline of the blade-supporting base of the ice skate blade holder in accordance with other embodiments of the invention;

30

Figure 15 is a side cross-sectional view of a variant of the ice skate blade holder

including internal material in accordance with another embodiment of the invention;

Figure 16 is a cross-sectional view of the ice skate blade holder of Figure 15;

- 5 Figure 17 is a side cross-sectional view of a variant of the ice skate blade holder including internal material comprising a filler and a reinforcement in accordance with another embodiment of the invention;

Figure 18 is a cross-sectional view of the ice skate blade holder of Figure 17;

10

Figure 19 is a cross-sectional view of a variant of the ice skate blade holder;

Figure 20 is a cross-sectional view of a variant of the ice skate blade holder;

- 15 Figures 21A to 21C are side cross-sectional views of a variant of the ice skate blade holder including a blade-detachment mechanism in accordance with another embodiment of the invention;

- 20 Figure 22 is a side view of a variant of the ice skate blade holder including a resilient element in accordance with another embodiment of the invention;

Figures 23A to 23G are cross-sectional views of variants of the ice skate blade holder in accordance with other embodiments of the invention;

- 25 Figures 24A to 24C are cross-sectional views of variants of the ice skate blade holder in accordance with other embodiments of the invention;

Figure 25 is a side view of a variant of the ice skate blade holder in accordance with another embodiment of the invention;

30

Figure 26 is a side view of a variant of the ice skate blade holder in accordance with

another embodiment of the invention;

Figure 27 is a bottom view of the ice skate blade holder of Figure 26;

- 5 Figure 28 is a front view of the ice skate blade holder of Figure 26;

Figures 29 and 30 are side cross-sectional views of variants of the ice skate blade holder in accordance with other embodiments of the invention;

- 10 Figure 31 is an exploded view of a variant of the ice skate including an outsole which is separate from the ice skate blade holder in accordance with another embodiment of the invention;

- Figure 32 is a side view of a variant in which the ice skate blade holder and a toe cap of a skate boot of the ice skate are integrally formed in accordance with another embodiment of the invention;
- 15

- Figure 33 is a side view of a variant in which the ice skate blade holder and an outer shell of the skate boot are integrally formed in accordance with another embodiment of the invention;
- 20

- Figure 34 is a side view of a variant in which the ice skate blade holder, the toe cap of the skate boot and the outer shell of the skate boot are integrally formed in accordance with another embodiment of the invention;
- 25

Figures 35 and 36 are side and top views of an internal frame of the ice skate blade holder in accordance with another embodiment of the invention;

- Figure 37 is a side view of an ice skate blade holder in accordance with another embodiment of the invention;
- 30

Figure 38 is a bottom view of the ice skate blade holder of Figure 37;

Figure 39 is a cross-sectional view taken along line 39-39 of Figure 38;

5 Figure 40 is a cross-sectional view taken along line 40-40 of Figure 39;

Figure 41 is a cross-sectional view identical to Figure 40 without the resilient element;

Figure 42 is a side view of the runner of the ice skate blade holder of Figure 37;

10

Figure 43 shows the runner of Figure 42 with layers of fibers used for the composite material;

Figure 44 is a side view of an ice skate blade holder in accordance with another
15 embodiment of the invention;

Figure 45 is a bottom view of the ice skate blade holder of Figure 44;

Figure 46 is a cross-sectional view taken along line 46-46 of Figure 45;

20

Figure 47 is a cross-sectional view taken along line 47-47 of Figure 46;

Figure 48 is a cross-sectional view of a variant of the ice skate blade in accordance with another embodiment of the invention;

25

Figure 49 is a cross-sectional view taken along line 49-49 of Figure 48;

Figure 49A shows a cross-sectional view of another embodiment;

30 Figure 50 is a cross-sectional view of an ice skate blade in accordance with a further embodiment of the invention;

Figure 51 is a cross-sectional view taken along line 50-50 of Figure 49;

Figure 52 is a side view of the runner of the ice skate blade of Figure 50;

5

Figure 53 shows the runner of Figure 52 with layers of fibers used for the composite material;

Figure 53A shows the runner of Figure 52 with a strip of fibers used for the composite material;

10

Figure 54 is a cross-sectional view of an ice skate blade in accordance with another embodiment of the invention;

15 Figure 55 is a cross-sectional view taken along line 55-55 of Figure 54; and

Figures 56 and 57 are side and front views of a right foot of a wearer of the ice skate with an integument of the foot shown in dotted lines and bones shown in solid lines.

20 In the drawings, embodiments of the invention are illustrated by way of example. It is to be expressly understood that the description and drawings are only for purposes of illustration and as an aid to understanding, and are not intended to be a definition of the limits of the invention.

25 **Detailed description of embodiments**

Figures 1 and 2 show an example of an ice skate 10 in accordance with an embodiment of the invention. The ice skate 10 comprises a skate boot 11 for enclosing a skater's foot, a blade holder 28, and a ice skate blade 52 for contacting an ice surface on which the skater skates. In this embodiment, the ice skate 10 is a hockey skate designed for playing ice hockey. In other embodiments, the ice skate 10 may be

30

designed for other types of skating activities. As further discussed below, the ice skate 10, including the ice skate blade holder 28, is lightweight and may provide other performance benefits to the skater (e.g., may facilitate and/or allow faster turns).

5 The skate boot 11 defines a cavity for receiving the skater's foot. With additional reference to Figures 56 and 57, the skater's foot includes toes T, a ball B, an arch ARC, a plantar surface PS, a top surface TS, a medial side MS and a lateral side LS. The top surface TS of the skater's foot is continuous with a lower portion of the skater's shin S. In addition, the skater has a heel H, an Achilles tendon AT, and an ankle A
 10 having a medial malleolus MM and a lateral malleolus LM that is at a lower position than the medial malleolus MM. The Achilles tendon AT has an upper part UP and a lower part LP projecting outwardly with relation to the upper part UP and merging with the heel H. A forefoot of the skater includes the toes T and the ball B, a hindfoot of the skater includes the heel H, and a midfoot of the skater is between the forefoot and
 15 midfoot.

In this embodiment, the skate boot 11 comprises a front portion 17 for receiving the toes T of the skater's foot, a rear portion 19 for receiving the heel H of the skater's foot, and an intermediate portion 21 between the front portion 17 and the rear portion 19.

20 More particularly, in this embodiment, the skate boot 11 comprises an outer shell 12, a toe cap 14 for facing the toes T, a tongue 16 extending upwardly and rearwardly from the toe cap 14 for covering the top surface TS of the skater's foot, a rigid insert 18 for providing more rigidity around the ankle A and the heel H of the skater's foot, an inner
 25 lining 20, a footbed 22, and an insole 24. The skate boot 11 also comprises lace members 38 and eyelets 42 punched into the lace members 38, the outer shell 12 and the inner lining 20 vis-à-vis apertures 40 in order to receive laces for tying on the skate
 10.

30 The inner lining 20 is affixed to an inner surface of the outer shell 12 and comprises an inner surface 32 intended for contact with the heel H and medial and lateral sides MS,

LS of the skater's foot and the skater's ankle A in use. The inner lining 20 is made of a soft material (e.g., a fabric made of NYLON® fibers or any other suitable fabric). The rigid insert 18 is sandwiched between the outer shell 12 and the inner lining 20 and may be affixed in any suitable way (e.g., glued to the inner surface of the outer shell 12 and stitched along its periphery to the outer shell 12). The footbed 22 is mounted inside the outer shell 12 and comprises an upper surface 34 for receiving the plantar surface PS of the skater's foot and a wall 36 projecting upwardly from the upper surface 34 to partially cup the heel H and extend up to a medial line of the skater's foot. The insole 24 has an upper surface 25 for facing the plantar surface PS of the skater's foot and a lower surface 23 on which the outer shell 12 may be affixed.

The outer shell 12 is thermoformed such that it comprises a heel portion 44 for receiving the heel H, an ankle portion 46 for receiving the ankle A, and medial and lateral side portions 50, 60 for facing the medial and lateral sides MS, LS of the skater's foot, respectively. The medial and lateral side portions 50, 60 include upper edges 51, 61 which connect to the lace members 38. The heel portion 44 may be thermoformed such that it is substantially cup shaped for following the contour of the heel H. The ankle portion 46 comprises medial and lateral ankle sides 52, 54. The medial ankle side 52 has a medial cup-shaped depression 56 for receiving the medial malleolus MM and the lateral ankle side 54 has a lateral cup-shaped depression 58 for receiving the lateral malleolus LM of the skater. The lateral depression 58 is located slightly lower than the medial depression 56, for conforming to the morphology of the skater's foot. The ankle portion 46 further comprises a rear portion 47 facing the lower part LP of the Achilles tendon AT. The rear portion 47 may be thermoformed such that it follows the lower part LP of the Achilles tendon AT. Furthermore, the skate boot 11 also includes a tendon guard 43 affixed to the rear portion 47 of the ankle portion 46 and extending upwardly therefrom.

The skate boot 11 may be constructed in any other suitable way in other embodiments. For example, in other embodiments, various components of the skate boot 11 mentioned above may be configured differently or omitted and/or the skate

boot 11 may comprise any other components that may be made of any other suitable materials and/or using any other suitable processes.

With additional reference to Figures 3 to 6, the blade holder 28 comprises an upper structure 132 facing the skate boot 11 and a lower structure 136 supporting the ice skate blade 52. As further discussed later, in this embodiment, the upper structure 132 and the lower structure 136 of the blade holder 28 define a hollow space 160 which occupies a substantial portion of the blade holder 28. This reduces a weight of the blade holder 28 and may provide additional advantages (e.g., easier and/or faster turns) as described below.

The blade holder 28 has a longitudinal axis A-A extending from a front portion 129 of the blade holder 28 to a rear portion 130 of the blade holder 28. The front portion 129 of the blade holder 28 defines a frontmost point 128' of the blade holder 28 and extends beneath and along the skater's forefoot in use, while the rear portion 130 of the blade holder 28 defines a rearmost point 128'' of the blade holder 28 and extends beneath and along the skater's hindfoot in use. A central portion 137 of the blade holder 28 is between the front and rear portions 129, 130 of the blade holder 28 and extends beneath and along the skater's midfoot in use. A length L of the blade holder 28 can be measured from the frontmost point 128' to the rearmost point 128''. The longitudinal axis A-A of the blade holder 28 defines a longitudinal direction of the blade holder 28 (i.e., a direction generally parallel to its longitudinal axis) and transversal directions of the blade holder 28 (i.e., directions transverse to its longitudinal axis), including a widthwise direction of the blade holder 28 (i.e., a lateral direction generally perpendicular to its longitudinal axis). The blade holder 28 also has a height direction normal to its longitudinal and widthwise directions.

In this embodiment, the upper structure 132 and the lower structure 136 of the blade holder 28 form an outer member 156 and an inner member 148 which is disposed between the outer member 156 and the skate boot 11. A lower void 161 of the hollow space 160 extends between the inner member 148 and the outer member

156, while an upper void 163 of the hollow space 160 extends between the inner member 148 and the skate boot 11. In this example, each of the outer member 156 and the inner member 148 is a U-shaped member (e.g., a cradle-shaped member). The inner and outer members 148, 156 may have any other suitable shape in other
 5 examples of implementation.

More particularly, in this embodiment, the upper structure 132 of the blade holder 28 comprises the U-shaped inner member 148 as well as a front member 140, a rear member 142, and an intermediate member 182 that are configured to be affixed to
 10 the skate boot 11. The front member 140 is connected to the front portion 17 of the skate boot 11 for supporting the ball B and toes T of the skater's foot, the rear member 142 is connected to the rear portion 19 of the skate boot 11 for supporting the heel H of the skater's foot, and the intermediate member 182 interconnects the front and rear members 140, 142 and extends below the arch ARC of the skater's
 15 foot.

The front, rear and intermediate members 140, 142, 182 of the upper structure 132 of the blade holder 28 form an upper surface of the blade holder 28 that faces the skate boot 11. More particularly, in this embodiment, the front, rear and intermediate
 20 members 140, 142, 182 form a single pedestal 180 which extends across substantially an entirety of the plantar surface PS of the skater's foot. In this example, the pedestal 180 formed by the front, rear and intermediate members 140, 142, 182 includes an outsole 126 to be affixed to the skate boot 11.

25 The U-shaped inner member 148 of the upper structure 132 of the blade holder 28 includes an elongated base 147 and a front arm 148₁ and a rear arm 148₂ which extend upwardly from the elongated base 147. The front arm 148₁ of the U-shaped inner member 148 extends upwardly towards a rear portion 140'' of the front member 140 and the rear arm 148₂ of the U-shaped inner member 148 extends
 30 upwardly towards a front portion 142' of the rear member 142. The elongated base

147 extends between the front and rear arms 148₁, 148₂ and, in this example, is elongated in the longitudinal direction of the blade holder 28.

5 The upper structure 132 of the blade holder 28 may be affixed to the skate boot 11 in any suitable way. For example, in this embodiment, the front, rear and intermediate members 140, 142, 182 of the upper structure 132 of the blade holder 28 may be fastened to the skate boot 11 by mechanical fasteners (e.g., rivets, screws, bolts) extending through openings 177 of these members, by an adhesive, and/or by any other fastening means.

10

The upper structure 132 of the blade holder 28 may be configured in various other ways in other embodiments.

15 The lower structure 136 of the blade holder 28 comprises an elongated blade-supporting base 157 for supporting the ice skate blade 52. The elongated blade-supporting base 157 is elongated in the longitudinal direction of the blade holder 28. More particularly, in this embodiment, the lower structure 136 comprises the U-shaped outer member 156 which includes the elongated blade-supporting base 157 and a front pillar 156₁ and a rear pillar 156₂ which extend upwardly from the
20 elongated blade-supporting base 157. The front pillar 156₁ extends towards the front portion 17 of the skate boot 11 and the rear pillar 156₂ extends towards the rear portion 19 of the skate boot 11. More specifically, in this embodiment, the front pillar 156₁ extends upwardly towards a front portion 140' of the front member 140 and the rear pillar 156₂ extends upwardly towards a rear portion 142'' of the rear member
25 142. The elongated blade-supporting base 157 extends between the front and rear pillars 156₁, 156₂.

30 The front and rear pillars 156₁, 156₂ of the U-shaped outer member 156 support the skate boot 11 and transmit forces exerted while the skater skates to the ice skate blade 52. In this embodiment, the front and rear pillars 156₁, 156₂ allow controlled

flexions of certain parts of the blade holder 28 while the skater skates that may be beneficial for the skater.

Notably, in this embodiment, with additional reference to Figure 7, the blade holder
 5 28 is responsive to a skating movement (e.g., a turning movement or a pushing movement) of the skater to undergo an elastic torsion of each of the front and rear pillars 156₁, 156₂ which induces an elastic flexion of the elongated blade-supporting base 157 and the ice skate blade 52 in the widthwise direction of the blade holder 28. That is, the blade holder 28 is configured to allow or facilitate an elastic torsion of
 10 each of the front and rear pillars 156₁, 156₂ which induces an elastic flexion of the elongated blade-supporting base 157 and the ice skate blade 52 in the widthwise direction of the blade holder 28 while the skater skates. This may be beneficial for the skater. For example, this may allow the skater to turn more easily and/or faster due to the curvature of the ice skate blade 52. As another example, this may create
 15 a spring effect, or “kickback”, in the widthwise direction of the blade holder 28 as the elongated blade-supporting base 157 and the ice skate blade 52 regain their normal (non-deflected) shape, which may help skating dynamics. The elastic torsion of a given one of the front and rear pillars 156₁, 156₂ manifests itself as a rotational deformation θ and the elastic flexion of the elongated blade-supporting base 157
 20 and the ice skate blade 52 in the widthwise direction of the blade holder 28 manifests itself as a deflection δ in the widthwise direction of the blade holder 28 in which the elongated blade-supporting base 157 and the ice skate blade 52 acquire a certain curvature (e.g., a generally parabolic curvature).

25 Also, in this embodiment, the blade holder 28 allows an elastic flexion of a central portion of the upper structure 132 of the blade holder 28 located between the front and rear pillars 156₁, 156₂, which in this example includes the U-shaped inner member 148 and the intermediate member 182, in the height direction of the blade holder 28 while the skater skates. That would manifest itself as a deflection of the
 30 central portion of the upper structure 132 in the height direction of the blade holder 28 and may also be beneficial. For instance, it may create a kickback in the height

direction of the blade holder 28, which may help with skating dynamics. For example, during a pushing action, the elongated base 147 of the U-shaped inner member 148 can approach the elongated blade-supporting base 157 of the U-shaped outer member 156, causing the hollow space 160 to temporarily change
 5 shape during compression of the blade holder 28. When the skater's pushing action ends, the U-shaped inner and outer members 148, 156 move away from one another and return to their initial position.

More particularly, in this embodiment, the front and rear pillars 156_1 , 156_2 are
 10 significantly spaced apart and relatively short in the longitudinal direction of the blade holder 28. That is, a longitudinal spacing S of the front and rear pillars 156_1 , 156_2 (i.e., a maximal distance between the front and rear pillars 156_1 , 156_2 in the longitudinal direction of the blade holder 28) is relatively large and a minimal longitudinal dimension D of a cross-section of either of the front and rear pillars 156_1 ,
 15 156_2 (i.e., a minimal dimension in the longitudinal direction of the blade holder 28 of either of the front and rear pillars 156_1 , 156_2) is relatively small.

For example, in this embodiment, the longitudinal spacing S of the front and rear pillars 156_1 , 156_2 is greater than a sum of the minimal longitudinal dimension D of
 20 each of the front and rear pillars 156_1 , 156_2 . For instance, in some embodiments, the longitudinal spacing S of the front and rear pillars 156_1 , 156_2 may be at least three times greater, in some cases at least four times greater, in some cases at least five times greater, and in some cases at least six times greater than the sum of the minimal longitudinal dimension D of each of the front and rear pillars 156_1 , 156_2 , or
 25 may be even greater. In this example, the longitudinal spacing S of the front and rear pillars 156_1 , 156_2 is about eight times greater than the sum of the minimal longitudinal dimension D of each of the front and rear pillars 156_1 , 156_2 .

As another example, in some embodiments, a ratio S/L of the longitudinal spacing S
 30 of the front and rear pillars 156_1 , 156_2 over the length L of the blade holder 28 may be at least 0.6, in some cases at least 0.7, in some cases at least 0.8, in some cases

at least 0.9, and in some cases even greater (e.g., 0.95 or more). The ratio S/L may have any other value in other embodiments.

As yet another example, in some embodiments, a ratio S/D of the longitudinal spacing S of the front and rear pillars 156_1 , 156_2 over the minimal longitudinal dimension D of one of the front and rear pillars 156_1 , 156_2 may be at least 4, in some cases at least 6, in some cases at least 8, in some cases at least 10, in some cases at least 12, in some cases at least 14, in some cases at least 16, in some cases at least 18, and in some cases even greater (e.g., 20 or more). The ratio S/D may have any other value in other embodiments.

For instance, in this embodiment, the length L of the blade holder 28 may be about 300 mm, the minimal longitudinal dimension D of each of the front and rear pillars 156_1 , 156_2 may be about 15 mm, and the longitudinal spacing S of the front and rear pillars 156_1 , 156_2 may be about 270 mm. The length L of the blade holder 28, the minimal longitudinal dimension D of each of the front and rear pillars 156_1 , 156_2 , and the longitudinal spacing S of the front and rear pillars 156_1 , 156_2 may have any other values in other embodiments.

In addition to the front and rear pillars 156_1 , 156_2 being significantly spaced apart and relatively short in the longitudinal direction of the blade holder 28, in this embodiment, at least a significant part of the blade holder 28 is free of any inter-pillar structure comparable to at least one of the front and rear pillars 156_1 , 156_2 , i.e., any structure (i) between the front and rear pillars 156_1 , 156_2 , (ii) extending downwardly to and secured at the elongated blade-supporting base 157, (iii) having a material composition corresponding to that of (i.e., made of a same material or combination of materials as) a given one of the front and rear pillars 156_1 , 156_2 , and (iv) having a minimal cross-sectional area (in a plane parallel to the longitudinal direction of the blade holder 28) corresponding to at least half of that of the given one of the front and rear pillars 156_1 , 156_2 . For example, in this embodiment, at least a front quarter and a rear quarter of the blade holder 28 (i.e., a front quarter and a rear quarter of

the length L of the blade holder 28) are free of any inter-pillar structure comparable to at least one of the front and rear pillars 156₁, 156₂. More particularly, in this embodiment, at least one of (in this case both of) a front third and a rear third of the blade holder 28 are free of any inter-pillar structure comparable to at least one of the front and rear pillars 156₁, 156₂. Specifically, in this embodiment, the blade holder 28 (i.e., an entirety of the length L of the blade holder 28) is free of any inter-pillar structure comparable to at least one of the front and rear pillars 156₁, 156₂.

Another way of viewing the blade holder 28 is that, in this embodiment, at least a significant part of the blade holder 28 is free of any inter-pillar structure substantially limiting the widthwise flexion of the elongated blade-supporting base 157, i.e., any structure (i) between the front and rear pillars 156₁, 156₂, (ii) extending downwardly to and secured at the elongated blade-supporting base 157, (iii) having a material composition corresponding to that of (i.e., made of a same material or combination of materials as) a given one of the front and rear pillars 156₁, 156₂, and (iv) reducing the widthwise deflection of the elongated blade-supporting base 157 in response to a given load by at least 10%. For example, in this embodiment, at least a front quarter and a rear quarter of the blade holder 28 (i.e., a front quarter and a rear quarter of the length L of the blade holder 28) are free of any inter-pillar structure substantially limiting the widthwise flexion of the elongated blade-supporting base 157. More particularly, in this embodiment, at least one of (in this case both of) a front third and a rear third of the blade holder 28 are free of any inter-pillar structure substantially limiting the widthwise flexion of the elongated blade-supporting base 157. Specifically, in this embodiment, the blade holder 28 (i.e., an entirety of the length L of the blade holder 28) is free of any inter-pillar structure substantially limiting the widthwise flexion of the elongated blade-supporting base 157.

As shown in Figure 8, in some embodiments, the blade holder 28 may comprise an inter-pillar structure 138 extending downwardly to and secured at the elongated blade-supporting base 157, but the inter-pillar structure 138 may not substantially limit the widthwise flexion of the elongated blade-supporting base 157. The inter-

pillar structure 138 would be deemed to substantially limit the widthwise flexion of the elongated blade-supporting base 157 if the widthwise deflection of the elongated blade-supporting base 157 in response to a given load was at least 10% greater if the inter-pillar structure 138 was severed but the blade holder 28 was otherwise identical. Otherwise, it would be deemed that the inter-pillar structure 138 does not substantially limit the widthwise flexion of the elongated blade-supporting base 157. It can thus be determined whether the inter-pillar structure 138 substantially limits the widthwise flexion of the elongated blade-supporting base 157 by (1) measuring the deflection of the elongated blade-supporting base 157 in response to a given load applied at a given point on the elongated blade-supporting base 157 in the widthwise direction of the blade holder 28, (2) severing (e.g., cutting through) the inter-pillar structure 138 but keeping the blade holder 28 otherwise identical, and (3) measuring the deflection of the elongated blade-supporting base 157 in response to the given load applied at the given point on the elongated blade-supporting base 157 in the widthwise direction of the blade holder 28 after the inter-pillar structure 138 has been severed. If the deflection of the elongated blade-supporting base 157 with the inter-pillar structure 138 severed is at least 10% greater than the deflection of the elongated blade-supporting base 157 with the inter-pillar structure 138 intact, the inter-pillar structure 138 is deemed to substantially limit the widthwise flexion of the elongated blade-supporting base 157; otherwise, it is deemed that the inter-pillar structure 138 does not substantially limit the widthwise flexion of the elongated blade-supporting base 157.

Referring back to Figures 3 to 6, in this embodiment, at least a significant part of the blade holder 28 is free of any inter-pillar structure (i.e., any structure between the front and rear pillars 156₁, 156₂) extending downwardly to and secured at the elongated blade-supporting base 157. For example, in this embodiment, at least a front quarter and a rear quarter of the blade holder 28 are free of any inter-pillar structure extending downwardly to and secured at the elongated blade-supporting base 157. More particularly, in this embodiment, at least one of (in this case both of) a front third and a rear third of the blade holder 28 are free of any inter-pillar

structure extending downwardly to and secured at the elongated blade-supporting base 157. Specifically, in this embodiment, the blade holder 28 (i.e., an entirety of the length L of the blade holder 28) is free of any inter-pillar structure extending downwardly to and secured at the elongated blade-supporting base 157.

5

In this embodiment, therefore, the elongated blade-supporting base 157 is suspended only by the front and rear pillars 156₁, 156₂. The lower void 161 of the hollow space 160 extends from the front pillar 156₁ to the rear pillar 156₂. There is no structure extending upwardly from the U-shaped inner member 148 to the U-shaped outer member 156 between the front and rear pillars 156₁, 156₂. This may help to maximize an effect of the elastic flexion of the elongated blade-supporting base 157 and the ice skate blade 52 in the widthwise direction of the blade holder 28 while the skater skates, such as easier and/or faster turns and/or a transversal kickback, as discussed above. This may also help to maximize an effect of the elastic flexion of the central portion of the upper structure 132 of the blade holder 28 located between the front and rear pillars 156₁, 156₂, which in this example includes the U-shaped inner member 148 and the intermediate member 182, in the height direction of the blade holder 28 while the skater skates, such as a vertical kickback as previously mentioned.

20

The hollow space 160 of the blade holder 28 may be configured in various ways. For example, in this embodiment, the lower void 161 of the hollow space 160, which extends between the U-shaped inner and outer member 148, 156, is U-shaped. That is, each of a front region 171 and a rear region 173 of the lower void 161 has a greater height than an intermediate region 175 of the void 161. In this example of implementation, the front region 171 of the lower void 161 occupies most of a length and a height of the front portion 129 of the blade holder 28, which generally extends beneath and along the skater's forefoot in use. Similarly, the rear region 173 of the lower void 161 occupies most of a length and a height of the rear portion 130 of the blade holder 28, which extends beneath and along the skater's hindfoot in use. Also, in this embodiment, the upper void 163 of the hollow space 160 tapers in the

longitudinal direction of the blade holder 28. Specifically, in this example, the upper void 163 tapers towards the front portion of the blade holder 28. The hollow space 160 may have any other suitable configuration in other embodiments.

5 A void of the hollow space 160 of the blade holder 28, such as the lower void 161 or the upper void 163, extends in the longitudinal direction of the blade holder 28 from a given one of the front and rear pillars 156₁, 156₂ for at least a substantial portion of the longitudinal spacing S of the front and rear pillars 156₁, 156₂. For example, in some embodiments, a void of the hollow space 160 may extend in the longitudinal
10 direction of the blade holder 28 from a given one of the front and rear pillars 156₁, 156₂ for at least one-quarter of the longitudinal spacing S of the front and rear pillars 156₁, 156₂, in some cases at least one-third of the longitudinal spacing S of the front and rear pillars 156₁, 156₂, in some cases at least one half of the longitudinal spacing S of the front and rear pillars 156₁, 156₂, and in some cases even more. In
15 this embodiment, the lower void 161 of the hollow space 160 extends in the longitudinal direction of the blade holder 28 from the front pillar 156₁ to the rear pillar 156₂, i.e., for an entirety of the longitudinal spacing S of the front and rear pillars 156₁, 156₂.

20 The hollow space 160 of the blade holder 28, which is substantial, thus helps to reduce the weight of the blade holder 28 and may facilitate the elastic widthwise flexion of the elongated blade-supporting base 157 and the ice skate blade 52 and/or the elastic vertical flexion of the central portion of the upper structure 132 of the blade holder 28 while the skater skates, as discussed above.

25 The blade holder 28 can be made of any suitable material. In this embodiment, with additional reference to Figure 9, the blade holder 28 is at least mainly (i.e., mainly or entirely) made of a composite material 186. More particularly, in this embodiment, the composite material 186 is a fiber-matrix composite material that comprises a
30 matrix 187 in which fibers 189₁-189_F are embedded.

The matrix 187 may include any suitable substance. In this embodiment, the matrix 187 is a polymeric matrix. For example, the polymeric matrix 187 may include any other suitable polymeric resin, such as a thermosetting polymeric material (e.g., polyester, vinyl ester, vinyl ether, polyurethane, epoxy, cyanate ester, phenolic resin, etc.), a thermoplastic polymeric material (e.g., polyethylene, polypropylene, acrylic resin, polyether ether ketone (PEEK), polyethylene terephthalate (PET), polyvinyl chloride (PVC), poly(methyl methacrylate) (PMMA), polycarbonate, acrylonitrile butadiene styrene (ABS), nylon, polyimide, polysulfone, polyamide-imide, self-reinforcing polyphenylene, etc.), or a hybrid thermosetting-thermoplastic polymeric material.

The fibers 189₁-189_F may be made of any suitable material. In this embodiment, the fibers 189₁-189_F are carbon fibers. The composite material 186 is thus a carbon-fiber-reinforced plastic in this example of implementation. Any other suitable type of fibers may be used in other embodiments (e.g., polymeric fibers such as aramid fibers (e.g., Kevlar fibers), boron fibers, silicon carbide fibers, metallic fibers, glass fibers, ceramic fibers, etc.).

In this embodiment, respective ones of the fibers 189₁-189_F that are located in the U-shaped outer member 156 are oriented to be in tension when the elongated blade-supporting base 157 and the ice skate blade 52 are deflected by the deflection δ in the widthwise direction of the blade holder 28 due to the elastic flexion of the elongated blade-supporting base 157 and the ice skate blade 52 in the widthwise direction of the blade holder 28. This fiber tension tends to force the elongated blade-supporting base 157 and the ice skate blade 52 back into their normal (non-deflected) shape, thereby enhancing the kickback in the widthwise direction of the blade holder 28.

For example, in this embodiment, respective ones of the fibers 189₁-189_F that are located in the U-shaped outer member 156 extend in a direction having at least a component parallel to a longitudinal axis O-O of the U-shaped outer member 156. In

other words, respective ones of the fibers 189₁-189_F that are located in the U-shaped outer member 156 extend parallel or at an oblique angle to the longitudinal axis O-O of the U-shaped outer member 156. For instance, in some embodiments, an angle β between a fiber 189_x located in the U-shaped outer member 156 and the longitudinal axis O-O of the U-shaped outer member 156 may be from 0° (parallel) to 45°.

More particularly, in this embodiment, at least a majority of the fibers 189₁-189_F that are located in the elongated blade-supporting base 157 of the U-shaped outer member 156 extend parallel or at an oblique angle to the longitudinal axis O-O of the U-shaped outer member 156 in the elongated blade-supporting base 157. In this example of implementation, a totality of the fibers 189₁-189_F that are located in the elongated blade-supporting base 157 of the U-shaped outer member 156 extend parallel or at an oblique angle to the longitudinal axis O-O of the U-shaped outer member 156 in the elongated blade-supporting base 157.

The fibers 189₁-189_F may be arranged in any other suitable manner in other embodiments.

In order to further reduce the weight of the blade holder 28, in this embodiment, each of the U-shaped inner and outer members 148, 156 is hollow. That is, each of the U-shaped inner and outer members 148, 156 comprises an external wall 190 defining a cavity 191 which is empty. More particularly, in this embodiment, each of the U-shaped inner and outer members 148, 156 is a tubular member having an external surface 170 and an internal surface 172. The external wall 190 extends from the external surface 170 to the internal surface 172, while the cavity 191 is delimited by the internal surface 172. In this case, the cavity 191 of each of the U-shaped inner and outer members 148, 156 opens into a cavity 194 of each of the front and rear members 140, 142 of the upper structure 132 of the blade holder 28.

30

The U-shaped inner and outer members 148, 156 may have any suitable cross-sectional shape. For example, in this embodiment, the U-shaped inner member 148 has a cross-sectional shape that is oblong in the widthwise direction of the blade holder 28. The U-shaped outer member 156 has a cross-sectional shape that is generally trapezoidal, tapering downwardly, and shorter than the cross-sectional shape of the U-shaped inner member 148 in the widthwise direction of the blade holder 28. Also, in this embodiment, the cross-sectional shape of each of the U-shaped inner and outer members 148, 156 is substantially uniform over that member's length.

10

The blade holder 28 can be manufactured in any suitable manner using various processes. In this embodiment, the blade holder 28 is a one-piece molded blade holder made by a molding process. More particularly, in this embodiment, a plurality of layers of fibers, which are destined to provide the fibers 189_I-189_F of the blade holder 28, are layered onto one another on a support which is then placed in a mold to consolidate the composite material 186 of the blade holder 28. In this example, each of these layers of fibers is provided as a pre-preg (i.e., pre-impregnated) layer of fibers held together by an amount of matrix material, which is destined to provide a respective portion of the matrix 187 of the blade holder 28. Also, in this example, the support comprises one or more inflatable bladders (e.g., air bladders) on which the pre-preg layers are layered such that the one or more inflatable bladders can be inflated to define the external wall 190 and the cavity 191 of each of the U-shaped inner and outer members 148, 156 during molding in the mold. The support may also comprise one or more other components (e.g., silicone mold parts) on which the pre-preg layers may be layered to form other parts of the blade holder 28 (e.g., the front and rear members 140, 142 of the upper structure 132 of the blade holder 28) during molding in the mold. Various other manufacturing methods may be used to make the blade holder 28 in other embodiments.

30 With additional reference to Figures 10 and 11, the ice skate blade 52 may comprise a runner or strip 125 that is at least mainly made of an ice-contacting material 131

and comprises an ice-contacting surface 127 for sliding on the ice while the skater skates. The ice skate blade 52 may be constructed in any suitable way. In one embodiment, an entirety of the runner 125 of the ice skate blade 52 is made of the ice-contacting material 131. In this example of implementation, the ice-contacting material 131 is a metallic material (e.g., stainless steel). The ice skate blade 52 may be implemented in various other manners in other embodiments. The ice skate blade 52 can be attached to the blade holder 28 in any suitable way. For example, the elongated blade-supporting base 157 of the blade holder 28 comprises a bottom blade-attaching portion 135 for attaching the ice skate blade 52. More particularly, the bottom blade-attaching portion 135 is configured to fit and be adhesively retained in a recess 178 of the ice skate blade 52. Any suitable adhesive may be used to retain the ice skate blade 52 to the bottom blade-attaching portion 135 of the blade holder 28 (e.g., an epoxy-based adhesive, a polyurethane-based adhesive, etc.).

The runner 125 and the blade body may be retained together in various ways. For example, the runner 125' may be adhesively affixed. Any suitable adhesive may be used to affix the runner 125 (e.g., an epoxy-based adhesive, a polyurethane-based adhesive, etc.). As another example, in addition to or instead of being adhesively fastened, the runner 125 may be fastened using one or more mechanical fasteners (e.g., rivets, screws, etc.). In other embodiments, the runner 125 and the blade body may be mechanically interlocked via a plurality of interlocking portions of one of the runner and the blade body that extend in a plurality of interlocking openings of the other one of the runner and the blade body (e.g., the blade body may be overmolded onto the runner 125).

25

The ice skate 10, including the blade holder 28, may be constructed in various other ways in other embodiments.

For instance, in other embodiments, the U-shaped inner and outer members 148, 156 may be shaped in various other ways. For example, the U-shaped inner and outer members 148, 156 may have any other desired cross-sectional shape. Figure

12 shows an embodiment in which the U-shaped outer member 156 has a cross-sectional shape that is generally circular. As another example, the cross-sectional shape of the U-shaped inner member 148 or the U-shaped outer member 156 may vary along that member's length. Figures 13A to 14F show embodiments in which
5 the cross-sectional shape of the elongated blade-supporting base 157 of the U-shaped outer member 156 varies in width and/or height.

While in this embodiment the minimal longitudinal dimension D of each of the front and rear pillars 156₁, 156₂ of the U-shaped outer member 156 is substantially
10 identical, the minimal longitudinal dimension D the front pillar 156₁ may be substantially different from (i.e., larger or smaller than) the minimal longitudinal dimension D of the rear pillar 156₂.

Instead of being empty as in embodiments considered above, in other embodiments,
15 as shown in Figures 15 and 16, the cavity 191 of at least one, in this case both, of the U-shaped inner and outer members 148, 156 may contain internal material 181. More particularly, in this embodiment, the internal material 181 includes a filler 120 that fills at least part of the cavity 191. In this example of implementation, the filler 120 is foam. This may help to improve impact resistance and/or absorb vibrations
20 while the skater skates. For instance, the foam 120 may be polystyrene (PS) foam, polyurethane (PU) foam, ethylene vinyl acetate (EVA) foam, polypropylene (PP) foam, polyethylene (PE) foam, vinyl nitrile (VN) foam, or any other suitable foam. In some examples of implementation, the foam 120 may have been pre-molded to form an internal frame of the blade holder 28 over which the composite material 186 may
25 subsequently be molded. For instance, in some cases, instead of using an inflatable bladder as discussed above, the internal frame formed by the pre-molded foam 120 may constitute at least part of the support onto which the pre-preg layers of fibers are layered to mold the composite material 186. In other examples of implementation, the foam 120 may be injected into the cavity 191 after the
30 composite material 186 has been molded.

In some embodiments, as shown in Figures 17 and 18, the internal material 181 contained in the cavity 191 of at least one of the U-shaped inner and outer members 148, 156, in this case only the U-shaped outer member 156, may include a reinforcement 121 along with the filler 120 to reinforce that member. In this
5 embodiment, the reinforcement 121 is embedded in the filler 120. More particularly, in this example of implementation, the reinforcement 121 is a beam extending along the U-shaped outer member 156 and made of a material stiffer than the foam 120. In this case, the beam 121 is made of carbon fiber. The reinforcement 121 may be configured in various other ways in other embodiments (e.g., may be made of any
10 other suitable material, have any other suitable shape, extend along a shorter extent of the U-shaped outer member 156, etc.).

Instead of being provided only in the cavity 191 of each of the U-shaped inner and outer members 148, 156, in other embodiments, the internal material 181 may also
15 occupy the cavity 194 of each of the front and rear members 140, 142 of the upper structure 132 of the blade holder 28 such that it substantially occupies an entirety of a hollow space defined by the composite material 186 of the blade holder 28. For example, in some cases, as shown in Figures 35 and 36, the internal material 181 may thus be pre-molded into an internal frame 199 providing the support onto which
20 the pre-preg layers of fibers are layered to mold the composite material 186 of the entire blade holder 28.

In some embodiments, at least part (e.g., some or all) of the internal material 181 may be removed after the composite material 186 has been molded to leave empty
25 at least part of the cavity 191 of each of the U-shaped inner and outer members 148, 156 and/or of the cavity 194 of each of the front and rear members 140, 142 of the upper structure 132 of the blade holder 28. For example, in some embodiments, at least part of the internal material 181 may be dissolved by a solvent. For instance, in this embodiment in which the internal material 181 includes foam, the solvent may
30 be acetone. Any other suitable solvent may be used in other embodiments.

In other embodiments, the ice skate blade 52 can be attached to the blade holder 28 in various other manners. For example, in some embodiments, as shown in Figure 19, the elongated blade-supporting base 157 of the blade holder 28 may comprise a recess 159 to receive an upper part of the ice skate blade 52, which can be adhesively retained in the recess 159. As another example, instead of or in addition to using an adhesive, in some embodiments, the ice skate blade 52 and the elongated blade-supporting base 157 of the blade holder 28 may be retained together by one or more mechanical fasteners (e.g., rivets, screws, bolts, etc.). As yet another example, in some embodiments, as shown in Figure 20, the ice skate blade 52 and the elongated blade-supporting base 157 of the blade holder 28 may be mechanically interlocked via an interlocking portion 184 of one of the elongated blade-supporting base 157 and the ice skate blade 52 that extends into an interlocking void 183 of the other one of the elongated blade-supporting base 157 and the ice skate blade 52. For instance, the ice skate blade 52 can be positioned in a mold used for molding the blade holder 28 such that, during molding, an interlocking portion 184 of the material of the elongated blade-supporting base 157 flows into the interlocking void 183 of the ice skate blade 52 (i.e., the blade holder 28 is overmolded onto the blade 52).

While in some embodiments the ice skate blade 52 may be permanently attached to the blade holder 28, in other embodiments, as shown in Figures 21A to 21C, the blade holder 28 may comprise a blade-detachment mechanism 195 such that the ice skate blade 52 is detachable and removable from the blade holder 28 (e.g., when the ice skate blade 52 is worn out or otherwise needs to be replaced or removed from the blade holder 28). In this embodiment, the ice skate blade 52 includes a plurality of projections, including a front projection 52^F and a rear projection 52^R, the rear projection having a “hook” shape. The blade-detachment mechanism 195 includes an actuator 196 and biasing members 197 which bias the actuator 196 in a direction towards the front portion 129 of the blade holder 28. To position the ice skate blade 52 onto the blade holder 28, the front projection 52^F is first positioned within a corresponding depression (or hole) on the blade holder 28 (see Figure 21A).

The rear projection 52^R can then be pushed upwardly, thereby causing the biasing members 197 to bend and the actuator 196 to move in a rearward direction (see Figure 21B). The rear projection 52^R will eventually reach a position which will allow the biasing members 197 to force the actuator 196 towards the front portion 129 of the blade holder 28, thereby locking the ice skate blade 52 in place (see Figure 21C). The ice skate blade 52 can then be removed by pushing against a finger actuating surface 198 on the actuator 196 to release the rear projection 52^R from its corresponding depression (or hole) on the blade holder 28. The blade-detachment mechanism 195 may be configured in various other ways in other embodiments.

10

In some embodiments, as shown in Figure 22, the blade holder 28 may comprise a resilient element 150 disposed between its upper structure 132 and its lower structure 136 and resiliently deformable (i.e., configured to change in shape under load and subsequently recover its original shape) while the skater skates. In this embodiment, the resilient element 150 is a damper to dampen vibrations in the blade holder 28 while the skater skates. Notably, in this example, the resilient element 150 dampens vibrations due to the elastic flexion of the elongated blade-supporting base 157 of the U-shaped outer member 156 while the skater skates. This absorption of vibrations may also help to reduce noise generated by the blade holder 28 while the skater skates.

20

In this embodiment, the resilient element 150 extends upwardly from the U-shaped outer member 156. More particularly, in this embodiment, the resilient element 150 extends from the U-shaped outer member 156 to the U-shaped inner member 148. The resilient element 150 is positioned between the elongated blade-supporting base 157 of the U-shaped outer member 156 and the elongated base 147 of the U-shaped inner member 148. More specifically, the resilient element 150 is positioned in the central arch-underlying portion 166 of the blade holder 28 and engages with the external surfaces 170 of the U-shaped inner and outer members 148, 156. As such, in addition to its vibration absorption capability, the resilient element 150 may also be used to adjust a degree of movement permitted between the U-shaped inner

25

30

and outer members 148, 156, in the widthwise direction and/or the height direction of the blade holder 28.

The resilient element 150 can be implemented in any suitable way. For example, in
5 this embodiment, the resilient element 150 comprises a cushion 151 (i.e., an elastic
body) for reducing vibrations. More particularly, in this embodiment, the cushion 151
is made of an elastic material (i.e., a material capable of recovering size and shape
after deformation) different from the composite material 186 of the blade holder 28.
The elastic material of the cushion 151 may be relatively soft. For instance, in this
10 embodiment, the elastic material of the cushion 151 may have a hardness of no
more than 95 durometers Shore A. The hardness of the elastic material of the
cushion 151 may have any other suitable value in other embodiments. In this
example of implementation, the elastic material of the cushion 151 is polyurethane.
Any other suitable elastic material may be used for the cushion 151 in other
15 examples of implementation (e.g., rubber, thermoplastic elastomer, foam, etc.)

The resilient element 150 can be secured between the upper structure 132 and the
lower structure 136 of the blade holder 28 in any suitable way. For example, in this
embodiment, the resilient element 150 is adhesively secured to each of the U-
20 shaped inner and outer members 148, 156 by an adhesive at these members'
respective interfaces. In other embodiments, the resilient element 150 may be
secured to one or both of the U-shaped inner and outer members 148, 156 by one or
more mechanical fasteners (e.g., rivets, screws, bolts, etc.).

25 In this embodiment, the resilient element 150 is shaped as a graphical element that
conveys information to an observer. For example, in this embodiment, the resilient
element 150 is configured as a word (i.e. a combination of characters, in this case
"ABCD") which may be associated with a brand of the blade holder 28 and/or the ice
skate 10. In other embodiments, the resilient element 150 may be shaped as a logo
30 or any other graphical element associated with a team of the skater or a brand of the
blade holder 28 and/or the ice skate 10, or as any other desired graphical element.

The resilient element 150 can be constructed in various other manners in other embodiments. For example, in some embodiments, as shown in Figures 23A to 23G, the resilient element 150 may comprise at least one thin flexible arm 152 that
5 extends from the U-shaped outer member 156 to the U-shaped inner member 148 and bends when the U-shaped inner and outer members 148, 156 move relative to one another. In such embodiments, the thin flexible arm 152 may be made of the composite material 186 of the blade holder 28 or of a different material.

10 While in embodiments considered above the resilient element 150 is permanently secured to the U-shaped inner and outer members 148, 156, in other embodiments, as shown in Figures 24A to 24C, the resilient element 150 may be attachable to and detachable from the blade holder 28. This may allow a customization of the blade holder 28 by allowing the skater to use or not use the resilient element 150 and/or
15 use a selected one of a plurality of different resilient elements like the resilient element 150 which have different properties. For instance, in this embodiment, the resilient element 150 comprises a pair of cushions 158₁, 158₂ that can be retained on respective sides of a centerline bisecting the U-shaped inner and outer members 148, 156 by a mechanical fastener (e.g., a screw, a bolt, a clamp, etc.).

20

In some embodiments, as shown in Figure 25, the blade holder 28 may comprise an inter-pillar structure 162 between the front and rear pillars 156₁, 156₂ and extending downwardly to and secured at the elongated blade-supporting base 157 of the U-shaped outer member 156. More particularly, in this embodiment, the inter-pillar
25 structure 162 comprises a plurality of ribs 149₁, 149₂ which extend downwardly from the U-shaped inner member 148 to the U-shaped outer member 156. In this example, each of the ribs 149₁, 149₂ has a similar construction to the U-shaped inner and outer members 148, 156 (i.e., each of the ribs 149₁, 149₂ is made of the same composite material as the U-shaped inner and outer members 148, 156). In
30 fact, in this example, the ribs 149₁, 149₂ are molded with the U-shaped inner and outer members 148, 156 during molding of the blade holder 28.

The inter-pillar structure 162 may be implemented in any other suitable way in other embodiments. For example, in other embodiments, the inter-pillar structure 162 may comprise a different number of ribs similar to ribs 149₁, 149₂ to connect the U-shaped inner and outer members 148, 156 (i.e., a single rib or more than two ribs).
5 As another example, while the ribs 149₁, 149₂ are shown to extend in a direction almost perpendicular to the longitudinal axis A-A of the blade holder 28, a rib similar to ribs 149₁, 149₂ may extend in any direction in other embodiments. As yet another example, in other embodiments, the ribs 149₁, 149₂ may be made of a different
10 material than the U-shaped inner and outer members 148, 156 and/or may be full.

The blade holder 28 may have any other desirable configuration in other embodiments.

15 For example, in some embodiments, as shown in Figures 26 to 28, the upper structure 132 of the blade holder 28 comprises the U-shaped inner member 148 as well as the front member 140 and the rear member 142 that are configured to be affixed to the skate boot 11, but is free of an intermediate member (such as intermediate member 182) extending between the front and rear members 140, 142
20 and affixed to the skate boot 11. The front member 140 is connected to the front portion of the skate boot 11 for supporting the ball B and toes T of the skater's foot F and the rear member 142 is connected to the rear portion of the skate boot 11 for supporting the heel H of the skater's foot F. With the U-shaped inner member 148 being located in between and generally lower than the front and rear members 140,
25 142, the front and rear members 140, 142 form upper surfaces of front and rear pedestals 139, 141 of the blade holder 28.

As another example, in some embodiments, as shown in Figure 29, the upper structure 132 of the blade holder 28 comprises the front member 140, the rear
30 member 142 and the intermediate member 182 that are configured to be affixed to the skate boot 11, but is free of a U-shaped inner member like the U-shaped inner

member 148. In other embodiments, as shown in Figure 30, the upper structure 132 of the blade holder 28 comprises the front member 140 and the rear member 142 that are configured to be affixed to the skate boot 11, but is free of a U-shaped inner member like the U-shaped inner member 148.

5

While in certain embodiments considered above the upper structure 132 of the blade holder 28 includes the outsole 126 to be affixed to the skate boot 11, in other embodiments, as shown in Figure 31, the skate boot 11 may itself include an outsole 55. The outsole 55 of the skate boot 11 includes an upper surface 28 on which the
10 outer shell 12 may be affixed and a lower surface 27 on which the blade holder 28 is mounted.

The blade holder 28 may be made using any other suitable manufacturing process in other embodiments. For example, in other embodiments, the blade holder 28 may
15 be formed as a single piece via compression molding or injection molding. In other embodiments, the blade holder 28 may be formed of two separate pieces that are pressed onto either side of the ice skate blade 52 and affixed to one another via any appropriate fastening means (e.g., rivets, screws, adhesive, heat-melt welding, etc.).

20 In some embodiments, certain parts of the skate boot 11 may be integrally molded with the blade holder 28. For example, in some embodiments, as shown in Figure 32, instead of the skate boot 11 having the toe cap 14 separately affixed, a toe cap 314 of the skate boot 11 may be integrally molded with the blade holder 28 such that the blade holder 28 and the toe cap 314 constitute a one-piece molded component.

25 As another example, in some embodiments, as shown in Figure 33, instead of the outer shell 12 of the skate boot 11 having been manufactured separately from the blade holder 28, an outer shell 312 of the skate boot 11 may be integrally molded with the blade holder 28 such that the blade holder 28 and the outer shell 312 constitute a one-piece molded component. As yet another example, in some
30 embodiments, as shown in Figure 34, an outer shell 412 and a toe cap 414 of the skate boot 11 may be integrally molded with the blade holder 28 such that the blade

holder 28, the outer shell 412 and the toe cap 414 constitute a one-piece molded component.

Referring to Figures 37 to 41, a blade holder in accordance with a further embodiment is identified at numeral 500. The blade holder 500 comprises a U-shaped inner member 502 and a U-shaped outer member 504 spaced from the U-shaped inner member 502 to define a void or hollow space 506 between the U-shaped inner member 502 and the U-shaped outer member 504.

10 The blade holder 500 also comprises a front member 508 defining a front peripheral wall 510 with an upper surface 512 for facing a bottom portion of the front portion 17 of the skate boot 11 and a rear member 514 defining a rear peripheral wall 516 with an upper surface 518 for facing a bottom portion of the rear portion 19 of the skate boot 11. As best seen in Figure 38, each of the front and rear peripheral walls 510, 15 516 of the front and rear members 508, 514 comprises apertures 519 for affixing the blade holder 500 to the bottom portion of the front and rear portions 17, 19 of the skate boot 11. As it is well known in the art, rivets may pass in the apertures 519 for affixing the blade holder 500 to the skate boot 11.

20 The blade holder 500 also comprises an intermediate member 520 extending between the front and rear members 508, 514, the intermediate member 520 having an upper surface 522 for facing a bottom portion of the skate boot 11 between the front and rear portions 17, 19. The front and rear peripheral walls 510, 516 of the front and rear members 508, 514 and the intermediate member 520 define a 25 pedestal for facing the bottom portion of the skate boot 11. Instead of being integrally formed with the front and rear members 508, 514 of the blade holder 500, in another embodiment, the intermediate member may be a separate component that is affixed to the bottom portion of the skate boot.

30 The U-shaped inner member 502 comprises an elongated portion 524, a front portion 526 extending upwardly from the elongated portion 524 and having an upper

end 528 integrally formed with the front member 508 and a rear portion 530 extending upwardly from the elongated portion 524 and having an upper end 532 integrally formed with the rear member 514.

- 5 The U-shaped outer member 504 comprises an elongated blade-supporting base 534, a front pillar 536 and a rear pillar 538. The front and rear pillars 536, 538 are spaced apart in the longitudinal direction of the blade holder 500. The front pillar 536 extends from the elongated blade-supporting base 534 towards the front portion 17 of the skate boot 11 (towards the front portion of the front member 508) and the rear
- 10 pillar 538 extends from the elongated blade-supporting base 534 towards the rear portion 19 of the skate boot 11 (towards the rear portion of the rear member 514). The front pillar 536 has an upper end 540 integrally formed with the front member 508 and the rear pillar 538 has an upper end 542 integrally formed with the rear member 514. The elongated blade-supporting base 534 extends from the front pillar
- 15 536 to the rear pillar 538.

The elongated portion 524 of the U-shaped inner member 502 overlaps a portion of the elongated blade-supporting base 534 and is spaced apart from the elongated blade-supporting base 534. In another embodiment, the elongated portion of the U-

20 shaped inner member may rather contact the elongated blade-supporting base 534.

The hollow space 506 of the blade holder 500 may be configured in various ways. For example, the hollow space 506 may be defined by a front hollow region 540, an intermediate hollow region 542 and a rear hollow region 544, which together extend

25 between the U-shaped inner member 502 and the U-shaped outer member 504 and define the U-shaped hollow region or space 506. That is, each of the front hollow region 540 and the rear hollow region 544 of the hollow space 506 has a greater height than the intermediate hollow region 542 of the hollow space 506.

- 30 In this embodiment, the front hollow region 540 of the hollow space 506 occupies most of a length and a height of the front portion of the blade holder 500, which

generally extends beneath and along the skater's forefoot in use. Similarly, the rear hollow region 544 of the hollow space 506 occupies most of a length and a height of the rear portion of the blade holder 500, which extends beneath and along the skater's hindfoot in use. The hollow space 506 may have any other suitable
5 configuration in other embodiments.

The blade holder 500 may also comprise a resilient element 546 disposed between the elongated portion 524 of the U-shaped inner member 502 and the elongated blade-supporting base 534 of the U-shaped outer member 504. The resilient
10 element 546 is configured to deform (i.e., configured to change in shape under load and subsequently recover its original shape) when the U-shaped inner member 502 and the U-shaped outer member 504 move relative to each other while the skater skates.

15 The resilient element 546 may be a damper to dampen vibrations in the blade holder 500 while the skater skates. Notably, in this example, the resilient element 546 dampens vibrations due to the elastic flexion of the elongated blade-supporting base 534 of the U-shaped outer member 504 while the skater skates. This absorption of vibrations may also help to reduce noise generated by the blade holder 500 while
20 the skater skates.

In addition to its vibration absorption capability, because the resilient element 546 is disposed between the elongated portion 524 of the U-shaped inner member 502 and the elongated blade-supporting base 534, it may also be used to adjust a degree of
25 movement permitted between the U-shaped inner and outer members 502, 504, in the widthwise direction and/or the height direction of the blade holder 500.

The resilient element 546 may comprise a cushion (i.e., an elastic body) for reducing vibrations. The resilient element 546 may be made of an elastic material (i.e., a
30 material capable of recovering size and shape after deformation) different from the fiber-matrix composite material of the blade holder 500. The elastic material of the

resilient element 546 may be relatively soft. For instance, the elastic material of the resilient element 546 may have a hardness of no more than 95 durometers Shore A. The hardness of the elastic material of the resilient element 546 may have any other suitable value in other embodiments. The resilient element 546 may be made of
5 polyurethane. Any other suitable elastic material may be used in other examples of implementation (e.g., rubber, thermoplastic elastomer, foam, etc.)

The resilient element 546 may be associated with a brand of the blade holder 546 and/or the ice skate 10. In other embodiments, the resilient element 546 may be
10 shaped as a logo or any other graphical element associated with a team of the skater or a brand of the blade holder 500 and/or the ice skate 10, or as any other desired graphical element.

The resilient element 546 can be secured between the elongated portion 524 of the
15 U-shaped inner member 502 and the elongated blade-supporting base 534 in any suitable way. For example, the resilient element 546 may be permanently secured to the elongated portion 524 of the U-shaped inner member 502 and the elongated blade-supporting base 534. In other embodiments, the resilient element 546 may be attachable to and detachable from the blade holder 500. More particularly, as best
20 seen in Figures 39 to 41, the elongated portion 524 of the U-shaped inner member 502 may comprise a recess or groove 548 for receiving a projection 550 provided on the upper portion of the resilient element 546 and the elongated blade-supporting base 534 may comprise a plurality of indentations or depressions 552 for receiving pegs or projections 554 provided on the bottom portion of the resilient element 546.
25 This may allow a customization of the blade holder 500 by allowing the skater to use or not use the resilient element 546 and/or use a selected one of a plurality of different resilient elements like the resilient element 546 which have different properties.

30 The elongated blade-supporting base 534 also comprises a bottom blade portion 556 extending downwardly therefrom and the blade holder 500 also comprises an

ice skate blade 558 having a top portion mounted or affixed to the bottom blade portion 556 and a bottom portion defining an ice-contacting surface 560. The ice skate blade 558 may be made of a strip that is at least partially made of metal (e.g. stainless steel, carbon steel, tungsten carbide or titanium), of a strip of engineering
 5 plastic or a strip that is at least partially made of ceramic material (e.g. aluminum titanate, aluminum zirconate, sialon, silicon nitride, silicon carbide, zirconia and partially stabilized zirconia or a combination of two or more of these materials).

At least part of the elongated blade-supporting base 534, front pillar 536, rear pillar
 10 538, U-shaped inner member 502, front member 508, rear member 514 and intermediate member 520 is made of a composite material. For example, the composite material may be a fiber-matrix composite material that comprises a matrix 562 in which fibers 564₁-564_F are embedded.

15 The matrix 562 may include any suitable substance. In this embodiment, the matrix 562 is a polymeric matrix. For example, the polymeric matrix 562 may include any other suitable polymeric resin, such as a thermosetting polymeric material (e.g., polyester, vinyl ester, vinyl ether, polyurethane, epoxy, cyanate ester, phenolic resin, etc.), a thermoplastic polymeric material (e.g., polyethylene, polypropylene, acrylic
 20 resin, polyether ether ketone (PEEK), polyethylene terephthalate (PET), polyvinyl chloride (PVC), poly(methyl methacrylate) (PMMA), polycarbonate, acrylonitrile butadiene styrene (ABS), nylon, polyimide, polysulfone, polyamide-imide, self-reinforcing polyphenylene, etc.), or a hybrid thermosetting-thermoplastic polymeric material.

25

The fibers 564₁-564_F may be made of any suitable material. In this embodiment, the fibers 564₁-564_F are carbon fibers. The composite material is thus a carbon-fiber-reinforced plastic in this example of implementation. Any other suitable type of fibers may be used in other embodiments (e.g., polymeric fibers such as graphite fibers,
 30 carbon graphite fibers, aramid fibers (e.g., Kevlar fibers), boron fibers, silicon carbide fibers, ceramic fibers, metallic fibers, glass fibers, polypropylene fibers, etc.).

In one embodiment, respective ones of the fibers 564₁-564_F that are located in the elongated blade-supporting base 534 (and its bottom blade portion 556) are oriented to be in tension when the elongated blade-supporting base 534 and the ice skate blade 558 are deflected by the deflection in the widthwise direction of the blade holder 500 due to the elastic flexion of the elongated blade-supporting base 534 (including its bottom blade portion 556) and the ice skate blade 558 in the widthwise direction of the blade holder 500. This fiber tension tends to force the elongated blade-supporting base 534 (including its bottom blade portion 556) and the ice skate blade 558 back into their normal (non-deflected) shape, thereby enhancing the kickback in the widthwise direction of the blade holder 500. The blade holder 500 may thus be responsive to the skating movement of the skater to undergo an elastic torsion of each of the front pillar and the rear pillar 536, 538 which induces an elastic flexion of the elongated blade-supporting base 534 (and its bottom blade portion 556) and the ice skate blade 558 in the widthwise direction of the blade holder 500.

For example, at least a majority of the fibers 564₁-564_F that are located in the elongated blade-supporting base 534 (and its bottom blade portion 556) may extend parallel or at an oblique angle to the longitudinal axis of the elongated blade-supporting base 534 (and its bottom blade portion 556) or a totality of the fibers 564₁-564_F that are located in the elongated blade-supporting base 534 (and its bottom blade portion 556) may extend parallel or at an oblique angle to the longitudinal axis of the elongated blade-supporting base 534 (and its bottom blade portion 556).

25

The fibers 564₁-564_F may be arranged in any other suitable manner in other embodiments.

The U-shaped inner member 502 may comprise fiber-matrix composite material that offers less resilience than the fiber-matrix composite material of the U-shaped outer member 504. For example, the fiber-matrix composite material of the U-shaped

30

inner member 502 may comprise glass fibers or polypropylene fibers and the fiber-matrix composite material of the U-shaped outer member 504 may comprise carbon fibers, graphite fibers or carbon graphite fibers.

5 Each of the U-shaped inner and outer members 502, 504 may be hollow. That is, the U-shaped inner member 502 comprises an external wall 566 defining a cavity 568 and the outer member 504 comprises an external wall 570 defining a cavity 572. The U-shaped inner member 502 may be a tubular member having an external surface 574 and an internal surface 576. The external wall 566 extends from the external
10 surface 574 to the internal surface 576, while the cavity 568 is delimited by the internal surface 576. The elongated blade-supporting base 534 and front and rear pillars 536, 538 of the U-shaped outer member 504 may be a tubular member having an external surface 578 and an internal surface 580. The external wall 570 extends from the external surface 578 to the internal surface 580, while the cavity
15 578 is delimited by the internal surface 580. In this case, the cavities 568, 572 of the U-shaped inner and outer members 502, 504 opens into cavities 582, 584 of the front and rear members 508, 514 of the blade holder 500. It is understood that the external walls 566, 570 may be part of the external walls of the blade holder 500 and that the cavities 568, 572, 582, 584 may define a single empty cavity of the blade
20 holder 500.

The U-shaped inner and outer members 502, 504 may have any suitable cross-sectional shape. For example, as best seen in Figure 40, the U-shaped inner member 502 may have a cross-sectional shape that is oblong in the widthwise
25 direction of the blade holder 500. The U-shaped outer member 504 may have a cross-sectional shape that is generally trapezoidal, tapering downwardly, and shorter than the cross-sectional shape of the U-shaped inner member 502 in the widthwise direction of the blade holder 500. Also, the cross-sectional shape of each of the U-shaped inner and outer members 502, 504 may be substantially uniform over the
30 length of the tubular part of the member.

The blade holder 500 can be manufactured in any suitable manner using various processes. For example, a plurality of layers of fibers, which are destined to provide the fibers 564₁-564_F of the blade holder 500, are layered onto one another on a support which is then placed in a mold to consolidate the composite material of the blade holder 500. In this example, each of these layers of fibers is provided as a pre-preg (i.e., pre-impregnated) layer of fibers held together by an amount of matrix material, which is destined to provide a respective portion of the matrix 562 of the blade holder 500. The support may comprise one or more inflatable bladders (e.g., air bladders) on which the pre-preg layers are layered such that the one or more inflatable bladders can be inflated to define the external walls 566, 570 and the cavities 568, 572 of each of the U-shaped inner and outer members 502, 504 during molding in the mold. The support may also comprise one or more other components (e.g., silicone mold parts or foam parts) on which the pre-preg layers may be layered to form other parts of the blade holder 500 (e.g., the front and rear members 508, 514) during molding in the mold. Various other manufacturing methods may be used to make the blade holder 500 in other embodiments.

Referring to Figures 39 to 43, the ice skate blade 558 has a top portion 586 and a bottom portion 588 defining the Ice-contacting surface 560. The top portion 586 of the ice skate blade 558 comprises a plurality of anchoring members 590 (e.g. hooks, projections, channels or interlocking openings) such that the top portion 586 of the ice skate blade 558 is within the fiber-matrix composite material of the elongated blade-supporting base 534 for retaining the ice skate blade 558 to the blade holder 500. As shown in Figure 43, the fiber-matrix composite material of the elongated blade-supporting base 534 (including its bottom blade portion 556) may be made of layers of fibers 592 and at least one layer of fibers is located within the anchoring elements 590 such that the anchoring elements 590 are embedded in the fiber-matrix composite material of the elongated blade-supporting base 534 (including its bottom blade portion 556).

30

In other embodiments, the bottom blade portion of the elongated blade-supporting base may define a recess and the top portion of the ice skate blade may comprise a projection affixed into the recess of the bottom blade portion of the elongated blade-supporting base. In a further embodiment, the bottom blade portion of the elongated blade-supporting base may define a projection and the top portion of the ice skate blade may comprise a recess in which the projection of the bottom blade portion of the elongated blade-supporting base is affixed.

A blade holder in accordance with a further embodiment is shown in Figures 44 to 47 in which the same reference numbers are used for the same features as those for the blade holder 500. The blade holder 600 has blade holder and ice skate blade constructions similar to the blade holder 500 but the blade holder 600 does not comprise the intermediate member 520 and the resilient element 546. The blade holder 600 rather comprises a front member 608 defining a front peripheral wall 610 with an upper surface 612 for facing a bottom portion of the front portion 17 of the skate boot 11 and a rear member 614 defining a rear peripheral wall 616 with an upper surface 618 for facing a bottom portion of the rear portion 19 of the skate boot 11, the front peripheral wall 610 being separate from the rear peripheral wall 616 and defining separate front and rear pedestals for being mounted to the front and rear portions 17, 19 of the skate.

As best seen in Figure 47, the blade holder 600 has an elongated portion 624 and an elongated blade-supporting base 634 that do not comprise recesses, grooves, indentations or depressions. In another embodiment, it is understood that the blade holder may comprise a resilient element that may be permanently secured to the elongated portion and the elongated blade-supporting base.

The blade holder 600 also comprises an internal material 692. More particularly, the internal material 692 includes a filler that fills at least part of the cavities 568, 572, 582, 584. The filler may be made of foam. This may help to improve impact resistance and/or absorb vibrations while the skater skates. For instance, the foam

may be polystyrene (PS) foam, polyurethane (PU) foam, ethylene vinyl acetate (EVA) foam, polyvinyl chloride (PVC) foam, polypropylene (PP) foam, polyethylene (PE) foam, vinyl nitrile (VN) foam, ethylene polypropylene foam, polyisocyanurate foam or any other suitable foam. In some examples of implementation, the foam
5 may have been pre-molded to form an internal frame of the blade holder 600 over which the composite material may subsequently be molded.

As for the blade holder 500, the blade holder 600 can be manufactured in any suitable manner using various processes. For example, a plurality of layers of fibers,
10 which are destined to provide the fibers 564_I-564_F of the blade holder 600, are layered onto one another on a support which is then placed in a mold to consolidate the composite material of the blade holder 600. In this example, each of these layers of fibers is provided as a pre-preg (i.e., pre-impregnated) layer of fibers held together by an amount of matrix material, which is destined to provide a respective portion of
15 the matrix 662 of the blade holder 600. The support may comprise a single support of foam or a plurality of support members of foam on which the pre-preg layers are layered. It is understood that one of the cavities may comprise a first foam member and another of the cavities may comprise a second foam member, the second foam member having properties (density) different from the first foam member. For
20 example, the first foam member may be high-density foam and the second foam member may be low-density foam. It is also understood that one of the cavities may comprise a first foam member and another of the cavities may comprise a second foam member, the second foam member being different from the first foam member. For example, the first foam member may be ethylene vinyl acetate foam and the
25 second foam member may be polyurethane foam. It is further understood that one of the cavities may not comprise any internal material. For, example, the cavities 582, 584 of the front and rear members 508, 514 may not comprise any internal material. In another embodiment, the cavity 568 of the U-shaped inner member 502 may comprise a foam material that has less resilience or rigidity than the foam material
30 occupying the cavity 572 of the U-shaped outer member 504. It is further understood that the internal material may entirely occupy the cavities 568, 572, 582, 584 such

that the internal surfaces of the U-shaped inner and outer members 502, 504 are entirely covered by the internal material or may partially occupy the cavities 568, 572, 582, 584 such that there are voids or hollow areas between the internal material and the internal surfaces of the U-shaped inner and outer members 502, 504. In a further embodiment, voids or hollows areas may be present in the internal material.

As indicated previously, the blade holder may be responsive to the skating movement of the skater to undergo an elastic torsion of each of the front pillar and the rear pillar which induces an elastic flexion of the elongated blade-supporting base, its bottom blade portion and the ice skate blade in the widthwise direction of the blade holder.

Reproduced below, is a chart representing lateral displacement in the middle of the ice skate blade of different holders (size 8) depending on the force applied in the middle of the blade/runner (pressure contact area on the blade/runner being 300mm²):

Player's weight (Lbs)	Lateral force (Lbs) (75% of weight)	Lateral force (N)	Displacement (mm) Holder #1	Displacement (mm) Holder #2	Displacement (mm) Holder #3	Displacement (mm) Holder #4	Displacement (mm) Holder #5
240	180	801	2.93	4.86	6.16	5.51	7.72
200	150	667	2.55	4.11	5.25	4.73	6.61
175	131	584	2.30	3.68	4.63	4.13	5.75
150	113	500	2.04	3.25	4.05	3.61	5.00

As indicated previously, the blade holder in accordance with the above embodiments is lightweight and may provide other performance benefits to the skater (e.g., may facilitate and/or allow faster turns). In this regard, the weight, volume and density of a prior BAUER LIGHTSPEED EDGE blade holder commercialized in 2013, with an ice skate blade LS3, was about 300.5 grams, 165 cm³ and 1.82 g/cm³ for a size 8. With the blade holder and ice skate blade according to the invention, the weight is

significantly reduced. For example, for a size 8, the weight, volume and density of the blade holder 500 are about 160.4 grams, 149.2 cm³ and 1.08 g/cm³ for a weight reduction of almost 50%. In different samples/prototypes of the blade holders 500, 600, the density is about 1.05 g/cm³ to about 1.10 g/cm³ for a size 8.

5

Figures 48 and 49 show an ice skate blade 52' that comprises a blade body 124' and a runner or strip 125' that are made of different materials. The blade body 124' extends above the runner 125' and is mounted to the blade holder 28. The runner 125' includes the ice-contacting surface 127' that slides on the ice while the skater skates. The blade body 124' is at least mainly made of a first material 128', which will be referred to as a "blade body material", and the runner 125', including its ice-contacting surface 127', is at least mainly made of an ice-contacting material 131' which is different from the blade body material 128'. For example, the ice-contacting material 131' is harder than the blade body material 128'. More particularly, the ice-contacting material 131' is a metallic material (e.g., stainless steel) and the blade body material 128' is a composite material.

The blade body material 128' is a fiber-matrix composite material that comprises a matrix 133' in which fibers 134'₁-134'_B are embedded.

20

The matrix 133 may include any suitable substance. In this embodiment, the matrix 133 is a polymeric matrix. For example, the polymeric matrix 133 may include any other suitable polymeric resin, such as a thermosetting polymeric material (e.g., polyester, vinyl ester, vinyl ether, polyurethane, epoxy, cyanate ester, phenolic resin, etc.), a thermoplastic polymeric material (e.g., polyethylene, polypropylene, acrylic resin, polyether ether ketone (PEEK), polyethylene terephthalate (PET), polyvinyl chloride (PVC), poly(methyl methacrylate) (PMMA), polycarbonate, acrylonitrile butadiene styrene (ABS), nylon, polyimide, polysulfone, polyamide-imide, self-reinforcing polyphenylene, etc.), or a hybrid thermosetting-thermoplastic polymeric material.

30

The fibers 134₁-134_F may be made of any suitable material. In this embodiment, the fibers 134₁-134_F are carbon fibers. The blade body material 128 is thus a carbon-fiber-reinforced plastic in this example of implementation. Any other suitable type of fibers may be used in other embodiments (e.g., polymeric fibers such as graphite
5 fibers, carbon graphite fibers, aramid fibers (e.g., Kevlar fibers), boron fibers, silicon carbide fibers, ceramic fibers, metallic fibers, glass fibers, polypropylene fibers, etc.).

In this embodiment, respective ones of the fibers 134₁-134_F are oriented to be in tension when the ice skate blade 52' is deflected by the deflection in the widthwise
10 direction of the blade holder 28 due to the elastic flexion of the elongated blade-supporting base 157 and the ice skate blade 52' in the widthwise direction of the blade holder 28. This fiber tension tends to force the ice skate blade 52' back into its normal (non-deflected) shape, thereby enhancing the kickback in the widthwise direction of the blade holder 28.

15 For example, respective ones of the fibers 134₁-134_F extend in a direction having at least a component parallel to a longitudinal axis E-E of the ice skate blade 52'. In other words, respective ones of the fibers 134₁-134_F extend parallel or at an oblique angle to the longitudinal axis E-E of the ice skate blade 52'. For instance, an angle α
20 between a fiber and the longitudinal axis E-E of the ice skate blade 52' may be from 0° (parallel) to 45°.

In one embodiment, at least a majority of the fibers 134₁-134_F extend parallel or at an oblique angle to the longitudinal axis E-E of the ice skate blade 52'. In another
25 embodiment, a totality of the fibers 134₁-134_F extend parallel or at an oblique angle to the longitudinal axis E-E of the ice skate blade 52'.

The fibers 134₁-134_F may be arranged in any other suitable manner in other
30 embodiments.

As seen in Figure 49, the bottom portion of the blade body 124' may define a projection and the top portion of the runner 125' may comprise a recess in which the projection the bottom blade portion of the elongated blade-supporting base is affixed. In another embodiment shown in Figure 49A, the bottom portion of the blade body 124A' may define a recess and the top portion of the runner 125A' may comprise a projection affixed into the recess of the bottom blade portion of the elongated blade-supporting base.

Figures 50 to 53 show an ice skate blade 52'' that has a blade body 124' with a construction similar to the construction of the blade body 124' but wherein a different runner or strip 125'' is used. The runner or strip 125'' may be made of stainless steel, carbon steel, tungsten carbide, titanium, engineering plastic, aluminum titanate, aluminum zirconate, sialon, silicon nitride, silicon carbide or zirconia and partially stabilized zirconia. The runner 125'' has a top portion 126'' and a bottom portion 128'' defining an ice-contacting surface 127''. The top portion 126'' of the runner 125'' comprises a plurality of anchoring members 190'' (e.g. hooks, projections, channels or interlocking openings) such that the top portion 126'' of the runner 125'' is within the fiber-matrix composite material 133' of the blade body 124' for retaining the runner 125'' to the blade body 124'. As shown in Figure 53, the fiber-matrix composite material 133' of the blade body 124' may be made of layers 192'' of fibers and at least one layer 192'' of fibers is located within the anchoring elements 190'' such that the anchoring elements 190'' are embedded in the fiber-matrix composite material 133' of the blade body 124'. In another embodiment shown in Figure 53A, the fiber-matrix composite material 133' of the blade body 124' may be made of strips or bands 192A'' of fibers.

Figures 54 and 55 show an ice skate blade 52''' that has a construction similar to the construction of the ice skate blade 52'' but wherein the blade body 124'' has a reinforcing member 193''' on each side extending along the longitudinal axis of the ice skate blade 52'''.

To facilitate the description, any reference numeral designating an element in one figure designates the same element if used in any other figures. In describing the embodiments, specific terminology has been resorted to for the sake of clarity but the invention is not intended to be limited to the specific terms so selected, and it is
5 understood that each specific term comprises all equivalents. In some embodiments, any feature of any embodiment described herein may be used in combination with any feature of any other embodiment described herein. Certain additional elements that may be needed for operation of certain embodiments have not been described or illustrated as they are assumed to be within the purview of those of ordinary skill
10 in the art. Moreover, certain embodiments may be free of, may lack and/or may function without any element that is not specifically disclosed herein. Although various embodiments have been illustrated, this was for the purpose of describing, but not limiting, the invention. Various modifications will become apparent to those skilled in the art and are within the scope of this invention, which is defined more
15 particularly by the attached claims.

CLAIMS

1. A skate for skating on ice, the skate comprising:
 - a one-piece component, comprising:
 - 5 ○ a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a fiber-reinforced composite layer; and
 - 10 ○ a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the fiber-reinforced composite layer;
 - 15 - a toe cap separately affixed to the one-piece component;
 - wherein the one-piece component defines at least one void extending laterally from a medial side of the skate to a lateral side of the skate; and
 - wherein the void occupies most of a height of the blade holder body.
- 20 2. The skate of claim 1, wherein at least a majority of the skate boot body is made of the first part of the fiber-reinforced layer and formed integrally with the second part of the fiber-reinforced composite layer.
3. The skate of claim 2, wherein an entirety of the skate boot body is made of the first part of the fiber-reinforced composite layer and formed integrally with the second part of the fiber-reinforced composite layer.
- 25 4. The skate of any one of claims 1 to 3, wherein the medial side portion, the lateral side portion, the heel portion, and the ankle portion of the skate boot body are made of the first part of the fiber-reinforced composite layer material and are
- 30 formed integrally with the second part of the fiber-reinforced composite layer.

5. The skate of any one of claims 1 to 4, wherein: the skate boot body comprises a toe portion to enclose toes of the user's foot; and the medial side portion, the lateral side portion, the heel portion, the ankle portion, and the toe portion of the skate boot body are made of the first part of the fiber-reinforced composite layer and are formed integrally with the second part of the fiber-reinforced composite layer.
6. The skate of any one of claims 1 to 5, wherein the fiber-reinforced composite layer comprises continuous fibers.
7. The skate of claim 6, wherein respective ones of the continuous fibers of are interlaced.
8. The skate of any one of claims 1 to 7, wherein the fiber-reinforced composite layer comprises a pre-impregnated fiber layer.
9. The skate of claim 8, wherein: the pre-impregnated fiber layer is a first pre-impregnated fiber layer; and the skate comprises a second pre-impregnated fiber layer that overlies the first pre-impregnated fiber layer.
10. The skate of any one of claims 1 to 9, wherein the fiber-reinforced composite layer comprises carbon fibers.
11. The skate of any one of claims 1 to 10, wherein the fiber-reinforced composite layer comprises at least one of graphite fibers, carbon graphite fibers, aramid fibers, boron fibers, silicon carbide fibers, ceramic fibers, metallic fibers, glass fibers, and polypropylene fibers.
12. The skate of any one of claims 1 to 11, wherein the skate boot comprises lacing members affixed to the skate boot body and configured to receive a lace.

13. The skate of any one of claims 1 to 12, wherein the blade holder comprises a blade-supporting base configured to hold the blade such that the blade is detachable and removable from the blade holder body.
- 5 14. The skate of claim 13, wherein the blade holder comprises a blade-connecting mechanism configured to attach the blade to and remove the blade from the blade holder body.
15. The skate of claim 14, wherein the blade-connecting mechanism comprises a
10 hollow space to receive and engage a connecting portion of the blade.
16. The skate of claim 15, wherein the hollow space of the blade-connecting mechanism is hook-shaped and the connecting portion of the blade is a hook.
- 15 17. The skate of any one of claims 14 to 16, wherein the blade-connecting mechanism comprises an actuator manually operable to detach the blade from the blade holder body.
18. The skate of any one of claims 1 to 17, wherein: the blade holder comprises a
20 front pillar and a rear pillar spaced apart in a longitudinal direction of the blade holder body; and a longitudinal spacing of the front pillar and the rear pillar in the longitudinal direction of the blade holder body is greater than a sum of a minimal longitudinal dimension of the front pillar in the longitudinal direction of the blade holder body and a minimal longitudinal dimension of the rear pillar in the
25 longitudinal direction of the blade holder body.
19. The skate of claim 18, wherein the longitudinal spacing of the front pillar and the rear pillar in the longitudinal direction of the blade holder body is at least three times greater than the sum of the minimal longitudinal dimension of the front pillar
30 in the longitudinal direction of the blade holder body and the minimal longitudinal dimension of the rear pillar in the longitudinal direction of the blade holder body.
20. The skate of any one of claims 18 and 19, wherein the longitudinal spacing of the front pillar and the rear pillar in the longitudinal direction of the blade holder body
35 is at least five times greater than the sum of the minimal longitudinal dimension of

the front pillar in the longitudinal direction of the blade holder and the minimal longitudinal dimension of the rear pillar in the longitudinal direction of the blade holder.

- 5 21. The skate of any one of claims 1 to 20, wherein the skate boot comprises a tendon guard affixed to the skate boot body.
22. The skate of any one of claims 1 to 21, further comprising internal material within a wall formed of the second part of the fiber-reinforced composite layer.
- 10 23. The skate of claim 22, wherein the internal material comprises foam.
24. The skate of any one of claims 22 and 23, wherein the internal material constitutes an internal frame on which the second part of the fiber-reinforced composite layer is formed.
- 15 25. The skate of any one of claims 22 to 24, wherein the internal material is injection molded.
- 20 26. The skate of any one of claims 1 to 21, further comprising an internal frame covered by the second part of the fiber-reinforced composite layer.
27. The skate of claim 26, wherein the internal frame extends from a front region of the blade holder to a rear region of the blade holder and for at least a majority of a height of the blade holder.
- 25 28. The skate of any one of claims 26 and 27, wherein and the internal frame wraps partially about the at least one void.
- 30 29. The skate of any one of claims 26 to 28, wherein the internal frame comprises foam.
- 35 30. The skate of any one of claims 26 to 29, wherein the internal frame is injection molded.

31. The skate of any one of claims 1 to 30, wherein the at least one void extends along a majority of a length of the blade holder.
- 5 32. The skate of any one of claims 1 to 29, wherein the void is a first void and the one-piece component defines a second void extending laterally from a medial side of the skate to a lateral side of the skate.
33. A skate for skating on ice, the skate comprising:
- 10 - a one-piece component, comprising:
- a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's foot, and an ankle portion to receive an ankle of the user, the skate
 - 15 boot body including at least a first part of a fiber-reinforced composite layer; and
 - a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the fiber-reinforced
 - 20 composite layer; and
- a toe cap separately affixed to the one-piece component.
34. The skate of claim 33, wherein at least a majority of the skate boot body is made of the first part of the fiber-reinforced layer and formed integrally with the second
- 25 part of the fiber-reinforced composite layer.
35. The skate of claim 34, wherein an entirety of the skate boot body is made of the first part of the fiber-reinforced composite layer and formed integrally with the second part of the fiber-reinforced composite layer.
- 30 36. The skate of any one of claims 33 to 35, wherein the medial side portion, the lateral side portion, the heel portion, and the ankle portion of the skate boot body

are made of the first part of the fiber-reinforced composite layer material and are formed integrally with the second part of the fiber-reinforced composite layer.


- 5 37. The skate of any one of claims 33 to 35, wherein: the skate boot body comprises a toe portion to enclose toes of the user's foot; and the medial side portion, the lateral side portion, the heel portion, the ankle portion, and the toe portion of the skate boot body are made of the first part of the fiber-reinforced composite layer and are formed integrally with the second part of the fiber-reinforced composite layer.
- 10 38. The skate of any one of claims 33 to 37, wherein the fiber-reinforced composite layer comprises continuous fibers.
- 15 39. The skate of claim 38, wherein respective ones of the continuous fibers of are interlaced.
40. The skate of any one of claims 33 to 39, wherein the fiber-reinforced composite layer comprises a pre-impregnated fiber layer.
- 20 41. The skate of claim 40, wherein: the pre-impregnated fiber layer is a first pre-impregnated fiber layer; and the skate comprises a second pre-impregnated fiber layer that overlies the first pre-impregnated fiber layer.
- 25 42. The skate of any one of claims 33 to 41, wherein the fiber-reinforced composite layer comprises carbon fibers.
- 30 43. The skate of any one of claims 33 to 41, wherein the fiber-reinforced composite layer comprises at least one of graphite fibers, carbon graphite fibers, aramid fibers, boron fibers, silicon carbide fibers, ceramic fibers, metallic fibers, glass fibers, and polypropylene fibers.
44. The skate of any one of claims 33 to 43, wherein the skate comprises lacing members affixed to the skate boot body and configured to receive a lace.

45. The skate of any one of claims 33 to 44, wherein the blade holder comprises a blade-supporting base configured to hold the blade such that the blade is detachable and removable from the blade holder body.
- 5
46. The skate of claim 45, wherein the blade holder comprises a blade-connecting mechanism configured to attach the blade to and remove the blade from the blade holder body.
- 10
47. The skate of claim 46, wherein the blade-connecting mechanism comprises a hollow space to receive and engage a connecting portion of the blade.
48. The skate of claim 47, wherein the hollow space of the blade-connecting mechanism is hook-shaped and the connecting portion of the blade is a hook.
- 15
49. The skate of claim 46, wherein the blade-connecting mechanism comprises an actuator manually operable to detach the blade from the blade holder body.
50. The skate of any one of claims 33 to 49, wherein: the blade holder comprises a front pillar and a rear pillar spaced apart in a longitudinal direction of the blade holder body; and a longitudinal spacing of the front pillar and the rear pillar in the longitudinal direction of the blade holder body is greater than a sum of a minimal longitudinal dimension of the front pillar in the longitudinal direction of the blade holder body and a minimal longitudinal dimension of the rear pillar in the longitudinal direction of the blade holder body.
- 20
51. The skate of claim 50, wherein the longitudinal spacing of the front pillar and the rear pillar in the longitudinal direction of the blade holder body is at least three times greater than the sum of the minimal longitudinal dimension of the front pillar in the longitudinal direction of the blade holder body and the minimal longitudinal dimension of the rear pillar in the longitudinal direction of the blade holder body.
- 25
- 30

52. The skate of claim 50, wherein the longitudinal spacing of the front pillar and the rear pillar in the longitudinal direction of the blade holder body is at least five times greater than the sum of the minimal longitudinal dimension of the front pillar in the longitudinal direction of the blade holder and the minimal longitudinal dimension of the rear pillar in the longitudinal direction of the blade holder.
53. The skate of any one of claims 33 to 52, wherein the skate comprises a tendon guard affixed to the skate boot body.
54. The skate of any one of claims 33 to 53, further comprising internal material within a wall formed of the second part of the fiber-reinforced composite layer.
55. The skate of claim 54, wherein the internal material comprises foam.
56. The skate of any one of claims 54 and 55, wherein the internal material constitutes an internal frame on which the second part of the fiber-reinforced composite layer is formed.
57. The skate of any one of claims 54 to 56, wherein the internal material is injection molded.
58. The skate of any one of claims 33 to 53, further comprising an internal frame covered by the second part of the fiber-reinforced composite layer.
59. The skate of claim 57, wherein the internal frame extends from a front region of the blade holder to a rear region of the blade holder and for at least a majority of a height of the blade holder.
60. The skate of any one of claims 57 to 59, wherein: the one-piece component defines a plurality of voids extending laterally from a medial side of the skate to a lateral side of the skate; and the internal frame wraps partially about at least one of the voids.

61. The skate of any one of claims 57 to 60, wherein the internal frame comprises foam.
62. The skate of any one of claims 57 to 61, wherein the internal frame is injection
5 molded.
63. The skate of any one of claims 33 to 62, wherein the fiber-reinforced composite layer comprises fibers which are oriented in pre-determined directions.
- 10 64. A skate for skating on ice, the skate comprising:
- a one-piece component, comprising:
 - o a skate boot body that comprises a medial side portion to face a medial side of a user's foot, a lateral side portion to face a lateral side of the user's foot, a heel portion to receive a heel of the user's
15 foot, and an ankle portion to receive an ankle of the user, the skate boot body including at least a first part of a material layer; and
 - o a blade holder body integrally formed with the skate boot body and configured to hold a blade for engaging the ice, the blade holder body including at least a second part of the material layer;
 - 20 - an injection-molded component distinct from the one-piece component and affixed to the one-piece component.
65. The skate of claim 64, wherein the injection-molded component is disposed within a wall formed of the second part of the material layer.
25
66. The skate of claim 65, wherein the injection-molded component is an internal frame.
67. The skate of any one of claims 64 to 66, wherein the material layer is a fiber-reinforced fiber-reinforced composite layer.
30
68. The skate of any one of claims 64 to 67, wherein the injection-molded component comprises foam.

1/43

**FIG. 1**




FIG. 2





FIG. 3

4/43

**FIG. 4**

5/43




FIG. 5




FIG. 6




FIG. 7




FIG. 8

8/43




FIG. 9

9/43




FIG. 10




FIG. 11

10/43




FIG. 12

11/43




FIG. 13A




FIG. 13B




FIG. 14A

12/43




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 14F

13/43




FIG. 15




FIG. 16

14/43




FIG. 17




FIG. 18

15/43





FIG. 20

FIG. 19

16/43




FIG. 21A

17/43




FIG. 21B




FIG. 21C




FIG. 22

20/43




FIG. 23A




FIG. 23B








FIG. 23C

21/43

**FIG. 23D****FIG. 23E****FIG. 23F****FIG. 23G**

22/43




FIG. 24A




FIG. 24B




FIG. 24C




FIG. 25



FIG. 26

25/43




FIG. 27




FIG. 28

26/43




FIG. 29




FIG. 30




FIG. 31

28/43




FIG. 32




FIG. 33

29/43




FIG. 34

30/43




FIG. 35




FIG. 36

31/43




FIG. 37




FIG. 38

33/43




FIG. 39




FIG. 40




FIG. 41

35/43




FIG. 42




FIG. 43

36/43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48



FIG. 49

FIG. 49A





FIG. 51



41/43




FIG. 53

FIG. 53A

42/43




FIG. 54




FIG. 55

