



(12) **United States Patent**
Buck et al.

(10) **Patent No.:** **US 10,987,154 B2**
(45) **Date of Patent:** ***Apr. 27, 2021**

(54) **ELECTROSURGICAL GENERATORS AND SENSORS**

(71) Applicant: **COVIDIEN LP**, Mansfield, MA (US)

(72) Inventors: **Dean C. Buck**, Loveland, CO (US);
Edward L. Brannan, Erie, CO (US);
Mark A. Johnston, Boulder, CO (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 98 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/402,049**

(22) Filed: **May 2, 2019**

(65) **Prior Publication Data**

US 2019/0290351 A1 Sep. 26, 2019

Related U.S. Application Data

(63) Continuation of application No. 14/557,533, filed on Dec. 2, 2014, now Pat. No. 10,292,753.

(51) **Int. Cl.**

A61B 18/12 (2006.01)
A61B 18/14 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 18/1233** (2013.01); **A61B 18/1445** (2013.01); **A61B 18/1477** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC G01R 15/181; A61B 18/1233
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,252,052 A 5/1966 Nash
3,431,487 A 3/1969 Savage
(Continued)

FOREIGN PATENT DOCUMENTS

DE 179607 C 3/1905
DE 390937 C 3/1924
(Continued)

OTHER PUBLICATIONS

European Examination Report dated Jul. 3, 2020 issued in corresponding EP Appln. No. 15191320.9.

(Continued)

Primary Examiner — Lee E Rodak


Assistant Examiner — Adam S Clarke

(74) *Attorney, Agent, or Firm* — Carter, DeLuca & Farrell LLP

(57) **ABSTRACT**

An electrosurgical generator includes a radio frequency output stage configured to output at least one radio frequency waveform and a sensor for sensing current. The sensor includes a current sensor coil having: an outer coil, an inner coil coupled to and disposed within the outer coil, and at least one shielding member disposed over the outer coil. Each of the at least one shielding member and the outer coil define an opening therethrough. The generator also includes at least one active lead coupled to the radio frequency output stage and passing through the current sensor coil. The current sensor coil is configured to output a signal indicative of a current within the at least one active lead.

20 Claims, 21 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

DE	3510586	A1	10/1986
DE	3604823	A1	8/1987
DE	3904558	A1	8/1990
DE	3942998	A1	7/1991
DE	4206433	A1	9/1993
DE	4339049	A1	5/1995
DE	19506363	A1	8/1996
DE	19717411	A1	11/1998
DE	19848540	A1	5/2000
DE	102008058737	A1	4/2010
EP	0246350	A1	11/1987
EP	0267403	A2	5/1988
EP	0296777	A2	12/1988
EP	0310431	A2	4/1989
EP	0325456	A2	7/1989
EP	0336742	A2	10/1989
EP	0390937	A1	10/1990
EP	0556705	A1	8/1993
EP	0608609	A2	8/1994
EP	0694291	A1	1/1996
EP	0836868	A2	4/1998
EP	0880220	A2	11/1998
EP	0882955	A1	12/1998
EP	1051948	A2	11/2000
EP	1366724	A1	12/2003
EP	1776929	A1	4/2007
EP	2281521	A1	2/2011
EP	2407116	A1	1/2012
EP	2510895	A1	10/2012
EP	3028656	A1	6/2016
EP	3028658	A1	6/2016
FR	1275415	A	11/1961
FR	1347865	A	1/1964
FR	2313708	A1	12/1976
FR	2364461	A1	4/1978
FR	2502935	A1	10/1982
FR	2517953	A1	6/1983
FR	2573301	A1	5/1986
JP	63005876		1/1988
JP	2002065690	A	3/2002
JP	2005185657	A	7/2005
SU	166452		11/1964
SU	727201	A2	4/1980
WO	0072027	A1	11/2000
WO	02/00129		1/2002
WO	0211634	A1	2/2002
WO	0245589	A2	6/2002
WO	03090635	A1	11/2003
WO	2006/050888	A1	5/2006
WO	2008053532	A1	5/2008
WO	2010007017	A1	1/2010

OTHER PUBLICATIONS

U.S. Appl. No. 11/242,458, filed Oct. 3, 2005, Daniel J. Becker.
 Wald et al., "Accidental Burns", JAMA, Aug. 16, 1971, vol. 217, No. 7, pp. 916-921.
 Valfors et al., "Automatically Controlled Bipolar Electrocoagulation—'COA-COMP'", Neurosurgical Review 7:2-3 (1984) pp. 187-190.
 Sugita et al., "Bipolar Coagulator with Automatic Thermocontrol", J. Neurosurg., vol. 41, Dec. 1944, pp. 777-779.
 Prutchi et al. "Design and Development of Medical Electronic Instrumentation", John Wiley & Sons, Inc. 2005.
 Momozaki et al. "Electrical Breakdown Experiments with Application to Alkali Metal Thermal-to-Electric Converters", Energy conversion and Management; Elsevier Science Publishers, Oxford, GB; vol. 44, No. 6, Apr. 1, 2003 pp. 819-843.
 Muller et al. "Extended Left Hemicolectomy Using the LigaSure Vessel Sealing System", Innovations That Work; Company Newsletter; Sep. 1999.
 Ogden Goertzel Alternative to the Fourier Transform: Jun. 1993 pp. 485-487, Electronics World; Reed Business Publishing, Sutton, Surrey, BG vol. 99, No. 9. 1687.

Hadley I C D et al., "Inexpensive Digital Thermometer for Measurements on Semiconductors", International Journal of Electronics; Taylor and Francis. Ltd.; London, GB; vol. 70, No. 6 Jun. 1, 1991; pp. 1155-1162.
 Burdette et al. "In Vivo Probe Measurement Technique For Determining Dielectric Properties At VHF Through Microwave Frequencies", IEEE Transactions on Microwave Theory and Techniques, vol. MTT-28, No. 4, Apr. 1980 pp. 414-427.
 Richard Wolf Medical Instruments Corp. Brochure, "Kleppinger Bipolar Forceps & Bipolar Generator", 3 pp. Jan. 1989.
 Astrahan, "A Localized Current Field Hyperthermia System for Use with 192-Iridium Interstitial Implants" Medical Physics, 9 (3), May/June. 1982.
 Alexander et al., "Magnetic Resonance Image-Directed Stereotactic Neurosurgery: Use of Image Fusion with Computerized Tomography to Enhance Spatial Accuracy", Journal Neurosurgery, 83; (1995) pp. 271-276.
 Geddes et al., "The Measurement of Physiologic Events by Electrical Impedance" Am. J. MI, Jan. Mar. 1964, pp. 16-27.
 Cosman et al., "Methods of Making Nervous System Lesions", In William RH, Rengachary SS (eds): Neurosurgery, New York: McGraw-Hill, vol. 111, (1984), pp. 2490-2499.
 Anderson et al., "A Numerical Study of Rapid Heating for High Temperature Radio Frequency Hyperthermia" International Journal of Bio-Medical Computing, 35 (1994) pp. 297-307.
 Benaron et al., "Optical Time-Of-Flight and Absorbance Imaging of Biologic Media", Science, American Association for the Advancement of Science, Washington, DC, vol. 259, Mar. 5, 1993, pp. 1463-1466.
 Cosman et al., "Radiofrequency Lesion Generation and Its Effect on Tissue Impedance", Applied Neurophysiology 51: (1988) pp. 230-242.
 Zlatanovic M., "Sensors in Diffusion Plasma Processing" Microelectronics 1995; Proceedings 1995; 20th International Conference CE on Nis, Serbia Sep. 12-14, 1995; New York, NY vol. 2 pp. 565-570.
 Ni W. et al. "A Signal Processing Method for the Coriolis Mass Flowmeter Based on a Normalized . . .", Journal of Applied Sciences—Yingyong Kexue Xuebao, Shangha CN, vol. 23 No. 2;(Mar. 2005); pp. 160-164.
 Chicharo et al. "A Sliding Goertzel Algorithm" Aug. 1996, pp. 283-297, Signal Processing, Elsevier Science Publishers B.V. Amsterdam, NL vol. 52 No. 3.
 Bergdahl et al., "Studies on Coagulation and the Development of an Automatic Computerized Bipolar Coagulator" Journal of Neurosurgery 75:1, (Jul. 1991) pp. 148-151.
 Cosman et al., "Theoretical Aspects of Radiofrequency Lesions in the Dorsal Root Entry Zone", Neurosurgery 15: (1984) pp. 945-950.
 Goldberg et al., "Tissue Ablation with Radiofrequency: Effect of Probe Size, Gauge, Duration, and Temperature on Lesion Volume" Acad Radio (1995) vol. 2, No. 5, pp. 399-404.
 Medtrex Brochure—Total Control at Full Speed, "The O.R. Pro 300", 1 p. Sep. 1998.
 Valleylab Brochure "Valleylab Electrosield Monitoring System", 2 pp. Nov. 1995.
 Extended European Search Report corresponding to European Application No. 13196200.3, dated Apr. 24, 2014; 6 pages.
 Extended European Search Report corresponding to European Application No. 13196199.7, dated Apr. 25, 2014; 6 pages.
 European Search Report, dated Apr. 18, 2016, corresponding to European Application No. 15191279.7; 9 pages.
 European Search Report, dated Apr. 21, 2016, corresponding to European Application No. 15191320.9; 6 pages.
 European Search Report, dated May 10, 2016, corresponding to European Application No. 15191339.9; 10 pages.
 European Communication, dated Aug. 10, 2016, corresponding to European Application No. 15191320.9; 9 pages.
 Momozaki et al. "Electrical Breakdown Experiments with Application to Alkali Metal Thermal-to-Electric Converters", Energy conversion and Management; Elsevier Science Publishers, Oxford, GB; vol. 44, No. 6, Apr. 1, 2003 pp. 819-843. cited by applicant.
 U.S. Appl. No. 10/406,690, filed Apr. 3, 2003, Michael S. Klicek.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 10/573,713, filed Mar. 28, 2006, Robert H. Wham.

* cited by examiner




Fig. 1




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 20

R₁




Fig. 19




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25A

Fig. 25B




Fig. 25C




Fig. 25D




Fig. 25E




Fig. 26D




Fig. 26E




Fig. 26F




Fig. 27A




Fig. 27B




Fig. 28A




Fig. 28B




Fig. 29A




Fig. 29B




Fig. 29C




Fig. 30A




Fig. 30B




Fig. 30C




Fig. 31A




Fig. 31B




Fig. 31C




Fig. 32A




Fig. 32B




Fig. 33

ELECTROSURGICAL GENERATORS AND SENSORS

CROSS-REFERENCE TO RELATED APPLICATION

The present application is a continuation of U.S. patent application Ser. No. 14/557,533, filed on Dec. 2, 2014, which is related to U.S. patent application Ser. No. 14/557,557 filed on Dec. 2, 2014 and U.S. patent application Ser. No. 14/557,579, filed on Dec. 2, 2014. The entire contents of all of the foregoing applications are incorporated by reference herein.

BACKGROUND

Technical Field

The present disclosure relates to an electrosurgical system and method for operating an electrosurgical generator. More particularly, the present disclosure relates to a system, apparatus, and method for measuring current in an electrosurgical generator.

Background of Related Art

Electrosurgery involves application of high radio frequency electrical current to a surgical site to cut, ablate, or coagulate tissue. In monopolar electrosurgery, a source or active electrode delivers radio frequency alternating current from the electrosurgical generator to the targeted tissue. A patient return electrode is placed remotely from the active electrode to conduct the current back to the generator.

In bipolar electrosurgery, return and active electrodes are placed in close proximity to each other such that an electrical circuit is formed between the two electrodes (e.g., in the case of an electrosurgical forceps). In this manner, the applied electrical current is limited to the body tissue positioned between the electrodes. Accordingly, bipolar electrosurgery generally involves the use of instruments where it is desired to achieve a focused delivery of electrosurgical energy between two electrodes positioned on the instrument, e.g. forceps or the like. Electrosurgical procedures outlined above may utilize various tissue and energy parameters in a feedback-based control system. There is continual need to improve sensors that measure various tissue and energy properties utilized in the feedback-based control systems.

SUMMARY

Various embodiments of the present disclosure are described herein with reference to the drawings wherein:

According to one embodiment of the present disclosure, an electrosurgical generator is provided. The generator includes a radio frequency output stage, a sensor for sensing current, and an active lead. The radio frequency output stage is configured to output at least one radio frequency waveform. The sensor includes a current sensor coil including an outer coil including an opening therethrough and an inner coil coupled to and disposed within the outer coil. The active lead is coupled to the radio frequency output stage and passes through the current sensor coil opening. The current sensor coil is configured to output a first signal indicative of a current within the active lead.

In embodiments, the electrosurgical generator may further include at least one return lead coupled to the radio frequency output stage. The at least one return lead may pass

through the current sensor coil. The current sensor coil may be configured to output a second signal indicative of a current within the at least one return lead. The sensor may further include a conditioning circuit configured to integrate, amplify, and/or filter the first signal or the second signal to output a processed signal indicative of the current of the first signal and/or the second signal. The conditioning circuit may be fully-differential.

In embodiments, the current sensor coil may be disposed within a printed circuit board. In embodiments, the sensor may further include at least one shielding member disposed over the outer coil. The printed circuit board may include a plurality of outer conductive traces. Each trace may be coupled to the at least one active lead and be interconnected by at least one via through the printed circuit board. The printed circuit board may further include a top dielectric layer, a first dielectric intermediate layer, a bottom dielectric layer, and a second dielectric intermediate layer. The outer coil may include a plurality of top conductive traces disposed between the top dielectric layer and the first dielectric intermediate layer of the printed circuit board. A plurality of bottom conductive traces may be disposed between the bottom dielectric layer and the second dielectric intermediate layer of the printed circuit board. The outer conductive traces may be disposed over the outer surfaces of the bottom and top dielectric layers. A plurality of inner and outer vias may interconnect the pluralities of top and bottom conductive traces. The shielding member may be disposed over an outer dielectric layer, which is disposed over the outer surface of at least one of the top dielectric layer or the bottom dielectric layer. The inner coil may include at least one conductive trace disposed within the outer coil and between the first and second dielectric intermediate layers of the printed circuit board.

In embodiments, the current sensor coil may include diametrically opposed first and second ends. Each of the outer coil and the inner coil may include first and second portions separated at the second end. The conditioning circuit may include first and second terminals coupled to the first and second portions of the outer coil, respectively. The first and second portions of the inner coil may be coupled to a third terminal at the first end. The first portions of the outer coil and the inner coil may be coupled to each other at the second end and the second portions of the outer coil and the inner coil may be coupled to each other at the second end. The at least one active lead and/or the at least one return lead may be symmetrically disposed over the current sensor coil about an axis defined between the first and second ends. The at least one active lead and/or the at least one return lead may be disposed at a non-zero angle relative to the axis. The at least one active lead and/or the at least one return lead may be disposed transversely relative to the axis.

In another aspect of the present disclosure, another embodiment of an electrosurgical generator is provided. The electrosurgical generator includes a radio frequency output stage, a sensor for sensing current, and at least one active lead. The radio frequency output stage is configured to output at least one radio frequency waveform. The sensor includes a current sensor coil defining an opening there-through and diametrically opposed first and second ends. The current sensor coil includes an outer coil including a first semi-circular portion and a second semi-circular portion and an inner coil disposed within the outer coil. The inner coil includes a first semi-circular portion and a second semi-circular portion. The first semi-circular portions and the second semi-circular portions of the inner and outer coils are separated at the second end. The at least one active lead

and/or at least one return lead are coupled to the radio frequency output stage and pass through the current sensor coil. The current sensor coil is configured to output a differential signal indicative of a current within the at least one active lead and/or at least one return lead.

In embodiments, the current sensor coil may further include at least one shielding member disposed over the outer coil and define a second opening therethrough in alignment with the opening of the current sensor coil.

In embodiments, the sensor may further include a conditioning circuit coupled to the inner and outer coils at the first end and configured to integrate, amplify, and/or filter the differential signal to output a processed signal indicative of the current.

In embodiments, the at least one active lead and/or the at least one return lead may be symmetrically disposed over the current sensor coil about an axis defined between the first and second ends. In another aspect of the present disclosure, the at least one active lead and/or the at least one return lead may be disposed at a non-zero angle relative to the axis. In yet another aspect of the present disclosure, the at least one active lead and/or the at least one return lead may be disposed transversely relative to the axis.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of the present disclosure are described herein with reference to the drawings wherein:

FIG. 1 is a perspective view of the components of one illustrative embodiment of an electrosurgical system according to the present disclosure;

FIG. 2 is a front view of one embodiment of an electrosurgical generator according to the present disclosure;

FIG. 3 is a schematic, block diagram of the embodiment of an electrosurgical generator of FIG. 2 according to the present disclosure;

FIG. 4 is a schematic diagram of a current sensor according to the present disclosure;

FIG. 5 is a partially-exposed, isometric view of a current sensor disposed within a printed circuit board according to the present disclosure;

FIG. 6 is a partially-exposed, plan view of a current sensor coil of FIG. 5 according to the present disclosure;

FIG. 7 is an enlarged schematic view of the current sensor coil of FIG. 6 according to the present disclosure;

FIG. 8 is a side, partial cross-sectional view of the printed circuit board of FIG. 5 according to the present disclosure;

FIG. 9 is a plan view of the printed circuit board of FIG. 5 according to the present disclosure;

FIG. 10 is a schematic circuit diagram of a gain amplifier according to the present disclosure;

FIG. 11 is a schematic circuit diagram of a differential to single-ended amplifier according to the present disclosure;

FIG. 12 is a schematic circuit diagram of a high-pass filter according to the present disclosure;

FIG. 13 is a schematic circuit diagram of a low-pass filter according to the present disclosure;

FIG. 14 is a schematic circuit diagram of an integrator according to the present disclosure;

FIG. 15 is a plot of individual and combined gain response of the current sensor coil of FIG. 4 and the integrator shown in FIG. 14 according to the present disclosure;

FIG. 16 is a schematic diagram of the current sensor coil of FIG. 4 according to the present disclosure;

FIG. 17 is a schematic diagram of a differential-mode current sensor coil according to the present disclosure;

FIG. 18 shows another embodiment of a current sensor and conditioning circuit according to the present disclosure;

FIG. 19 is a schematic diagram of the differential-mode current sensor coil of FIG. 17 according to the present disclosure.

FIG. 20 is a plot of individual and combined gain response of a current sensor coil, an integrator, a bandpass filter shown in FIG. 18 according to the present disclosure;

FIG. 21 is a schematic diagram of the current sensor of FIG. 18 according to the present disclosure;

FIG. 22 is a schematic diagram of the current sensor of FIG. 18 with parasitic capacitive coupling according to the present disclosure;

FIG. 23 is a schematic diagram of the current sensor of FIG. 18 with balanced out parasitic capacitive coupling according to the present disclosure;

FIG. 24 is a schematic diagram of the current sensor of FIG. 18 having a shielding member according to the present disclosure;

FIG. 25A is a perspective view of a current sensor coil according to the present disclosure;

FIG. 25B is a front view of the current sensor coil of FIG. 25A according to the present disclosure;

FIG. 25C is a side view of the current sensor coil of FIG. 25A according to the present disclosure;

FIG. 25D is an exploded view of the current sensor coil of FIG. 25A according to the present disclosure;

FIG. 25E is a plan view of the current sensor coil of FIG. 25A according to the present disclosure;

FIG. 26A is a partially-exposed, plan view of a current sensor coil of the current sensor of FIG. 25A according to one embodiment of the present disclosure;

FIG. 26B is an enlarged area 26B of the current sensor coil of FIG. 26A according to the present disclosure;

FIG. 26C is an enlarged area 26C of the current sensor coil of FIG. 26A according to the present disclosure;

FIG. 26D is a perspective, schematic view of the current sensor coil of FIG. 26A according to the present disclosure;

FIG. 26E is a plot of an erroneous error signal as function of wire position of the current sensor coil of FIG. 26A as a function of an angle of leads passing therethrough according to the present disclosure;

FIG. 26F is a schematic diagram of the current sensor coil of FIG. 26A with parasitic capacitive coupling according to the present disclosure;

FIG. 27A is a perspective, schematic view of a current sensor coil according to another embodiment of the present disclosure;

FIG. 27B is a schematic diagram of the current sensor of FIG. 27A according to the present disclosure;

FIG. 28A is a perspective, schematic view of the current sensor coil according to another embodiment of the present disclosure;

FIG. 28B is a schematic diagram of the current sensor of FIG. 28A with parasitic capacitive coupling according to the present disclosure;

FIG. 29A is a perspective, schematic view of the current sensor coil according to another embodiment of the present disclosure;

FIG. 29B is a plot of an erroneous error signal as function of lead position of the current sensor coil of FIG. 29A as a function of an angle of leads passing therethrough according to the present disclosure;

FIG. 29C is a schematic diagram of the current sensor of FIG. 29A with parasitic capacitive coupling according to the present disclosure;

5

FIG. 30A is a perspective, schematic view of the current sensor coil according to another embodiment of the present disclosure;

FIG. 30B is a plot of an erroneous error signal as function of lead position of the current sensor coil of FIG. 30A as a function of an angle of leads passing therethrough according to the present disclosure;

FIG. 30C is a schematic diagram of the current sensor of FIG. 30A with parasitic capacitive coupling according to the present disclosure;

FIG. 31A is a perspective, schematic view of the current sensor coil according to another embodiment of the present disclosure;

FIG. 31B is a plot of an erroneous error signal as function of lead position of the current sensor coil of FIG. 31A as a function of an angle of leads passing therethrough according to the present disclosure;

FIG. 31C is a schematic diagram of the current sensor of FIG. 31A with parasitic capacitive coupling according to the present disclosure;

FIG. 32A is a partially-exposed, plan view of a current sensor coil of the current sensor according to another embodiment of the present disclosure;

FIG. 32B is a perspective, schematic view of the current sensor of FIG. 32A according to the present disclosure; and

FIG. 33 is a partially-exposed, plan view of a current sensor coil of the current sensor according to a further embodiment of the present disclosure.

DETAILED DESCRIPTION

Particular embodiments of the present disclosure are described hereinbelow with reference to the accompanying drawings. In the following description, well-known functions or constructions are not described in detail to avoid obscuring the present disclosure in unnecessary detail.

A generator according to the present disclosure can perform monopolar and/or bipolar electrosurgical procedures, including, for example, cutting, coagulation, ablation, and vessel sealing procedures. The generator may include a plurality of outputs for interfacing with various electrosurgical instruments (e.g., a monopolar instrument, return electrode, bipolar electrosurgical forceps, footswitch, etc.). Further, the generator includes electronic circuitry configured to generate radio frequency energy specifically suited for various electrosurgical modes (e.g., cut, blend, coagulate, division with hemostasis, fulgurate, spray, etc.) and procedures (e.g., monopolar, bipolar, vessel sealing). In embodiments, the generator may be embedded, integrated or otherwise coupled to the electrosurgical instruments providing for an all-in-one electrosurgical apparatus. In further embodiments, the generator may include a current sensor coil configured to sense current supplied to one or more electrosurgical instruments. The current sensor coil according to the present disclosure minimizes and/or eliminates, the unwanted signal that is coupled via the parasitic capacitances, which can lead to erroneous current sensor measurements. In embodiments, coupling is directed to ground through a shielding member. In further embodiments, the signal is zeroed by coupling an additional equal, but opposite voltage signal.

FIG. 1 is a perspective view of the components of one illustrative embodiment of a bipolar and monopolar electrosurgical system 10 according to the present disclosure. The system 10 may include one or more monopolar electrosurgical instruments 20 having one or more active electrodes 23 (e.g., electrosurgical cutting probe, ablation electrode(s),

6

etc.) for treating tissue of a patient. Electrosurgical alternating current is supplied to the instrument 20 by a generator 200 via a supply line 24 that is connected to an active terminal 230 (FIG. 3) of the generator 200, allowing the instrument 20 to cut, coagulate, ablate and/or otherwise treat tissue. The alternating current is returned to the generator 200 through a return electrode pad 26 via a return line 28 at a return terminal 232 (FIG. 3) of the generator 200. For monopolar operation, the system 10 may include a plurality of return electrode pads 26 that, in use, are disposed on a patient to minimize the chances of tissue damage by maximizing the overall contact area with the patient. In addition, the generator 200 and the return electrode pads 26 may be configured for monitoring tissue-to-patient contact to ensure that sufficient contact exists therebetween.

The system 10 may also include one or more bipolar electrosurgical instruments, for example, a bipolar electrosurgical forceps 30 having one or more electrodes for treating tissue of a patient. The electrosurgical forceps 30 includes a housing 31 and opposing jaw members 33 and 35 disposed at a distal end of a shaft 32. The jaw members 33 and 35 have one or more active electrodes 34 and a return electrode 36 disposed therein, respectively. The active electrode 34 and the return electrode 36 are connected to the generator 200 through cable 38 that includes the supply and return lines 24, 28 coupled to the active and return terminals 230, 232, respectively (FIG. 3). The electrosurgical forceps 30 is coupled to the generator 200 at a connector having connections to the active and return terminals 230 and 232 (e.g., pins) via a plug disposed at the end of the cable 38, wherein the plug includes contacts from the supply and return lines 24, 28 as described in more detail below.

With reference to FIG. 2, a front face 240 of the generator 200 is shown. The generator 200 may be any suitable type (e.g., electrosurgical, microwave, etc.) and may include a plurality of connectors 250, 252, 254, 256, 258, 260, 262 to accommodate various types of electrosurgical instruments (e.g., electrosurgical forceps 30, etc.).

The generator 200 includes a user interface 241 having one or more display screens or information panels 242, 244, 246 for providing the user with variety of output information (e.g., intensity settings, treatment complete indicators, etc.). Each of the screens 242, 244, 246 is associated with corresponding connectors 250-262. The generator 200 includes suitable input controls (e.g., buttons, activators, switches, touch screen, etc.) for controlling the generator 200. The display screens 242, 244, 246 are also configured as touch screens that display a corresponding menu for the electrosurgical instruments (e.g., electrosurgical forceps 30, etc.). The user then adjusts inputs by simply touching corresponding menu options.

Screen 242 controls monopolar output and the devices connected to the connectors 250 and 252. Connector 250 is configured to couple to a monopolar electrosurgical instrument (e.g., electrosurgical instrument 20) and connector 252 is configured to couple to a foot switch (not shown). The foot switch provides for additional inputs (e.g., replicating inputs of the generator 200). Connector 254 is configured to couple to electrode pad 26. Screen 244 controls monopolar and bipolar output and the devices connected to the connectors 256 and 258. Connector 256 is configured to couple to other monopolar instruments. Connector 258 is configured to couple to a bipolar instrument (not shown).

Screen 246 controls bipolar sealing procedures performed by the forceps 30 that may be plugged into the connectors 260 and 262. The generator 200 outputs energy through the connectors 260 and 262 suitable for sealing tissue grasped

by the forceps **30**. In particular, screen **246** outputs a user interface that allows the user to input a user-defined intensity setting. The user-defined setting may be any setting that allows the user to adjust one or more energy delivery parameters, such as power, current, voltage, energy, etc. or sealing parameters, such as energy rate limiters, sealing duration, etc. The user-defined setting is transmitted to a controller **224** of generator **200** (FIG. 3) where the setting may be saved in memory **226**. In embodiments, the intensity setting may be a number scale, such as for example, from one to ten or one to five. In embodiments, the intensity setting may be associated with an output curve of the generator **200**. The intensity settings may be specific for each forceps **30** being utilized, such that various instruments provide the user with a specific intensity scale corresponding to the forceps **30**.

FIG. 3 shows a schematic block diagram of the generator **200** configured to output electrosurgical energy. The generator **200** includes a controller **224**, a power supply **227**, and a radio-frequency (RF) amplifier **228**. The power supply **227** may be a high voltage, DC power supply connected to an AC source (e.g., line voltage) and provides high voltage, DC power to the RF amplifier **228** via leads **227a** and **227b**, which then converts high voltage, DC power into treatment energy (e.g., electrosurgical or microwave) and delivers the energy to the active terminal **230**. The current is returned thereto via the return terminal **232** as energy is dissipated into the tissue. The active and return terminals **230** and **232** are coupled to the RF amplifier **228** through an isolation transformer **229**. The RF amplifier **228** is configured to operate in a plurality of modes, during which the generator **200** outputs corresponding waveforms having specific duty cycles, peak voltages, crest factors, etc. It is envisioned that in other embodiments, the generator **200** may be based on other types of suitable power supply topologies.

The controller **224** includes a processor **225** operably connected to a memory **226**, which may include transitory type memory (e.g., RAM) and/or non-transitory type memory (e.g., flash media, disk media, etc.). The processor **225** includes an output port that is operably connected to the power supply **227** and/or RF amplifier **228** allowing the processor **225** to control the output of the generator **200** according to either open and/or closed control loop schemes. A closed loop control scheme is a feedback control loop, in which a plurality of sensors measure a variety of tissue and energy properties (e.g., tissue impedance, tissue temperature, output power, current and/or voltage, etc.), and provide feedback to the controller **224**. The controller **224** then signals the power supply **227** and/or RF amplifier **228**, which adjusts the DC and/or power supply, respectively. Those skilled in the art will appreciate that the processor **225** may be substituted for by using any logic processor (e.g., control circuit) adapted to perform the calculations and/or set of instructions described herein including, but not limited to, field programmable gate array, digital signal processor, and combinations thereof.

The generator **200** according to the present disclosure includes a plurality of sensors **280**, e.g., an RF current sensor **280a**, and an RF voltage sensor **280b**. Various components of the generator **200**, namely, the RF amplifier **228**, the RF current and voltage sensors **280a** and **280b**, may be disposed on a printed circuit board (PCB). The RF current sensor **280a** is coupled to the plurality of active leads **228a** and/or plurality of return leads **228b** and provides measurements of the RF current supplied by the RF amplifier **228**. The RF voltage sensor **280b** is coupled to the active and return terminals **230** and **232** and provides measurements of the RF

voltage supplied by the RF amplifier **228**. In embodiments, the RF current and voltage sensors **280a** and **280b** may be coupled to active and return leads **228a** and **228b**, which interconnect the active and return terminals **230** and **232** to the RF amplifier **228**, respectively.

The RF current and voltage sensors **280a** and **280b** provide the sensed RF voltage and current signals, respectively, to the controller **224**, which then may adjust output of the power supply **227** and/or the RF amplifier **228** in response to the sensed RF voltage and current signals. The controller **224** also receives input signals from the input controls of the generator **200**, the instrument **20** and/or forceps **30**. The controller **224** utilizes the input signals to adjust the power output by the generator **200** and/or performs other control functions thereon.

Transformers are conventionally used as current and voltage sensors as they provide a required patient isolation. However, the gain that transformers provide fluctuates due to temperature, signal amplitude, etc. This makes accurate readings difficult with respect to the phase and gain-bandwidth of the sensor signals. As a result, the signals need to be post-processed to arrive at accurate representations. The present disclosure provides for novel current sensor **280a** which overcome the problems of conventional sensors.

FIG. 4 shows an RF current sensor **300**, which includes a conditioning circuit **301** and a current sensor coil **302**. As used herein, the term “current sensor coil” refers to an electrical device for measuring alternating current (e.g., RF current) and includes an outer conductor coil (e.g., toroid) that acts as an active conductor wrapped around an inner conductor, a so-called “Bucking coil” that acts as a return conductor and a lead **228a** carrying the current passing through an opening **303** (FIG. 6) in the coil **302**. The coil **302** may have any suitable shape such as helical, toroidal, etc. In embodiments, the coil may have a polygonal cross-section. The current sensor coil **302** may include a low permeability core (e.g., air core) and provides a voltage output having a time-derivative of the current being measured to a conditioning circuit that integrates the output to provide a voltage signal indicative of the current. In embodiments, the current sensor coil **302** may be implemented on a printed circuit board and may include an opening so that the current sensor coil **302** may be wrapped about the conductor carrying the current to be measured. In further embodiments, the current sensor coil **302** may also be implemented using wire and may be wound around a toroidal magnetic core.

The current sensor coil **302** is coupled to conditioning circuit **301** having a resistor network **304**, which includes resistors **304a** and **304b**. In embodiments, the conditioning circuit **301** may be implemented as any integrator (e.g., logic processor) or differential amplifier. The resistor network **304** removes resonance of the coil **302** at its resonant frequency. As described in further details below with respect to FIGS. 5-9, the current sensor coil **302** is disposed about one or more active leads **228a** and the coil **302** is configured to measure the current passing therethrough as a sensor signal. The sensor signal from the coil **302** is then supplied to an optional gain amplifier **306** which increases the amplitude of the sensor signal and buffers the coil **302**. The gain amplifier **306** or the coil **302**, if the gain amplifier **306** is not used, is also coupled to an amplifier **308**, which is in turn, coupled to a bandpass filter **310**. The amplifier **308** is a differential-to-single-ended converter whose function is to convert the differential signal from the coil **302** to a single-ended signal. The amplifier **308** may have a monolithic configuration that provides improved common mode rejection.

The bandpass filter **310** removes higher and lower frequency components of the sensor signal which is then transmitted to an integrator **312**. Since the voltage that is induced in the current sensor coil **302** is proportional to the rate of change of current that is flowing through the active lead **228a**, the integrator **312** is utilized to provide an output sensor signal that is proportional to the current.

In embodiments, the integrator **312** may be coupled to a switchable attenuation circuit **314**, which may include one or more actively switched components. The attenuation circuit **314** may then be coupled to additional components such as an offset circuit **316**, analog-digital converters, and the like prior to supplying the signal to the controller **224**.

FIGS. 5-9 show the current sensor coil **302** according to the present disclosure. The coil **302** has a substantially circular shape having an opening **303** (FIG. 6) defined therethrough. The active lead **228a** is disposed through the opening **303** of the coil **302**, allowing the coil **302** to measure the current flow through the active lead **228a**. If the return lead **228b** is also being measured, additional traces may be used to provide for passage through the opening **303** of the current sensor coil **302** as described in detail below with respect to FIGS. 17-33.

As shown in FIGS. 5 and 6, the coil **302** has a substantially toroidal shape and is formed on a printed circuit board (PCB) **400** and includes an inner circumferential region **302a** and an outer circumferential region **302b**. The coil **302** includes forming an inner portion (“Bucking coil”) **405** of the coil **302** and an outer coil **407**. In embodiments, the coil **302** may have any other suitable shape (e.g., having a polygonal cross-section) with the outer coil **407** wrapped about the inner coil **405** and defining an opening through the coil **302**. In embodiments, the coil **302** may be a coil-wrapped phenolic toroid having a low permeability (μ).

In embodiments, where only one of the active leads **228a** is used, the magnetic field is reflective of the current I_p passing only through the active lead **228a**. The outer coil **407** detects the magnetic field in either embodiment and produces a first voltage corresponding to the first magnetic field. The outer coil **407** also may detect a second unwanted magnetic field and produces a second voltage corresponding to the second magnetic field. The second magnetic field is orthogonal to the first magnetic field and is not related to the sensed current. The inner coil **405** senses the second magnetic field and produces a third voltage proportional to the second magnetic field. The second voltage and third voltage produced have approximately the same magnitude such that they cancel each other. In embodiments where the plurality of active leads **228a** and/or plurality of return leads **228b** are disposed together, the current flowing through the active leads **228a** and return leads **228b** produce a net first magnetic field proportional to the sensed current I_s .

The PCB **400** may be a multilayer PCB formed from any suitable dielectric material, including, but not limited to composite materials composed of woven fiberglass cloth with an epoxy resin binder such as FR-4 grade as designated by National Electrical Manufacturers Association. As shown in FIG. 8, the PCB **400** includes a first or top layer **404a** and a bottom layer **404e**. For simplicity FIG. 5, FIG. 6, FIG. 8, and FIG. 9 will show only the active lead **230**. It will be understood that in every case a plurality of active leads and/or a plurality of return leads may be used. The active lead **228a** is coupled to conductive traces **408a** and **408f**, respectively, which are disposed over the top and bottom layers **404a** and **404e** as shown in FIGS. 8 and 9. The active lead **228a** may be coupled to a patient side connector **420** disposed on the PCB **400** as shown in FIG. 9. The traces

408a and **408f** are interconnected through the opening **303** (FIG. 6) using one or more vias **409a**, which pass through the entire PCB **400** (e.g., layers **404a-404e**).

The outer coil **407** includes a top trace **408b** disposed between the top layer **404a** and an intermediate layer **404b** of the PCB **400**. The outer coil **407** also includes a bottom trace **408e** disposed between the bottom layer **404e** and an intermediate layer **404d** of the PCB **400**. The traces **408b** and **408e** are interconnected by a plurality of inner vias **409b** and outer vias **409c**. The layers **404a** and **404e** insulate the coil **302** (e.g., outer coil **407**) conductive traces **408a** and **408f** and provide an isolation barrier between the patient and the generator **200**.

As shown in FIGS. 5-7, the inner vias **409b** are arranged to form the inner circumferential region **302a** of the coil **302** and the outer vias **409c** form the outer circumferential region **302b** of the coil **302**. The inner and outer vias **409b** and **409c** pass through the layers **404b**, **404c**, and **404d**. The inner vias **409b** and outer vias **409c** may be disposed in a concentric configuration. In a non-staggered configuration, corresponding inner and outer vias **409b** and **409c** lie along same rays. In a staggered configuration, the inner and outer vias **409b** and **409c** lie along alternating rays “r” as shown in FIGS. 5-7. The rays “r” are disposed at an angle “a” relative to each other and the inner vias **409b** are separated by a distance “d.” Each of the inner vias **409b** is connected to two neighboring outer vias **409c** through traces **408b** and **408e** and vice versa. The interconnection of the vias **409b** and **409c** with the traces **408b** and **408e** forms a plurality of loops, which in turn, form the outer coil **407** as shown in FIG. 5.

The outer coil **407** may include any suitable number of turns, in embodiments from about 50 turns to about 100 turns. The maximum number of turns depends on the radius of the inner circumferential region **302a**, via aspect ratio, thickness of the outer coil traces **407** and/or PCB **400**, and spacing between the turns based on the limits of manufacturability of the PCB material (e.g., trace to trace, trace to via, via annular pad dimension, anything that may limit the placement of the conductors on the PCB).

With reference to FIGS. 6 and 8, the inner coil **405** is disposed within the outer coil **407** and also has a substantially circular shape. The inner coil **405** may include an upper trace **408c** and a bottom trace **408d**. The traces **408c** and **408d** are disposed over a dielectric layer **404c**, such that the traces **408c** and **408d** are insulated from each other. The traces **408c** and **408d** may be electrically coupled to each other. In embodiments, the inner coil **405** may be formed from a single trace.

As shown in FIGS. 6 and 9, the coil **302** is coupled to the conditioning circuit **301** at a side connector **422**, which may also be disposed on the PCB **400**. The coil **302** includes a first terminal **410a** coupled to the inner coil **405** and a second terminal **410b** coupled to the outer coil **407**. In particular, the outer coil **407** is disposed over the inner coil **405** and is coupled thereto. Thus, two terminals **410a** and **410b** are disposed at one end of the coil **302**. The interconnection between the inner coil **405** and the outer coil **407** as well as the connection to the terminals **410a** and **410b** may be made through the vias **409b** and **409c**.

The controller **224** is provided to sensor signals from the sensor **300**, which are then utilized to determine the current. Various formulas may be utilized by the controller **224** to determine the current. The voltage produced by the coil **302** may be calculated using the formula (I):

11

$$V_{OUT} = \frac{-A_{LOOP} N_{LOOPS}}{2\pi R_{COIL}} \mu_0 \frac{dI}{dt} \quad (I)$$

In formula (I), A is the area of the turn (e.g., loop) formed by the vias **409b** and **409c** with the traces **408b** and **408e**, N is the number of turns, R is the major radius of the coil **302**, to is the magnetic constant, dI/dt is the rate of change of the current being measured by the coil **302**.

Inductance and capacitance of the coil may be calculated using the formulae (II)-(IV), respectively. Capacitance of the coil **302** is used to determine self-resonance and may be calculated using parallel-wire model formulae, namely, capacitances of inner and outer vias **409b** and **409c** and traces **408b** and **408e**.

$$L_{Coil} = \frac{\mu_0 \cdot N_{Turns}^2 \cdot I_{coil}}{2\pi} \ln \left(\frac{r_{coil_inner} + w_{coil}}{r_{coil_inner}} \right) \quad (II)$$

$$C_{Coil} = N_{Turns} \cdot (2 \cdot C_{trace-trace} + C_{via-inner} + C_{via-outer}) \quad (III)$$

$$C_{||} = \frac{\pi \cdot \epsilon_0 \cdot \epsilon_r \cdot l_{trace/via}}{\ln \left(\frac{d_{between_trace/via}}{2 \cdot r_{via/trace}} + \sqrt{\frac{d_{between_trace/via}^2}{r_{via/trace}^2} - 1} \right)} \quad (IV)$$

In formulae (II)-(IV), in addition to the variable and constants utilized in formula (I), t is thickness (e.g., distance between conductive traces **408b** and **408e**), r is radius, w is the radial distance between inner and outer circumferential regions **302a** and **302b**, Rcoil_inner is the radial distance to the inner circumferential region **302a**, l is length, Co is vacuum permittivity constant, and ϵ_r is the relative dielectric constant of the PCB.

With reference to FIGS. **4** and **10-15**, components of conditioning circuit **301** of the sensor **300** is shown. Since the coil **302** provides a differentiating response, the output must be integrated to provide the actual response through the conditioning circuit **301** of the sensor **300**. The output of the coil **302** is integrated to produce a signal that is proportional to the current in the active lead **228a**. The conditioning circuit **301** provides integration with the integrator **312**. This allows for easy adjustability of the sensor gain, utilization in the control loop and processing by an analog-digital converter. Gain may be set by adjusting the frequency setpoint of the integrator **312**. The setpoint may be achieved by selection of hardware component values (e.g., discrete resistor or capacitor substitution), selection of software values (e.g., digital or analog potentiometers or adjustable capacitors), including programmable gain amplifiers as described in detail below, or combinations thereof.

The gain amplifier **306** of the conditioning circuit **301** is shown in FIG. **10** and includes a pair of operational amplifiers **306a** and **306b** configured to provide differential gain without adding to the common-mode gain. The sensor signal from the coil **302** is provided to the positive terminals of the amplifiers **306a** and **306b**. The outputs of the amplifiers **306a** are interconnected by a gain setting voltage divider network **306c** including three resistors **306d**, **306e**, **306f**. Terminal resistors **306d** and **306f** are coupled in parallel with capacitors **306g** and **306h**, respectively. The signal from the parallel circuits is coupled to the negative terminals of the amplifiers **306a** and **306b**, which provide closed-loop feed-

12

back thereto. Capacitors **306g** and **306h** provide amplifier stabilization and may also provide for the integration of the signal.

The output of each of the operational amplifiers **306a** and **306b** is provided to the differential to single-ended amplifier **308**, which is shown in FIG. **11**. In particular, the output of the amplifiers **306a** and **306b** is supplied to the positive and negative inputs of the amplifier **308**. The amplifier **308** combines the output of the amplifiers **306a** and **306b** to provide a single output to the bandpass filter **310**. The amplifier **308** includes a closed feedback circuit having a reference signal connected to ground including a resistor **308a**, which is connected in series with a capacitor **308b** that is coupled in parallel with a resistor **308c**. The bandpass filter **310** includes a high-pass filter **309** and a low-pass filter **311** as shown in FIGS. **12** and **13**, respectively. In embodiments, the output from the amplifier **308** may be passed through the high-pass filter **309** before being passed through the low-pass filter **311**, or vice versa.

The high-pass filter **309** is configured to pass high frequencies and attenuate lower frequencies. The high-pass filter **309** includes an operational amplifier **309a**. The output from the amplifier **308** is provided to the input of the amplifier **309a** through a first capacitor **309b** coupled in series with a second capacitor **309c** and a first resistor **309d** and a second resistor **309e**. The negative input of the amplifier **309a** is provided by a feedback loop from a third resistor **309f** coupled in series with a grounded fourth resistor **309g**.

The low-pass filter **311** is configured to pass low frequencies and attenuates higher frequencies. The low-pass filter **311** includes an operational amplifier **311a**. The input from the high-pass filter **309** is provided to the input of the amplifier **311a** through a first resistor **311b** coupled in series with a second resistor **311c** and a first capacitor **311d** and a second capacitor **311e**. The negative input of the amplifier **311a** is provided by a feedback loop from a third resistor **311f** coupled in series with a grounded fourth resistor **311g**.

Since the voltage that is induced in the current sensor coil **302** is proportional to the rate of change of current that is flowing through the active lead **228a**, the integrator **312** is utilized to provide an output signal that is proportional to the sensed current. In embodiments, a leaky integrator may be used. As used herein the term "leaky integrator" refers to an integrator having a low-pass filter as described in further detail below with respect to FIG. **14**. The integrator **312** includes an amplifier **312a** with a positive input thereof coupled to a ground. The input from the bandpass filter **310** is fed through a low-pass filter **312b**, which includes a first resistor **312c** coupled in series with a second resistor **312d** that is coupled in parallel with a capacitor **312e**. The second resistor **312d** and the capacitor **312e** are also coupled to the output of the amplifier **312a** thereby providing a closed loop feedback thereto. The input signal is then fed to the negative input of the amplifier **312a**.

The integrator **312** provides a negative slope of voltage gain verses frequency. This compensates, or flattens the opposite slope of the signal coming from the coil **302**. Further, the integrator **312** has extremely high DC gain. The frequency band of interest for the generator **200** is well above DC. The integrator gain would create problems if a DC offset were present at its input. The high-pass portion of the band-pass filter **310** reduces the low frequency components and reduces any DC offset, which mitigates issues caused by the integrator's amplification of these components.

FIG. 15 shows a graph 500 illustrating individual gain response of the coil 302, the integrator 312, and the combined response of the coil 302 and the integrator 312. The graph 500 shows the overall response of the coil 302 as a plot 502, the response of the integrator 312 as a plot 504, and the combined response of the coil 302 and the integrator 312 of the sensor 300 as a plot 506, which is a combination of the plots 502 and 504. Frequency, f_1 , is determined by the response of the integrator 312 and frequency, f_2 , is determined by the resonant frequency of the coil 302.

With reference to FIGS. 16 and 17, the active lead 228a carries both common-mode (CM) and differential-mode (DM) current. For the purpose of measuring energy delivered to the patient, DM current can provide useful data. Thus, having a system and method of separating the DM current from the CM current in a conductor would then allow for more accurate sensors. In a single-conductor Rogowski coil, the CM current and DM current are indistinguishable from one another.

With continued reference to FIG. 17, by adding a second conductor, namely, the return lead 228b, and appropriately orienting the return lead 228b through differential-mode RF current sensor 600 a signal as a function of the DM current. The relationship between the measured current and the sensor signal V_{signal} depends on the core being used in the RF current sensor.

As illustrated in FIG. 17, the CM currents on the active lead 228a and return lead 228b pass through the center of the current sensor 600, but in opposite directions. The flux produced by CM currents cancel each other out, and the current sensor 600 produces zero signal in proportion to the CM current. The DM currents pass through the current sensor 600 in the same direction due to the routing of the active lead 228a and return lead 228b, namely, looping of the return lead 228b. The flux produced by DM currents are additive, and the current sensor 600 produces a signal that is based on the sum of (e.g., twice of) the DM current. If an iron or ferrite core is being used, then V_{signal} is proportional to the DM current, thus in FIG. 16, V_{signal} is proportional to the sum of CM and DM currents and in FIG. 17 V_{signal} is proportional to the sum of only the DM currents. If an air core is being used, then V_{signal} is proportional to time rate of change of V_{signal} , thus in FIG. 16, V_{signal} is proportional to a derivative of the sum of CM and DM currents and in FIG. 17 V_{signal} is proportional to the sum of time derivative of only the DM currents. Although the above-described embodiment is related to a Rogowski coil as a current sensor, the disclosed orientation of the active and return leads may be applied to any type of a current-sense transformer.

FIG. 18 shows a current sensor assembly 604 including the differential-mode RF current sensor 600 and a fully differential condition circuit 650 according to the present disclosure. The current sensor 600 includes a current sensor coil 602 and is shown schematically in FIG. 19. The current sensor 600 is configured to measure individual first and second currents of active and return leads 228a and 228b or a net current. Current transformers are configured to measure either common-mode current or differential-mode current flow. In a typical application using power electronics, such as an inverter for generating alternating current, complex currents flow which have both differential and common-mode components which make up the totality of the flowing current.

The current flowing through each of the leads 228a and 228b generates a corresponding magnetic field within the current sensor 600. The net magnetic field then affects the

current sensor 600, which detects the differential-mode current. The embodiment of the current sensor coil 602 of FIG. 19 is configured as a differential-mode current sensor since it allows for use with multiple active and return leads 228a, 228b and 228c, 228d (FIG. 33).

The current sensor 600 and the conditioning circuit 650 provide a completely differential signal, which provides better noise immunity. First and second terminals 612a and 612b of the current sensor coil 602 are coupled to the conditioning circuit 650. Current sensor coil 602 also includes a third terminal 612c as described in further detail below with respect to FIG. 26A.

Each of the first and second terminals 612a, 612b is coupled to a differential integrator 637, which includes a plurality of resistors 635a, 635b. The differential integrator 637 compensates for the derivative nature of the sensor signal from the current sensor coil 602 as described above with respect to the current sensor coil 302. One or more of the resistors 635a, 635b may be coupled to differential gain switches (e.g., MOSFETs, analog switches, relays etc.) 636a, 636b, respectively. The switches 636a, 636b are configured to change the value of the resistors 635a, 635b, respectively, to adjust the gain of the conditioning circuit 650.

The resistors 635a, 635b are coupled to input terminals of an amplifier 638. The differential integrator 637 also includes capacitors 638a, 638b coupled to the amplifier 638. The differential integrator 637 is, in turn, coupled to an active bandpass filter 640, which also includes an amplifier 641 and associated circuit components. The bandpass filter 640 is then coupled to an analog-to-digital converter 642, which then transmits the converted digital signal to the controller 224.

FIG. 20 is a graph 700 of a gain response of the current sensor assembly 604 of FIG. 18 according to the present disclosure. The graph 700 shows individual and combined gain responses of the current sensor coil 602, differential integrator 637, and the bandpass filter 640. The graph 700 shows the overall response of the current sensor coil 602 as a plot 702, the response of the differential integrator 637 as a plot 704, and the response of the bandpass filter 640 as a plot 706. The graph 700 also shows the combined response of the current sensor coil 602, differential integrator 637, and the bandpass filter 640 as a plot 708, which is a combination of the plots 702, 704, and 706. Frequency, f_1 , is determined by the response of the differential integrator 637 and the bandpass filter 640, and frequency, f_2 , is determined by the bandpass filter 640.

In certain situations, the RF energy passing through the leads 228a and 228b may have relatively high voltage but low current. Undesired voltage signal from the leads 228a and 228b, which acts as primary conductors can couple to the current sensor coil 602, which acts as a secondary winding, producing a significant error signal. The present disclosure provides for systems and methods for reducing the error signal due to voltage coupling between the active leads 228a and 228b and the current sensor coil 602. In particular, the present disclosure provides for specific arrangement of the active and/or return leads 228a, 228b relative to the current sensor coil 602 such that the undesired voltage signal is coupled as a common-mode signal and is then cancelled or reduced by the common rejection capabilities of the conditioning circuit 650. The present disclosure also provides for shielding the current sensor coil 602 to minimize coupling of the voltage signal. In embodiments, any combinations of arrangement of the active and/or return

leads **228a**, **228b** and/or shielding may be utilized to minimize coupling of the voltage signal.

With reference to FIGS. **21** and **22**, the voltage coupling due to parasitic capacitance is described. FIGS. **21** and **22** illustrate the generator **200** including the RF amplifier **228** supplying RF current, I_p , through the active lead **228a** with the current sensor coil **602** sensing the primary current, I_p , passing therethrough. The primary current, I_p , induces a secondary current, I_s , in the current sensor coil **602**, which develops a voltage, V_o .

In situations where the voltage at the active lead **228a** is relatively large but the primary current, I_p , is low (e.g., near zero), the resulting V_o should also be near zero. With reference to FIG. **22**, the high voltage capacitively couples from the active lead **228a** to the current sensor coil **602**, as represented schematically by a parasitic capacitance C_{p1} , which produces an erroneous output voltage.

FIG. **23** shows an embodiment of the present disclosure for reducing or eliminating erroneous output voltage signal output by the conditioning circuit **650**. The present disclosure provides for a system of positioning the active leads **228a** and/or return leads **228b** in such a way as to balance the capacitive coupling therefrom to the current sensor coil **602**. The conditioning circuit **650** then reduces the erroneous output voltage due to its common-mode rejection capability.

The active lead **228a** is passed through the current sensor coil **602** to generate a second parasitic coupling capacitance, C_{p2} , which is also coupled to the current sensor coil **602**. In particular, the capacitances C_{p1} and C_{p2} are coupled symmetrically about the sensor current sensor coil **602**. The capacitance C_{p2} couples a voltage from the active lead **228a** to the current sensor coil **602** similarly to the capacitance C_{p1} , thereby balancing the circuit such that the resulting voltage is a common-mode voltage, which is then rejected by the conditioning circuit **650**.

FIG. **24** shows another embodiment of the present disclosure for reducing or eliminating erroneous output voltage by the conditioning circuit **650**. The current sensor **600** includes one or more shielding members **606** disposed between the active leads **228a** and the current sensor coil **602** to prevent or reduce the voltage coupling from active lead **228a** to current sensor coil **602**.

FIGS. **25A-E** show an embodiment of the current sensor **600** including a circular current sensor coil **602** disposed on a printed circuit board (PCB) **601**, which may be formed using the techniques described above with respect to the current sensor coil **302** of FIGS. **5-9**. The current sensor **600** includes one or more active leads **228a**, **228c** and return leads **228b**, **228d** passing through an opening **603** of the current sensor coil **602**. The leads **228a**, **228b**, **228c**, **228d** may be any suitable conductive leads (e.g., wires) having an insulating sheath. In embodiments, the leads **228a**, **228b**, **228c**, **228d** may be printed as conductive traces on the PCB **601** and passed through the current sensor coil **602** as vias, such as traces **408a** and **408f** and via **409a** as described above with respect to FIGS. **5** and **9**.

The current sensor **600** also includes a pair of shielding members **606a** and **606b** disposed over upper and lower surfaces of the current sensor coil **602**. With reference to FIG. **25E**, the shielding member **606a** is shown and described, which is substantially similar to the shielding member **606b**. The shielding member **606a** is formed from a conductive material and is coupled to a ground "g" as shown in FIG. **24**. The shielding member **606a** includes an opening **608** therethrough for passage of leads **228a**, **228b**, **228c**, **228d**. The shielding member **606a** is configured and dimensioned to substantially cover the current sensor coil

602. Since the current sensor coil **602** is disposed on the PCB **601**, the shielding members **606a** and **606b** may be substantially flat. The shielding member **606a** may be a discrete conductive layer attached to the PCB **601** on which the current sensor coil **602** is disposed using any suitable fasteners, adhesives, and combinations thereof.

In embodiments, the shielding members **606a**, **606b**, may be formed as layers on the PCB **601** as shown in FIG. **25E**. As a result, the PCB **601** may include additional dielectric layers (e.g., outer dielectric layers) to accommodate the shielding members **606a**, **606b** as integrated layers. The shielding members **606a**, **606b** may be printed as a conductive layer on the PCB **601** as described above with respect to the printing of the current sensor coil **302**. This configuration may be used in embodiments in which the leads **228a**, **228b**, **228c**, **228d** are formed as vias and traces. In particular, an additional dielectric layer may be disposed on top of the conductive trace **408b** (FIG. **8**), on top of which the shielding member **606a** is then formed, as well as below conductive trace **408e** (FIG. **8**), below which the shielding member **606b** is then formed.

The current sensor **600** also includes a pair of opposing spacers **610a** and **610b**. The spacers **610a** and **610b** are formed from a dielectric material and when assembled define an opening therethrough which aligns with the opening **603** of the current sensor coil **602**. The leads **228a**, **228b**, **228c**, **228d** are wrapped around and through the spacers **610a** and **610b** as shown in FIG. **25D** to maintain the leads **228a**, **228b**, **228c**, **228d** in a predetermined spatial relationship relative to themselves and the current sensor coil **602** to cancel and/or reduce the effects of parasitic capacitance as described above. The current sensor **600** also includes a pair of opposing housing portions **630a**, **630b** enclosing the interior components of the current sensor **600**. The housing portions **630a**, **630b** also secure leads **228a**, **228b**, **228c**, **228d** relative to each other and the current sensor coil **602**.

With reference to FIGS. **26A-31C**, embodiments of a single-wire orientation of the active lead **228a** about the current sensor coil **602** are shown. The coil **602** includes forming an inner coil **605** and an outer coil **607**. With specific reference to FIG. **26A**, the current sensor coil **602** at a first end **609** includes two terminals **612a** and **612b** coupled to the outer coil **607** and the third terminal **612c** coupled to the inner coil **605**. The third terminal **612c** also couples the inner coil **605** to the ground at the first end **609**. The inner coil **605** center taps the outer coil **607** at a second end **611** as described in further detail below with respect to FIGS. **26B** and **26C**.

With continued reference to FIG. **26A**, the outer coil **607** includes a semi-circular first portion **607a** and a semi-circular second portion **607b** and the inner coil **605** includes a semi-circular first portion **605a** and a semi-circular second portion **605b**. The first and second portions **605a**, **605b** and **607a**, **607b** are disposed symmetrically (e.g., on left and right sides) about an axis "X-X" defined between diametrically opposed (e.g., 180° apart) first and second ends **609** and **611** of the current sensor coil **602**, respectively.

With reference to FIGS. **26B** and **26C**, enlarged schematic views of the first and second ends **609** and **611** of the current sensor coil **602**, respectively, are shown. The first portion **607a** of the outer coil **607** is coupled between the first terminal **612a** on top (e.g., at first end **609**) and a first connection **611a** of the first portion **605a** of the inner coil **605** on the bottom (e.g., at second end **611**). The second portion coil **607b** of the outer coil **607** is coupled between the second terminal **612b** on top (e.g., at first end **609**) and a second connection **611b** of the second portion **605b** of the

inner coil 605 on bottom (e.g., at second end 611). Each of the first and second portions 605a, 605b of the inner coil 605 is coupled between the third terminal 612c at the first end 609 of the current sensor coil 602 and their respective connections 611a, 611b at second end 611 of the current sensor coil 602.

With reference to FIGS. 26D-F, a top portion of the active lead 228a is passed across a top surface 602a of the current sensor coil 602 and is disposed in a $-\alpha$ orientation, e.g., at an angle α relative to the axis "X-X." A bottom portion of active lead 228 extends through the opening 603 and across a bottom surface 602b of the current sensor coil 602 such that the bottom portion of active lead 228a is disposed in a $+\alpha$ orientation relative to the axis "X-X." It should be appreciated that movement in the $-\alpha$ direction along sensor coil 602 in FIG. 26D corresponds to movement in a downwardly direction along sensor coil 602 in FIG. 26F. Similarly, movement in the $+\alpha$ direction along sensor coil 602 in FIG. 26D corresponds to movement in an upwardly direction along sensor coil 602 in FIG. 26F.

The active lead 228a is disposed symmetrically about the axis "X-X" across the top and bottom surfaces 602a, 602b of the current sensor coil 602 such that the erroneous voltage signals, V_e , generated by the active lead 228a are canceled out. In particular, the portion of the active lead 228a disposed on the top surface 602a and the portion of the active lead 228a disposed on the bottom surface 602b are symmetrical about the axis "X-X."

The top portion of active lead 228a creates capacitive coupling or parasitic capacitance C_t within the sensor coil 602 at location L1 (FIG. 26F). Similarly, the bottom portion of active lead 228a creates capacitive coupling or parasitic capacitance C_b within sensor coil 602 at location L2 (FIG. 26F). Two operating points identified as "P1" and "P2" in FIG. 26E correspond to locations L1 and L2, respectively, in FIG. 26F. An error signal V_e is generated at location L1 and an error signal V_e is created at location L2. The differential amplifier takes the difference of these two error signals to generate an output of zero (i.e., $V_x = V_e - V_e = 0$). With the inner coil 605 attached at the center of the outer coil 607, the capacitive coupling is balanced, causing the erroneous signal to be a common-mode voltage. Thus the differential circuitry causes the erroneous error signal to be removed. Accordingly, the embodiments of sensor circuit 602 provided above are balanced, have shielding, or are both balanced and have shielding such that the circuits produce little to no output signal V_x when there is no input current.

FIG. 26E shows a plot 800 illustrating a logarithmic ratio of output voltage V_x of the amplifier to the voltage on active lead 228a vs. angular location. The logarithmic ratio is calculated using the equation of $20 \text{ Log}(|V_x|/|V_{in}|)$, in which V_x is the output of the differential amplifier and V_{in} is the voltage on active lead 228a. Operating points "P1" and "P2" correspond to the locations L1 and L2 of the parasitic capacitances C_t , C_b shown in FIG. 26F. The slope of the graph illustrates sensitivity, i, of the output voltage V_x of the differential amplifier as a function of positional angle between the axis "X-X" and the active lead 228a. As the angle increases from about 0° to about 90° , the sensitivity to erroneous voltage signals V_e of the current sensor coil 602 decreases. This relationship may be used to locate the active lead 228a relative to the axis "X-X" to obtain the most accurate reading of the current passing therethrough while minimizing the interference caused by the erroneous voltage signals V_e .

With reference to FIGS. 27A-B, 28A-B, 29A-C, 30A-C, and 31A-C, multiple embodiments of single wire configura-

tions of the sensor coil 602 are shown. With specific reference to FIGS. 27A and 27B, sensor coil 602 includes a length of wire, namely the inner coil 605, passing through the middle of the sensor coil 602 such that the wire extends from a first end 609 to a second end 611 of sensor coil 602. The top surface of sensor coil 602 in FIG. 27A corresponds to the left side of sensor coil 602 in FIG. 27B. Similarly, the bottom surface of sensor coil 602 in FIG. 27A corresponds to the right side of sensor coil 602 in FIG. 27B.

With respect to FIG. 28A, sensor coil 602 is shown, differing from sensor coil 602 shown in FIG. 27A by the addition of wire 228a running through the central opening in sensor coil 602. Assuming there is no current traveling through the wire 228a, the output of the sensor coil 602 should be ideally zero. The wire 228a is in close proximity to the sensor coil 602 and will capacitively couple via C_t an undesired error voltage, V_e , from the wire 228a to the sensor coil 602. The position of wire 228a relative to the sensor coil 602 determines the location at which the error voltage is coupled, and thus affects how the circuit processes the signal. This, in turn, affects the output signal V_o .

FIGS. 29A-C, FIGS. 30A-C, and FIGS. 31A-C show additional single-wire configurations of the sensor coil 602. With specific reference to FIG. 29A, the wire 228a is routed on the top and the bottom of sensor coil 602. Thus, each of the top and bottom portions of wire 228a couples to the sensor coil 602 forming a parasitic capacitance C_t , C_b , as shown in FIG. 29C. Since both C_t and C_b are at 0 degrees relative to the axis "X-X," they are capacitively coupled to the center tap of the sensor coil 602, which is grounded and therefore signal V_e is zero, hence, V_x is also zero. This corresponds to the operating points "P1" and "P2" shown in FIG. 29B representative of a low error signal. Although this configuration provides for a low error signal, any movement in α yields a large change in error voltage.

FIG. 30A shows both top and bottom portions of active lead 228a disposed in $+\alpha$ direction. As shown in FIG. 30C, the top and bottom portions of active lead 228a are capacitively coupled at the same location due to the overlap of the active lead 228a on the sensor coil 602, but off the center tap due to the placement of active lead 228a in FIG. 30A as compared to the configuration shown in FIGS. 29A-C. An error signal V_e , is coupled into the sensor coil 602 by each of the top and bottom portions of the active lead 228a. This corresponds to the operating points "P1" and "P2" shown in FIG. 30B representative of error signal. The error signal is coupled to the negative input of the amplifier, and produces an output of $V_x = -2V_e$, since two active leads 228a are coupling to the same location.

FIG. 31A shows the top and bottom portions of active lead 228a moved in the $-\alpha$ direction. The top and bottom portions of active lead 228a are capacitively coupled at the same location due to the overlap of the active lead 228a on the sensor coil 602, but off the center tap due to the placement of active lead 228a in FIG. 31A as compared to the configuration shown in FIGS. 29A-C. An error signal V_e , is coupled into the sensor coil 602 by each of the top and bottom portions of the active lead 228a. This corresponds to the operating points "P1" and "P2" shown in FIG. 31B representative of error signal. The error signal is coupled to the positive input of the amplifier, and produces an output of $V_x = +2V_e$, since two active leads 228a are coupling to the same location.

With reference to FIGS. 32A and 32B, a two-wire orientation of the active lead 228a and return lead 228b about the current sensor coil 602 is shown schematically. The active and return leads 228a, 228b are passed across the top surface

19

602a of the current sensor coil 602, through the opening 603, and across the bottom surface 602b of the current sensor coil 602. The top and bottom portions of the active lead 228a are symmetrical about the axis "X-X" at a first angle, $-\alpha$ and $+\alpha$, respectively, and the top and bottom portions of the return lead 228b are symmetrical about the axis "X-X" at a second angle, $+\beta$ and $-\beta$, respectively. The active and return leads 228a, 228b may be disposed at an angle $\pm\alpha$, $\pm\beta$, respectively, from about 0° to about 90° relative to the axis "X-X." In embodiments, angles $\pm\alpha$, $\pm\beta$ may be the same, as shown in FIG. 32B, or different, as shown in FIG. 32A.

With reference to FIG. 33, multiple active leads 228a and 228c and multiple return leads 228b and 228d may be used depending on the number of outputs within the generator 200, e.g., bipolar, monopolar, etc. The active and return leads 228a, 228c and 228b, 228d are also disposed in a symmetrical relationship (e.g., transverse to the axis "X-X") relative to each other about the axis "X-X," such that the erroneous voltage signals are cancelled.

In embodiments, any number of active and return leads 228a, 228c and 228b, 228d may be wrapped about the current sensor coil 602 as illustrated in FIG. 33. This configuration may include two pairs of active and return leads 228a, 228c, and 228b, 228d, which may be disposed in an overlapping relationship, such that active and return leads 228a, 228c and 228b, 228d, respectively are disposed over each other. This arrangement may be used with a differential-mode current transformer configuration.

While several embodiments of the disclosure have been shown in the drawings and/or discussed herein, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

What is claimed is:

1. A sensor for sensing current, the sensor comprising: a current sensor coil defining an opening therethrough and having a top surface and a bottom surface; and an active lead passing through the opening of the current sensor coil, the active lead including:
 - a top portion extending parallel with and over the top surface of the current sensor coil at a first non-zero acute angle relative to an axis that extends through a first end of the current sensor coil and a center of the opening of the current sensor coil; and
 - a bottom portion extending parallel with and over the bottom surface of the current sensor coil at a second non-zero acute angle relative to the axis, the first non-zero acute angle and the second non-zero acute angle being symmetrical relative to each other about the axis.
2. The sensor according to claim 1, wherein the current sensor coil includes:
 - an outer coil;
 - a pair of first and second terminals coupled to the outer coil at the first end of the current sensor coil; and
 - an inner coil coupled to and disposed within the outer coil.
3. The sensor according to claim 2, wherein the current sensor coil is configured to output a differential signal indicative of a current within the at least one active lead.
4. The sensor according to claim 2, wherein the current sensor coil is disposed within a printed circuit board.

20

5. The sensor according to claim 4, wherein the current sensor coil further includes a shielding member disposed over the outer coil.

6. The sensor according to claim 5, wherein the printed circuit board includes:

- a plurality of outer conductive traces each coupled to the active lead, the plurality of outer conductive traces being interconnected by at least one via through the printed circuit board.

7. The sensor according to claim 6, wherein the printed circuit board includes:

- a top dielectric layer;
- a first dielectric intermediate layer;
- a bottom dielectric layer; and
- a second dielectric intermediate layer.

8. The sensor according to claim 7, wherein the outer coil includes:

- a plurality of top conductive traces disposed between the top dielectric layer and the first dielectric intermediate layer of the printed circuit board;

- a plurality of bottom conductive traces disposed between the bottom dielectric layer and the second dielectric intermediate layer of the printed circuit board, wherein the plurality of outer conductive traces are disposed over an outer surface of the bottom dielectric layer and the top dielectric layer; and

- a plurality of inner and outer vias interconnecting the pluralities of top conductive traces and the pluralities of bottom conductive traces.

9. The sensor according to claim 8, wherein the shielding member is disposed over an outer dielectric layer disposed over the outer surface of at least one of the top dielectric layer or the bottom dielectric layer.

10. The sensor according to claim 7, wherein the inner coil includes:

- a conductive trace disposed within the outer coil and between the first and second dielectric intermediate layers of the printed circuit board.

11. The sensor according to claim 3, wherein each of the outer coil and the inner coil includes first and second portions, the first and second portions being separated at a second end of the current sensor coil, which is opposite the first end.

12. The sensor according to claim 11, further comprising: a conditioning circuit configured to at least one of integrate, amplify, or filter the differential signal to output a processed signal indicative of the current of the differential signal.

13. The sensor according to claim 12, wherein the conditioning circuit is coupled to the first terminal and the second terminal, which are coupled to the first portion and the second portion of the outer coil, respectively, at the first end of the current sensor coil, and the first portion and the second portion of the inner coil are coupled to a third terminal at the first end of the current sensor coil.

14. The sensor according to claim 13, wherein the first portion of the outer coil and the first portion of the inner coil are coupled to each other at the second end and the second portion of the outer coil and the second portion of the inner coil are coupled to each other at the second end.

15. An electrosurgical generator, comprising:

- a radio frequency output stage configured to output at least one radio frequency waveform;

- a sensor including:

- a current sensor coil defining an opening therethrough and having a top surface and a bottom surface; and

21

an active lead passing through the opening of the current sensor coil, the active lead including:
 a top portion extending parallel with and over the top surface of the current sensor coil at a first non-zero acute angle relative to an axis that extends through a first end of the current sensor coil and a center of the opening of the current sensor coil; and
 a bottom portion extending parallel with and over the bottom surface of the current sensor coil at a second non-zero acute angle relative to the axis, the first non-zero acute angle and the second non-zero acute angle being symmetrical relative to each other about the axis.

16. The electrosurgical generator according to claim 15, further comprising a return lead coupled to the radio frequency output stage and passing through the current sensor coil, wherein the current sensor coil is configured to output a second signal indicative of a current within the return lead.

17. The electrosurgical generator according to claim 15, wherein the current sensor coil includes:

22

an outer coil;
 a pair of first and second terminals coupled to the outer coil at the first end of the current sensor coil; and
 an inner coil coupled to and disposed within the outer coil.

18. The electrosurgical generator according to claim 17, wherein the current sensor coil is configured to output a differential signal indicative of a current within the active lead.

19. The electrosurgical generator according to claim 18, wherein the current sensor coil is disposed within a printed circuit board.

20. The electrosurgical generator according to claim 19, wherein the current sensor coil further includes a shielding member disposed over the outer coil and the printed circuit board includes a plurality of outer conductive traces each coupled to the active lead, the plurality of outer conductive traces being interconnected by at least one via through the printed circuit board.

* * * * *