



(51) International Patent Classification:

F02M 35/108 (2006.01) *F02B 37/00* (2006.01)
B64D 33/02 (2006.01) *F02C 6/12* (2006.01)
F01C 1/22 (2006.01) *F02C 7/04* (2006.01)
F02B 33/40 (2006.01) *F02M 31/20* (2006.01)

(21) International Application Number:

PCT/CA2016/050162

(22) International Filing Date:

19 February 2016 (19.02.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/118,891 20 February 2015 (20.02.2015) US
 14/806,883 23 July 2015 (23.07.2015) US

(71) Applicant: **PRATT & WHITNEY CANADA CORP.**
 [CA/CA]; 1000 Marie-Victorin, (01BE5), Longueuil,
 Québec J4G 1A1 (CA).

(72) Inventors: **THOMASSIN, Jean**; 2325 De Rome, Ste-Julie,
 Québec J3E 2K2 (CA). **BOLDUC, Stéphane**; 2139
 boul. De Boucherville, St-Bruno-de-Montarville, Québec
 J3V 4J1 (CA). **VILLENEUVE, Bruno**; 918 Nicole-Le-
 maire, Boucherville, Québec J4B 5P7 (CA). **BERUBE,**
Stéphane; 1345 Route Edouard VII, St-Philippe, Québec
 J0L 2K0 (CA). **FONTAINE, Mike**; 1325, rue de Bour-
 gogne, Boucherville, Québec J4B 7W9 (CA). **GAGNON-**
MARTIN, David; 2150 rue des Iris, Longueuil, Québec

J4J 1P6 (CA). **JULIEN, André**; 464, Place de la Mitrelle,
 Ste-Julie, Québec J3E 3P1 (CA). **CUNNINGHAM, Mark**;
 4630 Mariette Avenue, Montréal, Québec H4B 2G2 (CA).
LAFORTUNE, Serge; 2270 Pierre, Mascouche, Québec
 J7K 3C2 (CA). **LEGARE, Pierre-Yves**; 41, rue Laurier,
 Chambly, Québec J3L 5S4 (CA).

(74) Agent: **NORTON ROSE FULBRIGHT CANADA**
LLP/S.E.N.C.R.L., S.R.L.; Suite 2500, 1 place Ville-Mar-
 ie, Montreal, Québec H3B 1R1 (CA).

(81) Designated States (unless otherwise indicated, for every
 kind of national protection available): AE, AG, AL, AM,
 AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
 BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
 DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
 HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
 KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
 MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
 PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
 SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
 TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
 kind of regional protection available): ARIPO (BW, GH,
 GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
 TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
 TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
 DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
 LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
 SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
 GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ENGINE INTAKE ASSEMBLY WITH SELECTOR VALVE




FIG. 6A

(57) Abstract: An intake assembly for a compressor providing compressed air to an internal combustion engine core, including an air conduit having at least one heat exchanger extending thereacross, an intake plenum for the compressor, a first intake conduit connected to the air conduit upstream of the heat exchanger(s), a second intake conduit connected to the air conduit downstream of the heat exchanger(s), and a selector valve configurable between a first configuration to allow a fluid communication between the intake plenum and the air conduit through the first intake conduit and a second configuration to prevent the fluid communication through the first intake conduit. Fluid communication between the intake plenum and the air conduit through the second intake conduit is allowed at least when the selector valve is in the second configuration. An engine assembly and method of supplying air to a compressor are also discussed.



Declarations under Rule 4.17:

Published:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))* — *with international search report (Art. 21(3))*

ENGINE INTAKE ASSEMBLY WITH SELECTOR VALVE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority from U.S. application No. 14/806,883 filed July 23, 2015 and U.S. provisional application No. 62/118,891 filed February 20, 2015, the entire contents of which are incorporated by reference herein.

TECHNICAL FIELD

[0002] The application relates generally to compound engine assemblies and, more particularly, to supercharged or turbocharged compound engine assemblies used in aircraft.

BACKGROUND OF THE ART

[0003] Compound engine assemblies including a compressor used as a supercharger or turbocharger may define a relatively bulky assembly which may be difficult to fit into existing aircraft nacelles, thus creating some difficulty in adapting them for aircraft applications.

SUMMARY

[0004] In one aspect, there is provided an intake assembly for a compressor providing compressed air to an internal combustion engine core, the intake assembly comprising: an air conduit having at least one heat exchanger extending thereacross such that an airflow through the air conduit circulates through the at least one heat exchanger, each of the at least one heat exchanger configured to circulate a fluid to be cooled in heat exchange relationship with the airflow circulating therethrough; an intake plenum configured for connection to an inlet of the compressor; a first intake conduit providing fluid communication between the intake plenum and the air conduit and connected to the air conduit upstream of the at least one heat exchanger; a second intake conduit providing fluid communication between the intake plenum and the air conduit and connected to the air conduit downstream of the at least one heat exchanger; and a selector valve configurable between a first configuration where the selector valve allows the fluid communication between the intake plenum and the air conduit through the first intake conduit and a second configuration where the selector valve prevents the

fluid communication between the intake plenum and the air conduit through the first intake conduit, the fluid communication between the intake plenum and the air conduit through the second intake conduit being allowed at least when the selector valve is in the second configuration.

[0005] In another aspect, there is provided an engine assembly comprising: an engine core including at least one internal combustion engine each including a rotor sealingly and rotationally received within a respective internal cavity to provide rotating chambers of variable volume in the respective internal cavity; a compressor having an outlet in fluid communication with an inlet of the engine core; a first intake conduit in fluid communication with an inlet of the compressor and with a first source of air; a second intake conduit in fluid communication with the inlet of the compressor and with a second source of air warmer than the first source of air; and a selector valve configurable to selectively open and close at least the fluid communication between the inlet of the compressor and the first intake conduit.

[0006] In a further aspect, there is provided a method of supplying air to a compressor providing compressed air to an internal combustion engine core, the method comprising: directing air through an air conduit and through at least one heat exchanger extending across the air conduit; directing part of the air from the air conduit to an inlet of the compressor through a selected one of a first and second intake conduits, the first intake conduit connected to the air conduit upstream of the at least one heat exchanger and the second intake conduit connected to the air conduit downstream of the at least one heat exchanger; and preventing the air from flowing from the air conduit to the inlet of the compressor through the other one of the first and second conduits.

DESCRIPTION OF THE DRAWINGS

[0007] Reference is now made to the accompanying figures in which:

[0008] Fig. 1 is a schematic view of a compound engine assembly in accordance with a particular embodiment;

[0009] Fig. 2 is a cross-sectional view of a Wankel engine which can be used in a compound engine assembly such as shown in Fig. 1, in accordance with a particular embodiment;

[0010] Fig. 3 is a schematic tridimensional view of the compound engine assembly of Fig. 1 in accordance with a particular embodiment;

[0011] Fig. 4 is a schematic cross-sectional view of a nacelle installation of the compound engine assembly of Fig. 3, in accordance with a particular embodiment;

[0012] Fig. 5 is a schematic tridimensional view of an intake assembly of the compound engine assembly of Fig. 4, in accordance with a particular embodiment;

[0013] Fig. 6A is a schematic side cross-sectional view of part of the intake assembly of Fig. 5;

[0014] Fig. 6B is an enlarged schematic side cross-sectional view of part of the intake assembly of Fig. 6A; and

[0015] Fig. 7 is a schematic tridimensional view of an inlet lip of the intake assembly of Fig. 5, in accordance with a particular embodiment.

DETAILED DESCRIPTION

[0016] Described herein are a compound engine assembly 10 and its installation for a propeller airplane. In the embodiment shown, the compound engine assembly 10 includes a liquid cooled heavy fueled multi-rotor rotary engine core 12 and a turbine section 18 used as an exhaust energy recovery system. As will be detailed below, other configurations for the engine core 12 are also possible.

[0017] Referring to Fig. 1, the engine core 12 has an engine shaft 16 driven by the rotary engine(s) and driving a rotatable load, which is shown here as a propeller 8. It is understood that the compound engine assembly 10 may alternately be configured to drive any other appropriate type of load, including, but not limited to, one or more generator(s), drive shaft(s), accessory(ies), rotor mast(s), compressor(s), or any other appropriate type of load or combination thereof. The compound engine assembly 10 further includes a compressor 14, and a turbine section 18 compounding power with the engine core 12.

[0018] The engine core 12 may include 2, 3, 4 or more rotary engines drivingly engaged to the shaft 16. In another embodiment, the engine core 12 includes a single rotary engine. Each rotary engine has a rotor sealingly engaged in a

respective housing, with each rotary engine having a near constant volume combustion phase for high cycle efficiency. The rotary engine(s) may be Wankel engine(s). Referring to Fig. 2, an exemplary embodiment of a Wankel engine is shown. Each Wankel engine comprises a housing 32 defining an internal cavity with a profile defining two lobes, which is preferably an epitrochoid. A rotor 34 is received within the internal cavity. The rotor defines three circumferentially-spaced apex portions 36, and a generally triangular profile with outwardly arched sides. The apex portions 36 are in sealing engagement with the inner surface of a peripheral wall 38 of the housing 32 to form three working chambers 40 between the rotor 34 and the housing 32.

[0019] The rotor 34 is engaged to an eccentric portion 42 of the shaft 16 to perform orbital revolutions within the internal cavity. The shaft 16 performs three rotations for each orbital revolution of the rotor 34. The geometrical axis 44 of the rotor 34 is offset from and parallel to the axis 46 of the housing 32. During each orbital revolution, each chamber 40 varies in volume and moves around the internal cavity to undergo the four phases of intake, compression, expansion and exhaust.

[0020] An intake port 48 is provided through the peripheral wall 38 for successively admitting compressed air into each working chamber 40. An exhaust port 50 is also provided through the peripheral wall 38 for successively discharging the exhaust gases from each working chamber 40. Passages 52 for a glow plug, spark plug or other ignition element, as well as for one or more fuel injectors (not shown) are also provided through the peripheral wall 38. Alternately, the intake port 48, the exhaust port 50 and/or the passages 52 may be provided through an end or side wall 54 of the housing; and/or, the ignition element and a pilot fuel injector may communicate with a pilot subchamber (not shown) defined in the housing 32 and communicating with the internal cavity for providing a pilot injection. The pilot subchamber may be for example defined in an insert (not shown) received in the peripheral wall 38.

[0021] In a particular embodiment the fuel injectors are common rail fuel injectors, and communicate with a source of Heavy fuel (e.g. diesel, kerosene (jet fuel), equivalent biofuel), and deliver the heavy fuel into the engine(s) such that the combustion chamber is stratified with a rich fuel-air mixture near the ignition source and a leaner mixture elsewhere.

[0022] For efficient operation the working chambers 40 are sealed, for example by spring-loaded apex seals 56 extending from the rotor 34 to engage the peripheral wall 38, and spring-loaded face or gas seals 58 and end or corner seals 60 extending from the rotor 34 to engage the end walls 54. The rotor 34 also includes at least one spring-loaded oil seal ring 62 biased against the end wall 54 around the bearing for the rotor 34 on the shaft eccentric portion 42.

[0023] Each Wankel engine provides an exhaust flow in the form of a relatively long exhaust pulse; for example, in a particular embodiment, each Wankel engine has one explosion per 360° of rotation of the shaft, with the exhaust port remaining open for about 270° of that rotation, thus providing for a pulse duty cycle of about 75%. By contrast, a piston of a reciprocating 4-stroke piston engine typically has one explosion per 720° of rotation of the shaft with the exhaust port remaining open for about 180° of that rotation, thus providing a pulse duty cycle of 25%.

[0024] In a particular embodiment which may be particularly but not exclusively suitable for low altitude, each Wankel engine has a volumetric expansion ratio of from 5 to 9, and operates following the Miller cycle, with a volumetric compression ratio lower than the volumetric expansion ratio, for example by having the intake port located closer to the top dead center (TDC) than an engine where the volumetric compression and expansion ratios are equal or similar. Alternately, each Wankel engine operates with similar or equal volumetric compression and expansion ratios.

[0025] It is understood that other configurations are possible for the engine core 12. The configuration of the engine(s) of the engine core 12, e.g. placement of ports, number and placement of seals, etc., may vary from that of the embodiment shown. In addition, it is understood that each engine of the engine core 12 may be any other type of internal combustion engine including, but not limited to, any other type of rotary engine, and any other type of non-rotary internal combustion engine such as a reciprocating engine.

[0026] Referring back to Fig. 1, the rotary engine core 12 is supercharged with the compressor 14 mounted in-line with the engine core, i.e. the compressor rotor(s) 14a rotate co-axially with the engine shaft 16. In the embodiment shown, the compressor rotor(s) 14a are engaged on a compressor shaft 15, and the engine shaft 16 is in driving engagement with the compressor shaft 15 through a step-up

gearbox 20. In a particular embodiment, the gearbox 20 is a planetary gear system. In a particular embodiment, the compressor shaft 15 includes a sun gear 20s which is drivingly engaged to carrier-mounted planet gears 20p, which are drivingly engaged to a fixed ring gear 20r. The rotating carrier assembly is connected to the engine shaft 16, for example through a splined connection. In a particular embodiment, the planetary gear system elements (sun gear, planet gears and ring gear) within the gearbox 20 are configured to define a speed ratio of about 7:1 between the compressor shaft 15 and engine core shaft 16. It is understood that any other appropriate configuration and/or speed ratio for the gearbox 20 may alternately be used.

[0027] In the embodiment shown and referring particularly to Fig. 1, the compressor 14 is a centrifugal compressor with a single rotor 14a. Other configurations are alternately possible. The compressor 14 may be single-stage device or a multiple-stage device and may include one or more rotors having radial, axial or mixed flow blades.

[0028] The outlet of the compressor 14 is in fluid communication with the inlet of the engine core 12, which corresponds to or communicates with the inlet of each engine of the engine core 12. Accordingly, air enters the compressor 14 and is compressed and circulated to the inlet of the engine core 12. In a particular embodiment, the compressor 14 includes variable inlet guide vanes 22 through which the air circulates before reaching the compressor rotor(s) 14a.

[0029] The engine core 12 receives the pressurized air from the compressor 14 and burns fuel at high pressure to provide energy. Mechanical power produced by the engine core 12 drives the propeller 8.

[0030] Each engine of the engine core 12 provides an exhaust flow in the form of exhaust pulses of high pressure hot gas exiting at high peak velocity. The outlet of the engine core 12 (i.e. the outlet of each engine of the engine core 12) is in fluid communication with the inlet of the turbine section 18, and accordingly the exhaust flow from the engine core 12 is supplied to the turbine section 18.

[0031] The turbine section 18 includes at least one rotor engaged on a turbine shaft 19. Mechanical energy recovered by the turbine section 18 is compounded with that of the engine shaft 16 to drive the propeller 8. The turbine shaft 19 is mechanically

linked to, and in driving engagement with, the engine shaft 16 through a reduction gearbox 24, for example through an offset gear train with idler gear. In a particular embodiment, the elements of the reduction gearbox 24 (e.g. offset gear train) are configured to define a reduction ratio of approximately 5:1 between the turbine shaft 19 and the engine shaft 16. The engine shaft 16 is also mechanically linked to, and in driving engagement with, the propeller 8 through the same reduction gearbox 24. In a particular embodiment, the reduction gearbox 24 includes two gear train branches: a compounding branch 24c mechanically linking the turbine shaft 19 and the engine shaft 16 and a downstream planetary branch 24p mechanically linking the engine shaft 16 and propeller 8. In another embodiment, the turbine shaft 19 and engine shaft 16 may be engaged to the propeller 8 through different gearboxes, or the turbine shaft 19 may be engaged to the engine shaft 16 separately from the engagement between the engine shaft 16 and the propeller 8. In particular embodiment, the turbine shaft 19 is engaged to the compressor gearbox 20.

[0032] As can be seen in Figs. 1 and 3, the turbine shaft 19 is parallel to and radially offset from (i.e., non-coaxial to) the engine shaft 16 and compressor shaft 15. The compressor rotor(s) 14a and engine shaft 16 are thus rotatable about a common axis (central axis of the compressor and engine shafts 15, 16) which is parallel to and radially offset from the axis of rotation of the turbine rotor(s) 26a, 28a (central axis of the turbine shaft 19). In a particular embodiment, the offset configuration of the turbine section 18 allows for the turbine section 18 to be enclosed in a casing separate from that of the engine core 12 and the compressor 14, such that the turbine section 18 is modular and removable (e.g. removable on-wing) from the remainder of the compound engine assembly 10.

[0033] Referring particularly to Fig. 1, the turbine section 18 may include one or more turbine stages. In a particular embodiment, the turbine section 18 includes a first stage turbine 26 receiving the exhaust from the engine core 12, and a second stage turbine 28 receiving the exhaust from the first stage turbine 26. The first stage turbine 26 is configured as a velocity turbine, also known as an impulse turbine, and recovers the kinetic energy of the core exhaust gas while creating minimal or no back pressure to the exhaust of the engine core 12. The second stage turbine 28 is configured as a pressure turbine, also known as a reaction turbine, and completes the recovery of available mechanical energy from the exhaust gas. Each turbine 26, 28 may be a centrifugal or axial device with one or more rotors having radial, axial or

mixed flow blades. In another embodiment, the turbine section 18 may include a single turbine, configured either as an impulse turbine or as a pressure turbine.

[0034] A pure impulse turbine works by changing the direction of the flow without accelerating the flow inside the rotor; the fluid is deflected without a significant pressure drop across the rotor blades. The blades of the pure impulse turbine are designed such that in a transverse plane perpendicular to the direction of flow, the area defined between the blades is the same at the leading edges of the blades and at the trailing edges of the blade: the flow area of the turbine is constant, and the blades are usually symmetrical about the plane of the rotating disc. The work of the pure impulse turbine is due only to the change of direction in the flow through the turbine blades. Typical pure impulse turbines include steam and hydraulic turbines.

[0035] In contrast, a reaction turbine accelerates the flow inside the rotor but needs a static pressure drop across the rotor to enable this flow acceleration. The blades of the reaction turbine are designed such that in a transverse plane perpendicular to the direction of flow, the area defined between the blades is larger at the leading edges of the blades than at the trailing edges of the blade: the flow area of the turbine reduces along the direction of flow, and the blades are usually not symmetrical about the plane of the rotating disc. The work of the pure reaction turbine is due mostly to the acceleration of the flow through the turbine blades.

[0036] Most aeronautical turbines are not “pure impulse” or “pure reaction”, but rather operate following a mix of these two opposite but complementary principles – i.e. there is a pressure drop across the blades, there is some reduction of flow area of the turbine blades along the direction of flow, and the speed of rotation of the turbine is due to both the acceleration and the change of direction of the flow. The degree of reaction of a turbine can be determined using the temperature-based reaction ratio (equation 1) or the pressure-based reaction ratio (equation 2), which are typically close to one another in value for a same turbine:

$$(1) \text{Reaction}(T) = \frac{(t_{S3} - t_{S5})}{(t_{S0} - t_{S5})}$$

$$(2) \text{Reaction}(P) = \frac{(P_{S3} - P_{S5})}{(P_{S0} - P_{S5})}$$

where T is temperature and P is pressure, s refers to a static port, and the numbers refers to the location the temperature or pressure is measured: 0 for the inlet of the turbine vane (stator), 3 for the inlet of the turbine blade (rotor) and 5 for the exit of the turbine blade (rotor); and where a pure impulse turbine would have a ratio of 0 (0%) and a pure reaction turbine would have a ratio of 1 (100%).

[0037] In a particular embodiment, the first stage turbine 26 is configured to take benefit of the kinetic energy of the pulsating flow exiting the engine core 12 while stabilizing the flow and the second stage turbine 28 is configured to extract energy from the remaining pressure in the flow while expanding the flow. Accordingly, the first stage turbine 26 has a smaller reaction ratio than that of the second stage turbine 28.

[0038] In a particular embodiment, the second stage turbine 28 has a reaction ratio higher than 0.25; in another particular embodiment, the second stage turbine 28 has a reaction ratio higher than 0.3; in another particular embodiment, the second stage turbine 28 has a reaction ratio of about 0.5; in another particular embodiment, the second stage turbine 28 has a reaction ratio higher than 0.5.

[0039] In a particular embodiment, the first stage turbine 26 has a reaction ratio of at most 0.2; in another particular embodiment, the first stage turbine 26 has a reaction ratio of at most 0.15; in another particular embodiment, the first stage turbine 26 has a reaction ratio of at most 0.1; in another particular embodiment, the first stage turbine 26 has a reaction ratio of at most 0.05.

[0040] It is understood that any appropriate reaction ratio for the second stage turbine 28 (included, but not limited to, any of the above-mentioned reaction ratios) can be combined with any appropriate reaction ratio for the first stage turbine 26 (included, but not limited to, any of the above-mentioned reaction ratios), and that these values can correspond to pressure-based or temperature-based ratios. Other values are also possible. For example, in a particular embodiment, the two turbines 26, 28 may have a same or similar reaction ratio; in another embodiment, the first stage turbine 26 has a higher reaction ratio than that of the second stage turbine 28. Both turbines 26, 28 may be configured as impulse turbines, or both turbines 26, 28 may be configured as pressure turbines.

[0041] In an embodiment where the engine core 12 includes one or more rotary engine(s) each operating with the Miller cycle, the compressor pressure ratio and the turbine section pressure ratio may be higher than a similar engine assembly where the engine core includes one or more rotary engine(s) having similar or equal volumetric compression and expansion ratios. The higher pressure ratio in the turbine section may be accommodated by additional axial turbine stage(s), an additional radial turbine, and/or a combination of axial and radial turbines suitable to accept the higher pressure ratio.

[0042] Referring to Fig. 4, a nacelle installation of the compound engine assembly 10 according to a particular embodiment is shown. The installation includes an intake assembly 66 which features a common inlet 68 and air conduit 70 for the engine assembly (through the compressor 14) and the oil and coolant heat exchangers 72, 74. The air conduit 70 extends from the inlet 68 to an opposed outlet 76. The inlet 68 and outlet 76 of the air conduit 70 communicate with ambient air outside of or around the assembly 10, for example ambient air outside of a nacelle receiving the assembly. In the embodiment shown, the ambient air penetrates the compound engine assembly 10 through the inlet 68 of the air conduit 70 – the inlet 68 of the air conduit 70 thus defines a nacelle inlet, i.e. an inlet of the assembly 10 as a whole.

[0043] It can be seen that the heat exchangers 72, 74 extend across the air conduit 70, such that the airflow through the air conduit 70 circulates through the heat exchangers 72, 74. In the embodiment shown, the heat exchangers 72, 74 include an oil heat exchanger 72 which receives the oil from the engine assembly oil system and circulates it in heat exchange relationship with the airflow, such as to cool the oil; and a coolant heat exchanger 74 which receives the coolant from the engine core 12 (e.g. water, oil or other liquid coolant) and circulates it in heat exchange relationship with the airflow, such as to cool the coolant. Although two heat exchangers 72, 74 are shown, it is understood that alternately a single heat exchanger or more than two heat exchangers may be provided in the air conduit 70. The two heat exchangers 72, 74 are shown as being placed in parallel, such that a portion of the airflow separately circulates through each heat exchanger. Alternately, the heat exchangers 72, 74 may be placed in the air conduit 70 in series such that the same portion of the airflow circulates through one than through the other of the heat exchangers, although such a configuration may necessitate the use of larger

heat exchangers. It is also understood that the angle of the heat exchangers 72, 74 within the conduit 70 may be different from that shown. In a particular embodiment, the angle of the heat exchangers 72, 74 with respect to the airflow within the conduit 70 is selected to obtain a desired balance between pressure losses and effectiveness of the heat exchangers, in consideration of the available space within the conduit 70.

[0044] The intake assembly 66 includes an intake plenum 78 configured for connection to and fluid communication with the inlet of the compressor 14. In the embodiment shown and as can be more clearly seen in Fig. 5, the intake plenum 78 is annular. Other configurations are possible.

[0045] Referring to Figs. 4, 5 and 6A, the intake assembly 66 includes first and second intake conduits 80, 82 providing fluid communication between the air conduit 70 and the intake plenum 78. The first intake conduit 80 is connected to the air conduit 70 upstream of the heat exchangers 72, 74, so that the portion of the air conduit 70 upstream of the heat exchangers 72, 74 defines a first source of air. The second intake conduit 82 is connected to the air conduit 70 downstream of the heat exchangers 72, 74, so that the portion of the air conduit 70 downstream of the heat exchangers 72, 74 defines a second source of air warmer than the first source. In the embodiment shown and as can be more clearly seen in Fig. 4, the air conduit 70 is configured to define a diffuser upstream of the heat exchangers 72, 74, such as to decelerate the flow to a low velocity flow at the inlet of the heat exchangers 72, 74. The first intake conduit 80 is connected in the diffuser; in a particular embodiment, the first intake conduit 80 is connected to the air conduit 70 where air velocity is at a minimum. Such a configuration may allow for minimizing of pressure losses.

[0046] Referring to Figs. 6A-6B, in a particular embodiment, the intake conduits 80, 82 are in fluid communication with the intake plenum 78 through an engine intake 84 containing an air filter 86. An air filter bypass valve 88 is provided in the engine intake 84 to allow airflow to the intake plenum 78 around the air filter 86 in case of inadvertent air filter blockage. In a particular embodiment, the air filter bypass valve 86 is a spring loaded pressure differential operated valve.

[0047] The intake assembly 66 further includes a selector valve 90 positioned upstream of the air filter 86 and allowing for the selection of the intake conduit 80, 82

used to circulate the air from the air conduit 70 to the intake plenum 78. The selector valve 90 is thus configurable between a configuration where the fluid communication between the intake plenum 78 and the air conduit 70 through the first intake conduit 80 is allowed and a configuration where the fluid communication between the intake plenum 78 and the air conduit 70 through the first intake conduit 80 is prevented.

[0048] In the particular embodiment shown in Fig. 4, the selector valve 90 only acts to selectively block or prevent the communication through the first intake conduit 80, i.e. the intake conduit connected to the air conduit 70 upstream of the heat exchangers 72, 74. The communication through the second intake conduit 82 remains open in both configurations.

[0049] In the particular embodiment shown in Figs. 6A and 6B, the selector valve 90 is provided at a junction between the two intake conduits 80, 82, and acts to selectively block or prevent the communication through both intake conduits 80, 82. Accordingly, in the configuration shown in Fig. 6A, the selector valve 90 allows the fluid communication between the intake plenum 78 and the air conduit 70 through the first intake conduit 80 while preventing the fluid communication between the intake plenum 78 and the air conduit 70 through the second intake conduit 82; and in the configuration shown in Fig. 6B, the selector valve 90 prevents the fluid communication between the intake plenum 78 and the air conduit 70 through the first intake conduit 80 while allowing the fluid communication between the intake plenum 78 and the air conduit 70 through the second intake conduit 82. In the embodiments shown, the selector valve 90 includes a flap pivotable between the two configurations, and blocks the communication through one or the other of the intake conduits 80, 82 by blocking the communication between that intake conduit 80, 82 and the intake plenum 78. Other types of valves 90 and/or valve positions are also possible.

[0050] The selector valve 90 thus allows for the selection of cooler air (first intake conduit 80, taking air upstream of the heat exchangers 72, 74) or warmer air (second intake conduit 82, taking air downstream of the heat exchangers 72, 74) to feed the compressor 14 and engine assembly 10, based on the operating conditions of the engine assembly 10. For example, in icing conditions, the fluid communication through the second conduit 82 may be selected by blocking the fluid communication through the first conduit 80, so that that the warmer air from downstream of the heat

exchangers 72, 74 is used to feed the compressor 14, such as to provide de-icing capability for the engine intake 84, air filter 86, intake plenum 78 and compressor inlet with fixed and variable geometries; and in non-icing flight conditions, the fluid communication through the first conduit 80 may be selected so that colder air is used to feed the compressor 14 to provide for better engine performance (as compared to hotter air).

[0051] Also, selection of the flow through the second intake conduit 84 to extract the engine air downstream of the heat exchangers 72, 74 can be used to generate airflow through the heat exchangers 72, 74. For example, for a turboprop engine at ground idle, there is no inlet ram pressure to force air through the air conduit 70 and heat exchangers 72, 74, and the propeller pressure rise may not be sufficient to draw enough air to provide sufficient cooling in the heat exchangers 72, 74; similar conditions may occur at taxi operations on the ground (engine at low power). Extracting the engine air downstream of the heat exchangers 72, 74 produces a “sucking” effect pulling the air through the heat exchangers 72, 74, which in a particular embodiment may allow for sufficient cooling without the need of a fan or blower to provide for the necessary air circulation. A bleed-off Valve 75 can optionally be provided downstream of the compressor 14 and upstream of the engine core 12 (i.e. in the fluid communication between the compressor outlet and the engine core inlet), and opened during idle or taxi operation to increase compressor flow such as to increase the “sucking” effect of extracting the engine air downstream of the heat exchangers 72, 74, and accordingly increase the airflow through the heat exchangers 72, 74. Moreover, an intercooler may optionally be provided just upstream of the engine core 12 to cool the compressor flow prior to routing it to the engine core.

[0052] In a particular embodiment, the engine intake assembly 66 can be configured as an inertial particle separator when the fluid communication through the first conduit 80 is selected, so that when the air from upstream of the heat exchangers 72, 74 is used to feed the engine, the heavy particles are entrained downstream of the heat exchangers 72, 74. In the embodiment shown in Fig. 4, the junction between the first conduit 80 and the air conduit 70 is configured as the inertial particle separator: the first conduit 80 defines a sharp turn with respect to the air conduit 70 (e.g. by extending close to or approximately perpendicular thereto), extending at a sufficient angle from the air conduit 70 such that the heavier particles

(e.g. ice, sand) continue on a straight path while the air follows the sharp turn, and by the first conduit 80 and air conduit 70 are sized to achieve adequate air velocities to ensure separation of the particles.

[0053] In the embodiment shown, the air conduit 70 is configured such that all of the air entering the air conduit 70 is circulated through the heat exchangers 72, 74 and/or to the intake plenum 78. Alternately, a bypass conduit could be provided such that a portion of the air entering the conduit 70 is diverted from (i.e. bypasses) the heat exchangers 72, 74 and the intake plenum 78 and is instead directly circulated to the outlet 76. In a particular embodiment, the junction between the bypass conduit and the air conduit 70 is configured as the inertial particle separator, through selection of an appropriate orientation and relative sizing of the bypass conduit with respect to the air conduit 70.

[0054] In a particular embodiment and as shown in Fig. 7, the lip of the assembly inlet 68 is de-iced by circulating hot coolant through a coil tube 98 disposed in the lip and made of material having appropriate heat conduction properties. The coil tube 98 has an inlet in fluid communication with the coolant system of the engine core 12 and an outlet in fluid communication with the coolant heat exchanger 74, such that a fraction of the hot coolant flowing out of the engine core 12 is routed to the coil tube 98 of the inlet lip 68 for de-icing, and then rejoins the remainder of the hot coolant flow from the engine core 12 prior to sending the flow to the heat exchanger 74.

[0055] Although in the embodiment shown the heat exchangers 72, 74 and engine assembly 10 have a common inlet 68 and the first and second intake conduits 80, 82 communicate with a same air conduit 70 extending from that inlet, it is understood that alternately the engine assembly 10 and heat exchangers 72, 74 may have separate inlets. The first intake conduit 80 may thus communicate with a source of fresh air separate from that feeding the heat exchangers 72, 74.

[0056] Alternately, the common inlet 68 and air conduit 70 used to feed the heat exchangers 72, 74 and the compressor 14 may be used with a single intake conduit providing the fluid communication between the intake plenum 78 and the air conduit 70, and connected to the air conduit 70 at any appropriate location (downstream or upstream of the heat exchangers).

[0057] Referring back to Fig. 4, in a particular embodiment, variable cowl flaps 92 are pivotally connected to an outer wall 94 of the air conduit 70 downstream of the heat exchangers 72, 74, each adjacent a respective opening 96 defined through the outer wall 94. The flaps 92 are movable between an extended position (shown) where they extend away from the respective opening 96 and a retracted position where they close the respective opening 96, such as to modulate the airflow through the air conduit 70 and heat exchangers 72, 74. The openings 96 communicate with ambient air outside of or around the assembly 10 when the flaps are extended, for example ambient air outside of a nacelle receiving the assembly, such that air from the air conduit 70 may exit the conduit through the openings 96. In a particular embodiment, the cowl flaps 92 are positioned in accordance with the power demand on the engine assembly 10, such as to regulate the temperature of the oil and coolant being cooled in the heat exchangers 72, 74 while reducing or minimizing cooling drag; for example, the cowl flaps 92 are open at take-off and closed at cruise speed.

[0058] The cowl flaps 92 may have any appropriate configuration. For example, in a particular embodiment, the cowl flaps 92 have a straight airfoil shape; in another embodiment, the cowl flaps 92 have a cambered airfoil shape, configured to flow the exit air horizontally to produce a more effective thrust. In a particular embodiment, the cowl flaps 92 are configured as louvers, each connected to a rod, and an actuator slides the rod to pivot the cowl flaps 92 between the extended and retracted positions to open or close the louvers. Other configurations are also possible.

[0059] In a particular embodiment, the air conduit outlet 76 downstream of the cowl flaps 92 is shaped to define a nozzle, to form an exit jet opening. In a particular embodiment, the configuration of the nozzle is optimized to minimize the drag induced by the heat exchangers 72, 74 at the cruise speed operating conditions.

[0060] Although any of the above described and shown features and any combination thereof may provide for a suitable configuration to be used as a turboprop engine and/or be received in an aircraft nacelle, in a particular embodiment, the combination of all of the above described and shown features of the compound engine assembly provide for an engine configuration specifically tailored for use as an aircraft turboprop engine.

[0061] The above description is meant to be exemplary only, and one skilled in the art will recognize that changes may be made to the embodiments described without departing from the scope of the invention disclosed. For example, although the engine assembly has been described as a compound engine assembly, it is understood that elements of the compound engine assembly can be used with non-compounded engine assemblies, and with compound engine assemblies having different configurations, for example engine assemblies where the compressor is in driving engagement with the turbine section without being directly engaged to the engine core; such elements include, but are not limited to, the intake assembly and its components. Still other modifications which fall within the scope of the present invention will be apparent to those skilled in the art, in light of a review of this disclosure, and such modifications are intended to fall within the appended claims.

CLAIMS

1. An intake assembly for a compressor providing compressed air to an internal combustion engine core, the intake assembly comprising:
 - an air conduit having at least one heat exchanger extending thereacross such that an airflow through the air conduit circulates through the at least one heat exchanger, each of the at least one heat exchanger configured to circulate a fluid to be cooled in heat exchange relationship with the airflow circulating therethrough;
 - an intake plenum configured for connection to an inlet of the compressor;
 - a first intake conduit providing fluid communication between the intake plenum and the air conduit and connected to the air conduit upstream of the at least one heat exchanger;
 - a second intake conduit providing fluid communication between the intake plenum and the air conduit and connected to the air conduit downstream of the at least one heat exchanger; and
 - a selector valve configurable between a first configuration where the selector valve allows the fluid communication between the intake plenum and the air conduit through the first intake conduit and a second configuration where the selector valve prevents the fluid communication between the intake plenum and the air conduit through the first intake conduit, the fluid communication between the intake plenum and the air conduit through the second intake conduit being allowed at least when the selector valve is in the second configuration.
2. The intake assembly as defined in claim 1, wherein the selector valve in the first configuration prevents the fluid communication between the intake plenum and the air conduit through the second intake conduit.
3. The intake assembly as defined in claim 2, wherein the selector valve includes a flap located at a junction between the first and second intake conduits and pivotable between the first and second configurations, the flap in the first configuration

preventing the fluid communication between the second intake conduit and the intake plenum, the flap in the second configuration preventing the fluid communication between first intake conduit and the intake plenum.

4. The intake assembly as defined in claim 1, wherein the at least one heat exchanger includes two heat exchangers extending in parallel across the air conduit.
5. The intake assembly as defined in claim 1, wherein the air conduit defines a diffuser upstream of the at least one heat exchanger, the first intake conduit connected to the air conduit in the diffuser.
6. The intake assembly as defined in claim 1, further comprising an air filter between the intake plenum and the first and second intake conduits.
7. The intake assembly as defined in claim 1, wherein a junction between the first conduit and the air conduit is configured as an inertial particle separator.
8. An engine assembly comprising:
 - an engine core including at least one internal combustion engine each including a rotor sealingly and rotationally received within a respective internal cavity to provide rotating chambers of variable volume in the respective internal cavity;
 - a compressor having an outlet in fluid communication with an inlet of the engine core;
 - a first intake conduit in fluid communication with an inlet of the compressor and with a first source of air;
 - a second intake conduit in fluid communication with the inlet of the compressor and with a second source of air warmer than the first source of air; and
 - a selector valve configurable to selectively open and close at least the fluid communication between the inlet of the compressor and the first intake conduit.

9. The engine assembly as defined in claim 8, wherein the selector valve closes the fluid communication between the inlet of the compressor and the second intake conduit when the fluid communication between the inlet of the compressor and the first intake conduit is open and opens the fluid communication between the inlet of the compressor and the second intake conduit when the fluid communication between the inlet of the compressor and the first intake conduit is closed.
10. The engine assembly as defined in claim 8, comprising an air conduit having at least one heat exchanger extending thereacross such that an airflow through the air conduit circulates through the at least one heat exchanger, each of the at least one heat exchanger configured to circulate a fluid of the engine assembly in heat exchange relationship with the airflow circulating therethrough, the first source of air being a portion of the air conduit located upstream of the at least one heat exchanger, and the second source of air being a portion of the air conduit located downstream of the at least one heat exchanger.
11. The engine assembly as defined in claim 10, wherein the at least one heat exchanger includes first and second heat exchangers extending in parallel across the air conduit, the first heat exchanger in fluid communication with an oil system of the engine assembly and the second heat exchanger in fluid communication with a coolant system of the engine core.
12. The engine assembly as defined in claim 10, wherein the air conduit defines a diffuser upstream of the at least one heat exchanger, the first intake conduit communicating with the air conduit in the diffuser.
13. The engine assembly as defined in claim 8, further comprising a turbine section having an inlet in fluid communication with an outlet of the engine core and configured to compound power with the engine core.
14. The engine assembly as defined in claim 13, further comprising a bleed-off valve in the fluid communication between the outlet of the compressor and the inlet of the engine core.

15. The engine assembly as defined in claim 10, further comprising a turbine section having an inlet in fluid communication with an outlet of the engine core and configured to compound power with the engine core.
16. The engine assembly as defined in claim 8, wherein the rotor of each of the at least one internal combustion engine has three apex portions separating the rotating chambers and mounted for eccentric revolutions within the respective internal cavity, the respective internal cavity having an epitrochoid shape with two lobes.
17. The engine assembly as defined in claim 8, wherein the first and second intake conduits are in fluid communication with the inlet of the compressor through an intake plenum, the assembly further comprising an air filter between the intake plenum and the first and second intake conduits.
18. A method of supplying air to a compressor providing compressed air to an internal combustion engine core, the method comprising:
- directing air through an air conduit and through at least one heat exchanger extending across the air conduit;
 - directing part of the air from the air conduit to an inlet of the compressor through a selected one of a first and second intake conduits, the first intake conduit connected to the air conduit upstream of the at least one heat exchanger and the second intake conduit connected to the air conduit downstream of the at least one heat exchanger; and
 - preventing the air from flowing from the air conduit to the inlet of the compressor through the other one of the first and second conduits.
19. The method as defined in claim 18, wherein the internal combustion engine core is part of a compound engine assembly for an aircraft, the method further comprising selecting the first intake conduit to direct the part of the air from the air conduit to the inlet of the compressor during flight, and selecting the second intake conduit to direct the part of the air from the air conduit to the inlet of the compressor during ground idle.

20. The method as defined in claim 18, wherein the internal combustion engine core is part of a compound engine assembly for an aircraft, the method further comprising selecting the first intake conduit to direct the part of the air from the air conduit to the inlet of the compressor during flight in non-icing conditions, and selecting the second intake conduit to direct the part of the air from the air conduit to the inlet of the compressor during icing conditions.




Fig-1




Fig-2





Fig-3






Fig-5





Fig. 6A

**FIG. 6B**




FIG-7

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CA2016/050162

A. CLASSIFICATION OF SUBJECT MATTER

IPC: **F02M 35/108** (2006.01), **B64D 33/02** (2006.01), **F01C 1/22** (2006.01), **F02B 33/40** (2006.01),
F02B 37/00 (2006.01), **F02C 6/12** (2006.01) (more IPCs on the last page)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: **F02M 35/108** , **B64D 33/02** , **F01C 1/22** , **F02B 33/40** ,
F02B 37/00 , **F02C 6/12** , **F02C 7/04** , **F02M 31/20**

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic database(s) consulted during the international search (name of database(s) and, where practicable, search terms used)

FamPat using Questel Orbit. Search terms: heated, air, intake, de-icing, valve.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US2004/0123849A1 (Bryant) 01 July 2004 (01-07-2004) *Fig 2D*	1-20
A	US5375580 (Stolz et al.) 27 December 1994 (27-12-1994) *columns 5,6,7*	1-20
A	US2003/0015183A1 (Sealy et al.) 23 January 2003 (23-01-2003) *Fig 1*	1-20
A	US2010/0071639A1 (Wegner et al.) 25 March 2010 (25-03-2010) *Fig 9*	1-20
A	US2009/0314005A1 (Messmer) 24 December 2009 (24-12-2009) *description*	1-20

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* "A" "E" "L" "O" "P"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance earlier application or patent but published on or after the international filing date document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) document referring to an oral disclosure, use, exhibition or other means document published prior to the international filing date but later than the priority date claimed	"T" "X" "Y" "&"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art document member of the same patent family
--------------------------------------	--	--------------------------	--

Date of the actual completion of the international search
12 April 2016 (12-04-2016)

Date of mailing of the international search report
21 April 2016 (21-04-2016)

Name and mailing address of the ISA/CA
Canadian Intellectual Property Office
Place du Portage I, C114 - 1st Floor, Box PCT
50 Victoria Street
Gatineau, Quebec K1A 0C9
Facsimile No.: 819-953-2476

Authorized officer

Arthur Gary Grant (819) 953-9698

F02C 7/04 (2006.01) , *F02M 31/20* (2006.01)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/CA2016/050162

Patent Document Cited in Search Report	Publication Date	Patent Family Member(s)	Publication Date
US2004123849A1	01 July 2004 (01-07-2004)	US2004123849A1	01 July 2004 (01-07-2004)
		US6951211B2	04 October 2005 (04-10-2005)
		AT253173T	15 November 2003 (15-11-2003)
		AU743600B2	31 January 2002 (31-01-2002)
		AU3288397A	09 February 1998 (09-02-1998)
		CA2276245A1	22 January 1998 (22-01-1998)
		CN1244233A	09 February 2000 (09-02-2000)
		DE69725873D1	04 December 2003 (04-12-2003)
		DE69725873T2	09 September 2004 (09-09-2004)
		EP0938625A1	01 September 1999 (01-09-1999)
		EP0938625A4	14 November 2001 (14-11-2001)
		EP0938625B1	29 October 2003 (29-10-2003)
		EP1365126A2	26 November 2003 (26-11-2003)
		EP1365126A3	02 January 2004 (02-01-2004)
		EP1522690A2	13 April 2005 (13-04-2005)
		EP1522690A3	08 June 2005 (08-06-2005)
		EP1632658A1	08 March 2006 (08-03-2006)
		ES2210541T3	01 July 2004 (01-07-2004)
		GEP20032872B	10 September 2002 (10-09-2002)
		RU2189468C2	20 September 2002 (20-09-2002)
		US6279550B1	28 August 2001 (28-08-2001)
		US2005115547A1	02 June 2005 (02-06-2005)
		US7222614B2	29 May 2007 (29-05-2007)
		US7281527B1	16 October 2007 (16-10-2007)
		US2006021606A1	02 February 2006 (02-02-2006)
		US2008092860A2	24 April 2008 (24-04-2008)
		US8215292B2	10 July 2012 (10-07-2012)
		US2004065308A1	08 April 2004 (08-04-2004)
		US2005098162A1	12 May 2005 (12-05-2005)
		US2008201058A1	21 August 2008 (21-08-2008)
		US2008201059A1	21 August 2008 (21-08-2008)
		US2008208434A1	28 August 2008 (28-08-2008)
		US2008208435A1	28 August 2008 (28-08-2008)
		WO9802653A1	22 January 1998 (22-01-1998)
		WO2005116416A1	08 December 2005 (08-12-2005)
US5375580A	27 December 1994 (27-12-1994)	US5375580A	27 December 1994 (27-12-1994)
		AU657189B2	02 March 1995 (02-03-1995)
		AU3186593A	29 July 1993 (29-07-1993)
		BR9300242A	27 July 1993 (27-07-1993)
		CA2087459A1	24 July 1993 (24-07-1993)
		CA2087459C	21 March 2000 (21-03-2000)
		MX9300322A	01 July 1993 (01-07-1993)
		NO930185D0	20 January 1993 (20-01-1993)
		NO930185A	26 July 1993 (26-07-1993)
		NO300285B1	05 May 1997 (05-05-1997)
US2003015183A1	23 January 2003 (23-01-2003)	US2003015183A1	23 January 2003 (23-01-2003)
		US6561169B2	13 May 2003 (13-05-2003)
US2010071639A1	25 March 2010 (25-03-2010)	US2010071639A1	25 March 2010 (25-03-2010)
		AT521799T	15 September 2011 (15-09-2011)
		BRPI0807304A2	20 May 2014 (20-05-2014)
		CN101641502A	03 February 2010 (03-02-2010)
		CN101641502B	14 November 2012 (14-11-2012)
		DE102007010123A1	04 September 2008 (04-09-2008)
		EP2129889A1	09 December 2009 (09-12-2009)
		EP2129889B1	24 August 2011 (24-08-2011)
		US2010089342A1	15 April 2010 (15-04-2010)
		WO2008104373A1	04 September 2008 (04-09-2008)
		WO2008104402A1	04 September 2008 (04-09-2008)

(continued on next page)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CA2016/050162

(continuation of previous page)

Patent Document Cited in Search Report	Publication Date	Patent Family Member(s)	Publication Date
US2009314005A1	24 December 2009 (24-12-2009)		US2009314005A1 24 December 2009 (24-12-2009)
		BRPI0821738A2	16 June 2015 (16-06-2015)
		CA2710279A1	09 July 2009 (09-07-2009)
		EP2235342A2	06 October 2010 (06-10-2010)
		JP2011508138A	10 March 2011 (10-03-2011)
		KR20100096252A	01 September 2010 (01-09-2010)
		WO2009086187A2	09 July 2009 (09-07-2009)
		WO2009086187A3	30 December 2009 (30-12-2009)