



US006850088B2

(12) **United States Patent**
Uh et al.

(10) **Patent No.:** **US 6,850,088 B2**
(45) **Date of Patent:** **Feb. 1, 2005**

(54) **APPARATUS AND METHOD FOR TESTING LIQUID CRYSTAL DISPLAY PANEL**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Ji-Heum Uh**, Seoul (KR); **Sang-Sun Shin**, Kyoungsangbuk-Do (KR)

(73) Assignee: **LG.Philips LCD Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/790,088**

(22) Filed: **Mar. 2, 2004**

(65) **Prior Publication Data**

US 2004/0163449 A1 Aug. 26, 2004

Related U.S. Application Data

(62) Division of application No. 10/260,569, filed on Oct. 1, 2002.

(30) **Foreign Application Priority Data**

Mar. 6, 2002 (KR) 2002-11969

(51) **Int. Cl.⁷** **G01R 31/00**

(52) **U.S. Cl.** **324/770**

(58) **Field of Search** 324/770, 727,
324/158.1, 514; 439/110, 106, 153; 438/113,
33, 464, 458

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,978,580 A 9/1976 Leupp et al.
4,653,864 A 3/1987 Baron et al.

(List continued on next page.)

JP	57038414	3/1982
JP	57088428	6/1982
JP	58027126	2/1983
JP	60164723	8/1985
JP	60217343	10/1985
JP	61007822	1/1986
JP	61055625	3/1986
JP	62089025	4/1987
JP	62090622	4/1987
JP	62205319	9/1987
JP	63109413	5/1988
JP	63110425	5/1988
JP	63128315	5/1988
JP	63311233	12/1988
JP	05127179	5/1993
JP	05265011	10/1993
JP	05281557	10/1993
JP	05281562	10/1993
JP	06051256	2/1994
JP	06148657	5/1994
JP	6160871	6/1994
JP	06265915	9/1994

Primary Examiner—David A. Zarneke


Assistant Examiner—Trung Q. Nguyen

(74) *Attorney, Agent, or Firm*—McKenna Long & Aldridge LLP

(57) **ABSTRACT**

An apparatus and a method testing liquid crystal display panel which are able to test whether or not burr remains on longer sides and on shorter sides of a unit liquid crystal display panel using first to fourth testing bars in a touch method, and able to measure a distance between the longer sides and a distance between the shorter sides of the unit liquid crystal display panel.

16 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

4,775,225	A	10/1988	Tsuboyama et al.
5,247,377	A	9/1993	Omeis et al.
5,263,888	A	11/1993	Ishihara et al.
5,379,139	A	1/1995	Sato et al.
5,406,989	A	4/1995	Abe
5,499,128	A	3/1996	Hasegawa et al.
5,507,323	A	4/1996	Abe
5,511,591	A	4/1996	Abe
5,539,545	A	7/1996	Shimizu et al.
5,548,429	A	8/1996	Tsujita
5,642,214	A	6/1997	Ishii et al.
5,680,189	A	10/1997	Shimizu et al.
5,742,370	A	4/1998	Kim et al.
5,757,451	A	5/1998	Miyazaki et al.
5,852,484	A	12/1998	Inoue et al.
5,854,664	A	12/1998	Inoue et al.
5,861,932	A	1/1999	Inata et al.
5,952,678	A	9/1999	Ashida
5,956,112	A	9/1999	Fujimori et al.
6,001,203	A	12/1999	Yamada et al.
6,011,609	A	1/2000	Kato et al.
6,016,178	A	1/2000	Kataoka et al.
6,016,181	A	1/2000	Shimada
6,055,035	A	4/2000	Von Gutfeld et al.
6,163,357	A	12/2000	Nakamura
6,219,126	B1	4/2001	von Gutfeld
6,226,067	B1	5/2001	Nishiguchi et al.
6,236,445	B1	5/2001	Foschaar et al.
6,304,306	B1	10/2001	Shiomi et al.
6,337,730	B1	1/2002	Ozaki et al.
6,414,733	B1	6/2002	Ishikawa et al.
6,583,643	B2 *	6/2003	Lin 324/770
6,590,624	B1 *	7/2003	Lee 349/54

FOREIGN PATENT DOCUMENTS

JP	07128674	5/1995
JP	07181507	7/1995
JP	08095066	4/1996
JP	08106101	4/1996
JP	08171094	7/1996
JP	08190099	7/1996
JP	08240807	9/1996
JP	09005762	1/1997

JP	09026578	1/1997
JP	09073075	3/1997
JP	09073096	3/1997
JP	09127528	5/1997
JP	09230357	9/1997
JP	09281511	10/1997
JP	09311340	12/1997
JP	10123537	5/1998
JP	10123538	5/1998
JP	10142616	5/1998
JP	10221700	8/1998
JP	10282512	10/1998
JP	11014953	1/1999
JP	11038424	2/1999
JP	11064811	3/1999
JP	11109388	4/1999
JP	11174477	7/1999
JP	11212045	8/1999
JP	11344714	12/1999
JP	2000029035	1/2000
JP	2001117105	4/2001
JP	2001133794	5/2001
JP	2001142074	5/2001
JP	2001147437	5/2001
JP	2001154211	6/2001
JP	2001255542	9/2001
JP	2001264782	9/2001
JP	2001330840	11/2001
JP	2001356354	12/2001
JP	2002014360	1/2002
JP	2002023176	1/2002
JP	2002049045	2/2002
JP	2002082340	3/2002
JP	2002090759	3/2002
JP	2002090760	3/2002
JP	2002107740	4/2002
JP	2002122872	4/2002
JP	2002122873	4/2002
JP	2002080321	6/2002
JP	2002202512	7/2002
JP	2002202514	7/2002
JP	2002214626	7/2002

* cited by examiner

FIG. 1
RELATED ART




FIG. 2
RELATED ART




FIG. 3A
RELATED ART




FIG. 3B
RELATED ART




FIG. 4A
RELATED ART




FIG. 4B
RELATED ART




FIG. 4C
RELATED ART




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8A




FIG. 8B





FIG. 8C



1

APPARATUS AND METHOD FOR TESTING LIQUID CRYSTAL DISPLAY PANEL

This application is a divisional of prior application Ser. No. 10/260,569, filed Oct. 1, 2002.

This application claims the benefit of the Korean Application No. P2002-011969 filed on Mar. 6, 2002, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display (hereinafter "LCD") panel, and more particularly, to an apparatus and a method for testing a size of a unit LCD panel and status of cut surface after cutting LCD panels fabricated on a large mother substrate into individual unit LCD panels.

2. Discussion of the Related Art

In general, an LCD device displays a desired picture by individually supplying a data signal according to picture information to the liquid crystal cell arranged in a matrix form and controlling light transmittance through liquid crystal molecules of the liquid crystal cells.

In the LCD device, TFT (hereinafter "TFT") array substrates are formed on a large mother substrate and color filter substrates are formed on an additional mother substrate. Then, by attaching the two mother substrates, a plurality of LCD panels are simultaneously formed. Because yield can be increased by simultaneously forming a plurality of LCD panels on a glass substrate of a large area, a process of cutting the attached two mother substrates into unit LCD panels is required.

Conventionally, the cutting processing includes forming a predetermined cutting line on the surface of the substrate with a pen having a higher hardness than the glass substrate and propagating a crack along the predetermined cutting line. The cutting process of the unit LCD panel will be described in detail with reference to the accompanied drawings.

FIG. 1 is a schematic plan view showing a unit LCD panel formed with a TFT array substrate and color filter substrate attached to face into each other.

In FIG. 1, the LCD panel 10 includes a picture display unit 13 having a plurality of liquid crystal cells arranged in a matrix form, a gate pad unit 14 connected to a plurality of gate lines of the picture display unit 13, and a data pad unit 15 connected to a plurality of data lines of the picture display unit 13.

The gate pad unit 14 and the data pad unit 15 are formed at the marginal portion of the TFT array substrate 1. The marginal portion does not overlap the color filter substrate 2.

The gate pad unit 14 supplies a scan signal supplied from the gate driver integrated circuit to the gate lines of the picture display unit 13. The data pad unit 15 supplies picture information supplied from the data driver integrated circuit to the data lines of the picture display unit 13.

The data lines receive picture information and the gate lines receive the scan signal. The data lines and gate lines cross orthogonally on the TFT array substrate 1 of the picture display unit 13. At each of the crossed portion, a thin film transistor (TFT) is formed for switching the liquid crystal cells that are defined by the crossing of the data and gate lines. A pixel electrode is formed in each liquid crystal cell to be connected to the TFT for driving the liquid crystal cell. Further, a protective film is formed over the entire surface to protect the pixel electrode and the TFT.

2

A plurality of color filters are formed on the color filter substrate 2. The color filters for a cell region are separated from adjacent cell regions by a black matrix. Common transparent electrodes corresponding to the pixel electrodes are formed on the color filter substrate 2.

A cell gap is formed between the TFT array substrate 1 and the color filter substrate 2 so that the two substrates are spaced apart and face each other. The TFT array substrate 1 and the color filter substrate 2 are attached by a sealant (not shown) formed at the exterior of the picture display unit 13. A liquid crystal layer (not shown) is formed in the space between the TFT array substrate 1 and the color filter substrate 2.

FIG. 2 illustrates a cross-sectional view showing a plurality of unit LCD panels formed in the first mother substrate having the TFT array substrates and the second mother substrate having the color filter substrates.

As shown in FIG. 2, a plurality of unit LCD panels are formed in such a manner that one side of the unit LCD panel TFT array substrates 1 protrudes by as much as a dummy region 31 of the unit LCD panel color filter substrates.

The protrusion of the unit LCD panel is provided because the gate pad unit 14 and the data pad unit 15 are formed at the marginal portion provided by the protrusion where the TFT array substrates 1 and the color filter substrates 2 do not overlap.

Thus, the color filter substrates 2 formed on the second mother substrate 30 are formed to be isolated by as much as dummy regions 31 which correspond to the protrusions of the TFT array substrates 1.

Each unit LCD panel is disposed at the first and second mother substrates 20 and 30 so that the area of the first and the second mother substrates 20 and 30 are used at the maximum. Depending on a model of unit LCD panel being fabricated, the unit LCD panels are generally formed to be isolated by as much as the second dummy regions 32.

After the first mother substrate 20 where the TFT array substrates 1 are formed and the second mother substrate 30 where the color filter substrates 2 are formed are attached each other, the LCD panels are individually cut. The dummy regions 31 formed at the region where the color filter substrates 2 of the second mother substrate 30 are isolated and the second dummy regions 32 isolating the unit LCD panels, are simultaneously removed.

FIG. 3 is an exemplary view showing a testing apparatus for LCD panel according to related art.

As shown in FIG. 3, the testing apparatus comprises a first and a second testing bars 101 and 102 for testing the cutting status of longer sides of the unit LCD panel 100 (that is, a side where the data pad unit is formed and the opposite side of the unit LCD panel). A third and a fourth testing bars 103 and 104 for testing the cutting status of shorter sides of the unit LCD panel 100 (that is, a side where the gate pad unit is formed and the opposite of the unit LCD panel).

The first and second testing bars 101 and 102 test whether or not a burr remains on the longer sides of the unit LCD panel 100 in a touch method. The third and fourth testing bars 103 and 104 test whether or not a burr is remains on the shorter sides of the unit LCD panel 100 by the same method as the first and second testing bars 101 and 102.

On the other hand, the size of the unit LCD panel 100 can be varied according to the models of unit LCD panel being fabricated. Therefore, the first and second testing bars 101 and 102 and the third and fourth testing bars 103 and 104 are formed to have same lengths as the longer sides and the

3

shorter sides, respectively of the largest unit LCD panel **100** that may be fabricated, and thereby, the test can be performed for all models of unit LCD panel **100**.

Also, in the unit LCD panel **100**, a color filter substrate **120** is stacked on a TFT array substrate **110**, and two sides of the TFT array substrate **110** are formed to protrude beyond the color filter substrate **120**. This is because that the gate pad unit and data pad unit are formed on the TFT array substrate **110** in a marginal portion that does not overlap the color filter substrate **120**, as described with reference to FIG. 1.

Therefore, one of the longer sides and one of the shorter sides of the unit LCD panel **100** have a step shape. The first testing bar **101** corresponds to the one of the longer sides of the unit LCD panel **100** on which the data pad unit is formed. The third testing bar **103** corresponds to the one of the shorter sides of the unit LCD panel **100** on which the gate pad unit is formed. Thus, to test the longer sides of the unit LCD panel **100**, the first testing bar **101** is formed to be engaged with the one of longer sides of the unit LCD panel **100** having the step shape. In addition, to test the shorter sides of the unit LCD panel **100**, the third testing bar **103** is formed to be engaged with the one of shorter sides of the unit LCD panel **100** having the step shape.

Hereinafter, a testing method of unit LCD panel using the above apparatus will now be described with reference to the accompanying sequential exemplary views, FIGS. 4A to 4C.

As shown in FIG. 4A, the unit LCD panel **100** is loaded on a first table (not shown) including the first to fourth testing bars **101** to **104**. At that time, the color filter substrate **120** is stacked on the TFT array substrate **110**, and two sides of the TFT array substrate **110** are formed to protrude beyond the color filter substrate **120** by the gate pad unit and the data pad unit as described above. The first testing bar **101** is formed to be engaged with the one of the longer sides of the unit LCD panel **100** having the step shape caused by the data pad unit. The third testing bar **103** is formed to be engaged with the one of the shorter sides of the unit LCD panel **100** having the step shape caused by the gate pad unit.

Next, as shown in FIG. 4B, the first and second testing bars **101** and **102** test whether or not the burr remains on the longer sides of the unit LCD panel **100** in the touch method.

As shown in FIG. 4C, the third and fourth testing bars **103** and **104** test whether or not the burr remains on the shorter sides of the unit LCD panel **100** in the touch method.

As described above, the unit LCD panel **100** is determined whether it is fine or inferior by testing the longer and shorter sides of the unit LCD panel **100** using the first to fourth testing bars **101** to **104** in the touch method. After that, the unit LCD panels **100** that are fine are selected at a predetermined interval and are removed from the production line to test whether or not the cut size of the unit LCD panel **100** is appropriate using an extra measuring device.

According to the apparatus and the method for testing LCD panel of the related art, the burr remaining on the unit LCD panel is tested, and the unit LCD panel of good quality is extracted from the production line with a predetermined period to test whether or not the size of the cut unit LCD panel is appropriate using an extra measuring device. Therefore, an operator should move the unit LCD panel from the production line to the measuring device for testing the size of cut LCD panel and perform the size test on the measuring device.

The above processes are inconvenient, and the productivity is lowered since the time spent on testing the size of the cut unit LCD panel is increased.

4

In addition, an additional measuring device of high price is needed, and accordingly, costs for equipment and maintenance of the production line are increased, and thereby, the cost price of the product is also increased.

Also, the size test is performed by sampling the unit LCD panels a predetermined interval, and therefore, reliability of the test is lowered. In addition, if the unit LCD panel is determined to be inferior, the operation is stopped, and all unit LCD panels from the panel previously sampled to the panel which will be sampled next should be tested and determined whether they are inferior or fine. Therefore, the unit LCD panels which have undergone post-processes may be discarded, and accordingly, material and time can be wasted.

SUMMARY OF THE INVENTION

Accordingly, an advantage of the present invention is to provide an apparatus and a method for simplifying tests of size of LCD panel and of status of cut surface, after cutting the LCD panels formed on a large mother substrate into individual unit LCD panels.

To achieve the advantage of the present invention, as embodied and broadly described herein, there is provided an apparatus for testing an LCD panel including first and second testing bars corresponding to longer sides of a unit liquid crystal display panel testing for defect along a grinding edge of the unit liquid crystal display panel and measuring a distance between the longer sides of the unit liquid crystal display panel; and third and fourth testing bars corresponding to shorter sides of a unit liquid crystal display panel testing for defect along a grinding edge of the unit liquid crystal display panel and measuring a distance between the shorter sides of the unit liquid crystal display panel.

In addition, to achieve the object of the present invention, there is provided a method for testing an LCD panel including loading a unit liquid crystal display panel on a first table including first, second, third and fourth testing bars; and measuring a distance between the longer sides of the unit liquid crystal display panel while operating the first and second testing bars and a distance between the shorter sides of the unit liquid crystal display panel while operating the third and fourth testing bars.

The foregoing and other features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention.

In the drawings:

FIG. 1 is a plan view illustrating a unit LCD panel formed in the TFT array substrate and a color filter substrate for an LCD device, which are attached to face into each other;

FIG. 2 is a cross-sectional view showing a plurality of LCD panels formed in the first mother substrate including the TFT array substrates and the second mother substrate with the color filter substrate of FIG. 1;

FIG. 3 is an exemplary view showing an apparatus for testing LCD panel according to the related art;

FIGS. 4A to 4C are exemplary views showing a method for testing LCD panel according to the related art in order using the apparatus of FIG. 3;

5

FIG. 5 is an exemplary view showing an apparatus for testing LCD panel according to an embodiment of the present invention;

FIGS. 6A to 6C are exemplary views showing a method for testing LCD panel according to the embodiment of the present invention in order using the apparatus of FIG. 5;

FIG. 7 is an exemplary view showing an apparatus for testing LCD panel according to another embodiment of the present invention; and

FIGS. 8A and 8B are exemplary views showing a method for testing LCD panel according to another embodiment of the present invention in order using the apparatus of FIG. 7.

FIGS. 8A and 8C is an exemplary view showing a method for testing LCD panel according to another embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to the illustrated embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

FIG. 5 is an exemplary view showing an apparatus for testing an LCD panel according to an embodiment of the present invention. As shown therein, the apparatus for testing an LCD panel comprises a first and a second testing bars **201** and **202** for testing cutting status of longer sides of a unit LCD panel **200** (that is, a side where a data pad unit is formed and an opposite side of the unit LCD panel), and for measuring a distance (D1) between the longer sides of the unit LCD-panel **200**, and a third and a fourth testing bars **203** and **204** for testing cutting status of shorter sides of the unit LCD panel **200** (that is, a side where a gate pad unit is formed and an opposite side of the LCD panel), and for measuring a distance (D2) between the shorter sides of the unit LCD panel **200**.

The first and second testing bars **201** and **202** test whether or not burr remains on the longer sides of the unit LCD panel **200** in a touch method and measure the distance D1 between the longer sides of the unit LCD panel **200**. In addition, the third and fourth testing bars **203** and **204** test whether or not the burr remains on the shorter sides of the unit LCD panel **200** in same method as that of the first and second testing bars **201** and **202** and measure the distance (D2) between the shorter sides of the unit LCD panel **200**.

On the other hand, the size of the unit LCD panel vary according to model, and therefore, it is desirable that the first and second testing bars **201** and **202** and the third and fourth testing bars **203** and **204** are formed to have lengths corresponding to the longer sides and shorter sides of the largest unit LCD panel **200** to be tested so that the testing bars be applied to all models of the unit LCD panel **200**. In addition, it is desirable that the first to fourth testing bars **201** to **204** measure the distance D1 between the longer sides of the unit LCD panel **200** and the distance D2 between the shorter sides of the unit LCD panel **200** using a gauge built therein.

Also, in the unit LCD panel **200**, a color filter substrate **220** is stacked on a TFT array substrate **210**, and two sides of the TFT array substrate **210** are formed to protrude beyond the color filter substrate **220**. This is so that the gate pad unit and data pad unit can be formed at a marginal portion of the TFT substrate **210** that does not overlap the color filter substrate **220**, as described with reference to FIG. 1.

Because of the protruding edge of the TFT array substrate **210**, one of the longer sides and one of the shorter sides of

6

the unit LCD panel **200** have a step shape. The first testing bar **201** corresponds to the one of the longer sides of the unit LCD panel **200** on which the data pad unit is formed. The third testing bar **203** corresponds to the one of the shorter sides of the unit LCD panel **200** on which the gate pad unit is formed. Thus, to test the longer sides of the unit LCD panel **200**, the first testing bar **201** is formed to be engaged with the one of longer sides of the unit LCD panel **200** having the step shape. In addition, to test the shorter sides of the unit LCD panel **200**, the third testing bar **203** is formed to be engaged with the one of shorter sides of the unit LCD panel **200** having the step shape.

Hereinafter, a method for testing unit LCD panel using the above apparatus will be described in detail with reference to FIGS. 6A to 6C.

As shown in FIG. 6A, the unit LCD panel **200** is loaded on a first table (not shown) on which the first to fourth testing bars **201** to **204** are disposed. At that time, the color filter substrate **220** is stacked on the TFT array substrate **210**, and two side of the TFT array substrate **210** are formed to protrude beyond the color filter substrate **220** by the data pad unit and the gate pad unit as described above. The first testing bar **201** is formed to be engaged with the one of the longer sides of the unit LCD panel **200** having the step shape caused by the data pad unit. The third testing bar **203** is formed to be engaged with the one of the shorter sides of the unit LCD panel **200** having the step shape caused by the gate pad unit.

Next, as shown in FIG. 6B, the first and second testing bars **201** and **202** test whether or not the burr remains on the longer sides of the unit LCD panel **200** in the touch method and measure the distance D1 between the longer sides of the unit LCD panel **200**.

In addition, as shown in FIG. 6C, the third and fourth testing bars **203** and **204** test whether or not burr remains on the shorter sides of the unit LCD panel **200** in the touch method and measure the distance D2 between the shorter sides of the unit LCD panel **200**.

As described above, the apparatus according to the embodiment of the present invention tests whether or not burr remains on the longer and shorter sides of the unit LCD panel **200** in the touch method using the first to fourth testing bars **201** to **204** and measures the distance D1 between the longer sides of the unit LCD panel **200** and the distance D2 between the shorter sides of the unit LCD panel **200**. Thus, an additional measuring device as in the related art is not needed and sizes of all unit LCD panels **200** are tested.

On the other hand, FIG. 7 is an exemplary view showing an apparatus for testing LCD panel according to another embodiment of the present invention. As shown therein, the apparatus for testing LCD panel includes first and second testing bars **301** and **302** testing cutting status of longer sides of a unit LCD panel **300** (that is, a side where a data pad unit is formed and the opposite side) and measuring a distance (D1) between the longer sides of the unit LCD panel **300**; and third and fourth testing bars **303** and **304** testing cutting status of shorter sides of the unit LCD panel **300** (that is, a side where a gate pad unit is formed and the opposite side), and measuring a distance (D2) between the shorter sides of the unit LCD panel **300**. At that time, the fourth testing bar **304** is formed to corresponded to shorter sides of a model having the smallest size of unit LCD panel **300** unlike in the first embodiment of the present invention.

The first to fourth testing bars **301** to **304** measure the distance D1 between the longer sides of the unit LCD panel **300** and the distance D2 between the shorter sides of the LCD panel **300** using a built-in gauge.

Hereinafter, a method for testing unit LCD panel using the above apparatus according to another embodiment of the present invention will be described with reference to FIGS. 8A and 8B.

As shown in FIG. 8A, the unit LCD panel 300 is loaded on a first table (not shown) including the first to fourth testing bars 301 to 304. At that time, the color filter substrate 320 is stacked on the TFT array substrate 310, and two side of the TFT array substrate 310 protrude beyond the color filter substrate 320 by the data pad unit and the gate pad unit as described above. The first testing bar 301 is formed to be engaged with the one of the longer sides of the unit LCD panel 300 having the step shape because of the data pad unit. The third testing bar 303 is formed to be engaged with the one of the shorter sides of the unit LCD panel 300 having the step shape because of the gate pad unit.

Next, as shown in FIG. 8B, the first to fourth testing bars 301 to 304 test whether or not burr remains on the longer sides and on the shorter sides of the unit LCD panel 300 in the touch method and measure the distance D1 and the distance D2 of the unit LCD panel 300.

As described above, according to another embodiment of the present invention, the first to fourth testing bars 301 to 304 are operated at the same time to test whether or not burr remains on the longer and shorter sides of the unit LCD panel 300 and to measure the distance D1 and the distance D2 of the unit LCD panel 300. Accordingly, if the first to fourth testing bars 301 to 304 are all fabricated to have the lengths corresponding to the longer and shorter sides of the largest unit LCD panel 300 model as in the first embodiment, the first and second testing bars 301 and 302 will contact the third and fourth testing bars 303 and 304 if all are applied to engage the unit LCD panel at the same time.

Therefore, in the another embodiment of the present invention, the fourth testing bar 304 is fabricated to have the length corresponding to the shorter sides of the smallest unit LCD panel 300 model to prevent the first and second testing bars 301 and 302 from contacting the third and fourth testing bars 303 and 304 when these four testing bars 301 to 304 are operated simultaneously.

As illustrated in FIG. 8C, it is possible that one of the testing bars for testing the longer sides of the LCD panel may be formed to correspond the longer side of a model having the smallest size of LCD panel. Also, as illustrated in FIGS. 8B and 8C, the remaining testing bars may be formed to correspond to the longest possible size of their corresponding LCD panel edges to be tested.

In addition to the distance measures described above, it is possible to measure the dimensions D1 and D2 across the top of the unit LCD panel by using corresponding measurement sensors or gauges on the upper step portion of one testing bar and on the testing bar for testing the opposite edge of the LCD panel. In such instance, the testing bar for testing the opposite edge may not have a step portion. Therefore, the height of the testing bar for testing the opposite edge should have a height that allows it to extend above the plane of the top surface of the unit LCD panel. Such sensor or gauge can be an optical measurement device.

It is also possible that the testing of a length of an edge corresponding to one of the testing bars can be measured by sensors on the single testing bar that comes into contact with the edge whose length is to be measured. Referring to FIG. 7, for example, testing bar 302 may measure the length D1 of the long edge of the unit LCD panel 300 without reference to the location of any other testing bar. Similarly, referring still to FIG. 7, for example, testing bar 303 may measure the

length D2 of the short edge of the unit LCD panel 300 without reference to the location of any other testing bar.

According to the apparatus for testing LCD panel of the another embodiment, the test only can be performed for some portion of the shorter side of the unit LCD panel 300 corresponding to the fourth testing bar 304. However, testing of unit LCD panel 300, and measuring the distances D1 and D2 can be performed faster than the first embodiment of the present invention.

As described above, the apparatus and the method for testing LCD panel according to the present invention test whether or not burr remains on the longer sides and on the shorter sides of the unit LCD panel using the first to fourth testing bars in the touch method and measure the distance between longer sides and the distance between the shorter sides of the unit LCD panel using the gauge built in the first to fourth testing bars.

Therefore, the troublesome and inconvenient operations of related art such as extracting a unit LCD panel from the production line and moving it to an extra measuring device for testing the size of the LCD panel can be prevented. In addition, the time for testing the size of unit LCD panel can be reduced, and thereby, the productivity can be increased. An additional measuring device is not required and therefore, the costs for equipment and maintenance of the production line can be reduced.

Also, the size test can be performed for all unit LCD panels simply, and thereby the reliability of test can be improved as compared to the sampling method for extracting the unit LCD panel with a predetermined period and testing the size as in the related art.

In addition, in the related art, if the unit LCD panel is determined as inferior, the operation is stopped and all unit LCD panels from the panel sampled previously to the panel which will be sample next are tested to determine whether these are inferior or fine. Therefore, the unit LCD panels which have undergone the post-processes may be discarded, and accordingly, the material and time can be wasted. However, according to the present invention, the above problems can be prevented by testing all panels.

On the other hand, according to the apparatus and method for testing LCD panel of another embodiment of the present invention, the fourth testing bar is fabricated to have the length corresponding to the shorter side of the smallest unit LCD panel model, and thereby, the first to fourth testing bars can be operated at the same time to test whether or not burr remains on the longer sides and on the shorter sides of the unit LCD panel and to measure the distance between longer sides and the distance between the shorter sides of the LCD panel.

Therefore, according to another embodiment of the present invention, the testing for LCD panel and measuring the distances can be performed faster than the first embodiment of the present invention, and thereby, the productivity can be improved.

What is claimed is:

1. A method for testing a liquid crystal display panel, comprising:

loading a unit liquid crystal display panel on a first table including first, second, third and fourth testing bars; and

measuring a distance between the longer sides of the unit liquid crystal display panel while operating the first and second testing bars and a distance between the shorter sides of the unit liquid crystal display panel while operating the third and fourth testing bars.

9

2. The method of claim 1, further comprising testing for burr defect on at least one of the longer and shorter sides of the unit liquid crystal display panel.

3. The method of claim 2, wherein the testing includes testing whether or not the burr is remained on the longer sides of the unit liquid crystal display panel using the first and second testing bars.

4. The method of claim 2, wherein the testing includes testing whether or not the burr is remained on the shorter sides of the unit liquid crystal display panel using the third and fourth testing bars.

5. The method of claim 2, wherein testing includes testing whether or not the burr is remained on the longer sides and on the shorter sides of the unit liquid crystal display panel using the first to fourth testing bars at the same time.

6. The method of claim 2, wherein testing at least one of the longer and shorter sides of the unit liquid crystal display panel includes checking a cut edge of the unit liquid crystal display panel.

7. The method of claim 6, wherein checking the cut edge is performed by touching at least one of the first, second, third and fourth testing bars to the cut edge of the unit liquid crystal display panel.

8. The method of claim 1, further comprising:

cutting a plurality of liquid crystal display panels into unit liquid crystal display panels prior to loading a unit liquid crystal display panel.

9. The method of claim 1, wherein the first and third testing bars have a step shape.

10. The method of claim 9, wherein at least one of the longer and shorter sides of the unit liquid crystal display panel engage with the step shape of at least one of the first and third testing bars.

10

11. The method of claim 1, wherein measuring a distance between the longer sides and a distance between the shorter sides is performed using a gauge.

12. The method of claim 1, wherein the unit liquid crystal display panel includes a color filter substrate on a thin film transistor array substrate.

13. A method for testing a liquid crystal display panel, comprising:

loading a unit liquid crystal display panel on a first table including first and second testing bars; and

testing for defect on opposite sides of the unit liquid crystal display panel using the first and second testing bars and at the same time measuring a distance of at least one side of the unit liquid crystal display panel.

14. The method of claim 13, wherein one of the first and second testing bars includes position sensors and wherein the measuring comprises measuring the distance of the at least one side of the unit liquid crystal display panel using the position sensors.

15. The method of claim 13, wherein the first and second testing bars include optical sensors and wherein the measuring comprises measuring a distance of the at least one side of the unit liquid crystal display panel using the optical sensors.

16. The method of claim 15, wherein the optical sensors includes a light source on one of the first and second testing bars and a photo detector on the other of the first and second testing bars wherein the measuring comprises measuring the intensity of light received by the photo detector from the light source.

* * * * *