

(86) Date de dépôt PCT/PCT Filing Date: 2007/03/08
(87) Date publication PCT/PCT Publication Date: 2007/09/13
(85) Entrée phase nationale/National Entry: 2008/09/05
(86) N° demande PCT/PCT Application No.: US 2007/063534
(87) N° publication PCT/PCT Publication No.: 2007/103998
(30) Priorités/Priorities: 2006/03/08 (US60/780,426);
2007/02/15 (US60/890,186)


(51) Cl.Int./Int.Cl. *B65D 47/00* (2006.01)

(71) Demandeur/Applicant:
GILERO, LLC, US

(72) Inventeurs/Inventors:
JARNAGIN, SCOTT P., US;
PETERS, BRYAN, US;
MOSLER, THEODORE J., US;
KOROGI, TODD M., US

(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : COUVERCLE ANTI-CONTAMINATION POUR UN RACCORD POUR PASSAGE DE FLUIDE
(54) Title: ANTI-CONTAMINATION COVER FOR FLUID CONNECTIONS



(57) **Abrégé/Abstract:**

A fluid connector is described, the connector comprising a housing having an access site, and a cover member passively positioned in a covering relationship with the access site 1 he cover member is in a covering relationship with the access site such

(57) **Abrégé(suite)/Abstract(continued):**

that the cover member is substantially reversable from an uncovered relationship under load to the initial covering relationship. A method of preventing contamination and aseptically covering an access site of a fluid connector with a cover member is also described.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 September 2007 (13.09.2007)

PCT

(10) International Publication Number
WO 2007/103998 A3

(51) International Patent Classification:
B65D 47/00 (2006.01)

Alafia Court, Raleigh, NC 27616 (US). **KOROGI, Todd, M.** [US/US]; 1618 Frazier Ridge Lane, Mebane, NC 27302 (US).

(21) International Application Number:

PCT/US2007/063534

(74) Agents: **BAUM, Allen, R.** et al.; Hutchison Law Group PLLc, P.O. Box 13686, Raleigh, NC 27612 (US).

(22) International Filing Date: 8 March 2007 (08.03.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/780,426 8 March 2006 (08.03.2006) US
60/890,186 15 February 2007 (15.02.2007) US

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **GILERO, LLC** [US/US]; P.o. Box 13561, Research Triangle Park, NC 27709-3561 (US).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **JARNAGIN, Scott, P.** [US/US]; 433 Guilford Circle, Raleigh, NC 27608 (US). **PETERS, Bryan** [US/US]; 7309-6hiheng Court, Raleigh, NC 27615 (US). **MOSLER, Theodore, J.** [US/US]; 5433

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: ANTI-CONTAMINATION COVER FOR FLUID CONNECTIONS



(57) Abstract: A fluid connector is described, the connector comprising a housing having an access site, and a cover member passively positioned in a covering relationship with the access site. The cover member is in a covering relationship with the access site such that the cover member is substantially reversible from an uncovered relationship under load to the initial covering relationship. A method of preventing contamination and aseptically covering an access site of a fluid connector with a cover member is also described.

WO 2007/103998 A3

WO 2007/103998 A3



FR, GB, GR, HU, IE, IS, IT, LU, LV, MC, MT, NL, PL,
PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

(88) Date of publication of the international search report:

13 March 2008

ANTI-CONTAMINATION COVER FOR FLUID CONNECTIONS

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application Nos.
5 60/780,426, filed March 8, 2006, and 60/890,186, filed February 15, 2007, the entire disclosures of which are incorporated herein by reference in their entirety.

FIELD

[0002] This invention relates to fluid connector covers adaptable and more
10 particularly to passively activated fluid connector covers. The covers may be impregnated or contain an anti-microbial agent to eliminate or reduce contamination of an access site of the fluid connector.

BACKGROUND

15 [0003] Existing fluid connectors are typically designed without a covering for protecting the access site while it is not in use. Some access sites include screw threads which allow them to more easily be connected to IV tubing during lengthy accesses. However, most external fluid connectors normally remain uncovered and completely exposed with little or no barrier to potential contaminants. Contaminants
20 may include, but are not limited to, germs, bacteria, air, dirt, clothing, skin and perspiration.

[0004] Because of the exposure of the fluid connector and access site to contaminants, the use of an aseptic cleansing procedure is typically required prior to accessing the site. Using currently accepted techniques, the cleansing process alone
25 involves several steps and the use of numerous materials for each port access. In order to assure an aseptic environment, a second person may be needed to assist the first with the cleansing process. The clinician may not disinfect the access site for various reasons, including forgetting to do so, not having the appropriate disinfectant swab readily available, being in a hurry, not understanding the importance or a
30 combination of these issues.

[0005] When access to the fluid connector is complete, it will again come into contact with the patient's skin or clothing and immediately become susceptible to contamination, requiring repetition of the above procedure the next time the access

site is accessed. The cleansing procedure, even if properly followed, is very time consuming. Materials must be gathered prior to access, and an assistant may be required before the procedure can be started. The more frequent the access, the greater the risk of subsequent contamination.

5 [0006] Recent scientific studies suggest that the external access site of a fluid connector may be the place of origin of bacteria infecting the device. These studies recommend that manipulation of the access site be kept at a minimum, and that a more rigorous approach to aseptic technique be undertaken such as the time consuming, expensive and difficult measures as discuss above. While studies have suggested that the hub of catheter devices be properly covered, such studies fail to propose any cover design apart from indicating covers are needed to protect against contamination.

10 [0007] While external injection port covers directed to maintaining sterility of catheter hubs have been disclosed, these external injection port cover designs require that the cover include threaded elements to securably cover the corresponding threaded elements of the fluid connector. Thus, the cover requires manual manipulation for removal and replacement thereof on the fluid connector and may require a unique design for each fluid connector. Minimization of such manipulation and universal design of an aseptic cover for fluid connectors would improve the compliance and sterility of the fluid connector manipulations.

SUMMARY

25 [0008] To address the aforementioned problems, a fluid connector cover for fluid connectors is herein described, which may be adaptable to swabable, luer-activated needle-free valves of various forms e.g. luer locking adapters, y-sites, vial adapters, as well as pre-slit septums accessible by blunt cannula, and septums accessible by needles. The cover may passively cover the access site of fluid connectors of various shapes and types. The cover may provide anti-contamination material to the access site. After access, the cover may passively re-position over the access site to provide a clean and aseptic condition at the access site.

30 [0009] A fluid connector comprising a housing is provided. The housing comprises an access site, a rigid arm with a proximal and distal end, a flexible member joining the rigid arm to the housing between the proximal and the distal end of the rigid arm,

and a cover member. The cover member is integral with the distal end of the rigid arm and positioned to cover the access site. The cover member is displaceable from an initial position covering access site to a second position uncovering the access site upon displacement of the rigid arm.

- 5 **[0010]** A cover adapter is provided comprising a body member securable to a fluid connector having an access site, a rigid arm with a proximal and distal end, a flexible member joining the rigid arm to the body member between the proximal and the distal end of the rigid arm, and a cover member. The cover member is integral with the distal end of the rigid arm and positioned to cover the access site of the connector.
- 10 The cover member is displaceable from an initial position covering the access site to a second position uncovering the access site upon displacement of the proximal end of the rigid arm.

- [0011]** A fluid connector is provided comprising a housing. The housing comprises at least one fluid access site and attachment members, a body member secured to the housing with corresponding attachment members, and a flexible member extending from the body member and at least partially surrounding the housing with at least a portion of the flexible member secured to the housing. A rigid arm having a proximal end and a distal end is joined to the body member between the proximal end and the distal end. A cover member is secured to the distal end of the rigid arm and covers
- 15 the access site.
- 20 the access site.

- [0012]** A housing for a fluid connector cover is provided. The housing comprises an access site, attachment members positioned on the housing, and at least one housing retaining member projecting from the housing. The attachment members and the at least one housing retaining member cooperatively receive a fluid connector cover adapter. The adapter comprises a body member having corresponding attachment members securable to the fluid connector attachment members, a flexible member coupled to the body member and securable by the at least one housing retaining member, and a rigid arm having a proximal end and a distal end. The rigid arm is joined to the body member between the proximal end and the distal end. A
- 25 cover member, secured to the distal end of the rigid arm, is positioned to cover the access site.
- 30 the access site.

[0013] A fluid connector comprising a housing is provided. The housing comprises at least one fluid access site, attachment members, a body member secured to the

housing with corresponding attachment members and a rigid arm having a proximal end and a distal end. An elastomeric member loads the rigid arm between the proximal and the distal end. A cover member integral with the distal end of the rigid arm is positioned to cover the access site.

- 5 [0014] A method of preventing or eliminating contamination of an access site of a fluid connector is provided. The method comprises providing a fluid connector cover comprising a housing, at least one access site, and a rigid member. A cover member is cooperatively connected to the rigid member to provide a covering relationship between the access site and the cover member.

10

BRIEF DESCRIPTION OF THE FIGURES

[0015] FIG. 1 is a perspective view of an embodiment of the fluid connector cover.

[0016] FIG. 2A is a perspective view of an embodiment of the fluid connector
15 cover.

[0017] FIG. 2B is a perspective view of the embodiment of FIG 2A with external device engaged.

[0018] FIG. 3 is a perspective view of an embodiment of the fluid connector cover on a y-body connector.

20 [0019] FIG. 4 is a perspective view of an embodiment of the fluid connector cover.

[0020] FIG. 5 is a perspective view of an embodiment of the fluid connector cover.

[0021] FIG. 6 is a perspective view of an embodiment of the fluid connector cover.

[0022] FIG. 7 is a side cross-section view of the cover portion of the embodiment of FIG. 6.

25 [0023] FIG. 8 is a perspective view of an embodiment of the fluid connector cover.

[0024] FIG. 9 is a perspective view of an embodiment of the fluid connector cover.

[0025] FIG. 10 is a perspective view of an embodiment of a cover adapter.

[0026] FIG. 11 is a perspective view of an embodiment of the fluid connector cover.

30 [0027] FIG. 12 is a perspective view of an embodiment of the fluid connector cover of FIG. 11 in an activated state.

[0028] FIG. 13 is a perspective view of an embodiment of the fluid connector cover on a y-body connector.

- [0029] FIG. 14 is a perspective view of the embodiment of FIG. 13 in an activated state.
- [0030] FIG. 15 is a perspective view of an embodiment of a cover adapter.
- [0031] FIG. 16 is a perspective view of an embodiment of a fluid connector housing.
- [0032] FIG. 17 is a perspective view of an embodiment of the fluid connector cover.
- [0033] FIG. 18 is a perspective view of the embodiment of the fluid connector cover of FIG. 17 in an activated state.
- 10 [0034] FIG. 19 is a perspective view of an embodiment of a cover adapter.
- [0035] FIG. 20 is a perspective view of an embodiment of the fluid connector cover.
- [0036] FIG. 21 is a perspective view of an embodiment of the fluid connector cover.
- 15 [0037] FIG. 22 is a perspective view of the embodiment of FIG. 21 prior to engaging an external device.
- [0038] FIG. 23 is a perspective view of an embodiment of the fluid connector cover.
- [0039] FIG. 24 is a perspective view of an embodiment of a cover adapter.
- 20 [0040] FIG. 25 is a perspective view of the embodiment of the fluid connector cover of FIG. 23 in an activated state.
- [0041] FIGs. 26A and 26B are cross-sectional and perspective views, respectively, of an embodiment of a cover adapter.
- [0042] FIG. 27 is a cross-sectional view of an embodiment of a cover adapter.
- 25 [0043] FIG. 28 is a perspective view of an embodiment of a cover adapter.
- [0044] FIG. 29 is a detail side view of an embodiment of a cover adapter.
- [0045] FIG. 30 is a perspective view of an embodiment of a cover adapter.
- [0046] FIG. 31 is a perspective view of an embodiment of a fluid connector cover.
- [0047] FIG. 32 is a perspective view of an embodiment of a fluid connector cover of FIG. 31 with an engaged external device.
- 30 [0048] FIGs. 33A and 33B are perspective views of embodiments of a fluid connector cover with a vial adapter in an initial and activated state, respectively.

DETAILED DESCRIPTION

[0049] A fluid connector cover for fluid connectors is herein described, which may be adaptable to swabable, luer-activated needle-free valves of various forms e.g. luer locking adapters, y-sites, vial adapters, penetetrable septums accessible by blunt cannulaor by needles. The cover may passively cover the access site of a fluid connector such that a user must intervene to expose the access site. The cover may provide anti-contamination material to the access site. This may be accomplished by several features of the cover, as described herein and summarized in the figure descriptions that follow.

10 [0050] As used herein, the term "access site" refers generally to a fluid port providing entry by a piercing, penetrating, or inserting device. By way of example, an access site includes the female port of a needle-free valve and a penetetrable septum accessible by cannula e.g., blunt cannula, respectively. Penetrable septum may include pre-slit and un-slit septum. The access sit includes the adjacent area in
15 proximity to the access site.

[0051] The cover may at least partially cover the access site of the connector. The cover may provide a covering relationship with the access site. The covering relationship includes direct contact or being in close proximity to the access site. This may prevent many of the infections typically caused by touch contamination, for
20 example, at the injection site of infusion devices.

[0052] The fluid connector cover may be of a passive design, which generally refers to a requirement that a user actively forces the cover off of the access site, thus, the fluid connector cover will be positioned at or over the face of the access site in its natural state. This feature may guard against misuse and provide for the face of the
25 valve remaining protected from possible contamination. For example, using the fluid connector cover herein described, nurses, clinicians or other medical professionals may not need to re-cover the fluid connector. Therefore, the possibility of the cover falling off or being lost and/or discarded and exposing the access site is reduced or eliminated.

30 [0053] The fluid connector cover herein described may be designed such that a minimal number of components are added to an existing fluid connector. These designs and other features of the fluid connector cover herein described may utilize many of the parts already found in fluid connectors such as needle-free valves. This

may limit additional parts and associated costs as well as new or complicated assembly procedures. In addition, changes to current needle-free valve parts may be done without complicating tooling, and many of the herein disclosed designs may be made with an open/close mold action, minimizing production cost.

5 [0054] The fluid connector cover herein described may be integrated with connectors comprising access sites. The fluid connector cover herein described may be integrated into the connector housing, by way of example, through a flexible beam connection, strap connection, or snap means. Other ways of integrating the fluid connector cover to the connector housing may include a cylindrical clip adapted to
10 secure around at least a portion of the housing of the connector, or a strap fitted around the housing. The fluid connector cover herein described may provide for a mating hole and lug configuration such that activation of the cover provides a pivoting action. The fluid connector cover herein described may be adapted to connectors comprising integrated standard threads to provide connection with a
15 female luer, and/or snap on or rest over an access site of a fluid connector. The fluid connector cover herein described may comprise cutouts such as to allow snap-fit-like flexibility for variable sized valves.

[0055] The fluid connector cover herein described may stay external to a fluid connector housing and may touch the surface of the access site. The cover may
20 require removal before accessing the access site and to actuate the fluid pathway.

[0056] The term “fluid” as used herein, refers to gas, liquid or a combination of gas and liquid.

[0057] The fluid connector cover may function “passively”. Functioning “passively” means that unless a practitioner actively forces the cover off of the access
25 site, the fluid connector cover remains in a covering relationship with the access site, at least until and before the first use of the connector. By way of example, the natural state of the fluid connector cover is covering the access site. The passive fluid connector cover may provide against misuse in the field and may ensure the exposed surface of the access site remains covered and/or protected. The passive fluid
30 connector cover may eliminate or reduce the need for nurses, clinicians or other medical professionals to re-cover the valve and therefore reduce or eliminate the possibility of the cover falling off on its own and/or exposing the access site to contamination. The passive functionality includes, for example, a pre-loaded

returning force allowing the cover to return to the access site upon disconnect. The returning force may include a preload condition e.g., a load where the access site will remain covered in the event that the returning force yields under normal operation. By way of example, the returning force may be supplied with a spring, elastomeric material or cantilevered beam. The pre-load force may create a condition where the access site will remain covered should the pre-load elements yield under normal operation.

[0058] The fluid connector cover may operate substantially automatically upon engagement by an external device with the access site without user intervention of the fluid connector cover. For example, the cover member may comprise extending flexible arms which provide for deflection of the cover member when the external device engages the access site. The cover member may be comprised of two or more mating sections which form a cover over the access site when in an initial state. The mating section may be deflected away during engagement. Flexible arms may provide a load to the mating sections in the initial state such that upon disengagement of the external device the segments may return to the initial state covering the access site.

[0059] A fluid connector cover may comprise a housing. The housing and other components attached or adapted for attachment thereto may be of plastic construction or may be fabricated out of one or more materials designed to withstand chemical attack from substances, such as solvents and IV drugs. Materials include for example, thermoplastics, engineering thermoplastics, filled or unfilled, and composites. Thermoplastics include materials such as polybutylene terephthalate PBT, cyclic olefinic copolymers COC's, thermoplastic polyurethanes TPU, rigid polyvinyl chloride PVC, and polycarbonate PC.

[0060] The fluid connector cover may comprise a body member. The body member may be integral with the connector housing. The body member may provide attachment means for securably attaching to the connector housing.

[0061] The fluid connector cover comprises a rigid member. The rigid member may be integral with the connector housing or may be integral with the body member of the connector cover. The rigid member may be cooperatively coupled with a cover member which provides for covering the access site.

[0062] The fluid connector cover may comprise a flexible member. The flexible member may join the rigid member to the body member or may join the rigid member to the connector housing. The flexible member may comprise a thinned wall or narrowed width section of the rigid member. The flexible member may provide a load to the rigid member.

[0063] The use of the phrases “flexible member” and “rigid member” are to be taken in context as elements used together in the operation of the fluid connector cover and not necessarily a representation of a material property of the members. For example, rigidity and flexibility of the members may be provided by varying thickness and cross-sectional area of a single material, or the rigidity and flexibility of the members may be provided by using a thermoplastic material and an elastomeric material.

[0064] The fluid connector cover herein described may include a shroud element. The shroud element at least partially surrounds the cover member such as to cover the sides of the access site. A portion of the shroud element may provide for accepting of the access site upon return of the cover member to its initial state. The portion of the shroud may include a cut out or missing section, for example, positioned opposite the rigid member attachment point to cover member.

[0065] Any surface or combination of surfaces of fluid connector cover herein described may include and/or be impregnated, and/or otherwise covered, with an aseptically effective material. The aseptically effective material may comprise an anti-microbial agent. The cover member may comprise separate and/or replaceable element containing an anti-microbial agent. The separate element may be adapted to absorb new or additional anti-microbial agents. For example, the separate element may include a sponge, foam or absorbable material sized to be received by the cover member. The separate element may be secured temporarily or permanently to the cover member. The separate element may be secured by one or more securing elements integral with the cover member or shroud.

[0066] The fluid connector cover herein described may integrate a cover member with a body member or fluid connector housing by way of a flexible member. The flexible member may be shaped as a beam or arm. The cover member may be positioned at a distal end of the arm, the arm being connected to the flexible beam connected to the body or the housing, for example, in a lever arm-fulcrum flexible

beam relationship. Pressing the proximal portion of the arm activates the device by flexing the beam, which moves the cover away from the access site in an arc-like motion.

[0067] The fluid connector cover herein described may comprise a cover adapter
5 having attachment means for securely fastening with the fluid connector housing. For example, the cover body may comprise a ball/pin and socket, interference-type snap-on structure, a clip or combinations thereof. The fluid connector cover herein described may comprise a clip member formed of the body member for surrounding at least a portion of the connector housing. The clip member may provide for
10 securing the cover adapter onto the connector housing and may further utilize joining methods, such as adhesives or ultrasonic welding, to prevent relative motion between the connector housing and the cover adapter. The cover adapter may further comprise a flexible beam and arm as described above, such that pressing the lower portion of the arm moves the cover away from the access site of the connector housing in an arc-
15 like motion.

[0068] The fluid connector cover herein described may comprise a threaded cover member with an integrated strap, the strap having at its opposite end the cover member. The strap may be attached to the connector housing such that the strap is free to rotate around the connector housing body. The rotation of the strap about the
20 connector housing may provide for facile threaded engagement or disengagement of the cover member. An alternate threaded cover member to that previously described. Thus, the strap may be integrated with the connector housing while the cover member, located at the opposite end of the strap, is free to rotate relative to the strap.

[0069] The fluid connector cover herein described may be integrated with a fluid
25 connector housing such that the cover member may be vertically translatable and arcuately rotatable about the connector housing. In this configuration, the cover may be pushed down over the access site and/or any threaded elements. Thus, the cover member may comprise integral projecting flexible arms, the arms comprising tracks which securably attach to the housing to provide vertical and arcuate motion to the
30 cover member relative to the connector housing. The cover member may be of a cup-like shape. The cover member may be adapted to snap-fit on the access site, for example to keep the underside covering surface of the cover member flush against the

face of the access site. The cover member may also utilize the thread forms on the access site as the mating snap elements.

5 [0070] The fluid connector cover herein described may comprise one or more flexible arms proximally integral with a fluid connector housing, or the flexible arms may be adapted to securably attach thereto. The flexible arm may be cooperatively coupled with the cover member at the distal end of the flexible arm such that applied force upon the flexible arm toward the connector housing translates the cover member from the access site to provide access thereto.

10 [0071] The fluid connector cover may further comprise a flexible member that surrounds the housing and may be cooperatively coupled to the fluid connector cover. The flexible member may provide a restoring force to the fluid connector cover such that the fluid connector cover returns to its initial state covering the access site. The flexible member may be combined with the previously described embodiments. Thus, for the fluid connector cover comprising rigid arm and beam elements, the flexible member may be used to provide a restoring force for or load to the rigid arm.

15 [0072] For example, applied force, such as digital pressure from a user, to the lower portion of the rigid arm provides rotation about a clip-like means and, in turn, the beam flexes and creates the restoring force returning the cover over the access site. The connector housing may be a connection point for the clip-like means, and may also restrict the movement of the beam, causing the part of the beam to flex and/or creating or complementing the restoring force to re-cover the access site. The flexible arms may snap-on to corresponding lugs integral with the fluid connector housing. The lugs may be designed such that the flexible arms deflect when the clip is activated. The flexible arm may be, for example, of a U-, V-, or W-shape.

20 [0073] The fluid connector cover may comprise attachment means. Attachment means may include a rotatable clip-like means to provide for rotation of the fluid connector cover body around the outside surface of the connector housing. The cover body may include a flexible segment joining a rigid arm to the cover body, the rigid arm distally terminating in a cover member. The connector housing may comprise a connection point for the clip-like means and a ramp element cooperatively engage the rotatable clip-like means to provide deflection of the flexible segment. The flexible segment may provide a load when the clip-like means are rotated and cooperatively engaged with the ramp element. Deflection of the flexible segment moves the cover

25 30

member from the access site. The load may re-position the cover member after the clip-like means are disengaged with the ramp element.

[0074] The fluid connector cover may comprise an elastomeric material. The elastomeric material may secure the cover member over the access site and/or provide a returning force. The elastomeric material may be combined with the previously disclosed embodiments. The elastomeric material may be integrated with the clip-like means or other attachment members. The elastomeric material may be integrated, for example, over-molding or adhesive bonding. Attachment means connecting the fluid connector cover body to the connector housing access site may be a pivoting connection. The lower portion of the attachment means may be covered with the elastomeric material to improve tactile feel, finger control, and/or ergonomic stability. The attachment means may be made entirely of an elastomeric material such that the rigid member and flexible member functioning may be controlled by material thicknesses and cross-sections. The elastomeric material may provide for improved sealing between the cover member and the access site by reducing or eliminating any gaps between the access site and cover member. The elastomeric material may provide for conformal sealing between the cover member and a non-planar access site, for example. Various elastomeric materials may be used, such as, but not limited to, reaction-injection molded RIM elastomers, silicones, polyurethanes, thermoplastic elastomers TPE e.g., SANTOPRENE™, and synthetic polyisoprenes.

[0075] Where applicable, connection geometry for attachment members that do not integrate with the connector housing may be optimized for manufacturability of the connector. For example, an injection-molded connector housing may comprise attachment members positioned such that the mold tool only requires simple modification rather than retooling. As a means of cost reduction, embodiments of this concept may be integrated into the intended access site. The fluid connector cover may comprise a cover member connected to a distal end of a rigid member, the rigid member joined to the connector by a flexible member arm. Applied force to the rigid member provides flex which moves the cover away from the access site in an arc-like motion.

[0076] The fluid connector cover may be integrated with a connector housing for example, using a flexible beam connection, strap connection, or snap means. Other ways of integrating are through a cylindrical clip that fits around the body of the

housing or a strap fitted around the housing. Standard threads may be integrated into the fluid connector cover to provide a securable connection with a female luer, or may snap-on or rest over the access site. For example, cutouts in the fluid connector cover body may allow sufficient flexibility for snap-fitting onto any size fluid connector

5 housing.

[0077] The cover member may be integrated with the connector housing or may be a separate component of the fluid connector cover. The cover member may be cooperatively joined or integral with a rigid or flexible member, for example, having the shape of an arm connected to the connector housing.

10 [0078] The cover may be adaptable to commercially available connectors including, but not limited to, Cardinal Health SmartSite® and SmartSite® Plus, ICU Medical Clave®, CLC2000®, and TEGO™, BD Posiflow™ and Q-Syte™, Baxter FLOLINK, CLEARLINK, and INTERLINK, B|Braun ULTRASITE®, Medegen MaxPlus™, Halkey-Roberts Swabable Luer Valve, RyMed Technologies InVision-
15 Plus®, Vygon Bionector®, and Borla bSite™. Additionally, the cover may be adaptable to female connectors of stopcocks and IV manifolds.

[0079] Methods of preventing or eliminating contamination of an access site of a fluid connector are provided. As used herein, the term “prevent” and its grammatical equivalents refer to any reduction of the level and/or virulence contamination of the
20 access site. As used herein, the term “contamination” and its grammatical equivalents refer to material not intended to be present on or in the access site. Preventing or eliminating contamination of an access site of a fluid connector may include, for example, providing a passive cover member positioned in a covering relationship with the access site. The cover member may prevent or eliminate contact of the access site
25 with the user, material and/or surfaces that may contain virulent material. The cover member may passively cover the access site until user intervention provides access to the access site, for example, using digital pressure applied to the fluid connector cover.

[0080] The fluid connector herein described may contain an aseptically effective
30 agent to provide infection controlling properties to the connector. Medical articles are frequently fabricated from polymeric materials such as polypropylene, silicone rubber, ABS, or polyurethane by molding and extruding techniques. Imparting aseptically effective properties to such medical devices made from polymeric

materials includes, for example, incorporating an anti-microbial agent into the material during the process of forming the device.

[0081] As used herein, the term "aseptically effective agent" refers to chemicals or compositions of matter that either kill or prevent growth of virulent organisms. A preferred aseptically effective agent is an anti-microbial agent. Anti-microbial agents include antibacterial agents which kill bacteria, antiviral agents which kill viruses, antifungal agents which kill fungi, and anti-parasitic drugs which kill parasites. Aseptically effective agents include biocides and antibiotics.

[0082] As used herein, the phrase "microorganisms," refers to, for example, Gram positive and Gram negative bacteria, including resistant strains thereof, for example methicillin-resistant *Staphylococcus aureus* MRSA, vancomycin-resistant *Enterococci* VRE and penicillin-resistant *Streptococcus pneumoniae* PRSP strains. Preferably, it is defined to include all bacteria Gram+, Gram- and acid fast strains and yeasts such as *Candida albicans*. Most preferably, it is defined to include all bacteria Gram+, Gram-, and acid fast, yeasts, and both envelope and naked viruses such as human influenza, rhinovirus, poliovirus, adenovirus, hepatitis, HIV, herpes simplex, severe acute respiratory syndrome SARS, H5N1 viruses, and avian flu.

[0083] The term "biocides" refers generally to a chemical agent which inactivates living microorganisms. Biocides include, for example, agents of broad spectrum activity, agents that inhibit growth e.g., bacteriostatic, fungistatic, or sporistatic and agents that kill the target organism e.g., bactericidal, fungicidal, sporicidal, or virucidal.

[0084] As used herein, the term "containing," when referenced in regard to an aseptically effective agent, refers to any method of incorporating the agent to a fluid connector cover. This may include, for example, melt addition of the agent to a polymer melt during extrusion or manufacturing; topical application methods; absorbable impregnated pads; and other non-standard methods such as plasma treatment, electrostatic attachment, vapor deposition, radiation surface graft copolymerizations using for example UV, gamma rays and electron-beam radiation sources, or the use of chemical initiation to produce graft copolymerized surfaces having anti-microbial activity, etc.

[0085] The aseptically effective agent containing fluid connector cover preferably rapidly inhibits and controls the growth of microorganisms. For example, an anti-

microbial agent may provide a reduction in the concentration of a broad spectrum of microorganisms by a magnitude of at least 1 log₁₀ as measured by shaker flask method, liquid droplet challenge test, and/or aerosol challenge test within about 30 minutes. The anti-microbial agent containing fluid connector cover may lead to a
5 reduction in microbial concentration by a factor of 3 log₁₀ i.e., reduction by 10³ colony forming units per gram of material cfu/g within about 30 minutes. The anti-microbial agent containing fluid connector cover may lead to a reduction in microbial concentration by a factor of 4 log₁₀ or more within about 30 minutes.

[0086] The anti-microbial agent containing fluid connector cover may provide at
10 least a 1 log₁₀ reduction in the transfer of a broad spectrum of viable microorganisms when contacting another surface as compared to an untreated control item as measured by the contact transfer protocol, for example, as outlined in U.S. Patent Application Publication No. 2004/0151919, incorporated herein by reference.

[0087] The anti-microbial agent containing fluid connector cover may be non-
15 leaching. "Non-leaching" anti-microbial surface is one that passes ASTM E2149-01 testing protocol entitled "Standard Test Method for Determining the Anti-microbial Activity of Immobilized Anti-microbial Agents Under Dynamic Contact Conditions." The lack of a zone of inhibition with the treatment agents chosen may demonstrate the active species does not leach from the treated substrate.

20 [0088] Aseptically effective agents may be compounded in thermoplastic resins or elastomers to produce a concentrate which is then dry blended with the virgin resin and co-molded or overmolded. For example, an anti-microbial agent may be generally distributed throughout the bulk of the cover such that enough of the anti-microbial agent is present on or near the access site surface to provide anti-microbial
25 activity. Concentration of the anti-microbial present on or near the surface of the access site may depend on several factors including anti-microbial concentration in the melt relative to the main body of resin or type of resin, processing conditions and thermal history, crystallinity of the resin, and relative thermodynamic compatibility of the resin and the anti-microbial. The anti-microbial may be compatible with
30 thermoplastic resin in the melt for processability, and yet may be less compatible with the resin at ambient conditions so that the anti-microbial agent may migrate to a certain extent to the surface of the cover. Processing aids may be used to assist

migration of the anti-microbial agent to the surface of the cover in contact with the access site.

[0089] Anti-microbial agents that may be used in the fluid connector cover as herein described to provide anti-microbial action, include, but are not limited to, 1-alkyl-1,5-diazapentane, alexidine, alkyl-amino-alkyl glycine, alkylsulfosuccinate, anatase TiO₂, bamboo extract, benzalkonium chloride, bromo-compound, cetrimide, cetylpyridium chloride, chitosan, chlorhexidine biguanide, chlorhexidine diacetate, chlorhexidine digluconate, citric acid, cyanobutane, dialkyl-dimethyl-phosphonium salt, dithiocarbamate, hexachlorophene, hydrogen peroxide, hydrotropes strong emulsifiers and chaotropic agents alkyl polyglycosides, isothiazolin, neem oil, poly-hexamethylene biguanide, polyphenols from green or black tea extract, polyquaternary amine; metal-containing species and oxides thereof, quaternary ammonium compound, quaternary ammonium compounds benzalkonium chloride, quaternary ammonium siloxane, quaternized cellulose and other quaternized polymers, silver salts such as silver sulfadiazine either in particle form or incorporated into support matrix or polymer, stabilized oxidants such as chlorine dioxide, stabilized peroxide urea peroxide, mannitol peroxide, sulfites sodium metabisulfite, thiazole, thiocyanate, thione, tourmaline, light-activated porphyrins, triclocarban, triclosan, and salts thereof. Depending on the particular material used and the method of incorporation of the anti-microbial agent into the product, many of the above agents may be used alone or synergistically to achieve product properties of interest.

[0090] Referring now to the drawings, various illustrative embodiments will be described. Referring now to FIG. 1, fluid connector cover 130 may be integrated into connector housing 50 comprising an access site 208. When lower portion 103 of the rigid arm 99 is pushed towards the housing, the upper portion of the arm comprising cover member 101 pulls away from the access site of the housing in an arc-like motion, allowing for insertion of a mating connector. Cantilevered flexible member 102 bends to provide a load or force to substantially return the upper portion of the arm and cover member 101 back over the access site, for example, upon disconnection of the mating connection. Finger grips 104 may be added for finger stability and ergonomic control.

[0091] Referring now to FIGs. 2A and 3, fluid connector cover 140 comprises body member 12 non-integrated with connector housing 50b. The body attachment

members 106 provide for clip-on and/or adhesion onto different shaped connector housing bodies. Cut-out 128 in the body member may provide attachment on connectors with external geometry protruding from the intended access site body, such as Y-shaped valve 180, as shown in FIG. 3. Shroud 105 may be provided for additional coverage and stability of the cover member. The shroud may extend past the access site.

[0092] Referring now to FIG. 2B, a mating connector 123 attached to fluid connector housing 50B with fluid connector cover of FIG. 2A. The flexible member 102B may bend to provide a load as digital force is applied to the lower portion 103B of rigid member 99B. Upon disconnection of the mating connection body, the load in the rigid member may return cover member 101B to the access site.

[0093] Referring now to FIGs. 4-5, fluid connector cover 150 comprises cover member 108 with threaded element 68, the cover member integrated with a strap 107 having annular clearance around connector housing 50C. Cover member 108 may be screwed onto the threaded element 66 of the housing to cover access site 208 while the strap 107 may rotate around the housing. Fluid connector cover 160 comprises threaded cover member 109 which may be fitted with annular clearance to flexible strap 110 integrated into the housing of the connector. Cover member 109 may turn or spin freely in the strap, for example, while screwing onto threaded elements 66B of connector body.

[0094] Referring now to FIGs. 6-7, fluid connector member 170 comprise cover member 112 which provides for snap-on functionality of cover member 112 onto corresponding receiving elements or set of elements 116 of connector housing 50D. Cutouts 115 may be provided to allow the cover member walls to flex when engaging elements 116. Groove 114 of the cover member securably attaches onto corresponding attachment members 111 of connector housing 50D. The grooves may allow the cover member to be lifted and swung away from access site 208 in an arc-like motion and may provide a load to return cover member to a position over access site. Finger grips 113 may be integrated into cover member 112 to provide for application and removal of the cover member. Undercuts 117 on cover member 112 may be provided to secure to corresponding engaging elements 116 on housing.

[0095] FIGs. 8 and 9 generally depict fluid connector covers where the translation of the cover member corresponds to the direction of the applied force. . Referring

now to FIG. 8, actuator 120 may be joined to rigid arm members 121 and flexible arm members 118. Arm members 118 may be secured to housing with snap-on attachment means 119. Arm members 121 may transmit load to flexible linking arms 118 when pressed inward, moving cover member 122 away from the access site.

- 5 Upon disconnecting, tension in the flexible arm 118 may provide force for the cover member 122 to return back and cover the access site. FIG. 9 actuator 120A may comprise a continuous element 124 having attachment means such as clip-like element 125 securing actuator 120A to connector housing, terminating at cover member 122A. Continuous element 124 comprises opening for providing access to
- 10 access site 208. Continuous element 124 may be U-, V, or W-shaped such as to provide a load to passively translate cover member 122A back to initial state covering access site. Cover member 122A may include an angled lead-in element 126 to aid in seating cover member 122A upon returning to its initial state.

- [0096] Referring now to FIG. 10, flexible member 102C is shown with alternate
- 15 beam geometry. The “s” shaped geometry may minimize stress and/or reduce the actuation force. Other shapes and configurations are envisaged such as to provide a force for passively returning the cover member to the access site.

- [0097] Referring now to FIGs. 11-12, fluid connector cover 200 is shown. Cover body 212 comprising flexible member 201 at least partially surrounds connector
- 20 housing 202. Rigid arm 204 attaches to cover body between cover member 203 and lower portion 205. Digital force to the lower portion 205 translates cover member 203 off access site 208 in an arc-like motion to expose the access site. Housing retaining means 207 on housing 202 restricts the movement of flexible member 201 providing flexation and load for returning cover member to the access site.

- 25 [0098] Referring now to FIGs. 13-14, fluid connector cover 200 is shown attached to a y-configuration connector housing 209 in an initial state and in a user-activated state exposing access site 208.

- [0099] Referring now to FIG. 15, cover adapter 200A of FIGs. 11-14 is shown. Attachment elements 210 may create a pivot point for the cover body 212. Lead-in
- 30 chamfers 213 may be provided to aid in vertical z-axis assembly of cover adapter to housing.

- [0100] Referring now to FIG. 16, connector housing 250 with corresponding attachment members 211 to attachment elements 210 of FIG. 15 are shown.

Attachment members 211 may provide snap-in-place and pivoting of cover adapter 200A.

[0101] Referring now to FIGs. 17-18, fluid connector cover 300 is shown in an initial state and an activated state, respectively. Collar 308 connects cover adapter 301 to connector housing 303. Beam-like flexible member 305 connects collar 308 to cover member 307. Rotation about connector housing 303 forces flexible member 305 up ramp 302. Ramp 302 may be integrated on connector housing 303. Finger grips 306 may be added to the collar for manipulation. Rotation of flexible member may be limited by housing retaining member 304. The ramp provides for flexible member 305 and cover member 307 to expose access site 208.

[0102] Referring now to FIG. 19, cover adapter 301 of the fluid connector cover of FIG. 18 without connector housing is shown. Cutout 310 of collar 308 provides for snap-on assembly of cover adapter to a fluid connector housing.

[0103] Referring now to FIG. 20, fluid connector cover 400 is shown. Cover body 401 may be attached to the connector housing 402 with a peg and hole assembly 406, which also acts as a rotation or pivot point. Finger-like flexible member 404 connects to lower portion 405 of rigid member 408. Flexible member 404 may provide load to rigid member. Digital pressure to lower portion 405 causes flexible member 404 to deflect against lower connector housing 403 and rigid member 408 to deflect outward, translating cover portion 407 from access site.

[0104] Referring now to FIGs. 21-22, automatic fluid connector cover 500 is shown. Cover body 501 may be fastened onto the connector housing 550 by a collar 505 with living hinge 507 and snap-fit element 504. Cover segments 503 connect to flexible arms 502 of the cover body. Insertion of external device 506 spreads cover segments apart to allow access to the access site.

[0105] Referring now to FIG. 23, fluid connector cover 600 comprises body member 609 connected to the connector housing 650 between rigid member 605 lower portion 604 and distal end having cover member 606. Elastomeric member 601 holds the cover member 606 adjacent the access site in an initial state. Digital pressure to the lower portion 604 translates cover member 606 from the access site in an arc-like motion and provides force to rigid member 605 for returning of the cover member to the access site. Housing retaining element 207 may be integrated with the housing for retaining elastomeric member and/or preventing slippage.

[0106] Referring now to FIG. 24, the cover adapter without the connector housing is shown without the elastomeric member. Retaining element for receiving the elastomeric member 607 as well as a grip element 603 for providing finger stability and ergonomic control are depicted.

5 [0107] Referring now to FIG. 25, fluid connector cover 600 is shown in the activated state. Digital pressure to lower portion 604 of the rigid member translates cover member 606 in an arc-like motion, exposing access site 208. The connector housing and/or the retaining element 207 allows the elastomeric member to stretch providing a load for returning the cover member over the access site 208. Elastomeric
10 member may be continuous or multiple elastomeric members that may be individually retained by housing retaining elements provided on the housing.

[0108] Referring to FIGs. 26A and 26B, cross-sectional and perspective view, respectively, of cover adapter 700 are shown. Cover adapter 700 comprises integrated elastomeric material. The joining method of the cover adapter may include two-shot
15 co-injection, over-molding or adhesion. Rigid member 703 distally terminates to cover portion 701 that may be seated adjacent the access site in the natural state. Rigid member 703 between and/or including the cover member 701 and lower portion 702 may contain elastomeric material, for example by overmolding of the cover adapter. Elastomeric covering surface 708 provides for contact with the access site.
20 Material channel 709 may provide for connecting the elastomeric covering surface with the flexible member 704. The elastomeric material may cover the lower portion 702 as well as provide gripping elements 705. Elements 707 may be provided in the rigid member 703 to assist elastomeric material adhesion to the cover adapter.

[0109] Referring now to FIG. 27, a cross-sectional view of cover adapter 720 is
25 shown. Retaining element 710 provides for securing elastomeric covering surface 708 to the cover member and may provide a gate location for injecting the elastomer material. Cover adapter 730 comprising cover member 711, as an extension of the rigid member 703, without elastomeric material is shown in FIG. 28.

[0110] Referring now to FIG. 29, cover adapter 740 is shown. Cover body member
30 721 comprises rigid member 706 having separate elastomeric bodies; covering surface 712 and flexible member 704. Body member 721 may include gripping elements 705.

[0111] Referring now to FIG. 30, cover adapter 800 is shown. Cover member 712B and rigid member 706B may be entirely elastomeric material. Functionality of

the adapter may be provided by thin sections for flexibility and thick sections for rigidity.

[0112] Referring now to FIGs.31 and 32, cover adapter 740 is shown in the initial passive state and an activated state. Penetrable septum type connector 900 is shown with attached cover adapter 740. Penetrating member 69 is provided access to access site 208 when digital force (not shown) is applied to rigid member 706.

[0113] Referring now to FIGs.33A and 33B, cover adapter 740 is shown in the initial passive state and an activated state adapted to vial adapter 950.

[0114] The fluid connector cover may be provided in a separate sterile package. The protective cover described in this document is not limited to use with I.V. products, Y-connectors, male/female luers and the like. Touch contamination is an issue with many connection applications. A protective cover, particularly a passive fluid connector cover as herein described may prevent or eliminate microbial growth and may also minimize particulate and other foreign material from being flushed or otherwise introduced through a fluid connection. Adaptations of the designs could be made to fit the parts to virtually any connection device.

[0115] Any and all of the components of the fluid connector cover may be injection molded, compression molded and/or transfer molded. Formed parts may further be overmolded with elastomeric material. Tooling of simple open/close design may be used. Integration of the fluid connector cover with the connector housing may provide a method to incorporate a cover without increasing the number of components, which may reduce assembly cost. Modification of existing female connector housings to provide for fluid connector covers as herein described may utilize tooling of the same orientation as for molding the existing housing. This may minimize cost in modifying current housings for adaptation of the fluid connector cover.

[0116] The fluid connector cover described above will normally be supplied in assembled form or as a kit, and may be provided sterile. The term "fluid connector cover kit" as used herein is intended to include within its scope the fluid connector cover or cover adapter thereof in partially or fully disassembled form. The fluid connector cover or kit may contain a fluid connector and a separate fluid connector cover assemblage for user-assembly. The fluid connector cover may be secured to or permanently affixed to the fluid connector.

[0117] In this specification and the appended claims, the singular forms "a," "an," and "the" include plural reference unless the context clearly dictates otherwise.

[0118] As used herein, "comprising" and grammatical equivalents thereof are inclusive or open-ended terms that do not exclude additional, unrecited elements or
5 method steps. "Comprising" is to be interpreted as including the more restrictive terms "consisting of" and "consisting essentially of."

[0119] As used herein, "consisting of" and grammatical equivalents thereof exclude any element, step, or ingredient not specified in the claim.

[0120] As used herein, "consisting essentially of" and grammatical equivalents
10 thereof limit the scope of a claim to the specified materials or steps and those that do not materially affect the basic and novel characteristic or characteristics of the claimed invention.

[0121] While the invention has been described in detail and with reference to specific embodiments thereof, it will be apparent to one skilled in the art that various
15 changes and modifications may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A fluid connector comprising
 - a housing having an access site;
 - 5 a rigid arm with a proximal and distal end;
 - a flexible member joining the rigid arm to the housing between the proximal and the distal end of the rigid arm; and
 - a cover member integral with the distal end of the rigid arm and positioned to cover the access site, the cover member displaceable from an initial position covering
 - 10 access site to a second position uncovering the access site upon displacement of the rigid arm.
2. The fluid connector of claim 1, wherein the access site is a female connector.
- 15 3. The fluid connector of claim 1, wherein the access site is a penetrable septum.
4. The fluid connector of claim 1, wherein the flexible member provides a load to the rigid arm.
- 20 5. The fluid connector of claim 4, wherein the load displaces the cover member from the second position to the initial position.
6. The fluid connector of claim 1, wherein the cover member contains an anti-microbial agent.
- 25 7. A cover adapter comprising
 - a body member securable to a fluid connector having an access site;
 - a rigid arm with a proximal and distal end;
 - a flexible member joining the rigid arm to the body member between the
 - 30 proximal and the distal end of the rigid arm; and
 - a cover member integral with the distal end of the rigid arm and positioned to cover the access site of the connector, the cover member displaceable from an initial

position covering the access site to a second position uncovering the access site upon displacement of the proximal end of the rigid arm.

5 8. The cover adapter of claim 7, wherein the cover member contains an anti-microbial agent.

9. A cover adapter comprising

a body member adapted to at least partially surround a fluid connector having an access site;

10 a rigid arm having a proximal end and distal end;

a flexible member joining the rigid arm between the proximal and the distal end to the body member and providing a load to the rigid arm; and

15 a cover member integral with the distal end of the rigid arm and positioned to cover the access site of the connector, the cover member being cooperatively displaceable from an initial position covering the access site to a second position uncovering the access site upon displacement of the rigid arm.

20 10. The cover adapter of claim 9, wherein the cover member contains an anti-microbial agent.

11. A fluid connector comprising

a housing comprising at least one fluid access site and attachment members;

a body member secured to the housing with corresponding attachment members;

25 a rigid arm having a proximal end and a distal end, the rigid arm joined to the body member between the proximal end and the distal end;

a flexible member secured to the body member and at least partially surrounding the housing, the flexible member providing a load to the rigid arm; and
30 a cover member secured to the distal end of the rigid arm and covering the access site.

12. The fluid connector of claim 11, wherein the flexible member provides a load to the rigid arm.

13. The fluid connector of claim 11, wherein the cover member contains an anti-
5 microbial agent.

14. A cover adapter comprising
a body member having attachment members securable to a fluid connector;
a rigid arm having a proximal end and a distal end, the rigid arm joined to the
10 body between the proximal end and the distal end;
a flexible member secured to the body member and at least partially surround the fluid connector, the flexible member adapted to provide a load to the rigid arm;
and
a cover member secured to the distal end of the rigid arm positioned to cover
15 the access site.

15. The cover adapter of claim 14, wherein the cover member contains an anti-microbial agent.

20 16. A fluid connector comprising
a housing having an access site, the housing comprising a ramp element at least partially surrounding an external portion of the housing;
a collar at least partially surrounding the housing and in cooperative relationship with the ramp element;
25 a flexible member having a proximal end and a distal end, the proximal end joined to the collar; and
a cover member integral with the distal end of the flexible member and positioned to cover the access site, the cover member displaceable from an initial position covering the access site to a second position uncovering the access site by
30 rotation of the collar and cooperative engagement with the ramp element.

17. The fluid connector of claim 16, wherein the cover member contains an anti-microbial agent.

18. A fluid connector comprising

a housing comprising at least one fluid access site and attachment members;

a body member secured to the housing with corresponding attachment

5 members;

a rigid arm having a proximal end and a distal end, the rigid arm joined to the body member between the proximal end and the distal end;

a flexible member loading the rigid arm; and

a cover member secured to the distal end of the rigid arm and covering the access site, the cover member cooperatively displaceable from the access site by displacement of the rigid arm.

19. The fluid connector of claim 18, wherein the body member is pivotable about the attachment members.

15

20. The fluid connector of claim 18, wherein the cover member contains an anti-microbial agent.

21. A fluid connector comprising

20 a housing comprising at least one fluid access site and attachment members;

a body member secured to the housing with corresponding attachment members;

a rigid arm having a proximal end and a distal end, the rigid arm joined to the body member between the proximal end and the distal end;

25 an elastomeric member loading the rigid arm between the proximal and the distal end; and

a cover member integral with the distal end of the rigid arm and covering the access site, the cover member displaceable from the access site by displacement of the rigid arm.

30

22. The fluid connector of claim 21, wherein the elastomeric material is integral with at least a portion of the body member or the body member and the rigid arm.

23. The fluid connector of claim 21, wherein the body member is pivotable about the attachment members.
24. The fluid connector of claim 21, wherein the elastomeric member loads the rigid
5 arm.
25. The fluid connector of claim 21, wherein the cover member comprises an elastomeric material.
- 10 26. The fluid connector of claim 21, wherein the access site is a female connector.
27. The fluid connector of claim 21, wherein the access site is a penetrable septum.
28. The fluid connector of claim 21, wherein the cover member contains an anti-
15 microbial agent.
29. A cover adapter comprising
a body member comprising attachment members securable to a fluid connector housing having at least one access site and corresponding attachment members;
20 a rigid arm having a proximal end and a distal end, the rigid arm joined to the body member between the proximal end and the distal end;
an elastomeric member loading the rigid arm; and
a cover member secured to the distal end of the rigid arm positioned to cover the access site.
- 25 30. The cover adapter of claim 29, wherein the elastomeric material is integral with at least a portion of the body member or the body member and the rigid arm.
31. The cover adapter of claim 29, wherein the cover member comprises an
30 elastomeric material.
32. The cover adapter of claim 29, wherein the access site is a female connector.

33. The cover adapter of claim 29, wherein the access site is a penetrable septum.

34. The cover adapter of claim 29, wherein the cover member contains an anti-microbial agent.

5

35. A cover adapter comprising

a body member securable to a fluid connector having an access site;

a rigid member comprising a proximal end integral with the body member, the rigid member displaceable towards the body member; and

10 a cover member integral with the distal end of the rigid member and positioned to cover the access site, the cover member being displaceable from an initial position covering the access site to a second position uncovering the access site upon displacement of the rigid member towards the body member.

15 36. The cover adapter of claim 35, wherein the rigid member is U-, V-, or W-shaped.

37. The cover adapter of claim 35, wherein the cover member contains an anti-microbial agent.

20 38. A fluid connector comprising

a housing comprising at least one fluid access site and attachment members;

at least one flexible arm having a proximal end and a distal end, the flexible arm secured to the housing at the proximal end with corresponding attachment members;

25 a cover positioned at the distal end of the flexible arm and covering the access site;

at least one rigid arm having a first end adjoining the at least one flexible arm in proximity to or including a portion of the cover and a second end projecting from the flexible arm and away from the housing;

30 an actuator attached or integral with the second end of the at least one rigid arm;

wherein the cover member is displaceable from an initial position covering the access site to a second position uncovering the access site upon displacement of the actuator.

5 39. The fluid connector of claim 38, wherein the actuator comprises a first end positioned away from the housing and a second end in contact with the housing.

40. The fluid connector of claim 38, wherein the cover member comprises an elastomeric material.

10

41. The fluid connector of claim 38, wherein the access site is a female connector.

42. The fluid connector of claim 38 wherein the access site is a penetrable septum.

15 43. The fluid connector of claim 38, wherein the cover member contains an anti-microbial agent

44. A housing for a fluid connector, the housing comprising
an access site

20

attachment members positioned on the housing; and

at least one housing retaining member positioned on the housing;

wherein the attachment members and the at least one housing retaining member cooperatively receive a cover adapter comprising

a body member having corresponding attachment members securable to the

25

housing;

a flexible member coupled to the body member and securable by the at least one housing retaining member;

a rigid member having a proximal end and a distal end, the rigid member joined to the body member between the proximal end and the distal end; and

30

a cover member secured to the distal end of the rigid arm positioned to cover the access site.

45. The housing of claim 44, wherein the flexible member comprises an elastomeric material.

46. The housing of claim 44, wherein the cover member comprises an elastomeric material.

47. The housing of claim 44, wherein the access site is a female connector.

48. The housing of claim 44 wherein the access site is a penetrable septum.

49. The housing of claim 44, wherein the cover member contains an anti-microbial agent

50. A method of aseptically covering an access site of a fluid connector, the method comprising:

providing a fluid connector comprising

a housing and at least one access site;

a rigid member; and

a cover member cooperatively connected to the rigid member and in a covering relationship with the access site, the cover member containing an aseptically effective material in proximity to the access site.

51. The method of claim 50, wherein the aseptically effective material is an anti-microbial agent.

52. The method of claim 50, wherein the cover member is under a load such that the cover member is passively held in a covering relationship with the access site.

53. The method of claim 50, wherein the access site is a female connector.

54. The method of claim 50, wherein the access site is a penetrable septum.

55. A method of preventing or eliminating contamination of an access site of a fluid connector, the method comprising:

providing a fluid connector cover comprising:

a housing and at least one access site;

5 a rigid member; and

a cover member cooperatively connected to the rigid member; and

providing a covering relationship between the access site and the cover member.

10 56. The method of claim 55, wherein the cover member is under a load such that the cover member is passively held in a covering relationship with the access site.

57. The method of claim 55, wherein the cover member comprises an elastomeric material.

15

58. The method of claim 55, wherein the cover member comprises an aseptically effective material.

59. The method of claim 55, wherein the access site is a female connector.

20

60. The method of claim 55, wherein the access site is a penetrable septum.

61. The method of claim 55, wherein the cover member comprises an elastomeric material.

25

62. The method of claim 55, wherein the rigid member comprises an elastomeric material.

63. A fluid connector comprising

30 a housing comprising an access site;

a cover member passively positioned in an initial covering relationship with the access site;

wherein the cover member is in a covering relationship with the access site such that the cover member is substantially reversible from an uncovered relationship under load to the initial covering relationship.

5 64. The fluid connector of claim 63, wherein the cover member contains an anti-microbial agent.

65. A fluid connector comprising

a housing comprising at least one access site;

10 a flexible arm having a proximal end and a distal end, the proximal end secured to the housing; and

a cover member secured to the distal end of the flexible arm, the cover member rotatable about the distal end of the flexible arm, the cover member containing an anti-microbial agent;

15 wherein the flexible arm is of a length sufficient to allow the cover member to cover the access site.

66. A fluid connector comprising

a housing comprising at least one access site;

20 a flexible arm having a proximal end and a distal end, the proximal end connected to the housing, the proximal end of the flexible arm rotatable about the housing; and

a cover member secured to the distal end of the flexible arm, the cover member containing an anti-microbial agent;

25 wherein the flexible arm is of a length sufficient to allow the cover member to cover the access site.

67. A fluid connector comprising

a housing comprising attachment members and at least one access site; and

30 a cover member comprising a cover with proximally extending arm elements, the arm elements having segments defining a slot securably receiving the attachment members which together with the attachment members provide a track and groove, the cover reversably displaceable from an initial position covering the access site to a

second position vertically displaced from the initial position uncovering the access site.

68. The fluid connector of claim 67, wherein the cover member contains an anti-
5 microbial agent.

1/18




FIG 1





FIG 2A

2/18



3/18







FIG 4

FIG 5


4/18



5/18



6/18



7/18





FIG 13

FIG 12

8/18



9/18





FIG 16

FIG 17

10/18



11/18





FIG 21

FIG 20

12/18



13/18






FIG 25

FIG 24


14/18





15/18



16/18



17/18



18/18




FIG 33B




FIG 33A

