



(51) International Patent Classification:

A61F 2/24 (2006.01)

(21) International Application Number:

PCT/US2019/019976

(22) International Filing Date:

28 February 2019 (28.02.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/636,672 28 February 2018 (28.02.2018) US

62/781,817 19 December 2018 (19.12.2018) US

16/286,436 26 February 2019 (26.02.2019) US

(71) Applicant: **EDWARDS LIFESCIENCES CORPORATION** [US/US]; One Edwards Way, Irvine, CA 92614 (US).

(72) Inventors: **COOPER, Alexander, H.**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **SCHWARTZ, Juliet, Laura**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **PHAM, Wendy, Vo**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **LUONG, Hieu, Minh**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **SANCHEZ, Julio, Cesar**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **PETERSON, Matthew, A.**; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US). **RATZ, J., Brent**; 123 Church Street, Winchester, MA 01890 (US). **AI, Lisong**; 213 Firefly, Irvine, CA 92618 (US).

(74) Agent: **HAUSER, David, L.** et al.; Edwards Lifesciences, One Edwards Way, Irvine, CA 92614 (US).

(54) Title: PROSTHETIC MITRAL VALVE WITH IMPROVED ANCHORS AND SEAL




FIG. 9

(57) **Abstract:** A mitral valve prosthesis includes an hourglass shaped inner frame and a bulbous outer frame. A valve body having a plurality of leaflets is positioned within an interior region of the inner frame. The leaflets are shaped to substantially conform to an interior surface of the inner frame when the leaflets are in an open position. As a result, the gap between the leaflets and the inner frame is decreased, thereby reducing the likelihood of thrombus formation. Ventricular anchors are preferably provided along a distal end of the inner frame. The anchors extend proximally for placement behind native mitral valve leaflets. A fabric skirt may extend along an inner or outer surface of the outer frame. In preferred embodiments, the fabric skirt extends distally beyond a distal end of the outer frame and is adapted for forming a seal along the mitral valve annulus.



(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (*Art. 21(3)*)
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (*Rule 48.2(h)*)

PROSTHETIC MITRAL VALVE WITH IMPROVED ANCHORS AND SEAL

BACKGROUND

Field

[0001] Certain embodiments disclosed herein relate generally to prostheses for implantation within a lumen or body cavity. In particular, certain embodiments relate to expandable prostheses such as replacement heart valves, such as for the mitral valve, that are configured to be secured to intraluminal tissue and prevent paravalvular leakage.

Description of the Related Art

[0002] Human heart valves, which include the aortic, pulmonary, mitral and tricuspid valves, function essentially as one-way valves operating in synchronization with the pumping heart. The valves allow blood to flow downstream, but block blood from flowing upstream. Diseased heart valves exhibit impairments such as narrowing of the valve or regurgitation, which inhibit the valves' ability to control blood flow. Such impairments reduce the heart's blood-pumping efficiency and can be a debilitating and life threatening condition. For example, valve insufficiency can lead to conditions such as heart hypertrophy and dilation of the ventricle. Thus, extensive efforts have been made to develop methods and apparatuses to repair or replace impaired heart valves.

[0003] Prostheses exist to correct problems associated with impaired heart valves. For example, mechanical and tissue-based heart valve prostheses can be used to replace impaired native heart valves. More recently, substantial effort has been dedicated to developing replacement heart valves, particularly tissue-based replacement heart valves that can be delivered with less trauma to the patient than through open heart surgery. Replacement valves are being designed to be delivered through minimally invasive procedures and even percutaneous procedures. Such replacement valves often include a tissue-based valve body that is connected to an expandable frame that is then delivered to the native valve's annulus.

[0004] These replacement valves are often intended to at least partially block blood flow. However, a problem occurs when blood flows around the valve on the outside of the prosthesis. For example, in the context of replacement heart valves, paravalvular leakage

has proven particularly challenging. An additional challenge relates to the ability of such prostheses to be secured relative to intraluminal tissue, e.g., tissue within any body lumen or cavity, in an atraumatic manner. Yet another challenge arises when trying to reduce the likelihood of thrombosis within parts of the replacement valves.

SUMMARY

[0005] Embodiments of the present disclosure are directed to a prosthesis, such as but not limited to a replacement heart valve. Further embodiments are directed to delivery systems, devices and/or methods of use to deliver and/or controllably deploy a prosthesis, such as but not limited to a replacement heart valve, to a desired location within the body. In some embodiments, a replacement heart valve and methods for delivering a replacement heart valve to a native heart valve, such as a mitral valve, are provided.

[0006] In some embodiments, a delivery system and method are provided for delivering a replacement heart valve to a native mitral valve location. The delivery system and method may utilize a transseptal approach. In some embodiments, components of the delivery system facilitate bending of the delivery system to steer a prosthesis from the septum to a location within the native mitral valve. In some embodiments, a capsule is provided for containing the prosthesis for delivery to the native mitral valve location. In other embodiments, the delivery system and method may be adapted for delivery of implants to locations other than the native mitral valve.

[0007] The present disclosure includes, but is not limited to, the following embodiments.

[0008] Embodiment 1: A mitral valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis having a proximal end and a distal end, the prosthesis comprising an inner frame comprising a body comprising a plurality of circumferentially extendable struts, and a plurality of longitudinally extending struts, wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells, and a plurality of inner frame anchoring features extending distally from the body, wherein the inner frame is generally hourglass shaped in the expanded position, an outer frame connected to the inner frame and comprising

a plurality of connected first v-shaped struts extending around a circumference of the prosthesis, and a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts, a valve body connected within an interior surface of the inner frame, the valve body comprising a plurality of leaflets arranged to allow flow in a first direction and prevent flow in a second direction opposite the first direction, wherein the leaflets conform to the interior surface of the inner frame when the valve body is in an open position for reducing a formation of thrombi between the plurality of leaflets and the interior surface of the inner frame, and a fabric skirt connected to an inner surface of the outer frame and extending distally beyond a distal end of the outer frame, wherein the fabric skirt is adapted for contacting a mitral annulus and forming a seal.

[0009] Embodiment 2: The mitral valve prosthesis of Embodiment 1, wherein the plurality of separate second v-shaped struts are thinner than the plurality of connected first v-shaped struts.

[0010] Embodiment 3: The mitral valve prosthesis of Embodiment 1 or Embodiment 2, further comprising a stiffness improving material attached to the outer frame, the inner frame, and the plurality of inner frame anchoring features, the stiffness improving material providing tension to the inner frame anchoring features when the prosthesis is in the expanded position and not providing tension to the inner frame anchoring features when the prosthesis is in the compressed position.

[0011] Embodiment 4: The mitral valve prosthesis of any one of Embodiments 1-3, wherein the plurality of inner frame anchoring features extend radially outwardly and then proximally, wherein each of the plurality of inner frame anchoring features ends with an anchoring tip.

[0012] Embodiment 5: The mitral valve prosthesis of Embodiment 4, wherein a distal end of the outer frame is longitudinally spaced above each of the anchoring tips.

[0013] Embodiment 6: The mitral valve prosthesis of any one of Embodiments 1-5, wherein a distal end of the outer frame ends proximal to a distal end of the two or more rows of cells.

[0014] Embodiment 7: The mitral valve prosthesis of any one of Embodiments 1-6, wherein the inner frame comprises a mushroom tab at a proximal end of at least one of the plurality of longitudinally extending struts.

[0015] Embodiment 8: The mitral valve prosthesis of any one of Embodiments 1-7, wherein the inner frame and the outer frame each comprise a plurality of apertures at or near a proximal end of the inner frame and the outer frame, and wherein each of the plurality of apertures of the inner frame generally aligns with an aperture of the plurality of apertures of the outer frame.

[0016] Embodiment 9: The mitral valve prosthesis of any one of Embodiments 1-8, wherein the outer frame comprises a plurality of outer frame anchoring features extending radially outwards.

[0017] Embodiment 10: The mitral valve prosthesis of any one of Embodiments 1-9, wherein the skirt is positioned between the inner frame and the outer frame.

[0018] Embodiment 11: The mitral valve prosthesis of any one of Embodiments 1-11, further comprising a valve body positioned within an interior of the inner frame, the valve body comprising a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

[0019] Embodiment 12: The mitral valve prosthesis of any one of Embodiments 1-11, wherein the expandable replacement heart valve prosthesis is configured to act as a replacement mitral heart valve.

[0020] Embodiment 13: The mitral valve prosthesis of any one of Embodiments 1-12, wherein each of the plurality of inner frame anchoring features ends with a pair of L-shaped anchors, the pair of L-shaped anchors being radially offset from one another.

[0021] Embodiment 14: The mitral valve prosthesis of any one of Embodiments 1-13, wherein the outer frame comprises a plurality of proximally extending struts extending between connections of adjacent connected first v-shaped struts.

[0022] Embodiment 15: The mitral valve prosthesis of Embodiment 14, wherein the outer frame comprises a circumferential shoulder spaced from a proximal end and a distal end of the outer frame, the circumferential shoulder being the radially outermost portion of the outer frame.

[0023] Embodiment 16: The mitral valve prosthesis of Embodiment 16, wherein the proximally extending struts are spaced radially inwards from the circumferential shoulder, and wherein a distal end of each of the plurality of first v-shaped struts is spaced radially inwards from the circumferential shoulder.

[0024] Embodiment 17: The mitral valve prosthesis of any one of Embodiments 1-16, wherein the expandable replacement heart valve prosthesis comprises nine inner frame anchoring features.

[0025] Embodiment 18: A delivery assembly configured to delivery an expandable replacement heart valve prosthesis, the delivery assembly comprising a steerable delivery system configured to releasably retain the expandable replacement heart valve prosthesis in a compressed position, and the expandable replacement heart valve prosthesis configured to expandable between the compressed position and an expanded position, the prosthesis comprising an inner frame comprising a plurality of circumferentially extendable struts, a plurality of longitudinal extending struts, and a plurality of inner frame anchoring features, wherein the inner frame is generally hourglass shaped in the expanded position, and an outer frame connected to the inner frame and comprising a plurality of connected first v-shaped struts extending around a circumference of the prosthesis, wherein the steerable delivery system is configured to sequentially expand portions of the prosthesis from the compressed position to the expanded position.

[0026] Embodiment 19: The delivery assembly of Embodiment 18, wherein the outer frame further comprises a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts.

[0027] Embodiment 20: The delivery assembly of Embodiment 18 or Embodiment 19, wherein the steerable delivery system further comprises an anchor separator comprising a body, a plurality of extensions extending radially away from the body, the plurality of extensions forming a plurality of longitudinally extending grooves, each of the plurality of longitudinally extending grooves configured to receive one of the plurality of inner frame anchoring features in the compressed position, and a lumen longitudinally extending through the body, wherein the body and the plurality of extensions are radially inwardly tapered at a proximal end and distal end of the anchor separator.

[0028] Embodiment 21: An expandable replacement heart valve prosthesis. The prosthesis can be configured to transition between a compressed position and an expanded position. The prosthesis can comprise an inner frame. The inner frame can comprise a plurality of circumferentially extendable struts. The inner frame can comprise a plurality of longitudinally extending struts. The plurality of circumferentially extendable struts and the plurality of longitudinally extending struts can form two or more rows of cells. The inner frame can comprise a plurality of inner frame anchoring features. The inner frame can be generally hourglass shaped in the expanded position. The prosthesis can comprise an outer frame. The outer frame can be connected to the inner frame. The outer frame can comprise a plurality of connected first v-shaped struts. The plurality of connected first v-shaped struts can extend around a circumference of the prosthesis. The outer frame can comprise a plurality of separate second v-shaped struts. Each of the separate second v-shaped struts can be attached within each of the connected first v-shaped struts. The plurality of separate second v-shaped struts can be thinner than the plurality of connected first v-shaped struts. The prosthesis can comprise a stiffness improving material attached to the outer frame. The stiffness improving material can be attached to the inner frame. The stiffness improving material can be attached to the plurality of inner frame anchoring features. The stiffness improving material can provide tension to the inner frame anchoring features when the prosthesis is in the expanded position. The stiffness improving material may not providing tension to the inner frame anchoring features when the prosthesis is in the compressed position.

[0029] Embodiment 22: The prosthesis of Embodiment 21, wherein the stiffness improving material can comprise sutures, fabric, or cloth.

[0030] Embodiment 23: The prosthesis of Embodiments 21-22, wherein the outer frame can comprise a plurality of outer frame anchoring features.

[0031] Embodiment 24: The prosthesis of Embodiments 21-23, wherein the prosthesis can be configured for use as a replacement mitral valve.

[0032] Embodiment 25: The prosthesis of any one of Embodiments 21-24, wherein the prosthesis can comprise a skirt positioned between the inner frame and the outer

frame. The skirt can be configured to automatically tuck within cells in the outer frame when the prosthesis is compressed.

[0033] Embodiment 26: The prosthesis of any one of Embodiments 21-25, wherein the prosthesis can comprise a valve body. The valve body can be positioned within an interior of the first frame. The valve body can comprise a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

[0034] Embodiment 27: An expandable replacement heart valve prosthesis configured to transition between a compressed position and an expanded position, wherein the inner frame can comprise a generally cylindrical first frame and an inwardly curved secondary frame located within the generally cylindrical first frame and attached to the generally cylindrical first frame, the inwardly curved secondary frame forming a generally hourglass shape within a longitudinal lumen of the inner frame.

[0035] Embodiment 28: The prosthesis of Embodiment 27, wherein the secondary frame can comprise a plurality of longitudinal struts on an outer surface of a fabric component.

[0036] Embodiment 29: The prosthesis of Embodiment 27, wherein the secondary frame can comprise a balloon filled with fluid.

[0037] Embodiment 30: The prosthesis of Embodiment 27, wherein the secondary frame can comprise a swellable material.

[0038] Embodiment 31: The prosthesis of any one of Embodiments 21-26, comprising the features of any one of Embodiments 27-30.

[0039] Embodiment 32: The prosthesis of any one of Embodiments 21-31, wherein each of the plurality of inner frame anchoring features can end with a pair of L-shaped anchors, the pair of L-shaped anchors being radially offset from one another.

[0040] Embodiment 33: A delivery system configured to deliver a prosthesis comprising a plurality of anchors, including any of the prostheses described herein this specification. The delivery system comprises an anchor separator comprising a body, a plurality of extensions extending radially away from the body, the plurality of extensions forming a plurality of longitudinally extending grooves for receiving the anchors of the prosthesis, and a lumen longitudinally extending through the body. The body and the plurality

of extensions are radially inwardly tapered at a proximal end and distal end of the anchor separator.

[0041] Embodiment 34: An expandable replacement heart valve prosthesis. The prosthesis can be configured to transition between a compressed position and an expanded position. The prosthesis can comprise a frame. The frame can have an inlet side. The frame can have a middle portion. The frame can have an outlet side. The frame can decrease in diameter at least from the inlet side to the middle portion. The prosthesis can comprise a valve body comprising a plurality of leaflets positioned within the frame. Each of the valve leaflets can have an inlet end positioned along the decreasing diameter portion of the frame.

[0042] Embodiment 35: The prosthesis of Embodiment 34, wherein the frame can be an hourglass shape.

[0043] Embodiment 36: An expandable replacement heart valve prosthesis. The prosthesis can be configured to transition between a compressed position and an expanded position. The prosthesis can comprise an inner frame. The inner frame can comprise a plurality of inner frame anchoring features. The features can extend from a lower portion of the inner frame. The prosthesis can comprise an outer frame. The outer frame can be connected to the inner frame. The prosthesis can comprise a stiffness improving material. The material attached to the outer frame. The material attached to the inner frame. The material attached to the plurality of inner frame anchoring features. The stiffness improving material can provide tension to the inner frame anchoring features when the prosthesis is in the expanded position. The material may not provide tension to the inner frame anchoring features when the prosthesis is in the compressed position.

[0044] Embodiment 37: The prosthesis of Embodiment 36, wherein the inner frame anchoring features can comprise a plurality of anchors. The anchors can extend radially outward from the inner frame. The anchors can extend generally toward an upper portion of the inner frame.

[0045] Embodiment 38: The prosthesis of any one of Embodiments 36 or 37, wherein the outer frame can extend over the inner frame.

[0046] Embodiment 39: The prosthesis of any one of Embodiments 36-38, wherein the stiffness improving material can comprise suture, fabric, or cloth material. The

material can extend from a lower portion of the outer frame. The material can attach to the inner frame anchoring features. The material can attach to a lower portion of the inner frame.

[0047] Embodiment 40: An expandable replacement heart valve prosthesis. The prosthesis can be configured to transition between a compressed position and an expanded position. The prosthesis can comprise a frame. The frame can comprise a plurality of connected first v-shaped struts. The struts can extend around a circumference of the prosthesis. The frame can comprise a plurality of separate second v-shaped struts. Each of the separate second v-shaped struts can be attached within each of the connected first v-shaped struts. The plurality of separate second v-shaped struts can be thinner than the plurality of connected first v-shaped struts.

[0048] Embodiment 41: An expandable replacement heart valve prosthesis. The prosthesis can be configured to transition between a compressed position and an expanded position. The prosthesis can comprise a frame. The frame can comprise a plurality of circumferentially extendable struts. The frame can comprise a plurality of longitudinally extending struts. The plurality of circumferentially extendable struts and the plurality of longitudinally extending struts can form two or more rows of cells.

[0049] Embodiment 42: A frame which can comprise a cell pattern as shown and described in Figures 3, 4 and/or 5A.

[0050] Embodiment 43: A prosthesis comprising one or more features of the foregoing description.

[0051] Embodiment 44: A method of treating valve insufficiency comprising one or more features of the foregoing description.

[0052] Embodiment 45: A delivery system for delivering the prosthesis comprising one or more features of the foregoing description.

[0053] Embodiment 46: The mitral valve prosthesis of any one of Embodiments 1-14, wherein free edges of a distal end of each of the plurality of leaflets are spaced away from the inner frame.

[0054] Embodiment 47: The mitral valve prosthesis of any one of Embodiments 1-15, wherein the fabric skirt is connected to an outer surface of a distal end of the inner

frame, and wherein the fabric skirt is held in tension between the outer frame and the inner frame.

[0055] Embodiment 48: The mitral valve prosthesis of any one of Embodiments 1-16, wherein the fabric skirt has sufficient flexibility to conform against a mitral annulus.

[0056] Embodiment 49: A mitral valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis having a proximal end and a distal end, the prosthesis comprising an inner frame comprising a body comprising a plurality of circumferentially extendable struts, and a plurality of longitudinally extending struts, wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells, and a plurality of inner frame anchoring features extending distally from the body, wherein the inner frame is generally hourglass shaped in the expanded position, an outer frame connected to the inner frame and comprising a plurality of connected first v-shaped struts extending around a circumference of the prosthesis, and a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts, a valve body connected within an interior surface of the inner frame, the valve body comprising a plurality of leaflets arranged to allow flow in a first direction and prevent flow in a second direction opposite the first direction, and a fabric skirt connected to an inner surface of the outer frame and an outer surface of a distal end of the inner frame under tension, wherein the fabric skirt extends distally beyond a distal end of the outer frame, and wherein the fabric skirt is adapted for conforming against a mitral annulus.

[0057] Embodiment 50: A mitral valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis having a proximal end and a distal end, the prosthesis comprising an inner frame comprising a body comprising a plurality of circumferentially extendable struts, and a plurality of longitudinally extending struts, wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells, and a plurality of inner frame anchoring features extending distally from the body, wherein the inner frame is generally hourglass shaped in the expanded position, an outer frame connected to the inner frame and comprising a plurality of connected first v-shaped struts extending around a circumference of

the prosthesis, and a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts.

BRIEF DESCRIPTION OF THE DRAWINGS

[0058] These and other features, aspects and advantages are described below with reference to the drawings, which are intended to illustrate embodiments of prostheses including embodiments of various components of these prostheses.

[0059] **FIGURE 1** illustrates an embodiment of a multi-portion replacement prosthesis.

[0060] **FIGURE 2** illustrates an embodiment of an inner frame of the multi-portion replacement prosthesis shown in **FIGURE 1**.

[0061] **FIGURE 3** illustrates a flat pattern of an embodiment of the inner frame shown in **FIGURE 2**.

[0062] **FIGURE 4** illustrates a portion of the inner frame of **FIGURE 2**.

[0063] **FIGURES 5A-5E** illustrate an inner frame having an hourglass shape.

[0064] **FIGURES 5F-5I** illustrate leaflets opening in a frame having an hourglass shape such as shown in **FIGURES 5A-5E**.

[0065] **FIGURES 5J-5K** illustrate a cross section of leaflets in open and closed positions in a frame having an hourglass shape such as shown in **FIGURES 5A-5E**.

[0066] **FIGURES 6A-6D** illustrate an embodiment of an outer frame of the multi-portion replacement prosthesis shown in **FIGURE 1**.

[0067] **FIGURE 7A** illustrates a flat pattern of the outer frame of **FIGURE 6** in a compressed configuration.

[0068] **FIGURE 7B** illustrates a flat pattern of the outer frame of **FIGURE 6** in an expanded configuration.

[0069] **FIGURES 7C-7D** illustrate alternate embodiments of a flat pattern of an outer frame.

[0070] **FIGURES 8A-8B** illustrate alternative flat patterns for an outer frame.

[0071] **FIGURES 9-11** illustrate a multi-portion replacement prosthesis with an outer skirt.

[0072] **FIGURE 12** illustrate a multi-portion replacement prosthesis having outer frame anchoring features.

[0073] **FIGURES 13A-13B** illustrate auto-tucking features of embodiments of the disclosed prosthesis.

[0074] **FIGURES 14A-14B** illustrate an embodiment for improving inner frame anchoring feature stiffness.

[0075] **FIGURE 15** illustrates an alternate embodiment for improving inner frame anchoring feature stiffness.

[0076] **FIGURE 16** illustrates assessment of prosthesis function prior to release.

[0077] **FIGURES 17A-17B** illustrate an embodiment of replacement prosthesis.

[0078] **FIGURES 18A-20** illustrate an embodiment of an alternative replacement prosthesis.

[0079] **FIGURE 21** illustrates an embodiment of a replacement prostheses.

[0080] **FIGURE 22** shows an embodiment of an inner frame of an alternate replacement prosthesis.

[0081] **FIGURES 23** shows an embodiment of an outer frame of an alternate replacement prosthesis.

[0082] **FIGURE 24** show an embodiment of anchoring elements.

[0083] **FIGURES 25A-25B** illustrate embodiments of an anchor separator.

[0084] **FIGURE 26** illustrates an embodiment of an anchor separator within a frame of a replacement prosthesis.

[0085] **FIGURES 27A-27B** show and embodiment of an anchor separator in use with a replacement prosthesis.

[0086] **FIGURES 28A-28B** show an embodiment of a suturing system for attachment to a delivery system.

[0087] **FIGURE 29** is an embodiment of an alternative replacement prosthesis.

[0088] **FIGURES 30A-30D** illustrates an embodiment of a multi-portion replacement prosthesis.

[0089] **FIGURE 31** illustrates an alternate embodiment of an inner frame with a secondary inner frame having an hourglass shape.

[0090] **FIGURE 32** illustrates a schematic representation of a transseptal delivery approach.

[0091] **FIGURE 33** illustrates a schematic representation of a valve prosthesis positioned within a native mitral valve.

[0092] **FIGURE 34** illustrates a schematic representation of a valve prosthesis positioned within a native mitral valve.

[0093] **FIGURE 35** shows an embodiment of a delivery system for use with any of the prostheses disclosed herein.

DETAILED DESCRIPTION

[0094] The present specification and drawings provide aspects and features of the disclosure in the context of several embodiments of prostheses, replacement heart valves, and methods that are configured for use in the vasculature of a patient, such as for replacement of natural heart valves in a patient. These embodiments may be discussed in connection with replacing specific valves such as the patient's mitral valve. However, it is to be understood that the features and concepts discussed herein can be applied to replacing other types of valves including, but not limited to, the aortic valve, the pulmonary valve, and the tricuspid valve. Moreover, it is to be understood that the features and concepts discussed herein can be applied to products other than heart valve implants. For example, the controlled positioning, deployment, and/or securing features described herein can be applied to medical implants, for example other types of expandable prostheses, for use elsewhere in the body, such as within a vein, or the like. In addition, particular features of a prosthesis should not be taken as limiting, and features of any one embodiment discussed herein can be combined with features of other embodiments as desired and when appropriate.

[0095] Certain terminology may be used in the following description for the purpose of reference only, and thus are not intended to be limiting. For example, terms such as "upper", "lower", "upward", "downward", "above", "below", "top", "bottom" and similar terms refer to directions in the drawings to which reference is made. Terms such as "proximal", "distal", "radially outward", "radially inward", "outer", "inner", and "side", describe the orientation and/or location of portions of the components or elements within a

consistent but arbitrary frame of reference which is made clear by reference to the text and the associated drawings describing the components or elements under discussion. Such terminology may include the words specifically mentioned above, derivatives thereof, and words of similar import. Similarly, the terms “first”, “second”, and other such numerical terms referring to structures neither imply a sequence or order unless clearly indicated by the context.

[0096] In some embodiments, the term “proximal” may refer to the parts of the prostheses, or components thereof, which are located closer to the operator of the device and system (e.g., the clinician implanting the prosthesis). The term “distal” may refer to the parts of the prostheses, or components thereof, which are located further from the operator of the device and system (e.g., the clinician implanting the prosthesis). However, it is to be understood that this terminology may be reversed depending on the delivery technique utilized (e.g., a transapical approach as compared to a transseptal approach). In some situations, the prosthesis, or components thereof, may be oriented such that an upper end is a proximal portion and a lower end is a distal portion.

[0097] In some situations, the prosthesis, or components thereof, the upper end may be an inflow end and the lower end may be an outflow end. For example, a valve body used with the prosthesis can allow flow from the upper end to the lower end. However, it is to be understood that the inflow end and the outflow end may be reversed. For example, the valve body used with the prosthesis can allow flow from the lower end to the upper end.

[0098] A longitudinal axis of the prosthesis, or components thereof, may be defined as the central axis that extends through the center of the prosthesis or component between the upper and lower ends of the prosthesis or component (e.g., the prosthesis, the outer frame, and/or the inner frame). The prostheses described herein may be replacement valves that can be designed to replace a damaged or diseased native heart valve such as a mitral valve, as discussed above. It should be understood that the prostheses are not limited to being a replacement valve.

[0099] As will be described in further detail below, the prostheses can include an inner frame and/or an outer frame or an inner portion and/or an outer portion. In some embodiments, the inner frame can be a valve frame designed to support a valve body. In

some embodiments, the outer frame can be a sealing frame designed to form a seal about a periphery of the outer frame. For example, the outer frame can engage tissue of a body cavity about a periphery of the outer frame and form a seal with said tissue. In some embodiments described herein, the outer frame can be attached to the inner frame at one or more stationary couplings such that the outer frame is fixed to the inner frame at one or more locations. It is to be understood that the outer frame can be attached to the inner frame via one or more movable couplings such as, but not limited to, rails. This can beneficially allow the outer frame to be adjusted relative to the inner frame to better conform to the anatomy of a patient's body cavity.

[0100] The inner frame and/or outer frame may be described as having an upper region, an intermediate region, and a lower region. In some situations, such as those in which the prostheses are positioned within a native mitral valve, the upper region can be generally positioned supra-annularly (i.e., above the plane of the annulus), the intermediate region can be generally positioned intra-annularly (i.e., within the plane of the annulus), and the lower region can be positioned sub-annularly (i.e., below the plane of the annulus). However, it is to be understood that in some situations, the positioning of the inner frame and/or outer frame relative to the annulus can differ. Moreover, it is to be understood that in some embodiments, the inner frame and/or outer frame can omit one or more of the upper region, the intermediate region, and/or the lower region.

[0101] While certain combinations of inner frames and outer frames are described herein, it is to be understood that the inner frames and outer frames can be interchanged. This can beneficially allow the prosthesis to be configured in a manner which better suits the native anatomy of the patient. Moreover, while the inner frames and outer frames can be attached prior to delivery into the patient, it is to be understood that the inner frames and outer frames can be delivered separately into the patient and subsequently attached in the patient's body. This can beneficially reduce the crimp profile when delivering the frames to the body cavity. The prostheses described herein can be used as a standalone device. For example, the prosthesis can be deployed at a native mitral valve and be sized and shaped appropriately to replace the function of the native mitral valve. However, it is to be understood that the prostheses described herein can be used with other devices. For example,

one or more clips can be used to hold together native leaflets of a heart valve. This can advantageously allow a smaller prosthesis to be utilized at the native mitral valve.

Embodiments of Replacement Valves and Frames

[0102] **Figure 1** shows an embodiment of the frame of a multi-portion prosthesis **100** in an expanded configuration. The prosthesis **100** can include, but are not limited to, an inner frame **120**, an outer frame **140**, a valve body **160** (shown in **Figures 9-11**), and a skirt **180** (also shown in **Figures 9-11**). A longitudinal axis of the prosthesis **100** may be defined as the central axis that extends through the center of the prosthesis **100** between the upper and lower ends of the prosthesis **100**. In some situations, the prosthesis **100** may be oriented such that an upper end of the prosthesis **100** is a proximal portion and a lower end of the prosthesis **100** is a distal portion. The illustrated prosthesis **100**, as well as other prostheses described herein, may include components which are self-expanding or balloon expandable. For example, in some embodiments, the inner frame **120** and/or outer frame **140** can be self-expanding. The prosthesis **100**, as well as other prostheses described herein, may be a replacement valve that can be designed to replace a damaged or diseased native heart valve such as a mitral valve, as discussed above. It should be understood that the prosthesis **100**, as well as other prostheses described herein, are not limited to being a replacement valve.

[0103] Embodiments of the disclosed prosthesis **100** may have a reduced crimp inner diameter (ID), such as 25Fr, 24Fr, 23Fr, 22Fr, 21Fr, or 20Fr. Embodiments of the disclosed prosthesis **100** may have a reduced crimp ID, such as less than 25Fr, 24Fr, 23Fr, 22Fr, 21Fr, or 20Fr. Embodiments of the disclosed prosthesis **100** may have a reduced crimp ID, such as greater than 25FR, 24Fr, 23Fr, 22Fr, 21Fr, or 20Fr. In some embodiments, the prosthesis **100** may have a crimp length of 48, 47, 46, 45, 44, 43, 42, 41, or 40mm. In some embodiments, the prosthesis **100** may have a crimp length of less than 48, 47, 46, 45, 44, 43, 42, 41, or 40mm. In some embodiments, the prosthesis **100** may have a crimp length of greater than 48, 47, 46, 45, 44, 43, 42, 41, or 40mm. In some embodiments, the prosthesis **100** may only require retrieval forces of 60, 55, 50, 45, or 40 lbs. to compress the prosthesis **100**. In some embodiments, the prosthesis **100** may only require retrieval forces of less than 60, 55, 50, 45, or 40 lbs. to compress the prosthesis **100**. In some embodiments, the

prosthesis **100** may only require retrieval forces of greater than 60, 55, 50, 45, or 40 lbs. to compress the prosthesis **100**.

[0104] As further disclosed below, the multi-portion prosthesis **100** can be made of one or more frames, such as one, two, or three frames. In some embodiments, the prosthesis **100** can be a dual-frame design, having an inner and an outer frame. In some embodiments, the inner and outer frame are integrally formed into one frame. In other embodiments, the frames can be separate and connected together.

Inner Frame

[0105] **Figure 2** illustrates the inner frame **120** of the prosthesis **100** with the outer frame **140** removed for clarity. Further, **Figure 3** illustrates a flat pattern of the inner frame **120**. The inner frame **120** can generally include an inner frame body **122** and an inner frame anchoring feature **124** (if used in a mitral valve, also known as a ventricular or distal anchor). The inner frame body **122** can have an upper region **126**, an intermediate region **128**, and a lower region **130**. As shown, the inner frame body **122** can have a generally cylindrical shape such that the diameters of the upper region **126**, the intermediate region **128**, and the lower region **130** are generally equivalent. However, it is to be understood that the diameters of the upper region **126**, the intermediate region **128**, and/or the lower region **130** can be different, such as the hourglass shape discussed below with respect to **Figures 5A-5E**. For example, in some embodiments, a diameter of the intermediate region **128** can be larger/smaller than the upper region **126** and the lower region **130** such that the frame body **122** has a generally bulbous shape. In some embodiments, the diameter of the lower region **130** can be larger than the diameter of the upper region **126**. In other embodiments, the diameter of the upper region **126** can be larger than the diameter of the lower region **130**. Moreover, although the inner frame body **122** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the inner frame body **122** can have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0106] In some situations, such as those in which the prosthesis **100** is positioned within a native mitral valve, the upper region **126** can be generally positioned supra-annularly

(i.e., above the plane of the annulus), the intermediate region **128** can be generally positioned intra-annularly (i.e., within the plane of the annulus), and the lower region **130** can be positioned sub-annularly (i.e., below the plane of the annulus). However, it is to be understood that in some situations, the positioning of the inner frame **120** relative to the annulus can differ. For example, the intermediate region **128** can be positioned supra-annularly. Moreover, it is to be understood that in some embodiments, the inner frame **120** can omit one or more of the upper region **126**, the intermediate region **128**, and/or the lower region **130**.

[0107] As shown **Figure 2**, the inner frame **120** can include inner frame anchoring feature(s) **124** (in some embodiments ventricular anchors) which can extend generally downwardly and/or radially outwardly at or proximate a lower end of the lower region **130** of the inner frame body **122**. The inner frame anchoring feature **124** can extend upwardly towards the upper region **126** after extending radially outwards. As will be discussed in further detail below, components of the inner frame **120**, such as the inner frame anchoring feature **124**, can be used to attach or secure the prosthesis **100** to a native valve. For example, in some situations, the inner frame anchoring feature **124** can be used to attach or secure the prosthesis **100** to a native mitral valve. In such an embodiment, the inner frame anchoring feature **124** can be positioned to contact or engage a native mitral valve annulus on a ventricular side, tissue beyond the native valve annulus on a ventricular side, native leaflets on a ventricular side, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. When positioned within the native mitral valve, the inner frame anchoring feature **124** can beneficially eliminate, inhibit, or limit upward movement of the prosthesis **100** when subject to upwardly directed forces such as those which are applied on the prosthesis **100** during systole. As shown, the prosthesis **100** can have nine inner frame anchoring features **124**, but in some embodiments may have more or less, such as 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, or 12 inner frame anchoring features **124**.

[0108] With continued reference to the inner frame **120** illustrated in **Figure 2**, the inner frame anchoring feature **124** can have ends or tips **124a** positioned radially outwardly relative to the longitudinal axis of the prosthesis **100**. The inner frame anchoring

feature **124** can extend at or proximate a lower end of the lower region **130** of the inner frame body **122**. As shown, the inner frame anchoring feature **124** can be formed from a plurality of individual anchors extending from the frame body **122**. The anchors can extend downwardly from one or more attachment points to the frame body **122** including, but not limited to, lower apices of cells **134b**. The anchors can bend to extend generally radially outwardly of the longitudinal axis of the prosthesis **100**. As shown in the illustrated embodiment, the anchors can extend upwardly towards an end or tip **124a**.

[0109] As shown in the illustrated embodiment, the tips or ends **124a** extend upwardly in a direction parallel or generally parallel to the longitudinal axis of the prosthesis **100**. In some embodiments, the tip or end **124a** of anchoring feature **124** can extend generally perpendicular to the longitudinal axis of the prosthesis **100**. This can beneficially increase the tissue contact area of the tip **124a** of the anchor. This increased tissue contact area can beneficially reduce the stress applied by the tip **124a** to tissue thereby reducing the amount of pressure and potential for trauma to the tissue. In some embodiments, the tip or ends **124a** of the anchoring feature **124** extend radially inward towards the longitudinal axis and/or radially outward away from the longitudinal axis.

[0110] The tips or ends **124a** as described above can advantageously provide atraumatic surfaces that may be used to contact or engage intraluminal tissue without causing unnecessary or undesired trauma to tissue. For example, the tips or ends **124a** can form flat, substantially flat, curved or other non-sharp surfaces to allow the tips to engage and/or grasp tissue, without necessarily piercing or puncturing through tissue. A looped end or looped anchor, such as shown in **Figure 5A**, may assist the frame in not getting caught up on structures at or near the treatment location. For example, each loop can be configured so that when the prosthesis **100** is deployed in-situ and the anchoring features **124a** expands away from the frame bodies **122**, the movement of each loop from a delivered position to a deployed position avoids getting caught on the papillary muscles. In some embodiments, the inner frame anchoring feature **124** can include a lacrosse-head-shaped tip or end **124a**. In some embodiments, the tips or ends **124a** of the inner frame **120** may have a split design such as shown in **Figure 24**.

[0111] The anchoring features **124** can include nine individual anchors; however, it is to be understood that a greater number or lesser number of individual anchors can be used. For example, the number of individual anchors can be chosen as a multiple of the number of commissures for the valve body **160** (shown in **Figure 10**). As such, for a prosthesis **100** with a valve body **160** having three commissures, the inner frame anchoring feature **124** can have three individual anchors (1:1 ratio), six individual anchors (2:1 ratio), nine individual anchors (3:1 ratio), twelve individual anchors (4:1 ratio), fifteen individual anchors (5:1 ratio), or any other multiple of three. It is to be understood that the number of individual anchors need not correspond to the number of commissures of the valve body **160**. Moreover, while the prosthesis **100** includes anchoring features **124** with twelve anchors each, it is to be understood that a greater number of anchors or a lesser number of anchors can be used.

[0112] With reference to the inner frame **120** illustrated in **Figures 9-11** and **17B**, the inner frame anchoring feature **124** can include covers and/or cushions **138** to surround or partially surround at least a portion of the inner frame anchoring feature **124**, such as the tips or ends **124a**. The covers and/or cushions **138** can be similar to those described in U.S. Publication No. 2015/0328000, which is incorporated by reference herein in its entirety. The covers and/or cushions **138** can either fit snugly around the tips **124a** of the inner frame anchoring feature **124** or can have extra padding so that the covers extend radially away from the inner frame body **122**. As shown in the illustrated embodiment, covers and/or cushions **138** are attached to a subset of anchors of the inner frame anchoring feature **124** such that a cover and/or cushion **138** is used on every third anchor. In some embodiments, the outer frame anchoring feature **144** can include covers and/or cushions to surround or partially surround at least a portion of the outer frame anchoring feature **144**, such as the tips or ends **144a**.

[0113] It is to be understood that greater or fewer numbers of covers and/or cushions **138** can be used with anchors of the inner frame anchoring feature **124**. For example, a cover and/or cushion **138** can be used on every other anchor such that there is a 1:2 ratio of covers and/or cushions **138** to anchors. As another example, a cover and/or cushion **138** can be used on every anchor (as shown in **Figures 9-11**). In some embodiments,

all of the anchors can have the covers and/or cushions with some of the anchors having less cushioning than others. In some embodiments, all of the anchors can have the padded covers. In other embodiments, all of the anchors can have the snugly fitting cushions.

[0114] The cover and/or cushion **138** can be formed from a deformable material. When the top portion of the cover and/or cushion **138** is subject to pressure due to a downwardly directed force, the cover and/or cushion **138** can compress and expand laterally outward. Such a force may be exerted upon the cover and/or cushion **138** when the cover and/or cushion **138**, for example, when the cover and/or cushion **138** contacts a ventricular side of the mitral valve annulus during systole. The compression and lateral expansion of cover and/or cushion **138** can increase the surface area of the cover and/or cushion **138** in contact with the tissue, thereby exerting less pressure on the tissue and reducing the potential for trauma.

[0115] The inner frame **120** can be formed from many different materials including, but not limited to a shape-memory metal such as Nitinol. The inner frame **120** can be formed from a plurality of struts forming open cells, discussed below. In some embodiments, the inner frame **120** can have a relatively rigid construction as compared to other components of the prosthesis **100** including, but not limited to, the outer frame **140**. This can be achieved, for example, by the dimensions of the struts and by the configuration of the struts. The relatively rigid construction can more strongly resist deformation when subject to stress. This can be beneficial during certain portions of the cardiac cycle, such as systole, during which the inner frame **120** may be subject to significant stresses on the inner frame anchoring feature **124**. The relatively rigid construction can also be beneficial when a valve body **160** is positioned within the inner frame **120** to maintain the shape of the valve body **160**. Moreover, the relatively rigid construction can be beneficial when the inner frame **120** is used for a valve-in-valve procedure wherein a supplemental prosthesis is positioned within the inner frame **120**. However, although the inner frame **120** has been described as having a relatively rigid construction, it is to be understood that in some embodiments the inner frame **120** can have a construction relatively flexible construction. For example, the inner frame **120** can have a construction which is about as flexible as, or more flexible than, other components of the prosthesis **100**, such as the outer frame **140**.

[0116] The diameter of the upper region **126**, intermediate region **128**, and/or lower region **130** of the inner frame body **122** may be chosen such that the inner frame body **122** is adequately spaced from the body cavity when the prosthesis **100** is positioned within the body cavity. For example, in embodiments where the prosthesis **100** is positioned within the native mitral valve, the inner frame body **122** may have a diameter which is less than the diameter of the native mitral valve annulus. In situations where the native mitral valve annulus is about 40mm in diameter, the diameter of the inner frame body **122** can be about 30mm. Accordingly, the diameter of the inner frame body **122** may be about 75% of the diameter of the native mitral valve annulus.

[0117] In some embodiments, the diameter of the inner frame body **122** may be between about 40% to about 90% of the diameter of the native valve annulus, between about 60% to about 85%, of the diameter of the native valve annulus, between about 70% to about 80% of the diameter of the native valve annulus, any other sub-range between these ranges, or any other percentage as desired. In some embodiments, the diameter of the inner frame body **122** can be in the range of about 20mm to about 40mm when expanded, in the range of about 25mm to about 35mm when expanded, in the range of about 28mm to about 32mm when expanded, any other sub-range within these ranges when expanded, or any other diameter when expanded as desired. Although the inner frame body **122** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the inner frame body **122** can be have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0118] In other embodiments, the diameter of portions of the inner frame body **122** such as the upper region **126**, intermediate region **128**, and/or lower region **130** may be chosen such that the inner frame body **122** is positioned at the periphery of the body cavity. For example, in embodiments where the prosthesis **100** is positioned within the native mitral valve, the inner frame body **122** may have a diameter which is about equal to the diameter of the native mitral valve annulus.

[0119] **Figure 4** illustrates a portion of the inner frame body **122**. As shown, the inner frame body **122** can include a plurality of struts with at least some of the struts forming cells **134a-b**. Any number of configurations of struts can be used, such as rings of undulating

struts shown forming ellipses, ovals, rounded polygons, and teardrops, but also chevrons, diamonds, curves, and various other shapes. The upper row of cells **134a** and the lower row of cells **134b** can have a diamond/parallelogram or generally diamond/ parallelogram shape. The rows of cells **134a-b** can be formed via a combination of struts. As shown in the illustrated embodiment, the upper row of cells **134a** can be formed from a first set of circumferentially-expansible struts **136a** at the top and bottom and a longitudinally extending strut **138**. The lower row of cells **136b** can be formed from the second set of circumferentially-expansible struts **136b** on the top and bottom and a longitudinally extending strut **138** on each side, which can be a continuation of the longitudinally extending strut mentioned above. As shown, the upper row of cells **134a** and the lower row of cells **136b** can share one circumferentially-expansible strut. For example, the bottom strut of the upper row of cells **134a** and the top strut of lower row of cells **136b** may be shared. The first and second sets of struts **136a-b** can have a zig-zag or undulating shape forming a repeating “V” shape. While the struts **136a-b** are generally described and illustrated as being straight segments, it is to be understood that some or all of the struts **136a-b** may not form entirely straight segments. For example, the struts **136a-b** can include some curvature such that the upper and/or lower apices are curved as shown in **Figure 2**.

[0120] Further, as shown in **Figure 4** the longitudinally extending strut **138** can generally extend from a bottom of the inner frame body **122** to a top of the inner frame body **122**. Advantageously, the longitudinally extending strut **138** may effectively experience little to no strain during crimping. The longitudinally extending strut **138** may be one single strut extending through both rows of cells **134a/134b**. Further, as shown each cell of the rows of cells **134a/134b** can be circumferentially between longitudinally extending struts **138**.

[0121] As shown in the illustrated embodiment, the upper row of cells **134a** and the lower row of cells **134b** extend in a direction generally parallel to the longitudinal axis of the prosthesis **100**. There can be a row of eighteen cells **134a** and a row of eighteen cells **134b**. While each of the cells **134a-b** are shown as having the same shape as other cells **134a-b** of the same row but mirrored, it is to be understood that the shapes of cells **134a-b** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows. In some embodiments, the

number of cells can correspond to the number of anchors or anchor tips forming the inner frame anchoring feature **124**. In some embodiments, both rows of cells **134a-b** can have different numbers of cells. Moreover, it is to be understood that fewer or greater numbers of rows of cells can be used.

[0122] The geometry of cells **134a-b** can allow the cells **134a-b** to foreshorten as the inner frame **120** is expanded. As such, one or more of cells **134a-b** can allow the inner frame **120** to foreshorten as the inner frame **120** is expanded. Foreshortening of the inner frame **120** can be used to secure the prosthesis to intraluminal tissue in a body cavity such as tissue at or adjacent a native valve including, but not limited to, a native valve annulus and/or leaflets. For example, expansion of the inner frame **120** can allow the inner frame anchoring feature **124** to extend radially outward and draw closer to tissue of the body cavity, such as a native valve annulus and/or leaflets, to engage tissue of the body cavity. In some embodiments, the use of longitudinally extending strut **138** can reduce the foreshortening.

[0123] Additionally, as shown in **Figure 2**, the inner frame **120** can include tabs (or locking tabs) **104** extending from a portion of the inner frame **120**. The tabs **104** can extend at or proximate an upper end of the upper region **126** of the inner frame body **122** such as upper apices of cells **134a**. The inner frame **120** can include twelve locking tabs **104**, however, it is to be understood that a greater number or lesser number of locking tabs can be used, such as 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or 11. The locking tabs **104** can extend generally upwardly from the upper region **126** of the inner frame body **122** in a direction generally aligned with the longitudinal axis of the prosthesis **100**. As shown in the illustrated embodiment, the locking tabs **104** can include a longitudinally-extending strut **132a**. At an upper end of the strut **132a**, the locking tab **104** can include an enlarged head **132b**. As shown, the enlarged head **132b** can have a semi-circular or semi-elliptical shape forming a “mushroom” shape with the strut **132a**.

[0124] In some embodiments, the inner frame **120** can include an eyelet **106**. The eyelet **106** can be advantageously used to couple the inner frame **120** to an outer frame **140**. For example, a suture can be passed through the eyelet **106** for coupling to an eyelet **143** of the outer frame **140**. In some embodiments, the eyelet **106** can be used to couple to other

components of a prosthesis in which the inner frame **120** is used such as, but not limited to, a valve body and/or a skirt.

[0125] While the locking tabs **104** have been described as being attached to the inner frame body **122**, it is to be understood that the locking tabs **104** can be attached to other portions of the prosthesis **100** such as, but not limited to, the outer frame body **142**. For example, in some embodiments, the locking tabs **104** can extend from an upper end of an upper region **146** of the outer frame body **142**. Moreover, it is to be understood that portions of, or the entirety of, the locking tabs **104** can be omitted. For example, in some embodiments, the strut **132a** can be omitted such that the enlarged head **132b** and eyelet **106** are positioned at an upper end of the upper region **126** of the inner frame body **122**, such as at upper apices of cell **134a**.

[0126] In some embodiments, each tab **104** can be aligned vertically over an inner frame anchoring feature **124**. In some embodiments, each tab **104** is circumferentially offset from an inner frame anchoring feature **124**. In some embodiments, there are the same number of tabs **104** as inner frame anchoring features **124**. In some embodiments, there are a different number of tabs **104** as inner frame anchoring features **124**. There can be more tabs **104** than inner frame anchoring features **124**. There can be less tabs **104** as inner frame anchoring features **124**.

[0127] In some embodiments, the tab **104** can be advantageously used to couple the inner frame **120** with multiple types of delivery systems. For example, the shape of the tab **104** can be used to secure the inner frame **120** to a “slot” based delivery system. The eyelets **106** can be used to secure the inner frame **120** to a “tether” based delivery system such as those which utilize sutures, wires, or fingers to control delivery of the inner frame **120** and the prosthesis. This can advantageously facilitate recapture and repositioning of the inner frame **120** and the prosthesis in situ. In some embodiments, the inner frame **120** and prosthesis can be used with the delivery systems described herein, including but not limited to, those described in U.S. Patent Nos. 8,414,644 and 8,652,203 U.S. Publication Nos. 2015/0238315, 2019/0008640, 2017/0056169, 2016/0317301 and 2017/0056171, the entireties of each of which have been incorporated by reference herein. In such embodiments,

the tab **104** may be omitted to advantageously the axial dimension between the upper end and the lower end of the inner frame **120** (i.e., the “height” of the inner frame **120**).

[0128] The inner frame **120**, and any other frame described herein, may include features and concepts similar to those disclosed in U.S. Patent Nos. 8,403,983, 8,414,644, and 8,652,203, U.S. Publication Nos. 2011/0313515, 2014/0277390, 2014/0277427, 2014/0277422, 2015/0328000, 2018/0021129, and 2018/0055629, the entireties of each of which are hereby incorporated by reference and made a part of this specification. This is inclusive of the entire disclosure and is not in any way limited to the disclosure of the associated frames. Moreover, although the inner frame **120** has been described as including an inner frame body **122** and an inner frame anchoring feature **124**, it is to be understood that the inner frame **120** need not include all components. For example, in some embodiments, the inner frame **120** can include the inner frame body **122** while omitting the inner frame anchoring feature **124**. Moreover, although the inner frame body **122** and the inner frame anchoring feature **124** have been illustrated as being unitarily or monolithically formed, it is to be understood that in some embodiments the inner frame body **122** and the inner frame anchoring feature **124** can be formed separately. In such embodiments, the separate components can be attached using any of the fasteners and/or techniques described herein. For example, the inner frame anchoring feature **124** can be formed separately from the inner frame body **122** and can be attached to the inner frame body **122**.

[0129] **Figures 5A-5E** illustrates an inner frame **220** with an “hourglass” or generally hourglass shape. A full multi-portion replacement valve with an hourglass inner frame is shown with respect to **Figures 30A-30D**. The inner frame **220** can incorporate any or all of the features discussed above with respect to inner frame **120**, for example inner frame anchoring feature **124**, and the inner frame **120** can incorporate any or all of the features discussed above with respect to inner frame **220**. Inner frame **220** can include an upper region **226**, an intermediate region **228**, and a lower region **230**. As shown, the intermediate region **228** can have a smaller diameter than the upper region **226**, the lower region **230**, or both. This can form an hourglass shape wherein the intermediate region **228** is thinner in diameter than both the upper region **226** and the lower region **230**. In some embodiments, the upper region **226** and the lower region **230** can have approximately the

same diameter. In some embodiments, the upper region **226** can have a larger diameter than the lower region **230**. In some embodiments, the upper region **226** can have a smaller diameter than the lower region **230**.

[0130] **Figures 5A-5E** further illustrates that the inner frame **220** can smoothly transition between the different diameters forming a curved shape. In some embodiments, the struts making up the inner frame **220** can be curved to form the hourglass. In some embodiments, the struts can be relatively straight, and there can be inflection points in the struts or at meeting points between the struts. In some embodiments, the inner frame **220** can be concave. In some embodiments, a portion of the inner frame **220**, such as the upper region **226**, the intermediate region **228**, and/or the lower region **230** may be concave. In some embodiments, the inner frame **220** can curve inward, or be thinner, in the middle than at the top and bottom. In some embodiments, the inner frame **220** can form the hourglass shape in its fully expanded form. In some embodiments, an hourglass can be shaped from a linear radially inwards taper from the upper region **226** to the intermediate region **228** (so the diameter is smaller at the intermediate region **228** than the upper region **226**) and a subsequent radially outwards taper (e.g., reversing the taper) from the intermediate region **228** to the lower region **230** (so the diameter is smaller at the intermediate region **228** than the lower region **230**). In some embodiments, the frame **220** may have a tapered waist or a narrowed waist.

[0131] In some embodiments, the inner frame **220** can taper radially inwards (e.g., reducing diameter) in one direction from one end to the other end. For example, the upper region **226** may have the largest diameter, and the inner frame **220** can taper radially inwards to the intermediate region **228**, and further radially inwards to the lower region **230**. In some embodiments, the lower region **230** may have the largest diameter, and the inner frame **220** can radially inwards to the intermediate region **228**, and further radially inwards to the upper region **226**. The taper may be smooth, or may be a series of straight portions, like steps. In some embodiments, the taper may occur in 1, 2, 3, 4, 5 straight lines reducing the diameter. In some embodiments, the taper may be curved. In some embodiments, the taper may be linear.

[0132] In some embodiments, a portion of the inner frame **220** may be tapered radially inwards, and a different portion may be cylindrical (or generally cylindrical). For example, the upper region **226** may be tapered radially inwards, but the intermediate region **228** and/or the lower region **230** may be cylindrical. In some embodiments, the lower region **230** may be tapered radially inwards, but the intermediate region **228** and/or the upper region **226** may be cylindrical.

[0133] In some embodiments, a portion of the inner frame **220** may be tapered radially inwards, and a different portion may be concave (or generally concave). For example, the upper region **226** may be tapered radially inwards, but the intermediate region **228** and/or the lower region **230** may be generally. In some embodiments, the lower region **230** may be tapered radially inwards, but the intermediate region **228** and/or the upper region **226** may be generally.

[0134] The hourglass shape and/or tapering described above can allow for the leaflets of the valve to be “flush” against the inner frame **220** when opened. Further, the longitudinal length of the leaflets can be against the inner frame **220** as much as possible. For example, each of the valve leaflets can have an inlet end positioned along the decreasing diameter portion of the frame as discussed above. Additionally, the narrower intermediate region **228** can provide for smaller replacement valve leaflets to be used, and the smaller diameter can allow for increased blood flow through the narrower area.

[0135] Embodiments of the inner frame **220** can advantageously reduce thrombogenicity. For example, the hourglass shape can help create a vortex which encourages particles to be washed-out during valve opening with high turbulence during closing. This can also include squeezing out any thrombus that may be forming in the gap between leaflets and the frame **220**. In addition, this shape can reduce leaflet thickening, which can cause increased risk of stroke. This can allow for the reduction or avoidance of blood thinners, or at least the avoidance of lifetime blood thinners. This could clinically lead to less anticoagulation, better durability, and lower stroke.

[0136] [0130] **Figures 5F-5I** illustrate the valve leaflets **231** opening in an hourglass shaped frame **220**. **Figure 5F** shows the outflow end open, **Figure 5G** shows the inflow end open, **Figure 5H** shows the outflow end closed, and **Figure 5I** shows the inflow

end closed. In some embodiments, the inlet end of the valve leaflets **231** can lie flat along the inner frame **220** when the valve is open. Thus, if the inner frame **220** is in a cylindrical frame, the valve leaflets **231** may not be parallel to the walls of the frame because the leaflets **231** naturally are inclined outwards in the opened position, causing compression or distortion of the leaflets. However, using the inner frame **220** shapes described above (an hourglass, tapered, concave or similar shape) where the valve leaflet **231** inlets are, then the valve leaflets **231** more naturally rest closer to the frame **220** itself when the valve is open as shown in **Figures 5F and 5G**, and do not compress or deform. Thus, the leaflets **231** follow the shape of the hourglass frame **220** when opening, providing for optimal washout. In some embodiments, the leaflets **231** can be attached generally at the intermediate region **228**, so when the leaflets **231** are opened they can extend further radially outwards in the larger diameter regions.

[0137] Further, the hourglass inner frame **220** can allow for the leaflets of the valve body to conform with and/or contact the inner surface of the hourglass inner frame **220**. Thus, the hourglass design can improve washout by reducing any gap between the seamline of the leaflets and the wall of the inner frame **220** on which the leaflets are attached to. Specifically, **Figure 5J** shows the leaflets **262** in the closed position and **Figure 5K** shows the leaflets **262** in the fully open position generally conforming to the inner frame **220**. Thus, as shown, in some embodiments the only portions of each of the leaflets **262** that do not contact the frame **220** when opened are the free edges of the leaflets **262** at the outlet end. Accordingly, almost the entire “belly” or “surface” of each of the leaflets **262** (e.g., the surface of the leaflets **262** which face the interior surface of the inner frame **220**) conform to and/or contact the inner frame **220** of the hourglass shape (e.g., reducing any gap between the leaflets **262** and the interior surface of the inner frame **220**). In some embodiments, over 50%, over 75%, over 90%, over 95%, or over 99% of the belly of the leaflets **262** can conform to and contact the interior surface of the inner frame **220** when in the fully open position. In some embodiments, the free edges of the outlet end of the leaflets **262** do not contact the inner frame **220**. In some embodiments, only the free edges of the outlet end of the leaflets **262** do not contact the inner frame **220**. In some embodiments, the free edges of

the outlet end of the leaflets **262** are spaced away from the interior surface of the inner frame **220**.

[0138] This configuration can be advantageous as free edges contacting the frame can create major durability issues, as constant opening and closing can wear on the edges and damage/destroy them. Thus, advantageously the hourglass inner frame **220** is shaped to achieve optimal contact between the leaflet surface and the frame surface when the leaflets **262** are fully opened while avoiding contact by the free edges to reduce overall damage to the leaflets during motion. This can improve washout and reduce thrombogenicity, while also providing a more durable leaflet.

[0139] While the hourglass and tapering shape is described above in conjunction with the inner frame **220**, similar dimensions/shapes can be used with respect to the outer frame **140** or a single frame prosthesis. Further, this can be applied to any type of valve, such as a replacement mitral valve or a replacement aortic valve.

[0140] **Figure 31** illustrates an example alternate configuration of the hourglass shape discussed above for the inner frame **220**, and can include any or all of the features discussed with respect to frames **120/220** shown in **Figures 2** and **5A**. Instead of the inner frame **220'** being an hourglass shape as discussed above with respect to inner frame **220**, the inner frame **220'** can have a non-hourglass cylindrical shape such as shown in **Figure 2** between its upper region **226'**, intermediate region **228'**, and lower region **230'**, as shown in **Figure 31**. For example, the inner frame **220'** can have a substantially constant cross-sectional dimension, e.g., generally circular, between its upper region **226'**, intermediate region **228'**, and lower region **230'**. An additional secondary inner frame **502** can then be attached (permanently or removably) on an inner surface of the inner frame **220'**. The secondary inner frame **502** can have a generally circular cross section.

[0141] The secondary inner frame **502** can be shaped to form an hourglass within the lumen of the inner frame **220'**. For example, an intermediate region **288'** can have a smaller radial diameter than the upper region **226'** and the lower region **230'**. In some embodiments, the upper region **226'** and the lower region **230'** can have approximately the same dimensions. In other embodiments, the dimensions may be different. In some embodiments, the transition between different diameters can be smooth, such as with a curve,

or can be angular with discrete corners. The secondary inner frame **502** can have a concave shape.

[0142] As shown in **Figure 31**, the secondary inner frame **502** can attach generally at proximal (e.g., in the upper region **226'**) and distal (e.g., in the lower region **230'**) ends of the secondary inner frame **502**, and a central portion of the secondary inner frame **502** can be located radially inwards from the ends and from the inner surface of the inner frame **220'**.

[0143] In some embodiments, a proximal portion of the secondary inner frame **502** can be attached to the inner frame **220'** proximal to where the tabs **104** begin. In some embodiments, a proximal portion of the secondary inner frame **502** can be attached to the inner frame **220'** distal to where the tabs **104** begin. In some embodiments, a proximal portion of the secondary inner frame **502** can be attached to the inner frame **220'** where the tabs **104** begin.

[0144] In some embodiments, a distal portion of the secondary inner frame **502** can be attached to the inner frame **220'** proximal to where the inner frame anchoring feature **124** begins bending radially outwards. In some embodiments, a distal portion of the secondary inner frame **502** can be attached to the inner frame **220'** distal to where the inner frame anchoring feature **124** begins bending radially outwards. In some embodiments, a distal portion of the secondary inner frame **502** can be attached to the inner frame **220'** where the inner frame anchoring feature **124** begins bending radially outwards.

[0145] The secondary inner frame **502** can be attached to the inner frame **220'** by, for example, sutures, adhesives, frictional forces, mechanical attachment, or the two frames can be integrally formed together.

[0146] The secondary inner frame **502** can be an "ultra-thin walled" inner frame, such as between 200-400 microns of thickness, though the particular size is not limiting. For example, the secondary inner frame **502** may be formed of a plurality of longitudinal strips (e.g., ribs), for example metallic, composite, or polymer strips. The strips could bow inwardly as the inner frame **220'** foreshortens upon radial expansion. In some embodiments, the strips could always be bowed inwardly. In some embodiments, the strips could be used in combination with a fabric or polymer. Thus, the secondary inner frame **502** could generally

be a tube of fabric with a plurality of ribs on the outside of the fabric that would push the fabric inwardly to form the hourglass shape. Alternatively, a thin braided mesh which can bow inwardly, such as during foreshortening, could be used in conjunction with a fabric as discussed above.

[0147] In some embodiments, a cloth or other fabric can be used to form the hourglass shape. For example, the cloth could act as a pocket that would fill with blood and harden over time into the particular hourglass shape. Alternatively, a balloon could be used to form the hourglass shape where the balloon could be filled with saline or other biocompatible fluid.

[0148] In some embodiments, a swellable material could be used to form the secondary inner frame **502**. The swellable material could absorb water, or other fluid, from blood and swell into the desired shape.

[0149] The secondary inner frame **502** can be advantageous as it leverages the highly stable cylindrical inner frame design of inner frame **220'** while still providing the anti-thrombosis benefit of the hourglass secondary inner frame **502**.

Outer Frame

[0150] With reference next to the outer frame **140** which is illustrated alone in **Figures 6A-6D**. The outer frame **140** can be incorporated into a prosthesis with any of the variations of the described inner frames. The outer frame **140** can provide a structure to which various components of the prosthesis **100** can be attached. The outer frame **140** can be attached to the inner frame **120** using any of the fasteners and/or techniques described herein including, but not limited to, mechanical fasteners, such as sutures, staples, fabric screws, rivets, interfacing members (e.g., tabs and slots which can be on the inner frame **120** and the outer frame **140**), and any other type of mechanical fastener as desired, chemical fasteners such as adhesives and any other type of chemical fastener as desired, fastening techniques such as welding, soldering, sintering, and any other type of fastening technique as desired, and/or a combination of such fasteners and techniques. In some embodiments, the inner frame **120** and the outer frame **140** can be indirectly attached via an intermediate component,

such as the skirt **180**. In some embodiments, sutures are used to attached eyelet **143** of the outer frame **140** with eyelet **106** of the inner frame **120**.

[0151] The outer frame **140** can be attached to the inner frame **120** at one or more attachment points. The outer frame **140** can be tautly attached to the inner frame **120** such that little to no relative movement between the outer frame **140** and the inner frame **120** occurs at the one or more attachment points. In other embodiments, the outer frame **140** can be loosely attached to the inner frame **120** such that some relative movement between the outer frame **140** and the inner frame **120** can occur at the one or more attachment points. Although the outer frame **140** is illustrated as a separate component from the inner frame **120**, it is to be understood that the frames **120**, **140** can be unitarily or monolithically formed.

[0152] As shown in the illustrated embodiment, the outer frame **140** can include an outer frame body **142**. In some embodiments, such as shown in **Figure 12**, the outer frame **140** can further include an outer frame anchoring feature **144** (if used in a mitral valve, also known as an atrial or proximal anchor). However, as shown in **Figures 6A-6D** (and **Figures 9-11**), the outer frame may not include an outer frame anchoring feature **144**.

[0153] The outer frame body **142** can have an upper region **146**, an intermediate region **148**, and a lower region **150**. In some situations, such as those in which the prosthesis **100** is positioned within a native mitral valve, the upper region **146** can be generally positioned supra-annularly, the intermediate region **148** can be generally positioned intra-annularly, and the lower region **150** can be positioned sub-annularly. However, it is to be understood that in some situations, the positioning of the outer frame **140** relative to the annulus can differ. Moreover, it is to be understood that in some embodiments, the outer frame **140** can omit one or more of the upper region **146**, the intermediate region **148**, and/or the lower region **150**.

[0154] When in an expanded configuration such as a fully expanded configuration, the outer frame body **142** can have an enlarged/bulbous shape with the intermediate region **148** and the lower region **150** being larger than the upper region **146**, or the intermediate region **148** being larger than the lower region **150** and the upper region **146**. The bulbous shape of the outer frame body **142** can advantageously allow the outer frame body **142** to engage a native valve annulus, native valve leaflets, or other body cavity, while

spacing the inlet and outlet from the heart or vessel wall. This can help reduce undesired contact between the prosthesis **100** and the heart or vessel, such as the atrial and ventricular walls of the heart. The bulbous shape can further enhance securement of the outer frame body **142** to the body cavity. For example, in some embodiments, the bulbous shape can allow the intermediate region **148** to extend further radially outward compared to an anchoring feature. In this manner, the intermediate region **148** can exert a greater radial force on tissue of the body cavity and/or can more completely conform to the tissue of the body cavity, such as the native valve annulus and/or native leaflets.

[0155] The upper region **146** of the outer frame body **142** can include a generally longitudinally-extending section **146a** and an outwardly-extending section **146b**. The longitudinally-extending section **146a** can be generally concentric with the inner frame body **122**. The outwardly-extending section **146b** can extend radially outwardly away from the longitudinal axis **102** of the prosthesis **100**. The outwardly-extending section **146b** can extend in a direction that is more perpendicular to the longitudinal axis **102** than parallel and/or in a downward direction from the longitudinally-extending section **146a**. However, it is to be understood that the outwardly-extending section **146b** can extend generally perpendicularly to the longitudinal axis **102** and/or in an upward direction from the longitudinally-extending section **146a**. Moreover, it is to be understood that the longitudinally-extending section **146a** can be omitted such that the upper region **146** extends radially outwardly at the upper end of the upper region **146**.

[0156] At the juncture between the longitudinally-extending section **146a** and the outwardly-extending section **146b**, the outer frame body **140** can include a bend **152**. The bend **152** can be about a circumferential axis such that the outwardly-extending section **146b** extends in a direction more perpendicular to the longitudinal axis of the outer frame **140** than the longitudinally-extending section **146a**. In some embodiments, the bend **152** can generally form an arc with an angle between about 20 degrees to about 90 degrees. For example, as shown in the illustrated embodiment, the arc can have an angle of about 60 degrees. In some embodiments, the bend **152** can form an arc with an angle between about 30 degrees to about 60 degrees. The radius of curvature of the arc may be constant such that the bend **152** forms a circular arc or may differ along the length of the bend **152**.

[0157] In some embodiments, the outwardly-extending section **146b** can form an angle of between about 20 degrees to about 70 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, an angle of between about 30 degrees to about 60 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, an angle of between about 40 degrees to about 50 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, an angle of about 45 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, any subrange within these ranges, or any other angle as desired. In some embodiments, the outwardly-extending section **146b** can form an angle of less than 70 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, an angle of less than 55 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, an angle of less than 40 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, an angle of less than 25 degrees with a plane orthogonal to the longitudinal axis of the prosthesis **100**, or less than any other angle as desired.

[0158] The intermediate region **148** of the outer frame body **142** can extend generally downwardly from the outwardly-extending section **146b** of the upper region **146**. As shown, the intermediate region **148** can have a generally constant diameter from an upper end of the intermediate region **148** to a lower end of the intermediate region **148** such that the intermediate region **148** forms a generally cylindrical shape. However, it is to be understood that the diameters of the upper end, the lower end, and/or the portion therebetween can be different. For example, a diameter of the portion between the upper end and the lower end can be larger than the upper end and the lower end such that the intermediate region **148** has a generally bulbous shape. In some embodiments, the diameter of the lower end can be larger than the diameter of the upper end. In other embodiments, the diameter of the upper end can be larger than the diameter of the lower end. Moreover, although the outer frame body **142** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the outer frame body **142** can be have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0159] In some embodiments, the lower region **150** can be curved and/or inclined towards the longitudinal axis of the frame such that the lower ends of the lower region **150**

can extend in a direction that is between about 20 degrees to about 80 degrees with respect to a plane parallel to the longitudinal axis, between about 25 degrees to about 70 degrees with respect to a plane parallel to the longitudinal axis between about 30 degrees to about 60 degrees with respect to a plane parallel to the longitudinal axis, about 30 degrees with respect to a plane parallel to the longitudinal axis. The lower region **150** can be curved and/or inclined towards the longitudinal axis such that the lower ends of the lower region **150** can extend in a direction generally perpendicular to the longitudinal axis.

[0160] In some embodiments, the outer frame body **142** in an expanded configuration can have a diameter at its widest portion of between about 30mm to about 60mm, between about 35mm to about 55mm, about 40mm, any sub-range within these ranges, or any other diameter as desired. In some embodiments, the outer frame body **142** in an expanded configuration can have a diameter at its narrowest portion between about 20mm to about 40mm, any sub-range within these ranges, or any other diameter as desired. In some embodiments, the outer frame body **142** in an expanded configuration can have a diameter at a lower end of the lower region **150** between about 20mm to about 40mm, any sub-range within these ranges, or any other diameter as desired. In some embodiments, in an expanded configuration, the ratio of the diameter of the outer frame body **142** at its widest portion to the diameter of the frame body **142** at its narrowest portion can be about 3:1, about 5:2, about 2:1, about 3:2, about 4:3, any ratio within these ratios, or any other ratio as desired.

[0161] The outer frame body **142** can have an axially compact configuration relative to the radial dimension. The outer frame body **142** in an expanded configuration can have an the axial dimension between the upper and lower ends of the outer frame body **142** (i.e., the “height” of the outer frame body **142**) of between about 10mm to about 40mm, between about 18mm to about 30mm, about 20mm, any sub-range within these ranges, or any other height as desired. In some embodiments, the ratio of the diameter of the largest portion of the outer frame body **142** to the height of the outer frame body **142** when the frame is in its expanded configuration can be about 3:1, about 5:2, about 2:1, about 3:2, about 4:3, about 13:10, about 5:4, or about 1:1. Thus, in some embodiments the width at the largest portion of the outer frame body **142** can be greater than the height of the outer frame body **142**.

[0162] With continued reference to the outer frame **140** illustrated in **Figures 6A-6D**, the outer frame body **142** can include a plurality of struts with at least some of the struts forming cells **154**. Any number of configurations of struts can be used, such as rings of undulating struts shown forming ellipses, ovals, rounded polygons, and teardrops, but also chevrons, diamonds, curves, and various other shapes.

[0163] The cells **154** can have an irregular octagonal shape such as a “teardrop” shape. The cells **154** can be formed via a combination of struts. As shown in the illustrated embodiment, the upper portion of cells **154** can be formed from a set of circumferentially-expandable struts **156a** having a zig-zag or undulating shape forming a repeating “V” shape. The circumferentially-expandable struts **156a** can be inclined or curved radially outwardly away from the longitudinal axis of the prosthesis **100** such that an upper portion of the struts **156a** are positioned closer to the longitudinal axis of the prosthesis **100** than the lower portion of the struts **156a**. The bottom portion of cells **154** can be formed from a set of struts **156b** extending downwardly from a central or generally central location of each of the “V” shapes. The struts **156b** can extend along with a plane parallel to and/or extending through the longitudinal axis of the prosthesis **100**.

[0164] While the struts **156** are generally described and illustrated as being straight segments, it is to be understood that some or all of the struts **156** may not form entirely straight segments. For example, the struts **156** can include some curvature such that the upper and/or lower apices are curved.

[0165] The geometry of cells **154** can allow the cells **154** to foreshorten as the outer frame **140** is expanded. As such, one or more of cells **154** can allow the outer frame **140** to foreshorten as the outer frame **140** is expanded. Foreshortening of the outer frame **140** can be used to secure the prosthesis to intraluminal tissue in a body cavity such as tissue at or adjacent a native valve including, but not limited to, a native valve annulus and/or leaflets. For example, expansion of the outer frame **140** can allow the outer frame **140** to exert a radially outward force against the tissue at or adjacent the native valve, such as the native valve annulus and/or leaflets.

[0166] **Figures 7A-7B** illustrate a flat pattern of the outer frame **140** in the compressed (**Figure 7A**) and expanded (**Figure 7B**) position. As shown, struts **156b** are

generally held circumferentially between struts **156a** in both the compressed and expanded position. Further, in some embodiments, the struts **156a/156b** can be asymmetric, thus making some struts compressible/expandably weaker than other struts. In particular, struts **156b** can have a different width/thickness than struts **156a**. While symmetric cells can have uneven expansion and crimp, the asymmetric cells disclosed herein can have even expansion and crimping. Further, having the different width/thickness can promote stability of the valve. The larger struts can be what the delivery system hold onto, so these can be stronger so when the delivery system crimps the prosthesis 100, it has more leverage over the thinner struts. However, in some embodiments struts **156a/156b** are the same thickness/width (e.g., are symmetric).

[0167] In some embodiments, struts **156b** can be 100%, 95%, 90%, 80%, 70%, 60%, 50%, 40%, or 30% the thickness/width of struts **156a**. In some embodiments, struts **156b** can be less than 100%, 95%, 90%, 80%, 70%, 60%, 50%, 40%, or 30% the thickness/width of struts **156a**. In some embodiments, struts **156b** can be greater than 95%, 90%, 80%, 70%, 60%, 50%, 40%, or 30% the thickness/width of struts **156a**.

[0168] **Figures 7C-7D** illustrates another embodiment of a flat pattern of an outer frame **140**, and can include any or all of the features discussed above with respect to **Figures 7A-7B**. Features disclosed with respect to **Figures 7C-7D** can be used in conjunction with, or instead of any of the outer frame features discussed herein. Advantageously, the outer frame **140** can include a notch **151** that partially extends into the strut **156a'** at the connection between the struts **156a'/156b'**. The notch can be rounded, as shown in **Figure 7D**, or may be triangular, squared, or another cut pattern and the particular shape of the notch is not limiting. The notch **151** can save approximately 0.25mm of material per strut, allowing for a total reduction of 4.55mm in circumference as compared to non-notched configurations. Further, as the peak force is generally at the connection of the struts **156a'/156b'**, and the design can reduce the overall straight on the outer frame **140**.

[0169] Additionally, the outer frame **140** can include a tab **145** extending proximally away from the eyelet **143**, such as also shown in the following **Figures 8A-8B**. This can allow for better attachment between the outer frame and the inner frame, for example by allowing for a second aperture per strut and more area for sutures to attach, and

can provide for an alternative attachment mechanism. Thus, the tab **145** can be, for example, a mushroom tab as disclosed herein with respect to the inner frame **120**, and may allow for attachment into the delivery system.

[0170] **Figures 8A-8B** illustrate flat patterns of alternative configurations of the outer frame **140**, and can include any or all of the features disclosed above with respect to **Figures 7A-7D**. Notably, **Figure 8A** illustrates an outer frame **140** having outer frame anchoring feature **144**, an expanded version of which is shown in **Figure 12**. In addition, both **Figures 8A and 8B** include tabs **145** extending upwards.

[0171] In embodiments including the outer frame anchoring feature **144**, such as shown in **Figure 12**, the outer frame anchoring feature **144** can extend outwardly relative to the longitudinal axis **102** of the prosthesis **100**. The outer frame anchoring feature **144** can extend at or proximate the juncture between the upper region **146** and the intermediate region **148** of the outer frame body **142**. The outer frame anchoring feature **144** can extend in a direction that is more perpendicular to the longitudinal axis **102** than parallel and/or can extend in a downward direction from the longitudinally-extending section **146a**. The outer frame anchoring feature **144** can extend in a direction generally aligned with the outwardly-extending section **146b** of the upper region **146**. However, it is to be understood that the outer frame anchoring feature **144** can extend generally perpendicularly to the longitudinal axis **102** and/or in an upward direction.

[0172] In some embodiments, the outer frame anchoring feature **144** can extend in a direction that is more perpendicular to the longitudinal axis of the prosthesis **100** than parallel. As shown, the outer frame anchoring feature **144** can extend in a downward direction generally parallel to the outwardly-extending section **146b**. In some embodiments, the outer frame anchoring feature **144** can extend generally perpendicularly to the longitudinal axis **102** and/or in an upward direction.

[0173] As shown in the illustrated embodiment, the outer frame **140** can include tabs **118** extending from a portion of the outer frame **140** such as an upper end of the outer frame **140**. The tabs **118** can include an eyelet **143**. The tab **118** can be advantageously used to couple the outer frame **140** to an inner frame **120** of the prosthesis. For example, a suture can be passed through the eyelet **143** for coupling to an inner frame **120**. In some

embodiments, the tabs **118** can be used to couple to other components of a prosthesis in which the outer frame **140** is used such as, but not limited to, a valve body and/or a skirt.

[0174] In some embodiments, the tab **118** can be advantageously used to couple the outer frame **140** with multiple types of delivery systems. For example, the shape of the tab **118** can be used to secure the outer frame **140** to a “slot” based delivery system. The eyelets **120** can be used to secure the outer frame **140** to a “tether” based delivery system such as those which utilize sutures, wires, or fingers to control delivery of the outer frame **140** and the prosthesis. This can advantageously facilitate recapture and repositioning of the outer frame **140** and the prosthesis in situ. In some embodiments, the outer frame **140** and prosthesis can be used with the delivery systems described herein, including but not limited to, those described in U.S. Patent Nos. 8,414,644 and 8,652,203 and U.S. Publication Nos. 2015/0238315, the entireties of each of which are incorporated by reference herein. In some embodiments, a tab can be positioned at an end of a strut similar to locking tabs **232**.

[0175] While the below discusses anchoring features **124**, **144**, it will be understood that the prosthesis **100** may not include feature **144**. One or both anchoring features **124**, **144** (if used) can contact or engage a native valve annulus, such as the native mitral valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. In some embodiments, one or both anchoring features **124**, **144** (if used) do not contact or engage, or only partially contact or engage, a native valve annulus, such as the native mitral valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. However, it is to be understood that in some embodiments, when the prosthesis **100** is used for a replacement mitral valve prosthesis, during diastole and/or systole, both the inner frame anchoring feature **124** and the outer frame anchoring feature **144** (if used) can be sized to contact or engage the native mitral valve annulus.

[0176] The anchoring features **124**, **144** (if used) and anchor tips **124a**, **144a** (if used) are preferably located along the prosthesis **100** with at least part of the foreshortening portion positioned between the anchoring features **124**, **144** (if used) so that a portion of the

anchoring features **124**, **144** (if used) will move closer together with expansion of the prosthesis **100**. This can allow the anchoring features **124**, **144** (if used) to close in on opposite sides of the native mitral annulus to thereby secure the prosthesis at the mitral valve. In some embodiments, the anchoring features **124**, **144** (if used) can be positioned such that the anchoring features **124**, **144** (if used) do not contact opposing portions of the native mitral annulus at the same time. For example, when the prosthesis **100** is used for a replacement mitral valve prosthesis, during at least systole, in some embodiments the inner frame anchoring feature **124** is sized to contact or engage the native mitral valve annulus whereas the outer frame anchoring feature **144** (if used) is sized to be spaced from the native mitral valve annulus. This can be beneficial when outer frame anchoring feature **144** (if used) is used to provide stabilization and help align the prosthesis. In some embodiments, the anchoring features **124**, **144** (if used) can be positioned such that the anchoring features **124**, **144** (if used) grasp opposite side of the native mitral annulus.

[0177] While the anchoring features **124**, **144** (if used) have been illustrated as extending from the lower end of the lower region **130** of the inner frame body **122** and at a junction between the upper region **146** and the intermediate region **148** of the outer frame body **142** respectively, it is to be understood that the anchoring features **124**, **144** (if used) can be positioned along any other portion of the prosthesis **100** as desired. Moreover, while two anchoring features **124**, **144** (if used) have been included in the illustrated embodiment, it is to be understood that a greater number or lesser number of sets of anchoring features can be utilized.

[0178] Components of the outer frame **140**, such as the outer frame body **142** can be used to attach or secure the prosthesis **100** to a native valve, such as a native mitral valve. For example, the intermediate region **148** of the outer frame body **142** and/or the outer anchoring feature **144** can be positioned to contact or engage a native valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. In situations where the outer frame body **142** is positioned within a native mitral valve, the outer frame body **142** can beneficially eliminate, inhibit, or limit downwardly directed forces such as those which are applied on the prosthesis **100** during diastole and/or

upwardly directed forces such as those which are applied on the prosthesis **100** during systole. As another example, the outer frame body **142** can be sized and positioned relative to the inner frame anchoring feature **124** such that tissue of the body cavity positioned between the outer frame body **142** and the inner frame anchoring feature **124**, such as native valve leaflets and/or a native valve annulus, can be engaged or pinched to further secure the prosthesis **100** to the tissue. For example, the lower region **150** of the outer frame body **142** can be positioned at or proximate a tip or end of the inner frame anchoring feature **124**. As shown, the lower region **150** of the outer frame body **142** is positioned such that at least a portion is positioned radially inward of and below the inner frame anchoring feature **124**. In some embodiments, a portion of the outer frame **140**, such as the lower region **150**, can be attached to the inner frame body **122** via one or more tethers or sutures to limit the outward extension of the outer frame **140** relative to the inner frame body **122**. This can beneficially maintain a portion of the outer frame **140** between the inner frame body **122** and the inner frame anchoring feature **124**. Although the inner frame anchoring feature **124** is shown extending from the inner frame body **122**, it is to be understood that such an anchoring feature can extend from the outer frame body **140**.

[0179] Use of an inner frame **120** and an outer frame **140** can be beneficial for the design of the prosthesis in that the inner frame **120** can be designed to suit the structure of the valve body **160** and the outer frame **140** can be designed to suit the anatomy of the body cavity in which the prosthesis **100** is to be used. For example, the valve body **160** (shown in **Figure 10**) can be cylindrical and have a smaller diameter than the body cavity. In such an embodiment, the inner frame **120** can advantageously have a smaller shape and/or size to support the valve body **160** while the outer frame **140** can have a larger shape and/or size to secure the prosthesis **100** to the body cavity. Moreover, in embodiments in which the outer frame **140** is larger than the inner frame **120**, the shape of the outer frame **140** can beneficially enhance hemodynamic performance. For example, the shape of the outer frame **140** with a larger, generally cylindrical intermediate region **148** can allow for significant washout on an underside of the valve body **160**. This washout can beneficially reduce the risk of thrombosis or clot formation under and around the valve body **160**.

[0180] The outer frame **140** can be formed from many different materials including, but not limited to, a shape-memory metal such as Nitinol. The outer frame **140** can be formed from a plurality of struts forming open cells. In some embodiments, the outer frame **140** can have a more flexible construction as compared to other components of the prosthesis **100** such as, but not limited to, the inner frame **120**. This can be achieved, for example, by the dimensions of the struts and by the configuration of the struts. For example, fewer struts, thinner struts, and/or a different material for the struts can be used. The more flexible construction can allow the outer frame **140** to better conform to the anatomy of the body cavity, such a native valve annulus and/or native leaflets. This can be beneficial for anchoring against the body cavity and/or forming a seal against the body cavity. However, it is to be understood that in some embodiments the outer frame **140** can have a construction which is about as rigid as, or more rigid than, other components of the prosthesis **100**, such as the inner frame **120**.

[0181] The outer frame **140**, and any other frame described herein, may include features and concepts similar to those disclosed in U.S. Patent Nos. 8,403,983, 8,414,644, and 8,652,203, U.S. Publication Nos. 2011/0313515, 2014/0277390, 2014/0277427, 2014/0277422, 2018/0021129, 2018/0055629, and 2015/0328000, the entireties of each of which have been incorporated by reference. Moreover, although the outer frame **140** has been described as including an outer frame body **142** and an outer frame anchoring feature **144**, it is to be understood that the outer frame **140** need not include all components. For example, in some embodiments, the outer frame **140** can include the outer frame body **142** while omitting the outer frame anchoring feature **144**. Moreover, although the outer frame body **142** and the outer frame anchoring feature **144** have been illustrated as being unitarily or monolithically formed, it is to be understood that in some embodiments the outer frame body **142** and the outer frame anchoring feature **144** can be formed separately. In such embodiments, the separate components can be attached using any of the fasteners and techniques described herein. For example, the outer frame anchoring feature **144** can be formed separately from the outer frame body **142** and can be attached to the outer frame body **142**.

Skirt

[0182] **Figures 9-11** illustrate the prosthesis **100** with the skirt **180**. The skirt **180** can be attached to the inner frame **120** and/or outer frame **140** (or any of the alternate frames disclosed herein). As shown, the skirt **180** can be positioned around and secured to a portion of, or the entirety of, the exterior of the inner frame **120** and/or outer frame **140**, such as in between the two frames **120/140**. The skirt **180** can also be secured to a portion of the valve body **160**. The skirt **180** can follow the contours of the outer frame **140**, such as the contours of the upper region **146**, the intermediate region **148**, and/or the lower region **150**. In some embodiments, the skirt **180** can be used to attach the outer frame **140** to the inner frame **120**. Although not shown, it is to be understood that the skirt **180** can be positioned around and secured to a portion of, or the entirety of, an interior of the inner frame **120** and/or the outer frame **140**. Moreover, it is to be understood that while the skirt **180** can follow the contours of portions of the inner frame **120** and the outer frame **140**, at least a portion of the skirt **180** can be spaced apart from at least a portion of both the inner frame **120** and the outer frame **140**. In some embodiments, the skirt **180** can be spaced apart from the upper region **146** of the outer frame **140**. For example, the skirt **180** can be positioned below the upper region **146**. In such an embodiment, the spaced-apart portion of the skirt **180** can be loose such that the skirt **180** is movable relative to the upper region **146** or can be taut such that the skirt **180** is generally fixed in position. The skirt **180**

[0183] The skirt **180** can be annular and can extend entirely circumferentially around the inner frame **120** and/or outer frame **140**. The skirt **180** can prevent or inhibit backflow of fluids, such as blood, around the prosthesis **100**. For example, with the skirt **180** positioned annularly around an exterior of the inner frame **120** and/or outer frame **140**, the skirt **180** can create an axial barrier to fluid flow exterior to the inner frame **120** and/or outer frame **140** when deployed within a body cavity such as a native valve annulus. The skirt **180** can encourage tissue in-growth between the skirt **180** and the natural tissue of the body cavity. This may further help to prevent leakage of blood flow around the prosthesis **100** and can provide further securement of the prosthesis **100** to the body cavity. In some embodiments, the skirt **180** can be tautly attached to the inner frame **120** and/or outer frame **140** such that the skirt **180** is generally not movable relative to the inner frame **120** and/or outer frame **140**. In some embodiments, the skirt **180** can be loosely attached to the inner

frame **120** and/or outer frame **140** such that the skirt **180** is movable relative to the inner frame **120** and/or outer frame **140**.

[0184] In some embodiments, the skirt **180** can be formed from a material such as knit polyester (e.g., polyethylene terephthalate (PET), polyvalerolactone (PVL)) or any other biocompatible material such as those which are wholly or substantially fluid impermeable, flexible, stretchable, deformable, and/or resilient. The skirt **180** and/or the liner may be made from the same or similar materials. As shown in the illustrated embodiment, the skirt **180** can be formed as separate components. The components can be attached together using any of the fasteners and/or techniques described herein including, but not limited to, mechanical fasteners, such as sutures, staples, screws, rivets, interfacing members (e.g., tabs and slots), and any other type of mechanical fastener as desired, chemical fasteners such as adhesives and any other type of chemical fastener as desired, fastening techniques such as welding, soldering, sintering, and any other type of fastening technique as desired, and/or a combination of such fasteners and techniques.

[0185] In some embodiments, the skirt **180** can be attached to the inner frame **120**, such as at one of the struts. For example, the skirt **180** can attach to longitudinally extending strut **138** or the circumferentially extending struts **136a/13b**. The skirt **180** can be attached through sutures, adhesives, tying, etc. and the attachment is not limiting. In some embodiments, the skirt **180** can also be attached to the outer frame **140**.

[0186] As the skirt **180** is attached to the inner frame **120**, when the prosthesis **100** first begins to crimp, such as for retraction/retrieval, the skirt **180** is pulled inwardly with the inner frame **180**. Thus, the skirt **180** can be tucked between the struts of the outer frame **140**. It can be advantageous to perform this automatic tucking as in some embodiments a large amount of material (such as cloth) of the outer skirt **180** is needed to seal particularly large annuluses. Accordingly, the skirt **180** can bunch up/prevent low profile crimping or require large amounts of force to fully crimp the prosthesis because of the skirt **180** “clogging” the struts and preventing closure. Thus, manual tucking can be avoided and retrieval forces can be removed. **Figures 13A-13B** illustrate the automatic tucking of the cloth into the prosthesis **100**.

[0187] As shown in **Figure 9**, the ventricular portion (e.g., the bottom, distal, or lower portion) of the skirt **180** (e.g., fabric skirt) may act as a “curtain” around the inner frame **220**. For example, the ventricular portion **182** of the outer skirt **180** is not attached to the outer frame **140** as the outer frame **140** ends above this portion of the skirt **180**. This portion **182** is also not attached to the inner frame **220** until the bottom of the skirt **180**. Thus, the portion **182** of the outer skirt **180** is circumferentially unattached, and is instead held generally in tension between an inner surface of the outer frame **140** and the an outer surface of the ventricular or distal end of the inner frame **220**. This allows the outer skirt **180** to flex or bend when radial pressure is applied to it. Thus, the outer skirt **180** has the flexibility to conform to a valve annulus, such as the mitral valve annulus, which can create an improved seal between the prosthesis **100** and the annulus. This can be especially advantageous as by having the curtain configuration and a reduced outer frame **140**, the overall profile of the device can be reduced. Further, by eliminating the lower portion of the outer frame **140** (e.g., the portion that would surround portion **182**), the outer frame **140** can compress more easily against the inner frame **220** and the overall structure can compress to a much smaller diameter as compared to a device having an outer frame extending all the way to the inner frame anchoring features **124**.

[0188] **Figures 14A-B and 15** illustrate an embodiment of a prosthesis **100** which can improve the stiffness of the inner frame anchoring features **124** using the outer skirt **180**. In particular, the skirt **180** can be added into the prosthesis **100** to increase the stiffness of the inner frame anchoring features **124**, for example by distributing force between the inner frame **120**, the outer frame **140**, and the added stiffness improving material **192** (which can be a portion of skirt **180**). Thus, the stiffness improving material **192** can be incorporated into, or can be the same, as the skirt **180** or can be its own separate material.

[0189] **Figures 14A-B** illustrate an example embodiment of the improved stiffness. As shown, the prosthesis can include the inner frame **120** having the inner frame anchoring features **124**, the outer frame **140**, and the stiffness improving material **192**. In some embodiments, the stiffness improving material **192** can be cloth, fabric, or other soft material such as discussed above with respect to skirt **180**. As shown, the stiffness improving material **192** can be attached at three different points on the prosthesis **100**. The stiffness

improving material **192** can be located between the frames **120/140** or radially outwards of both frames **120/140**.

[0190] At one point, the stiffness improving material **192** can be attached to a lower end of the outer frame **140**. This stiffness improving material **192** can be attached at the base apices of struts **156a** or at the base apices of struts **156b**. However, the stiffness improving material **192** can be attached at any particular point of the outer frame **140**. In some embodiments, the stiffness improving material **192** can be attached to outer frame anchoring feature **144** if used. The attachment can be sutures, threads, chemical adhesives, mechanical fastening, and the particular attachment is not limiting.

[0191] Next, the stiffness improving material **192** can be attached on the inner frame anchoring features **124**. For example, it can be attached approximately midway along the inner frame anchoring features **124**, such as shown in **Figures 14A-B**. However, the stiffness improving material **192** can be attached at any point along the inner frame anchoring features **124**, and the particular location is not limiting. The attachment can be generally at the midpoint of the stiffness improving material **192**, but this is not limiting. The attachment can be sutures, threads, chemical adhesives, mechanical fastening, and the particular attachment is not limiting.

[0192] Further, the second end of the stiffness improving material **192** can be attached to a portion of the inner frame **120**. For example, it can be attached at the longitudinally extending strut **138** or at the circumferentially extending struts **136b**. The stiffness improving material **192** can be attached at the first and second ends generally at the same longitudinal position. At some embodiments, the stiffness improving material **192** is attached to the inner frame **120** at a different longitudinal position than where it is attached to the outer frame **140**. In some embodiments, the stiffness improving material **192** is attached to the inner frame **120** at a lower longitudinal position (e.g., towards the inner frame anchoring features **124**) than where it is attached to the outer frame **140**. In some embodiments, the stiffness improving material **192** is attached to the inner frame **120** at a higher longitudinal position (e.g., away from the inner frame anchoring features **124**) than where it is attached to the outer frame **140**. The attachment can be sutures, threads, chemical adhesives, mechanical fastening, and the particular attachment is not limiting.

[0193] **Figure 14A** shows the prosthesis **100** in the expanded position. As shown, the stiffness improving material **192** is pulled taught, thereby applying an upward force on the stiffness improving material **192** and thus the inner frame anchoring features **124**. Once the prosthesis **100** begins compress, as shown in **Figure 14B**, the stiffness improving material **192** becomes slack, thus reducing the stiffness of the inner frame anchoring features **124** and facilitating retrieval.

[0194] In some embodiments, the stiffness improving material **192** can extend along a circumference of the prosthesis **100** such as discussed above with respect to skirt **180**. In some embodiments, the stiffness improving material **192** can extend partially around the circumference of the prosthesis **100**. In some embodiments, multiple the stiffness improving material **192** can be used. In some embodiments, the stiffness improving material **192** is attached to every inner frame anchoring features **124**. In some embodiments, the stiffness improving material **192** is attached to every other inner frame anchoring features **124**. In some embodiments, the stiffness improving material **192** is attached to every third inner frame anchoring features **124**.

[0195] Further, the use of the stiffness improving material **192** can create a “sealed void”, “clot pocket”, “cloth pocket”, or “pocket” between the inner frame **120** and the outer frame **140**. The pocket is an empty volume covered with the stiffness improving material **192** between the inner frame **120** and the outer frame **140**. This can reduce thrombosis formation on the prosthesis **100** as in an open configuration blood can flow through struts in the frames and circulate between the frames causing thrombus. In some embodiments, there can be a number of holes in the stiffness improving material **192**, and thus the stiffness improving material **192** can inflate, clot over, and permanently stay inflated.

[0196] **Figure 15** illustrates an alternate stiffness improving material **192** where the stiffness improving material **192** is one or more sutures. As shown, a single suture can extend around the circumference of the prosthesis **100**, but in some embodiments multiple discrete sutures can be used. In this embodiment, the sutures extend between outer frame anchoring features **144** and circumferentially adjacent inner frame anchoring feature **124**, thus forming a “zig-zag” pattern around the prosthesis **100**. As shown, the stiffness improving material **192** can pass through apertures at the ends of the outer frame anchoring

features **144**. The stiffness improving material **192** can either be tied in or pass through the apertures. The stiffness improving material **192** can then attach to material around the inner frame anchoring feature **124**. In some embodiments, the stiffness improving material **192** can wrap around the inner frame anchoring features **124** themselves, such as forming a loop in the suture or extending through an aperture or around a protrusion in the inner frame anchoring feature **124**. However, in some embodiments outer frame anchoring features **144** may not be used and the sutures can attach directly to the outer frame **140** such as discussed above.

[0197] Advantageously, the use of the stiffness improving material **192** of any of the above embodiments can prevent the outer frame **140** from crimping inside the inner frame **120**. This can be done by providing sufficient tension with the stiffness improving material **192** to prevent insertion of lower portions of the outer frame **140** from entering the inner frame **120**.

[0198] Although the prosthesis **100** has been described as including an inner frame **120**, an outer frame **140**, a valve body **160**, and a skirt **180**, it is to be understood that the prosthesis **100** need not include all components. For example, in some embodiments, the prosthesis **100** can include the inner frame **120**, the outer frame **140**, and the valve body **160** while omitting the skirt **180**. Moreover, although the components of the prosthesis **100** have been described and illustrated as separate components, it is to be understood that one or more components of the prosthesis **100** can be integrally or monolithically formed. For example, in some embodiments, the inner frame **120** and the outer frame **140** can be integrally or monolithically formed as a single component.

[0199] Additionally, the prosthesis **100** may only include a single frame. For example, just the inner frame **120**, just the outer frame **140**, or a combination of the two in a single frame. Thus, the concepts discussed above, such as the hourglass shape, the strut/cell shape, etc. can be incorporated into a single frame prosthesis.

[0200] Moreover, the prosthesis **100** may be applicable to a prosthesis having more than just the inner frame **120** and the outer frame **140**. Thus, the concepts discussed above, such as the hourglass shape, the strut/cell shape, etc. can be incorporated into a prosthesis having 1, 2, 3, 4, 5, or 6 frames.

[0201] **Figure 16** illustrates an embodiment of the prosthesis **100** being radially compressed.

[0202] **Figures 17A-17B** illustrate embodiments of the prosthesis **100** with some modifications which can be used in conjunction with any of the implementations disclosed herein. As shown in the figures, the outer frame **140** can have a substantial angular change (e.g., bend or shoulder) between the upper region **146** and the intermediate region **148** and the lower region **150**. In some embodiments, the bend could be 50, 60, 70, 80, 90, or 100 degrees. In some embodiments, the bend could be greater than 50, 60, 70, 80, 90, or 100 degrees. In some embodiments, the bend could be less than 50, 60, 70, 80, 90, or 100 degrees. In some embodiments, the lower region **150** may have approximately the same radial diameter than the intermediate region **148**. In some embodiments, the lower region **150** may have smaller radial diameter than the intermediate region **148**. This can, for example, allow the frame to act as a “plug” or “cork” within the mitral valve annulus. In some embodiments, the mitral valve annulus, or other structural heart features, may apply radially inward pressure on the prosthesis **100**, causing some indents, bends, or compression of the intermediate region **148** or the lower region **150**, which can allow the prosthesis **100** to achieve a tighter fit. The prosthesis **100** can have a scalloped inflow. This can help reduce atrial projection and promote flow prior to release from the delivery system. **Figure 17B** illustrates an embodiment of an inner frame anchoring feature **124**. As shown, the distal tip can be covered by a first material **121**, such as ePTFE or other plastic, while the main curve can be covered by a second material **123**. The second material **123** can be a foam or fabric. In some embodiments, the second material **123** can be a PET-covered polyurethane foam, though this is not limiting. The two materials can be attached together, such as by suturing, shrinkage, friction, or mechanical fastening, or can be separate.

[0203] **Figure 29** illustrates an alternate embodiment of a prosthesis **100** which can include any or all of the features described herein. As shown, the outer frame **140** can have a bulbous (or generally bulbous shape). For example, the outer frame **140** can have a shoulder as shown in **Figure 29**.

[0204] The different iterations of the prosthesis frame disclosed above, such as, but not limited to, the ones shown in **Figure 1**, **Figure 9**, **Figure 12**, **Figure 17A**, **Figure 21**,

Figure 29, and **Figure 30A**, can provide advantageous for the implantation procedure. For example, as discussed below, the prosthesis **100** expands from a compressed configuration to an expanded configuration during delivery. This can be done in or around the mitral annulus. When the outer frame **140**, including any of the variations of the outer frame **140** discussed above, is expanded, it can circumferentially press against tissue on the circumference of the mitral annulus. This shape can provide a form of retention to stop the prosthesis **100** from going into the left ventricle in diastole, and generally stabilize the prosthesis **100** in the mitral valve annulus. Thus, in some implementations the prosthesis **100** outer frame **140** may not fully expand, and may be minimally to partially compressed within the mitral annulus. In other implementations, the prosthesis **100** may fully expand, and be retained within the left ventricle by the inner frame anchoring features and in the left atrium by the bulbous shape, for example including the shoulders, of the outer frame **140**. In some implementations, after release of the prosthesis **100**, it can be moved towards the left ventricle by the heart where it will then “cork” in the mitral annulus.

Valve Body

[0205] With reference next to the valve body **160** illustrated in **Figure 10**, the valve body **160** can be positioned within the inner frame **120**. The valve body **160** can be a replacement heart valve which includes a plurality of valve leaflets **262**. The valve leaflets **262** can include a first edge, second edge, and tabs for attaching the valve leaflets **262** together at commissures of the valve body **160**. The tabs can be used to secure the valve leaflets **262** to the inner frame **120**. The first edge can be an arcuate edge and can be generally fixed in position relative to the frame **120**. The second edge can be a freely moving edge which can allow the valve body **160** to open and close.

[0206] The plurality of valve leaflets **262** can function in a manner similar to the native mitral valve, or to any other valves in the vascular system as desired. The plurality of valve leaflets **262** can open in a first position and then engage one another to close the valve in a second position. The plurality of valve leaflets **262** can be made to function as a one way valve such that flow in one direction opens the valve and flow in a second direction opposite the first direction closes the valve. For example, the valve body **160** can open allow to blood

to flow through the valve body **160** in a direction from an upper end to a lower end. The valve body **160** can close to inhibit blood flow through the valve body **160** in a direction from the lower end to the upper end. In situations where the prosthesis **100** is oriented such that an upper end is a proximal end and a lower end is a distal end, the valve body **160** can be positioned such that the valve body **160** can open to allow blood to flow through the valve body **160** in a proximal-to-distal direction and close to inhibit blood flow in a distal-to-proximal direction. The valve body **160** can be constructed so as to open naturally with the beating of the heart. For example, the valve body **160** can open during diastole and close during systole. The valve body **160** can replace a damaged or diseased native heart valve such as a diseased native mitral valve.

[0207] The valve body **160** can include a liner. The liner can be used to assist with fluid flow through and/or around the prosthesis **100**, such as through and around the inner frame **120** and the valve leaflets **262**. The liner can surround at least a portion of the valve leaflets **262** and be connected to one or more of the valve leaflets **262**. For example, the one or more valve leaflets **262** can be attached to the liner along the first edge of the valve leaflets **262**.

[0208] The liner can be positioned within the interior of the inner frame **120** and can form an inner wall of the prosthesis **100**. For example, the liner can be positioned such that the liner is radially inward, relative to the longitudinal axis of the prosthesis **100**, from the struts **136a-c** of the inner frame **120**. In this manner, the fluid pathway towards the valve leaflets **262** can be relatively smooth. It is also contemplated that the liner can at least be partially positioned along an exterior of the inner frame **120** and/or outer frame **140** such that at least a portion of the liner is radially outward, relative to the longitudinal axis of the prosthesis **100**, from struts of the inner frame **120** and/or outer frame **140**. The liner can be positioned along an upper or inlet side of the inner frame **120**. The liner can extend from the first edge of the valve leaflets **262** towards the upper end of the inner frame **120**. The liner can also extend below the first edge of the valve leaflet **262** towards the lower end of the inner frame **120**. The liner can also be made to move with foreshortening portions of the inner frame **120**.

[0209] In some embodiments, the liner can extend the entire length of the inner frame **120** or the inner frame body **122**. In other embodiments, it can extend along only part of the length of the inner frame body **122** as shown. In some embodiments, the ends of the valve leaflets **262** can coincide with ends of the liner. In addition, one or more of the ends of the inner frame body **122** can coincide with the ends of the liner. An end of the liner can be positioned between the upper end of the inner frame **120** and the valve leaflets **262**. The end of the liner can extend above an upper end of the inner frame body **122** and extend along a portion of the locking tabs. In some embodiments, the end of the liner can be positioned at or proximate an uppermost portion of the first or arcuate edge of the valve leaflet **262** below the upper end of the inner frame body **122**.

[0210] Other shapes and configurations can also be used for the valve body **160**. In some embodiments, the liner may extend along the length of the leaflets, but is not connected to them. In the illustrated embodiment, the liner is attached to the inner frame **120** and at least a portion of the leaflets **262**, such as the first or arcuate edge, is attached to the liner. Portions of the valve leaflets **262**, such as the portions of the first edge and/or tabs, can also be attached to the inner frame **120**. The liner and/or the valve leaflets **262** can be attached to the inner frame **120** or to each other using any of the fasteners and/or techniques described herein including, but not limited to, mechanical fasteners, such as sutures, staples, screws, rivets, interfacing members (e.g., tabs and slots), and any other type of mechanical fastener as desired, chemical fasteners such as adhesives and any other type of chemical fastener as desired, fastening techniques such as welding, soldering, sintering, and any other type of fastening technique as desired, and/or a combination of such fasteners and techniques.

[0211] The liner can be constructed in multiple different ways. The liner can be made a layer of resilient material, such as such as knit polyester (e.g., polyethylene terephthalate (PET), polyvalerolactone (PVL)) or any other biocompatible material such as those which are wholly or substantially fluid impermeable, flexible, stretchable, deformable, and/or resilient. In some embodiments, the liner can be made from a material that is more flexible than the valve leaflet material. The upper and/or lower end of the liner can be straight, curved, or have any other desired configuration. For example, as shown in the illustrated embodiment, the liner can have a straight edge forming the end. In other

embodiments, the end can be patterned to generally correspond to the undulations at one end of the inner frame **120**. The liner can be formed of one piece or multiple pieces.

[0212] In another embodiment of the liner, the end can extend past the inner frame **120** and can be wrapped around it. Thus, the liner can extend from the interior of the inner frame **120** to the exterior of the inner frame **120**. The liner can extend completely around the inner frame **120** for 1/4, 1/3, 1/2, or more of the length of inner frame **120**.

[0213] Methods of placement and delivery of the prosthesis **100** can be found in U.S. Patent Publication No. 2018/005629, which is hereby incorporated by reference in its entirety.

Additional Valve Prostheses

[0214] **Figures 18A-20** illustrate alternative embodiments of a prosthesis that can be used with the disclosed delivery systems **10** and methodology discussed herein. **Figures 18A-20** illustrates another alternate embodiment of a prosthesis, which is similar to the prosthesis described with respect to Figure 33-35 of U.S. Pat. Pub. No. 2018/0055629, except that an outer frame anchoring feature is described in this publication. The entirety of U.S. Pat. Pub. No. 2018/0055629, including the description relating to Figures 33-35 as well as all other description relating to the prosthesis, delivery system and methods, are hereby incorporated by reference. The embodiments of **Figures 18A-20** can have similar or the same features to the other prostheses discussed herein. In some embodiments, the prosthesis may be a single frame prosthesis. In some embodiments, the prosthesis may be a dual frame prosthesis. In some embodiments for use as a replacement mitral valve, the prosthesis includes distal or ventricular anchors similar to those described above (see, for example, anchoring feature **1524** described below), but does not include proximal or atrial anchors.

[0215] With reference next to **Figure 18A**, an embodiment of a prosthesis **1500** in an expanded configuration is illustrated. The prosthesis **1500** can include an inner frame **1520**, an outer frame **1540**, a valve body **1560**, and one or more skirts, such as an outer skirt **1580** and an inner skirt **1590**.

[0216] With reference first to the inner frame **1520**, the inner frame **1520** can include an inner frame body **1522** and an inner frame anchoring feature **1524**. The inner

frame body **1522** can have an upper region **1522a**, an intermediate region **1522b**, and a lower region **1522c**. As shown, the inner frame body **1522** can have a generally bulbous shape such that the diameters of the upper region **1522a** and the lower region **1522c** are less than the diameter of the intermediate region **1522b**. The diameter of the upper region **1522a** can be less than the diameter of the lower region **1522c**. This can beneficially allow the use of a smaller valve body **1560** within the inner frame **1520** while allowing the inner frame body **1522** to have a larger diameter proximate the connection between the inner frame body **1522** and the inner frame anchoring feature **1524**. This larger diameter can reduce the radial distance between the connection and the tip or end of the inner frame anchoring feature **1524**. This can beneficially enhance fatigue resistance of the inner frame anchoring feature **1524** by reducing the length of the cantilever.

[0217] While the illustrated inner frame body **1522** is bulbous, it is to be understood that the diameters of the upper region **1522a**, the intermediate region **1522b**, and/or the lower region **1522c** can be the same such that the inner frame body **1522** can have more of a constant cross-sectional dimension along one or more regions. Moreover, while the illustrated embodiment includes a lower region **1522a** having a greater diameter than the upper region **1522c**, it is to be understood that the diameters of the upper and lower regions **1522a**, **1522c** can be the same or the diameter of the upper region **1522a** can be greater than the diameter of the lower region **1522c**. Moreover, although the inner frame body **1522** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the inner frame body **1522** can have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0218] With reference next to the outer frame **1540** illustrated in **Figure 18A**, the outer frame **1540** can be attached to the inner frame **1520** using any suitable fastener and/or other technique. Although the outer frame **1540** is illustrated as a separate component from the inner frame **1520**, it is to be understood that the frames **1520**, **1540** can be unitarily or monolithically formed.

[0219] As shown in the illustrated embodiment, the outer frame **1540** can include an outer frame body **1542**. The outer frame body **1542** can have an upper region **1542a**, an

intermediate region **1542b**, and a lower region **1542c**. When in an expanded configuration such as a fully expanded configuration, the outer frame body **1542** can have an enlarged shape with the intermediate region **1542b** and the lower region **1542c** being larger than the upper region **1542a**. The enlarged shape of the outer frame body **1542** can advantageously allow the outer frame body **1542** to engage a native valve annulus, native valve leaflets, or other tissue of the body cavity, while spacing the upper end from the heart or vessel wall.

[0220] The upper region **1542a** of the outer frame body **1542** can include a first section **1546a** and a second section **1546b**. The first section **1546a** can be sized and/or shaped to generally match the size and/or shape of the inner frame **1520**. For example, the first section **1546a** can have a curvature which matches a curvature of the upper region **1522a** of the inner frame body **1522**. The second section **1546b** can extend radially outwardly away from the inner frame **1520**. As shown in the illustrated embodiment, the transition between the first section **1546a** and the second section **1546b** can incorporate a bend such that the second section **1546b** extends radially outwardly at a greater angle relative to the longitudinal axis.

[0221] The intermediate region **1542b** of the outer frame body **1542** can extend generally downwardly from the outwardly-extending section **1546b** of the upper region **1542a**. As shown, the intermediate region **1542b** can have a generally constant diameter from an upper end to a lower end such that the intermediate region **1542b** forms a generally cylindrical shape. The lower region **1542c** of the outer frame body **1542** can extend generally downwardly from the lower end of the intermediate region **1542b**. As shown, the lower region **1542c** of the outer frame body **1542** can have a generally constant diameter from an upper end to a lower end such that the lower region **1542c** forms a generally cylindrical shape. As shown, the diameters of the intermediate region **1542b** and the lower region **1542c** are generally equivalent such that the intermediate region **1542b** and the lower region **1542c** together form a generally cylindrical shape.

[0222] While the intermediate and lower regions **1542b**, **1542c** have been described as cylindrical, it is to be understood that the diameters of the upper end, the lower end, and/or the portion therebetween can be different. For example, a diameter of the portion between the upper end and the lower end can be larger than the upper end and the lower end

such that the intermediate region **1542b** and/or lower region **1542c** forms a generally bulbous shape. In some embodiments, the diameter of the lower end can be larger than the diameter of the upper end. In other embodiments, the diameter of the upper end can be larger than the diameter of the lower end. Moreover, although the outer frame body **1542** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the outer frame body **1542** can be have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0223] The outer frame **1540**, such as the outer frame body **1542** can be used to attach or secure the prosthesis **1500** to a native valve, such as a native mitral valve. For example, the intermediate region **1542b** of the outer frame body **1542** can be positioned to contact or engage a native valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. As another example, the outer frame body **1542** can be sized and positioned relative to the inner frame anchoring feature **1524** such that tissue of the body cavity positioned between the outer frame body **1542** and the inner frame anchoring feature **1524**, such as native valve leaflets and/or a native valve annulus, can be engaged or pinched to further secure the prosthesis **1500** to the tissue.

[0224] With continued reference to the prosthesis **1500** illustrated in **Figure 18A**, the valve body **1560** is attached to the inner frame **1520** within an interior of the inner frame body **1522**. The valve body **1560** functions as a one-way valve to allow blood flow in a first direction through the valve body **1560** and inhibit blood flow in a second direction through the valve body **1560**.

[0225] The valve body **1560** can include a plurality of valve leaflets **1562**, for example three leaflets **1562**, which are joined at commissures. The valve body **1560** can include one or more intermediate components **1564**. The intermediate components **1564** can be positioned between a portion of, or the entirety of, the leaflets **1562** and the inner frame **1520** such that at least a portion of the leaflets **1542** are coupled to the frame **1520** via the intermediate component **1564**. In this manner, a portion of, or the entirety of, the portion of the valve leaflets **1562** at the commissures and/or an arcuate edge of the valve leaflets **1562** are not directly coupled or attached to the inner frame **1520** and are indirectly coupled or

“float” within the inner frame **1520**. For example, a portion of, or the entirety of, the portion of the valve leaflets **1562** proximate the commissures and/or the arcuate edge of the valve leaflets **1562** can be spaced radially inward from an inner surface of the inner frame **1520**. By using one or more intermediate components **1564**, the valve leaflets **1562** can be attached to non-cylindrical frames **1520** and/or frames **1520** having a diameter larger than that of the diameter of the valve leaflets **1562**.

[0226] With reference next to the outer skirt **1580** illustrated in **Figure 18A**, the outer skirt **1580** can be attached to the inner frame **1520** and/or outer frame **1540**. As shown, the outer skirt **1580** can be positioned around and secured to a portion of, or the entirety of, the exterior of the outer frame **1540**. The skirt **1580** can also be secured to a portion of the valve body **1560** such as, but not limited to, the intermediate components **1564**. For example, the skirt **1580** can be attached to an inflow region of the intermediate components **1564**. As shown, the outer skirt **1580** can follow the contours of the outer frame **1540**; however, it is to be understood that at least a portion of the skirt **1580** can be spaced apart from at least a portion of both the inner frame **1520** and the outer frame **1540**.

[0227] With reference next to the inner skirt **1590** illustrated in **Figure 18A**, the inner skirt **1590** can be attached to the valve body **1560** and the outer skirt **1580**. As shown, a first end of the inner skirt **1590** can be coupled to the valve body **1560** along portions of the valve body **1560** which are proximate the inner frame **1520**. A second end of the inner skirt **1590** can be attached to the lower region of the outer skirt **1580**. In so doing, a smooth surface can be formed under each of the leaflets. This can beneficially enhance hemodynamics by allowing blood to more freely circulate and reducing areas of stagnation. In some embodiments, the inner skirt **1590** can beneficially reduce contact between the outer frame body **1542** and the inner frame body **1522**.

[0228] Although the prosthesis **1500** has been described as including an inner frame **1520**, an outer frame **1540**, a valve body **1560**, and skirts **1580**, **1590**, it is to be understood that the prosthesis **1500** need not include all components. For example, in some embodiments, the prosthesis **1500** can include the inner frame **1520**, the outer frame **1540**, and the valve body **1560** while omitting the skirt **1580**. Moreover, although the components of the prosthesis **1500** have been described and illustrated as separate components, it is to be

understood that one or more components of the prosthesis **1500** can be integrally or monolithically formed. For example, in some embodiments, the inner frame **1520** and the outer frame **1540** can be integrally or monolithically formed as a single component.

[0229] **Figure 18B** illustrates an alternate embodiment of **Figure 18A** with modifications to the design of the skirts (or cloth) **1580/1590**. As shown, the skirts **1580/1590** can contact both the inner frame **1520** and outer frame **1540**. The skirts **1580/1590** can start on the inside of the outer **1540**, transition to the outside of the outer frame **1540**, then attach to the bottom of the outside of the inner frame **1520**, then proceed up along the outside of the inner frame **1520**. By closing the skirts **1580/1590**, this could avoid/reduce clot formation/embolization.

[0230] With reference next to **Figures 19-20**, an embodiment of a prosthesis **1600** in an expanded configuration is illustrated. This prosthesis **1600** may be similar in construction to the prosthesis **1500** described above. The prosthesis **1600** can include an inner frame **1620**, an outer frame **1640**, a valve body **1660**, and one or more skirts, such as an outer skirt **1680** and an inner skirt **1690**.

[0231] With reference first to the outer frame **1640** illustrated in **Figures 19-20**, the outer frame **1640** can be attached to the inner frame **1620** using any known fasteners and/or techniques. Although the outer frame **1640** is illustrated as a separate component from the inner frame **1620**, it is to be understood that the frames **1620**, **1640** can be unitarily or monolithically formed.

[0232] As shown in the illustrated embodiment, the outer frame **1640** can include an outer frame body **1642**. The outer frame body **1642** can have an upper region **1642a**, an intermediate region **1642b**, and a lower region **1642c**. At least a portion of the upper region **1642a** of the outer frame body **1642** can be sized and/or shaped to generally match the size and/or shape of an upper region **1622a** of the inner frame **1620**. As shown in the illustrated embodiment, the upper region **1642a** of the outer frame body **1642** can include one or more struts which generally match the size and/or shape of struts of the inner frame **1620**. This can locally reinforce a portion of the prosthesis **1600** by effectively increasing the wall thickness of the combined struts.

[0233] When in an expanded configuration such as in a fully expanded configuration, the outer frame body **1642** can have a shape similar to that of outer frame body **1542** described above in connection with **Figure 18A**. As shown, the intermediate region **1642b** and the lower region **1642c** can have a diameter which is larger than the diameter of the upper region **1642a**. The upper region **1642a** of the outer frame body **1642** can have a decreasing diameter from a lower end to an upper end such that the upper region **1642a** is inclined or curved radially inwards towards the longitudinal axis of the prosthesis **1600**. Although the outer frame body **1642** has been described and illustrated as being cylindrical or having circular cross-sections, it is to be understood that all or a portion of the outer frame body **1642** can have a non-circular cross-section such as, but not limited to, a D-shape, an oval or an otherwise ovoid cross-sectional shape.

[0234] With continued reference to the outer frame **1600** illustrated in **Figure 19**, the outer frame body **1642** can include a plurality of struts with at least some of the struts forming cells **1646a-c**. Any number of configurations of struts can be used, such as rings of undulating struts shown forming ellipses, ovals, rounded polygons, and teardrops, but also chevrons, diamonds, curves, and various other shapes.

[0235] The upper row of cells **1646a** can have an irregular octagonal shape such as a “heart” shape. This additional space can beneficially allow the outer frame **1640** to retain a smaller profile when crimped. The cell **1646a** can be formed via a combination of struts. As shown in the illustrated embodiment, the upper portion of cells **1646a** can be formed from a set of circumferentially-expansible struts **1648a** having a zig-zag or undulating shape forming a repeating “V” shape. The struts **1648a** can extend radially outwardly from an upper end to a lower end. These struts can generally match the size and/or shape of struts of the inner frame **1620**.

[0236] The middle portion of cells **1646a** can be formed from a set of struts **1648b** extending downwardly from bottom ends of each of the “V” shapes. The struts **1648b** can extend radially outwardly from an upper end to a lower end. The portion of the cells **1646a** extending upwardly from the bottom end of struts **1648b** may be considered to be a substantially non-foreshortening portion of the outer frame **1640**.

[0237] The lower portion of cells **1646a** can be formed from a set of circumferentially-expansible struts **1648c** having a zig-zag or undulating shape forming a repeating “V” shape. As shown in the illustrated embodiment, the struts **1648c** can incorporate a curvature such that the lower end of struts **1648c** extend more parallel with the longitudinal axis than the upper end of the struts **1648c**. One or more of the upper ends or tips of the circumferentially-expansible struts **1648c** can be a “free” apex which is not connected to a strut. For example, as shown in the illustrated embodiment, every other upper end or tip of circumferentially-expansible struts **1648b** is a free apex. However, it is to be understood that other configurations can be used. For example, every upper apex along the upper end can be connected to a strut.

[0238] The middle and/or lower rows of cells **1646b-c** can have a different shape from the cells **1646a** of the first row. The middle row of cells **1646b** and the lower row of cells **1646c** can have a diamond or generally diamond shape. The diamond or generally diamond shape can be formed via a combination of struts.

[0239] The upper portion of cells **1646b** can be formed from the set of circumferentially-expansible struts **1648c** such that cells **1646b** share struts with cells **1646a**. The lower portion of cells **1646b** can be formed from a set of circumferentially-expansible struts **1648d**. As shown in the illustrated embodiment, one or more of the circumferentially-expansible struts **1648d** can extend generally in a downward direction generally parallel to the longitudinal axis of the outer frame **1640**.

[0240] The upper portion of cells **1646c** can be formed from the set of circumferentially-expansible struts **1648d** such that cells **1646c** share struts with cells **1646b**. The lower portion of cells **1646c** can be formed from a set of circumferentially-expansible struts **1648e**. Circumferentially-expansible struts **1648e** can extend generally in a downward direction.

[0241] As shown in the illustrated embodiment, there can be a row of nine cells **1646a** and a row of eighteen cells **1646b-c**. While each of the cells **1646a-c** are shown as having the same shape as other cells **1646a-c** of the same row, it is to be understood that the shapes of cells **1646a-c** within a row can differ. Moreover, it is to be understood that any number of rows of cells can be used and any number of cells may be contained in the rows.

[0242] As shown in the illustrated embodiment, the outer frame **1600** can include a set of eyelets **1650**. The upper set of eyelets **1650** can extend from an upper region **1642a** of the outer frame body **1642**. As shown, the upper set of eyelets **1650** can extend from an upper portion of cells **1646a**, such as the upper apices of cells **1646a**. The upper set of eyelets **1650** can be used to attach the outer frame **1640** to the inner frame **1620**. For example, in some embodiments, the inner frame **1620** can include one or more eyelets which correspond to the eyelets **1650**. In such embodiments, the inner frame **1620** and outer frame **1640** can be attached together via eyelets **1650** and corresponding eyelets on the inner frame **1620**. For example, the inner frame **1620** and outer frame **1640** can be sutured together through said eyelets or attached via other means, such as mechanical fasteners (e.g., screws, rivets, and the like).

[0243] As shown, the set of eyelets **1650** can include two eyelets extending in series from each “V” shaped strut. This can reduce the likelihood that the outer frame **1640** twists along an axis of the eyelet. However, it is to be understood that some “V” shaped struts may not include an eyelet. Moreover, it is to be understood that a fewer or greater number of eyelets can extend from a “V” shaped strut.

[0244] The outer frame **1640** can include a set of locking tabs **1652** extending from at or proximate an upper end of the upper region **1642a**. As shown, the locking tabs **1652** can extend upwardly from the set of eyelets **1650**. The outer frame **1640** can include twelve locking tabs **1652**, however, it is to be understood that a greater number or lesser number of locking tabs can be used. The locking tabs **1652** can include a longitudinally-extending strut **1652a**. At an upper end of the strut **1652a**, the locking tab **1652** can include an enlarged head **1652b**. As shown, the enlarged head **1652b** can have a semi-circular or semi-elliptical shape forming a “mushroom” shape with the strut **1652a**. The locking tab **1652** can include an eyelet **1652c** which can be positioned through the enlarged head **1652b**. It is to be understood that the locking tab **1652** can include an eyelet at other locations, or can include more than a single eyelet.

[0245] The locking tab **1652** can be advantageously used with multiple types of delivery systems. For example, the shape of the struts **1652a** and the enlarged head **1652b** can be used to secure the outer frame **1640** to a “slot” based delivery system, such as the

inner retention member **40** described above. The eyelets **1652c** and/or eyelets **1650** can be used to secure the outer frame **1640** to a “tether” based delivery system such as those which utilize sutures, wires, or fingers to control delivery of the outer frame **1640** and the prosthesis **1600**. This can advantageously facilitate recapture and repositioning of the outer frame **1640** and the prosthesis **1600** in situ.

[0246] The outer frame **1640**, such as the outer frame body **1642** can be used to attach or secure the prosthesis **1600** to a native valve, such as a native mitral valve. For example, the intermediate region **1642b** of the outer frame body **1642** and/or the outer anchoring feature **1644** can be positioned to contact or engage a native valve annulus, tissue beyond the native valve annulus, native leaflets, and/or other tissue at or around the implantation location during one or more phases of the cardiac cycle, such as systole and/or diastole. As another example, the outer frame body **1642** can be sized and positioned relative to the inner frame anchoring feature **1624** such that tissue of the body cavity positioned between the outer frame body **1642** and the inner frame anchoring feature **1624**, such as native valve leaflets and/or a native valve annulus, can be engaged or pinched to further secure the prosthesis **1600** to the tissue. As shown, the inner frame anchoring feature **1624** includes nine anchors; however, it is to be understood that a fewer or greater number of anchors can be used. In some embodiments, the number of individual anchors can be chosen as a multiple of the number of commissures for the valve body **1660**. For example, for a valve body **1660** have three commissures, the inner frame anchoring feature **1624** can have three individual anchors (1:1 ratio), six individual anchors (2:1 ratio), nine individual anchors (3:1 ratio), twelve individual anchors (4:1 ratio), fifteen individual anchors (5:1 ratio), or any other multiple of three. In some embodiments, the number of individual anchors does not correspond to the number of commissures of the valve body **1660**.

[0247] With continued reference to the prosthesis **1600** illustrated in **Figures 19-20**, the valve body **1660** is attached to the inner frame **1620** within an interior of the inner frame body **1622**. The valve body **1660** functions as a one-way valve to allow blood flow in a first direction through the valve body **1660** and inhibit blood flow in a second direction through the valve body **1660**.

[0248] The valve body 1660 can include a plurality of valve leaflets 1662, for example three leaflets 1662, which are joined at commissures. The valve body 1660 can include one or more intermediate components 1664. The intermediate components 1664 can be positioned between a portion of, or the entirety of, the leaflets 1662 and the inner frame 1620 such that at least a portion of the leaflets 1662 are coupled to the frame 1620 via the intermediate component 1664. In this manner, a portion of, or the entirety of, the portion of the valve leaflets 1662 at the commissures and/or an arcuate edge of the valve leaflets 1662 are not directly coupled or attached to the inner frame 1620 and are indirectly coupled or “float” within the inner frame 1620.

[0249] With reference next to the outer skirt 1680 illustrated in **Figure 19**, the outer skirt 1680 can be attached to the inner frame 1620 and/or outer frame 1640. As shown, the outer skirt 1680 can be positioned around and secured to a portion of, or the entirety of, the exterior of the outer frame 1640. The inner skirt 1690 can be attached to the valve body 1660 and the outer skirt 1680. As shown in **Figure 40**, a first end of the inner skirt 1690 can be coupled to the valve body 1660 along portions of the valve body 1660 which are proximate the inner frame 1620. A second end of the inner skirt 1690 can be attached to the lower region of the outer skirt 1680. In so doing, a smooth surface can be formed along under each of the leaflets. This can beneficially enhance hemodynamics by allowing blood to more freely circulate and reducing areas of stagnation.

[0250] Although the prosthesis 1600 has been described as including an inner frame 1620, an outer frame 1640, a valve body 1660, and skirts 1680, 1690, it is to be understood that the prosthesis 1600 need not include all components. For example, in some embodiments, the prosthesis 1600 can include the inner frame 1620, the outer frame 1640, and the valve body 1660 while omitting the skirt 1680. Moreover, although the components of the prosthesis 1600 have been described and illustrated as separate components, it is to be understood that one or more components of the prosthesis 1600 can be integrally or monolithically formed. For example, in some embodiments, the inner frame 1620 and the outer frame 1640 can be integrally or monolithically formed as a single component.

[0251] **Figures 21** illustrates an embodiment of the frame of prosthesis 1600 which can have two different sizes. The prostheses 1600 may just be scaled for size, and

there are no substantive/functional differences between the two. Prosthesis 100 can also be made of various sizes.

[0252] **Figure 22** shows the inner frame 1520 of prosthesis 1600 and **Figure 23** shows the outer frame 1540 of prosthesis 1600.

[0253] **Figure 24** illustrates a distal end of an inner frame anchoring feature 1624 of prosthesis 1600, though the same structure can be used for any of the prostheses 100 disclosed herein. As shown, the distal tip 1625 of the inner frame anchoring feature 1624 can include two struts 1627 ending with generally L-shaped anchors 1629 that face circumferentially opposite directions. As shown, the L-shaped anchors 1629 are not circumferentially aligned so that each L-shaped anchor 1629 has a free end. For example, a first of the struts 1627 can bend radially inward as compared to a second of the struts 1627. The L-shaped anchors 1629 can be spaced 1, 2, 3, 4, 5, or 6 mm away from each other. In some embodiments, more struts 1627 and more anchors 1629 can be used. The L-shaped anchors 1629 provide for a greater area of attachment of any cushions/sutures, thereby preventing slippage or movement of the cushions.

Anchor Separator

[0254] **Figures 25A-27B** illustrate embodiments of an anchor separator that can be used with any of the above-described embodiments of prostheses.

[0255] In some loading procedures, the inner frame anchoring features disclosed herein may not load uniformly, but instead cross or spiral as they load. This non-uniform loading can be disadvantageous as it can cause non-uniform straining of the inner frame anchoring feature, which may make the prosthesis more prone to fracturing or cracking. The non-uniform loading can also cause increases in valve loading and/or deployment forces, which may cause further loads on the frame, on soft tissue, or on fabric/suturing components.

[0256] Accordingly, **Figures 25A-25B** illustrate an embodiment of an anchor separator 2500. As shown, the anchor separator 2500 can be a body 2502 having a lumen 2504 extending generally along a longitudinal centerline of the body 2502, and can include a plurality of longitudinally extending groves 2506 formed by a plurality of extensions 2508 on

an outer radial surface of the body **2502**. The body **2502** can be generally tubular with the extensions **2508** extending radially off of the tubular body **2502**.

[0257] As shown, the extensions **2508** can be generally triangular shaped having a base of the triangle being the outer radialmost position, though the particular shape is not limiting. Adjacent extensions **2508** form generally rectangular grooves **2506** or slots between them along a longitudinal length of the body **2502** configured to receive the inner frame anchoring features **1624**. In some embodiments, the extensions/grooves **2508/2506** can extend fully along a longitudinal length of the body **2502**. In some embodiments, the extensions/grooves **2508/2506** can extend 95%, 90%, 85%, 80%, or 75% of a longitudinal length of the body **2502**. In some embodiments, the extensions/grooves **2508/2506** can extend greater than 95%, 90%, 85%, 80%, or 75% of a longitudinal length of the body **2502**. In some embodiments, the extensions/grooves **2508/2506** can extend less than 95%, 90%, 85%, 80%, or 75% of a longitudinal length of the body **2502**.

[0258] In some embodiments, the body **2502** can have 3, 4, 5, 6, 7, 8, 9, 10, 11, or 12 grooves **2506**. In some embodiments, the body **2502** can have greater than 3, 4, 5, 6, 7, 8, 9, 10, 11, or 12 grooves **2506**. In some embodiments, the body can have less than 3, 4, 5, 6, 7, 8, 9, 10, 11, or 12 grooves **2506**. In some embodiments, the body **2502** can have the same amount of grooves **2506** as the prosthesis has inner frame anchoring features **1624**. In some embodiments, the body **2502** can have fewer grooves **2506** than the replacement valve has inner frame anchoring features **1624**. In some embodiments, the body **2502** can have more grooves **2506** than the replacement valve has inner frame anchoring features **1624**.

[0259] In some embodiments, such as shown in **Figures 25A-25B**, the body **2502** can be tapered radially inwards towards the proximal and distal ends of the body **2502** (e.g., generally along a longitudinal axis). Further, as shown, the extensions **2508** can similarly be radially tapered inwards on the proximal and distal ends. This can reduce or prevent the separator **2500** from catching on the deployed prostheses when the delivery system is retracted through the prosthesis.

[0260] Accordingly, the inner frame anchoring features can be releasably loaded into the grooves **2506** to prevent them from twisting, rotating, moving, or displacing out of plane. The inner frame anchoring features can be retained in the grooves **2506** by a radially

outer sheath, and when the sheath is removed the inner frame anchoring features **1624** can release from the grooves **2506**. An example prosthesis is shown in **Figure 26** with anchoring features **1624** (but similarly could be used for **124**) inserted into the separator **2500**. The inner frame anchoring features can be loaded uniformly around a circumference of the separator **2500**. **Figures 27A-27B** illustrate the separator **2500** used with a delivery system, such as delivery system **10** disclosed below.

[0261] In some embodiment, the separator **2500** can slide along a shaft, such as the nosecone shaft of the delivery system described in US Pat. App. Pub. Nos. 2017/0056169, 2016/0317301, 2017/0056171, 2019/0008640, the entirety of each of which is hereby incorporated by reference. In some embodiments, the separator **2500** can be fixed to the shaft. In some embodiments, the separator **2500** can have an axial/longitudinal degree of freedom along the shaft. In some embodiments, the separator **2500** can have a rotational degree of freedom along the shaft. Preferably, the separator **2500** can be axially fixed but can have free rotation. This can allow the separator **2500** to be adjusted as the prosthesis gets pulled inside the delivery system catheter, thereby aligning all of the inner frame anchoring features circumferentially. In some embodiments, the separator **2500** may not be attached to the delivery system.

Delivery System Suture Attachment

[0262] **Figures 28A-28B** illustrate a prosthesis **100**, including any discussed above, having a suture **2802** configured to attach to a delivery system, such as the one discussed below. For example, fingers, knobs, or shafts in the delivery system may releasably hold onto the suture **2802**. In some embodiments, the delivery system can include an additional suture for connecting to suture **2802**, such as shown in **Figure 28B**. The additional suture **2804** can wrap around and/or intertwine with suture **2802** to connect the prosthesis **100** to the delivery system.

[0263] The suture **2802** can be permanently attached to the prosthesis **100** or can be removed upon delivery. In some embodiments, the suture **2802** can be biodegradable.

[0264] As shown, the suture **2802** can generally extend around an outer circumference of the atrial end of the prosthesis **100**. In some embodiments, the suture **2802**

can extend fully or partially around the circumference. The suture **2802** can be attached to the prosthesis **100** in a number of ways. In some embodiments, the suture **2802** can pass through the eyelets **120** in the outer frame. The suture **2802** can pass through all or some of the eyelets **120**. In some embodiments, the suture **2802** can wrap or otherwise attach to the tabs **104** of the inner frame. In some embodiments, the suture **2802** can attach to both the outer frame and the inner frame. In some embodiments, the suture **2802** can be compressed between the two frames. In some embodiments, the suture **2802** can be attached, such as chemically or mechanically, to the prosthesis **100**.

Delivery System

[0265] **Figure 35** illustrates an embodiment of a delivery device, system, or assembly **10**, such as described in U.S. Pat. Pub. No. 2019/0008640, hereby incorporated by reference in its entirety. The delivery system **10** can be used to deploy a prosthesis, such as a replacement heart valve, within the body. In some embodiments, the delivery system **10** can use a dual plane deflection approach to properly delivery the prosthesis. Replacement heart valves can be delivered to a patient's heart mitral valve annulus or other heart valve location in various manners, such as by open surgery, minimally-invasive surgery, and percutaneous or transcatheter delivery through the patient's vasculature. Example transfemoral approaches may be found in U.S. Pat. Pub. No. 2015/0238315, filed February 20, 2015, the entirety of which is hereby incorporated by reference in its entirety. While the delivery system **10** is described in connection with a percutaneous delivery approach, and more specifically a transfemoral delivery approach, it should be understood that features of delivery system **10** can be applied to other delivery system, including delivery systems for a transapical delivery approach.

[0266] The delivery system **10** can be used to deploy a prosthesis, such as a replacement heart valve as described elsewhere in this specification, within the body. The delivery system **10** can receive and/or cover portions of the prosthesis such as a first end (e.g., atrial end) and second end (e.g., ventricular end) of the prosthesis **100**. For example, the delivery system **10** may be used to deliver an expandable implant or prosthesis **100**, where the prosthesis **100** includes the first end and the second end, and wherein the second end is

configured to be deployed or expanded before the first end. Discussion of the attachment of the prosthesis **100** to the delivery system **10** can be found in U.S. Publication No. 2015/0328000A1, hereby incorporated by reference in its entirety. Further details and embodiments of a replacement heart valve or prosthesis and its method of implantation are described in U.S. Publication Nos. 2015/0328000 and 2016/0317301 the entirety of each of which is hereby incorporated by reference and made a part of this specification.

[0267] The delivery system **10** can be relatively flexible. In some embodiments, the delivery system **10** is particularly suitable for delivering a replacement heart valve to a mitral valve location through a transseptal approach (e.g., between the right atrium and left atrium via a transseptal puncture).

[0268] As shown in **Figure 35**, the delivery system **10** can include a shaft assembly **12** comprising a proximal end **11** and a distal end **13**, wherein a handle **14** is coupled to the proximal end of the assembly **12**. The shaft assembly **12** can be used to hold the prosthesis for advancement of the same through the vasculature to a treatment location. The delivery system **10** can further comprise a relatively rigid live-on (or integrated) sheath **51** surrounding the shaft assembly **12** that can prevent unwanted motion of the shaft assembly **12**. The live-on sheath **51** can be attached at a proximal end of the shaft assembly **12** proximal to the handle **14**, for example at a sheath hub. The shaft assembly **12** can include an implant retention area at its distal end that can be used for this purpose. In some embodiments, the shaft assembly **12** can hold an expandable prosthesis in a compressed state at implant retention area for advancement of the prosthesis **100** within the body. The shaft assembly **12** may then be used to allow controlled expansion of the prosthesis **100** at the treatment location. In some embodiments, the shaft assembly **12** may be used to allow for sequential controlled expansion of the prosthesis **100**. In some embodiments, the prosthesis **100** may be rotated in the implant retention area.

[0269] As discussed in U.S. Pat. Pub. No. 2019/0008640, the distal end of the delivery system **10** can include one or more subassemblies such as an outer sheath assembly, a mid shaft assembly, a rail assembly, an inner shaft assembly, and a nose cone assembly. In some embodiments, the delivery system **10** may not have all of the assemblies disclosed

herein. For example, in some embodiments a full mid shaft assembly may not be incorporated into the delivery system **10**.

[0270] In particular, embodiments of the disclosed delivery system **10** can utilize a steerable rail in the rail assembly for steering the distal end of the delivery system **10**, allowing the implant to be properly located in a patient's body. The steerable rail can be, for example, a rail shaft that extends through the delivery system **10** from the handle **14** generally to the distal end. In some embodiments, the steerable rail has a distal end that ends proximal to the implant retention area. A user can manipulate the bending of the distal end of the rail, thereby bending the rail in a particular direction. In preferred embodiments, the rail has more than one bend along its length, thereby providing multiple directions of bending. As the rail is bent, it presses against the other assemblies to bend them as well, and thus the other assemblies of the delivery system **10** can be configured to steer along with the rail as a cooperating single unit, thus providing for full steerability of the distal end of the delivery system.

[0271] Once the rail is steered into a particular location in a patient's body, the prosthesis **100** can be advanced along or relative to the rail through the movement of the other sheaths/shafts relative to the rail and released into the body. For example, the rail can be bent into a desired position within the body, such as to direct the prosthesis **100** towards the native mitral valve. The other assemblies (e.g., the outer sheath assembly, the mid shaft assembly, the inner assembly, and the nose cone assembly) can passively follow the bends of the rail. Further, the other assemblies (e.g., the outer sheath assembly, the mid shaft assembly, the inner assembly, and the nose cone assembly) can be advanced together (e.g., relatively together, sequentially with one actuator, simultaneously, almost simultaneously, at the same time, closely at the same time) relative to the rail while maintaining the prosthesis **100** in the compressed position without releasing or expanding the prosthesis **100** (e.g., within the implant retention area). The other assemblies (e.g., the outer sheath assembly, the mid shaft assembly, the inner assembly, and the nose cone assembly) can be advanced distally or proximally together relative to the rail. In some embodiments, only the outer sheath assembly, mid shaft assembly, and inner assembly are advanced together over the rail. Thus, the nose cone assembly may remain in the same position. The assemblies can be

individually, sequentially, or simultaneously, translated relative to the inner assembly in order to release the implant **100** from the implant retention area.

[0272] In some embodiments, the outer sheath assembly, the mid shaft assembly, the inner shaft assembly, and the nose cone assembly translate together (e.g., relatively together, sequentially with one actuator, simultaneously, almost simultaneously, at the same time, closely at the same time). This distal translation can occur while the implant **100** remains in a compressed configuration within the implant retention area.

[0273] Starting with the outermost assembly, the delivery system **10** can include an outer sheath assembly forming a radially outer covering, or sheath, to surround an implant retention area and prevent the implant from radially expanding. Specifically, the outer sheath assembly can prevent radial expansion of the distal end of the implant from radially expanding. Moving radially inward, the mid shaft assembly can be composed of a mid shaft hypotube with its distal end attached to an outer retention member or outer retention ring for radially retaining a portion of the prosthesis in a compacted configuration, such as a proximal end of the prosthesis **100**. The mid shaft assembly can be located within a lumen of the outer sheath assembly. Moving further inwards, the rail assembly can be configured for steerability, as mentioned above and further described below. The rail assembly can be located within a lumen of the mid shaft assembly. Moving further inwards, the inner shaft assembly can be composed of an inner shaft with its distal end attached to inner retention member or inner retention ring (such as a PEEK ring) for axially retaining the prosthesis, for example the proximal end of the prosthesis. The inner shaft assembly can be located within a lumen of the rail assembly. Further, the most radially-inward assembly is the nose cone assembly which includes the nose cone shaft having its distal end connected to the nose cone. The nose cone can have a tapered tip. The nose cone assembly is preferably located within a lumen of the inner shaft assembly. The nose cone assembly can include a lumen for a guide wire to pass therethrough.

[0274] The shaft assembly **12**, and more specifically the nose cone assembly, inner assembly, rail assembly, mid shaft assembly, and outer sheath assembly, can be collectively configured to deliver a prosthesis **100** positioned within the implant retention area to a treatment location. One or more of the subassemblies can then be moved to allow

the prosthesis **100** to be released at the treatment location. For example, one or more of the subassemblies may be movable with respect to one or more of the other subassemblies. The handle **14** can include various control mechanisms that can be used to control the movement of the various subassemblies as will also be described in more detail below. In this way, the prosthesis **100** can be controllably loaded onto the delivery system **10** and then later deployed within the body. Further, the handle **14** can provide steering to the rail assembly, providing for bending/flexing/steering of the distal end of the delivery system **10**.

[0275] The inner retention member, the outer retention ring, and the outer sheath assembly can cooperate to hold the prosthesis **100** in a compacted configuration. The inner retention member can engage struts (for example **132a/132b**) at the proximal end of the prosthesis **100** in **Figure 2**. For example, slots located between radially extending teeth on the inner retention member can receive and engage the struts which may end in mushroom-shaped tabs on the proximal end of the prosthesis **100**. The mid shaft assembly can be positioned over the inner retention member so that the first end of the prosthesis **100** is trapped between the inner retention member and the outer retention ring, thereby securely attaching it to the delivery system **10** between the mid shaft assembly and the inner retention member. The outer sheath assembly can be positioned to cover the second end of the prosthesis **100**.

[0276] The outer retention member may be attached to a distal end of the mid shaft hypotube which can in turn be attached to a proximal tube at a proximal end, which in turn can be attached at a proximal end to the handle **14**. The outer retention member can provide further stability to the prosthesis **100** when in the compressed position. The outer retention member can be positioned over the inner retention member so that the proximal end of the prosthesis **100** is trapped therebetween, securely attaching it to the delivery system **10**. The outer retention member can encircle a portion of the prosthesis **100**, in particular the first end, thus preventing the prosthesis **100** from expanding. Further, the mid shaft assembly can be translated proximally with respect to the inner assembly into the outer sheath assembly, thus exposing a first end of the prosthesis **100** held within the outer retention member. In this way the outer retention member can be used to help secure a prosthesis **100** to or release it from the delivery system **10**. The outer retention member can have a cylindrical or elongate

tubular shape, and may be referred to as an outer retention ring, though the particular shape is not limiting.

[0277] The mid shaft hypotube itself can be made of, for example, high density polyethylene (HDPE), as well as other appropriate materials as described herein. The mid shaft hypotube can be formed of a longitudinally pre-compressed HDPE tube, which can provide certain benefits. For example, the pre-compressed HDPE tube can apply a force distally onto the outer retention member, thus preventing accidental, inadvertent, and/or premature release of the prosthesis 100. Specifically, the distal force by the mid shaft hypotube keeps the distal end of the outer retention member distal to the inner retention member, thus preventing the outer retention member from moving proximal to the inner retention member before it is desired by a user to release the prosthesis 100. This can remain true even when the delivery system 10 is bent/deflected at a sharp angle. Further disclosure for the outer retention member and mid shaft hypotube can be found in U.S. Pat. Pub. No. 2016/0317301, hereby incorporated by reference in its entirety.

[0278] In the compressed position, the inner frame anchoring features 124 can be located in a delivered configuration where the inner frame anchoring features 124 point generally distally. The inner frame anchoring features 124 can be restrained in this delivered configuration by the outer sheath assembly. Accordingly, when the outer sheath is withdrawn proximally, the inner frame anchoring features 124 can flip positions (e.g., bend approximately 180 degrees) to a deployed configuration (e.g., pointing generally proximally). In other embodiments, the inner frame anchoring features 124 can be held to point generally proximally in the delivered configuration and compressed against the body of the prosthesis frame.

[0279] The delivery system 10 may be provided to users with a prosthesis 100 preinstalled. In other embodiments, the prosthesis 100 can be loaded onto the delivery system shortly before use, such as by a physician or nurse.

Valve Delivery Positioning

[0280] Methods of using the delivery system 10 in connection with a replacement mitral valve will now be described. In particular, the delivery system 10 can be used in a

method for percutaneous delivery of a replacement mitral valve to treat patients with moderate to severe mitral regurgitation. The below methods are merely examples of the how the delivery system may be used. It will be understood that the delivery systems described herein can be used as part of other methods as well.

[0281] As shown in **Figure 32**, in one embodiment the delivery system **10** can be placed in the ipsilateral femoral vein **1074** and advanced toward the right atrium **1076**. A transseptal puncture using known techniques can then be performed to obtain access to the left atrium **1078**. The delivery system **10** can then be advanced in to the left atrium **1078** and then to the left ventricle **1080**. **Figure 32** shows the delivery system **10** extending from the ipsilateral femoral vein **1074** to the left atrium **1078**. In embodiments of the disclosure, a guide wire is not necessary to position the delivery system **10** in the proper position, although in other embodiments, one or more guide wires may be used.

[0282] Accordingly, it can be advantageous for a user to be able to steer the delivery system **10** through the complex areas of the heart in order to position a replacement mitral valve in line with the native mitral valve. This task can be performed with or without the use of a guide wire with the above disclosed system. The distal end of the delivery system can be advanced into the left atrium **1078**. A user can then manipulate the rail assembly to target the distal end of the delivery system **10** to the appropriate area. A user can then continue to pass the bent delivery system **10** through the transseptal puncture and into the left atrium **1078**. A user can then further manipulate the delivery system **10** to create an even greater bend in the rail assembly. Further, a user can torque the entire delivery system **10** to further manipulate and control the position of the delivery system **10**. In the fully bent configuration, a user can then place the replacement mitral valve in the proper location. This can advantageously allow delivery of a replacement valve to an in-situ implantation site, such as a native mitral valve, via a wider variety of approaches, such as a transseptal approach.

[0283] The rail assembly can be particularly advantageous for entering into the native mitral valve. As discussed above, the rail assembly can form two bends, both of which can be located in the left atrium **1078**. The bends in the rail assembly can position the prosthesis (such as any of the designs disclosed above) so that it is coaxial with the native mitral valve. Once the prosthesis is coaxial, the outer sheath assembly, mid shaft assembly,

inner assembly, and nose cone assembly can together be advanced (e.g., using a depth knob of a handle) distally relative to the rail assembly. These assemblies advance straight off of the rail assembly, thus advancing them coaxial with the native mitral valve until the prosthesis is to be released while maintain the prosthesis in the compressed configuration, as discussed below.

[0284] Reference is now made to **Figure 33** which illustrates a schematic representation of a portion of an embodiment of a replacement heart valve **100** positioned within a native mitral valve of a heart **83**. Further details regarding how the prosthesis may be positioned at the native mitral valve are described in U.S. Publication No. 2015/0328000A1, the entirety of which is hereby incorporated by reference, including but not limited to Figures 13A-15 and paragraphs [0036]-[0045]. A portion of the native mitral valve is shown schematically and represents typical anatomy, including a left atrium positioned above an annulus **1106** and a left ventricle positioned below the annulus **1106**. The left atrium and left ventricle communicate with one another through a mitral annulus **1106**. Also shown schematically in **Figure 33** is a native mitral leaflet **1108** having chordae tendineae **1110** that connect a downstream end of the mitral leaflet **1108** to the papillary muscle of the left ventricle **1080**. The portion of the prosthesis **100** disposed upstream of the annulus **1106** (toward the left atrium) can be referred to as being positioned supra-annularly. The portion generally within the annulus **1106** is referred to as positioned intra-annularly. The portion downstream of the annulus **1106** is referred to as being positioned sub-annularly (toward the left ventricle).

[0285] As shown in **Figure 33**, the replacement heart valve (e.g., prosthesis **100**) can be positioned so that the mitral annulus **1106** is located above the inner frame anchoring features **124**. In some situations, the prosthesis **100** can be positioned such that ends or tips of the inner frame anchoring features **124** contact the annulus **1106** as shown, for example, in **Figure 33**. In some situations, the prosthesis **100** can be positioned such that ends or tips of the inner frame anchoring features **124** do not contact the annulus **1106**. In some situations, the prosthesis **100** can be positioned such that the inner frame anchoring features **124** do not extend around the leaflet **1108**.

[0286] As illustrated in **Figure 33**, the replacement heart valve **70** can be positioned so that the ends or tips of the inner frame anchoring features **124** are on a ventricular side of the mitral annulus **1106**. The inner frame anchoring features **124** can be positioned such that the ends or tips of the inner frame anchoring features **124** are on a ventricular side of the native leaflets beyond a location where chordae tendineae **1110** connect to free ends of the native leaflets. The inner frame anchoring features **124** may extend between at least some of the chordae tendineae **1110** and, in some situations such as those shown in **Figure 33**, can contact or engage a ventricular side of the annulus **1106**. It is also contemplated that in some situations, the inner frame anchoring features **124** may not contact the annulus **1106**, though the inner frame anchoring features **124** may still contact the native leaflet **1108**. In some situations, the inner frame anchoring features **124** can contact tissue of the left ventricle **104** beyond the annulus **1106** and/or a ventricular side of the leaflets.

[0287] During delivery, the inner frame anchoring features **124** (along with the frame) can be moved toward the ventricular side of the annulus **1106**, such as by translating the other assemblies proximally with respect to the rail assembly, with the inner frame anchoring features **124** extending between at least some of the chordae tendineae **1110** to provide tension on the chordae tendineae **1110**. The degree of tension provided on the chordae tendineae **1110** can differ. For example, little to no tension may be present in the chordae tendineae **1110** where the leaflet **1108** is shorter than or similar in size to the inner frame anchoring features **124**. A greater degree of tension may be present in the chordae tendineae **1110** where the leaflet **1108** is longer than the inner frame anchoring features **124** and, as such, takes on a compacted form and is pulled proximally. An even greater degree of tension may be present in the chordae tendineae **1110** where the leaflets **1108** are even longer relative to the inner frame anchoring features **124**. The leaflet **1108** can be sufficiently long such that the inner frame anchoring features **124** do not contact the annulus **1106**.

[0288] As discussed above, the prosthesis **100** may not include an outer frame anchoring feature. However, some embodiments such as shown in **Figure 12** may include the outer frame anchoring feature **144**. The outer frame anchoring feature **144**, if present, can be positioned such that the ends or tips of the outer frame anchoring feature **144** are adjacent the

atrial side of the annulus **1106** and/or tissue of the left atrium beyond the annulus **1106**. In some situations, some or all of the outer frame anchoring feature **144** may only occasionally contact or engage atrial side of the annulus **1106** and/or tissue of the left atrium **1078** beyond the annulus **1106**. For example, the outer frame anchoring feature **144** may be spaced from the atrial side of the annulus **1106** and/or tissue of the left atrium beyond the annulus **1106**. The outer frame anchoring feature **144** could provide axial stability for the prosthesis **100**. It is also contemplated that some or all of the outer frame anchoring feature **144** may contact the atrial side of the annulus **1106** and/or tissue of the left atrium beyond the annulus **1106**. **Figure 34** illustrates the prosthesis **100** implanted in the heart **83**. Although the illustrated replacement heart valve includes both proximal and distal anchors, it will be appreciated that proximal and distal anchors are not required in all cases. For example, a replacement heart valve with only distal anchors may be capable of securely maintaining the replacement heart valve in the annulus. This is because the largest forces on the replacement heart valve are directed toward the left atrium during systole. As such, the distal anchors are most important for anchoring the replacement heart valve in the annulus and preventing migration.

[0289] From the foregoing description, it will be appreciated that an inventive product and approaches for implantable prostheses are disclosed. While several components, techniques and aspects have been described with a certain degree of particularity, it is manifest that many changes can be made in the specific designs, constructions and methodology herein above described without departing from the spirit and scope of this disclosure.

[0290] Certain features that are described in this disclosure in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations, one or more features from a claimed combination can, in some cases, be excised from the combination, and the combination may be claimed as any subcombination or variation of any subcombination.

[0291] Moreover, while methods may be depicted in the drawings or described in the specification in a particular order, such methods need not be performed in the particular order shown or in sequential order, and that all methods need not be performed, to achieve desirable results. Other methods that are not depicted or described can be incorporated in the example methods and processes. For example, one or more additional methods can be performed before, after, simultaneously, or between any of the described methods. Further, the methods may be rearranged or reordered in other implementations. Also, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described components and systems can generally be integrated together in a single product or packaged into multiple products. Additionally, other implementations are within the scope of this disclosure.

[0292] Conditional language, such as “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include or do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments.

[0293] Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc. may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require the presence of at least one of X, at least one of Y, and at least one of Z.

[0294] Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” “generally,” and “substantially” may refer to an amount that is within less than or equal to 10% of, within less than or equal to 5% of, within less than or equal to 1% of, within less than or equal to 0.1% of, and within less than or equal to 0.01% of the stated amount. If the stated amount is 0 (e.g., none, having no), the above recited ranges can be specific ranges,

and not within a particular % of the value. For example, within less than or equal to 10 wt./vol. % of, within less than or equal to 5 wt./vol. % of, within less than or equal to 1 wt./vol. % of, within less than or equal to 0.1 wt./vol. % of, and within less than or equal to 0.01 wt./vol. % of the stated amount.

[0295] Some embodiments have been described in connection with the accompanying drawings. The figures are drawn to scale, but such scale should not be limiting, since dimensions and proportions other than what are shown are contemplated and are within the scope of the disclosed inventions. Distances, angles, etc. are merely illustrative and do not necessarily bear an exact relationship to actual dimensions and layout of the devices illustrated. Components can be added, removed, and/or rearranged. Further, the disclosure herein of any particular feature, aspect, method, property, characteristic, quality, attribute, element, or the like in connection with various embodiments can be used in all other embodiments set forth herein. Additionally, it will be recognized that any methods described herein may be practiced using any device suitable for performing the recited steps.

[0296] While a number of embodiments and variations thereof have been described in detail, other modifications and methods of using the same will be apparent to those of skill in the art. Accordingly, it should be understood that various applications, modifications, materials, and substitutions can be made of equivalents without departing from the unique and inventive disclosure herein or the scope of the claims.

WHAT IS CLAIMED IS:

1. A mitral valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis having a proximal end and a distal end, the prosthesis comprising:

an inner frame comprising:

a body comprising:

a plurality of circumferentially extendable struts; and

a plurality of longitudinally extending struts;

wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells; and

a plurality of inner frame anchoring features extending distally from the body;

wherein the inner frame is generally hourglass shaped in the expanded position;

an outer frame connected to the inner frame and comprising:

a plurality of connected first v-shaped struts extending around a circumference of the prosthesis; and

a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts;

a valve body connected within an interior surface of the inner frame, the valve body comprising a plurality of leaflets arranged to allow flow in a first direction and prevent flow in a second direction opposite the first direction, wherein the leaflets conform to the interior surface of the inner frame when the valve body is in an open position for reducing a formation of thrombi between the plurality of leaflets and the interior surface of the inner frame; and

a fabric skirt connected to an inner surface of the outer frame and extending distally beyond a distal end of the outer frame, wherein the fabric skirt is adapted for contacting a mitral annulus and forming a seal.

2. The mitral valve prosthesis of Claim 1, wherein the plurality of separate second v-shaped struts are thinner than the plurality of connected first v-shaped struts.

3. The mitral valve prosthesis of Claim 1 or Claim 2, further comprising a stiffness improving material attached to the outer frame, the inner frame, and the plurality of inner frame anchoring features, the stiffness improving material providing tension to the inner frame anchoring features when the prosthesis is in the expanded position and not providing tension to the inner frame anchoring features when the prosthesis is in the compressed position.

4. The mitral valve prosthesis of any one of Claims 1-3, wherein the plurality of inner frame anchoring features extend radially outwardly and then proximally, wherein each of the plurality of inner frame anchoring features ends with an anchoring tip.

5. The mitral valve prosthesis of Claim 4, wherein a distal end of the outer frame is longitudinally spaced above each of the anchoring tips.

6. The mitral valve prosthesis of any one of Claims 1-5, wherein a distal end of the outer frame ends proximal to a distal end of the two or more rows of cells.

7. The mitral valve prosthesis of any one of Claims 1-6, wherein the inner frame comprises a mushroom tab at a proximal end of at least one of the plurality of longitudinally extending struts.

8. The mitral valve prosthesis of any one of Claims 1-7, wherein the inner frame and the outer frame each comprise a plurality of apertures at or near a proximal end of the inner frame and the outer frame, and wherein each of the plurality of apertures of the inner frame generally aligns with an aperture of the plurality of apertures of the outer frame.

9. The mitral valve prosthesis of any one of Claims 1-8, wherein the outer frame comprises a plurality of outer frame anchoring features extending radially outwards.

10. The mitral valve prosthesis of any one of Claims 1-9, wherein the skirt is positioned between the inner frame and the outer frame.

11. The mitral valve prosthesis of any one of Claims 1-11, further comprising a valve body positioned within an interior of the inner frame, the valve body comprising a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

12. The mitral valve prosthesis of any one of Claims 1-11, wherein the expandable replacement heart valve prosthesis is configured to act as a replacement mitral heart valve.

13. The mitral valve prosthesis of any one of Claims 1-12, wherein each of the plurality of inner frame anchoring features ends with a pair of L-shaped anchors, the pair of L-shaped anchors being radially offset from one another.

14. The mitral valve prosthesis of any one of Claims 1-13, wherein the outer frame comprises a plurality of proximally extending struts extending between connections of adjacent connected first v-shaped struts.

15. The mitral valve prosthesis of Claim 14, wherein the outer frame comprises a circumferential shoulder spaced from a proximal end and a distal end of the outer frame, the circumferential shoulder being the radially outermost portion of the outer frame.

16. The mitral valve prosthesis of Claim 15, wherein the proximally extending struts are spaced radially inwards from the circumferential shoulder, and wherein a distal end of each of the plurality of first v-shaped struts is spaced radially inwards from the circumferential shoulder.

17. The mitral valve prosthesis of any one of Claims 1-16, wherein the expandable replacement heart valve prosthesis comprises nine inner frame anchoring features.

18. A delivery assembly configured to delivery an expandable replacement heart valve prosthesis, the delivery assembly comprising:

- a steerable delivery system configured to releasably retain the expandable replacement heart valve prosthesis in a compressed position; and

- the expandable replacement heart valve prosthesis configured to expandable between the compressed position and an expanded position, the prosthesis comprising:

- an inner frame comprising a plurality of circumferentially extendable struts, a plurality of longitudinal extending struts, and a plurality of inner

frame anchoring features, wherein the inner frame is generally hourglass shaped in the expanded position; and

an outer frame connected to the inner frame and comprising a plurality of connected first v-shaped struts extending around a circumference of the prosthesis;

wherein the steerable delivery system is configured to sequentially expand portions of the prosthesis from the compressed position to the expanded position.

19. The delivery assembly of Claim 18, wherein the outer frame further comprises a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts.

20. The delivery assembly of Claim 18 or Claim 19, wherein the steerable delivery system further comprises an anchor separator comprising:

a body;

a plurality of extensions extending radially away from the body, the plurality of extensions forming a plurality of longitudinally extending grooves, each of the plurality of longitudinally extending grooves configured to receive one of the plurality of inner frame anchoring features in the compressed position; and

a lumen longitudinally extending through the body;

wherein the body and the plurality of extensions are radially inwardly tapered at a proximal end and distal end of the anchor separator.

21. An expandable replacement heart valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis comprising:

an inner frame comprising:

a plurality of circumferentially extendable struts;

a plurality of longitudinally extending struts, wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells; and

a plurality of inner frame anchoring features;

wherein the inner frame is generally hourglass shaped in the expanded position;

an outer frame connected to the inner frame and comprising:

a plurality of connected first v-shaped struts extending around a circumference of the prosthesis; and

a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts;

wherein the plurality of separate second v-shaped struts are thinner than the plurality of connected first v-shaped struts; and

a stiffness improving material attached to the outer frame, the inner frame, and the plurality of inner frame anchoring features, the stiffness improving material providing tension to the inner frame anchoring features when the prosthesis is in the expanded position and not providing tension to the inner frame anchoring features when the prosthesis is in the compressed position.

22. The prosthesis of Claim 21, wherein the stiffness improving material comprises sutures or cloth.

23. The prosthesis of any one of Claims 21-22, wherein the outer frame comprises a plurality of outer frame anchoring features.

24. The prosthesis of any one of Claims 21-23, wherein the prosthesis is configured for use as a replacement mitral valve.

25. The prosthesis of any one of Claims 21-24, further comprising a skirt positioned between the inner frame and the outer frame, the skirt configured to automatically tuck within cells in the outer frame when the prosthesis is compressed.

26. The prosthesis of any one of Claims 21-25, further comprising a valve body positioned within an interior of the inner frame, the valve body comprising a plurality of leaflets configured to allow flow in a first direction and prevent flow in a second opposite direction.

27. An expandable replacement heart valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis comprising:

an inner frame comprising:

a generally cylindrical first frame and an inwardly curved secondary frame located within the generally cylindrical first frame and attached to the generally cylindrical first frame, the inwardly curved secondary frame forming a generally hourglass shape within a longitudinal lumen of the inner frame; and

a plurality of inner frame anchoring features extending from the generally cylindrical first frame; and

an outer frame connected to the inner frame.

28. The prosthesis of Claim 27, wherein the secondary frame comprises a plurality of longitudinal struts on an outer surface of a fabric component.

29. The prosthesis of Claim 27, wherein the secondary frame comprises a balloon filled with fluid.

30. The prosthesis of Claim 27, wherein the secondary frame comprises a swellable material.

31. The prosthesis of any one of Claims 21-26, comprising the features of any one of Claims 27-30.

32. The prosthesis of any one Claims 21-31, wherein each of the plurality of inner frame anchoring features ends with a pair of L-shaped anchors, the pair of L-shaped anchors being radially offset from one another.

33. A delivery system configured to deliver a prosthesis comprising a plurality of anchors, wherein the delivery system comprises an anchor separator comprising:

a body;

a plurality of extensions extending radially away from the body, the plurality of extensions forming a plurality of longitudinally extending grooves for receiving the anchors of the prosthesis; and

a lumen longitudinally extending through the body;

wherein the body and the plurality of extensions are radially inwardly tapered at a proximal end and distal end of the anchor separator.

34. An expandable replacement heart valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis comprising:

a frame having an inlet side, a middle portion and an outlet side, wherein the frame decreases in diameter at least from the inlet side to the middle portion; and

a valve body comprising a plurality of leaflets positioned within the frame, wherein each of the valve leaflets has an inlet end positioned along the decreasing diameter portion of the frame.

35. The prosthesis of Claim 34, wherein the frame has an hourglass shape.

36. An expandable replacement heart valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis comprising:

an inner frame comprising a plurality of inner frame anchoring features extending from a lower portion of the inner frame;

an outer frame connected to the inner frame;

a stiffness improving material attached to the outer frame, the inner frame, and the plurality of inner frame anchoring features, the stiffness improving material providing tension to the inner frame anchoring features when the prosthesis is in the expanded position and not providing tension to the inner frame anchoring features when the prosthesis is in the compressed position.

37. The prosthesis of Claim 36, wherein the inner frame anchoring features comprise a plurality of anchors that extend radially outward from the inner frame and extend generally toward an upper portion of the inner frame.

38. The prosthesis of any one of Claim 36 or Claim 37, wherein the outer frame extends over the inner frame.

39. The prosthesis of any one of Claims 36-38, wherein the stiffness improving material comprises suture, fabric, or cloth material that extends from a lower portion of the outer frame, attaches to the inner frame anchoring features, and attaches to a lower portion of the inner frame.

40. An expandable replacement heart valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis comprising:

a frame comprising:

a plurality of connected first v-shaped struts extending around a circumference of the prosthesis; and

a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts;

wherein the plurality of separate second v-shaped struts are thinner than the plurality of connected first v-shaped struts.

41. A prosthesis comprising one or more features of the foregoing description.

42. A method of treating valve insufficiency comprising one or more features of the foregoing description.

43. A method of loading a prosthesis onto a delivery system comprising one or more features of the foregoing description.

44. A delivery system for delivering the prosthesis comprising one or more features of the foregoing description.

45. The mitral valve prosthesis of any one of Claims 1-17, wherein free edges of a distal end of each of the plurality of leaflets are spaced away from the inner frame.

46. The mitral valve prosthesis of any one of Claims 1-17 and 45, wherein the fabric skirt is connected to an outer surface of a distal end of the inner frame, and wherein the fabric skirt is held in tension between the outer frame and the inner frame.

47. The mitral valve prosthesis of any one of Claims 1-17 and 45-46, wherein the fabric skirt has sufficient flexibility to conform against a mitral annulus.

48. A mitral valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis having a proximal end and a distal end, the prosthesis comprising:

an inner frame comprising:

a body comprising:

a plurality of circumferentially extendable struts; and

a plurality of longitudinally extending struts;

wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells; and

a plurality of inner frame anchoring features extending distally from the body;

wherein the inner frame is generally hourglass shaped in the expanded position;

an outer frame connected to the inner frame and comprising:

a plurality of connected first v-shaped struts extending around a circumference of the prosthesis; and

a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts;

a valve body connected within an interior surface of the inner frame, the valve body comprising a plurality of leaflets arranged to allow flow in a first direction and prevent flow in a second direction opposite the first direction; and

a fabric skirt connected to an inner surface of the outer frame and an outer surface of a distal end of the inner frame under tension, wherein the fabric skirt extends distally beyond a distal end of the outer frame, and wherein the fabric skirt is adapted for conforming against a mitral annulus.

49. A mitral valve prosthesis configured to transition between a compressed position and an expanded position, the prosthesis having a proximal end and a distal end, the prosthesis comprising:

an inner frame comprising:

a body comprising:

a plurality of circumferentially extendable struts; and

a plurality of longitudinally extending struts;

wherein the plurality of circumferentially extendable struts and the plurality of longitudinally extending struts form two or more rows of cells; and

a plurality of inner frame anchoring features extending distally from the body;

wherein the inner frame is generally hourglass shaped in the expanded position;

an outer frame connected to the inner frame and comprising:

a plurality of connected first v-shaped struts extending around a circumference of the prosthesis; and

a plurality of separate second v-shaped struts, each of the separate second v-shaped struts attached within each of the connected first v-shaped struts.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F

FIG. 5G




FIG. 5H

FIG. 5I




FIG. 5J




FIG. 5K




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28A




FIG. 28B




FIG. 29




FIG. 30A




FIG. 30B




FIG. 30C




FIG. 30D




FIG. 31





FIG. 32






FIG. 34




FIG. 35

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2019/019976

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/24
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2018/021129 A1 (PETERSON MATTHEW A [US] ET AL) 25 January 2018 (2018-01-25) cited in the application	1,2,4-17
A	paragraphs [0310] - [0319], [0357], [0366]; claims; figures 120,121,127,129	3
Y	US 2016/074160 A1 (CHRISTIANSON MARK [US] ET AL) 17 March 2016 (2016-03-17) paragraphs [0074] - [0083]; figures 4-12	1,2,4-17



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

3 July 2019

Date of mailing of the international search report

10/07/2019

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Douskas, K

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2019/019976

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 18-49
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
see FURTHER INFORMATION sheet PCT/ISA/210
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box II.2

Claims Nos.: 18-49

The application contains to many independent claims directed to different inventions. It is not possible to establish a clear line for searching the application.

Claim 1 is directed to a mitral valve having
an inner
hour glass shaped frame
a plurality of inner frame anchoring features

an outer frame having first V shaped struts and

second V shaped struts the second struts connected intermediate to the first struts
a valve body having leaflets

the leaflets conform to the interior surface of the inner frame

a fabric skirt connected to an inner surface of the outer frame and extending distally beyond the distal end of the frame for contacting a mitral annulus.

Claim 18 is directed to a delivery device configured to delivery of an expandable heart replacement prosthesis

The prosthesis of
claim 18 is different than the one of claim 1.

Claim 21 is directed to
an expandable heart replacement prosthesis
an outer frame having first V
shaped struts and

second V shaped struts the second struts connected
intermediate to the first struts

the plurality of the separate second
V-shaped struts are thinner than the plurality of the first V. shaped struts

a stiffness improving material attached to the outer frame, the inner frame and the plurality of inner frame anchoring features

The
prosthesis of claim 21 is different than the one of claim 1 or claim 18.

Claim 27 is directed to an expandable heart replacement prosthesis
an

inner hour glass shaped frame
a plurality of inner frame anchoring
features

an outer frame connected to the inner frame

The prosthesis of
claim 27 is different than the one of claim 1, 18 or claim 21.

Claim 33
is directed to A delivery system configured to deliver a prosthesis
comprising

The prosthesis of claim 33 is different than the one of claim

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

1, 18, 21 or claim 27.

Claim 34 is directed to An expandable replacement heart valve prosthesis

The prosthesis of claim 34 is different than the one of claim 1, 18, 21, 27 or claim 33.

Claim 36 is directed to an expandable heart replacement prosthesis the plurality of the separate second V-shaped struts are thinner than the plurality of the first V. shaped struts

a stiffness improving material attached to the outer frame, the inner frame and the plurality of inner frame anchoring features

The prosthesis of claim 36 is different than the one of claim 1, 21, 18, 27, 33 or claim 34.

Claim 40 is directed to an expandable heart replacement prosthesis an frame having first V shaped struts and second V shaped struts the second struts connected intermediate to the first struts

The prosthesis of claim 40 is different than the one of claim 1, 18, 21, 27, 33, 34 or claim 36.

Claim 48 is directed to a mitral valve having second V shaped struts the second struts connected intermediate to the first struts

a valve body having leaflets

a fabric

skirt connected to an inner surface of the outer frame and extending distally beyond the distal end of the frame for contacting a mitral annulus

The prosthesis of claim 49 is different than the one of claim 1, 18, 21, 27, 33, 34, 36 or claim 40.

Claim 49 is directed to a mitral valve having

an inner hour glass shaped frame

a plurality of inner

frame anchoring features

an outer frame having first V shaped struts

The prosthesis of claim 49 is different than the one of claim 1, 21, 27, 33, 34, 36, 40 or claim 48.

The aforementioned independent claims appear to relate effectively to the same subject-matter and to differ from each other only with regard to the definition of the subject-matter for which protection is sought and/or in respect of the terminology used for the features of that subject-matter. The aforementioned independent claims therefore lack conciseness and as such do not meet the requirements of Article 6 PCT.

The applicant was invited to indicate which ONE of the independent 1, 18, 21, 27, 33, 34, 36, 40, 48 or claim 49 is to be searched.

The applicant did not reply to the invitation. independent claim 1 and the dependent claims 2-17 only are therefore searched

The applicant's attention is drawn to the fact that claims relating to

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

inventions in respect of which no international search report has been established need not be the subject of an international preliminary examination (Rule 66.1(e) PCT). The applicant is advised that the EPO policy when acting as an International Preliminary Examining Authority is normally not to carry out a preliminary examination on matter which has not been searched. This is the case irrespective of whether or not the claims are amended following receipt of the search report or during any Chapter II procedure. If the application proceeds into the regional phase before the EPO, the applicant is reminded that a search may be carried out during examination before the EPO (see EPO Guidelines C-IV, 7.2), should the problems which led to the Article 17(2) declaration be overcome.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2019/019976

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2018021129 A1	25-01-2018	AU 2017298481 A1	07-02-2019
		CA 3031579 A1	25-01-2018
		CN 109715112 A	03-05-2019
		EP 3487452 A1	29-05-2019
		US 2018021129 A1	25-01-2018
		WO 2018017886 A1	25-01-2018

US 2016074160 A1	17-03-2016	US 2016074160 A1	17-03-2016
		US 2017196688 A1	13-07-2017
