



- (51) International Patent Classification:
H01R 13/523 (2006.01)
- (21) International Application Number:
PCT/EP2014/059925
- (22) International Filing Date:
15 May 2014 (15.05.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13170458.7 4 June 2013 (04.06.2013) EP
- (71) Applicant: SIEMENS AKTIENGESSELLSCHAFT
[DE/DE]; Wittelsbacherplatz 2, 80333 München (DE).
- (72) Inventor: PLANT, Christopher; 5 Durham Avenue, Lancaster, Lancashire LA1 4EE (GB).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,

DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CONNECTOR PART AND CONNECTOR ASSEMBLY

FIG 1



(57) Abstract: A connector part for use underwater or in a wet or severe environment, the connector part comprising a pin, projecting axially forwardly from a support, the pin comprising an axially extending electrically conductive portion, an axially extending sleeve comprising fibre reinforced plastic around said conductive portion, a protective layer around the sleeve to prevent exposure of the sleeve to ambient conditions when the pin is exposed to ambient conditions, and an axially extending conductive and impermeable layer between the sleeve and the protective layer.

Description

CONNECTOR PART AND CONNECTOR ASSEMBLY

5

Field of the invention

The present invention relates to a connector part for use underwater or in a wet or severe environment, and to a connector assembly comprising first and second connector parts arranged to be interengaged to establish an electrical connection.

Background

15

Electrical connectors for use underwater are known, for example from United Kingdom patent application No. GB-A-2,192,316, to have first and second connector parts in which the first connector part has at least one pin projecting from a support which is inserted into a housing and fixed in place by a retainer ring. The pin has an axially extending conductive copper core surrounded by an insulating sleeve which is arranged to expose an area of the conductive core at or near the tip of the pin for making electrical contact with a contact socket in the second connector part.

The housing extends in a forward axial direction from the support, radially outwardly of the contact pin, for alignment with and to receive a housing of the second connector part during interengagement. This extended housing of the first connector part defines a pin chamber in which the pin extends.

In the de-mated condition this pin chamber is exposed to the external environment and flooded with, for example, sea water. The conductive core at the tip of the pin is then exposed to the external environment, as is the insulating sleeve and the front face of the support.

The second connector part has a seal around an opening for receiving the pin in sealed manner when the first and second parts are interengaged, or mated. In the mated condition a portion of the pin near the support remains exposed to the external environment, such as sea water.

Electrical connectors of this type are known as wet mate connectors, because they are capable of being mated when underwater.

Wet mate connectors are used in the oil and gas industry to provide electrical power to electrical submersible pumps (ESPs) or compressors. ESPs are located in subsea wells and require electrical connection through a subsea well head. The ESP has an electric motor supplied by a cable connecting the motor to a wet mate connector at the well head. The cable may be connected to the back end of a first connector part as described above. A second connector part for mating with the first connector part pin is connected at its back end to a cable which is supplied from a remote power source, for example at the surface. The environment in which the first and second connector parts are used is subject to high temperatures, for example as high as 200°C. The environment is also a high pressure one and moreover there may be significant pressure differentials between the back of the support of the first connector part from which the connector pin projects and the pin chamber where the pin projects forwardly from the support. There is a challenge to design connector parts able to handle the high temperatures, high pressures, pressure differentials, and also capable of supplying sufficient power to meet the needs of the downhole equipment.

Summary

Accordingly, there is a need for an improved connector part.

This need is met by the features of the independent claims. The dependent claims describe embodiments of the invention.

Viewed from a first aspect the invention provides a connector
5 part for use underwater or in a wet or severe environment,
the connector part comprising a pin projecting axially forwardly from a support, the pin comprising an axially extending electrically conductive portion, an axially extending sleeve comprising fibre reinforced plastic around said conductive portion, and a protective layer around the sleeve to
10 prevent exposure of the sleeve to ambient conditions when the pin is exposed to ambient conditions.

By providing a sleeve comprising fibre reinforced plastic the
15 pin has good load bearing properties. In particular, it may provide a good pressure loading performance when used underwater at depths where high pressure prevails.

The protective layer around the sleeve prevents exposure of
20 the sleeve to ambient conditions when the pin is exposed to ambient conditions. The pin may be exposed along its full projecting length when the connector part is not mated with a second connector part, and it may be exposed in the region of the support even when it is mated. Whilst the sleeve comprising fibre reinforced plastic has good load bearing properties,
25 it is generally undesirable for it to be exposed to e.g. sea water, and hence is protected by the protective layer.

30 The sleeve may comprise a fibre filled polymer. The fibre reinforcement may be glass fibre. The fibre content in the fibre reinforced plastic may be between about 20% and about 60%, preferably between about 30% and about 50%, more preferably about 40% (weight percent). In one example, the sleeve
35 comprises polyetherketoneketone (PEKK). It may be provide with a 40 per cent glass fibre content.

The protective layer may comprise a plastic or polymer. The protective layer may have no fibre reinforcement. The protective layer may comprise an engineering polymer. The protective layer may comprise a polyaryletherketone (PAEK), such as polyetheretherketone (PEEK) or polyetherketoneketone (PEKK), for example.

The protective layer may cover all of the axial length of the sleeve where it projects axially forwardly from the support. In embodiments, none of the sleeve is exposed to ambient conditions when the pin is so exposed.

The conductive portion may have an electrical contact which is exposed. The electrical contact may be provided at or adjacent to the front end of the axially extending electrically conductive portion. The electrical contact can make an electrical connection when the connector part is mated with a second connector part. Thus, in an embodiment, when the connector part is not mated and the pin is exposed to ambient conditions, the protective layer and the contact region of the conductive portion may be exposed to ambient conditions, but not the sleeve comprising fibre reinforced plastic.

The sleeve may extend forwardly of the support over only part of the length of the pin which projects axially forwardly therefrom. The mechanical properties of the sleeve are most advantageous in the region of the pin adjacent to the support, where it is beneficial to provide additional strength. The protective layer may extend at least from the support to the electrical contact of the pin. The sleeve may extend forwardly over only part of this length.

The pin may extend in the support, as well as projecting axially forwardly therefrom. The pin may comprise a shoulder disposed in the support to prevent forward movement of the pin relative to the support. This is useful for example if there is a pressure differential between the back end of the pin and the part of the pin exposed to ambient conditions,

which may tend to force the pin forwardly. The shoulder may prevent forward movement of the pin relative to the support under such a pressure differential.

5 The sleeve may comprise a load bearing portion at the shoulder. The shoulder is a place where the pin can particularly benefit from a sleeve comprising fibre reinforced plastic, in view of the relative strength of such a material compared to non-fibre reinforced polymers.

10

In the embodiments in which the pin extends in the support, sealing means may be provided around an opening in the support from which the pin projects forwardly. The sealing means may comprise one or more seal members. The or each

15 seal member may be an O-ring, for example.

The protective layer serves the purpose of protecting the sleeve from ambient conditions where the pin is exposed thereto. The protective layer need not necessarily therefore extend into the support, or it may extend only a short distance into the support. The protective layer may extend rearwardly into the support to engage with the above mentioned sealing means. Rearwardly of the sealing means, the sleeve will generally not require protection from ambient

25

Where the pin comprises a shoulder disposed in the support, and the sleeve comprises a load bearing portion at the shoulder, the protective layer may extend over the shoulder. It may act as a compressible layer at the shoulder, for example in the manner of a washer. If the protective layer extends over the shoulder, this shoulder extending portion may be thinner than the protective layer where it is provided on the pin forwardly of the support.

35

In certain embodiments a conductive impermeable layer is provided between the sleeve and the protective layer.

The conductive impermeable layer may be a coating. The coating may be deposited on the surface of the sleeve. It may be applied to the surface of the sleeve. A coating differs from a separately fabricated metal tube. The coating may be a
5 metal coating, for example metal plating or a metallic paint. The protective layer may be moulded over the sleeve. If a conductive impermeable coating is provided, then the coating is first deposited on the sleeve before the protective layer is moulded over the coated sleeve. The coating preferably
10 therefore is capable of withstanding temperatures at which the protective layer is moulded, for example between 350°C to 390°C in the case of PEAK polymer.

The conductive impermeable layer, e.g. metal coating, is im-
15 permeable to water. It may therefore protect the sleeve from long term degradation due to water. The conductive impermeable layer does not have to be corrosion resistant, because it is covered by the protective layer. The conductive impermeable layer may serve to control the electric field generated
20 by the axially extending electrically conductive portion when the connector part is in use.

The conductive impermeable layer may extend annularly round the sleeve. The conductive impermeable layer may extend axi-
25 ally.

The conductive impermeable layer may extend axially rearwardly of the protective layer. The conductive impermeable layer may have a front portion extending forwardly of the
30 support, located between the sleeve and the protective layer, and a rear portion extending in the support disposed on the protective layer and forming an outside surface of the pin.

The invention also provides a connector assembly comprising a
35 connector part as disclosed herein, and a second connector part arranged to be interengaged with the first-mentioned connector part to establish an electrical connection. The second connector part may have a seal around an opening for

receiving the pin in sealed manner when the first and second connector parts are interengaged.

In the embodiments in which a conductive impermeable layer is provided, it is advantageous if the conductive impermeable layer extends along the pin in a region which, when the first and second connector parts are interengaged, is disposed radially inwardly of the seal of the second connector part.

This can provide effective electrical field control in this region, thereby protecting the seal from electrical stresses. The front of the seal (the front being considered with respect to the second connector part) is generally exposed to ambient conditions, such as seawater, whether the connector assembly is mated or de-mated. Therefore, in the absence of any conductive impermeable layer in the pin, the front of the seal would be subject to high electrical stress. This is because ambient water is at an earth potential, causing electrical stress concentration in the seal material where the front of the seal engages with the pin. The electrical stress is concentrated where the water at earth potential meets the axially extending surface of the pin and the radially extending surface of the seal.

The use of a conductive impermeable layer, for example a metal coating, in this region can thus provide effective electrical stress control. It is possible to avoid or minimise concentration of electrical stress where the water at earth potential meets the axially extending surface of the pin and the radially extending surface of the seal. The conductive impermeable layer is provided internally of the pin, between the sleeve and the protective layer. In the case of a coating, it is relatively easy to deposit and hence advantageous compared to using a fabricated metal tube, such as a tubular mesh.

Viewed from a second aspect the invention provides a connector part for use underwater or in a wet or severe environment, the connector part comprising a pin projecting axially for-

wardly from a support, and the pin comprising an axially extending electrically conductive portion, a first axially extending insulating layer around the conductive portion, a second axially extending insulating layer around the first insulating layer, and an axially extending conductive and impermeable coating between the first and second insulating layers.

The conductive impermeable coating can protect the first insulating layer and can also control the electrical field.

The first insulating layer is able to tolerate the electrical stresses around the conductive portion of the pin under such protected conditions. The second insulating layer, radially outwardly of the conductive impermeable coating, is protected from electrical stress and can serve the purpose of protecting the layer inwardly thereof from ambient conditions. It need not be designed to withstand significant electrical stresses, in view of the conductive impermeable coating radially inwardly thereof.

In an embodiment, the conductive impermeable coating may be deposited on the surface of the first insulating layer. It may be applied to the surface of the first insulating layer. A coating differs from a separately fabricated metal tube. By using a conductive impermeable coating, it is not necessary to mould a fabricated metal tube, such as a tubular mesh, into the pin.

In an embodiment, the conductive impermeable coating may be a metal coating, for example metal plating or a metallic paint.

The conductive impermeable coating, e.g. metal coating, is impermeable to water. It may therefore protect the first insulating layer from long term degradation due to water. The conductive impermeable coating does not have to be corrosion resistant, because it is covered by the second insulating layer. The conductive impermeable coating may serve to control the electric field generated by the axially extending

electrically conductive portion when the connector part is in use.

5 The conductive impermeable coating may extend annularly round the sleeve.

The first and second insulating layers may comprise the same material as each other.

10 The first and second insulating layers may comprise different materials. They may for example comprise two different polymers. The material of the first layer may be selected for its electrical insulation properties or its mechanical strength, and the material of the second layer may be select-
15 ed for its ability to withstand exposure to an aggressive environment, for example.

The invention also provides a connector assembly comprising a connector part in accordance with the second aspect of the
20 invention, and a second connector part arranged to be interengaged with the first-mentioned connector part to establish an electrical connection. The second connector part may have a seal around an opening for receiving the pin in sealed manner when the first and second connector parts are
25 interengaged.

It is advantageous if the conductive impermeable coating extends along the pin in a region which, when the first and second connector parts are interengaged, is disposed radially
30 inwardly of the seal of the second connector part. This can provide effective electrical field control in this region, thereby protecting the seal from electrical stresses. The front of the seal (the front being considered with respect to the second connector part) is generally exposed to ambient
35 conditions, such as seawater, whether the connector assembly is mated or de-mated. Therefore, in the absence of any conductive impermeable coating in the pin, the front of the seal would be subject to high electrical stress. This is because

ambient water is at an earth potential, causing electrical stress concentration in the seal material where the front of the seal engages with the pin. The electrical stress is concentrated where the water at earth potential meets the axially extending surface of the pin and the radially extending surface of the seal.

The use of a conductive impermeable coating in this region can thus provide effective electrical stress control. It is possible to avoid or minimise concentration of electrical stress where the water at earth potential meets the axially extending surface of the pin and the radially extending surface of the seal. The conductive impermeable coating is provided internally of the pin, between the first and second insulating layers. It is relatively easy to deposit and hence advantageous compared to using a fabricated metal tube, such as a tubular mesh.

In embodiments of the first or second aspects of the invention having a metal coating, the metal coating may comprise one coating layer or a plurality of coating layers, e.g. two coating layers. Thus there may be a base layer and a top layer. The coating may comprise a base layer of copper and a top layer of nickel.

The metal coating may comprise a base layer preferably less than 20 μm thick. Such a base layer may for example be copper. The base layer may be less than 15 μm thick, or less than 12 μm thick, or less than 10 μm thick, or less than 5 μm thick.

The metal coating may also comprise a top layer less than 20 μm thick. Such a top layer may for example be nickel. The top layer may be less than 15 μm thick, or less than 12 μm thick, or less than 10 μm thick, or less than 5 μm thick. The total thickness of the coating, whether it is made up of one coating layer or a plurality of coating layers, is preferably less than 100 μm , more preferably less than 75 μm or 50 μm or

40 μm or 30 μm or 20 μm or 10 μm . A thickness in the range of 10 μm to 30 μm , more preferably 15 μm to 25 μm is preferred.

- 5 A method of depositing the metal coating on the pin may comprise etching the surface to which it is to be applied, to provide a key, and depositing the metal layer on the keyed surface by a suitable deposition process. Preferably, after the surface is etched an activator is applied to the surface
10 before the coating is applied.

The connector part and the connector assembly of both aspects of the invention may be suitable for use subsea. They may for example be used to supply power to a subterranean or sub-
15 sea well. They may be used to supply power to an ESP or a compressor. They may be used to supply power to downhole equipment. The first-mentioned connector part may be connected at its back end to a cable leading to the equipment, and the second connector part may be connected at its back
20 end to a power supply. The connector part, and the connector assembly, may be suitable for withstanding high temperatures and high pressures. The first mentioned connector part may be suitable for withstanding a high pressure differential between the pin where it projects from the support and a back
25 end of the pin disposed in the support, such pressure differentials tending to urge the pin forwardly relative to the support.

Features of embodiments of the invention can be combined with
30 each other unless noted to the contrary.

Brief description of the drawings

Certain preferred embodiments of the invention will now be
35 described by way of example and with reference to the accompanying drawings, in which like reference numerals refer to like elements and in which:

Figure 1 shows an axial cross-sectional view of the interengaging parts of a connector assembly; and

Figure 2 shows an axial cross-sectional view of a pin
5 belonging to a first connector part of the connector assembly.

Detailed description

10 Figure 1 shows a connector assembly 10 comprising a first connector part 1 and a second connector part 2. The first connector part has a support 3 from which a connector pin 4 projects forwardly. The support is retained in a housing 5 of the first connector part 1 by a retaining member 6. The
15 connector pin 4 has a rear portion carried in the support 3 and an axially forwardly projecting portion disposed forwardly of the support. The pin 4 has an axially extending conductive portion or core 7 which at its rear end provides a rear electrical contact 8 for engagement in a socket of a
20 crimp or the like (not shown). At its front end the conductive core 7 has a front electrical contact 9. A pair of O-ring seals 11, 12 are provided near the front of the support 3 to seal the rear portion of the pin against water ingress.

25 The connector assembly is shown in the mated condition, with a small portion of the connector pin 4 being exposed to ambient conditions, such as seawater, in a region 13 between the first connector part 1 and the second connector part 2.

30 The second connector part 2 comprises an outer seal 14 defining an opening 15 through which the connector pin 4 extends into the second connector part 2. The outer seal 14 forms a primary barrier against water ingress. Axially rearwardly of the seal 14 (with respect to the second connector part) a second, inner seal 16 defines a second opening 17, through
35 which the pin 4 also passes in the mated condition of the connector assembly. The seal 16 is part of an elastomeric moulding which includes a flexible membrane 18 defining in-

wardly thereof a fluid filled chamber 19 which is able to provide pressure compensation of the chamber 19 with respect to another chamber 20 provided on the outside of the membrane 18. This chamber 20 is also fluid filled and extends between the first seal 14 and the second seal 17, as well as outwardly of the membrane 18. The outer chamber 20 is defined inwardly of a flexible membrane 23. The outer surface of the flexible membrane 23 is exposed to ambient pressure. Therefore, the outer chamber 20 is pressure balanced with respect to ambient conditions, and the inner chamber 19 is pressure balanced with respect to the outer chamber 20. Such pressure balancing tends to inhibit ingress of water or other contaminants into the second connector part 2, whether mated or demated.

Chamber 20 is thus a first, outer chamber, and chamber 19 is a second, inner chamber. Inside the inner chamber 19 an electrical contact socket 21 is provided for receiving the front electrical contact 9 of the connector pin 4 of the first connector part 1.

A forwardly spring biased shuttle piston 22 is provided in the second connector part 2. This is shown, in the mated condition of the connector assembly, pushed to a rearward position by the connector pin 4. In the unmated condition of the connector assembly, the shuttle piston 22 extends forwardly through the electrical contact socket 21, through the inner seal 16, and through the outer seal 15. It is biased forwardly by a spring (not shown) and held in this position to maintain the sealing integrity of the second connector part when the parts are not mated. The front end of the shuttle piston 22 in the unmated condition of the assembly is generally flush with the front of the outer seal 14.

Further details of the connector pin 4 are described with reference to Figure 2. The conductive core 7 extends forwardly from the rear electrical contact 8 to the front electrical contact 9. A glass fibre reinforced plastic or poly-

mer sleeve 24 is provided around the conductive core 7 and extends along the full length of the core other than the rear and front electrical contacts 8 and 9. The sleeve extends annularly round the core. In this embodiment, by way of example, the sleeve comprises a PEKK polymer and glass fibre. In this embodiment the polymer is filled with 40% glass fibre. The sleeve 24 provides the pin with mechanical strength. The pin has a load shoulder 25, having a generally conical configuration, increasing in diameter in a rearward direction. As seen in Figure 1, the load shoulder 25 engages against a corresponding conical shoulder 26 in the support 3 of the first connector part 1. The mechanical strength of the sleeve 24 provides a benefit in this load bearing region. If the connector assembly is used in conditions where the pressure at the rear of the pin is greater than the pressure at the front of the pin, then the pin experiences a forward thrust force. This is resisted by the load shoulder 25 of the pin engaging the corresponding load bearing surface 26 of the support 3.

The pin 4 has a protective layer provided around the sleeve 24 where it extends forwardly of the support. This protective layer 27 serves to protect the sleeve 24 from ambient conditions. The protective layer 27 extends annularly round the sleeve 24. It may be made of a polymer such as PEKK or PEEK, which is not provided with any fibre reinforcement, i.e. an unfilled polymer. The protective layer 27 extends forwardly to the front electrical contact 9. In this embodiment it extends rearwardly sufficiently far for it to be engaged by the seals 11 and 12 of the support 3. Therefore, the sleeve 24 to the rear of the protective layer 27 is not exposed to ambient conditions. The seals 11, 12 define a region axially rearwardly thereof which is sealed from ambient conditions.

The protective layer 27 has a rear end at the front of the load shoulder 25 of the pin 4. In alternative embodiments, the protective layer 27 can extend over the load shoulder.

It may therefore provide a compressible layer, or washer, around the load shoulder.

A metal coating 28 is provided over the sleeve 24, along a
5 length of the sleeve shown as "L". The metal coating extends from a rear end 29 over the length L to a front end 30. The front end 30 is surrounded by the protective layer 27 so that in use the high electrical stresses at the front end 30 are contained in the material of the protective layer 27. This
10 material is preferably moulded over the sleeve 24 after the metal coating 28 has been applied thereto and so there should be no trapped air in this region of high electrical stress.

The coating 28 is impermeable to water and, in addition to
15 the protective layer 27, provides protection to the sleeve 24 inwardly thereof. As seen in Figure 1, the metal coating extends axially across the part of the pin which is exposed at 13 to ambient conditions even when the connector parts are mated. Thus the metal coating 28 can protect the sleeve 24
20 from long term degradation when the connector is mated in the field.

The metal coating serves to control the electrical field around the conductive core 7. It will be seen in Figure 1
25 that the metal coating extends axially along the part of the pin that extends through the opening 15 defined by the seal 14 of the second connector part 2. Therefore the metal coating 28 protects the seal 14 from high electrical stresses.

30 In this embodiment the sleeve 24 and the protective layer 27 are made of different materials, the sleeve 24 being for providing mechanical strength and the protective layer 27 being for providing protection against ambient conditions. However, in alternative embodiments of the second aspect of
35 the invention, the two layers 24 and 27 may be made of the same material, or of two different materials neither of which contains fibre reinforcement. The metal coating then used between the two layers provides an impermeable barrier to

provide some protection for the inner layer. The metal coating also provides an electrical shield to the region radially outwardly thereof. It is easy to apply a metal coating to the inner layer during construction, compared to the use of a metal tube such as a metal mesh which has to be separately fabricated.

While specific embodiments of the invention are disclosed herein, various changes and modifications can be made without departing from the scope of the invention. The present embodiments are to be considered in all respect as illustrative and non-restrictive, and all changes coming within the meaning and equivalency range of the appended claims are intended to be embraced therein.

15

The following clauses set out features of the invention which may not presently be claimed in this application, but which may form the basis for future amendment or a divisional application:

20 A connector part for use underwater or in a wet or severe environment, the connector part comprising a pin projecting axially forwardly from a support, and the pin comprising an axially extending electrically conductive portion, a first axially extending insulating layer around the conductive portion, a second axially extending insulating layer around the first insulating layer, and an axially extending conductive and impermeable coating between the first and second insulating layers.

30 In an embodiment, the first and second layers may comprise the same material. In another embodiment, the first and second layers may comprise different materials.

The conductive impermeable coating may comprises a metal coating.

35 A connector assembly comprising a connector part as outlined in the preceding clauses, and a second connector part arranged to be interengaged with the first-mentioned connector part to establish an electrical connection.

In an embodiment, the second connector part has a seal around an opening for receiving the pin in sealed manner when the first and second connector parts are interengaged.

5 The conductive and impermeable coating may extend along the pin in a region which, when the first and second connector parts are interengaged, is disposed radially inwardly of the seal.

Claims

1. An electrical connector part for use underwater or in a wet or severe environment, the electrical connector part (1) comprising a pin (4), projecting axially forwardly from a support, the pin comprising an axially extending electrically conductive portion (7), an axially extending sleeve (24) comprising fibre reinforced plastic around said conductive portion (7), and a protective layer (27) around the sleeve (24) to prevent exposure of the sleeve (24) to ambient conditions when the pin (4) is exposed to ambient conditions.
2. An electrical connector part as claimed in claim 1, wherein the pin comprises a shoulder disposed in the support to prevent forward movement of the pin relative to the support.
3. An electrical connector part as claimed in claim 2, wherein the sleeve comprises a load bearing portion at the shoulder.
4. An electrical connector part as claimed in any of the preceding claims, wherein the sleeve comprises a fibre filled polymer.
5. An electrical connector part as claimed in any of the preceding claims, wherein the fibre reinforcement comprises or consists of glass fibres.
6. An electrical connector part as claimed in any of the preceding claims, wherein the fibre content in the fibre reinforced plastic is between about 20% and about 60%, preferably between about 30% and about 50%, more preferably about 40%.
7. An electrical connector part as claimed in any of the preceding claims, wherein the protective layer comprises a plastic or a polymer, in particular an engineering polymer.

8. An electrical connector part as claimed in any of the preceding claims, wherein the protective layer does not have fibre reinforcement.

5

9. An electrical connector part as claimed in any of the preceding claims, wherein the protective layer comprises or consists of a polyaryletherketone (PAEK), in particular polyetheretherketone (PEEK) or polyetherketoneketone (PEKK).

10

10. An electrical connector part as claimed in any of the preceding claims, comprising a conductive impermeable layer between the sleeve and the protective layer.

15 11. An electrical connector part as claimed in claim 10, wherein the conductive impermeable layer extends axially rearwardly of the protective layer.

12. An electrical connector part as claimed in claim 10 or
20 11, wherein the conductive impermeable layer comprises a metal coating.

13. An electrical connector assembly comprising an electrical connector part as claimed in any preceding claim, and a
25 second electrical connector part arranged to be interengaged with the first-mentioned electrical connector part to establish an electrical connection.

14. An electrical connector assembly as claimed in claim 13,
30 wherein the second electrical connector part has a seal around an opening for receiving the pin in sealed manner when the first and second electrical connector parts are interengaged.

35 15. An electrical connector assembly as claimed in claim 14, when dependent on claim 10, 11 or 12, wherein the conductive impermeable layer extends along the pin in a region which, when the first and second electrical connector parts are

interengaged, is disposed radially inwardly of the seal of the second electrical connector part.

FIG 1





FIG 2



INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2014/059925

A. CLASSIFICATION OF SUBJECT MATTER
INV. H01R13/523
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 236 018 A (KOBAYASHI AKIRA [JP] ET AL) 17 August 1993 (1993-08-17)	1-10,13
A	column 8, line 3 - column 9, line 4; figure 1	11,12, 14,15
Y	----- EP 0 048 601 A2 (CAIRNS JAMES L) 31 March 1982 (1982-03-31)	1-7, 10-15
A	page 4, line 14 - page 6, line 11; figures 2,3 page 7, line 19 - page 9, line 9	8,9
Y	----- WO 98/45635 A1 (EXXON RESEARCH ENGINEERING CO [US]) 15 October 1998 (1998-10-15)	1-7, 10-15
A	page 4, line 23 - page 5, line 4; figure 2 page 8, line 11 - page 9, line 6 page 10, line 14 - page 12, line 24; claim 1	8,9
	----- -/--	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 June 2014

Date of mailing of the international search report

16/06/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Bouhana, Emmanuel

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/059925

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 863 113 A1 (CARRIER KHEOPS BAC [FR]) 3 June 2005 (2005-06-03) page 1, line 3 - page 1, line 5; figure 1 page 3, line 5 - page 3, line 28 -----	1-15
A	GB 2 420 919 A (WEATHERFORD LAMB [US]) 7 June 2006 (2006-06-07) page 7, line 7 - page 9, line 13; figures 3,4,5,6 -----	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/059925

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5236018	A	17-08-1993	NONE
EP 0048601	A2	31-03-1982	DE 3171318 D1 14-08-1985 EP 0048601 A2 31-03-1982 JP S57118401 A 23-07-1982 US 4373767 A 15-02-1983
WO 9845635	A1	15-10-1998	AT 202191 T 15-06-2001 AU 730030 B2 22-02-2001 AU 6877898 A 30-10-1998 CA 2284012 A1 15-10-1998 CO 5021180 A1 27-03-2001 DE 69800929 D1 19-07-2001 DE 69800929 T2 15-11-2001 EP 0972154 A1 19-01-2000 ID 23795 A 11-05-2000 IL 131816 A 24-06-2003 PT 972154 E 30-11-2001 US 6240971 B1 05-06-2001 WO 9845635 A1 15-10-1998 ZA 9802880 A 22-04-1999
FR 2863113	A1	03-06-2005	NONE
GB 2420919	A	07-06-2006	CA 2528994 A1 06-06-2006 CA 2692330 A1 06-06-2006 GB 2420919 A 07-06-2006 GB 2438551 A 28-11-2007 US 2006148304 A1 06-07-2006 US 2007293087 A1 20-12-2007 US 2008293280 A1 27-11-2008