



US009821097B2

(12) **United States Patent**
Lazarus

(10) **Patent No.:** **US 9,821,097 B2**

(45) **Date of Patent:** **Nov. 21, 2017**

(54) **BODY CAVITY DRAINAGE DEVICES INCLUDING DRAINAGE TUBES HAVING INLINE PORTIONS AND RELATED METHODS**

(71) Applicant: **Merit Medical Systems, Inc.**, South Jordan, UT (US)

(72) Inventor: **Harrison M. Lazarus**, Salt Lake City, UT (US)

(73) Assignee: **Merit Medical Systems, Inc.**, South Jordan, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 318 days.

(21) Appl. No.: **14/318,568**

(22) Filed: **Jun. 27, 2014**

(65) **Prior Publication Data**
US 2015/0374890 A1 Dec. 31, 2015

(51) **Int. Cl.**
A61M 1/00 (2006.01)
A61M 25/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61M 1/008** (2013.01); **A61B 1/0052** (2013.01); **A61B 1/00165** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61M 25/0147; A61M 25/0133; A61M 25/0105; A61M 2025/015;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,393,002 A 1/1946 Smith
2,898,917 A 8/1959 Wallace
(Continued)

FOREIGN PATENT DOCUMENTS

RU 2012371 C1 5/1994
RU 2415682 C1 4/2011
(Continued)

OTHER PUBLICATIONS

Ben-Isaac et al., "Flexible Fiberoptic Pleuroscopy: Pleural and Lung Biopsy*," *Experimental Approaches*, Chest Journal No. 67, <http://journal.publications.chestnet.org/data/Journals/CHEST/20966/573.pdf>, May 5, 1975, pp. 573-576.

(Continued)


Primary Examiner — Adam Marcetich

(74) *Attorney, Agent, or Firm* — Stoel Rives LLP

(57) **ABSTRACT**

A body cavity drainage device includes a drainage tube with a distal end configured for insertion into the body cavity of a patient, a fluid outlet at a proximal end of the drainage tube; and an activation apparatus coupled to the drainage tube between the proximal end of the drainage tube and the distal end of the drainage tube. The activation apparatus may be configured to alter a position of the distal end of the drainage tube in response to an input at a control device of the activation apparatus, and a first portion of the drainage tube extending from the activation apparatus toward the distal end may be at least substantially coaxial with a second portion of the drainage tube extending from the activation apparatus toward the proximal end. Methods relate to forming a body cavity drainage devices.

18 Claims, 8 Drawing Sheets



(51)	Int. Cl.			5,772,670 A	6/1998	Brosa	
	<i>A61M 25/092</i>	(2006.01)		5,807,341 A	9/1998	Heim	
	<i>A61B 1/005</i>	(2006.01)		5,895,400 A	4/1999	Abela	
	<i>A61M 25/01</i>	(2006.01)		5,897,534 A	4/1999	Heim et al.	
	<i>A61B 90/00</i>	(2016.01)		5,987,344 A	11/1999	West et al.	
	<i>A61B 1/00</i>	(2006.01)		6,045,623 A	4/2000	Cannon et al.	
	<i>A61B 1/04</i>	(2006.01)		6,146,355 A *	11/2000	Biggs	A61M 25/0147 604/95.01
	<i>A61B 17/00</i>	(2006.01)		6,171,277 B1 *	1/2001	Ponzi	A61B 18/1492 604/22
	<i>A61B 50/00</i>	(2016.01)		6,183,450 B1	2/2001	Lois	
	<i>A61B 50/30</i>	(2016.01)		6,193,691 B1	2/2001	Beardsley	
(52)	U.S. Cl.			6,254,581 B1	7/2001	Scott	
	CPC	<i>A61B 1/042</i> (2013.01); <i>A61B 90/37</i>		6,468,260 B1	10/2002	Bumbalough et al.	
		(2016.02); <i>A61M 25/0136</i> (2013.01); <i>A61M</i>		6,500,167 B1	12/2002	Webster	
		<i>25/0147</i> (2013.01); <i>A61B 50/30</i> (2016.02);		6,514,273 B1	2/2003	Voss et al.	
		<i>A61B 2017/00327</i> (2013.01); <i>A61B 2050/005</i>		6,530,913 B1	3/2003	Giba et al.	
		(2016.02); <i>A61B 2050/314</i> (2016.02); <i>A61M</i>		6,530,935 B2	3/2003	Wensel et al.	
		<i>2209/10</i> (2013.01); <i>A61M 2210/101</i> (2013.01)		6,638,253 B2	10/2003	Breznock	
(58)	Field of Classification Search			6,907,992 B2	6/2005	McMichael et al.	
	CPC	A61B 2034/301; A61B 2017/003; A61B		7,037,290 B2	5/2006	Gardeski et al.	
		2017/00318; A61B 2017/00323; A61B		7,407,128 B1	8/2008	Chang	
		2017/00327		7,497,854 B2	3/2009	Gill et al.	
	See application file for complete search history.			7,578,814 B2	8/2009	Accisano, III et al.	
(56)	References Cited			7,740,623 B2	6/2010	Nayak et al.	
				7,758,586 B2	7/2010	Muto et al.	
				8,220,460 B2	7/2012	Tanaka	
				8,246,752 B2	8/2012	Boyle, Jr.	
				8,388,759 B2	3/2013	Boyle, Jr. et al.	
				8,409,070 B2	4/2013	Carol et al.	
	U.S. PATENT DOCUMENTS			2001/0005785 A1	6/2001	Sachse	
				2001/0007922 A1	7/2001	Schwager	
	3,225,762 A	12/1965	Guttman	2003/0208252 A1	11/2003	O'Boyle et al.	
	3,416,532 A	12/1968	Grossman	2003/0225364 A1	12/2003	Kraft et al.	
	3,610,231 A *	10/1971	Takahashi	2004/0035017 A1	2/2004	Yang	
			A61B 1/0052 385/118	2004/0116852 A1	6/2004	Scopton	
	3,683,929 A	8/1972	Holter	2005/0184186 A1	8/2005	Tsoi et al.	
	3,830,238 A	8/1974	Kurtz	2005/0277875 A1 *	12/2005	Selkee	A61M 25/0147 604/95.04
	3,863,641 A	2/1975	Popa				A61B 1/0052 600/149
	3,937,418 A	2/1976	Critelli	2006/0069311 A1 *	3/2006	Sullivan	
	3,943,929 A	3/1976	Patel				
	4,068,383 A	1/1978	Krebs	2006/0142695 A1	6/2006	Knudson	
	4,105,031 A	8/1978	Kurtz et al.	2006/0173449 A1 *	8/2006	Sharareh	A61B 18/1492 606/41
	4,202,510 A	5/1980	Stanish	2006/0217667 A1 *	9/2006	Accisano, III	A61M 25/007 604/174
	4,203,430 A	5/1980	Takahashi				
	4,228,802 A	10/1980	Trott et al.	2006/0264925 A1 *	11/2006	Sharareh	A61B 18/1492 606/41
	4,439,189 A	3/1984	Sargeant et al.				
	4,571,239 A	2/1986	Heyman	2006/0264988 A1	11/2006	Boyle	
	4,580,551 A *	4/1986	Siegmund	2006/0280773 A1	12/2006	Roschak et al.	
			A61B 1/0055 600/139	2007/0016133 A1	1/2007	Pepper	
	4,608,982 A	9/1986	Pollard	2007/0060997 A1	3/2007	de Boer	
	4,692,154 A	9/1987	Singery et al.	2007/0078455 A1	4/2007	Rashidi	
	4,769,019 A	9/1988	Kerwin	2007/0156116 A1	7/2007	Gonzalez	
	4,862,891 A	9/1989	Smith	2007/0167923 A1	7/2007	Deal	
	4,883,474 A	11/1989	Sheridan et al.	2007/0287993 A1	12/2007	Hinman et al.	
	4,920,980 A	5/1990	Jackowski	2008/0021415 A1	1/2008	Durkin et al.	
	5,026,358 A	6/1991	Everett, Jr. et al.	2008/0045921 A1	2/2008	Anderson et al.	
	5,040,543 A	8/1991	Badera et al.	2008/0097293 A1	4/2008	Chin et al.	
	5,047,018 A	9/1991	Gay et al.	2008/0236209 A1	10/2008	Conti et al.	
	5,108,368 A	4/1992	Hammerslag et al.	2009/0005771 A1 *	1/2009	Lieber	A61B 18/1492 606/34
	5,141,503 A	8/1992	Sewell				
	5,157,813 A	10/1992	Carroll	2009/0012365 A1	1/2009	Ueno et al.	
	5,205,830 A	4/1993	Dassa et al.	2009/0062769 A1	3/2009	Graves et al.	
	5,207,661 A	5/1993	Repschlager	2009/0227900 A1	9/2009	Kim et al.	
	5,297,310 A	3/1994	Cox et al.	2009/0270800 A1 *	10/2009	Spurchise	A61M 25/0074 604/95.04
	5,300,050 A	4/1994	Everett, Jr. et al.				
	5,312,357 A	5/1994	Buijs et al.	2009/0270838 A1	10/2009	Berthiaume et al.	
	5,364,351 A *	11/1994	Heinzelman	2009/0299327 A1	12/2009	Tilson et al.	
			A61M 25/0147 600/585	2010/0101061 A1	4/2010	Ha	
	5,370,610 A	12/1994	Reynolds et al.	2010/0137775 A1	6/2010	Hu et al.	
	5,397,321 A	3/1995	Houser et al.	2010/0168731 A1	7/2010	Wu et al.	
	5,409,462 A	4/1995	Ross	2010/0191057 A1	7/2010	Jansen et al.	
	5,409,468 A	4/1995	Sachse	2010/0222664 A1	9/2010	Lemon et al.	
	5,456,664 A	10/1995	Heinzelman et al.	2010/0249490 A1	9/2010	Farnan	
	5,540,648 A	7/1996	Yoon et al.	2010/0249520 A1	9/2010	Shelton, IV et al.	
	5,601,087 A	2/1997	Gunderson et al.	2010/0264244 A1	10/2010	Spencer	
	5,616,131 A	4/1997	Sauer et al.	2011/0040285 A1	2/2011	Boyle	
	5,630,795 A	5/1997	Kuramoto et al.				
	5,653,696 A	8/1997	Shiber et al.				

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0062268 A1 3/2011 Cheng
 2011/0077498 A1* 3/2011 McDaniel A61B 18/1492
 600/374
 2011/0213300 A1 9/2011 McWeeney et al.
 2011/0224647 A1 9/2011 Lazarus
 2011/0264089 A1* 10/2011 Zirkle A61B 5/042
 606/41
 2011/0282153 A1 11/2011 Ueki
 2012/0116161 A1* 5/2012 Nieman A61B 1/00052
 600/114
 2012/0157921 A1 6/2012 Hoofnagle et al.
 2012/0172703 A1* 7/2012 Esguerra A61B 5/062
 600/409
 2013/0023840 A1 1/2013 Loske et al.
 2013/0046250 A1* 2/2013 Bode A61M 5/31511
 604/228
 2013/0158379 A1* 6/2013 Selkee A61B 1/00052
 600/373
 2013/0204087 A1 8/2013 Jaworek et al.
 2013/0211385 A1 8/2013 Lazarus
 2013/0253505 A1* 9/2013 Schultz A61B 18/1492
 606/41
 2013/0276718 A1 10/2013 Valadez et al.
 2013/0310767 A1 11/2013 Solar et al.
 2014/0150782 A1 6/2014 Vazales et al.
 2014/0193138 A1 7/2014 Koren

2014/0290014 A1 10/2014 Myrick
 2015/0148595 A1 5/2015 Bagwell et al.
 2015/0374889 A1* 12/2015 Lazarus A61B 17/3415
 604/541
 2015/0374959 A1* 12/2015 Lazarus A61M 25/0136
 604/543

FOREIGN PATENT DOCUMENTS

WO 9325264 A1 12/1993
 WO 9952481 A1 10/1999

OTHER PUBLICATIONS

“Catheter prevents clogging,” Research & Development, <<<http://www.rdmag.com/printpdf/award-winners/2011/08/catheter-prevents-clogging>, Aug. 14, 2011>>, 3 pages.
 “Express Dry Seal Chest Drain, Instructions for Use,” Atrium, www.atriummed.com (2003) 2 pages.
 “Medical pleuroscopy”, <<http://www.cancercenter.com/treatments/medical-pleuroscopy/>>, Cancer Treatment Centers of America, retrieved Aug. 19, 2013, 2 Pages.
 “Rocket® Cardiothoracic Range,” Rocketmedical, Issue 1, R89947, Jan. 2011, 23 pages.
 International Preliminary Report on Patentability with Written Opinion for International Application No. PCT/US2015/038112, dated Dec. 27, 2016, 5 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

1

**BODY CAVITY DRAINAGE DEVICES
INCLUDING DRAINAGE TUBES HAVING
INLINE PORTIONS AND RELATED
METHODS**

BACKGROUND

Field

Embodiments of the invention relate to body cavity drainage devices and related devices and methods.

State of the Art

Drainage devices, especially for the evacuation of a pleural cavity, may consist of a hollow, flexible tube inserted through an incision into the pleural cavity. The shape and configuration of the pleural cavity often necessitates multiple incisions to be made to permit the drainage tube to reach various locations in the pleural cavity. The need for multiple incisions may generally result in an extended hospital stay for a patient suffering from a severe case of pleurisy.

BRIEF SUMMARY

In one embodiment of the disclosure, a body cavity drainage device includes a drainage tube with a distal end configured for insertion into the body cavity of a patient, a fluid outlet at a proximal end of the drainage tube, and an activation apparatus coupled to the drainage tube between the proximal end of the drainage tube and the distal end of the drainage tube. The activation apparatus may be configured to alter a position of the distal end of the drainage tube in response to an input at a control device of the activation apparatus. A first portion of the drainage tube extending from the activation apparatus toward the distal end maybe at least substantially coaxial with a second portion of the drainage tube extending from the activation apparatus toward the proximal end.

In another embodiment of the disclosure, a body cavity drainage device includes a body cavity drainage tube with a distal end configured for insertion into a body cavity of a patient and a proximal end with a fluid outlet, and an activation apparatus configured to bend the body cavity drainage tube. The activation apparatus may be disposed on the body cavity drainage device along the body cavity drainage tube intermediate the distal end and the proximal end.

In yet another embodiment of the disclosure, a method of forming a body cavity drainage device may include coupling an activation apparatus to a body cavity drainage tube intermediate a proximal end and distal end of the body cavity drainage tube, the distal end configured for insertion into a body cavity of a patient and the proximal end including a fluid outlet, the activation apparatus configured to bend the body cavity drainage tube in response to a torque input at a control device. The method may also include inserting at least one flexible member through at least one respective lumen in a wall of the body cavity drainage tube, and operatively connecting the at least one flexible member to the activation apparatus.

BRIEF DESCRIPTION OF THE SEVERAL
VIEWS OF THE DRAWINGS

FIG. 1 shows a top view of a drainage device according to an embodiment of the present disclosure;

FIG. 2 shows a side view of the drainage device of FIG. 1;

2

FIG. 3 shows a top cross-sectional view of the drainage device of FIG. 1;

FIG. 4 shows a top cross-sectional view of the drainage device of FIG. 1 in a bent position;

5 FIG. 5 shows an enlarged top view of an activation apparatus according to an embodiment of the present disclosure;

FIG. 6 shows a side cross-sectional view of the activation apparatus of FIG. 5;

10 FIG. 7 shows a schematic side view of a drainage device according to an embodiment of the present disclosure;

FIG. 8 shows a side view of a drainage tube placement tool according to an embodiment of the present disclosure;

15 FIG. 9 shows a detail view of the drainage tube placement tool of FIG. 8 disposed within a drainage tube;

FIG. 10 shows a cross-sectional detail view of the drainage tube placement tool of FIG. 8 disposed within a drainage tube;

20 FIG. 11 shows a side view of a drainage tube placement tool according to another embodiment of the present disclosure;

FIG. 12 shows a side view of a cleaning device for a drainage tube according to an embodiment of the present disclosure;

25 FIG. 13 shows a top view of a surgical kit including a drainage device and a drainage tube placement tool according to an embodiment of the present disclosure; and

30 FIG. 14 shows a cross-sectional view of a drainage device according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

35 As used herein, the term “distal” relates to an end of a device configured to be inserted into the body cavity of a patient, and the term “proximal” relates to an end of a device configured to be outside of a patient.

In one embodiment of the present disclosure, a body cavity drainage device includes a body cavity drainage tube with a proximal end and a distal end. The proximal end of the body cavity drainage tube may be connected to an activation apparatus including a rotatable control device and a compliant locking mechanism. Rotation of the rotatable control device may cause the distal end of the body cavity drainage tube to move relative to the proximal end of the drainage tube. In an unlocked position, the compliant locking mechanism may allow rotation of the rotatable control device. In a locked position, the compliant locking mechanism may substantially prevent rotation of the rotatable control device until a predetermined torque value is applied to the rotatable control device.

In another embodiment of the present disclosure, a body cavity drainage device includes a body cavity drainage tube extending along a central axis between a proximal end and a distal end. A fluid outlet may be oriented substantially coaxially with the drainage tube. The proximal end of the body cavity drainage tube may be attached to an activation apparatus. The activation apparatus may include a rotatable control device for controlling a position of the distal end of the body cavity drainage tube.

In yet another embodiment of the present disclosure, a body cavity drainage device placement tool for use with a body cavity drainage tube includes a shaft, a handle at or near a proximal end of the shaft, and a distal end of the shaft for insertion through at least one lateral opening of the body cavity drainage tube and at least partially through a central

3

lumen of the body cavity drainage tube for placement of the distal end of the body cavity drainage tube in a body cavity of a patient.

In yet another embodiment of the present disclosure, a package including at least three of a body cavity drainage device, a drainage tube placement tool, a drainage tube cleaning device, and a visualization device may be provided to a user.

FIG. 1 shows a drainage device 100 according to an embodiment of the present disclosure. The drainage device 100 may include a drainage tube 102 configured to provide drainage to a body cavity defined by or surrounded by soft tissue. For example, the drainage device 100 may be used to withdraw infection exudates from a pleural cavity by applying suction to the drainage tube 102. In addition, positive pressure may be applied to the drainage tube 102, such as to introduce a fluid into the drainage tube 102 and/or body cavity, such as to dissolve material to be removed or to dislodge flow restrictions within the drainage tube 102.

Although the drainage device 100 is described herein relative to use with pleural cavities, the present disclosure is not so limited. Accordingly, the drainage device 100, elements thereof, and accompanying elements described in the present disclosure may be used for drainage from or introduction of fluids into other body cavities such as, by way of non-limiting example, veins, arteries, abdominal cavities, cranial cavities, etc.

The drainage tube 102 may include a proximal end 104 and a distal end 106. The drainage tube 102 may include at least one of an axial opening 108 in the distal end 106 and one or more lateral openings 110 proximate the distal end 106 into an open lumen of the drainage tube 102. The drainage device 100 may be configured to inhibit damage to the soft tissue surrounding the cavity while a portion of the drainage device 100 is inserted into the cavity or moved about within the cavity. For example, the distal end 106 of the drainage device 100 may include a substantially blunted geometry to prevent damage to the body cavity. In other words, the distal end 106 may not have any sharp, pointed, or abrupt edges that, if present, could puncture or otherwise damage soft tissue of a body cavity. In some embodiments, the drainage device 100 may include any and all of the features and characteristics of the drainage devices described in U.S. patent application Ser. No. 13/840,986, filed Mar. 15, 2013 and published as US 2013/0211385, which is incorporated herein by reference for all that it discloses.

In some embodiments, the axial opening 108 and the one or more lateral openings 110 may have an average diameter that is substantially the same size or smaller than an average inside diameter of the drainage tube 102. Sizing the axial opening 108 and the one or more lateral openings in this manner relative to the inside diameter of the drainage tube 102 may ensure that any clots (e.g., blood clots) suctioned into the drainage tube 102 are sufficiently small to pass through the drainage tube 102 without obstructing (e.g., clogging) the drainage tube 102.

The proximal end 104 of the drainage tube 102 may be coupled to an activation apparatus 112 that may include a control device 114. The control device 114 may be, for example, a knob configured to be manually manipulated (e.g., rotated) by a user, such as a practitioner, physician, nurse, patient, or care provider.

FIG. 2 shows a side view of the drainage device 100 of FIG. 1. The drainage device 100 may include a fluid outlet 202 in fluid communication with the drainage tube 102 and may be configured for connection to a vacuum source for

4

removal of material from a body cavity or to a source of one or more treatments to be introduced into the body cavity. In some embodiments, the fluid outlet 202 may be an integral extension of the drainage tube 102.

FIG. 3 shows a cross-sectional view of the drainage device 100 of FIG. 1. An activation apparatus 112 may be attached at or near the proximal end 104 of the drainage tube 102. The activation apparatus 112 may include a pinion gear 302, a first rack 304, and a second rack 306. The first and second racks 304, 306 may be complementary to and meshed with the pinion gear 302. First and second flexible members 308, 310 may be attached to the first and second racks 304 and 306, respectively. The first and second flexible members 308, 310 may have an elongate shape and may include, for example, metallic wires made from steel, titanium, nitinol, or other metals or alloys. Additionally or alternatively, the first and second flexible members 308, 310 may include synthetic or natural fibers. As a further example, such wires or fibers may include a single strand or multiple strands of one or more materials bundled or woven together. The first and second flexible members 308, 310 may be disposed within closed lumens within a wall 312 of the drainage tube 102. The lumens through which the first and second flexible members 308, 310 extend may not be in fluid communication with the open lumen defined by the drainage tube 102 or with an exterior of the drainage tube 102. In some embodiments, the flexible members 308, 310 may be completely laterally enclosed within the wall 312 of the drainage tube 102. The lumens may be positioned within the wall of the drainage tube 102 such that each of the flexible members 308, 310 is substantially directly opposite the other across a diameter of the drainage tube 102.

FIG. 4 shows another cross-sectional view of the drainage device 100 of FIG. 1. The pinion gear 302 may rotate in response to an applied torque 402. As a non-limiting example, the torque 402 may be applied by a user manually operating the control device 114 (FIG. 1), which may be connected to the pinion gear 302. Other embodiments may include an automated system configured to operate the control device 114. Rotation of the pinion gear 302 may cause generally linear movement of the first rack 304 in a first direction 404 and a corresponding generally linear movement of the second rack 306 in a second, opposite direction 406. Movement of the first rack 304 may create tension in the first flexible member 308, which imparts a compressive force to a first side 408 of the drainage tube 102. Movement of the second rack 306 may allow slack in the second flexible member 310. The compressive force from the first flexible member 308 may cause the drainage tube 102 to contract along the first side 408 in which the first flexible member 308 is disposed and lengthen along a second side 410 in which the second flexible member 310 is disposed, causing the drainage tube 102 to assume an arcuate (e.g., bent) shape, such as the shape shown in FIG. 4. The magnitude of the applied torque 402 and the corresponding refraction of the first flexible member 308 may determine the extent of curvature imparted to the drainage tube 102. Torque may be applied in a direction opposite the direction indicated in FIG. 4, resulting in curvature of the drainage tube 102 in an opposite direction to the curvature shown. In some embodiments, the drainage device 100 may be configured such that the distal end 106 may rotate at least about 360° from a first fully curved position (e.g., pointing down and to the left in the perspective shown in FIG. 4) to a second, opposite fully curved position (e.g., pointing down and to the right from the same perspective).

5

In some embodiments, the drainage device **100** may include one or more optical fibers extending through lumens formed in the wall **312** of the drainage tube **102** and terminating at or near the distal end **106**. Such optical fibers may be connected to a visualization device (e.g., a camera

providing an image to an electronic display) to assist a user in placing or moving the drainage tube **102** within a patient's body cavity. Referring now to FIG. **5**, the activation apparatus **112** may include a compliant locking mechanism **500**. The compliant locking mechanism **500** may have a locked position in which the compliant locking mechanism **500** maintains the control device **114** in a predetermined position selected by a user. The user may release (e.g., place the compliant locking mechanism **500** in an unlocked position) the compliant locking mechanism **500** to facilitate rotation of the control device **114**. In some embodiments, the compliant locking mechanism **500** may be configured to allow rotation of the control device **114** under a sufficiently high applied torque **402** (FIG. **4**) even when the compliant locking mechanism is in the locked position.

In some embodiments, the compliant locking mechanism **500** may include a lock lever **502** with a proximal end **504** pivotably affixed to a main housing portion **506** of the activation apparatus **112**. As shown in FIG. **5**, the proximal end **504** of the lock lever **502** may be resiliently (e.g., elastically) attached to the main housing portion **506**. In some embodiments, the lock lever **502** may be integrally molded with the main housing portion **506** (e.g., by an injection molding process). In other words, the lock lever **502** may include a flexible structural portion (i.e., the resilient attachment of the proximal end **504** to the main housing portion **506**) for rotating the lock lever **502** between the locked and unlocked positions. In other embodiments, the lock lever **502** may be attached to the main housing portion **506** with, e.g., a pinned hinge, and may be biased to a locked position by an elastic biasing element (e.g., a spring).

A distal end **508** of the lock lever **502** may include serrations (e.g., gear teeth) **510** configured to substantially mesh with gear teeth **512** of the pinion gear **302**. In a locked position, the serrations **510** of the distal end **508** of the lock lever **502** may mesh with the gear teeth **512** of the pinion gear **302** and inhibit rotation of the pinion gear **302** when a torque is not applied (or an insufficient torque is applied) to the control device **114**, thereby fixing the control device **114** at a desired position.

When a user desires to unlock the compliant locking mechanism **500**, the user may depress the lock lever **502** with a force **602**, as shown in FIG. **6**. The lock lever **502** may pivot at the proximal end **504**, and the serrations **510** (FIG. **5**) of the distal end **508** may move downward (with reference to the orientation of FIG. **6**) to clear (i.e., disengage from) the gear teeth **512** of the pinion gear **302** and facilitate rotation of the control device **114** and pinion gear **302**. The user may then rotate the control device **114** to the desired position and release the lock lever **502** to maintain the control device **114** in the selected position.

Alternatively, the user may leave the lock lever **502** in the locked position, and apply torque to the control device **114**. At a sufficiently high torque value, the lock lever **502** may elastically deform at one or more locations, e.g., at an angled juncture **604**. As torque is applied to the control device **114**, mechanical interaction between the serrations **510** (FIG. **5**) and the gear teeth **512** may force the distal end **508** of the lock lever **502** in direction **606**, i.e., away from the pinion gear **302**. Under a sufficiently high applied torque, the lock

6

lever **502** may elastically deform enough to enable the serrations **510** (FIG. **5**) to disengage from the gear teeth **512** of the pinion gear **302** and allow rotation of the pinion gear **302** even when the lock lever **502** remains in a locked position (i.e., in the absence of force **602**). Thus, the compliant lock mechanism **500** may enable a user to adjust the position of the control device **114** without depressing the lock lever **502**, while maintaining the position of the control device **114** in the absence of a sufficiently high applied torque.

For example, the compliant lock mechanism **500** may be configured such that it avoids or reduces movement of the control device **114** resulting from incidental contact when in the locked position, but allows movement at a threshold level of applied torque. Such a level of applied torque may be, by way of example and not limitation, a torque value of greater than about 0.5 lb·ft (0.68 N·m), greater than about 1.0 lb·ft (1.36 N·m), or greater than about 5.0 lb·ft (6.8 N·m).

Accordingly, a method of draining fluid from a body cavity may include positioning a distal end of a tube of a body cavity drainage device at a first position within the body cavity. Fluid may be drained from the body cavity through the distal end of the tube of the body cavity drainage device while the distal end of the tube is in the first position. A user may depress a locking lever to unlock a rotatable control device of the body cavity drainage device external to the body cavity. The user may move the distal end of the tube of the body cavity drainage device to a second, different position within the body cavity. Moving the distal end of the tube of the body cavity drainage device may include rotating the rotatable control device of the body cavity drainage device, and the rotatable control device may be coupled to the distal end of the tube of the body cavity drainage device by flexible members.

In some embodiments, a drainage device may include a fluid outlet that is substantially aligned with the drainage tube. For example, referring now to FIG. **7**, a schematic side view of another embodiment of a drainage device **700** is shown. In this embodiment, a drainage tube **702** extends along a central axis A_c , through an activation apparatus **704**, and to a fluid outlet **706** also aligned along the central axis A_c . In some embodiments, a single tube extending through the activation apparatus **704** may form the drainage tube **702** and the fluid outlet **706**. In other words, the drainage device **700** may comprise a unitary drainage tube **702** with a distal end **708** for insertion into a body cavity of a patient, a proximal end **710** including a fluid outlet **706**, and an activation apparatus **704** disposed on the drainage tube **702** between the proximal end **710** and the distal end **708**. In other embodiments, the drainage tube **702** and the fluid outlet **706** may be two separate tubes coupled (e.g., bonded, press-fit, glued) together.

In the embodiment of FIG. **7**, a control device **714** may be disposed in a position offset from a central axis A_c of the drainage tube **702**. At least one flexible member **718**, substantially as described above in connection with FIGS. **3** and **4**, may extend from the control device **714** along an at least partially curvilinear (i.e., arcuate) path **720**. The at least one flexible member **718** may be constrained to the curvilinear path **720** by guides **716** in the activation apparatus **704** and channels in the drainage tube **702**. The control device **714**, the at least one flexible member **718**, and the drainage tube **702** may function in a similar manner to that described above in connection with FIGS. **3** and **4**. The activation apparatus **704** may further include a compliant locking mechanism, as described above in connection with FIGS. **5** and **6**.

7

Referring now to FIG. 8, a side view of a drainage tube placement tool 800 is shown. The drainage tube placement tool 800 may include a handle 802 affixed to a shaft 804 at a proximal end 806. The shaft 804 may be substantially straight, or may include a curved portion 810 near a distal end 808, as shown in FIG. 8. In some embodiments, the shaft 804 may have a substantially circular cross-sectional shape. In other embodiments, the shaft 804 may have a different cross-sectional shape, such as an elliptical shape, a rectangular shape, or combinations thereof.

The shaft 804 may include a shoulder 812 (e.g., a step) where the cross-sectional shape of the shaft 804 varies from a first diameter 814 to a second, smaller diameter 816. As shown in FIG. 8, the shoulder 812 may be disposed proximate the distal end 808 of the shaft 804. By way of example and not limitation, the shoulder 812 may be positioned within about one (1) inch (25.4 mm) or less of the distal end 808 of the shaft 804. In other embodiments (e.g., as shown below in FIG. 10), the shoulder may be disposed proximate the handle portion 802, or the drainage tube placement tool 800 may not include a shoulder.

Referring now to FIG. 9, a user may insert the shaft 804 of the drainage tube placement tool 800 through a lateral opening 910 of a drainage tube 902. The lateral opening 910 may be similar to the lateral openings 110 described in connection with FIGS. 1 and 2. In some embodiments, the lateral opening 910 may include features configured to facilitate insertion of the drainage tube placement tool 800 within the drainage tube 902. For example, a slit 912 may extend from a periphery of the lateral opening 910 into a wall 914 of the drainage tube 902. Upon insertion of the distal end 812 (FIG. 8) of the drainage tube placement tool 800 within the lateral opening 910, the slit 912 may at least partially open, as shown in FIG. 9, to ease passage of the drainage tube placement tool 800 through the drainage tube 902. Upon removal of the drainage tube placement tool 800 from the drainage tube 902, the slit 912 may substantially close, and the diameter of the lateral opening 910 may be substantially similar to the diameter of other lateral openings 916. Suction applied to the drainage tube 902 after removal of the drainage tube placement tool 800 may also assist the slit 912 to close. In other embodiments, the diameter of the lateral opening 910 may be greater than the diameter of other lateral openings 110.

The drainage tube placement tool 800 may be configured to stop at a predetermined insertion distance within the drainage tube 902. Referring now to FIG. 10, after the drainage tube placement tool 800 (FIG. 8) is inserted into the lateral opening 910 (FIG. 9) of the drainage tube 902, the user may continue to insert the drainage tube placement tool 800 within the drainage tube 902 until the shoulder 812 of the shaft 804 of the drainage tube placement tool 800 abuts a ferrule 1000 disposed near the distal end 106 of the drainage tube 902 and the shoulder 812 prevents further insertion of the placement tool 800 within the drainage tube 902. The portion of the shaft 804 having the second diameter 816 (FIG. 8) may enter an axial opening 1002 of the ferrule 1000. In this position, the distal end 808 (FIG. 8) of the drainage tube placement tool 800 may be disposed proximate a distal end 1004 of the drainage tube 902. In some embodiments, the axial opening 1002 of the ferrule 1000 may have a diameter smaller than an inside diameter of the drainage tube 102.

In some embodiments, the shaft 804 of the drainage tube placement tool 800 may have a length sufficient to extend through the lateral opening 910 of the body cavity drainage tube 902, through a central lumen of the body cavity

8

drainage tube 902, and position the distal end 808 of the shaft 804 past the distal end 1004 of the drainage tube 902. In other words, when the shaft 804 is inserted fully into the body cavity drainage tube 902, the distal end 808 of the shaft 804 may protrude beyond the distal end 1004 of the drainage tube 902.

In some embodiments, at least one of the flexible members 308, 310 (FIG. 3) or 718 (FIG. 7) may be attached to the ferrule 1000. In other words, the ferrule 1000 may be coupled to a control device (e.g., control device 114 (FIG. 3) or control device 714 (FIG. 7)) of an activation apparatus (e.g., activation apparatus 112 (FIG. 3) or activation apparatus 704 (FIG. 7)) through one or more flexible members 308, 310, and 718.

The drainage tube placement tool 800 may contribute additional stiffness (i.e., rigidity) to the drainage tube 902 to enable a user to insert the drainage tube 902 through an incision in a patient's body and into, e.g., the pleural cavity, without collapsing (e.g., kinking) the drainage tube 902. In some embodiments, the drainage tube placement tool 800 may be made from a material having a greater modulus of elasticity (i.e., a greater stiffness) than the material of the drainage tube 902.

In use, a user may insert the distal end 812 of the drainage tube placement tool 800 into the drainage tube 902, grasp the handle 802, and insert the drainage tube 902 with the drainage tube placement tool 800 disposed therein through an incision and into the body cavity. The user may then remove the drainage tube placement tool 800 from the drainage tube 902, leaving at least a portion of the drainage tube 902 disposed within the body cavity.

The curved portion 810 of the drainage tube placement tool 800 may be shaped to ease insertion of the drainage tube 902 with the drainage tube placement tool 800 disposed therein within a body cavity of a particular configuration. For example, the curved portion 810 of the drainage tube placement tool 800 may have a shape of a desired path the drainage tube 902 may follow as the drainage tube 902 is inserted into a body cavity. By way of another example, the curve may facilitate directing the placement of the drainage tube 902 within the body cavity.

Referring now to FIG. 11, another embodiment of a drainage tube placement tool 1100 is shown. The drainage tube placement tool 1100 may include a shaft 1104 with a shoulder 1102 disposed near a proximal end 1106 of the shaft 1104. A distal end 1108 of the shaft 1104 may be inserted in a lateral opening 910, 916 (FIG. 9) of a drainage tube 902. The shoulder 1102 may abut a wall 914 (FIG. 9) of the drainage tube 902 surrounding the lateral opening 910, 916 at a predetermined insertion distance. In other embodiments, the shoulder 1102 may be absent, and a handle 1110 may abut against the lateral opening 910, 916 to stop further insertion of the drainage tube placement tool 1100 into a drainage tube. Thus, the drainage tube placement tool 1100 may be used with a drainage tube device that does or does not include a ferrule 1000 (FIG. 10). For example, the drainage tube placement tool 1100 may be used with a drainage device according to the present disclosure, e.g., drainage devices 100, 700, or may be used with prior art drainage devices. As shown in FIG. 11, the shaft 1104 of the drainage tube placement tool 1100 may be substantially straight. In other embodiments, the shaft 1104 of the drainage tube placement tool 1100 may include a curved portion 810 like that shown in the embodiment of FIG. 8.

In some embodiments, the shaft 804, 1104 of the drainage tube placement tool 800, 1100 may be hollow (e.g., may include a channel therethrough) to accommodate a guide

wire for aiding placement of the drainage tube within a body cavity and/or to accommodate one or more optical fibers therein. A guide wire may be placed in a desired location through a hollow needle, and one or more dilators may be threaded over the guide wire to expand an incision made by the hollow needle through the skin and/or other tissue. When the incision is sufficiently expanded, the drainage tube placement tool **800**, **1100** may be inserted into a drainage tube **100**, **700** as described above, and the guide wire may be threaded through the drainage tube placement tool **800**, **1100**. A distal end of the drainage tube **100**, **700** may then be placed in the body cavity through the expanded incision using the guide wire. In some embodiments, one or more optical fibers may be inserted through the channel of the drainage tube placement tool **800**, **1100**. The one or more optical fibers may be connected to a visualization device (e.g., a camera in communication with an electronic display) to assist the user in placing a drainage tube **100**, **700** within the body cavity.

FIG. **12** shows an embodiment of a cleaning device **1200** according to the present disclosure. The cleaning device **1200** may include a handle **1202**, a shaft **1204**, and a cleaning instrument **1206**. The cleaning instrument **1206** may be configured to be inserted through an fluid outlet **202**, **704** (FIGS. **2** and **7**) of the drainage device **100**, **700**. In some embodiments, the cleaning instrument **1206** may be inserted into the drainage device **100**, **700** while a portion of the drainage tube **102** remains disposed within a body cavity. The cleaning instrument **1206** may be configured to retrieve solid matter, e.g., blood clots or other coagulations of physiological fluids, from the drainage tube **102**. In use, a user may remove a vacuum source from the fluid outlet **202**, **704** of the drainage device **100**, **700**. The user may then insert the cleaning instrument **1206** into the fluid outlet **202**, **704**, grasp the handle **1202**, and feed the cleaning device **1200** into the drainage tube **102** until the cleaning instrument **1206** contacts the solid matter. The user may remove the cleaning device **1200** and solid matter from the drainage tube **102** and reconnect the vacuum source to the fluid outlet **202**, **704**. In some embodiments, the cleaning instrument **1206** may comprise a coil of resilient material, such as a metal alloy or a polymer. The cleaning instrument **1206** may have a helical shape, which may be rotated within the drainage tube **102** to force the solid matter out of the drainage tube **102**.

Referring to FIG. **13**, a surgical kit **1300** may include at least a drainage device **100**, **700** and a drainage tube placement tool **800**, **1100**. Each of the drainage device **100**, **700** and the drainage tube placement tool **800**, **1100** in the surgical kit **1300** may be substantially as described above. In some embodiments, the surgical kit **1300** may also include one or more of a cleaning device **1200** for removal of obstructions in the drainage device **100**, **700**, a guide wire to facilitate placement of the drainage device **100**, **700**, at least one dilator for expanding an incision to facilitate placement of the drainage device **100**, **700**, and a visualization device **1302** to facilitate placement of the drainage device **100**, **700**. The visualization device **1302** may include, for example, a fiber optic scope and/or a camera. The elements in the surgical kit **1300** may provide complementary tools for a surgeon or other practitioner to use for draining a patient's body cavity. Each of the elements in the surgical kit **1300** or portions thereof may be sterilized and otherwise prepared for use in surgery. In addition, one or more of the elements in the surgical kit **1300** may be provided at least partially within a sterile envelope, protective covering, enclosure, or

other container within the surgical kit **1300** for additional protection from contamination or damage.

FIG. **14** illustrates an embodiment of a drainage device **1400** including an activation apparatus **1412** and a detachable drainage tube **1402**. The activation apparatus **1412** and detachable drainage tube **1402** may be configured to be detachably coupled together for positioning the detachable drainage tube **1402** in a body cavity (e.g., for initial insertion and/or for repositioning within the body cavity). The activation apparatus **1412** and detachable drainage tube **1402** may be selectively detached from each other, such as to provide increased mobility to a patient. The detachable drainage tube **1402** may include at least some similar features as the drainage tube **102** described above. For example, the detachable drainage tube **1402** may include a proximal end **1404**, a distal end **1406**, and one or more lateral openings **1410** proximate the distal end **1406** of the detachable drainage tube **1402**. The detachable drainage tube **1402** may also include elongated flexible members **1408** extending from the proximal end **1404** to at or near the distal end **1406** of the detachable drainage tube **1402**, which may be disposed within lumens longitudinally extending through a sidewall of the detachable drainage tube **1402**.

The activation apparatus **1412** may include at least some similar features as the activation apparatus **112** described above. For example, the activation apparatus **1412** may include a control device **1414**, such as a knob or other element configured to be manually manipulated (e.g., rotated) by a user to remotely move the distal end **1406** of the detachable drainage tube **1402** when coupled thereto. The control device **1414** may include a pinion configured to engage with first and second racks **1416**, **1418**.

The proximal end **1404** of the detachable drainage tube **1402** may be configured to couple the detachable drainage tube **1402** to the activation apparatus **1412**, and the activation apparatus **1412** may be configured to couple with the detachable drainage tube **1402** in a complementary fashion. Additionally, a linking element **1420** may be coupled to a proximal end of each of the elongated flexible members **1408** for operably connecting each of the elongated flexible members **1408** to a respective one of the first and second racks **1416**, **1418**. By way of example and not limitation, each linking element **1420** may include a hook and each of the first and second racks **1416**, **1418** may include a complementary slot or hook **1421**. When operably connected, the hook of the linking element **1420** may latch onto the complementary slot or hook **1421** of the respective one of the first and second racks **1416**, **1418**. By way of another example, the linking element **1420** may include a notch (e.g., an annular notch) and each of the first and second racks **1416**, **1418** may include a complementary ridge or O-ring configured to deflect and snap into the notch of the linking element **1420** when the detachable drainage tube **1402** is operably connected to the activation apparatus **1412**.

The activation apparatus **1412** may include a suction tube **1422** that may be configured to form a fluid seal with a proximal end of the detachable drainage tube **1402** when the detachable drainage tube **1402** is operably connected to the activation apparatus **1412**. Accordingly, suction may be applied to the suction tube **1422** to draw fluids from a body cavity through the detachable drainage tube **1402**.

Accordingly, the drainage device **1400** may be used to withdraw fluids from a body cavity of a patient by inserting the distal end **1406** of the detachable drainage tube **1402** into the body cavity and, prior to or after insertion of the distal end **1406** of the detachable drainage tube **1402**, operably coupling the activation apparatus **1412** to the proximal end

11

1404 of the detachable drainage tube 1402. To operably couple the activation apparatus 1412 to the detachable drainage tube 1402, a fluid seal may be formed between the detachable drainage tube 1402 and the suction tube 1422 and the linking elements 1420 may be coupled to the first and second racks 1416, 1418. When operably connected, the activation apparatus 1412 may be used to remotely position the distal end 1406 of the detachable drainage tube 1402 within the body cavity.

The activation apparatus 1412 may also be detached from the detachable drainage tube 1402, such as to enable increased patient mobility. For example, the linking elements 1420 may be decoupled from the first and second racks 1416, 1418, and the detachable drainage tube 1402 may be decoupled from the suction tube 1422. In some embodiments, after the activation apparatus 1412 is detached from the detachable drainage tube 1402, the proximal end of the detachable drainage tube 1402 may be capped or plugged to inhibit fluid from inadvertently draining out of the detachable drainage tube 1402.

Referring to FIG. 14 in conjunction with FIG. 13, the surgical kit 1300 may, in some embodiments, include the drainage device 1400 in a detached or an attached configuration. In some embodiments, more than one detachable drainage tube 1406, such as identical detachable drainage tubes 1406 or detachable drainage tubes 1406 of different lengths, diameters, materials, stiffnesses, etc., may be included in the surgical kit 1300.

While the disclosure may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the disclosure is not intended to be limited to the particular forms disclosed. Additionally, embodiments and features of the disclosure shown and/or described separately may be combined.

What is claimed is:

1. A body cavity drainage device, comprising:

a drainage tube with a distal end configured for insertion into the body cavity of a patient, the drainage tube comprising:

a central open lumen defined by a wall of the drainage tube and extending between the distal end and a proximal end of the drainage tube;

a plurality of lateral openings in the wall of the drainage tube proximate to the distal end of the drainage tube, each of the plurality of lateral openings in fluid communication with the central open lumen; and

a fluid outlet at the proximal end of the drainage tube, the fluid outlet in fluid communication with the central open lumen of the drainage tube; and

an activation apparatus coupled to the drainage tube between the proximal end of the drainage tube and the distal end of the drainage tube, a portion of the drainage tube extending through the activation apparatus, the activation apparatus configured to alter a position of the distal end of the drainage tube in response to an input at a control device of the activation apparatus, wherein a first portion of the drainage tube extending from the activation apparatus toward the distal end is at least substantially coaxial with a second portion of the drainage tube extending from the activation apparatus toward the proximal end, the control device comprising a first flexible member and a second flexible member each extending longitudinally through a first closed lumen and a second closed lumen, the first and second closed lumens disposed within the wall of the drainage

12

tube, the first flexible member and the second flexible member positioned substantially directly opposite each other about the central open lumen; and

wherein the first closed lumen and the second closed lumen are not in fluid communication with the central open lumen.

2. The body cavity drainage device of claim 1, wherein the activation apparatus is offset from a central axis of the drainage tube.

3. The body cavity drainage device of claim 1, wherein the at least two flexible members are configured to apply tension to the drainage tube to bend the drainage tube in response to the input at the control device of the activation apparatus.

4. The body cavity drainage device of claim 1, wherein the at least two flexible members extend between the control device and the wall of the drainage tube along an arcuate path.

5. The body cavity drainage device of claim 1, wherein the control device comprises a pinion gear and two racks configured to mesh with the pinion gear, and wherein each of the at least two flexible members are attached to a respective one of the two racks.

6. The body cavity drainage device of claim 1, wherein the control device comprises a knob configured for manual manipulation by a user.

7. The body cavity drainage device of claim 1, wherein each lateral opening of the plurality of lateral openings comprises a diameter less than an inside diameter of the drainage tube.

8. The body cavity drainage device of claim 1, further comprising a ferrule disposed at the distal end.

9. The body cavity drainage device of claim 8, wherein the ferrule has an inside diameter smaller than an inside diameter of the drainage tube.

10. The body cavity drainage device of claim 9, further comprising at least two flexible members coupling the ferrule to the control device of the activation apparatus.

11. A body cavity drainage device, comprising:

a body cavity drainage tube with a distal end configured for insertion into a body cavity of a patient and a proximal end with a fluid outlet, the body cavity drainage tube comprising:

a central open lumen defined by a wall of the body cavity drainage tube and extending between the distal end and the proximal end of the body cavity drainage tube; and

a plurality of lateral openings in the wall of the body cavity drainage tube proximate to the distal end of the body cavity drainage tube, each of the plurality of lateral openings in fluid communication with the central open lumen; and

an activation apparatus configured to bend the body cavity drainage tube, the activation apparatus disposed on the body cavity drainage device along the body cavity drainage tube intermediate the distal end and the proximal end, wherein a portion of the body cavity drainage tube extends through the activation apparatus, the activation apparatus comprising a first flexible member and a second flexible member each extending through a first closed lumen and a second closed lumen, the first and second closed lumens disposed within the wall of the body cavity drainage tube, the first flexible member and the second flexible member positioned substantially directly opposite each other about the central open lumen; and

13

wherein the first closed lumen and the second closed lumen are not in fluid communication with the central open lumen.

12. The body cavity drainage device of claim 11, wherein the activation apparatus comprises:

a control device connected to a pinion gear;
at least two racks configured to mesh with the pinion gear;
wherein each of the at least two flexible members are attached to a respective one of the at least two racks,
wherein the at least two flexible members are configured to apply tension to the body cavity drainage tube to bend the body cavity drainage tube.

13. The body cavity drainage device of claim 12, wherein the at least two flexible members extend from the activation apparatus to the wall of the body cavity drainage tube along an arcuate path.

14. The body cavity drainage device of claim 13, wherein the at least two flexible members are constrained to the arcuate path by at least one guide disposed within the activation apparatus.

15. The body cavity drainage device of claim 11, wherein the body cavity drainage tube comprises an optical fiber for connection to a visualization device, the optical fiber extending longitudinally through the wall of the body cavity drainage tube to the distal end of the body cavity drainage tube.

16. A method of forming a body cavity drainage device, comprising:

providing a body cavity drainage tube with a distal end configured for insertion into a body cavity of a patient, the body cavity drainage tube comprising:

a central open lumen defined by a wall of the body cavity drainage tube and extending between the distal end and a proximal end of the body cavity drainage tube;

a plurality of lateral openings in the wall of the drainage tube proximate to the distal end of the body cavity drainage tube, each of the plurality of lateral openings in fluid communication with the central open lumen; and

14

a fluid outlet at the proximal end of the body cavity drainage tube, the fluid outlet in fluid communication with the central open lumen of the body cavity drainage tube;

5 coupling an activation apparatus to the body cavity drainage tube intermediate the proximal end and the distal end of the body cavity drainage tube, a portion of the body cavity drainage tube extending through the activation apparatus, the activation apparatus configured to bend the body cavity drainage tube in response to a torque input at a control device;

10 inserting a first flexible member and a second flexible member through a first closed lumen and a second closed lumen, the first and second closed lumens disposed within the wall of the body cavity drainage tube, the first flexible member and the second flexible member positioned substantially directly opposite each other in the wall of the body cavity drainage tube about the central open lumen; and

15 operatively connecting the first flexible member and the second flexible member to the activation apparatus; and wherein the first closed lumen and the second closed lumen are not in fluid communication with the central open lumen.

20 17. The method of claim 16, wherein operatively connecting the at least two flexible members to the activation apparatus comprises connecting each of the at least two flexible members to a respective one of at least two movable racks of the activation apparatus.

25 18. The method of claim 17, wherein coupling an activation apparatus to a body cavity drainage tube intermediate a proximal end and distal end of the body cavity drainage tube comprises aligning a first portion of the body cavity drainage tube proximate the activation apparatus and extending toward the proximal end with a second portion of the body cavity drainage tube proximate the activation apparatus and extending toward the distal end.

* * * * *