



US007513182B2

(12) **United States Patent**
Tripard

(10) **Patent No.:** **US 7,513,182 B2**
(45) **Date of Patent:** **Apr. 7, 2009**

(54) **INTEGRATED CIRCUIT PACKAGE SEPARATORS**

(75) Inventor: **Jason E. Tripard**, Boise, ID (US)

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/215,664**

(22) Filed: **Aug. 30, 2005**

(65) **Prior Publication Data**

US 2005/0284274 A1 Dec. 29, 2005

Related U.S. Application Data

(62) Division of application No. 09/687,600, filed on Oct. 12, 2000, now Pat. No. 6,945,151, which is a division of application No. 09/533,058, filed on Mar. 22, 2000, now Pat. No. 6,718,858, which is a division of application No. 09/176,479, filed on Oct. 20, 1998, now Pat. No. 6,277,671.

(51) **Int. Cl.**
B26D 7/02 (2006.01)

(52) **U.S. Cl.** **83/467.1**; 83/468.5; 83/929.1; 83/953

(58) **Field of Classification Search** 83/451, 83/467.1, 468.5, 468.6, 56, 614, 929.1, 939, 83/953; 269/54.5, 54.1, 295, 265, 266, 309, 269/311, 310, 900, 903

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

154,694 A 9/1874 Martin
508,885 A * 11/1893 Johnston 269/296
1,275,899 A 8/1918 Freyberg
1,379,724 A 5/1921 Russell

2,305,339 A	12/1942	Deutscher	
2,373,968 A	4/1945	Lang	
3,905,100 A	9/1975	Kleine et al.	30/124
3,976,288 A	8/1976	Cuomo, Jr.	269/21
4,039,799 A *	8/1977	Stumpf	219/121.67
4,127,432 A	11/1978	Kuwano et al.	156/297
4,497,477 A	2/1985	Abel	269/303
4,506,442 A	3/1985	Alzmann et al.	29/830
4,807,504 A	2/1989	Vandermarliere	83/22
4,822,015 A	4/1989	Glasman et al.	269/54.1
4,832,323 A	5/1989	Principe et al.	269/54.5
4,930,759 A	6/1990	Potter et al.	269/54.5
5,005,814 A	4/1991	Gumbert	269/309


(Continued)

Primary Examiner—Stephen Choi
(74) *Attorney, Agent, or Firm*—Wells St. John P.S.

(57) **ABSTRACT**

Integrated circuit package separator for separating integrated circuit packages from a board. A base having a plurality of pins extending upwardly therefrom is provided. A support is provided over the base. The support has an upper surface and a plurality of holes extending therethrough. The pins extend through the holes and upwardly beyond the upper surface of the support. An actuator is provided beneath the support. A board having a plurality of integrated circuits bonded thereto is provided. The integrated circuits form a repeating pattern of integrated circuit packages across the board, and the board has a plurality of holes extending through it. The board is placed over the support upper surface with the pins extending into the holes in the board and cut to separate the integrated circuit packages from one another. After the cutting, the support is vertically displaced by the actuator to lift the support off the pins.

19 Claims, 6 Drawing Sheets




US 7,513,182 B2


Page 2


U.S. PATENT DOCUMENTS


5,063,800 A	11/1991	Jung et al.	83/14	5,836,224 A	11/1998	Gerber	
5,067,695 A	11/1991	Huddleston	269/21	5,839,337 A	11/1998	Neu	83/255
5,144,873 A	9/1992	Nasu	83/19	5,932,065 A	8/1999	Mitchell	156/556
RE34,125 E	11/1992	Amos et al.		5,970,606 A	10/1999	Buechele	29/830
5,173,766 A	12/1992	Long et al.	257/687	5,984,293 A	11/1999	Abrahamson et al.	269/266
5,218,753 A	6/1993	Suzuki et al.	29/740	5,988,393 A *	11/1999	Hsia et al.	206/711
5,288,061 A	2/1994	Pieroni	269/4.5	6,034,524 A	3/2000	Barringer et al.	
5,438,740 A	8/1995	Carr et al.	29/33	6,124,707 A *	9/2000	Kim et al.	324/158.1
5,480,133 A	1/1996	Motev et al.		6,146,504 A	11/2000	Patadia et al.	204/192.12
5,525,261 A *	6/1996	Incorvia et al.	252/500	6,150,240 A	11/2000	Lee et al.	438/460
5,628,237 A	5/1997	Lindee et al.		6,277,671 B1	8/2001	Tripard	438/113
5,765,337 A	6/1998	Lodewegen et al.		6,295,978 B1	10/2001	Wark et al.	
5,794,329 A	8/1998	Rossmeisl et al.	29/743	6,356,811 B1	3/2002	Beselt	
5,816,089 A	10/1998	Marando		6,540,014 B2	4/2003	Getchel et al.	
				6,701,910 B1	3/2004	Roberts	


* cited by examiner











INTEGRATED CIRCUIT PACKAGE SEPARATORS

RELATED PATENT DATA

This patent resulted from a divisional application of U.S. patent application Ser. No. 09/687,600, filed Oct. 12, 2000, now U.S. Pat. No. 6,945,151, issued Sep. 20, 2005, and titled "Integrated Circuit Package Separators", which is a divisional application of U.S. patent application Ser. No. 09/533,058, which was filed Mar. 22, 2000, now U.S. Pat. No. 6,718,858, issued Apr. 13, 2004, which is a divisional application of U.S. patent application Ser. No. 09/176,479, which was filed on Oct. 20, 1998, now U.S. Pat. No. 6,277,671, issued Aug. 21, 2001, the disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

The invention pertains to methods of forming integrated circuit packages, as well as to devices for separating integrated circuit packages.

BACKGROUND OF THE INVENTION

Circuit constructions having integrated circuit (IC) chips bonded to circuit boards (such as SIMMs and DIMMs) can be fabricated by joining IC chips on a single large circuit board comprising a plurality of the constructions. The circuit board can be subsequently cut to separate discrete constructions from one another. The discrete constructions are referred to herein as integrated circuit packages. The smaller the individual circuit packages, the more likely it is for industry processing to utilize the above-described method of forming the packages on a single large board and subsequently cutting individual packages from the board.

An exemplary prior art process of separating integrated circuit packages is described with reference to FIG. 1. FIG. 1 illustrates a board assembly 10 having a plurality of IC chips 12 (only some of which are labeled) bonded thereto. Chips 12 are aligned into individual IC package configurations 14 (only some of which are labeled) to form a repeating pattern of integrated circuit packages 14 across the board assembly 10. Dashed lines 16 are shown to illustrate the boundaries between individual IC packages 14. In the shown exemplary embodiment, assembly 10 comprises three separate circuit boards 11, 13 and 15. The number and size of individual circuit boards can vary depending on the number and size of IC packages that are ultimately to be formed.

Each of boards 11, 13 and 15 comprises a pair of lateral waste sections 21, 23 and 25, respectively. The lateral waste sections 21, 23 and 25 are separated from the remainder of boards 11, 13 and 15, respectively, by imaginary dashed lines 20, 22 and 24. In further processing, the individual IC packages 14 are separated from one another by cutting through boards 11, 13 and 15 along the regions illustrated by dashed lines 16. During the cutting to separate IC packages 14 from one another, boards 11, 13 and 15 are also cut along regions illustrated by dashed lines 20, 22 and 24 to remove waste portions 21, 23 and 25 from the lateral sides of the boards, and accordingly from lateral edges of the ultimately formed IC packages.

Orifices 19 (only some of which are labeled) are provided throughout circuit boards 11, 13 and 15. Specifically, pairs of orifices 19 are provided in each IC package 14, and at least two orifices 19 are provided in each of waste portions 21, 23 and 25.

FIG. 1 further illustrates an IC package separator 40 comprising a cutting mechanism 42 (shown schematically as a cutting wheel, although other cutting mechanisms, such as, for example, router bits or linear blades, are known to persons of ordinary skill in the art), a retaining table 44, and a control mechanism 45 configured to control orientation of cutting wheel 42 relative to table 44. Retaining table 44 can comprise, for example, an x-y table (i.e., a table horizontally adjustable in x and y directions; an "X", "Y" and "Z" axis system is illustrate in a lower corner of FIG. 1). Control mechanism 45 can control the x and y orientation of table 44 and the z (i.e., vertical) orientation of cutting mechanism 42 to precisely cut a board retained on table 44. Table 44, cutting mechanism 42, and control mechanism 45 can be comprised by commercially available cutting systems, such as, for example, Advanced Technology Incorporated's CM101 single spindle router (or, more generally, a circuit board depanelization router).

FIG. 1 also illustrates that table 44 comprises an upper platform 46. A subplate 48 is provided over platform 46, and a stripper plate 50 is provided over subplate 48. Subplate 48 comprises a plurality of upwardly extending pins 60 (only some of which are labeled), and stripper plate 50 comprises a number of orifices 62 configured to slide over pins 60. Subplate 48 is retained on table 44 by downwardly extending pins (not shown) which are aligned with and precisely received within orifices (not shown) extending within platform 46 of table 44.

Orifices 19 of boards 11, 13 and 15 align with pins 60. In operation, boards 11, 13 and 15 are slid over pins 60 until the pins protrude through orifices 19. Typically, orifices 19 are only about 0.003 inches wider than pins 60 to insure tight alignment of boards 11, 13 and 15 with subplate 48. After boards 11, 13 and 15 are retained on table 44 by pins 60, cutting mechanism 42 is utilized to cut along the regions illustrated by dashed lines 16, 20, 22 and 24. Such cutting separates discrete integrated circuit packages 14 from one another, as well as from waste regions 21, 23 and 25. The separated circuit packages are retained on table 44 by pins 60 extending through the packages. Specifically, each of individual packages 14 comprises a pair of orifices 19 and is thereby retained on table 44 by a pair of pins 60.

After the IC packages are separated from one another, stripper plate 50 is manually lifted off of subplate 42 to lift the IC packages 14 from pins 60. Once stripper plate 50 is lifted off from pins 60, the individual IC packages can be separated from stripper plate 50. An exemplary method of removing the IC packages from stripper plate 50 is to tilt plate 50 and allow the packages to slide off plate 50. After the packages 14 are removed, plate 50 can be returned to over 48 and used again for separating IC packages.

Difficulties can occur in utilizing the assembly of FIG. 1 for separating IC packages. For instance, separated IC packages can be broken as stripper plate 50 is lifted from subplate 48. It would be desirable to reduce or eliminate such problems.

SUMMARY OF THE INVENTION

In one aspect, the invention encompasses a method of forming integrated circuit packages. A base having a plurality of pins extending upwardly therefrom is provided. A support is provided over the base. The support has an upper surface and a plurality of holes extending therethrough. The pins extend through the holes and upwardly beyond the upper surface of the support. An actuator is provided beneath the support. A board having a plurality of integrated circuits bonded thereto is provided. The integrated circuits form a

repeating pattern of integrated circuit packages across the board, and the board has a plurality of holes extending through it. The board is placed over the support upper surface with the pins extending into the holes in the board. While the board is over the support upper surface, it is cut to separate the integrated circuit packages from one another. After the cutting, the support is vertically displaced by the actuator to lift the support off the pins.

In another aspect, the invention encompasses an integrated circuit package separator for separating integrated circuit packages from a board. The board comprises a plurality of integrated circuits bonded thereto, and has a plurality of holes extending within it. The separator includes a base having a plurality of pins extending upwardly therefrom and a support over the base. The support has an upper surface, a plurality of holes extending therethrough, and a pair of opposing ends. The pins extend through the holes in the support and upwardly beyond the upper surface of the support. The support and pins are configured such that the pins extend into the holes in the board when the board is placed over the support upper planar surface. The separator further includes a pair of actuators beneath the support and configured to vertically displace the support and lift the support off the pins. Additionally, the separator includes a cutting mechanism configured to cut the board while the board is over the support upper planar surface and thereby separate the integrated circuit packages from one another.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the invention are described below with reference to the following accompanying drawings.

FIG. 1 is a diagrammatic, perspective, exploded view of a prior art IC package separator and circuit board assembly.

FIG. 2 is a diagrammatic top view of an IC package separator of the present invention.

FIG. 3 is a diagrammatic, perspective, exploded view of an IC package separator of the present invention with a stripper plate of the present invention and a circuit board.

FIG. 4 is a view of the FIG. 3 assembly with the circuit board retained on the IC separator.

FIG. 5 is a view of the FIG. 4 assembly after the retained circuit board is cut to separate individual IC packages from one another.

FIG. 6 is a view of the FIG. 5 assembly after a stripper plate is lifted to release separated IC packages from retaining pins.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

This disclosure of the invention is submitted in furtherance of the constitutional purposes of the U.S. Patent Laws "to promote the progress of science and useful arts" (Article 1, Section 8).

An IC package separator of the present invention and a method of operation of such separator are described below with reference to FIGS. 2-6. In referring to FIGS. 2-6, similar numbering to that utilized above in describing prior art FIG. 1 will be used, with differences indicated by the suffix "a" or by different numerals.

Referring to FIG. 2, a separator 100 of the present invention is shown in top view. Separator 100 comprises a table 44a and a subplate 48a provided over table 44a. Table 44a can comprise, for example, an x-y table similar to the table 44 described above with reference to FIG. 1. Subplate 48a, like the above-described substrate 48 of FIG. 1, can be joined to

table 44a through a plurality of downwardly extending pins (not shown), and comprises a plurality of upwardly extending pins 60 (only some of which are labeled) configured to retain a circuit board assembly (not shown).

Subplate 48a differs from subplate 48 of FIG. 1 in that subplate 48a comprises notches 102 at its ends. Notches 102 are provided to allow room for a pair of forcer plates 104 and 106 to move vertically (in and out of the page of FIG. 2) relative to table 44. Forcer plates 104 and 106 comprise upwardly extending pins 108 and 110, respectively. Base plate 48a comprises an upper planar surface 115, and forcer plates 104 and 106 comprise upper planar surfaces 117 and 119, respectively. Upper planar surfaces 115, 117 and 119 ultimately support a circuit board assembly (not shown in FIG. 2). Planar surfaces 115, 117 and 119 are preferably substantially coplanar with one another to avoid distorting (e.g., bending) a supported circuit board assembly.

Forcer plates 104 and 106 are connected to actuators 112 and 114, respectively, configured to vertically displace forcer plates 104 and 106. In the exemplary shown embodiment, forcer plates 104 and 106 are connected to the actuators with screws 116. It is to be understood, however, that other mechanisms could be utilized for joining forcer plates 104 and 106 to actuators 112 and 114, including, for example, welding.

Actuators 112 and 114 are pneumatic (preferably air-powered) and connected to a gas source 120. An advantage of utilizing air powered actuators is that most wafer fabrication plants have a source of clean dry air available. Accordingly, it is relatively convenient to couple air powered actuators 112 and 114 into existing fabrication plants by simply connecting them to existing air lines. However, it is to be understood that the actuators can be powered by other sources besides air, including, for example, other fluids, such as liquids, as well as non-pneumatic and non-hydraulic sources, such as, for example, electricity.

Separator apparatus 100 comprises a cutting assembly (not shown in FIG. 2) and a controller (not shown in FIG. 2), analogous to the cutting assembly 42 and controller 45 of FIG. 1.

Referring to FIG. 3, IC circuit package separator 100 is shown in exploded view with a circuit board assembly 10 identical to the assembly described above with reference to FIG. 1.

A stripper plate 50a is provided between subplate 48a and circuit board assembly 10. Stripper plate 50a is similar to the stripper plate 50 of FIG. 1 in that plate 50a comprises a plurality of orifices 62 configured for receipt of pins 60. However, stripper plate 50a differs from plate 50 of FIG. 1 in that plate 50a also comprises orifices 122 configured for receipt of upwardly extending pins 108 and 110 of forcer plates 104 and 106. Pins 108 and 110 are preferably tapered pins, such as can be obtained from McMaster-Carr. Exemplary pins have a dimension of 0.248 inches at base, 0.2324 inches at top, and a length of 0.75 inches. The taper of the pins can assist in aligning support 50a over the pins during placement of support 50a onto base 48a.

Stripper plate 50a further differs from plate 50 of FIG. 1 in that plate 50a is configured for receipt of a series of panels 132, 134 and 136. Stripper plate 50a can comprise, for example, static-reduced plastic having a thickness of greater than $\frac{3}{16}$ inches, and panels 132, 134 and 136 can comprise, for example, aluminum. In the shown embodiment, panels 132, 134 and 136 are held to stripper plate 50a by a plurality of screws 138 (only some of which are labeled). It will be recognized, however, that other mechanisms can be utilized for holding panels 132, 134 and 136 to stripper plate 50a,

5

including riveting. Alternatively, panels **132**, **134** and **136** can be molded as part of stripper plate **50a**.

Panels **132**, **134** and **136** comprise ribs **140**, **142** and **144**, respectively (only some of which are labeled). Ribs **140**, **142** and **144** can assist in supporting board assembly **10**. Specifically, IC chips **12** are frequently provided on both an upper surface of circuit board assembly **10**, and a bottom surface (not shown). Ribs **140**, **142** and **144** (also referred to as blocks) have upper surfaces **141**, **143** and **145**, respectively, which contact the bottom surfaces of circuit boards **11**, **13** and **15** at locations between the IC chips **12** on the bottom of the board. Preferably, such upper surfaces are provided at a height approximately equal to a thickness of integrated circuit chip components **12**. Accordingly, when boards **11**, **13** and **15** are rested on panels **132**, **134** and **136**, respectively, the boards rest on the upper surfaces of blocks **140**, **142** and **144** while leaving integrated circuit chip components on the underside of boards **11**, **13** and **15** extending between block upper surfaces **141**, **143** and **145** and panels **132**, **134** and **136**. An exemplary block height (or thickness) of blocks **140**, **142** and **144** for a DRAM having IC chips **12** with a TSOP dimensional package is 0.040 inches \pm 0.005 inches. As another example, if IC chips **12** have a SOJ dimensional package, the block height is preferably 0.140 inches \pm 0.005 inches.

Blocks **140**, **142** and **144** can be formed as one piece with panels **132**, **134** and **136**. Alternatively, blocks **140**, **142** and **144** can be formed as discrete pieces from panels **132**, **134** and **136** that are subsequently fastened to the panels.

In the shown embodiment, blocks **140**, **142** and **144** are provided in a one-to-one correspondence with integrated chip packages **14**. Also, in the shown exemplary embodiment each of panels **132**, **134** and **136** is identical to one another, and in a one-to-one correspondence with individual boards **11**, **13** and **15**. It is to be understood, however, that the invention encompasses other embodiments (not shown) wherein the blocks are not provided in a one-to-one correspondence with packages **14**, wherein the panels are not identical to one another, and wherein the panels are not in a one-to-one correspondence with the individual boards.

Pins **60** extend upwardly beyond upper surfaces **141**, **143** and **145** of blocks **140**, **142** and **144**, and are configured to retain circuit board assembly **10** over stripper panel **50a**. In the shown embodiment, pins **60** do not extend through panels **132**, **134** and **136**. However, it is to be understood that the invention encompasses other embodiments wherein pins **60** do extend through such panels.

FIG. **3** shows a side perspective view of actuator **112**. In such view it can be seen that several ports **150**, **152**, **153**, **154**, **155** and **156** are provided between actuator **112** and gas source **120**. Valves (not shown) are provided between source **120** and one or more of ports **150**, **152**, **153**, **154**, **155** and **156**. Such valves enable fluid to be selectively flowed from source **120** into one or more of ports **150**, **152**, **153**, **154**, **155** and **156** to selectively control raising and lowering of forcer plate **104** with actuator **112**. For instance, flow of gas into port **152** can force a pneumatic cylinder to lift forcer plate **104**, and flow of gas into port **150** can force the pneumatic cylinder to lower forcer plate **104**.

Ports **154** and **156** are connected to release valves **163** and **165**, respectively, which enable a pressure on at least one side of the pneumatic cylinder of actuator **112** to be maintained at ambient pressure (generally, about 1 atmosphere). Specifically, release valves **163** and **165** comprise outlet ports **157** and **159**, respectively, which vent to a surrounding environment. Persons of ordinary skill in the art will recognize that one or more of ports **150**, **157** and **159** are utilized as gas outlet ports during lifting of forcer plate **104**, and port **152** com-

6

prises a gas inlet port during such lifting. In preferred embodiments of the present invention, the release valves are associated with an outlet side of actuator **112** to enable equilibration of a pressure at such outlet side to ambient prior to (and/or during) lifting of forcer plate **104**. Specifically, the release valves enable gas to be drained from outlet lines (more specifically, the gas is drained through ports **157** and **159** which are open to ambient conditions) prior to, and/or during, lifting with the actuator. Actuator **114** (FIG. **2**) is preferably identical to actuator **112** and connected to an identical valve and port assembly as that shown connected to actuator **112**. Accordingly, actuator **114** is also connected with release valves configured to equilibrate a back-pressure of the actuator to ambient prior to, and/or during, lifting of stripper panel **50a**. The equilibration of pressure at the outlet ends of both of actuators **112** and **114** to ambient during a lifting operation can enable both actuators to have an identical back-pressure during the lifting operation. This can facilitate having both actuators lift simultaneously and in unison. Such simultaneous lifting can avoid distortion (such as, for example, bending) of circuit board assembly **10** during the lifting.

Stripper plate **50a** has an upper planar surface **160** and a pair of opposing ends **162** and **164**. Opposing ends **162** and **164** overlie forcer plates **104** and **106**, respectively. In operation, actuators **112** and **114** are utilized to lift opposing ends **162** and **164** simultaneously and in unison. Such can be accomplished by, for example, maintaining approximately equal gas pressure at both of actuators **112** and **114** during lifting, and is found to reduce breakage of integrated circuit packages relative to prior art methods. The term "approximately" in the previous sentence is utilized to indicate the gas pressure at both actuators is equal within operational parameters.

A method of operation of separator **100** is described with reference to FIGS. **4-6**. In referring to FIGS. **4-6**, subplate **48a** is referred to as a base, and stripper plate **50a** is referred to as a support. Referring first to FIG. **4**, circuit board assembly **10** is shown retained on support **50a**. Specifically, circuit board assembly **10** is placed over support upper surface **160** with pins **60** extending through orifices **19** of the circuit boards **11**, **13** and **15**. Pins **60** and board assembly **10** are aligned such that each of the integrated circuit packages **14** is retained to the support **50a** by at least one pin, and, in the shown embodiment, is retained by 2 pins. In the FIG. **4** processing step, actuators **112** and **114** (FIG. **2**) are in a lowered position.

Referring to FIG. **5**, the individual integrated circuit packages **14** are separated from one another by cutting through boards **11**, **13** and **15**.

Referring to FIG. **6**, actuators **112** and **114** (FIG. **2**) are utilized to vertically displace support **50a** from base **48a**. Preferably, such vertical displacement comprises lifting both of ends **162** and **164** of support **50a** substantially simultaneously and substantially in unison with one another. (As used in the preceding sentence, the term "substantially" indicates that the lifting of both ends is simultaneous and in unison within operational parameters.) In exemplary applications the upper surface **160** of support **50a** is level prior to the lifting and remains level during the lifting. The lifting of support **50a** releases separated circuit packages **14** from pins **60**. After such release, support **50a** can be, for example, manually lifted from pins **108** and **110**, and the separated packages removed from support **50a**.

In compliance with the statute, the invention has been described in language more or less specific as to structural and methodical features. It is to be understood, however, that the invention is not limited to the specific features shown and described, since the means herein disclosed comprise pre-

ferred forms of putting the invention into effect. The invention is, therefore, claimed in any of its forms or modifications within the proper scope of the appended claims appropriately interpreted in accordance with the doctrine of equivalents.

The invention claimed is:

1. An integrated circuit package separator for separating a plurality of integrated circuit packages from one another, the integrated circuit packages being provided as integrated circuit chip components joined to a board, the separating including cutting the board, the separator comprising:

a plurality of panels, each panel comprising an elongated structure fastened to a support, the support comprising a planar upper surface;

a plurality of blocks over the panels, each block comprising an elongated structure extending parallel with each other block and each panel, each panel having two spaced blocks wherein the spacing is configured to support and maintain a stationary position of each integrated circuit package after being separated from the board, the blocks having curved upper surfaces and being configured to support the board while leaving the integrated circuit chip components extending between the block upper surfaces; and the panel between the block upper surfaces;

a cutting mechanism configured to cut the board while the board is supported on the blocks and to thereby separate the integrated circuit packages from one another;

wherein the plurality of the blocks are one piece with the panel; and

a pair of actuators, each actuator configured for driving a plate positioned beneath the support, the plates being moveable to vertically displace the support, each actuator comprising release values configured to equilibrate a back-pressure of the actuator to ambient prior to and during movement of the support.

2. The separator of claim 1 wherein each planar upper surface is positioned in a coplanar relationship to collectively establish a single and planar uppermost surface which is devoid of openings.

3. The separator of claim 1 wherein each panel physically contacts the support.

4. The separator of claim 1 wherein each panel is fastened to the support by being molded as part of the support.

5. The separator of claim 1 wherein the support comprises static-reduced plastic.

6. The separator of claim 1 wherein each panel comprises aluminum.

7. The separator of claim 1 wherein the plurality of the blocks are discrete pieces from the panels, and wherein the plurality of the blocks are fastened to the panels.

8. The separator of claim 1 wherein the plurality of the blocks are one piece with the panels.

9. An integrated circuit package separator for separating a plurality of integrated circuit packages from one another, the integrated circuit packages being provided as integrated circuit chip components joined to a board, the separating including cutting the board, the separator comprising:

a plurality of panels fastened to and a support with each panel elevationally above the support, each panel comprising a planar upper surface wherein each planar upper surface is positioned in a coplanar relationship to collectively establish a single and planar uppermost surface that extends as a single, continuous planar surface from one outer peripheral edge of the plane to all other outer peripheral edges of the plane of the planar uppermost surface which is devoid of inner peripheral edges and openings;

a plurality of blocks extending upward and over the uppermost surface collectively established by the plurality of the panels, each block comprising an elongated structure extending parallel with each other block, the blocks having curved upper surfaces and being configured to support the board while leaving the integrated circuit chip components extending between the curved upper surfaces and the panels; and

a cutting mechanism configured to cut the board while the board is supported on the blocks and to thereby separate the integrated circuit packages from one another; and

a pair of actuators, each actuator configured for driving a plate positioned beneath the support, the plates being moveable to vertically displace the support, each actuator comprising release values configured to equilibrate a back-pressure of the actuator to ambient prior to and during movement of the support.

10. An integrated circuit package separator for separating a plurality of integrated circuit packages from one another, the integrated circuit packages being provided as integrated circuit chip components joined to a board, the separating including cutting the board, the separator comprising:

a panel fastened to a support, the panel comprising a pair of lengthwise edges connected by a pair of widthwise edges, the panel is removably secured to the support;

a pair of blocks over and extending upwardly from the lengthwise edges of the panel, the blocks having curved upper surfaces and being configured to support the board while leaving the integrated circuit chip components extending between the upper surfaces of the blocks and the panel;

a cutting mechanism configured to cut the board while the board is supported on the blocks and to thereby separate the integrated circuit packages from one another; and

a pair of actuators, each actuator configured for driving a plate positioned beneath the support, the plates being moveable to vertically displace the support, each actuator comprising release values configured to equilibrate a back-pressure of the actuator to ambient prior to and during movement of the support.

11. The separator of claim 10 wherein the panel comprises an uppermost planar surface that extends continuously between the lengthwise and widthwise edges leaving no openings between the lengthwise and widthwise edges.

12. The separator of claim 10 wherein the pair of blocks extends at a height from the lengthwise edges of the panel, and wherein the height is approximately equal to a thickness of the integrated circuit chip components.

13. The separator of claim 10 wherein the panel comprises an uppermost planar surface that extends continuously between the lengthwise and widthwise edges leaving no openings between the lengthwise and widthwise edges, and wherein the pair of blocks extends at a height from the lengthwise edges of the panel, and wherein the height is approximately equal to a thickness of the integrated circuit chip components.

14. The separator of claim 10 wherein the pair of blocks extends at a height from the lengthwise edges of the panel, and wherein the height is approximately 0.040 inches \pm 0.005 inches.

15. The separator of claim 10 wherein the pair of blocks extends at a height from the lengthwise edges of the panel, and wherein the height is approximately 0.140 inches \pm 0.005 inches.

16. The separator of claim 10 wherein the panel comprises an uppermost planar surface that extends continuously between the lengthwise and widthwise edges leaving no

9

openings between the lengthwise and widthwise edges, and wherein the pair of blocks extends at a height from the lengthwise edges of the panel, and wherein the height is approximately equal to a thickness of the integrated circuit chip components, and wherein the panel is removably secured to the support with screws.

17. The separator of claim 10 wherein the panel comprises an uppermost planar surface that extends continuously between the lengthwise and widthwise edges leaving no openings between the lengthwise and widthwise edges, and

10

wherein the pair of blocks extends at a height from the lengthwise edges of the panel, and wherein the height is approximately 0.140 inches \pm 0.005 inches., and wherein the panel is removably secured to the support with screws.

18. The separator of claim 10 wherein the panel is removably secured to the support with screws.

19. The separator of claim 10 wherein the panel is removably secured to the support with rivets.

* * * * *