

(19) AUSTRALIAN PATENT OFFICE

(54) Title
Mask with gusset

(51)⁶ International Patent Classification(s)
A61M 16/06 20060101AFI2005100
 (2006.01) 8BMEP
 A61M 16/06 PCT/AU01/00746

(21) Application No: 2001267133 (22) Application Date: 2001.06.22

(87) WIPO No: W001/97893

(30) Priority Data

(31) Number	(32) Date	(33) Country
60/293,992	2001.05.30	US
60/213,251	2000.06.22	US
60/219,618	2000.07.21	US
		20070405

(43) Publication Date : 2002.01.02
 (43) Publication Journal Date : 2002.03.21

(71) Applicant(s)
ResMed Ltd.

(72) Inventor(s)
Gunaratnam, Michael Kassipillai, Frater, Robert Henry, Drew, Joanne

(74) Agent/Attorney
Halford & Co, GPO Box 4212, Sydney, NSW, 2001

(56) Related Art
US 5921239
US 5649532
US 5074297

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number
WO 01/97893 A1

(51) International Patent Classification⁷: A61M 16/06, A62B 18/08

(21) International Application Number: PCT/AU01/00746

(22) International Filing Date: 22 June 2001 (22.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/213,251	22 June 2000 (22.06.2000)	US
60/219,618	21 July 2000 (21.07.2000)	US
Not furnished	30 May 2001 (30.05.2001)	US

(71) Applicant (for all designated States except US): RESMED LTD. [AU/AU]; 97 Waterloo Road, North Ryde, NSW 2113 (AU).

2070 (AU). DREW, Joanne [GB/AU]; 2/1 Beatty Street, Balgowlah Heights, NSW 2093 (AU). GUNARATNAM, Michael, Kassipillai [AU/AU]; 3 Keiley Street, Marsfield, NSW 2122 (AU).

(74) Agents: DAVIDSON, Geoffrey, Robert et al.; Halford & Co., Level 7, 1 Market Street, Sydney, NSW 2000 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TL, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CR, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


{Continued on next page}

(72) Inventors; and
(75) Inventors/Applicants (for US only): FRATER, Robert, Henry [AU/AU]; 21a Napier Street, Lindfield, NSW

(54) Title: MASK WITH GUSSET



WO 01/97893 A1



(57) Abstract: A mask system for delivering air to a user includes a suspension mechanism (32) to allow relative movement between a face-contacting cushion (30) and a mask shell (20). The suspension mechanism also provides a predetermined force to the cushion that is a function of mask pressure, displacement of the cushion or both.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations," appearing at the beginning of each regular issue of the PCT Gazette.

MASK WITH GUSSET

This invention relates generally to masks for use in respiratory therapy. One use is in CPAP treatment of Obstructive Sleep Apnea. However, the mask arrangements presented herein are useful in other types of respiratory therapy. In the quest for an improved mask arrangement for respiratory therapy, there are various design objectives – effectiveness of seal between the mask and the patient's face, good compliance with a prescribed therapy regime, and patient comfort. The present invention provides various embodiments of a novel mask arrangement, which offers several distinct advantages over known mask arrangements.

BACKGROUND

In respiratory therapy where air is delivered to the mask under pressure, it is important to maintain a good seal between the mask and the patient's face. Leaks between the mask and the patient's face can reduce the desired air pressure in the mask and create increased noise. Both can reduce the effectiveness of, and compliance with, the therapy. In the first instance, the prescribed treatment parameters are not being maintained. In the latter, the increased noise can disrupt the sleep cycle of both the patient and the patient's bed partner.

Leaks are especially prone to occur as the patient moves during the night. Drag and movement of the air delivery tube or the mask system as the patient turns or moves can alter the positioning and alignment of the mask with respect to the patient's face, which movement can be translated or transferred to the cushion seal, creating leaks. Thus, while the mask may initially be leak free when attached to the patient, leaks are prone to develop later in the night as the patient moves in bed, awakening the patient. Hence, patients may tighten straps more than is necessary for pressure requirements in order to reduce or prevent leaks that result from movement.

Many different mask systems are known. One broad group of known mask systems include a rigid shell, a face-contacting cushion and headgear. The shell typically encompasses the nose or nose and mouth. Some known shells encompass the entire face. The cushion is typically constructed from a soft material such as silicone.

5 A headgear provides a means to secure the mask in position. One known form of headgear consists of an arrangement of straps.

Certain mask designs have been developed to increase the flexibility of the mask cushion to enhance patient comfort while maintaining an effective seal between
10 the mask and the patient. The Bubble Cushion (a registered trademark of ResMed, Ltd.) Mask, covered by US Patent No. 5,243,971, the subject matter of which is incorporated herein by reference, uses a flexible cushion membrane attached to a mask shell and the pressure inside the mask system to assist in the seal of the cushion membrane itself against the skin or face of the user.

15

The ResMed Mirage (a registered trademark of ResMed, Ltd.) Mask System, is covered by, inter alia, US Patent No. 6,112,746, the subject matter of which is incorporated herein by reference, has a contoured, three-dimensionally shaped cushion having an outer face-contacting membrane spaced apart from an inner frame rim to
20 both assist in the seal and increase the comfort of the patient. Neither of these masks incorporates an expanded gusset section for mounting the cushion to the mask to assist in sealing the mask to the patient (user).

25

A known fitting procedure with a known mask has been to supply the maximum air pressure to the mask that will be supplied to the mask during the therapy and to adjust the strap tension to the necessary level to prevent leaks at that maximum air pressure. However, in many therapy regimens, this maximum air pressure is often encountered only during a portion of the duration of the therapy and the mask air pressure is lower at other times during the therapy. Such is the case, for example,
30 when using auto-titrating or variable pressure systems or during ramp-up when using CPAP systems. Thus, the strap tension is higher than necessary during significant portions of the therapy duration. Further, since leaks are disruptive of both the

sleeping cycle and the prescribed therapy regimen, patients will often tighten the straps even more than is necessary to prevent leaks at the maximum encountered air pressure. In known masks, this higher than necessary strap pressure directly results in a higher than necessary force of the mask cushion on the patient's face, particularly as the pressure goes below the maximum mask air pressure.

See Figure 1, which shows a force diagram for a known mask 110 having a cushion 130 attached to a rigid shell 120. The cushion 130 includes a face-contacting portion 134 attached to a cushion sidewall 173. The cushion sidewall 173 can be 5 relatively flexible, as in the ResMed Bubble Cushion® mask, or relatively rigid, as in the ResMed Mirage® mask. Although the mask 110 would be in contact with the face 42 of a patient 40 (shown in phantom) in use, for purposes of clarity in this diagram 10 (as well as the diagram of Figure 10), a flat foundation 43 is substituted for the patient's face 40. The total force of prior art masks on the user's face F_m has been 15 found empirically to be given by the equation $F_m = F_c + F_{Ac}$, where F_c is the force of the cushion on the patient's face and F_{Ac} is the force on the patient's face of the mask air pressure P inside of the perimeter of A_c , the area of contact of the cushion with the patient's face. The force F_{Ac} is given by the equation $F_{Ac} = PA_c$. Since the force F_c is distributed around A_c and is not merely located at two points on the cushion, as it 20 might seem due to the limitations of the two-dimensional representation of Figure 1, this force is shown in parentheses. Although A_c is shown inward of the sidewall 173 as would be the case if the mask 110 had just been brought into contact with the user's face with a minimal contacting force, in practice, the face-contacting portion 134 tends to roll under when sufficient force is applied to the mask 110 to seal the mask to 25 the user's face such that A_c can expand outward, toward the sidewall 173.

The force (tension) in the headgear strap F_s for the prior art mask has been found empirically to be given by the equation $F_s = (F_c + F_{Ac})/(2\cos\theta)$, where θ is the angle of the head strap with respect to the mask 110. Thus, the force of the cushion on 30 the patient's face F_c is given by the equation $F_c = 2F_s\cos\theta - F_{Ac}$. The force of the mask cushion on the patient's face is difficult to distribute completely evenly around the cushion in known masks, especially at higher forces, and results in localized high

pressure spots around the mask cushion. This higher force on the face, and especially the localized high pressure spots, are uncomfortable to the patient and can disrupt the sleep cycle. See, for instance, Figure 2, which charts the force required to secure a mask on a face versus the air pressure in the mask (measured in centimeters H₂O). As 5 seen there, the force required to maintain a known mask sealed to the face throughout a mask air pressure range is most substantially affected by the maximum air pressure in the mask that will occur during therapy. That is, the force of the mask on the face remains at a fairly high level even when the pressure in the mask drops and this force of the mask on the face is directly related to the force necessary to seal the mask at the 10 maximum mask air pressure. Misalignment of the mask will move the curve upward as higher forces are required to seal the mask to the face in light of the misalignment.

This force on the face increases as the head straps of a known mask are tightened to increase the sealing force of the mask, and thereby compressing the 15 cushion and bringing the shell of the mask closer to the patient's face. When the straps are tightened, the shell of the mask moves a distance X between a position X₀ when a seal is first obtained to a position X_p when it reaches the point where the cushion is being compressed beyond its normal range. The mask shell may be able to move beyond X_p but the cushion tends to become rigid or nearly so at about X_p, thereby 20 limiting further travel. In a known mask, F_c generally increases at a first rate (i.e., the slope of the curve) as the mask moves toward the patient's face within a given range of X. This first rate occurs within the range of flexibility of the face-contacting portion 134. This first rate is also a function of the pressure in the mask acting on a back side 134 of the face-contacting portion 134 of the mask. Thus, as the pressure in the mask 25 increases, the first rate also increases within the given range of X.

However, the known cushion becomes less flexible as it is further compressed beyond such range of X. In a mask having a more flexible sidewall, as discussed above, F_c will then increase at a faster rate as the mask moves toward the patient's 30 face due to a spring-force imparted by the sidewall until such point as the sidewall is nearly completely compressed and directly passing on the force from the rigid mask shell to the face. In a mask having a more rigid sidewall, as discussed above, F_c will

then increase at an even faster rate for a short distance as the mask moves toward the patient's face but will quickly reach a point where the rigid sidewall is directly passing on the force from the rigid mask shell to the face.

5 See Figure 3, which charts the force required to secure a mask on a face versus the movement of the mask frame (shell) from a relaxed positioned toward the face. The solid curve of Figure 3 shows the force on the face for a known mask, such as the ResMed Mirage® mask, at a mask air pressure of 10 cms H₂O. It can be seen from this curve that the force on the face increases in generally linear proportion to the 10 movement of the mask towards the face within the range of flexibility the cushion 130. However, at such point where the cushion is nearly completely compressed (at approximately 5-7 mm in Figure 3) so that the generally rigid sidewalls of the cushion 130 begin directly transferring the force from the rigid shell 120 to the face, the force on the face increases dramatically as the mask shell moves toward the face.

15

U.S. Patent Nos. 5,492,116 and 5,655,527 to Scarberry disclose a full-face respiratory mask. The mask includes a flexible seal member 18 directly attached to a mask shell 12 and is attached to the user's head by head gear 24. The flexible seal member 18 itself contacts the user's face with a broad area of contact and maintains a 20 seal with the user's face through pressure in the space 62 acting directly upon seal membrane inner surface 54.

Japanese Provisional unexamined patent application (Laid-open Kokai) published January 6, 1999 entitled NASAL MASK FOR RESPIRATION, Provisional 25 Publication No. 11-397 discloses a bellows-formed elastic body between a mask shell and cushion. As seen in the figures of that publication, the bellows portion of the mask projects an area over the patient's face that is substantially the same as the contact area defined by the line of contact of the mask cushion with the patient's face. This publication teaches nothing about the relationship between the area of the 30 bellows and the force applied to the patient's face. Although the bellows provides limited mechanical flexibility, no significant pressure advantages or significant mechanical flexibility can be achieved. This mask does not overcome the sealing

problems incurred by movement of the mask with respect to the patient's face without utilizing an increased head strap pressure across the mask air pressure operating range.

SUMMARY OF THE INVENTION

5

In one aspect, the invention provides a mask system including a shell which in use is positioned in a predetermined position relative to a patient's face, a face-contacting cushion which in use transfers a force to the patient's face, and a means for permitting relative movement between the cushion and the shell wherein said means 10 provides a predetermined force on the cushion. In one form, the predetermined force is a function of mask pressure. In another form, the predetermined force is a function of the displacement of the shell relative to the face. In another form, the predetermined force is a function of both mask pressure and displacement of the shell relative to the face. In another form, the predetermined force is independently controlled. In another 15 form, the means for permitting relative movement between the cushion and the shell is provided by a gusset section positioned in-between the shell and the cushion.

In one aspect, the invention provides a mask system including a face-contacting cushion having a first projected area on the face, a mask shell and a gusset 20 section therebetween, the gusset section having a second projected area on the face wherein the second projected area is greater than the first projected area by greater than approximately 30%.

In another aspect the invention provides a mask system for use at a mask 25 pressure including headgear coupled to a shell which exerts forces on the shell and a face-contacting cushion which transfers forces to the face, constructed and arranged so that the force transferred from the face-contacting cushion to the face is a strong function of mask pressure. The greater projected area of the gusset arrangement with respect to the face contacting area of the cushion uses the air pressure in the mask to 30 expand the gusset into contact with the patient's face, even when the mask shell changes alignment with the patient's face, to provide a more secure seal between the mask and the patient. The expansion, contraction and bending of the gusset allows for

enhanced mechanical flexibility over known mask arrangements that helps to maintain a seal even when the patient moves significantly during sleep and the position of the mask with respect to the patient's face changes. Thus, the force of the mask on the face is most significantly proportional to the mask air pressure and the cushion is 5 maintained in secure sealing contact with the patient's face by the mask air pressure over a broader range of positioning of the mask with respect to the patient. This allows for the tension in the straps of the headgear to be generally less than with a known mask to securely seal the mask to the patient's face, especially at mask air pressures below the maximum mask air pressure for the therapy, providing greater 10 patient comfort and compliance with the prescribed respiration therapy regime.

While some membrane-type cushion mask arrangements accommodate limited relative movement between the cushion and the wearer's face while maintaining a tolerable seal, the present invention dramatically increases the level of 15 accommodation without a corresponding increase in the head strap pressure used to secure the mask to the patient. The gusset section provides a flexible component between the mask shell and the cushion in contact with the user's face while reducing the tension required in the headgear to maintain the seal.

20 Other embodiments of the present invention provide new mask cushion configurations that assist in maintaining the seal between the mask cushion and the user's face.

Another embodiment of the present invention includes the use of a novel baffle 25 element positioned within the interior space of the mask arrangement. The employment of a baffle member within the mask of the present invention minimizes short-circuiting of the intake gas directly to the exhaust vent with the resulting buildup of carbon dioxide. Thus, the baffle serves to reduce the functional dead space of the mask and reduce the level of carbon dioxide rebreathing by the patient.

30 With the foregoing in mind, other objects, features and advantages of the present invention will become more apparent upon consideration of the following

description and the appended claims with reference to the accompanying drawings, all of which form part of this specification, wherein like reference numerals designate corresponding parts in various figures.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a force diagram for a known mask;

Figure 2 charts the force required to secure both known and present invention
10 masks on a patient's face versus the air pressure in the mask;

Figure 3 charts the force required to secure both known and present invention
masks on a patient's face versus the movement of the mask shell from a relaxed
positioned toward the patient's face;

15

Figure 4 shows a side elevational view of a mask of the present invention;

Figure 5 shows a perspective view of the mask of Figure 4;

20

Figures 6-7 are partial sectional views of the gusset portion of the mask of
Figure 4 before and after inflation;

Figure 8 is an end elevational view of a mask shell side of the gusset portion of
the mask of Figure 4;

25

Figure 9 is a partial sectional view of the cushion of the mask of Figure 4;

Figure 10 shows a force diagram of the mask of Figure 4;

30

Figure 11 is a perspective view of a mask of the present invention attached to a
patient using strap-based headgear;

Figure 12 is a partial sectional view of an alternative embodiment of the gusset portion of the present invention;

5 Figure 13 is a partial side elevational view of an alternative embodiment of the gusset portion of the present invention;

Figure 14 is a partial sectional view of an alternative embodiment of the gusset portion of the present invention;

10 Figures 15-18 show sectional views of alternative embodiments of the mask of the present invention in contact with a patient's face;

15 Figure 19 diagrams the key characteristics, principal advantages and patient benefits deriving from the present invention and leading to increased therapy compliance by the patient;

Figure 20 shows an elevational view of the interior of the mask shell of one embodiment of the present invention;

20 Figure 21 shows a diagrammatic view of an alternative embodiment of the present invention;

Figure 22 shows a diagrammatic view of an alternative of the embodiment shown in Figure 21;

25 Figure 23 shows a partial sectional view of one alternative of the embodiment of Figure 21;

Figure 24 shows a partial sectional view of another alternative of the embodiment of Figure 21; and

Figures 25-30 show partial sectional views of alternative embodiments of a mask cushion of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

5

A first embodiment of the respiratory mask 10 of the present invention is shown in Figures 4-9. The mask 10 includes a generally rigid shell 20 having an air tube 22 for connecting to a pressurized air supply 23. A gusset portion 32 is attached to the shell 20 in a known manner such as gluing or mechanical fastening. The gusset portion 32 acts as a suspension mechanism for a cushion 30 and includes a flexible gusset sidewall 33. A partial sectional view of the gusset portion 32 is shown in Figure 6. In this embodiment, the gusset sidewall 33 has a generally uniform thickness and the gusset portion 32 has a generally triangular cross-section when not exposed to mask pressure. However, in this embodiment, the flexible sidewall 33 will balloon out when the mask 10 is pressurized to take on the more rounded cross-section shown in Figure 7. The Figure 8 end view of the gusset portion 32 shows that the gusset has a generally triangular outline to conform with the shape of the cushion 30 and shell 20.

Cushion 30 includes a face-contacting portion 34 that is adapted to engage the face 42 of a patient (user) 40 as shown in Figure 10. The face-contacting portion 34 of the cushion 30 can be in the form of a standard cushion, such as the ResMed Standard Cushion, or can be in the form of the prior ResMed Bubble Cushion® and Mirage® cushions discussed above or in another form as the circumstances warrant. In the preferred embodiment, shown in a partial sectional view in Figure 9, the cushion 30 of the present invention incorporates an outer membrane 70 that acts as the face contacting portion 34 and an inner rim 72 that provides a backing element for the membrane 70, as does the ResMed Mirage® mask. Both the outer membrane 70 and the inner rim 72 are connected to a relatively rigid sidewall 73 that connects with the flexible gusset portion 32. In a worn position, the mask encompasses the nares of the patient and provides a seal around the nose 44. In alternative embodiments, the mask can also enclose both the nose 44 and the mouth of the patient, just the mouth of the patient or the entire face. A headgear 50 (see Figure 11) having adjustable tensioning

straps 52 engages the shell 20 and is used to secure the mask 10 to the patient 40. In the preferred embodiment of the present invention, the headgear and tensioning straps are adjustable as to size but relatively inextensible once adjusted. Mask shell 20 includes an exhaust vent 21 for exhausting gases from the mask and a baffle 23 which 5 will be discussed in further detail below.

The gusset portion 32 includes two key characteristics that provide the benefits of one embodiment of the present invention. The first key characteristic of the gusset portion 32 is that it utilizes the pressure in the mask acting on its increased surface 10 area to provide the primary force for maintaining the face-contacting portion of the cushion in sealing contact with the user's face. The second key characteristic of the gusset portion is that it provides a decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20, thus allowing some relative movement between the mask and the user's face. This arrangement substantially 15 protects the seal from undue disturbance in the following scenarios: 1) displacement or tilting of mask shell or harness; 2) relaxation of the facial muscles; 3) movement of the patient; and/or 4) movement of the tube. Figure 11 shows one embodiment of the mask of the present invention attached to a patient.

20 Figure 10 shows a force diagram representative of the mask embodiment shown in Figures 4-9 (as well as various alternative embodiments of the present invention discussed below). Figure 10 shows A_c , the area of contact of the cushion with the patient's face and A_g , the area defined by the gusset portion 32, for the present invention mask.

25 The area A_g is a projected area on the user's face (i.e., projected on a plane normal to an axis of the mask) of an interior of the gusset portion 32 exposed to the mask air pressure. In the embodiment shown in Figures 4-10, A_g extends to the outermost interior surface of the sidewall 33 of the gusset portion 32 and includes A_c . 30 As can be seen, the addition of the gusset portion 32 to the mask 10 results in an area A_g being significantly greater with respect to the area A_c than is found in either the

prior ResMed® masks (see Figure 1) or the mask disclosed in Japanese Provisional Publication No. 11-397, discussed above.

The significance of this can be seen from the following. In one form of the invention, the total force of the mask on the face F_m is given by the empirical equation $F_m = F_c + F_{A_c} = P(A_g - kX) = 2F_s \cos\theta$. The force of the cushion on the patient's face F_c is given by the empirical equation $F_c = P(A_g - A_c - kX)$. The force (tension) in the headgear strap F_s is given by the empirical equation $F_s = P(A_g - kX)/(2\cos\theta)$, where k is the spring constant for the elasticity of the gusset portion and X is the amount of travel of the mask shell toward the face. Figure 10 also shows X_p , the working travel range of the gusset portion 32, although in practice, if the pressure in the mask pushes the face-contacting portion 34 away from the shell 20, X_p can be longer than is shown when the gusset is at rest.

Although k is usually not affected by pressure with respect to a purely mechanical spring, it has been found that within the pressure ranges occurring in the mask of the present invention, that k is proportional to both pressure and distance traveled. Thus, while in the present invention, the maximum force on the face F_m that could be expected to be exerted within X_p would be PA_g , testing has shown that this is reduced by the k factor which is both proportional to pressure in the mask and distance travelled.

For a prior art mask configuration, it is seen from Figure 1 that the force in the headgear strap $F_s = (F_c + PA_c)/(2\cos\theta)$. For the present invention mask, it is seen from Figure 10 that the force in the headgear strap $F_s = P(A_g - kX)/(2\cos\theta)$. The area defined by the gusset A_g is substantively larger than the area in contact with the face A_c . Therefore, at the point at which the cushion touches the face (the theoretical initial seal point when both $F_c = 0$ and $X = 0$), the force in the straps for the known mask will be $PA_g/(2\cos\theta)$ as opposed to $PA_g/(2\cos\theta)$ for the present invention mask. However, in reality, a contact force F_c greater than zero is required to: 1) maintain the seal between the face and the cushion because the profiles of the face and cushion are not perfectly matched, and 2) maintain this seal during movement of the face relative to

the shell. This force is balanced by the tension in the headgear straps in the known mask system and balanced by the pressure acting upon the gusset area alone, $A_g - A_c$, in the present invention mask system. Thus, within the normal operating mask air pressure range, and especially at lower operating mask air pressures, it has been found
5 that the headgear tension F_s is lower in the present invention mask system.

From Figure 10, it can also be seen that for the present invention mask, the contact force between the cushion and the face is proportional to the mask pressure, $F_c = P(A_g - A_c - kX)$. This has significant implications in therapies where the mask air
10 pressure varies during either the course of a breath or breath-to-breath or to meet other therapeutic needs. With known mask configurations, where the force of the cushion on the face varies little, if at all, with respect to the pressure in the mask, the tension in the straps must be set sufficiently high at low pressures such that the contact force of the cushion on the face is sufficient to maintain the seal with the face when higher
15 pressures are reached.

For the present invention configuration, both the cushion contact force and the strap tension are significantly affected by the pressure in the mask due to the significantly increased area of the gusset. Therefore, as they both are most
20 proportional to the pressure in the mask, they both will be significantly lower at low pressures and increase as the pressure reaches higher pressures.

In fact, in practice, it has been found that this holds true even at maximum mask air pressures. As an example, assume that A_c is the same in both a known mask
25 (as, for instance, the ResMed Mirage® mask) and the inventive mask (both using, say, the same configuration in the face-contacting portion of the cushion). F_{Ac} would be the same in both cases. Then you might expect that given proper alignment of both masks, the minimum necessary F_c for sealing the masks at a given pressure would be the same in both the known and inventive masks and thus, the required F_m to seal at a
30 given pressure to be the same in both cases. However, testing has shown that the present invention mask will seal at a lower force on the cushion, a lower force on the face, and a lower tension in the straps, even at the maximum mask air pressure, than

the known mask. It is believed that the test results reflect the real world situation. That is, no face is identical and exactly conforms to the cushion and further, that it is extremely difficult to maintain exact alignment of the mask with the face. This is even more the case with older and/or overweight patient that have loose skin, wrinkles and/or skin folds that hamper the sealing of the mask to the face. Testing has shown that the present invention mask is better able to accommodate these inconsistencies from user to user and provide better sealing performance at lower forces on the face (even at the maximum mask air pressure) than the known mask.

10 See also the chart in Figure 3 that shows a comparison of the present invention mask and known masks with respect to the force on the face as the mask shell moves toward the face. As long as the present invention is within the range X_p of the gusset, there is no sharp increase in the force on the face as with the known masks as the mask shell approaches the face. Beyond X_p , the force on the face will increase more dramatically, as happens with the known mask, so it is desirable when adjusting the headgear to bring the face contacting portion of the cushion only near or in very light contact with the face. In this way, the gusset is not compressed substantially so that in use the mask is still within the X_p range. This is possible because the seal is maintained by the pressure in the mask and not by compression of the cushion by the headgear. Adjustment of the headgear and mask is thus much simpler than in the known masks. While the range of X_p can be varied for different patients and therapies by varying the size and shape of the gusset section, it has been found that an X_p of between 10-30 mm has been effective. It is noted that the curves shown in Figure 3 are for a mask air pressure of 10 gf/cm² (grams force/centimeter²) These curves can be expected to rise and lower as the mask air pressure is increased and decreased, respectively, but will generally maintain the same shape within the operating pressure range of the mask.

30 In one embodiment of the present invention shown in Figures 4-9, the gusset and cushion are integrally molded of Silastic® 94-595 HC Liquid Silicone Rubber from Dow Corning®, the gusset sidewall 33 has a uniform thickness of 0.5 mm, the gusset has a long length (of the generally triangular A_g) of approximately 105 mm and

the long length of the generally triangular A_c is approximately 71 mm. The X_p is approximately 25 mm. Thus, the gusset (A_g) extends generally beyond the face-contacting portion of the cushion (A_c) by approximately 17 mm on each side. This provides for approximate figures for the A_c of 31.5 cm^2 , the A_g of 75 cm^2 , a gusset 5 only area ($A_g - A_c$) of 43.5 cm^2 and an A_g/A_c of approximately 2.4 (or 240%). These dimensions can be altered for different force relationships as desired, but in the preferred embodiments, A_g/A_c will be in the range of about 1.30-5.00 and desirably in the progressively narrowing ranges of 1.50-5.00, 2.00-4.00, and 2.25-3.50, but can be adjusted to fall within any range within the overall range of 1.30-5.00 or even within a 10 range extending beyond that range if circumstances warrant. This compares with an estimated A_g/A_c for the mask example disclosed in Japanese Provisional Publication No. 11-397 discussed above of approximately 1.08.

In the preferred embodiment of the mask, the total force applied to the face F_m 15 is approximately constant at between 35 to 108 grams per gf/cm^2 mask air pressure, preferably between about 40 to 88 grams per gf/cm^2 mask air pressure and most preferably between about 50 to 88 grams per gf/cm^2 mask air pressure. The force applied by the surface area in contact with the face F_c is maintained at an approximately constant proportion to the mask air pressure being delivered to the user 20 and is maintained between about 8 to 61 grams per gf/cm^2 mask air pressure, preferably between about 27 to 61 gms per gf/cm^2 mask air pressure and most preferably between about 40 to 61 grams per gf/cm^2 mask air pressure over a mask air pressure range of 4 to 25 gf/cm^2 . The force F_c is also maintained within a range of about 0.3 – 4 grams per gf/cm^2 pressure of the supply of pressurized breathable gas 25 per linear centimeter around a circumference of the cushion in contact with the user's face, preferably within a range of about 0.5 – 4 grams per gf/cm^2 pressure of the supply of pressurized breathable gas per linear centimeter around a circumference of the cushion in contact with the user's face, more preferably in a range of about 1 – 3 grams per gf/cm^2 pressure of the supply of pressurized breathable gas per linear 30 centimeter around a circumference of the cushion in contact with the user's face, and most preferably in a range of about 1.5 – 3 grams per gf/cm^2 pressure of the supply of pressurized breathable gas per linear centimeter around a circumference of the cushion

in contact with the user's face over a mask air pressure range of 4 to 25 gf/cm².

Although the preferred force ranges for the various forces are set forth in this paragraph, it should be recognized that the force ranges can be set between any two points within the respective overall force ranges given. It is noted that in the industry 5 of the present invention, most pressure measurements are given in centimeters water and that 1 centimeter water = 1 gf/cm² = 98.07 Pascals.

The gusset portion also allows the mask to maintain a seal with the patient's face over a range of about plus or minus 8° out of alignment with the patient's face.

10

It has also been found that the shape of the curve for the inventive mask shown in Figure 3 can be varied by altering the cross-section of the gusset or by providing a backstop for the gusset. Where the gusset has a very uniform thickness and curve, as shown in Figures 6 and 7, the curve for total force on the face versus movement of the 15 mask toward the face will be generally linear within X_p. It has generally been found desirable in testing to apply a higher sealing force earlier as the mask shell travels toward X_p. That is, it is advantageous to move from C, the minimum force to seal at the given pressure, toward D, the minimum force for the inflated gusset, earlier in the travel of the mask shell toward X_p. This provides a greater remaining amount of X_p 20 within which the mask will operate and a more gradual increase of the force of the mask on the face as the mask shell moves toward X_p within the remaining amount. The embodiments shown in Figures 12-14 help accomplish this goal.

In the first example, shown in Figure 12, the bases of the gusset sidewall are 25 thickened in an abrupt manner to stiffen the sidewall. In this embodiment, the force-displacement curve for the mask generally follows the curve for the cushion (i.e., the curve for the known mask shown in Figure 3) as it moves from C toward D and then a lower, generally linear slope until reaching X_p. See the long-dashed curve in Figure 3. However, changing the value for D can alter this curve. The value for D is calculated 30 by multiplying the area for the stiffened portion of the gusset sidewall by the pressure in the mask. The stiffened portion of the gusset sidewall is shown as A_s in Figure 10. If however, the value of A_s is increased by stiffening a greater portion of the gusset

sidewall, the value of D will increase. See the value for D' shown in Figure 3 and the short-dashed curve that corresponds to a mask embodiment where a greater portion of the gusset sidewall has been thickened (stiffened) to increase A_s . Thus, the long-dashed curve represents a gusset embodiment as shown in Figure 12 having an A_{s1} and the short-dashed curve represents a gusset embodiment as shown in Figure 12 having an A_{s2} greater than A_{s1} . It can be seen from Figure 3 that the gusset embodiment having the A_{s2} has reached the value D' much sooner as the mask shell moves toward X_p than the gusset embodiment having the A_{s1} , thereby leaving a greater remaining amount of the range X_p within which the mask shell can move in use.

A similar effect can be obtained by adding rigid backstops to the embodiment of Figures 6 and 7. See Figure 13, which shows an embodiment where rigid backstops 35 are attached to one or both of the gusset portion 32 and the shell 20. The rigid backstops contact the sidewalls of the gusset in the inflated mode and act as stiffeners to the portions of the sidewall that are contacted. Thus, the rigid backstops can provide the same effect as the embodiment of Figure 12. The backstops 35 can be placed on one or both sides of the gusset portion and can extend around either a portion, or all, of the perimeter of the gusset portion, as is necessary to provide the desired curve. The backstops can be made of the same material as the mask shell 20 and in one embodiment, one or both backstops 35 can be molded integrally with the shell 20. In alternative embodiments, the configurations shown in Figures 6, 7, 12, 14 and 16 can be used in combination with one another, i.e., one configuration on one side of the gusset and another configuration on the other side of the gusset, to specifically tailor the force/travel curve as desired. The thicknesses and dimensions of the various embodiments can also be altered to specifically tailor the force/travel curve. This ability to readily and specifically tailor the force/travel curve of the mask by altering gusset configurations and dimensions is another unique and advantageous aspect of the present invention.

30

Where the gusset has sidewalls having a tapered thickness, as shown in Figure 14, the resulting force-displacement curve will lie between the curve for the

embodiment of Figure 6 and the curve for the embodiment of Figure 12 (assuming comparable gusset base and intermediate thicknesses for the two embodiments).

The gusset portion need not be in the single gusset form discussed above, but 5 can have alternative configurations, examples of which are shown in Figures 15-18, along with the A_c and A_g for each example.

Figure 15 shows an alternative embodiment of the mask 10 where the gusset portion 32 is in the form of a double gusset providing the decoupling joint between the 10 face-contacting portion 34 of the cushion 30 and the mask shell 20. Of course, three or more gussets can be used in alternative embodiments of the gusset portion 32. Figure 16 shows an alternative embodiment of the mask 10 where the gusset portion 32 is in stepped form to provide the decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20. While three steps are shown in Figure 16, one 15 or more steps can be used in alternative embodiments. One advantage of this embodiment of gusset is the ease in molding the gusset portion 32 and cushion 30 together, since the shell side of the gusset portion 32 is completely open, i.e., there are no hidden surfaces. Figure 17 shows an alternative embodiment of the mask 10 where the gusset portion 32 is in the form of a piston 54 at the base of the cushion 30 axially 20 slideably engaged with a cylinder portion 56 of the shell 20. The piston 54 can thus move the cushion 30 in and out of the shell 20 to provide a decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20. A stop 58 can be provided on the shell 20 to prevent the piston and cushion from completely 25 disengaging with the shell 20 under pressure. A spring 60 can optionally be provided to push the piston 54 back into the shell 20 when the air pressure in the mask is decreased. The existence of the spring also simulates the elastic resistance of the gusset portions discussed above and adding a kX factor to the F_m equation. Without the spring, k would equal 0 within the range of movement of the piston.

30 Yet another alternative mask configuration is shown in Figure 18 which includes a gusset portion 32 having a larger upper barrel shaped gusset 78 and a lower smaller barrel shaped gusset 80. Alternatively, the larger and smaller gussets can be

reversed, made the same size or even given different configurations to custom tailor the force characteristics.

Figure 21 shows an alternative embodiment of the mask of the present invention wherein the gusset portion 32 has a flexible sidewall 33 having a generally circular or round cross-section enclosing a gusset chamber 190 having an interior volume separated from an interior 192 of the mask shell 20. In one version of this embodiment the gusset chamber 190 can be connected to the mask shell interior 192 through at least one port 193 in the sidewall 33. See Figure 23. In such a case, a pressure P_2 in the gusset chamber will be the same as a pressure P_1 in the interior of the mask shell, the effective area of the gusset portion 32 A_g will extend to the outermost interior surface of the gusset sidewall 33, and the gusset portion will operate similarly to the embodiment shown in Figure 10. However, in a preferred version of this embodiment, the interior of the gusset chamber 190 is connected through a port in the sidewall 33 to a separate pressurized supply of gas than is connected to the mask shell interior so that the pressure P_2 in the gusset chamber 190 can be controlled to be at a different pressure than the pressure P_1 in the mask shell interior 192. Thus, the force imparted by the gusset portion will be a product of the pressure P_2 and the area of the gusset portion. Further, in this embodiment, the area of the gusset portion is no longer determined by the outermost interior surface of the gusset sidewall as in the previous embodiments, but will be the projected area of the entire gusset chamber 190, including the area of the gusset chamber radially inward from the cushion sidewall. This area of the gusset chamber A_{gc} is shown in parentheses in Figure 21. This provides a high degree of flexibility in controlling the gusset portion and the mask.

First, if additional sealing force is needed from the gusset portion, the pressure P_2 can merely be increased, or vice-versa if less sealing force is needed. Second, since the force imparted on the cushion by the gusset portion is a product of the pressure P_2 and the area of the gusset portion A_{gc} , the area A_{gc} is less critical than in the previous embodiments because it can be offset by changes in the pressure P_2 . For instance, the outer periphery of the gusset portion can be made smaller in this embodiment than in

the previous embodiments because an interior portion of the gusset portion is now also adding to the pressurized area of the gusset portion. Further, the area A_{g2} of the gusset chamber can be varied as desired, and especially made smaller, by varying the pressure P_2 . This allows the mask to be made smaller, as compared to the other masks discussed above, to be less intrusive and more comfortable to the patient.

The pressure P_2 can be controlled to be in relatively constant proportion to P_1 or can be controlled to be in varying proportion to P_1 as the circumstances warrant. While it is currently believed that in most therapies, P_2 will be greater than P_1 for 10 most, if not all, of the therapy, it is contemplated that in certain situations, controlling P_2 to be less than P_1 can be desirable. In some instances, it is contemplated that P_2 be held constant. The gusset chamber in this embodiment is intended to be connected only to the second pressurized gas supply and otherwise be closed, especially to the atmosphere. Thus, there should be minimal leakage from the gusset chamber and the 15 second pressurized gas supply need only supply a small volume of gas, significantly less than the volume of gas that must be supplied for breathing purposes by the first pressurized gas supply. Further, the two separate pressurized gas supply sources for P_1 and P_2 can be provided by the same single gas pump and controlled by known control devices to be at the different desired pressures, or alternatively, two separate gas 20 pumps can be used for the gas supplies to the mask interior 192 and the gusset chamber 190, respectively, to separately control each of P_1 and P_2 .

The gusset chamber 190 can be connected to the second gas supply through a 25 port 194 in the gusset sidewall 33 connecting with a port 195 integrally molded with the mask shell 20 or can bypass the mask shell 20 and connect to the second gas supply through a port 196 in the gusset sidewall 33. See Figure 24, which shows both alternatives.

The embodiment of Figure 21 can have portions of the gusset sidewall 32 30 thickened/stiffened as discussed above with respect to Figures 12-14. However, the increased flexibility offered by controlling P_2 differently from P_1 means that the gusset sidewall can also be made generally uniform in thickness and a similar effect provided

by the stiffening in the previously described embodiments can be provided in this embodiment merely by altering the pressure P_2 as desired.

In an alternative embodiment of the mask shown in Figure 21, the gusset 5 portion 32 can have a generally diamond-shaped cross-section when the mask 10 is not in use or not pressurized, as shown in Figure 22, which cross-section can balloon to a generally circular cross-section when the gusset chamber is pressurized. Alternative shapes for the gusset portion 32 can also be used, including a piston/cylinder arrangement corresponding to Figure 17 discussed above.

10

The cushion can also have alternative configurations. See Figures 25-30, which show partial sectional views of the cushion 30. In each of these embodiments, the cushion 30 is provided with a flexible membrane 170 that acts as a face-contacting portion 134. The flexible membrane 170 is attached to the more rigid supporting 15 sidewall 173 of the cushion 30. These embodiments do not use an inner rim as does the embodiment shown in Figure 9. In each embodiment, the face-contacting portion 134 extends beyond an axially outer end 174 of the sidewall 173 when the cushion is at rest. The face-contacting portion 134 can move axially with respect to the sidewall 173 to alter an axial distance between the face-contacting portion 134 and the axially 20 outer end 174. That is, when a force is applied to the cushion toward the users' face, the face-contacting portion 134 will retract, axially moving toward the axially outer end 174 of the sidewall 173. The axially outer end 174 of the sidewall 173 will provide a generally positive end limit to this retraction when it contacts the user's face.

25

In the embodiments shown in Figures 25 and 26, the flexible membrane 170 is attached to the sidewall 173 at a position 175 axially inward from the axially outer edge 174, with a portion of the flexible membrane 170 extending axially outwardly alongside the sidewall 173 between the position 175 and the axially outer edge 174. In 30 these embodiments, axial movement of the face-contacting portion 134 is substantially provided by the flexibility of the flexible membrane 170. If a less rigid sidewall 173 is desired, for instance, to be more comfortable to the user when the axially outer edge

174 contacts the user's face, the sidewall 173 can have a hollow portion 176, especially between the position 175 and the axially outer edge 174. See Figure 26.

In the embodiments shown in Figures 27-30, the flexible membrane 170 is

5 connected to the sidewall 173 by a flexible connecting member 177 that provides for axial movement between the flexible member 170 and the sidewall 173. The flexible connecting member 177 can have a generally straight cross-section, as seen in Figure 27, a convoluted cross-section, as seen in Figure 28, or another cross-section. The flexible connecting member 177 can be attached to the sidewall 173 near the axially

10 outer end 174, as shown in Figures 27-29, or can be attached to the sidewall 173 at an axially inward position 175, as shown in Figure 30. As with the embodiment of Figure 26, the sidewall can be at least partially hollow to make the sidewall less rigid. See Figure 29. In the preferred embodiment, the flexible membrane 170, the flexible connecting member 177 and the sidewall 173 are integrally molded together.

15 Although the flexible membrane is shown as being attached to a cushion sidewall, it is contemplated that in alternative embodiments, the flexible membrane can be attached directly to the mask shell, with a portion of the mask shell acting as the axially outer edge 174.

20 The embodiments of Figure 25-30 can be used in conjunction with the gusset feature described above or can be used with known mask cushions. These embodiments provide good sealing characteristics with the face in a cushion that is easier and less expensive to manufacture than the known mask cushions. It is also to be understood that in the embodiments of Figures 27-30, the flexible connecting member can act similarly to the gusset feature described above when the mask is

25 pressurized. That is, the pressure in the mask will act on the flexible connecting member 177 to impart an additional force on the face-contacting portion 134 of the flexible membrane 170 and that additional force will have the same characteristics as described above with respect to the above-described embodiments. In the

30 embodiments of Figures 27-30, the area A_c would be measured the same as in the embodiments above and the area A_g would be measured to the interior surface of the sidewall 173 where the flexible connecting member 177 attaches to the sidewall 173.

Other alternative embodiments can use various combinations of any of the embodiments disclosed herein.

5 It should be recognized that the gusset portion of the present invention can be manufactured as a component separate from the cushion and mask shell but is attachable therebetween to provide the benefits described herein.

10 The reduced contact force, total force on the face and headgear tension across the mask air pressure range and especially at mask air pressures below the maximum mask air pressure improves patient comfort, in particular for auto-titrating devices which start therapy at low pressures at the beginning of the night when the patient is trying to get to sleep. The improved seal (which can be obtained with a lower contact force) reduces sleep disturbance to patients and partners by substantially reducing the 15 risk of leaks. The improved seal also increases the confidence of the patient in the seal, resulting in more comfortable therapy for the patient. See Figure 19, which diagrams how the key characteristics of the gusset portion of the present invention mask provide principal advantages leading to patient benefits and improved compliance with a prescribed therapy.

20 Another aspect of the present invention is the inclusion of the baffle 23 in the mask shell 20. The employment of the baffle in the mask shell 20 improves the movement of air within the mask. In the embodiment shown in Figures 4, 5 and 20, the baffle 23 is in the form of a flat plate disposed between the mask intake 22 and the 25 mask exhaust vent 21. The baffle 23 can extend into the mask generally horizontally or can tilt upward or downward. The baffle need not be in the form of a flat plate but can be V-shaped, curved, wavy or have some other configuration best designed to deflect air from the intake from directly flowing to the exhaust vent. The baffle 23 can be integrally molded with the mask shell or attached to the shell by other known 30 methods, including adhesive or ultrasonic bonding. It should be understood that the mask shell incorporating the baffle can be used in combination with the gusset

portion, but that either of these aspects can be used alone in a mask of the present invention.

While the invention has been described in accordance with what is presently believed to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and the scope of the appended claims, which claims are to be interpreted in the broadest manner so as to encompass all such equivalent structures.

CLAIMS

1. A breathable gas mask arrangement, comprising:
a mask shell having a portion adapted to receive a supply of pressurized breathable gas and a user side;
a gusset portion having a first side attached to the user side of the shell and having a second side;
a cushion having a first portion attached to the second side of the gusset portion and a second portion constructed and arranged to contact a user's face in use and provide a seal between the mask arrangement and the user's face; and
headgear constructed and arranged to attach the mask shell to the user;
wherein the gusset portion is constructed and arranged such that it can expand and contract to alter a distance between the mask shell and the cushion in use, the distance being within a range of movement of the gusset portion that is greater than 0 mm and less than 30 mm, and wherein an interior of the gusset portion is exposed to the supply of pressurized breathable gas and has a projected area on the user's face A_g that is greater than an area A_c of contact of the cushion with the user's face such that the supply of pressurized breathable gas acting on the area A_g provides a component of a contact force F_c of the cushion on the user's face, and a ratio of A_g/A_c is greater than 1.5 and less than 4.0.
2. The breathable gas mask arrangement according to **claim 1**, wherein the gusset portion is structured to expand or contract from an initial position to a position that is about 10-30 mm from the initial position.
3. The breathable gas mask arrangement according to **claim 1**, wherein the gusset portion is structured to expand or contract from an initial position to a position that is about 5-20 mm from the initial position.

4. The breathable gas mask arrangement according to **claim 1**, wherein the gusset portion is in the form of a piston that is axially slidably engaged with a cylinder portion of the shell.

5. The breathable gas mask arrangement according to **claim 1**, wherein the gusset portion includes a single gusset having a flexible sidewall with a generally triangular cross-section when not exposed to the supply of pressurized breathable gas that balloons to a generally rounded cross-section when exposed to the supply of pressurized breathable gas.

6. The breathable gas mask arrangement according to **claim 1** wherein the ratio of A_g/A_c is in the range of 1.6-4.0.

7. The breathable gas mask arrangement according to **claim 1** wherein the ratio of A_g/A_c is in the range of 1.8-3.5.

8. A breathable gas mask arrangement, comprising:
a mask shell having a portion adapted to receive a supply of pressurized breathable gas and a user side;
a gusset portion having a first side attached to the user side of the shell and having a second side;
a cushion having a first portion attached to the second side of the gusset portion and a second portion constructed and arranged to contact a user's face in use and provide a seal between the mask arrangement and the user's face; and
headgear constructed and arranged to attach the mask shell to the user;

wherein the gusset portion includes an elastic sidewall having a spring constant that is at least partially determinative of a force applied to the patient's face through the second portion of the cushion.

9. The breathable gas mask arrangement according to **claim 8**, wherein the gusset portion is constructed and arranged such that it can expand and contract to alter a distance between the mask shell and the cushion.

10. The breathable gas mask arrangement according to **claim 9**, wherein the distance is within a range of movement of the gusset portion that is greater than 0 mm and less than 30 mm.

11. The breathable gas mask arrangement according to **claim 8**, wherein an interior of the gusset portion is exposed to the supply of pressurized breathable gas and has a projected area on the user's face A_g which is greater than an area A_c of contact of the cushion with the user's face such that the supply of pressurized breathable gas acting on the area A_g provides a component of a contact force F_c of the cushion on the user's face, and a ratio of A_g/A_c is greater than 1.5 and less than 4.0.

12. The breathable gas mask arrangement according to **claim 11**, wherein the ratio of A_g/A_c is in the range of 1.6-4.0.

13. The breathable gas mask arrangement according to **claim 11**, wherein the ratio of A_g/A_c is in the range of 1.8-3.5.

14. The breathable gas mask arrangement according to **claim 8**, wherein the gusset portion includes a single gusset having a flexible sidewall with a generally triangular cross-section when not exposed to the supply of pressurized breathable gas that balloons to a generally rounded cross-section when exposed to the supply of pressurized breathable gas.




FIG. 1

SUBSTITUTE SHEET (RULE 26) RO/AU




FIG. 2

SUBSTITUTE SHEET (RULE 26) RO/AU




FIG. 3

SUBSTITUTE SHEET (RULE 26) RO/AU

4/13




FIG. 4




FIG. 5

SUBSTITUTE SHEET (RULE 26) RO/AU




FIG. 6

FIG. 7




FIG. 8




FIG. 9

SUBSTITUTE SHEET (RULE 26) RO/AU




FIG. 10

SUBSTITUTE SHEET (RULE 26) RO/AU

7/13




FIG. 11




FIG. 12




FIG. 14




FIG. 13

SUBSTITUTE SHEET (RULE 26) RO/AU




FIG. 15




FIG. 16

SUBSTITUTE SHEET (RULE 26) RO/AU

9/13




FIG. 17




FIG. 18

SUBSTITUTE SHEET (RULE 26) RO/AU




FIG. 19

SUBSTITUTE SHEET (RULE 26) RO/AU

11/13




FIG. 20




FIG. 21

SUBSTITUTE SHEET (RULE 26) RO/AU

12/13




FIG. 22




FIG. 23




FIG. 24

SUBSTITUTE SHEET (RULE 26) RO/AU

13/13




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30

SUBSTITUTE SHEET (RULE 26) RO/AU