



US009302067B2

(12) **United States Patent**
Mayer et al.

(10) **Patent No.:** **US 9,302,067 B2**
(45) **Date of Patent:** **Apr. 5, 2016**

(54) **APPARATUS FOR HUMIDIFYING A
RESPIRATORY GAS**

(71) Applicant: **ResMed R&D Germany GmbH**,
Martinsried (DE)

(72) Inventors: **Wolfgang Mayer**, Ebringen (DE);
Harald Genger, Starnberg (DE); **Stefan
Madaus**, Gräfelfing (DE); **Andreas
Klopp**, Munich (DE); **Stefan Schatzl**,
Weilhem (DE); **Harald Wolfgang
Vögele**, Gauting (DE); **Bernd Christoph
Lang**, Gräfelfing (DE)

(73) Assignee: **ResMed R&D Germany GmbH**,
Martinsried (DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/791,744**

(22) Filed: **Jul. 6, 2015**

(65) **Prior Publication Data**

US 2015/0306337 A1 Oct. 29, 2015

Related U.S. Application Data

(60) Continuation of application No. 13/916,930, filed on
Jun. 13, 2013, which is a continuation of application

(Continued)

(30) **Foreign Application Priority Data**

Aug. 5, 1999	(DE)	199 36 499
Oct. 13, 1999	(DE)	199 49 283
Oct. 13, 1999	(DE)	199 49 292
Oct. 13, 1999	(DE)	299 18 048

(51) **Int. Cl.**

A61M 16/16 (2006.01)

A61M 16/08 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61M 16/16** (2013.01); **A61M 16/0057**
(2013.01); **A61M 16/0816** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61M 16/16–16/186; A61M 16/1075;
A61M 16/1085; A61M 16/0816; A61M
16/0875; A61M 16/0883

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,085,833	A	2/1914	Wilson
1,974,843	A	9/1934	Blashfield

(Continued)

FOREIGN PATENT DOCUMENTS

AU	200065475	B2	4/2001
CA	2099665		7/1992

(Continued)

OTHER PUBLICATIONS

Fisher & Paykel Healthcare "SleepStyle™ 200 CPAP Series" Speci-
fication Sheet, 1998, 4 pages.

(Continued)

Primary Examiner — Valerie L Woodward


(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(57)

ABSTRACT

A humidifier assembly for a CPAP apparatus includes a liquid storage container configured to hold a body of liquid. The liquid storage container includes a humidifying region above a metallic heat conducting material, the humidifying region being a region inside the liquid storage container in which the liquid is evaporated into pressurized respiratory gas generated in the CPAP apparatus. The humidifier assembly further includes a base unit configured to a) receive the liquid storage container and b) connect to a CPAP unit of the CPAP apparatus. The base unit includes a housing providing a base portion to support the liquid storage container thereon, the base portion including a heating element configured to contact the heat conducting material of the liquid storage container when the liquid storage container is supported on the base unit. The base unit also includes an inlet configured to receive and be coupled to an outlet of the CPAP unit. In addition, the liquid storage container is removable from the base unit.

30 Claims, 12 Drawing Sheets



No. 12/958,718, filed on Dec. 2, 2010, now Pat. No. 8,469,025, which is a division of application No. 11/414,432, filed on May 1, 2006, now Pat. No. 7,938,112, which is a division of application No. 10/048,786, filed as application No. PCT/EP00/07602 on Aug. 4, 2000, now Pat. No. 7,096,864.

- A62B 9/00** (2006.01)
A61M 16/10 (2006.01)
A61M 16/00 (2006.01)

- CPC *A61M16/0858* (2014.02); *A61M 16/0875*
(2013.01); *A61M 16/109* (2014.02); *A61M*
16/162 (2013.01); *A62B 9/003* (2013.01);
A61M 2205/42 (2013.01); *A61M 2209/08*
(2013.01)

- ## References Cited

RE19,826	E	1/1936	Aisenstein	
2,220,669	A	11/1940	Allen	
2,598,978	A	6/1952	De Martin	
2,780,708	A	2/1957	Glynn et al.	
2,945,619	A	7/1960	Ballard	
3,171,353	A	3/1965	McMahan	
3,316,910	A	5/1967	Davis	
3,584,401	A	6/1971	Cryer et al.	
3,612,710	A	10/1971	Mount	
3,620,638	A	11/1971	Kaye et al.	
3,638,926	A	2/1972	Melville et al.	
3,659,604	A	5/1972	Melville et al.	
3,690,317	A	9/1972	Millman	
3,789,837	A	2/1974	Philips et al.	
3,806,102	A	4/1974	Valenta et al.	
3,864,440	A	2/1975	Giocoechea	
3,873,806	A	3/1975	Schossow	
3,954,920	A	5/1976	Heath	
4,037,994	A	7/1977	Bird	
4,051,205	A *	9/1977	Grant	A61M 16/1075 128/203.27
4,098,853	A *	7/1978	Brown	A61M 16/1075 128/200.13
4,105,372	A	8/1978	Mishina et al.	
4,152,379	A	5/1979	Suhr	
4,171,190	A	10/1979	Hudson	
4,222,971	A	9/1980	Eilert	
4,229,142	A	10/1980	Le Dall et al.	
4,237,080	A	12/1980	Elliott	
4,243,396	A	1/1981	Cronenberg	
4,336,798	A	6/1982	Beran	
4,351,327	A	9/1982	Rinne et al.	
4,383,800	A	5/1983	Becker et al.	
4,523,896	A	6/1985	Lhenry et al.	
4,532,088	A	7/1985	Miller	
4,576,616	A	3/1986	Mottram et al.	
4,588,425	A	5/1986	Usry et al.	
4,621,632	A	11/1986	Bartels et al.	
4,629,590	A	12/1986	Bagwell	
4,644,790	A	2/1987	Mizoguchi	
4,657,713	A	4/1987	Miller	
4,676,237	A	6/1987	Wood et al.	
4,686,354	A	8/1987	Makin	
4,753,758	A	6/1988	Miller	
4,767,576	A	8/1988	Bagwell	
4,789,388	A	12/1988	Nishibata	
4,799,287	A	1/1989	Belanger	
4,802,819	A	2/1989	Bevington	
4,807,616	A *	2/1989	Adahan	A61M 16/00 128/204.2

4,819,625	A *	4/1989	Howe	A61M 16/16 128/200.14
4,823,787	A *	4/1989	Adahan	A61M 16/00 128/203.27
4,838,258	A	6/1989	Dryden et al.	
4,870,961	A *	10/1989	Barnard	A61M 16/08 128/202.27
4,906,417	A	3/1990	Gentry	
4,913,140	A	4/1990	Orec et al.	
4,921,642	A	5/1990	LaTorraca	
4,926,856	A	5/1990	Cambio et al.	
4,941,469	A *	7/1990	Adahan	A61M 16/00 128/203.12
4,946,348	A	8/1990	Yapp	
4,953,546	A	9/1990	Blackmer et al.	
4,973,234	A	11/1990	Swenson	
4,993,411	A	2/1991	Callaway	
5,061,405	A	10/1991	Stanek et al.	
5,097,424	A	3/1992	Ginevri et al.	
5,127,800	A	7/1992	Hyll et al.	
5,199,009	A	3/1993	Svast	
5,231,979	A *	8/1993	Rose	A61M 16/16 128/200.24
5,237,987	A	8/1993	Anderson et al.	
5,259,370	A *	11/1993	Howe	A61M 16/16 128/200.14
5,271,391	A	12/1993	Graves	
5,329,939	A *	7/1994	Howe	A61M 16/162 128/200.14
5,339,825	A	8/1994	McNaughton et al.	
5,391,063	A	2/1995	Hantle et al.	
5,443,061	A	8/1995	Champaign et al.	
5,445,143	A	8/1995	Sims	
5,474,112	A	12/1995	Carola	
5,482,031	A	1/1996	Lambert	
5,483,616	A	1/1996	Chiu et al.	
5,537,997	A	7/1996	Mechlenburg et al.	
5,551,419	A	9/1996	Froehlich et al.	
5,558,084	A	9/1996	Daniell et al.	
5,564,415	A *	10/1996	Dobson	A61M 16/16 128/200.14
5,577,496	A	11/1996	Blackwood et al.	
5,588,423	A	12/1996	Smith	
5,598,837	A	2/1997	Sirianne, Jr. et al.	
5,651,775	A	7/1997	Walker et al.	
5,655,522	A	8/1997	Mechlenburg et al.	
5,673,687	A	10/1997	Dobson et al.	
5,682,289	A	10/1997	Schwegler et al.	
5,794,219	A	8/1998	Brown	
5,822,715	A	10/1998	Worthington et al.	
5,828,943	A	10/1998	Brown	
5,832,448	A	11/1998	Brown	
5,844,862	A	12/1998	Cocatre-Zilgien	
5,848,592	A	12/1998	Sibley	
5,865,171	A	2/1999	Cinquin	
5,870,283	A	2/1999	Maeda et al.	
5,878,743	A	3/1999	Zdrojkowski et al.	
5,879,163	A	3/1999	Brown et al.	
5,887,133	A	3/1999	Brown et al.	
5,888,053	A	3/1999	Kobayashi et al.	
5,895,595	A	4/1999	Haden	
5,897,493	A	4/1999	Brown	
5,899,855	A	5/1999	Brown	
5,913,310	A	6/1999	Brown	
5,916,493	A	6/1999	Miller et al.	
5,918,603	A	7/1999	Brown	
5,933,136	A	8/1999	Brown	
5,940,801	A	8/1999	Brown	
5,943,473	A	8/1999	Levine	
5,951,300	A	9/1999	Brown	
5,956,501	A	9/1999	Brown	
5,960,403	A	9/1999	Brown	
5,985,559	A	11/1999	Brown	
5,997,476	A	12/1999	Brown	
D419,658	S	1/2000	Matchett et al.	
6,023,686	A	2/2000	Brown	
6,032,119	A	2/2000	Brown et al.	
6,050,260	A	4/2000	Daniell et al.	
6,052,511	A	4/2000	Birdsell	

(56)

References Cited

U.S. PATENT DOCUMENTS

6,101,478 A	8/2000	Brown	8,020,551 B2	9/2011	Virr
6,109,865 A	8/2000	Ishikawa	8,028,693 B2	10/2011	Trevor-Wilson et al.
6,129,524 A	10/2000	Woollenweber et al.	8,042,535 B2	10/2011	Kenyon
6,131,571 A	10/2000	Lampotang et al.	8,091,547 B2	1/2012	Thudor et al.
6,135,432 A	10/2000	Hebblewhite et al.	8,469,025 B2	6/2013	Mayer et al.
6,144,837 A	11/2000	Quy	RE44,453 E	8/2013	Virr et al.
6,152,132 A	11/2000	Psaros	8,550,072 B2	10/2013	Thudor et al.
6,158,978 A	12/2000	Norbury, Jr.	2001/0017134 A1	8/2001	Bahr
6,161,095 A	12/2000	Brown	2001/0050080 A1	12/2001	Seakins et al.
6,185,095 B1	2/2001	Helot et al.	2002/0020930 A1	2/2002	Austin et al.
6,186,140 B1	2/2001	Hoague	2002/0022973 A1	2/2002	Sun et al.
6,189,870 B1	2/2001	Withall	2002/0056453 A1	5/2002	Klopp et al.
6,192,883 B1	2/2001	Miller	2002/0159897 A1	10/2002	Kegg et al.
6,202,991 B1	3/2001	Coniglio et al.	2003/0062045 A1	4/2003	Woodring et al.
6,210,116 B1	4/2001	Kuczaj et al.	2003/0065308 A1	4/2003	Lebel et al.
6,213,119 B1	4/2001	Brydon et al.	2003/0066526 A1	4/2003	Thudor et al.
6,216,691 B1	4/2001	Kenyon et al.	2003/0066530 A1	4/2003	Shahbazpour et al.
6,257,171 B1	7/2001	Rivard	2003/0076745 A1	4/2003	Chapman
6,275,652 B1	8/2001	Chauviaux	2003/0084900 A1	5/2003	LeClerc et al.
6,279,574 B1	8/2001	Richardson et al.	2003/0115085 A1	6/2003	Satoh
6,308,706 B1	10/2001	Lammers et al.	2003/0187525 A1	10/2003	Mann et al.
6,314,237 B1	11/2001	Glucksman	2003/0208465 A1	11/2003	Yurko et al.
6,332,462 B1	12/2001	Krohn	2003/0230308 A1	12/2003	Linden
6,338,473 B1	1/2002	Hebblewhite et al.	2003/0236450 A1	12/2003	Kocinski
6,340,288 B1	1/2002	Hulkkonen et al.	2004/0035422 A1	2/2004	Truitt et al.
6,349,724 B1	2/2002	Burton et al.	2004/0055597 A1	3/2004	Virr et al.
D454,393 S	3/2002	Lynch et al.	2004/0060559 A1	4/2004	Virr et al.
6,397,841 B1 *	6/2002	Kenyon	2004/0060561 A1	4/2004	Kwok et al.
		A61M 16/00	2005/0005937 A1	1/2005	Farrugia et al.
		128/202.27	2005/0103339 A1	5/2005	Daly et al.
6,398,197 B1	6/2002	Dickinson et al.	2005/0217673 A1	10/2005	Daly et al.
6,435,180 B1 *	8/2002	Hewson	2005/0247314 A1	11/2005	Virr et al.
		A61M 16/16	2006/0191531 A1	8/2006	Mayer
		128/203.12	2006/0237005 A1	10/2006	Virr et al.
6,471,493 B2	10/2002	Choi et al.	2007/0036662 A1	2/2007	Pensola et al.
D467,335 S	12/2002	Lithgow et al.	2007/0134085 A1	6/2007	Daly et al.
D468,011 S	12/2002	Lynch et al.	2008/0072900 A1	3/2008	Kenyon et al.
D468,017 S	12/2002	McCombs	2009/0229606 A1	9/2009	Tang et al.
6,514,053 B2	2/2003	Takura et al.	2010/0192094 A1	7/2010	Jeha et al.
6,543,449 B1	4/2003	Woodring et al.	2010/0229867 A1	9/2010	Bertinetti et al.
6,546,930 B1	4/2003	Emerson et al.	2011/0017212 A1	1/2011	Kenyon et al.
6,554,260 B1	4/2003	Lipscombe et al.	2011/0023877 A1	2/2011	Kenyon et al.
6,591,834 B1	7/2003	Colla et al.	2011/0073109 A1	3/2011	Mayer et al.
6,604,390 B1	8/2003	Nooner	2011/0180068 A1	7/2011	Kenyon et al.
6,615,444 B2	9/2003	McGill et al.	2013/0269696 A1	10/2013	Mayer et al.
6,622,724 B1	9/2003	Truitt et al.	2015/0020805 A1	1/2015	Kenyon et al.
6,669,630 B1	12/2003	Joliat et al.			
6,672,300 B1	1/2004	Grant			
6,678,215 B1	1/2004	Treyz et al.			
D487,311 S	3/2004	Lithgow et al.			
6,718,974 B1	4/2004	Moberg			
D493,520 S	7/2004	Bertinetti et al.			
D493,884 S	8/2004	Virr et al.			
6,772,999 B2	8/2004	Lipscombe et al.			
6,775,882 B2	8/2004	Murphy et al.			
D498,527 S	11/2004	Virr et al.			
6,827,340 B2	12/2004	Austin et al.			
6,837,260 B1	1/2005	Kuehn			
6,874,771 B2	4/2005	Birdsell et al.			
6,896,478 B2	5/2005	Botros et al.			
6,910,483 B2	6/2005	Daly et al.			
6,918,389 B2	7/2005	Seakins et al.			
6,935,337 B2	8/2005	Virr et al.			
6,997,188 B2	2/2006	Kwok et al.			
7,056,289 B2	6/2006	Kasper et al.			
7,089,930 B2	8/2006	Adams et al.			
7,096,864 B1	8/2006	Mayer et al.			
7,111,624 B2	9/2006	Thudor et al.			
7,128,729 B2	10/2006	Duchon et al.			
7,137,388 B2	11/2006	Virr et al.			
7,225,809 B1	6/2007	Bowen et al.			
7,413,173 B2	8/2008	DiMatteo et al.			
7,478,635 B2	1/2009	Wixey et al.			
7,614,398 B2	11/2009	Virr et al.			
7,616,871 B2	11/2009	Kramer			
7,677,246 B2	3/2010	Kepler et al.			
8,006,691 B2	8/2011	Trevor-Wilson et al.			

FOREIGN PATENT DOCUMENTS

CN	2086150	10/1991
CN	1314192	9/2001
DE	275612	1/1913
DE	30 05 094	8/1981
DE	36 23 162 A1	7/1986
DE	323162 A1	7/1986
DE	3623162 A1	7/1986
DE	3642637	6/1988
DE	38 23 242 A1	2/1990
DE	3823242 A1	2/1990
DE	90 14 848.7	3/1991
DE	9014848.7	3/1991
DE	41 38 098 C2	11/1991
DE	4138098 C2	11/1991
DE	42 44 493 A1	7/1993
DE	4244493 A1	7/1993
DE	93 17 450	6/1994
DE	3789221 T2	8/1994
DE	9409231.1 U1	12/1994
DE	195 15 739 C2	5/1995
DE	19515739 C2	5/1995
DE	195 15 739 A1	11/1996
DE	19630466	2/1998
DE	298 17 685	10/1998
DE	694 09 024 T2	10/1998
DE	29817685 U1	10/1998
DE	69409024 T2	11/1998
DE	19752672	3/1999
DE	29909611 U1	10/1999
DE	200 13 392 U1	10/2000

(56)

References Cited

FOREIGN PATENT DOCUMENTS

DE	100 21 782	11/2000
DE	199 36 499 A1	2/2001
DE	10016005 A1	12/2001
DE	20213232	4/2003
DE	102005007773 A1	9/2005
EP	0 201 985	11/1986
EP	0201985	11/1986
EP	0 274 996 B1	7/1988
EP	074996 B1	7/1988
EP	0274996	7/1988
EP	1023912 A1	2/1990
EP	0 376 584 A2	7/1990
EP	0 589 429 A1	3/1994
EP	0589 429	3/1994
EP	0 760 247	3/1997
EP	0 845 277 A2	6/1998
EP	0 893 750	1/1999
EP	0 903 160 A1	3/1999
EP	1 002 552 A2	5/2000
EP	1 023 912 A2	8/2000
EP	1 055 431	11/2000
EP	1087 322 A2	3/2001
EP	1318307	6/2003
EP	1 374 938	1/2004
FR	2 323 436	4/1977
FR	2 714 985	7/1995
GB	1556492 A	11/1979
GB	2069607 A	8/1981
GB	2 177 006 A	1/1987
GB	2177006 A	1/1987
GB	2192136 A	1/1988
GB	2293325	3/1996
GB	2353904 A	3/2001
JP	55-104925	8/1980
JP	58-036560	3/1983
JP	64-500088	1/1989
JP	2-19168	1/1990
JP	5-104681	4/1993
JP	6-26894	4/1994
JP	6-190928	7/1994
JP	7-145795 A	6/1995
JP	07-037195	7/1995
JP	08-178781	7/1996
JP	09-103490	4/1997
JP	11-398 A	1/1999
JP	2000-337670 A	5/1999
JP	2000-237316	9/2000
JP	2001-61814	3/2001
JP	2001-160102	6/2001
JP	2001-516277	9/2001
JP	2002-206498 A	7/2002
JP	2002-248167	9/2002
JP	2002-253672	9/2002
JP	2002-306601	10/2002
JP	2003-506161	2/2003
JP	2003-527160	9/2003
JP	2004-532666	10/2004
WO	88/00068	1/1988
WO	WO 93/05451	3/1993
WO	WO 95/15778	6/1995
WO	WO 97/32619	9/1997
WO	WO 98/04311 A1	2/1998
WO	WO 98/31937	7/1998
WO	WO 98/33433 A1	8/1998
WO	WO 98/41306	9/1998
WO	WO 98/57691 A1	12/1998
WO	WO 99/13932	3/1999
WO	WO 99/22793 A1	5/1999
WO	WO 99/22794	5/1999
WO	WO 99/64747	12/1999
WO	0021602	4/2000
WO	WO 00/21602	4/2000
WO	WO 00/27457	5/2000
WO	WO 00/32261	6/2000
WO	WO 00/38771	7/2000

WO	WO 00/42324	7/2000
WO	WO 01/10489 A2	2/2001
WO	WO 01/32069	5/2001
WO	WO 01/73653 A1	10/2001
WO	WO 02/02169 A1	1/2002
WO	02/20075	3/2002
WO	02/053217	7/2002
WO	02/066105	8/2002
WO	02/066106 A1	8/2002
WO	WO 02/066107 A1	8/2002
WO	03/090827	11/2003
WO	2005/011556	2/2005
WO	WO 2007/019628	2/2007
WO	WO 2009/059359	5/2009
WO	WO 2009/156921 A1	12/2009
WO	WO 2010/092496	8/2010

OTHER PUBLICATIONS

J. H. Emerson Co., Cough Assist, "Non-Invasive Removal of Bronchial Secretions," 2 pages.

Madaus Schwarzer Medizintechnik, "New Approaches in Diagnosis and Therapy—Moritz biLevel User Manual", May 1994, 38 pages. Photos of MAP Humidifier and Tub, 2 pages and cover sheet, undated.

ResMed "Sullivan® HumidAire® User's Instructions", 8 pages, undated.

MAP Medizin-Technologie GmbH, Moritz® S/Moritz® ST—Sailing toward therapeutic success . . . , 4 pages, undated.

Hoffrichter "Vector CPAP—Therapy With Technical Mastery", 4 pages, Oct. 1998.

German Patient Manual for Hoffrichter/Sandmann CPAP Respirator—Perfect CPAP Therapy, 30 pages plus Translation Verification Certificate, Mar. 1998.

European Search Report mailed Jul. 29, 2004 from Corresponding EP Appln. No. 00953159.1, 6 pgs. and 2 pages of English Translation.

De Vilbiss® Healthcare, "DeVilbiss IntelliPAP® Standard CPAP System," Nov. 2007, 2 pages.

Notice of Reasons for Rejection mailed Dec. 15, 2009 in Japanese Appln. No. 2006-515536, together with an English translation.

Breas Medical AB, "iSleep® 20", Dec. 2007, 2 pages.

Petition for Inter Partes Review of U.S. Pat. No. 7,614,398, mailed Aug. 16, 2013.

Declaration of Joseph Dyro, Petition Exhibit 1007.

Fisher & Paykel Healthcare, Specification Sheet for "SleepStyle™ 200 CPAP Series," 2005, 4 pages.

Fisher & Paykel Healthcare, Specification Sheet for "SleepStyle™ 600 CPAP Series," 2005, 4 pages.

Hoffrichter GmbH, "VECTOR Therapy in Perfection," 2002, 2 pages.

Fisher & Paykel Healthcare, "Two Easy Steps to Comfort, Humidification and Nasal CPAP Therapy," Aug. 1995, 4 pages.

MAP Medizin-Technologie GmbH, "minni Max nCPAP. The Respiratory Therapy Device With•Out an Integrated Humidifier," Dec. 2003, 17 pages.

MAP Medizintechnik fuer Arzt and Patient, maxII nCPAP moritzII biLEVEL, "The gentle Therapy for Sleep-Related Breathing Disorders," 2000, 4 pages.

ResMed "Sullivan® HumidAire® User's Instructions", 8 pages, 1998.

MAP Medizin-Technologie GmbH, Moritz® S/Moritz® ST—Sailing toward therapeutic success . . . , Jul. 2004, 4 pages.

Respironics Inc., "System One Heated Humidifier User Manual," May 2009, 20 pages.

ResMed, "The Sullivan® HumidAire™," 1997, 1 page.

Photos of HumidAire™, 11 pages.

Photos of tray system available before the critical date, with sample flow generator and humidifier, 5 pages.

Japanese Office Action mailed Mar. 23, 2010 in Japanese Appln. No. 2001-515003.

European Search Report mailed Dec. 17, 2012 in European Application No. 10185455.2, with English translation of the European Search Opinion (14 pages).

(56)

References Cited

OTHER PUBLICATIONS

European Search Report mailed Dec. 14, 2012 in European Application No. 10185462.8, with English translation of the European Search Opinion (10 pages).

Notification of Acceptance of Request for Invalidation, Issued: Dec. 24, 2014, in Chinese Patent No. 02804936.5, with English translation, 62 pages.

U.S. International Trade Commission, Inv. No. 337-TA-890, "Office of Unfair Import Investigations' Petition for Review of the Initial Determination," dated Sep. 3, 2014 (Public Version Filed: Oct. 8, 2014), 34 pages.

U.S. International Trade Commission, Inv. No. 337-TA-890, "Office of Unfair Import Investigations' Response to the Petitions for Review of the Initial Determination," dated Sep. 11, 2014 (Public Version Filed: Oct. 8, 2014), 37 pages.

Fisher & Paykel Limited, New Zealand Application No. 503495, filed Mar. 21, 2000, 29 pages.

U.S. International Trade Commission, Inv. No. 337-TA-890, "Office of Unfair Import Investigations' Reply to the Private Parties' Responses to the Commission Question," dated Nov. 7, 2014 (Public Version Filed: Dec. 3, 2014), 19 pages.

U.S. International Trade Commission, Inv. No. 337-TA-890, "Office of Unfair Import Investigations' Response to ResMed's Motion to Withdraw the '487 Patent or Alternatively Find No Violation Based on Technical Prong," dated Nov. 19, 2014 (Public Version Filed: Dec. 3, 2014), 5 pages.

U.S. International Trade Commission, Inv. No. 337-TA-890, "Notice of the Commission's Final Determination; Issuance of a Limited Exclusion Order and Cease and Desist Orders; Termination of the Investigation," Issued: Dec. 23, 2014, 25 pages.

U.S. Patent and Trademark Office, Case IPR2014-01196, U.S. Pat. No. Re. 44,453 E, "Decision Institution of Inter Partes Review 37 C.F.R. §42.108," Paper No. 7, Entered: Dec. 21, 2014, 11 pages.

U.S. Patent and Trademark Office, Case IPR2014-01196 and IPR2014-01363, U.S. Pat. No. Re. 44,453 E, "Scheduling Order," Entered: Jan. 21, 2015, 9 pages.

U.S. Patent and Trademark Office, Case IPR2014-01363, U.S. Pat. No. Re. 44,453 E, Decision Institution of Inter Partes Review 37 C.F.R. §42.108, Paper No. 7, Entered: Jan. 21, 2015, 21 pages.

Communication Pursuant to Article 94(3) EPC mailed Feb. 4, 2015 in European Application No. 12 159 042.6 (4 pages).

Notification of Acceptance of Request for Invalidation and English Translation for corresponding Chinese Patent No. 02804936.5, issued Mar. 20, 2014, 188 pages.

Microfilm of Japanese Utility-Model Application No. S54-003858 (Japanese Utility-Model Application Publication No. S55-104925).

MAP Medizintechnik, "Moritz II bil.level®—The gentle therapy for sleep-related breathing disorders" brochure, 6 pages, Jan. 2001.

Notification of Second Office Action mailed Jan. 27, 2006 in Chinese Appln. No. 02804936.5, with English translation (6 pages).

Notification of Reasons for Rejection mailed Feb. 19, 2008 in Japanese Appln. No. 2002-565664, with English translation (5 pages).

Final Notice of Reasons for Rejection delivered Sep. 24, 2008 in Japanese Appln. No. 2002-565664, with English translation (6 pages).

Notification of the First Office Action mailed Jul. 22, 2005 in Chinese Appln. No. 02804936.5, with English translation (8 pages).

Extended European Search Report mailed Apr. 28, 2011 in European Appln. No. 10189422.8 (5 pages).

International Search Report mailed Mar. 21, 2002 in International Appln. No. PCT/AU02/00155 (2 pages).

International Preliminary Examination Report completed Oct. 4, 2002 in International Appln. No. PCT/AU02/00155 (3 pages).

Office Action dated Jan. 22, 2008 in Japanese Patent Appln. No. 2002-565665 (w/ English translation) (12 pages).

Examination Report mailed Oct. 10, 2003 in New Zealand Appln. No. 527088 (2 pages).

Supplementary European Search Report mailed Sep. 15, 2009 in European Appln. No. 02700014.0 (3 pages).

Communication mailed Jul. 1, 2010 in European Appln. No. 02 700 014.0 (5 pages).

Extended European Search Report mailed May 4, 2012 in European Appln. No. 12159042.6 (5 pages).

ITC Action related to Certain Sleep-Disordered Breathing Treatment Systems and Components Thereof, Inv. No. 337-TA-, CBI 13-185, filed on Mar. 28, 2013, 57 pages.

ResMed's First Amended Complaint for Patent Infringement, filed in the United States District Court Central District of California Southern Division, filed on Apr. 8, 2013, 342 pages.

"Complaint for Patent Infringement—Jury Trial Demanded" as filed in the United States District Court, Southern District of California, Case No. 13CV1246 MMAWMC, dated May 13, 2013, 18 pages.

"Motion to Amend the Complaint and Notice of Investigation" as filed in the United States International Trade Commission, Investigation No. 337-TA-879, dated May 31, 2013, 18 pages.

Petition for Inter Partes Review of U.S. Pat. No. Re 44,453, *BMC Medical Co., Ltd.*, Petitioner v. *ResMed Limited*, Patent Owner, Case No. IPR2014-01363, Aug. 22, 2014, 66 pages.

Petition Exhibit 1004 in IPR2014-01363, Declaration of Steve Bordewick, Aug. 22, 2014, 90 pages.

Petition for Inter Parties Review of U.S. Pat. No. RE44,453 Under to 35 U.S.C. §§ 311 ET SEQ. and 37 C.F.R. §42.100 ET SEQ., *Apex Medical Corp.*, Petitioner v. *ResMed Limited*, Patent Owner, Case No. IPR2014-00551, Mar. 27, 2014, 38 pages.

Apex Medical Corporation, Petition Exhibit 1002 in IPR2014-00551, "ResMed's First Amended Complaint for Patent Infringement—Jury Trial Demanded", Case No. SACV-13-00498 CJC (RNBx), USDC, Central District of California, Southern Division, 18 pages.

Petition Exhibit 1006 in IPR2014-00551, Patent Owner Amendment mailed Mar. 27, 2009, in U.S. Appl. No. 11/181,807, 10 pages.

Petition Exhibit 1007 in IPR2014-00551, Declaration of Joseph Dyro in Support of Inter Partes Review of U.S. Pat. No. RE44,453, executed Mar. 26, 2014, 15 pages.

Petition for Inter Parties Review of U.S. Pat. No. Re. 44,453 Under to 35 U.S.C. §§311-319 and 37 C.F.R. §42.100 et seq., *BMC Medical Co. Ltd.*, Petitioner v. *ResMed Limited*, Patent Owner, Case No. IPR2014-01196, Jul. 23, 2014, 62 pages.

Petition Exhibit 1003 in IPR2014-01196, REMStar® Heated Humidifier Manual, Mar. 15, 2001, 8 pages.

Petition Exhibit 1004 in IPR2014-01196, Declaration of Steve Bordewick, Jul. 22, 2014, 59 pages.

Petition Exhibit 1006 in IPR2014-01196, Patent Owner ResMed Limited's Preliminary Response filed Jul. 10, 2014, in IPR2014-00551, 41 pages.

Petition Exhibit 1007 in IPR2014-01196, ITC Investigation No. 337-TA-890; Order No. 7: Initial Determination Granting Complainants' Motion to Amend Complaint and Notice of Investigation and Granting Respondents' Motion to Terminate the Investigation with Respect to U.S. Pat. No. 7,614,398, served Feb. 4, 2014, 8 pages.

Petition Exhibit 1008 in IPR2014-01196, Case No. 13-cv-1246-CAB (WMC), Order on Motion to Stay, Motion to Dismiss, and Related Discovery Request, Oct. 15, 2013, 3 pages.

Petition Exhibit 1009 in IPR2014-01196, Case No. SACV 13-00498: Order Granting Defendants' Motion to Stay Litigation Pending Inter Partes Review, Oct. 4, 2013, 3 pages.

Petition Exhibit 1010 in IPR2014-01196: Patent Prosecution History of Reissue U.S. Appl. No. 13/944,960, filed Jul. 18, 2013, 228 pages.

Petition Exhibit 1011 in IPR2014-01196: Patent Prosecution History of U.S. Pat. No. 7,614,398, 174 pages.

Petition Exhibit No. 1012 in IPR2014-01196: Patent Prosecution History of U.S. Pat. No. Re. 44,453, 2157 pages.

Petition Exhibit No. 1013 in IPR2014-01196: Proof of Service of 3B Medical, Inc. in Civil Action No. 13-cv-1246-MMA-WMC, 5 pages.

Petition Exhibit No. 1014 in IPR2014-01196: Australian Application No. PR 3117, filed Feb. 16, 2001, 17 pages.

Petition Exhibit No. 1016 in IPR2014-01196: ITC Investigation No. 337-TA-890: Order No. 14: Denying Respondents' Motion for Summary Determination of Invalidity of U.S. Pat. No. Re. 44,453, served Mar. 26, 2014, 19 pages.

Petition Exhibit No. 1020 in IPR2014-01196: Australian Application No. PR 7288, filed Aug. 27, 2001, 23 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Petition Exhibit No. 1022 in IPR2014-01196: ITC Investigation No. 337-TA-890: Notice of Commission Determination Not to Review an Initial Determination Granting the Complainants' Motion to Amend the Complaint and Notice of Investigation to Substitute U.S. Pat. No. Re. 44,453 for U.S. Pat. No. 7,614,398 and Granting Respondents' Motion to Terminate the Investigation with Respect to U.S. Pat. No. 7,614,398, Issued: Feb. 10, 2014, 3 pages.

Patent Owner Exhibit No. 2001 in IPR2014-00551, Applicant Transmittal to USPTO re Completion of National Phase Filing of the PCT Application for the Mayer Reference, Aug. 6, 2002, 4 pages.

Patent Owner Exhibit No. 2002 in IPR2014-00551, U.S. Pat. No. Re. 44,453 Patent Application Data Sheet, Initial May 4, 2011, 5 pages.

Patent Owner Exhibit No. 2003 in IPR2014-00551, Decision of the Patent Trial and Appeal Board Denying Institution of Inter Partes Review of U.S. Pat. No. 7,614,398, entered Feb. 20, 2014, 5 pages.

Patent Owner Exhibit No. 2005 in IPR2014-00551, U.S. National Stage Worksheet of USPTO re National Phase Requirements Completion for the Mayer Reference, 1 page.

Patent Owner Exhibit No. 2010 in IPR2014-00551, Deposition Transcript of Dr. Joseph F. Dyro in Connection with Inter Partes Review Proceedings IPR2013-00511, IPR2013-00512, IPR2013-00514, IPR2013-00515, and IPR2013-00516, Apr. 21, 2014, 46 pages.

Patent Owner Exhibit No. 2011 in IPR2014-00551, Patent Owner ResMed Limited's Preliminary Response to Apex Medical Corp.'s Petition for Inter Partes Review of U.S. Pat. No. 7,614,398, Case No. IPR2013-00513, Nov. 22, 2013, 15 pages.

Petition Exhibit No. 1015 in IPR2014-01196: ITC Investigation No. 337-TA-890: Order No. 8: Construing Terms of the Asserted Patents, served Jan. 17, 2014, 51 pages.

Australian Office Action for corresponding AU Appln. No. 2004248855, Mailed Nov. 6, 2009, 5 pages.

Australian Office Action for corresponding AU Appln. No. 2010201899, Mailed Jun. 10, 2010, 5 pages.

Examiner Summary from Meeting corresponding AU Appln. No. 2010201899, Aug. 12, 2010, 3 pages.

Chinese Office Action for co-pending Chinese Application No. 200480017315.1 and English translation, issued Oct. 9, 2009, 14 pages.

Supplementary European Search Report for Co-pending European Application No. 04737434.3, mailed Oct. 15, 2009, 4 pages.

International Search Report for PCT/AU2004/000810 mailed Oct. 1, 2004.

Office Action dated May 19, 2015 issued in related U.S. Appl. No. 14/445,190 (14 pages), including PTO-892 citing U.S. Pat. No. 5,573,713 and U.S. Pat. No. 4,351,327.

Office Action dated Feb. 25, 2015 issued in U.S. Appl. No. 12/659,963 citing U.S. Pat. No. 6,000,396 and U.S. Pat. No. 5,645,531 (99 pages).

Statement of Case dated Dec. 1, 2014 in New Zealand Application No. 607671 (6 pages).

Amended Notice of Opposition to Grant of Patent (Section 21) in New Zealand Application No. 607671 (2 pages).

Notice of Reasons for Rejection dated Dec. 22, 2014 issued in Japanese Application No. 2014-0006622 with English translation (6 pages).

Notice of Allowance dated Jan. 7, 2015 issued in U.S. Appl. No. 14/445,143 (32 pages).

Notice of Allowance dated Jan. 13, 2015 issued in U.S. Appl. No. 14/445,152 (35 pages).

Office Action dated Feb. 5, 2015 issued in related U.S. Appl. No. 14/445,190 with Form PTO-892 citing U.S. Pat. No. 4,025,590 to Igich (32 pages).

Notification of Second Office Action dated Dec. 24, 2014 issued in Chinese Application No. 201210297972.2 with English-language translation (14 pages).

Examination Report for copending European Appln No. 04737434.3, mailed Apr. 14, 2010, 8 pages.

Examination Report for copending European Appln No. 04737434.3, mailed Apr. 26, 2010, 8 pages.

Office Action for Parent U.S. Appl. No. 10/533,940, filed Dec. 29, 2006, mailed Oct. 12, 2010, 10 pages.

Office Action and English translation from copending JP Appln. No. 2006-515549, mailed Jan. 5, 2010, 11 pages.

Office Action and English translation from copending JP Appln. No. 2006-515549, mailed Nov. 2, 2010, 7 pages.

Office Action from corresponding European Appln. No. 04737434.3, mailed Apr. 14, 2010, 8 pages.

Office Action from corresponding European Appln. No. 04737434.3, mailed Apr. 26, 2010, 8 pages.

Kenyon et al., U.S. Appl. No. 12/900,008, filed Oct. 7, 2010.

Kenyon et al., U.S. Appl. No. 12/900,781, filed Oct. 8, 2010.

Hoffrichter/Sandmann CPAP Respirator—Perfect CPAP Therapy, 30 pages plus Translation Verification Certificate, Mar. 1998.

Japanese Office Action and its English Translation for Corresponding Japanese Appln. No. 2010-224862, mailed Jan. 4, 2011 (9 pages).

Japanese Office Action and its English Translation for Corresponding Japanese Appln. No. 2011-007671, mailed Mar. 1, 2011 (6 pages).

Australian Office Action for corresponding Australian Appin. No. 2010257238, mailed Mar. 10, 2011 (2 pages).

Office Action and English for corresponding Japanese Application No. 2006-515549, mailed Mar. 15, 2011, 4 pages.

Japanese Office Action and its English translation for corresponding Japanese Appln. No. 2010-224861, mailed Jan. 18, 2011 (7 pages).

Proceedings Correspondence issued on Mar. 1, 2012 in corresponding New Zealand Patent No. 567371.

Office Action issued on Aug. 24, 2012 in corresponding Australian Application No. 2010257238.

Office Action issued on Aug. 7, 2012 in corresponding Japanese Application No. 2010-153008 (with translation).

Office Action issued on Jan. 22, 2013 in corresponding Japanese Application No. 2011-201622.

Office Action issued on Mar. 7, 2013 in corresponding New Zealand Application No. 607671.

Office Action issued on Mar. 7, 2013 in corresponding New Zealand Application No. 596207.

Search Report issued on Jun. 6, 2013 in corresponding European Application No. 11175449.5.

Japanese Office Action (Decision of Rejection) for Application No. 2011-201622 dated Aug. 13, 2013 w/ English Translation (7 pages).

Office Action issued on Sep. 17, 2013 in corresponding Japanese Application No. 2010-153008 (with Translation).

Office Action issued on Oct. 4, 2013 in corresponding Australian Application No. 2013201490.

Office Action issued on Oct. 4, 2013 in corresponding Canadian Application No. 2,753,378.

Notice of Reasons for Rejection issued on Aug. 11, 2014 in corresponding Japanese Application No. 2011-201622 with English translation (2 pages).

Office Action dated Sep. 8, 2014 issued in corresponding Canadian Application No. 2,753,378 (2 pages).

REMStar® Heated Humidifier Manual, Mar. 15, 2001 (8 pages).

Australian Application No. PR 7288, filed Aug. 27, 2001, 23 pages.

Australian Application No. PR 3117, filed Feb. 16, 2001, 17 pages.

Fisher & Paykel Healthcare, "HC200 Series Nasal CPAP Blower & Heated Humidifier User's Manual", 1998, 17 pages.

Office Action dated Nov. 6, 2015 issued in European Application No. 06006804.6 with English translation (13 pages).

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6a




Fig. 6b




Fig. 7




Fig. 8b

Fig. 8a




Fig. 9




Fig. 10




Fig. 11a




Fig. 11b




Fig. 11c

1

APPARATUS FOR HUMIDIFYING A RESPIRATORY GAS

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 13/916,930, filed Jun. 13, 2013, which is a continuation of U.S. Ser. No. 12/958,718, filed Dec. 2, 2010, now U.S. Pat. No. 8,469,025, which is a divisional of U.S. application Ser. No. 11/414,432, filed May 1, 2006, now U.S. Pat. No. 7,938,112, which is a divisional of U.S. application Ser. No. 10/048,786, filed Aug. 6, 2002, now U.S. Pat. No. 7,096,864, which is the National Phase of International Application PCT/EP00/07602, filed Aug. 4, 2000, which designated the U.S. and claims priority to German Application No. 199 36 499.0, filed Aug. 5, 1999, German Application No. 199 49 292.1, filed Oct. 13, 1999, German Application No. 199 49 283.2, filed Oct. 13, 1999 and German Application No. 299 18 048.4, filed Oct. 13, 1999, respectively, the entire contents of each of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention concerns an apparatus for supplying a respiratory gas under an increased pressure comprising a blowing device for delivering the respiratory gas, a housing device for receiving the blowing device and a connecting device for connection of a humidifying apparatus for humidifying the respiratory gas delivered by the delivery device. The invention further concerns a humidifying apparatus for humidifying a respiratory gas as well as a respiratory gas tube or hose and a connecting apparatus therefor.

2. Description of Related Art

Apparatuses for supplying a respiratory gas under an increased pressure are used in particular in the field of sleep therapy for dealing with sleep-related respiratory disturbances. Supplying the respiratory gas under a predetermined increased pressure, usually in the range of between 5 and 20 mbar, provides for pneumatic splinting of the upper respiratory tracts of a patient, in a physiologically well compatible fashion, whereby it is possible to effectively prevent obstruction in that respiratory tract region.

Usually the respiratory gas is formed directly from the ambient air which is preferably sucked in by way of a filter device. In dependence on the climatic conditions which fluctuate in particular due to the time of year involved, it has proven to be advantageous for the respiratory gas which is supplied to the patient, for example by way of a blowing device, under a regulated, possibly alternating pressure, to be humidified from time to time. For that purpose it is possible to insert a humidifying device into the respiratory gas path between the blowing device and the respiratory mask, for example by way of an intermediate hose portion. CPAP-units with an integrated humidifying apparatus are also known.

In the case of the humidifying apparatuses which are only inserted into a hose line however, there is frequently the problem of inadequate strength and stability. In the case of CPAP-units with an integrated humidifying apparatus the latter has to be constantly taken around, even if there is temporarily no need for humidification of the respiratory gas.

SUMMARY OF THE INVENTION

Under the impulsion of that problem, the object of the invention is to provide an apparatus for supplying a respira-

2

tory gas and a humidifying apparatus which is provided for same, which is robust and simple to handle and which can be configured in an easy fashion according to respective requirements involved.

5 In accordance with the invention that object is attained by an apparatus for supplying a respiratory gas, having one or more features described below.

By virtue thereof, it is advantageously possible for a humidifying apparatus to be coupled directly laterally to a CPAP-unit easily and without the need for expert assembly 10 procedures, and without the CPAP-unit having to be lifted for that purpose. In that case the lower support portions by way of which the CPAP-unit is set up advantageously act directly as a guide device which permits the humidifying apparatus to be 15 easily pushed to the CPAP-unit. If for example there is temporarily no need for a humidifying apparatus or if the humidifying apparatus is to be temporarily separated from the CPAP-unit for cleaning purposes, the CPAP-unit can remain unchanged at the location at which it is set up and the humidifying apparatus can simply be removed towards the side, in 20 particular by being pulled off.

In accordance with a particularly preferred embodiment of the invention the connecting members are oriented substantially in the joining direction. In particular the main passage 25 cross-section for the respiratory gas which is delivered by the blowing device is advantageously formed by a tube connection, on to which can be fitted a connecting portion which is provided on a humidifying apparatus of correspondingly complementary configuration.

30 An embodiment of the invention which is particularly advantageous from esthetic points of view and in regard to a symmetrical structure for the CPAP-unit system is afforded if the corresponding connecting members are provided in an end (front side) of the unit. The surface portion of that end of 35 the unit is of a substantially complementary configuration to a portion of the humidifying apparatus, which is adjacent in the joined position.

An embodiment of the invention which is advantageous in particular in regard to particularly reliable coupling of a pressure measuring conduit is afforded if the connecting device 40 has said tube connection for conducting the respiratory gas therethrough and a conduit portion which is arranged adjacent thereto, for coupling a pressure-measuring conduit.

The tube connection for passing the respiratory gas therethrough and the conduit portion for the pressure measuring conduit, in accordance with a particularly preferred embodiment of the invention, are arranged in an opening in such a way that they do not project substantially beyond a main plane defined by the front end face of the unit. That affords 50 particularly effective protection for these comparatively filigree CPAP-unit connecting members.

In accordance with a particular aspect of the present invention the connecting device, for connection of the humidifying apparatus as required, includes electrical connecting members for affording an electrical connection to the humidifying apparatus. By way of those electrical connecting members it is advantageously possible to supply voltage to a heating device of the humidifying apparatus, without a corresponding voltage supply cable having to be manually connected for that purpose to the humidifying apparatus. The electrical connecting members can also be used for the transmission of electrical signals, for example for the transmission of a filling level signal or also for the transmission of electrical signals which are supplied for example in the region of the respiratory tube 60 connecting device.

A particularly effective coupling for the CPAP-unit to the humidifying apparatus which is intended for connection

thereto is achieved in accordance with the invention in that there is provided a latching device which can be manually put into a release position and which holds the humidifying apparatus in a joined position. By virtue of that arrangement it is advantageously possible for the humidifying apparatus to be designed in such a way as to save a great deal of weight, without in that respect involving the risk that it is by mistake pulled off the CPAP-unit by way of the connected respiratory gas tube or hose and caused to fall off the surface on which it is supported (for example an occasional table).

In accordance with a particularly preferred embodiment of the invention the CPAP-unit is designed in the bottom region in such a way that the connecting members and in particular the above-mentioned tube connection are arranged at a vertical heightwise level which exactly corresponds to the heightwise level of the connecting members provided on the humidifying apparatus.

Advantageously, the connecting members provided on the CPAP-unit and also those on the humidifying apparatus are positioned in a vertical direction in such a way that, when the CPAP-unit and the humidifying apparatus are set up on a substantially flat support, the humidifying apparatus can be pushed to the CPAP-unit, in which case the required orientation of those two modules in the vertical direction is already achieved by virtue of the surface on which they are standing. In order also to attain sufficient centering of the two modules in the lateral direction, centering aids are also provided in accordance with a particularly preferred embodiment of the invention. In that respect, a particularly robust centering aid is achieved if the inside wall of the opening which receives the tube connection is matched to the outside peripheral surface of the connecting projection provided on the humidifying apparatus.

In regard to the humidifying apparatus the object set forth hereinbefore is attained by a humidifying apparatus having one or more of the features described below. Such a humidifying apparatus can be coupled in a simple fashion to a suitable CPAP-unit, even by a lay person, without expert assembly procedures or a connecting tube or hose being required for that purpose. The CPAP-unit does not have to be lifted for that purpose.

Advantageously there is provided a humidifier unit which can be coupled to a base unit and which includes a cartridge-like refilling module which can be removed and re-fitted. The refilling module can be fixed in the humidifier unit by way of fixing devices, for example a bayonet fixing device. The refilling module can be sealed off in a portion-wise manner or completely in the humidifier unit by sealing devices.

In the context of a CPAP-therapy, spontaneous respiration of a patient is assisted by a respiratory gas under permanent increased pressure being supplied to the patient. That increased pressure affords pneumatic splinting of the upper respiratory tracts, whereby it is possible to obviate any respiratory tract obstructions which occur during a patient sleep phase. In the treatment of sleep-related respiratory disturbances in that manner, that increased-pressure artificial respiration usually extends over the entire sleep phase of the patient. In regard to improved physiological compatibility of that increased-pressure artificial respiration it has proven to be advantageous to humidify the respiratory gas which is fed to the patient. Usually, humidification of the respiratory gas is effected by the respiratory gas being passed over a water bath and in so doing absorbing moisture. An amount of water of about 750 ml is usually stored in that water bath. The water bath is preferably slightly heated by means of a heating device. When using those conventional humidifying apparatuses, it has been found that the absolute moisture content of

the respiratory gas, as viewed over the entire sleep phase, is subject to in part considerable fluctuations.

To resolve that problem, in accordance with a particular aspect of the present invention, there is described an apparatus, which is simple to handle, for the humidification of a respiratory gas, and a CPAP-unit which is intended for use therewith, by means of which it is possible to achieve uniform humidification of the respiratory gas. That is achieved by an apparatus for the humidification of a respiratory gas comprising a liquid storage space for storage of a liquid, a humidifying region for loading the respiratory gas with the liquid by the respiratory gas coming into contact in the humidifying region with the liquid, a respiratory gas supply device for supplying the respiratory gas to the humidifying region, and a respiratory gas withdrawal device for withdrawal of the humidified respiratory gas from the humidifying region, wherein there is provided a partial-amount discharge device for passing only a partial amount of the liquid stored in the liquid storage space into the humidifying region.

That arrangement makes it advantageously possible to provide a respiratory gas which is humidified according to the respective requirements involved, just a short time after the unit is brought into operation. With a desired heating effect for the humidifying medium, that can be achieved quickly and with a comparatively low level of power draw. As a result of the low level of power draw of the heating device the humidifying apparatus according to the invention is particularly suitable for operation independently of a mains network, by means of a battery or an accumulator.

In accordance with a particularly preferred embodiment of the invention the humidifying region is spatially separated from the liquid storage space. In order for supplying the humidifying medium from the liquid storage space, according to the respective requirements involved, there is preferably provided a fluid conduit device by way of which the humidifying region is in communication with the liquid storage space.

Provided between the humidifying region and the liquid storage space, in accordance with a preferred embodiment of the invention, is a separating wall which separates the humidifying region from the liquid storage space. The fluid conduit device is preferably arranged in such a way that it passes through the separating wall.

An embodiment of the invention which is advantageous in terms of particularly advantageous handleability and reliable filling of the humidifying region is afforded if the liquid storage space is arranged above the humidifying region in the position of use of the apparatus. By virtue of that arrangement, it is possible for the humidifying medium to be passed into the humidifying region as a result of the force of gravity acting thereon. The discharge of a partial amount of the liquid into the humidifying region is advantageously effected in dependence on a level of liquid in the humidifying region. In that way it is possible for a given minimum amount of humidifying liquid to be kept permanently available in the humidifying region.

The filling level in the humidifying region is advantageously quantitatively controlled by the introduction of air into the liquid storage space, for the discharge of a partial amount of the liquid out of the liquid storage space. For that purpose, in accordance with a particularly preferred embodiment, the air for introduction into the liquid storage space is drawn in by way of the humidifying region.

Control of the supply of air is preferably effected by the provision of a metering or quantitative control conduit device which extends between the liquid storage space and the humidifying region, wherein the conduit device has a first

5

mouth opening which is at the height of the level of liquid in the humidifying region and a second mouth opening which opens into the liquid storage space into a region above the level of liquid in the storage space. In that situation the first mouth opening is covered by the liquid disposed in the humidifying region until the level of liquid falls below the first mouth opening. As soon as the first mouth opening is cleared air can then flow into the liquid storage space by way of the quantitative control conduit device. As the result of that make-up flow of air, a small amount of fluid again passes into the humidifying region and the level of the liquid in the humidifying region rises until the first mouth opening is again below the level of the liquid.

The quantitative control conduit device is advantageously formed by a tube conduit which passes through the separating wall in a vertical direction.

The liquid is transferred from the liquid storage space into the humidifying region through a tube projection portion which extends from the separating wall into a region below the first mouth opening of the quantitative control conduit device or the air-introduction conduit device.

An embodiment of the humidifier which is robust and advantageous in terms of manufacture from production-engineering points of view is afforded by the separating wall and the two fluid conduit devices being of an integral nature.

The liquid storage space is preferably formed by a cup-shaped housing portion. That housing portion is preferably formed from a transparent or translucent material. Making the housing portion from a plastic material advantageously provides for protection from splintering and a still further reduction in the level of heat losses.

In accordance with a particularly preferred embodiment of the invention the humidifying region is formed in a trough or vat element. Particularly effective humidification of the respiration gas, with a structure which is still compact, can advantageously be achieved by the provision of air conduit devices which are arranged in such a way that air flows through the trough element substantially transversely or along a spiral path. That provides intensive contact of the respiratory gas with the partial amount of liquid accommodated in the humidifying region.

Particularly intensive humidification of the respiratory gas can be achieved by the provision of a heating device for heating the partial amount of liquid stored in the humidifying region. The heating device is preferably operated electrically, for example by a resistance heating means. The resistance heating means is preferably formed by a thin foil-like element thermally coupled to a bottom region of the trough element. For that purpose preferably the trough element has a bottom portion which is formed from a material of high thermal conductivity, in particular metal. As an alternative thereto or also in combination therewith, it is also possible for the heating device to be integrated directly into a wall portion, in particular a bottom portion, of the humidifying region.

Advantageously the integral member forming the separating wall is fitted in sealing relationship into the trough element by way of a first peripheral sealing device. The integral member preferably also includes a second peripheral sealing device which closes the liquid storage space in sealing relationship, in conjunction with the separating wall. The humidifying unit which is formed in that way can be opened for the refilling procedure by the trough element being removed from the housing portion which forms the liquid storage space.

In accordance with a particularly preferred embodiment of the invention, to receive the described humidifying unit there is provided a support or installation housing into which at least the trough element can be fitted. Advantageously the

6

trough element or the support housing is provided with a respiration tube connecting device for the connection of a respiration tube. In accordance with a particularly preferred embodiment of the invention there is provided a secondary or duplicate tube connecting device in the region of the respiration tube connecting device. By way of a secondary tube of preferably small diameter, which can be connected to the secondary tube connecting device, it is possible to implement pressure measurement in a region following the humidifying apparatus, for example in the region of a CO₂ exchange valve. The secondary tube connecting device is preferably arranged immediately beside a respiratory tube connecting projection. Advantageously the connecting structure provided on the humidifying apparatus for the respiration tube and preferably also for the secondary tube and in particular the pressure-measuring tube corresponds in respect of its constitution to the connecting structure correspondingly provided on a CPAP-unit. That advantageously provides for compatibility of the tube connections both with the CPAP-unit and also with the humidifying device which is possibly connected therebetween.

In that respect, a robust embodiment which is advantageous from the points of view of production engineering is afforded if the secondary tube connecting device and the respiration tube connecting device are formed integrally with the trough element or with the support housing.

In a particularly preferred embodiment of the invention the humidifying apparatus has connecting members which permit direct docking of the humidifying apparatus to a corresponding CPAP-unit.

For that purpose in accordance with a particularly preferred embodiment of the invention the CPAP-unit and the humidifying apparatus are so designed that they can be reliably and securely coupled. That arrangement preferably also entails coupling of the duplicate or secondary tube connecting device provided on the humidifying apparatus, to a connecting device provided on the CPAP-unit.

Independently of the measures described hereinbefore or also advantageously in combination therewith, the above-identified object in accordance with the invention is also attained by an apparatus for humidifying a respiratory gas comprising a liquid storage space for storing a liquid, a humidifying region for loading the respiratory gas with the liquid by the respiratory gas coming into contact in the humidifying region with the liquid, a respiratory gas supply device for supplying the respiratory gas to the humidifying region and a respiratory gas withdrawal device for withdrawal of the humidified respiratory gas from the humidifying region, wherein the liquid storage space is formed by a housing portion which is coupled to a trough element to form the humidifying region and there is provided a support or installation housing portion for receiving a unit formed by the housing portion and the trough element.

In terms of a CPAP-unit the object as set forth in the opening part of this specification is attained by a CPAP-unit comprising an outer housing, a conveyor device accommodated in the outer housing for conveying a respiratory gas to a respiratory gas outlet connection, a pressure-detection device, a control device for controlling the conveyor device in dependence on the detected pressure and a pressure-measuring connection for the connection of a pressure-detection conduit, wherein the respiratory gas outlet connection and the pressure-measuring connection are of a complementary configuration to connecting members provided on the humidifier side.

That advantageously affords a CPAP-system of a modular structure, which can be easily and quickly configured accord-

ing to the respective requirements involved, even by a lay person. The CPAP-unit system according to the invention is also distinguished, in a completely dismantled condition, by a high level of complexity and in addition can be transported in the form of a stable unit.

The invention further concerns a respiration tube connecting device for coupling a respiration tube formed from a flexible material to a CPAP-unit and a respiration tube provided with a corresponding connecting device.

Respiration tubes of that kind are used in particular in the therapy of sleep-related respiration disturbances. In that situation the respiratory gas is supplied to a patient under a predetermined increased pressure which possibly alternates during a respiration cycle, to provide for a pneumatic splinting effect for the upper respiratory tracts.

To control the respiratory gas pressure, it is known to detect by way of a pressure-measuring tube the pressure in the region of a respiratory mask or in a region which is preferably spaced therefrom by between about 10 and 15 times the inside diameter of the respiratory gas tube. That pressure-measuring tube is usually inserted into the respiration tube.

The respiration tube can be fitted directly or by way of an elastic connecting plug sleeve on to a connecting projection provided on a CPAP-unit. In that case the pressure-measuring tube is either fitted by plugging engagement on to a tube portion provided in coaxial relationship in the interior of the connecting projection or it is passed out of same by way of a small hole provided in the respiration tube and fitted in plugging engagement separately on to a corresponding pressure-detection connecting projection provided on the CPAP-unit. The known respiration tube connecting structures with integrated connecting members for a pressure-measuring tube involve the problem of a comparatively high level of respiratory resistance and difficulties in cleaning. Systems with a pressure-measuring tube which is passed freely out of same suffer from the problem that the connection of the pressure-measuring tube is forgotten under some circumstances so that this can result in an unacceptably high rise in pressure in terms of the respiratory gas feed.

Having regard to those circumstances and in accordance with a further concept of a way of attaining the object of the invention, there is provided a robust respiration tube system which is easy to handle and which is distinguished by involving a comparatively low level of respiratory resistance and with which correct coupling of the respiration tube to a CPAP-unit is guaranteed even without particular attention being paid.

In accordance with the invention that is attained by a respiration tube connecting apparatus having a base body, a respiratory gas passage duct formed in the base body, and a respiration tube connection portion for receiving an end portion of a respiration tube, which is distinguished in that provided in the base body in a region which is radially displaced with respect to the center of the respiratory gas passage duct is an additional coupling portion for coupling of an additional hose conduit to a complementary connecting structure provided on a respiratory gas source.

The base body is preferably formed from an elastomer material, whereby it is possible to provide for particularly reliable sealing integrity with the complementary connecting structure and adequate fixing of the plug connection.

The above-mentioned tube conduit connected to the additional coupling portion generally involves a pressure-measuring conduit. That additional tube conduit however may also be in the form of an analysis conduit for taking a respiratory gas sample or in the form of a flushing conduit for the

exchange of consumed respiratory gas or also in the form of a feed conduit for example for oxygen.

In accordance with a particularly preferred embodiment of the invention the passage cross-section of the respiratory gas passage duct substantially corresponds to the passage cross-section of the respiration tube. That advantageously ensures that the connecting plug does not contribute to a considerable degree to an increase in respiratory resistance.

The respiratory gas passage duct is preferably of a substantially circular cross-section and can be fitted with an easy press fit on to a connecting projection provided at the unit. Preferably the respiratory gas passage duct is of such a configuration, in its region which can be pushed on to the connecting projection, that the inside wall of the connecting projection adjoins substantially steplessly the inside wall of the following region of the respiratory gas passage duct.

The additional coupling portion is preferably formed by a cylindrical bore portion which is provided in the base body and which extends substantially parallel to the longitudinal center line of the respiratory gas passage duct. The inside diameter of the respiratory gas passage duct is preferably in the region of between 15 and 24 mm, preferably 19 mm—the inside diameter of the additional coupling portion is in the region of between 3 and 8 mm, preferably being 4 mm.

An embodiment of the invention which is particularly advantageous in terms of handling is preferably afforded if extending in the interior of the base body is a duct portion which leads from the additional coupling portion into the respiratory gas passage duct. The duct portion is preferably of a cross-section which is sufficient to receive the additional tube conduit.

Advantageously the additional tube conduit is inserted into the duct portion in sealing relationship, preferably being secured therein by adhesive. The additional tube conduit is preferably passed through the duct portion as far as a front end of the base body and introduced into the coupling portion.

A respiration tube fixing portion is advantageously formed in a region which is remote from the front end of the base body, wherein the respiration tube is fixed in the respiration tube fixing portion in sealing relationship, in particular being secured therein by adhesive or vulcanisation. As an alternative thereto or also in combination with those measures, it is also possible to provide in the respiration tube fixing portion a zone with a female screwthread, which is complementary in shape to the outside peripheral surface of a respiration tube which has a spiral insert.

In accordance with a preferred embodiment of the invention, towards the respiration tube, the inside region of the respiratory gas passage duct is also of such a configuration as to provide a substantially stepless transition into the respiration tube. That also achieves an effective reduction in respiratory resistance.

A particularly secure and load-bearing coupling between the respiration tube and the connecting plug structure is achieved by the base portion being injection-molded to the respiration tube and/or the additional tube conduit. The base body is preferably formed from an in particular transparent or translucent elastomer material, in particular silicone rubber.

The described connecting structure advantageously provides a respiration tube for a CPAP-unit, with a tube body which is formed from a flexible material, a pressure-measuring tube which is guided in the tube body, and a connecting plug structure provided at the end of the tube body, wherein the connecting plug structure is formed from an elastomer material and provided in the connecting plug structure is a duct portion by way of which the pressure-measuring tube is

passed out of a respiratory gas conduit region into a coupling portion which is disposed laterally beside a respiratory gas conduit portion.

The region of the connecting plug structure which accommodates the coupling portion preferably projects in a nose-like configuration radially beyond an outside peripheral surface of the respiration tube connecting portion, whereby it is possible to achieve particularly effective pre-positioning of the plug.

For the treatment of sleep-related respiratory disturbances it is known to feed a patient with a respiratory gas which is optionally humidified, under a predetermined increased pressure. In that respect, in most cases the provision of the respiratory gas under an increased pressure is effected by way of blowers which are regulated in respect of their rotary speed. Those blowers are usually accommodated in a preferably sound-insulated housing portion and are connected to a conduit system which leads to a humidifying device or directly to a coupling portion for the connection of a respiration tube. That coupling portion is generally in the form of a short tube connecting projection portion on to which the respiration tube can be fitted in sealing relationship.

Particularly in the case of CPAP-units for affording comparatively high respiratory gas pressure levels, it has been found to be advantageous to detect the instantaneous pressure in the respiration tube or within a respiration mask. That purpose is usually implemented by using a pressure-measuring tube, by way of which the pressure to be monitored is taken off at a defined measuring location and fed to a pressure transducer which for example is integrated into the CPAP-unit. In that case the pressure-measuring tube is fitted in sealing relationship on to a connecting projection, in a similar manner to the respiration tube. Compatibility problems frequently arise here, having regard to the large number of widely used respiration tube, pressure-measuring tube and humidifying systems.

In accordance with a further concept of the invention that is attained by a connecting structural component for a CPAP-unit having a tubular respiration gas conduction device whose passage cross-section substantially corresponds to the passage cross-section of a respiration tube provided for connection thereto, and a pressure-measuring tube connecting device for the connection of a pressure-measuring tube, wherein the respiration gas conduction device and the pressure-measuring connecting device are arranged in mutually juxtaposed relationship.

It is advantageously possible in that way for a conventional respiration tube, a conventional pressure-measuring tube or also a respiration tube with a combination plug assembly, to be connected to the correspondingly designed CPAP-unit.

The respiratory gas conduction device is preferably formed by a tube connecting projection whose inside diameter substantially corresponds to the inside diameter of a respiration tube. The pressure-measuring tube connecting device is also preferably formed by a tube connecting projection. Particularly effective protection for the two tube connecting projections is afforded by the two tube connecting projections being arranged in sunk relationship in an opening.

A particularly robust embodiment of the invention which is advantageous from production-engineering points of view is afforded if the pressure-measuring tube connecting device and the respiratory gas conduction device are of an integral construction.

In accordance with a particular aspect of the present invention the connecting, structural component is provided with a plate portion, wherein the respiratory gas conduction device passes through the plate portion. That plate portion preferably

forms a labyrinth cover means coated with a sound-insulating soft material. That soft material advantageously acts at the same time as a sealing means between adjacent portions of the labyrinth.

A further embodiment of the invention which is advantageous from production-engineering points of view is afforded if both tube connecting projections extend substantially perpendicularly from the plate portion. The connecting structural component in that case can be in a particularly advantageous manner in the form of a plastic material injection molding with tube portions which are formed integrally, that is to say in one piece, on the plate portion.

The plate portion is advantageously provided with a sealing device for fitting the structural component on to a labyrinth casing in sealing relationship. A plug connecting device is advantageously provided for fixing the connecting structural component, in particular for fixing the structural component to a bottom structure of a CPAP-unit.

BRIEF DESCRIPTION OF THE DRAWINGS

Further details and features of the invention will be apparent from the description hereinafter of a preferred embodiment of the invention with reference to the drawing in which:

FIG. 1 shows an assembly comprising a CPAP-unit and a humidifying apparatus which can be laterally coupled directly to the front or end thereof,

FIG. 2 is a simplified sectional view to explain the modular structure of the CPAP-assembly shown in FIG. 1,

FIG. 3 is a simplified view in longitudinal section through a humidifying apparatus according to the invention,

FIG. 4 is a simplified view in section taken perpendicular to the section line A-A in FIG. 3,

FIG. 5 is a perspective view of the humidifying apparatus of FIGS. 3 and 4 viewing on to the plug connecting arrangements provided for connection to a CPAP-unit,

FIG. 6a is a perspective view of a CPAP-unit with a connecting structure which is complementary to the humidifying apparatus,

FIG. 6b shows a perspective view of the humidifying apparatus of FIG. 5 but viewing on to the connecting structures at the respiration tube side,

FIG. 7 is a simplified view in axial section through an end portion of a respiration tube and associated connecting device,

FIG. 8a is a front view of the base body of the connecting device,

FIG. 8b is a side view of the respiration tube with connecting device mounted thereto,

FIG. 9 is a simplified view in section to illustrate a suitable complementary connecting structure on the unit,

FIG. 10 shows a perspective view of a structural component in accordance with a preferred embodiment of the invention, and

FIGS. 11a, 11b, 11c show three different compatible connecting options.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The apparatus arrangement shown in FIG. 1 includes a CPAP-unit here generally identified by reference numeral 1 and a humidifying apparatus 2 which can be connected thereto in modular relationship. Here the CPAP-unit 1 has a substantially block-shaped or box-shaped housing 3 which has a front end face 4, two side faces 5, 6 which are arranged in pairs in mutually opposite relationship and which are in

11

substantially parallel relationship with each other, and a rear side 7 which is arranged in the rearward region of the housing 3 in relation to the front end face 4, as well as an upper top face 8. Provided in the region of the front end face 4 is a connecting device 9 which, in the embodiment illustrated here, has a respiratory gas connecting portion 10, a pressure-measuring tube connecting portion 11 and an electrical connecting device 12. The respiratory gas connecting portion 10 and the pressure-measuring tube connecting portion 11 are arranged recessed substantially completely in an opening 13 which is only indicated here. The contact elements of an electrical connecting device 12 are also accommodated in an opening or recess so that those connecting members also do not project or do not project substantially beyond a surface defined by the front end face 4.

In the embodiment illustrated here the front end face 4 is of a slightly curved configuration, thereby affording particularly effective assistance in terms of centering the humidifying apparatus 2. The respiratory gas connecting portion 10 and the pressure-measuring tube connecting portion 11 are oriented in such a way that they extend substantially parallel to the joining direction which is indicated in simplified form by the arrow 14.

In its bottom region the CPAP-unit 1 has support or erection members (here support feet 15) which are such that the connecting members of the connecting device 9 are held at a predetermined vertical heightwise level which is matched precisely to the corresponding heightwise level of the connecting members of the humidifying apparatus 2.

The humidifying apparatus 2 includes a base body 16 and a liquid storage container 17 which is accommodated therein. The liquid storage container 17 can be removed from the base housing 16 for example for refilling it with humidifying liquid. The base housing has a connecting surface portion 18 which is of a correspondingly complementary configuration to the front end face 4 of the CPAP-unit 1 and in which are disposed the connecting members described in greater detail hereinafter with reference to FIG. 2.

On a side which is in opposite relationship to the connecting surface portion 18 the base housing 16 is again provided with connecting members which in terms of their structure and their arrangement substantially correspond to the connecting device 9 which has already been described with reference to the CPAP-unit 1. In that way it is then possible for the hose connecting plug provided for example for connection to the CPAP-unit 1 also to be connected directly to the humidifying apparatus 2. In that case connection of the pressure-measuring tube is achieved at the same time.

The humidifying apparatus 2 also has support feet 20 which provide that the connecting members on the humidifying apparatus in the region of the connecting surface portion 18 are held at a vertical heightwise level which corresponds to that of the connecting device 9.

As can be clearly seen from FIG. 2 the connecting device 9 on the CPAP-unit 1 is of a complementary configuration to the connecting device 21 on the humidifying apparatus 2. As indicated by the arrows 22 the two connecting devices 9 and 21 can be moved into the joined position in relation to each other. Particularly effective pre-positioning of the connecting members, in particular the respiratory gas connecting portion 10 and the corresponding counterpart portion 23, is achieved in this embodiment by the counterpart portion 23 also being centered by the inside wall 24 of the opening 13. The respiratory gas connecting portion 10 and the counterpart portion 23 on the humidifying apparatus 2 are disposed at exactly the same vertical heightwise level. Provided on the output side of the humidifying apparatus is a connecting structure which in

12

terms of its essential dimensions corresponds to the connecting structure provided on the CPAP-unit. The respiration tube connecting plug 25 illustrated here can thus be coupled if required directly to the CPAP-unit 1 or to the humidifying apparatus 2. By virtue of a pressure-measuring connecting conduit which is indicated into the humidifying apparatus, a communication is afforded between the pressure-measuring tube 26 and the pressure-measuring tube connecting portion 11, when the respiration tube connecting plug 25 is connected to the humidifying apparatus 2. The CPAP-apparatus arrangement described hereinbefore with reference to FIGS. 1 and 2 can be used as described in the following example of use.

It is firstly assumed that the CPAP-unit 1 is already set up on a table top, and now the respiratory gas being conveyed by the CPAP-unit 1 is to be humidified.

For that purpose, as indicated in FIG. 1, the humidifying apparatus according to the invention is also set up on the table top and is fitted on to the CPAP-unit in a joining direction which is parallel to the surface of the table and substantially perpendicular to the front end face of the CPAP-unit 1. When that is done, the connecting devices 9 and 21 which are provided on the CPAP-unit 1 and the humidifying apparatus 2 come together in the joining position. In addition, a voltage supply to a heating device provided on the humidifying apparatus 1 is also afforded by way of an electrical connecting device 12 which is only shown in FIG. 1. As soon as the two connecting devices 9, 21 have moved completely into the joined position, the two modules are fixed in that joined position by a latching device (not shown) so that the humidifying apparatus 2 is reliably coupled to the CPAP-unit. The respiratory gas tube which is originally connected directly to the CPAP-unit 1 and which has an integrated pressure-measuring conduit can be connected directly to the humidifying apparatus by way of the respiratory gas connecting plug identified by reference numeral 25 in FIG. 2. That also affords a corresponding coupling between the pressure-measuring tube 26 and the pressure-measuring tube connecting portion 11 provided on the CPAP-unit 1.

For the purposes of introducing humidifying water into the liquid storage container 17, the latter is removed from the base housing 16 of the humidifying apparatus. After the liquid storage container is filled it can be fitted into the base housing 16 again. The CPAP-apparatus system formed from two modules which can be laterally coupled, with a refilling unit which can be removed cartridge-like, is now ready for operation.

The view in FIG. 3 shows a longitudinal section through an apparatus for humidifying a respiratory gas (referred to hereinafter as the humidifying apparatus), in accordance with a preferred embodiment of the invention. Here, the illustrated embodiment of the humidifying apparatus includes a refilling unit 203 which is formed from a trough element 201 and a cup portion 202 coupled thereto and which can be easily removed from a support or installation housing 204 which here is of a multi-part nature.

The trough element 201 and the cup portion 202 are coupled together in sealing relationship. The trough element 201 and the cup portion 202 are coupled by way of a sealing structure 206 which, in the embodiment illustrated here, has a first sealing ring 207 and a second sealing ring 208. The two sealing rings 207 and 208 are accommodated in peripheral grooves provided in a separating element 209. The separating element 209 has a separating wall 205 which is here of an integral nature. The separating wall 205 separates the internal region of the cup portion 202 from the internal region of the trough element 201.

13

Formed in the cup portion **202**, in conjunction with the separating wall **205**, is a liquid storage space **210** in which initially the predominant part of the liquid provided for humidifying the respiratory gas is stored. Formed in the trough element **201** arranged beneath the cup portion **202** is a separate humidifying region in which only a partial amount of the humidifying liquid is accommodated. The level *a* of the liquid accommodated in the trough element **201** is maintained at a predetermined filling height by way of a quantitative control device. In the course of gradual consumption of the fluid in the trough element **201**, fluid is supplied as a make-up flow successively or continuously from the liquid storage space **210**. A preferred embodiment of a quantitative control device which is provided for that purpose will be described in detail hereinafter with reference to FIG. 3.

Here the trough element **201** is of a substantially shell-like nature and has a respiratory gas feed opening **211** and a respiratory gas discharge opening **212**. The respiratory gas which is conveyed by a CPAP-unit (not shown here) can flow into the trough element **201** by way of the respiratory gas feed opening **211**, according to the respiration activity of a patient. By means of a direction-changing device **213** which is only shown here in simplified form the feed flow of respiratory gas is directed on to the liquid in the trough element **201**. In that situation the respiratory gas supplied thereto is enriched with moisture. The correspondingly humidified respiratory gas can then flow away, by way of the respiratory gas discharge opening **212**.

In the embodiment illustrated here the trough element **201** can be heated by means of a heating device **214**. The heating device **214** comprises a heating element which is arranged in the support housing **204** in such a way that the bottom region of the trough element **201** can come into intimate contact therewith. In order to increase the transmission of heat between the fluid in the trough element **201** and the heating device **214** the bottom region **215** of the trough element **201** is formed from a material of high thermal conductivity, for example metal. In the last-mentioned embodiment the above-mentioned bottom region **215** can be formed for example by the insert molding method in the actual main body of the trough element **201**. The trough element **201** is of such a configuration that it can be inserted as an easy fit in self-positioning relationship into the support housing **204**. In that case the respiratory gas feed opening **211** and the respiratory gas discharge opening are aligned with conduits or openings provided in correspondingly complementary manner in the support housing **204**.

In the region adjacent to the respiratory gas feed opening **211** the support housing **204** is provided with a connecting portion **216** which, in the embodiment illustrated here, can be fitted directly on to a connecting portion of a CPAP-unit, which is of a correspondingly complementary configuration. Provided in the immediate proximity of the connecting portion **216** is a further connecting portion **217** which can be coupled to a pressure-detecting connection provided on a CPAP-unit. The connecting portion **217** forms part of a conduit system which ultimately communicates with the pressure-measuring connecting portion **218** provided on an opposite side of the humidifying apparatus. In particular a pressure-measuring tube can be connected to that pressure-measuring connection **218** for detecting the pressure in the region of the respiration hose, a gas change valve or possibly also directly in the mask region.

Beneath the pressure-measuring connecting portion **218** the support housing **204** is provided with a respiration tube connecting portion **219**. The tube connecting members formed at the outlet side on the humidifying apparatus are

14

identical to that of a CPAP-unit, in such a way that corresponding connecting tubes or hoses can be optionally connected either directly to the CPAP-unit or if necessary, when using the humidifying apparatus, only to the outlet side of the humidifying apparatus **2**. Provided beneath the connecting portion identified by reference numeral **216** is a plug connecting device (not shown here) by way of which it is possible to make an electrical connection between the heating device **214** and a voltage supply device provided on the CPAP-unit. Optionally it is also possible for electrical signals, for example pressure-measuring signals, to be transmitted by way of that plug connecting device.

The support housing **204** is further provided with a fixing device **220**, by way of which the humidifying apparatus can be mechanically comparatively rigidly coupled to a CPAP-unit.

A preferred embodiment of a quantitative control device for quantitative metering of the amount of fluid in the trough element **201** will be described hereinafter with reference to FIG. 4. The liquid storage space **210** and the humidifying region formed in the trough element **201** are separated from each other by way of the separating wall **205**. The fluid stored in the liquid storage space **210** can be passed if required into the humidifying region by way of a fluid conduit device **221**. In this case control of the make-up flow of fluid is implemented by control of the make-up introduction of air into the liquid storage space. In the embodiment illustrated here regulation of the make-up introduction of air is effected by way of a quantitative control conduit device **222** which, similarly to the above-mentioned fluid conduit device **221**, passes vertically through the separating wall **205**. The quantitative control conduit device **222** has a first mouth opening **223** and a second mouth opening **224**. The first mouth opening **223** is arranged at the height of the desired or reference level *a*. As long as the first mouth opening **223** is closed by the fluid in the trough element **201**, no make-up flow of air can pass into the liquid storage space **210** so that in turn no fluid can flow away out of the liquid storage space **210** by way of the fluid conduit device **221**. As soon as the level *a* falls below the level of the first mouth opening, a make-up flow of air can pass into the liquid storage space, whereby in turn fluid can pass out of the liquid storage space **210** into the trough element **201** or the separate humidifying region formed therein. The fluid conduit device **221** has a discharge mouth opening **225** which is somewhat below the reference level identified here by the letters *a*.

In the embodiment illustrated here the fluid conduit device **221**, the quantitative control conduit device **222** and the separating wall **205** are formed by an integral member. For the purposes of introducing the liquid into the liquid storage space, it is possible for that integral member to be withdrawn from the cup portion **202**. The cup portion **202** can optionally also be provided with a corresponding refilling opening which can be sealingly closed. The cup portion **202**, the integral member having the separating wall and the trough element can each be cleaned separately. The quantitative control conduit device **222** is of such a design configuration that the second mouth opening **224** provided thereon is above the maximum filling level of the liquid storage space **210**.

FIG. 5 is a perspective view of the humidifying apparatus described hereinbefore with reference to FIGS. 3 and 4. The cup portion which is preferably formed from a transparent material can be seen here in the form of a bowl of substantially cylindrical configuration. That bowl is fitted in a receiving portion which is also cylindrical and which is formed in the support housing **204**. In the region of the cup portion **202** the support housing **204** is of such a design configuration that the

15

cup portion can be gripped with one hand. The connecting portion **217** and the pressure-measuring connecting portion **218** which have already been described with reference to FIG. **3** are provided in the region of the rear side **226** of the humidifying apparatus. Provided beneath those connecting portions is the fixing device which is identified by reference **220** in FIG. **3** and which can provide particularly rigid coupling of the humidifying apparatus to a corresponding CPAP-unit. Provided in a receiving recess beneath the connecting portion **216** is an electrical plug connecting arrangement (not shown here) for providing an electrical connection for the heating device to the associated CPAP-unit.

Provided in the lateral region of the outer housing are switch members **227**, by way of which it is possible to set on the one hand the temperature of the liquid in the trough element **201** and the switch-on time for the humidifying apparatus.

The rear side **226** of the humidifying apparatus is of a configuration corresponding to the front side of a CPAP-unit described hereinafter with reference to FIG. **6a** so that the humidifying apparatus can be connected in a modular manner virtually without any intermediate space to the CPAP-unit.

The CPAP-unit shown in FIG. **6a** has a substantially cuboidal housing, in the upper region of which is provided a gripping arrangement **330**, by way of which the CPAP-unit can be gripped in an ergonomically advantageous manner. Provided in a front end region are connecting members **331**, for the connection of at least one respiration tube or hose.

The illustrated embodiment has a respiration hose connecting projection **332** and a pressure-measuring tube connecting projection **333**. The arrangement of those connecting members substantially corresponds to the arrangement of the connecting members **216** and **217** described with reference to FIG. **3**. The connecting members **331** are further of such a configuration that the connecting members **216**, **217** on the humidifying apparatus (FIG. **3**) can be directly fitted on or fitted in. Also provided in the bottom region of the CPAP-unit are engagement structures which can be brought into engagement with engagement portions of a complementary configuration, on the humidifying apparatus. The connecting members **331** are here arranged in recessed relationship in such a way that they do not project beyond an outside surface and in particular a front surface of the housing.

FIG. **6b** shows the humidifying apparatus described hereinbefore with reference to FIGS. **3**, **4** and **5**, viewing on to the front region thereof. The connecting portions **216** and **217** are arranged in recessed relationship, similarly as also in regard to the CPAP-unit. The connecting portions are surrounded by a plug-receiving space **234** into which can be inserted a plug preferably formed from a soft material, in particular silicone rubber.

The plug-receiving space **234** is preferably of such a nature that a corresponding plug slides both on the respective projection **216**, **217** and also along the wall of the plug-receiving space **234**.

The invention is not limited to the embodiments by way of example described hereinbefore. For example it is also possible for the described humidifying apparatus to be integrated directly into a corresponding CPAP-unit. It is also possible to fit into the support housing which can be docked in a simple fashion to a CPAP-unit, refilling units which deviate in respect of their structure and the humidifying principle involved, from the described humidifying apparatus. It is also possible for the trough element of the humidifying unit to be so designed that it can be connected directly to the CPAP-unit, omitting the support or installation housing. The described humidifying apparatus can also be connected to a respiratory

16

gas source, with the interposition of a hose conduit. The refilling unit can also be arranged in the form of a substantially trough-like unit under the CPAP-unit.

The respiration tube or hose **301** shown in FIG. **7** is provided in its end region with a connecting device **302** which here has a base body **303** formed from an elastomer material, in particular silicone rubber, with two coupling portions **304**, **305** formed therein.

The two coupling portions **304**, **305** are formed integrally by mutually parallel tube zones which are of circular cross-section. The inside diameter of the respective tube zone is slightly smaller than the outside diameter of the connecting projections which pass into the two tube zones when the plug is connected thereto and in that case is slightly enlarged.

Formed in the region of the base body, which is towards the hose or tube, is a fixing portion **306** in which the respiration tube **301** is fixed by way of a ring element **307**. The ring element **307** is here also formed from an elastomer material and is secured by adhesive to the outside surface of the respiration tube.

An additional tube—here a pressure-measuring tube **308**—is guided in the interior of the respiration tube **301**. The pressure-measuring tube **308** opens into the coupling portion **305** by way of a passage duct **309** formed in the base body **303**. The pressure-measuring tube **308** is secured by adhesive or vulcanisation in the base body **303**. The passage duct **309** is of such a configuration that the pressure-measuring tube **308** is only slightly curved. The angle α between the longitudinal center line of the coupling portion **304** and the longitudinal center line of the passage duct **309** is preferably less than 35° .

The transition of the inside wall of the pressure-measuring tube **309** into the coupling portion **305** is effected here substantially steplessly. A corresponding shoulder **310** is provided at the end of the passage duct **309**, for that purpose.

The respiratory gas conduit region **311** formed in the base body **303** in this case also forms a substantially stepless transition into the inner region of the respiration tube **301**.

With suitable elasticity of the tubes **301**, **308**, it is possible for them to be passed to the end face **312** of the base body **303** so that the coupling members on the unit side can pass directly into the tubes **301**, **308**.

The external configuration of the base body shown in FIG. **7** will be described in still greater detail with reference to FIGS. **8a** and **8b**. As can be clearly seen in particular from FIG. **8a**, the coupling portion intended for the connection of the additional tube is arranged at a radial spacing from the respiratory gas conduit coupling portion **304** in a region **314** of the base body **303**, which projects radially outwardly in a nose-like configuration. That provides for effective preliminary positioning of the base body in a recess provided in the unit.

That region which extends radially outwardly in a nose-like configuration decreases continuously towards the end of the base body **1**, which is towards the respiration tube. Provided in the region of the end towards the tube is a peripheral bead or ridge **315**, by way of which a flow of forces between the hose and the plug structure, which is advantageous from mechanical points of view, is achieved.

FIG. **9**, for explanatory purposes, shows a preferred embodiment of a connecting structure on the unit, which connecting structure is of a substantially complementary configuration to the coupling portions **304**, **305** provided in the base body **303** of the plug.

The projection portion which is identified here by reference **316** passes into the coupling portion **304** in the joined position of the assembly. The projection portion identified by

17

reference numeral 317 comes into engagement with the coupling portion in the joined position. The two projection portions 316, 317 are arranged in recessed relationship in a recess 318. The inside wall which defines the recess 318, in conjunction with the external contour of the base body 303 shown in FIG. 8a, provides for pre-positioning thereof.

The connecting structural component shown in FIG. 10 includes a respiratory gas conduction device which is here in the form of a tube projection portion 401. A further tube projection portion 402 is arranged adjacent to that tube projection portion 401, leaving an intermediate space. The tube projection portion 402 forms a pressure-measuring tube connecting device. The two tube projection portions 401, 402 are arranged in recessed relationship in a recess 403. That recess is surrounded by a front cover plate 404. The cover plate 404 and the wall defining the recess 403 are formed in one piece.

In a region remote from the end of the tube projection 401, which is towards the tube, it opens into a base plate 405 which here forms a cover plate for a labyrinth arrangement. This labyrinth arrangement which is not described in greater detail here forms a prolonged respiratory gas guide path for the absorption of any odors produced by a blowing device. The base plate 405 is coated with a sound-absorbing material, in particular foam, on the rear side which is not visible here.

Provided in a region between the base plate 405 and the cover plate 404 is a connecting duct 406, by way of which the interior of the tube projection 402 can be coupled to a pressure transducer arranged on a control board.

The connecting structural component is further provided with fixing devices 407, 408, by way of which that component can be fixed in a CPAP-unit in an easily interchangeable manner.

More particularly but not exclusively the conduit devices shown in FIGS. 11a, 11b and 11c can be connected to the illustrated connecting structural component.

In this respect FIG. 11a shows a compact plug which is advantageous in terms of handling, from ergonomic points of view, with an integrated pressure-measuring tube passage configuration.

FIG. 11b shows a respiration tube 409 and a pressure-measuring tube 410 which is independent thereof, both of which can be connected without a plug arrangement directly to a corresponding CPAP-unit, by way of the connecting structural component according to the invention.

FIG. 11c is a greatly simplified view showing a coupling portion of a humidifying apparatus which can be fitted directly to a CPAP-unit by way of the structural component according to the invention. In that case the projection portion identified by reference numeral 411 engages with the tube projection 401 and the bore portion 412 with the tube projection 402.

The invention claimed is:

1. A CPAP apparatus comprising:

- a CPAP unit with a blower configured to pressurize gas, the CPAP unit comprising an outlet in a side wall;
- a liquid storage container configured to hold a body of liquid, the liquid storage container comprising a humidifying region above a metallic heat conducting material, the humidifying region being a region inside the liquid storage container in which the liquid is evaporated into pressurized respiratory gas generated by the CPAP unit blower; and
- a humidifier base unit configured to a) receive the liquid storage container and b) connect to the CPAP unit, the base unit comprising:
 - a housing providing a) a base portion to support the liquid storage container thereon and b) a side wall

18

with a first surface configured to engage the side wall of the CPAP unit, the base portion including a heating element configured to contact the heat conducting material of the liquid storage container when the liquid storage container is supported on the base unit; and

an inlet at the side wall of the humidifier base unit configured to receive and be coupled to the outlet of the CPAP unit by moving the CPAP unit and the humidifier base unit housing toward each other, wherein the liquid storage container is removable from the humidifier base unit.

2. The CPAP apparatus according to claim 1, wherein the humidifier base unit housing and the liquid storage container are configured so that moving the liquid storage container to be fully received by the humidifier base unit aligns a liquid storage container inlet with a gas supply passage in the base unit housing.

3. The CPAP apparatus according to claim 2, wherein the side wall of the humidifier base unit housing comprises a) a first surface configured to face the CPAP unit and b) a second surface proximate the first surface and facing a direction substantially opposite a direction the first surface faces, the second surface being configured to face the liquid storage container,

wherein the gas supply passage terminates at the humidifier base unit inlet.

4. The CPAP apparatus according to claim 1, wherein an interior of the liquid storage container comprises at least one direction changing device configured to change a direction of a flow of gas inside the liquid storage container.

5. The CPAP apparatus according to claim 1, wherein the humidifier base unit includes electrical contact elements configured to communicate with a power supply.

6. The CPAP apparatus according to claim 1, wherein the humidifier base unit housing and the liquid storage container are configured so that securing the liquid storage container to the base unit aligns an inlet of the liquid storage container with a gas supply passage in the humidifier base unit housing,

wherein the side wall of the humidifier base unit housing comprises a) a first surface configured to face the CPAP unit and b) a second surface that is opposite the first surface and is configured to face the liquid storage container,

wherein the gas supply passage terminates at the humidifier base unit inlet,

wherein an interior of the liquid storage container comprises at least one baffle configured to change a direction of a flow of gas inside the liquid storage container, and wherein the humidifier base unit includes contact elements configured to communicate with a power supply.

7. The CPAP apparatus of claim 1, wherein the humidifier base unit is configured to a) directly dock with the CPAP unit without the CPAP unit being lifted and b) humidify the pressurized gas.

8. The CPAP apparatus according to claim 7, wherein the side wall of the CPAP unit is configured to engage and disengage from the side wall of the humidifier base unit, at least a portion of the side wall of the CPAP unit being convex and a portion of the first surface of the side wall of the humidifier base unit being configured to engage the convex portion and being concave.

9. The CPAP apparatus according to claim 7 further comprising a latching device configured to couple the side wall of the CPAP unit to the side wall of the humidifier base unit.

10. The CPAP apparatus according to claim 7, wherein the side wall of the CPAP unit comprises a first electrical con-

19

necter and the side wall of the humidifier base unit comprises a second electrical connector configured to engage the first electrical connector to provide electrical power to the heating element when the CPAP unit and the humidifier base unit are coupled together.

11. A humidifier assembly for a CPAP unit, the humidifier assembly comprising:

- a liquid storage container configured to hold a body of liquid, the liquid storage container comprising a humidifying region above a heat conducting material, the humidifying region being a region inside the liquid storage container in which the liquid is evaporated into pressurized respiratory gas generated in the CPAP unit; and
- a base body configured to support the liquid storage container and configured to be directly laterally coupled to the CPAP unit, the liquid storage container being removable from the base body, the base body comprising:
 - a connecting portion configured to be directly fitted to a tube connector of the CPAP unit and receive pressurized gas from the CPAP unit when the base body is directly laterally coupled to the CPAP unit;
 - a laterally extending gas feed passage configured to convey pressurized gas from the connecting portion to a gas feed opening of the liquid storage container, the base body and the liquid storage container being configured so that the gas feed opening is automatically aligned to receive pressurized gas from the laterally extending gas feed passage when the liquid storage container is fully received by the base body; and
 - a resistance heater in a base portion of the base body, the resistance heater being configured to be in direct contact with the heat conducting material of the liquid storage container when the liquid storage container is supported on the base body.

12. The humidifier assembly according to claim 11, wherein the liquid storage container further comprises a respiratory gas discharge opening and the base unit further comprises a) a respiration tube connection portion configured to be coupled to a respiration tube and b) a respiratory gas discharge passage configured to convey pressurized gas from the respiratory gas discharge opening to the respiration tube connection portion, and

wherein the base body and the liquid storage container are configured so that the respiratory gas discharge opening is automatically aligned with the respiratory gas discharge passage when the liquid storage container is fully received by the base body.

13. The humidifier assembly according to claim 11, wherein the base body further comprises an electrical connecting device configured to receive at least one of a) voltage supply for the resistance heater and b) electrical signals for controlling the humidifier assembly, wherein the electrical connecting device is configured to automatically engage the CPAP unit when the CPAP unit and the humidifier assembly are coupled together.

14. The humidifier assembly according to claim 11, wherein the base body comprises engagement structures configured to engage the CPAP unit and directly laterally couple the humidifier assembly to the CPAP unit.

15. The humidifier assembly according to claim 11, wherein the base body comprises a latching device configured to engage the CPAP unit and directly laterally couple the humidifier assembly to the CPAP unit.

16. The humidifier assembly according to claim 11, wherein the liquid storage container further comprises a respiratory gas discharge opening and the base unit further com-

20

prises a) a respiration tube connection portion configured to be coupled to a respiration tube and b) a respiratory gas discharge passage configured to convey pressurized gas from the respiratory gas discharge opening to the respiration tube connection portion,

wherein the base body and the liquid storage container are configured so that the respiratory gas discharge opening is automatically aligned with the respiratory gas discharge passage when the liquid storage container is fully received by the base body,

wherein the base body further comprises an electrical connecting device configured to receive at least one of a) voltage supply for the resistance heater and b) electrical signals for controlling the humidifier assembly, wherein the electrical connecting device is configured to automatically engage the CPAP unit when the CPAP unit and the humidifier assembly are coupled together, and wherein the base body comprises engagement structures configured to engage the CPAP unit and directly laterally couple the humidifier assembly to the CPAP unit.

17. A CPAP apparatus comprising:

the humidifier assembly according to claim 11; and the CPAP unit configured to be directly, laterally coupled to the humidifier assembly,

wherein the humidifier assembly is configured to a) be connected to the CPAP unit in modular relationship and b) humidify the pressurized gas, wherein the CPAP unit comprises a tube connection configured to be selectively coupled to one of the connection portion of the humidifier assembly and a respiration tube configured to deliver the pressurized gas to a patient.

18. The CPAP apparatus according to claim 17, wherein the CPAP unit and the humidifier assembly are configured so that the a tube connection of the CPAP unit and the connection portion of the humidifier assembly are automatically positioned at exactly the same vertical heightwise level when the CPAP unit and the humidifier assembly stand on the same flat the surface.

19. The CPAP apparatus according to claim 17, wherein the CPAP unit and the humidifier assembly further comprise support feet configured to position the connecting portion of the humidifier assembly and the tube connection of the CPAP unit at the same vertical heightwise level.

20. The CPAP apparatus according to claim 17, wherein the CPAP unit and the humidifier assembly are configured to be coupled together in a joining direction, and wherein the CPAP unit and the humidifier assembly connecting members are oriented substantially in the joining direction.

21. A humidifier assembly for a CPAP unit, the humidifier assembly comprising:

a base unit with a first upright surface facing a first direction and a second upright surface adjacent the first upright surface and facing a second direction opposite the first direction, the first upright surface being configured to engage the CPAP unit, the base unit having an inlet at the first upright surface;

at least one centering aid configured to center the base unit with respect to the CPAP unit in a lateral direction when the base unit is coupled to the CPAP unit;

a gas flow passage extending at least from the base unit inlet to the second upright surface; and

a liquid storage container configured to be coupled to and removed from the base unit, the liquid storage container comprising an inlet,

wherein the gas flow passage and the liquid storage container inlet are configured to cooperate to form a continuous sealed air path from the base unit inlet to an

21

interior of the liquid storage container when the liquid storage container is coupled to the base unit.

22. The humidifier assembly according to claim 21, wherein the base unit air inlet is configured to be coupled to an air outlet of the CPAP unit.

23. The humidifier assembly according to claim 21, wherein the liquid storage container comprises a third upright surface configured to be adjacent the second upright surface when the liquid storage container is coupled to the base unit, and wherein at least a portion of the second upright surface has a curvature that is complimentary to a curvature of the third upright surface.

24. The humidifier assembly according to claim 21, wherein the liquid storage container comprises a third upright surface configured to be adjacent the second upright surface when the liquid storage container is coupled to the base unit, and wherein at least a portion of the second upright surface is curved and has the same center of curvature of a corresponding portion of the third upright surface.

25. The humidifier assembly according to claim 21, wherein the liquid storage container comprises:

a bottom portion, at least part of the bottom portion being constructed of a heat conducting material, wherein the base unit comprises a heating element configured to contact the heat conducting material of the bottom portion of the liquid storage container when the liquid storage container is coupled to the base unit.

26. The humidifier assembly according to claim 21, wherein the base unit air inlet is configured to be coupled to an air outlet of the CPAP unit,

wherein the liquid storage container comprises a third upright surface configured to be adjacent the second upright surface when the liquid storage container is coupled to the base unit,

wherein at least a portion of the second upright surface has a curvature that is complimentary to and has the same center of curvature as a corresponding portion of the third upright surface,

wherein the liquid storage container comprises a bottom portion, at least part of the bottom portion being constructed of a heat conducting material, and

22

wherein the base unit comprises a heating element configured to contact the heat conducting material of the bottom portion of the liquid storage container when the liquid storage container is coupled to the base unit.

27. A CPAP apparatus comprising:

a humidifier assembly according to claim 21; and

the CPAP unit configured to be coupled to the humidifier assembly, the CPAP unit having a block-shaped or box-shaped housing,

wherein the humidifier assembly is configured to a) be connected to the CPAP unit in a modular manner virtually without any intermediate space between the CPAP unit and the humidifier assembly and b) humidify pressurized gas.

28. The CPAP apparatus according to claim 27, wherein the CPAP unit housing comprises an engagement face configured to engage and disengage from the first upright surface of the humidifier assembly base unit, at least a portion of the engagement face of the CPAP unit being convex and a portion of the first upright surface of the humidifier assembly base unit being configured to engage the convex portion and being concave.

29. The CPAP apparatus according to claim 27, wherein the CPAP unit comprises an engagement face configured to engage the first upright surface of the humidifier assembly, the CPAP unit comprising a first electrical connector and the first upright surface of the humidifier assembly base unit comprises a second electrical connector configured to engage the first electrical connector to provide electrical power to a heating element of the humidifier assembly base unit when the CPAP unit and the humidifier assembly are coupled together.

30. The CPAP apparatus according to claim 27 further comprising a latching device configured to be selectively moved between a locked position and a release to couple the CPAP unit to the humidifier assembly base unit and decouple the CPAP unit from the humidifier base unit.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,302,067 B2
APPLICATION NO. : 14/791744
DATED : April 5, 2016
INVENTOR(S) : Mayer et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the claims:

In claim 30, at column 22, line 35, "...moved between a locked position and a release to couple the CPAP unit to the humidifier assembly base unit and decouple the CPAP unit from the humidifier base unit" should be corrected to **"moved between a locked position and a release position to couple the CPAP unit to the humidifier assembly base unit and decouple the CPAP unit from the humidifier assembly base unit."**

Signed and Sealed this
Thirty-first Day of May, 2016

A handwritten signature in black ink, reading "Michelle K. Lee". The signature is fluid and cursive, with the first letters of each name being capitalized and prominent.

Michelle K. Lee
Director of the United States Patent and Trademark Office