



(22) Date de dépôt/Filing Date: 2012/04/23

(41) Mise à la disp. pub./Open to Public Insp.: 2012/12/24

(30) Priorité/Priority: 2011/06/24 (US13/167,879)

(51) Cl.Int./Int.Cl. *G05B 15/02* (2006.01),
G05B 19/418 (2006.01), *H04N 7/18* (2006.01)


(71) Demandeur/Applicant:
THE BOEING COMPANY, US

(72) Inventeurs/Inventors:
REID, ERIC M., US;
MERKLEY, ALAN RAY, US

(74) Agent: SMART & BIGGAR

(54) Titre : SYSTEME DE CONTROLE DE FABRICATION

(54) Title: MANUFACTURING CONTROL SYSTEM



(57) Abrégé/Abstract:

A method and apparatus comprising a tracking system and a controller in communication with the tracking system. The tracking system is configured to identify characteristics about a group of portable machines configured to perform a number of manufacturing operations on a workpiece. The controller is configured to control performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system.

ABSTRACT

A method and apparatus comprising a tracking system and a controller in
5 communication with the tracking system. The tracking system is configured to identify
characteristics about a group of portable machines configured to perform a number of
manufacturing operations on a workpiece. The controller is configured to control
performance of the number of manufacturing operations on the workpiece using the
characteristics about the group of portable machines identified using the tracking system.

MANUFACTURING CONTROL SYSTEM

BACKGROUND INFORMATION

5 **Field:**

The present disclosure relates generally to manufacturing and, in particular, to manufacturing structures using machines. Still more particularly, the present disclosure relates to a method and apparatus for manufacturing structures using computer controlled machines.

10

Background:

15

When manufacturing structures, such as those for aircraft, many different operations are performed to form the structures. For example, two components may be assembled to form a structure. These components may be fastened and/or attached to each other during the manufacturing process.

Machines may be used to position the components relative to each other. Further, these and/or other machines also may be used to form holes, install fasteners, and seal the holes. Operations also may be performed to inspect these manufacturing operations as well as the finished structure.

20

In manufacturing structures, different types of machines are used. Typically, these machines are often large and not easily moveable. For example, large machines may be in fixed locations. As a result, the different components are moved to the location of the machines to perform different manufacturing operations.

25

These large machines are in fixed locations and may be computer controlled machines that provide desired accuracy as well as repeatability. With these types of computer controlled machines, a high level of timing may be present. As a result, less human intervention or operation is needed. These types of machines also are easily manageable.

30

However, the cost and/or amount of space in a manufacturing facility needed for these types of machines is often greater than desired. Further, performing maintenance for these machines may be difficult. When using a machine in a fixed location to perform manufacturing operations on one or more components, performing concurrent work on

other portions of these components may be restricted. This restriction may be caused by, for example, zones in which the operators are not allowed to enter during the performance of the manufacturing operations by the machine.

When assembling components, portable machines may also be used. These machines are moveable from one location to another location. Portable machines typically cost less and have less complexity as compared to the larger machines that require movement of parts to those machines. These types of portable machines may allow for many machines to be used at substantially the same time. As a result, the time needed to process components may be reduced.

Portable machines, however, may require frequent movement to different locations to perform manufacturing operations. The time needed to setup these types of machines to perform machining operations may be greater than desired.

Further, portable machines typically only provide one type of functionality as compared to larger machines which may be configured to perform multiple functions. For example, a portable machine may only be configured to drill holes and may not be configured to seal and/or install fasteners into the holes. A different machine may need to be moved to the location to perform other functions.

Although portable machines provide greater flexibility than machines that are in fixed locations, more coordination of these machines is needed to provide efficient performance in manufacturing operations. Further, more experienced operators may be required to operate portable machines as compared to machines that are in fixed locations. For example, operators may need to be experienced in placing the portable machines in the appropriate locations, selecting the correct programs for operating the portable machines, and taking into account locations that may not be reachable by the portable machines.

Therefore, it would be advantageous to have a method and apparatus that takes in account at least some of the issues discussed above as well as possibly other issues.

SUMMARY

In one advantageous embodiment, an apparatus comprises a tracking system and a controller in communication with the tracking system. The tracking system is configured

to identify characteristics about a group of portable machines configured to perform a number of manufacturing operations on a workpiece. The controller is configured to control performance of the number of manufacturing operations on the workpiece using characteristics about the group of portable machines identified by the tracking system.

5 In another advantageous embodiment, an aircraft manufacturing system comprises a group of portable machines, a tracking system, and a controller. The group of portable machines is configured to perform a number of manufacturing operations on a workpiece for an aircraft. The tracking system is configured to identify characteristics about the group of portable machines. The controller is in communication with the tracking
10 system. The controller is configured to control performance of the number of manufacturing operations on the workpiece using at least one of the characteristics about the group of portable machines identified using the tracking system, information about the workpiece, and information about the group of portable machines.

 In yet another advantageous embodiment, a method for managing manufacturing
15 operations is provided. Characteristics about a group of portable machines are identified using a tracking system and a controller. Performance of a number of manufacturing operations on a workpiece is controlled by the group of portable machines using the characteristics about the group of portable machines identified using the tracking system.

 The features, functions, and advantages can be achieved independently in various
20 embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

25

 The novel features believed characteristic of the disclosure are set forth in the appended claims. The disclosure itself, however, as well as a preferred mode of use, further objectives, and advantages thereof, will best be understood by reference to the following detailed description of an advantageous embodiment of the present disclosure
30 when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a manufacturing environment in accordance with an advantageous embodiment;

Figure 2 is an illustration of a manufacturing environment in the form of a block diagram in accordance with an advantageous embodiment;

Figure 3 is an illustration of a tracking system in the form of a block diagram in accordance with an advantageous embodiment;

5 **Figure 4** is an illustration of a group of portable machines in the form of a block diagram in accordance with an advantageous embodiment;

Figure 5 is an illustration of a placement system in the form of a block diagram in accordance with an advantageous embodiment;

10 **Figure 6** is an illustration of a manufacturing environment in accordance with an advantageous embodiment;

Figure 7 is an illustration of another manufacturing environment in accordance with an advantageous embodiment;

Figure 8 is an illustration of a display on a graphical user interface in accordance with an advantageous embodiment;

15 **Figure 9** is an illustration of a flowchart of a process for managing manufacturing operations in accordance with an advantageous embodiment;

Figure 10 is an illustration of a flowchart of a process for managing manufacturing operations in accordance with an advantageous embodiment;

20 **Figure 11** is an illustration of a process for inspecting holes that have been drilled into a workpiece in accordance with an advantageous embodiment;

Figure 12 is an illustration of a data processing system in accordance with an advantageous embodiment;

Figure 13 is an illustration of an aircraft manufacturing and service method in accordance with an advantageous embodiment; and

25 **Figure 14** is an illustration of an aircraft in which an advantageous embodiment may be implemented.

DETAILED DESCRIPTION

30 The different advantageous embodiments recognize and take into account a number of different considerations. A number, as used herein with reference to items, means one or more items. For example, a number of considerations is one or more

considerations. For example, the different advantageous embodiments recognize and take into account that using portable machines is more desirable than using machines that are in fixed locations if the portable machines can be more accurately controlled.

The different advantageous embodiments also recognize and take into account that using a computer system to manage the placement and programming of portable machines may reduce the time needed for operating these machines. Further, using this type of computer system may reduce the number of errors that may occur when operating these portable machines.

Thus, the different advantageous embodiments provide a method and apparatus for managing manufacturing operations. In one advantageous embodiment, an apparatus comprises a tracking system and a controller in communication with the tracking system. The tracking system is configured to identify characteristics about a group of portable machines configured to perform a number of manufacturing operations on a workpiece. The controller is configured to control performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system.

With reference now to the figures and, in particular, with reference to **Figure 1**, an illustration of a manufacturing environment is depicted in accordance with an advantageous embodiment. In this depicted example, a pictorial illustration of manufacturing environment **100** is shown.

In this illustrative example, manufacturing operations are performed on wing **102** in manufacturing environment **100**. Wing **102** is located inside of cell **104** within manufacturing environment **100**. Cell **104** is a location in which manufacturing operations are performed on a structure, such as wing **102**. In these illustrative examples, manufacturing system **106** comprises tracking system **108**, controller **110**, and group of portable machines **112**.

In this illustrative example, tracking system **108** comprises cameras **114**, **116**, **118**, **120**, **122**, **124**, **126**, **128**, **130**, **132**, **134**, **136**, and **138**. Group of portable machines **112** comprises portable machines **140**, **142**, **144**, **146**, **148**, **150**, and **152**. As used herein, “a group”, when used with reference to items means one or more items. For example, “group of portable machines **112**” is one or more portable machines.

Tracking system **108** is configured to identify characteristics of group of portable machines **112** in these illustrative examples. A portable machine in group of portable machines **112** is any machine or piece of equipment that may be used to perform a manufacturing operation on a workpiece.

5 In this illustrative example, manufacturing system **106** also includes placement system **154**. Placement system **154** includes placement machines **156**, **158**, **160**, and **162**. Placement machines **156**, **158**, and **160** are used to place portable machines **140**, **142**, and **144** on the underside of wing **102**, while placement machine **162** is used to place portable machines **146**, **148**, **150**, and **152** on the topside of wing **102** in these illustrative
10 examples.

Placement system **154** is controlled by controller **110** in these illustrative examples. Controller **110** takes the form of a computer and identifies locations at which group of portable machines **112** should be placed.

15 Placement of group of portable machines **112** is directed by controller **110** to place group of portable machines **112**. The placement is based on information about group of portable machines **112** identified by tracking system **108** in these illustrative examples. This information includes characteristics about group of portable machines **112**. In addition to using placement system **154** to place group of portable machines **112**, human operators such as human operator **164** and human operator **166** also may assist in
20 positioning group of portable machines **112** relative to wing **102**.

With the use of controller **110** and the information identified by tracking system **108**, group of portable machines **112** may be more precisely placed onto locations on wing **102** to perform manufacturing operations as compared to human operators placing group of portable machines **112** onto wing **102** without assistance from controller **110**.

25 Further, in these illustrative examples, controller **110** is configured to control the performance of manufacturing operations by group of portable machines **112** using the characteristics about group of portable machines **112** identified by tracking system **108**.

30 With reference now to **Figure 2**, an illustration of a manufacturing environment in the form of a block diagram is depicted in accordance with an advantageous embodiment. Manufacturing environment **100** in **Figure 1** is an example of one implementation for manufacturing environment **200** shown in block form in **Figure 2**.

Manufacturing environment **200** is used to perform number of manufacturing operations **202** on workpiece **204**. Workpiece **204** may be any object on which number of manufacturing operations **202** are performed by a machine. A manufacturing operation in the number of manufacturing operations is selected from one of a drilling operation, a sealing operation, a fastener installation operation, an inspection operation, and a painting operation. Workpiece **204** may be a single part or multiple parts.

Wing **102** in **Figure 1** is an example of workpiece **204**. Other illustrative examples of workpiece **204** may include, for example, without limitation, an aircraft, an aircraft part, a wing, a stabilizer, a portion of a fuselage, an engine, an engine housing, a landing gear assembly, and other suitable types of workpieces.

In these illustrative examples, number of manufacturing operations **202** are performed on workpiece **204** inside cell **206**. Cell **206** is a location in which number of manufacturing operations **202** may be performed. In these illustrative examples, cell **206** may be an enclosed space, such as a building, a hanger, or some other suitable structure. In other illustrative examples, cell **206** may be an area in a manufacturing facility, a factory, a production plant, or some other location.

Manufacturing system **208** is configured to perform number of manufacturing operations **202** on workpiece **204** within cell **206**. As depicted, manufacturing system **208** comprises tracking system **210**, controller **212**, placement system **214**, and group of portable machines **216**.

A portable machine in group of portable machines **216** is a machine that can be moved to a number of different locations on workpiece **204** to perform one or more of number of manufacturing operations **202**. Portable machines in group of portable machines **216** may be of different types and/or the same type. Portable machine **226** is an example of one of group of portable machines **216**. Further, tool **228** may be connected to portable machine **226** in these illustrative examples.

As used herein, a first component “connected to” a second component means that the first component can be connected directly or indirectly to the second component. In other words, additional components may be present between the first component and the second component. The first component is considered to be indirectly connected to the second component when one or more additional components are present between the two components. When the first component is directly connected to the second component,

no additional components are present between the two components. Tool **228** is the first component, and portable machine **226** is the second component in this illustrative example.

5 Tool **228** may be configured to perform one or more of number of manufacturing operations **202** on workpiece **204**. In these illustrative examples, tool **228** may be moved independently of portable machine **226**. In other words, tool **228** may be moved relative to workpiece **204** without moving portable machine **226**.

10 In these illustrative examples, portable machine **226** may take the form of a hand tool, a flex track machine, a robotic machine, or some other suitable type of machine that can move relative to workpiece **204**. A flex track machine is a modular multi-axis numerically-controlled positioning system that performs number of manufacturing operations **202**.

15 In this illustrative example, tracking system **210** is configured to identify information **217** about group of portable machines **216**. In particular, information **217** about group of portable machines **216** is information about one, some, or all of group of portable machines **216**. Further, this information may be about the tools connected to these portable machines. For example, information **217** may include information about portable machine **226** and/or tool **228** connected to portable machine **226**.

20 Additionally, information **217** may include characteristics **218** about one, some, or all of group of portable machines **216** and/or any of the tools connected to group of portable machines **216**. Characteristics **218** may include, for example, at least one of position **220**, orientation **222**, movement **224**, and other suitable characteristics about group of portable machines **216**. Characteristics **218** may also include an identifier for a portable machine in group of portable machines **216**.

25 As used herein, the phrase “at least one of”, when used with a list of items, means different combinations of one or more of the listed items may be used and only one of each item in the list is needed. For example, “at least one of item A, item B, and item C” may include, for example, without limitation, item A, or item A and item B. This example also may include item A, item B, and item C, or item B and item C. In other
30 examples, “at least one of” may be, for example, without limitation, two of item A, one of item B, and ten of item C; four of item B and seven of item C; and other suitable combinations.

In these illustrative examples, position **220**, orientation **222**, and movement **224** may be identified for portable machine **226**. Position **220**, orientation **222**, and movement **224** for portable machine **226** may be identified relative to workpiece **204** and/or cell **206**. Additionally, position **220**, orientation **222**, and movement **224** may be identified for tool **228**. Position **220**, orientation **222**, and movement **224** for tool **228** may be relative to workpiece **204**, portable machine **226**, and/or cell **206**.

In these illustrative examples, tracking system **210** is configured to identify characteristics **218** about group of portable machines **216** in a number of different ways. As one illustrative example, tracking system **210** may use a motion capture system to identify characteristics **218**.

Further, tracking system **210** may also be used to identify workpiece information **230** about workpiece **204** and/or manufacturing information **232**. Workpiece information **230** about workpiece **204** may include a type of material for workpiece **204**, dimensions of workpiece **204**, a position of workpiece **204** in cell **206**, an orientation of workpiece **204** in cell **206**, information about features on workpiece **204** and/or other suitable types of information.

The features on workpiece **204** may include features already present on workpiece **204** prior to the performance of number of manufacturing operations **202**, features formed by the performance of number of manufacturing operations **202**, and/or other suitable types of features on workpiece **204**. Features may include, for example, without limitation, holes in workpiece **204**, fasteners installed in workpiece **204**, sealant applied to workpiece **204**, a flange on workpiece **204**, and/or other suitable types of features.

In these depicted examples, manufacturing information **232** may include information about the performance of number of manufacturing operations **202** on workpiece **204** by group of portable machines **216**. Manufacturing information **232** may include any information that may be used for performing number of manufacturing operations **202**.

For example, manufacturing information **232** may include information about the features formed on workpiece **204** by group of portable machines **216**, a total number of group of portable machines **216** to be used to perform number of manufacturing operations **202** on workpiece **204** at a point in time, a rate at which holes are formed on

workpiece **204**, a rate at which fasteners are installed in workpiece **204**, and/or other suitable types of information.

In these illustrative examples, controller **212** may be implemented using computer system **233**. Computer system **233** comprises a number of computers. When more than
5 one computer is present in computer system **233**, the computers may be in communication with each other.

As depicted, computer system **233** is present in cell **206** in these examples. However, in other illustrative examples, one or more of the computers in computer system **233** may be located in a location remote to cell **206**. Further, in some illustrative
10 examples, one or more of the computers in computer system **233** may be portable. For example, computer system **233** may be a laptop computer, tablet computer, a personal digital assistance computer, or some other suitable type of portable computer system. In this manner, computer system **233** may be moved to different locations other than cell **206**.

15 Controller **212** may be implemented using hardware, software, or a combination of the two in computer system **233**. When in the form of software, controller **212** may take the form of program code run by a computer within computer system **233**.

In these illustrative examples, controller **212** is in communication with tracking system **210**. For example, controller **212** may be configured to communicate with
20 tracking system **210** using a number of wired communications links, a number of wireless communications links, a number of optical communications links, and/or other suitable types of communications links.

Controller **212** is configured to receive at least one of information **217** about group of portable machines **216**, workpiece information **230**, and manufacturing
25 information **232** from tracking system **210**. These different types of information may be received before, during, and/or after the performance of number of manufacturing operations **202**.

Controller **212** is configured to control the performance of number of manufacturing operations **202** using at least one of information **217**, workpiece
30 information **230**, and manufacturing information **232**. In particular, in these illustrative examples, controller **212** may control the performance of number of manufacturing

operations **202** by group of portable machines **216** on workpiece **204** using characteristics **218** about group of portable machines **216** identified using tracking system **210**.

In these depicted examples, controller **212** may control the performance of number of manufacturing operations **202** using group of portable machines **216** in a number of different ways. For example, controller **212** may send number of commands **234** to group of portable machines **216** to perform a particular manufacturing operation in number of manufacturing operations **202**. Number of commands **234** may be sent to one, some, or all of group of portable machines **216** to control the performance of the particular manufacturing operations by one, some, or all of group of portable machines **216**.

Number of commands **234** may include, for example, without limitation, a command to move a tool a particular distance, a command to begin drilling, a command to apply sealant at a location on workpiece **204**, a command to move a portable machine, and/or other suitable commands. These types of commands may be used when a portable machine has intelligence or a capability to perform different operations with less direction from controller **212**.

In some illustrative examples, controller **212** may control the performance of number of manufacturing operations **202** by group of portable machines **216** by downloading program code **236** to group of portable machines **216**. Program code **236** may be run by group of portable machines **216** to cause group of portable machines **216** to perform one or more of number of manufacturing operations **202**.

Additionally, placement system **214** is configured to move group of portable machines **216** to number of locations **238** on workpiece **204**. For example, placement machine **237** in placement system **214** may place portable machine **226** on workpiece **204**.

Placement system **214** may be controlled by controller **212** and/or human operators depending on the particular implementation. When human operators are used to operate placement system **214**, controller **212** may provide feedback to the human operators as to when a correct placement of group of portable machines **216** occurs with respect to number of locations **238**.

Further, controller **212** may control placement system **214** to control the movement of group of portable machines **216** in manufacturing environment **200**. In this

manner, a possibility of two or more portable machines in group of portable machines **216** colliding with each other may be reduced. Further, controller **212** may control placement system **214** to reduce a possibility of one or more of group of portable machines **216** colliding with other equipment in manufacturing environment **200**, having undesired contact with workpiece **204**, and/or moving to a location in manufacturing environment **200** increasing difficulty in performing number of manufacturing operations **202** by group of portable machines **216**.

Placement system **214** may comprise at least one of a platform, a crane, a robotic arm, a movable rack, or some other suitable type of apparatus that is configured to move a portable machine to a desired location to perform at least one manufacturing operation in number of manufacturing operations **202**. Of course, depending on the implementation, placement system **214** may comprise any structure and/or device configured to move one, some, or all of group of portable machines **216**, a portion of portable machine **226**, and/or tool **228** connected to portable machine **226**.

Further, in these illustrative examples, operator station **240** may be present in cell **206**. Operator station **240** may be part of controller **212**, part of manufacturing system **208**, and/or a separate system from manufacturing system **208** in cell **206**.

In these depicted examples, operator station **240** allows human operators to view information **217** about group of portable machines **216**, workpiece information **230**, and/or manufacturing information **232** identified by tracking system **210**. For example, tracking system **210** and/or controller **212** may be configured to send these different types of information to operator station **240**.

As depicted in these examples, this information and/or other suitable types of information may be displayed on graphical user interface **242** on display system **243** at operator station **240**. Display system **243** may comprise any number of display devices. For example, display system **243** may include at least one of a touchscreen, a monitor, a liquid crystal display (LCD), a head-mounted display device, and other suitable types of display devices.

In some illustrative examples, controller **212** may generate visual cues, audible cues, and/or other indications using display system **243** that may be used by an operator to control the movement of group of portable machines **216** using placement system **214**.

In this manner, an operator may avoid moving a portable machine, such as a hand tool, too close to workpiece **204**.

Further, human operators are able to interact with graphical user interface **242** using number of input devices **244**. Number of input devices **244** may include, for example, without limitation, at least one of a keyboard, a virtual keyboard, a mouse, a pen, a joystick, a motion sensing input device, a motion tracking system, a camera, a video camera, and other suitable types of input devices.

Operator station **240** may allow human operators to interact with controller **212**, placement system **214**, group of portable machines **216**, and/or tracking system **210**. As one illustrative example, a human operator may use number of input devices **244** to control the movement of portable machine **226** relative to workpiece **204**.

In some illustrative examples, a human operator may use operator station **240** to modify number of manufacturing operations **202** to be performed on workpiece **204**. In other illustrative examples, a human operator may use operator station **240** to manage which portable machines in group of portable machines **216** perform number of manufacturing operations **202** on workpiece **204** and how number of manufacturing operations **202** are performed. In one illustrative example, a human operator may use operator station **240** to manage the types of information being identified by tracking system **210**.

In other illustrative examples, controller **212** and/or tracking system **210** may be used to manage the locations of human operators within manufacturing environment **200**. For example, tracking system **210** may be used to keep track of the locations of human operators performing number of manufacturing operations **202** on workpiece **204** using group of portable machines **216**.

With reference now to **Figure 3**, an illustration of a tracking system in the form of a block diagram is depicted in accordance with an advantageous embodiment. In this illustrative example, tracking system **210** from **Figure 2** is depicted in more detail.

Tracking system **210** includes sensor system **300**. Sensor system **300** comprises number of sensors **302**. Number of sensors **302** may include sensors of different forms. For example, number of sensors **302** may include number of cameras **304**.

Number of cameras **304** generates images **306**, which may be used to identify characteristics **218** about group of portable machines **216** in **Figure 2**. Tracking system

210 may identify characteristics **218** using images **306** or may send images **306** to controller **212** in **Figure 2**. Controller **212** may use images **306** to identify characteristics **218** about group of portable machines **216**.

In some illustrative examples, number of sensors **302** may include number of global positioning system receivers **308**. A global positioning system receiver in number of global positioning system receivers **308** may be associated with portable machine **226**, tool **228**, or both portable machine **226** and tool **228** in **Figure 2**. Tracking system **210** is configured to identify position information for portable machine **226** and/or tool **228** using the global positioning system receiver. Further, number of global positioning system receivers **308** may be used to track multiple portable machines in group of portable machines **216** in **Figure 2** simultaneously.

A first component, such as a global positioning system receiver, may be considered to be associated with a second component, such as tool **228**, by being secured to the second component, bonded to the second component, welded to the second component, fastened to the second component, and/or connected to the second component in some other suitable manner. The first component also may be connected to the second component using a third component. The first component may also be considered to be associated with the second component by being formed as part of and/or an extension of the second component.

In one illustrative example, tracking system **210** may include number of radio frequency identification tags **310** and number of radio frequency identification readers **312**. A radio frequency identification tag in number of radio frequency identification tags **310** may be associated with, for example, portable machine **226**, tool **228**, or both. Number of radio frequency identification readers **312** is configured to read signals transmitted from the radio frequency identification tags. Further, based on signal strengths and/or direction, number of radio frequency identification readers **312** identifies characteristics **218** for portable machine **226**, tool **228**, or both.

As another illustrative example, tracking system **210** may include laser tracking system **314**. Laser tracking system **314** may be used to identify characteristics **218** for group of portable machines **216**. In particular, laser tracking system **314** may be configured for tracking individual portable machines in group of portable machines **216** and/or the individual tools connected to these portable machines.

In these illustrative examples, number of radio frequency identification readers **312** and/or laser tracking system **314** may be part of sensor system **300** for tracking system **210**. Further, one or more of these systems in tracking system **210** may be used alone or in combination with other systems to identify characteristics **218**. For example, both laser tracking system **314** and number of cameras **304** may be used to identify characteristics **218**.

With reference now to **Figure 4**, an illustration of a group of portable machines in the form of a block diagram is depicted in accordance with an advantageous embodiment. In this illustrative example, group of portable machines **216** from **Figure 2** is depicted in more detail. When more than one portable machine is present in group of portable machines **216**, group of portable machines **216** may take the form of homogeneous portable machines **400** and/or heterogeneous portable machines **402**.

In these illustrative examples, a portable machine in group of portable machines **216** comprises at least one of computer controlled portable machine **404**, operator controlled portable machine **406**, and some other suitable type of portable machine that may be controlled by controller **212** in **Figure 2**.

As depicted, computer controlled portable machine **404** may include housing **408**, controller **410**, number of tools **412**, movement system **414**, communications unit **416**, and sensor system **418**. Controller **410**, number of tools **412**, movement system **414**, communications unit **416**, and sensor system **418** may be associated with housing **408** for computer controlled portable machine **404**.

Controller **410** may be a computer system, a processor unit, or some other suitable piece of hardware. Controller **410** may provide different levels of intelligence for computer controlled portable machine **404**. In some cases, controller **410** merely receives commands to move computer controlled portable machine **404** particular distances and/or directions and to drill to a particular depth.

In other illustrative examples, controller **410** runs program code **236** received from controller **212** to perform number of manufacturing operations **202** in **Figure 2**. Program code **236** may be, for example, instructions that provide distances to move on workpiece **204** and locations on workpiece **204** at which drilling operations should be performed.

In other illustrative examples, program code **236** may provide more intelligence. For example, program code **236** may include a neural network, an artificial intelligence program, or some other suitable type of program code. With this type of program code, identification of holes and locations to be drilled may be provided to computer controlled portable machine **404**. Computer controlled portable machine **404** then perform number of manufacturing operations **202**. Computer controlled portable machine **404** may perform one or more of number of manufacturing operations **202** from **Figure 2** based on an identification of where number of manufacturing operations **202** are to be performed and the type of operations to be performed.

In these illustrative examples, number of tools **412** includes tools that may be used to perform manufacturing operations. For example, number of tools **412** may include at least one of a drill, a screwdriver, a sealant applicator, a cutter, a hole inspection tool, a torque tool, and other suitable types of tools.

Movement system **414** moves computer controlled portable machine **404** relative to workpiece **204** in **Figure 2**. Movement system **414** may include, for example, without limitation, at least one of wheels, legs, tracks, rollers, and other suitable types of locomotion devices. The tracks may be, for example, tracks that fit around wheels, such as on a tank. In other cases, the tracks may be laid out on workpiece **204** and wheels, and/or some other suitable mechanism in movement system **414**, may move housing **408** along the tracks to move computer controlled portable machine **404**.

In these illustrative examples, communications unit **416** is configured to provide communication between controller **410** for computer controlled portable machine **404** and controller **212** in manufacturing system **208** in **Figure 2**. Communications unit **416** may provide wired, wireless, optical, and/or some other suitable type of communication.

Sensor system **418** provides feedback as to whether number of manufacturing operations **202** are being performed in a manner that is desired. Sensor system **418** may not be present in computer controlled portable machine **404** in some cases and may be unnecessary with the use of tracking system **210**.

In these illustrative examples, operator controlled portable machine **406** may comprise housing **422**, tool **424**, and controller **426**. A human operator may move or position operator controlled portable machine **406** with respect to workpiece **204** in **Figure 2**. Controller **212** from **Figure 2** may send a signal to controller **426** to allow

operation of tool **424**. This signal is sent when controller **212** determines that operator controlled portable machine **406** is ready to perform a manufacturing operation.

For example, tool **424** may need to be in a particular position and orientation with respect to workpiece **204** for the manufacturing operation to be performed. When the particular position and orientation for tool **424** is present, controller **426** sends the signal to allow operation of tool **424**. Controller **426** may be as simple as a switch that is remotely controlled by controller **212** to supply power to tool **424** or may take the form of a processor unit depending on the particular implementation.

With reference now to **Figure 5**, an illustration of a placement system in the form of a block diagram is depicted in accordance with an advantageous embodiment. In this illustrative example, placement system **214** from **Figure 2** is depicted in more detail. As depicted, placement system **214** comprises number of placement machines **500**. Placement machine **501** is an example of one of number of placement machines **500**.

In these illustrative examples, placement machine **501** includes number of movement devices **502**. Number of movement devices **502** may include at least one of robotic arm **503**, track system **504**, movable rack **506**, cart **508**, platform **510**, crane **512**, and other suitable types of devices configured to move a portable machine in group of portable machines **216** in **Figure 2**. Further, number of movement devices **502** may include devices configured to move placement machine **501**.

A movement device in number of movement devices **502** may be computer controlled and/or operated by a human operator. As one illustrative example, portable machine **226** from **Figure 2** may be placed in cart **508**. Cart **508** may be a movable cart. Cart **508** may be moved by a human operator and/or may be moved in response to commands from, for example, controller **212** in **Figure 2**.

In these illustrative examples, track system **504** may include number of tracks **514**. Number of tracks **514** may be tracks that may be movable. For example, a track in number of tracks **514** may be placed on workpiece **204** from **Figure 2**. Portable machine **226** in **Figure 2** may be placed on the track and may have wheels that allow portable machine **226** to move along the track to perform number of manufacturing operations **202**. When portable machine **226** needs to be moved to a different location on workpiece **204**, the track and portable machine **226** may be moved to a different location.

In some illustrative examples, some or all of number of movement devices **502** may be associated with a portable machine in group of portable machines **216**. For example, number of movement devices **502** may include wheels that are associated with portable machine **226**.

5 The illustration of manufacturing environment **200** in **Figure 2** and the different systems within manufacturing system **208** depicted in **Figures 2-5** are not meant to imply physical or architectural limitations to the manner in which an advantageous embodiment may be implemented. Other components in addition to and/or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are
10 presented to illustrate some functional components. One or more of these blocks may be combined and/or divided into different blocks when implemented in an advantageous embodiment.

For example, in some illustrative examples, a number of tools in addition to, or in place of, tool may be connected to portable machine **226**. Tracking system **210** may be
15 configured to identify characteristics **218** for each of these tools.

Further, in other illustrative examples, operator station **240** may not be present in cell **206**. For example, a human operator may use a portable head-mounted device to interact with controller **212**. In some illustrative examples, a human operator interacts with controller **212** using a computer system in a location remote to cell **206**. In this
20 manner, the human operator may be involved in managing the performance of number of manufacturing operations **202** performed in cell **206** without being present in cell **206**.

In other illustrative examples, additional components may be present in tracking system **210** other than the components described in **Figure 3**. For example, tracking system **210** may include an infrared imaging system, an x-ray imaging system, and/or
25 some other suitable type of component.

With reference now to **Figure 6**, an illustration of a manufacturing environment is depicted in accordance with an advantageous embodiment. In this illustrative example, manufacturing environment **600** is an example of one implementation for manufacturing environment **200** in **Figure 2**.

30 As depicted, workpiece **602** and manufacturing system **604** are present in cell **605** in manufacturing environment **600**. Workpiece **602** is part of a fuselage of an aircraft in

this illustrative example. Manufacturing system **604** is configured to perform manufacturing operations on workpiece **602**.

In this illustrative example, manufacturing system **604** includes controller **606**, placement system **608**, tracking system **610**, and group of portable machines **612**. Group of portable machines **612** includes portable machines **613**, **615**, **617**, and **619**.

Controller **606** is configured to control the performance of manufacturing operations on workpiece **602** by group of portable machines **612**. As depicted, controller **606** is implemented using computer system **614**. Computer system **614** includes display system **616**. Display system **616** is an example of one implementation for display system **243** in **Figure 2**. Human operator **618** may use information displayed on display system **616** to move one or more of group of portable machines **612** and/or manage the performance of manufacturing operations on workpiece **602**.

In this illustrative example, placement system **608** includes structure **620** having arm **622** and track system **624**. Arm **622** of structure **620** is connected to portable machine **617** in this depicted example. Human operator **618** may move arm **622** of structure **620** to move portable machine **617** relative to workpiece **602**.

In this depicted example, portable machine **617** may be a hand tool that may be allowed to operate once the tool is in a correct position relative to workpiece **602**. For example, controller **606** may be configured to control the operation of portable machine **617** by sending a command to move a switch to turn on the power for portable machine **617** once portable machine **617** is in the correct position.

Track system **624** includes tracks **626**, **628**, **630**, and **632** attached to workpiece **602**. Portable machine **615** moves along track **626** in this illustrative example. Portable machine **613** moves along track **628**, and portable machine **619** moves along track **630**. Further, portable machine **617** may be disconnected from arm **622** of structure **620** and placed on track **632** and attached to workpiece **602**.

In this depicted example, tracking system **610** comprises cameras **634**, **636**, **638**, **640**, **642**, **644**, **646**, **648**, **650**, **652**, **654**, **656**, and **658**. These cameras generate images used to identify information about group of portable machines **612**, such as position, orientation, and movement.

With reference now to **Figure 7**, an illustration of another manufacturing environment is depicted in accordance with an advantageous embodiment. In this

illustrative example, manufacturing environment **700** is an example of one implementation for manufacturing environment **200** in **Figure 2**.

As depicted, manufacturing operations are being performed on aircraft **702** by manufacturing system **704** in manufacturing environment **700**. Manufacturing system **704** includes controller **706**, tracking system **708**, group of portable machines **710**, and placement system **712**.

Tracking system **708** comprises cameras **714**, **716**, **718**, **720**, **722**, **724**, **726**, **728**, **730**, **732**, **734**, and **736**. Placement system **712** includes vehicles **740**, **742**, **744**, **746**, and **748** that may be used to move portable machines **750**, **752**, **754**, **756**, **758**, **760**, **762**, **764**, **766**, **768**, **770**, and **772** in group of portable machines **710** towards aircraft **702** and place them on aircraft **702**. Further, placement system **712** may also include movement devices (not shown) associated with group of portable machines **710** that allow group of portable machines **710** to move along the various surfaces of aircraft **702**.

With reference now to **Figure 8**, an illustration of a display on a graphical user interface is depicted in accordance with an advantageous embodiment. In this illustrative example, graphical user interface **800** is an example of one implementation for graphical user interface **244** in **Figure 2**. As depicted, display **802** is displayed on graphical user interface **800**. A human operator may use display **802** to monitor the progress of manufacturing operations being performed on a workpiece.

Display **802** includes part number **804**, work order **806**, kit number **808**, tool jig **810**, operation **812**, video **814**, and log **816**. Part number **804** identifies the particular workpiece on which manufacturing operations are being performed. Work order **806** identifies the particular work order for which the manufacturing operations are being performed. Kit number **808** identifies a group of unique components to be installed in a specific location on the workpiece. Tool jig **810** identifies the tool used to perform the manufacturing operations.

In this illustrative example, operation **812** identifies the particular manufacturing operation being performed and information about the operation. In this illustrative example, a drilling operation is being performed.

Video **814** is a video of the drilling operation generated as the drilling operation is being performed. This video may be generated using, for example, number of cameras

306 in tracking system 210 in **Figure 3**. Additionally, log 816 identifies dates and times for operations and/or tasks performed.

With reference now to **Figure 9**, an illustration of a flowchart of a process for managing manufacturing operations is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 9** may be implemented using manufacturing system 208 in **Figure 2** to manage number of manufacturing operations 202 performed on workpiece 204 in **Figure 2**.

The process begins by identifying characteristics about a group of portable machines using a tracking system (operation 900). In operation 900, the characteristics may be identified using, for example, images and/or video generated by, for example, a motion capture system.

The process controls performance of a number of manufacturing operations on the workpiece by the group of portable machines using the characteristics about the group of portable machines (operation 902), with the process terminating thereafter. Operation 902 may be performed using a controller, such as controller 212 in **Figure 2**.

In operation, performance of the number of manufacturing operations on the workpiece may be performed by sending commands, signals, and/or program code to the group of portable machines. For example, the controller sends a command to a portable machine in the group of portable machines to move a certain distance in a certain direction on the workpiece. As another illustrative example, the controller sends a signal to the portable machine turning on a power switch to a tool connected to the portable machine.

With reference now to **Figure 10**, an illustration of a flowchart of a process for managing manufacturing operations is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 10** may be implemented using manufacturing system 208 in **Figure 2** to manage number of manufacturing operations 202 performed on workpiece 204 in manufacturing environment 200 in **Figure 2**.

The process begins by moving a workpiece on which manufacturing operations are to be performed into a cell (operation 1000). The cell is an area in which the manufacturing operations are to be performed. The cell may be, for example, a hangar, an area in a manufacturing facility, a building, a room in a factory, or some other suitable type of area.

The process moves a group of portable machines configured to perform the manufacturing operations onto the workpiece (operation **1002**). Next, the process identifies characteristics about the group of portable machines using a tracking system (operation **1004**).

5 In operation **1004**, the tracking system may take the form of, for example, a motion capture system. The motion capture system may be used to identify a position, an orientation, and movement of each of the group of portable machines and/or any tools connected to each portable machine. In this illustrative example, operation **1004** may be performed before and/or after the manufacturing operations are performed as well as
10 while the manufacturing operations are being performed.

 The process determines whether any of the portable machines in the group of portable machines needs to be moved on the workpiece to perform the manufacturing operations (operation **1006**). Movement of a portable machine may include moving one or more tools connected to the portable machine without moving the portable machine
15 itself.

 If any of the portable machines in the group of portable machines needs to be moved, the process moves these portable machines on the workpiece based on the characteristics about the group of portable machines (operation **1008**). The process performs the manufacturing operations using the group of portable machines (operation
20 **1010**).

 The process determines whether the manufacturing operations to be performed have been completed (operation **1012**). If the manufacturing operations have been completed, the process terminates. Otherwise, the process returns to operation **1006** as described above.

25 In this illustrative example, operation **1012** may be performed while operation **1010** is being performed. In this manner, a portable machine and/or tool connected to the portable machine may be moved on workpiece as the manufacturing operations are being performed. For example, while a first portion of the group of portable machines are drilling holes along a length of the workpiece, a second portion of the group of portable
30 machines may be installing fasteners into each of the holes as the second group is moved on the workpiece.

With reference again to operation **1006**, if none of the group of portable machines needs to be moved, the process proceeds to operation **1010** as described above.

With reference now to **Figure 11**, an illustration of a flowchart of a process for inspecting holes that have been drilled into a workpiece is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 11** may be implemented using manufacturing system **208** in **Figure 2**.

The process begins by establishing a data connection between a probe and a controller (operation **1100**). In this illustrative example, the probe is configured to generate data for a measurement of a diameter for a hole. The probe may be connected to a portable machine. The controller in operation **1100** may be implemented using controller **212** in **Figure 2**.

The process calibrates the probe (operation **1102**). In some illustrative examples, operation **1102** may be performed prior to operation **1100**. The process then moves the portable machine on the workpiece such that the probe is positioned over a hole on the workpiece (operation **1104**).

Thereafter, the process determines whether the probe is the correct tool for measuring the diameter of the hole in the workpiece (operation **1105**). If the probe is not the correct tool for measuring the diameter of the hole, the process terminates. In other words, the measurement is not performed.

Otherwise, if the probe is the correct tool, the probe generates data for a measurement of the diameter of the hole (operation **1106**). The process determines whether all of the holes in the workpiece have been inspected (operation **1107**). If all of the holes in the workpiece have been inspected, the process terminates. Otherwise, the process then moves the portable machine and/or the probe relative to the workpiece (operation **1108**). In operation **1108**, the portable machine and/or the probe may be moved towards another hole to be inspected.

The process identifies information about the position, orientation, and movement of the probe and the portable machine using a motion capture system as the portable machine and the probe are moved relative to the workpiece (operation **1110**). In this illustrative example, operation **1110** may be performed while operation **1108** is being performed. Further, operation **1110** may be performed continuously, as all of the holes in the workpiece are inspected, or periodically.

The controller controls the movement of the portable machine with the probe relative to the workpiece using the information about the position, orientation, and movement of the portable machine and the probe (operation **1112**). Thereafter, the process returns to operation **1107** as described above.

5 In operation **1112**, the control sends commands to the portable machine to direct movement of the portable machine and/or the probe relative to the workpiece. In particular, the controller may use the information identified about the position, orientation, and movement of the probe to find the nearest hole that is to be inspected next. The controller may then send commands to the portable machine to move the
10 portable machine and/or probe a certain distance and/or in a certain direction relative to the workpiece.

 In this illustrative example, operation **1112** may be performed while operation **1108** is being performed. In this manner, the movement of the portable machine with the probe relative to the workpiece as the holes are inspected may be controlled to reduce the
15 time and/or effort needed for inspecting all of the holes.

 The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of the methods and apparatus in an advantageous embodiment. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, function, and/or a
20 portion of an operation or step. For example, one or more of the blocks may be implemented as program code, in hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware may, for example, take the form of integrated circuits that are manufactured or configured to perform one or more operations in the flowcharts or block diagrams.

25 In some alternative implementations of an advantageous embodiment, the function or functions noted in the block may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the
30 illustrated blocks in a flowchart or block diagram.

 Turning now to **Figure 12**, an illustration of a data processing system is depicted in accordance with an advantageous embodiment. In this illustrative example, data

processing system **1200** may be used to implement a computer in computer system **233** in **Figure 2**, controller **410** in **Figure 4**, and/or controller **426** in **Figure 4**. Data processing system **1200** includes communications fabric **1202**, which provides communications between processor unit **1204**, memory **1206**, persistent storage **1208**, communications unit **1210**, input/output (I/O) unit **1212**, and display **1214**.

Processor unit **1204** serves to execute instructions for software that may be loaded into memory **1206**. Processor unit **1204** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. Further, processor unit **1204** may be implemented using a number of heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **1204** may be a symmetric multi-processor system containing multiple processors of the same type.

Memory **1206** and persistent storage **1208** are examples of storage devices **1216**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Storage devices **1216** may also be referred to as computer readable storage devices in these examples. Memory **1206**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **1208** may take various forms, depending on the particular implementation.

For example, persistent storage **1208** may contain one or more components or devices. For example, persistent storage **1208** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **1208** also may be removable. For example, a removable hard drive may be used for persistent storage **1208**.

Communications unit **1210**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **1210** is a network interface card. Communications unit **1210** may provide communications through the use of either or both physical and wireless communications links.

Input/output unit **1212** allows for input and output of data with other devices that may be connected to data processing system **1200**. For example, input/output unit **1212** may provide a connection for user input through a keyboard, a mouse, and/or some other

suitable input device. Further, input/output unit **1212** may send output to a printer. Display **1214** provides a mechanism to display information to a user.

Instructions for the operating system, applications, and/or programs may be located in storage devices **1216**, which are in communication with processor unit **1204** through communications fabric **1202**. In these illustrative examples, the instructions are in a functional form on persistent storage **1208**. These instructions may be loaded into memory **1206** for execution by processor unit **1204**. The processes of the different embodiments may be performed by processor unit **1204** using computer implemented instructions, which may be located in a memory, such as memory **1206**.

These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **1204**. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory **1206** or persistent storage **1208**.

Program code **1218** is located in a functional form on computer readable media **1220** that is selectively removable and may be loaded onto or transferred to data processing system **1200** for execution by processor unit **1204**. Program code **1218** and computer readable media **1220** form computer program product **1222** in these examples. In one example, computer readable media **1220** may be computer readable storage media **1224** or computer readable signal media **1226**. Computer readable storage media **1224** may include, for example, an optical or magnetic disk that is inserted or placed into a drive or other device that is part of persistent storage **1208** for transfer onto a storage device, such as a hard drive, that is part of persistent storage **1208**.

Computer readable storage media **1224** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory, that is connected to data processing system **1200**. In some instances, computer readable storage media **1224** may not be removable from data processing system **1200**. In these examples, computer readable storage media **1224** is a physical or tangible storage device used to store program code **1218** rather than a medium that propagates or transmits program code **1218**. Computer readable storage media **1224** is also referred to as a computer readable tangible storage device or a computer readable physical storage device. In other words, computer readable storage media **1224** is a media that can be touched by a person.

Alternatively, program code **1218** may be transferred to data processing system **1200** using computer readable signal media **1226**. Computer readable signal media **1226** may be, for example, a propagated data signal containing program code **1218**. For example, computer readable signal media **1226** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link. In other words, the communications link and/or the connection may be physical or wireless in the illustrative examples.

In some advantageous embodiments, program code **1218** may be downloaded over a network to persistent storage **1208** from another device or data processing system through computer readable signal media **1226** for use within data processing system **1200**. For instance, program code stored in a computer readable storage medium in a server data processing system may be downloaded over a network from the server to data processing system **1200**. The data processing system providing program code **1218** may be a server computer, a client computer, or some other device capable of storing and transmitting program code **1218**.

The different components illustrated for data processing system **1200** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different advantageous embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **1200**. Other components shown in **Figure 12** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code.

In another illustrative example, processor unit **1204** may take the form of a hardware unit that has circuits that are manufactured or configured for a particular use. This type of hardware may perform operations without needing program code to be loaded into a memory from a storage device to be configured to perform the operations.

For example, when processor unit **1204** takes the form of a hardware unit, processor unit **1204** may be a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is

configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. With this type of implementation, program code **1218** may be omitted because the processes for the different embodiments are implemented in a hardware unit.

In still another illustrative example, processor unit **1204** may be implemented using a combination of processors found in computers and hardware units. Processor unit **404** may have a number of hardware units and a number of processors that are configured to run program code **1218**. With this depicted example, some of the processes may be implemented in the number of hardware units, while other processes may be implemented in the number of processors.

In another example, a bus system may be used to implement communications fabric **1202** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

Embodiments of the disclosure may be used in the context of aircraft manufacturing and service method **1300** as shown in **Figure 13** and aircraft **1400** as shown in **Figure 14**. Turning first to **Figure 13**, an illustration of an aircraft manufacturing and service method is depicted in accordance with an advantageous embodiment. During pre-production, aircraft manufacturing and service method **1300** may include specification and design **1302** of aircraft **1400** in **Figure 14** and material procurement **1304**.

During production, component and subassembly manufacturing **1306** and system integration **1308** of aircraft **1400** in **Figure 14** takes place. Thereafter, aircraft **1400** in **Figure 14** may go through certification and delivery **1310** in order to be placed in service **1312**. While in service **1312** by a customer, aircraft **1400** in **Figure 14** is scheduled for routine maintenance and service **1314**, which may include modification, reconfiguration, refurbishment, and other maintenance or service.

Each of the processes of aircraft manufacturing and service method **1300** may be performed or carried out by a system integrator, a third party, and/or an operator. In these examples, the operator may be a customer. For the purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, a leasing company, a military entity, a service organization, and so on.

With reference now to **Figure 14**, an illustration of an aircraft is depicted in which an advantageous embodiment may be implemented. In this example, aircraft **1400** is produced by aircraft manufacturing and service method **1300** in **Figure 13** and may include airframe **1402** with plurality of systems **1404** and interior **1406**. Examples of systems **1404** include one or more of propulsion system **1408**, electrical system **1410**, hydraulic system **1412**, and environmental system **1414**. Any number of other systems may be included. Although an aerospace example is shown, different advantageous embodiments may be applied to other industries, such as the automotive industry.

Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manufacturing and service method **1300** in **Figure 13**. In one illustrative example, components or subassemblies produced in component and subassembly manufacturing **1306** in **Figure 13** may be fabricated or manufactured in a manner similar to components or subassemblies produced while aircraft **1400** is in service **1312** in **Figure 13**. As yet another example, a number of apparatus embodiments, method embodiments, or a combination thereof may be utilized during production stages, such as component and subassembly manufacturing **1306** and system integration **1308** in **Figure 13**.

A number of apparatus embodiments, method embodiments, or a combination thereof may be utilized while aircraft **1400** is in service **1312** and/or during maintenance and service **1314** in **Figure 13**. The use of a number of the different advantageous embodiments may substantially expedite the assembly of and/or cost of aircraft **1400**. As one illustrative example, manufacturing system **208** in **Figure 2** may be used during maintenance and service **1314** to manufacture parts that may be needed to perform replacement of parts in aircraft **1400**, perform upgrades of aircraft **1400**, reconfiguration of aircraft **1400**, and other operations.

Thus, the different advantageous embodiments provide a method and apparatus for managing manufacturing operations. In one advantageous embodiment, an apparatus comprises a tracking system and a controller in communication with the tracking system. The tracking system is configured to identify characteristics about a group of portable machines configured to perform a number of manufacturing operations on a workpiece. The controller is configured to control performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machine identified using the tracking system.

In this manner, one or more of the different advantageous embodiments provide a system for managing manufacturing operations that reduces the time and/or effort needed for moving portable machines relative to a workpiece to perform the manufacturing operations. In particular, the different advantageous embodiments provide a system for directing movement of portable machines relative to a workpiece more accurately and efficiently as compared to human operators moving these machines without assistance from a manufacturing system, such as manufacturing system 208.

The description of the present disclosure has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the disclosure in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different advantageous embodiments may provide different advantages as compared to other advantageous embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the disclosure, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**

1. An apparatus comprising:

5

a tracking system configured to identify characteristics about a group of portable machines configured to perform a number of manufacturing operations on a workpiece; and

10

a controller in communication with the tracking system, wherein the controller is configured to control performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system.

15

2. The apparatus of claim 1 further comprising:

the group of portable machines.

20

3. The apparatus of claim 1, wherein the tracking system is further configured to identify information about the workpiece.

4. The apparatus of claim 1, wherein the tracking system comprises a number of cameras.

25

5. The apparatus of claim 1, wherein the tracking system comprises:

a number of radio frequency identification tags associated with the group of portable machines; and

30

a number of radio frequency identification readers configured to identify position information about the group of portable machines using the number of radio frequency identification tags.

6. The apparatus of claim 1, wherein the controller is configured to receive information about the workpiece and information about the group of portable machines from the tracking system in which the information about the group of portable machines comprises the characteristics about the group of portable machines and wherein in being configured to control the performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines are identified using the tracking system, the controller is configured to control the performance of the number of manufacturing operations on the workpiece using the information about the workpiece, the information about the group of portable machines, and the characteristics about the group of portable machines identified using the tracking system.
7. The apparatus of claim 1, wherein in being configured to control the performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system, the controller is configured to send at least one of a command and a program to the group of portable machines to control the performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system.
8. The apparatus of claim 1, wherein when a portable machine in the group of portable machines is a tool positioned by a human operator and wherein in being configured to control the performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system, the controller is configured to send a signal to allow the portable machine to be operated by the human operator when the characteristics about the tool in the group of portable machines identified using the tracking system indicates that the tool is in a position relative to the workpiece to perform a desired manufacturing operation on the workpiece.

9. The apparatus of claim 1, wherein a portable machine in the group of portable machines is selected from one of a computer controlled portable machine and an operator controlled portable machine.

5

10. The apparatus of claim 1, wherein the characteristics about the group of portable machines comprise at least one of a position of a portable machine, an orientation of the portable machine, and movement of the portable machine.

10

11. The apparatus of claim 1, wherein a manufacturing operation in the number of manufacturing operations is selected from one of a drilling operation, a sealing operation, a fastener installation operation, an inspection operation, and a painting operation.

15

12. The apparatus of claim 1, wherein the workpiece is selected from one of an aircraft, an aircraft part, a wing, a stabilizer, a portion of a fuselage, an engine, an engine housing, and a landing gear assembly.

13. An aircraft manufacturing system comprising:

20

a group of portable machines configured to perform a number of manufacturing operations on a workpiece for an aircraft;

25

a tracking system configured to identify characteristics about the group of portable machines; and

30

a controller in communication with the tracking system, wherein the controller is configured to control performance of the number of manufacturing operations on the workpiece using at least one of the characteristics about the group of portable machines identified using the tracking system, information about the workpiece, and information about the group of portable machines.

14. A method for managing manufacturing operations, the method comprising:

identifying characteristics about a group of portable machines using a
tracking system and a controller; and

controlling performance of a number of manufacturing operations on a
workpiece by the group of portable machines using the characteristics
about the group of portable machines identified using the tracking
system.

15. The method of claim 14 further comprising:

identifying information about the workpiece using the tracking system and
the controller.

16. The method of claim 14 further comprising:

receiving information about the workpiece and information about the
group of portable machines; and

wherein the controlling step comprises:

controlling the performance of the number of manufacturing
operations on the workpiece using the information about the
workpiece, the information about the group of portable machines,
and the characteristics about the group of portable machines
identified using the tracking system.

17. The method of claim 14, wherein the controlling step comprises:

sending at least one of a command and a program to the group of portable machines to control the performance of the number of manufacturing operations on the workpiece using the characteristics about the group of portable machines identified using the tracking system.

5

- 18.** The method of claim **14**, wherein a portable machine in the group of portable machines is a tool positioned by a human operator and wherein the controlling step comprises:

10

sending a signal to allow the portable machine to be operated by the human operator when the characteristics about the group of portable machines identified using the tracking system indicates that the portable machine is in a position relative to the workpiece to perform a desired manufacturing operation on the workpiece.

15

- 19.** The method of claim **14**, wherein the identifying step comprises:

identifying the characteristics about the group of portable machines using a number of cameras in the tracking system.

20

- 20.** The method of claim **14**, wherein the characteristics about the group of portable machines comprise position information and further comprising:

25

identifying the position information about the group of portable machines using a number of radio frequency identification readers and a number of radio frequency identification tags in the tracking system, wherein the number of radio frequency identification tags is associated with the group of portable machines.

30

Application number / numéro de demande: 2775480

Figures: 8

Pages: _____

Unscannable items
received with this application
(Request original documents in File Prep. Section on the 10th floor)

Documents reçu avec cette demande ne pouvant être balayés
(Commander les documents originaux dans la section de préparation des dossiers au
10^{eme} étage)





FIG. 1

200 FIG. 2 2/11






FIG. 3

3/11




FIG. 4

4/11

FIG. 5





FIG. 9






FIG. 6

6/11




FIG. 7





FIG. 10

9/11


START

FIG. 11



10/11

FIG. 12



11/11

