

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 October 2006 (12.10.2006)

PCT

(10) International Publication Number
WO 2006/105680 A1

(51) International Patent Classification:
A01K 1/015 (2006.01)

(74) Agent: MCSTEA, John, Anthony; Ueberlandstrasse 138,
CH-8600 Duebendorf (CH).

(21) International Application Number:
PCT/CH2006/000187

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 3 April 2006 (03.04.2006)

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/668,176 4 April 2005 (04.04.2005) US

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(71) Applicant (for all designated States except US): **GIVAUDAN SA** [CH/CH]; Chemin De La Parfumerie 5, CH-1214 Vernier (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **QUELLET, Christian** [CH/CH]; Rue Neuve 20, CH-2502 Biel (CH). **BOUWMEESTERS, Johnny** [NL/CH]; Zelgliackerstrasse 5, CH-8618 Oetwil Am See (CH). **DELORENZI, Sibilla** [CH/CH]; Röschenbachstrasse 54, CH-8037 Zürich (CH). **MCGEE, Thomas** [GB/US]; 34 Village Gate Way, Nyack, New York 10960 (US).

(54) Title: FRAGRANCE COMPOSITION

(57) Abstract: A solid, free-flowing composition adapted to deliver fragrance or malodor counteractant in a consumer product that is subjected to actual or potential malodorous influences, comprising: a delivery system consisting of a core material surrounded by a fragranced material comprising microdroplets of a dispersed fragrance in a fragrance-encapsulating material, optionally surrounded by a protective coating, and, an external absorbent material in which the fragrance delivery vehicle is dispersed. The invention is especially effective with respect to animal litters, especially those for cats.

WO 2006/105680 A1

FRAGRANCE COMPOSITION

This invention relates to an odour control composition that is capable of absorbing malodor and moisture and simultaneously releasing a fragrance in a controlled way, more particularly to such compositions for use in consumer products, especially solid consumer products for odour control such as sanitary products, diapers, pet litters, air fresheners, central air systems, humidity absorbers and the like.

Absorbent materials have traditionally been used to absorb malodors and moisture. In some cases, odor-counteracting compounds such as a chemically reactive substance, a masking scent or a pleasant fragrance is added directly to the absorbent. Adding malodor-counteracting compounds directly to absorbents has, however, severe drawbacks. Firstly, irreversible adsorption of part of the malodor-counteracting compound often alters the efficacy of the compound. Secondly, due to specific odorant-absorbent interactions, some components of the added fragrance may be more absorbed or retained than others within the pores of the absorbent, leading to distortion of the olfactive characteristics of the fragrance. Thirdly, adding odorants directly to absorbents usually leads to over-dosed olfactive impact of freshly prepared composition and under-dosed olfactive impact of aged composition. The release of the smell is, in the case in which the fragrance has been added directly to absorbent, essentially uncontrolled.

Furthermore, fragrances have been traditionally added to consumer products by mixing a liquid fragrance into the product. There are a number of problems with this approach, such as the possibility of unacceptably high fragrance loss during manufacture, uneven distribution of fragrance in the product, clogging of manufacturing machinery and poorer mechanical properties of the final product.

US 6,803,833 discloses a process for releasing fragrance in the presence of absorbent materials by providing a delivery vehicle containing an enrobing material, a fragrance and a fixative, wherein the enrobing material is a powder material that is capable of absorbing oleophilic substances, and the fixative is a high molecular weight, low melting wax or solid, such as polyethylene glycol.

Although the process described in US 6,803,833 certainly provides improved odor control compared to the prior art, it has the disadvantage of relying on a range of fixatives and

enrobing materials that are not known to be highly efficient in retaining volatile fragrance ingredients over a prolonged period of time, especially at room temperature and above. Thus, it is expected that such fragrance delivery vehicles will lose their odor-control efficacy with time.

- 5 Spray drying of the fragrance in a soluble matrix, such as dextrin, maltodextrin and sugar, has been used to try to protect the fragrance. However, while this procedure has produced encapsulation, the resulting encapsulated form is invariably a fine powder, which is difficult to handle and to incorporate homogeneously in the product, and which is prone to attrition during processing of the product.
- 10 Furthermore, spray-dried fragranced particles are generally very sensitive to humidity, and exposure to moisture over a long period of time often results in fragrance losses and decreased olfactory performance.

Accordingly, there remains a need to provide an odor-control composition that is capable of absorbing malodor and moisture and simultaneously releasing a fragrance or volatile 15 malodor-counteracting substances in a controlled way and which does not suffer from the drawbacks quoted above. In particular, there remains a need to provide an odor-control composition having the capability of retaining the fragrance or volatile malodor-counteracting substance over a prolonged period of time, even under drastic storage conditions such as temperatures exceeding 35 °C and relative humidity higher than 65%, 20 while still releasing this fragrance in contact with aqueous liquids such as urine, refrigeration water, and the like.

It has now been found that the disadvantages of the known art can be substantially and even completely overcome by the use of a particular multifunctional odor-control 25 composition. The invention therefore provides a solid, free-flowing composition adapted to deliver fragrance or malodor counteractant in a consumer product that is subjected to actual or potential malodorous influences, comprising:

- a delivery system consisting of a core material surrounded by a fragranced material comprising microdroplets of a dispersed fragrance in a fragrance-encapsulating material, optionally surrounded by a protective coating,

and,

- an external absorbent material in which the fragrance delivery vehicle is dispersed.

In a particular embodiment of the invention, the composition consists essentially of a

5 delivery system and an external absorbent material, as hereinabove defined.

In a particular embodiment of the invention, both delivery system and external absorbent materials are in free-flowing, granulated form. The external absorbent has a particle size ranging from 0.2 to 10 millimetres, and in particular 0.5 to 5 millimetres, whereas the delivery system has particle sizes preferably ranging from 0.5 to 4 millimetres, in

10 particular from 1.5 to 3 millimetres and from 0.8 to 3 millimetres. These sorts of size ranges are particularly desired and one of the advantages of the present invention is that the particles of the delivery system may easily be made these sizes.

The shape of the particles is not critical. Although the particles of both delivery system and external absorbent are preferably essentially spherical, as such a shape is more

15 attractive in appearance and particles of this shape are less prone to attrition during transport, it is possible for the particles of one or both of the delivery system and the external absorbent to have other shapes. Examples of other shapes include platelets (especially favoured for animal litters), crystals, cylinders, ellipsoids and fibres. In non-spherical cases, the dimensions hereinabove given refer to the major dimension of the
20 particle.

In a most preferred embodiment of the invention, the delivery system and the external absorbent phase are of different colors.

The invention additionally comprises a method of reducing or eliminating malodor, comprising the contacting of an actual or potential source of malodor with a free-flowing
25 solid malodor counteractant composition as hereinabove define.

By "core material" is meant a particulate material that is dispersed in or coated with a fragranced material, or coated with a fragrance-encapsulating material. The core material may absorb part of the fragrance included in the delivery system and facilitate its delayed release. The number and sizes of core material particles present are not narrowly critical,

provided the particle size requirements of the final product are met. The core material may be any such material known to the art that can be produced at or reduced to the desired size for internal use in particles. It may be organic or inorganic. It is permissible to use a blend of two or more such absorbent materials.

5 The core material has, in one embodiment, a bulk density of from 0.2-2.0g/cm³, more particularly from 0.2-1.5g/cm³, 0.5-1.2g/cm³ and 0.8-1.2g/cm³.

Furthermore, the core material may be a water-soluble material or a water-insoluble absorbent material, or a mixture thereof. It will be obvious to a person skilled in the art, that, by varying the composition of the core material, it is possible to obtain core materials 10 that are completely soluble in water, partially soluble or dispersible in water or completely insoluble in water, depending on the type of application envisioned and on the visual effect desired.

Examples of water-soluble core materials useful as core material in this invention include 15 (but are not limited to) inorganic materials like salts of alkaline metals and alkaline earth metals, and organic materials like low molecular weight, non-cellulosic carbohydrate such as sucrose, fructose, saccharose, and other sugars, maltodextrins, and powders of water-soluble polymers such as polyvinyl alcohol, polystyrene sulfonate, polyacrylates and the like.

20 In a particular embodiment of the invention, the water-soluble core material is essentially at least one water-soluble sugar.

In a further embodiment, the core material consists essentially of a water-insoluble organic material. In a particular embodiment, the core material is of vegetal origin. In a further particular embodiment, the core material consists of corn cob. This embodiment is further 25 discussed hereinunder.

Typical non-limiting examples of suitable water-insoluble absorbent materials include clays such as diatomaceous earth, sodium and calcium bentonites, sepiolites, illite and kaolinite; zeolites, aluminosilicates and porous or mesoporous silicates, silica gel, hydrated silicon dioxide, which may be modified by chemical treatment; organic materials 30 such as ground corn cob, husks, wheat fibres and cellulose fibres.

In a further embodiment, the core material consists essentially of a water-insoluble absorbent material. In a more preferred embodiment the core material is an inorganic material. In an even more preferred embodiment, the core material is identical to the external absorbent material. This embodiment is further discussed hereinunder.

- 5 Fragrance materials for use in compositions of the present invention may be selected from natural products such as essential oils, absolutes, resinoids, resins, concretes, and synthetic perfume components such as hydrocarbons, alcohols, aldehydes, ketones, ethers, acids, acetals, ketals and nitriles, including saturated and unsaturated compounds, aliphatic, carbocyclic and heterocyclic compounds, or precursors of any of the above. Other 10 examples of odorant compositions which may be used are described in H 1468 (United States Statutory Invention Registration). The fragrance may optionally have aroma chemicals that are known to reduce the perception of malodors. The fragrance may optionally have aroma chemicals that are known to reduce the perception of malodors and/or prevent their formation via antimicrobial action.
- 15 Non-limiting examples of malodor counteractants include aldehydes such as trimethyl hexanal, benzaldehyde, vanillin, lyral, methyl dihydro jasmonate, ligustral, melonal, octyl aldehyde, citral, cymal, nonyl aldehyde, bourgeonal, lauric aldehyde; enones such as ionone alpha, ionone beta, ionone gamma methyl, alcohols such as cycloalkyl tertiary alcohol, cyclohexyl-2-methyl-2-butanol, cyclohexyl-1-ethanol; ketones such as 4- 20 ethylcyclohexyl methyl ketone, 3, and 4-isopropylcyclohexyl methyl ketone and 4- cyclohexyl-4-methyl-2-pentanone; esters such as geranyl crotonate, cyclohexyl-1-ethyl-n- butyrate, cyclohexyl-1-ethyl-acetate, 2-hydroxyethyl p-tert-butylphenoxyacetate, 6- hydroxylhexyl phenoxyacetate, 4-hydroxybutyl phenoxyacetate, benzyl cinnamate, octyl methoxy cinnamate, phenyl cinnamate, fumaric acid esters, 2-hydroxyethyl 25 phenoxyacetate, 2-hydroxyethyl p-tert-butylphenoxyacetate, 6-hydroxylhexyl phenoxyacetate, 4-hydroxybutyl phenoxyacetate, methyl and ethyl esters of 3-methyl-2- hexenoic acid, cyclohexylmethyl and cyclohexenylmethyl; carbonates such as isocyclogeraniol carbonates, cyclohexene carbonates, cyclohexane carbonates, norbornene carbonates, and dihydroisocyclogeraniol carbonates; nitriles, such as 3-methyl-5-phenyl- 30 pentanenitrile and 3-methyl-5-cyclohexyl-pantanenitrile and their mixtures .

Non-limiting examples of antimicrobial materials include cyclic alcohols, for example, 3-phenyl-2-propen-1-ol, 4-(1-methylethyl)-benzene methanol, 2-phenyl-ethanol, 3-phenyl-propanol benzyl alcohol, phenyl ethyl alcohol; branched or unbranched linear alcohols, for example, from 10-undecenol, 1-nonanol, lactones, for example, 5-hexyl-furan-2(3h)-one, dihydro-5-pentyl-2(3h)-furanone, cyclic ethers such as 2,4,4'-trichloro-2-hydroxy-diphenyl ether; phenolic compounds, such as phenol, 2-methyl phenol, 4-ethyl phenol; essential oils such as rosemary, thyme, lavender, eugenol, geranium, tea tree, clove, lemon grass, peppermint, anise, lemons, oranges, sandalwood, cedar, vervaine, or their active components such as anethole, thymol, eucalyptol, eugenol, farnesol, menthol, limonene, methyl salicylate, salicylic acid, terpineol, nerolidol, geraniol, cedrol, cavacrol, verbenone, eucalyptol and pinocarvone, hinokitiol, berberine, cinnamic aldehyde, cinnamyl alcohol and mixtures thereof; cyclic aldehydes, for example, 2-methyl-3-phenyl-2-propenal, 2-phenyl-propanal, branched or unbranched linear aldehydes, for example, 3,7-dimethyl-octa-2,6-dien-1-al, 2,4-nonadienal; and their mixtures thereof.

15 Fragrance materials particularly suitable for use with the present invention are those having a loss factor lower than 10^4 Pa ppm, wherein the term "Loss Factor" refers to a parameter that is related to the losses of fragrance material during agglomeration in a fluidized bed and is defined as the product of the pure component saturation vapour pressure (Pa) in the standard state (278.15 K, 1 atm) and the water solubility (ppm) at room temperature. Vapour pressures and water solubility data for commercially-available fragrance components are well known and so the Loss Factor for a given fragrance component may be easily calculated. Alternatively, vapour pressure and water solubility measurements may be easily taken using techniques well known in the art. Vapour pressure of fragrance components may be measured using any of the known quantitative 20 headspace analysis techniques, see for example Mueller and Lamparsky in "Perfumes: Art, Science and Technology", Chapter 6 "The Measurement of Odors" at pages 176 – 179 (Elsevier 1991). The water solubility of fragrances may be measured according to techniques known in the art for the measurement of sparingly water-soluble materials. A preferred technique involves the formation of a saturated solution of a fragrance 25 component in water. A tube with a dialysed membrane is placed in the solution such that after equilibration an idealised solution is formed within the tube. The tube may be removed and the water solution therein extracted with a suitable organic solvent to remove 30

the fragrance component. Finally the extracted fragrance component may be concentrated and measured, for example using gas chromatography. Other methods of measuring fragrances are disclosed in Gygax et al, Chimia 55 (2001) 401-405.

By "fragrance-encapsulating material" is meant a barrier material effectively preventing the fragrance from diffusing out of the delivery system. Fragrance-encapsulating materials are hydrophilic materials that may be selected from:

- (1) water-soluble or water-dispersible polymer, especially polysaccharides and modified polysaccharides, such as starch and modified starch or dextrin bearing octenyl succinate moieties;
- 10 (2) maltodextrin, sugars, sugar alcohols, mannitol, inulin, and trehalose;
- (3) natural or synthetic gums such as alginate esters, gum arabic, gum tragacanth and gum karaya, carrageenan, xanthanes, agar-agar, pectines, and pectic acid;
- 15 (4) synthetic water-soluble or partially water -soluble, or -degradable polymers, such as (i) vinyl polymers such as poly(vinyl alcohol), poly(vinyl alcohol-vinyl acetate) copolymers, poly(vinyl alcohol-vinyl acetate-sodium vinyl sulfonate) copolymers; poly(vinyl pyrrolidone) and copolymer derivatives such as poly(vinyl pyrrolidone-vinyl acetate), poly(vinylpyrrolidone-vinyl alcohol), poly(vinylpyrrolidone-styrene); (ii) alkali-soluble polymers, e.g. poly(acrylic acid), poly(maleic acid), poly(alkyl(meth)acrylate- (meth)acrylic acid) copolymer, poly(acrylic acid-maleic acid)copolymer, poly(acrylamide), poly(methacrylic acid), poly((meth)acryl amide), (iii) poly(ethylene oxide) and poly(ethylene oxide – propylene oxide) block copolymers;
- 20 (iv) mixtures thereof;
- 25 (5) Biodegradable (bio)polymers such as (i) polyesters, especially polymers of lactic, glycolic, hydroxybutyric acid derivatives such as poly (D,L-lactide), poly (L-lactide), poly (L-lactide-co-glycolide), poly(D,L-lactide-co-glycolide), poly (D,L-lactide-co-glycolide-D-glucose), poly (hydroxybutyric acid) and further derivatives, copolymers or mixtures thereof; (ii) water soluble or water dispersible forms of poly (3-hydroxy butyrate) derivatives; (iii) lignin derivatives such as

lignosulphonates, oxylignins and kraft lignins and further derivatives or mixture thereof;

Preferred fragrance-encapsulating material is a mixture of modified starch bearing
5 octenyl succinate moieties and mannitol, admixed in a weight% ratio of from 90:10
to from 10:90, particularly from 80:20 to 50:50.

By "protective coating" is meant a thin layer of a material having the function of preventing low levels of moisture present in the product causing breakdown or clumping of the particles, yet which, in the presence of larger amounts of water in use, will break
10 down and allow release of the fragrance. Suitable protective coating materials are selected from cellulose, microcrystalline cellulose, cellulose ethers and esters such as ethyl cellulose, cellulose acetate, hydroxyethyl cellulose, hydroxypropyl methyl cellulose, hydroxypropyl methyl cellulose acetate, phthalate or succinate, as well as enteric/aquateric coatings and mixture thereof, carrageenan, chitosan, aceto-acetylated polyvinylalcohols,
15 poly(alkyleneoxide) homopolymers and block copolymers, poly(vinylmethylether), poly(vinylether-maleic anhydride), organosilicones, and inorganic materials such as silicates, sulfates, borates, oxides, hydroxides, clay minerals, celites, zeolites in colloidal or powder form. The preferred protective coating is microcrystalline cellulose and hydroxyethyl cellulose, or a mixture thereof with carrageenan, maltodextrin and
20 polyethylene glycol.

If color in the compositions be desired, it may be provided by the use of any suitable coloring matter. Coloring matters especially suitable for use in the present invention include water-soluble dyes and water-dispersible pigments having high affinity with the
25 encapsulating material and, consequently, limited capability to migrate into the surroundings. It is preferred not to use coloring matters that migrate easily under the action of water, as these can lead to discoloration and staining of the composition, resulting in undesirable appearance, staining of the container or devices containing the composition, and staining of the environment surrounding the containers or devices should
30 part of the composition be spilled out of these. It will be obvious to everybody skilled to the art that the selection of a suitable coloring matter will depend on the nature of the encapsulating material and that this selection relies on laboratory screening work. A convenient method of screening and selecting suitable coloring matters involves, for

example, putting a colored particle of the delivery system on a bed of absorbent material, adding a certain amount of water (e.g. 1 ml) on to this particle and measuring the diameter of the colored spot which may result from coloring matter migration after a certain time (e.g. 24 hours). Coloring matters that generate colored spots with radius smaller than the 5 average diameter of the colored particle are considered as suitable for the scope of the present invention. Preferred coloring matters are water-dispersible pigments such as phthalocyanine pigments. Most preferred colouring matters are aqueous dispersions of water-dispersible pigments formulated with styrene-acrylic resins.

The delivery system according to the present invention may contain formulation additives, 10 such as emulsifiers, binders and anti-clumping agents, functional additives such as pH modifiers, and bioactive agents, such as anti microbial agents, insect repellent, and attractants.

The delivery system has a bulk density of 0.2-2.0, in particular, 0.4-2.0, 0.4-1.3, 0.5-1.5 15 and 0.7-1.1g/cm³, while the ratio of the bulk density of the delivery system to the bulk density of the external absorbent is between 0.5 and 1.5, particularly between 0.7 and 1.3 and more particularly between 0.8 and 1.2.

The delivery system is mixed with an external absorbent material. By “external absorbent 20 material” is meant any free-flowing material that may absorb an aqueous liquid or a malodor in sufficient quantity to provide dampness and/or malodor control. Materials capable of absorbing more than 50% by weight of water or of decreasing substantially the headspace concentration and perception of malodor smell belong to the category of absorbent materials particularly useful in the present invention. It is considered as not 25 relevant in the context of the present invention to make the difference between absorption and adsorption and, therefore, materials that are usually considered as adsorbent materials are included in the category of absorbent materials.

The free-flowing external absorbent may be particulate, for example, in the form of 30 spherical or elongate particles, or fibrils. Typical external absorbent materials are selected, for example, from clays such as diatomaceous earth, sodium and calcium bentonites, sepiolites, illite and kaolinite; zeolites, aluminosilicates and porous or mesoporous silicates; cyclodextrins; activated charcoals; super-absorbing polymers such

as polyacrylates, polyacrylamides or sulfonated polystyrene; organic absorbents such as ground corn cob, rice hull ash, ground alfalfa, cracked wheat, semolina, wood shavings, chopped soya bean stalk, peanut hull, wood shavings, and mixtures thereof. Mixtures of such absorbent materials with filler materials such as cellulose, sand, soil, ground rock, fly 5 ash, or mixtures thereof, can be considered as absorbent materials, provided these mixtures exhibit appreciable water uptake and malodor absorbing properties as quoted above. Typically, the absorbent material is conditioned in order to improve its pourability, free flowability and aspect, to remove fine dusty particles and prevent excessive clumping in the presence of water. Typical conditioning treatments include but are not limited to 10 granulation or agglomeration, compaction, extrusion and gasket extrusion, to provide granulated forms, beads, rods and flakes, which, optionally, can be admixed with anti-clumping agents. The methods of making these forms are well-known to the art.

In a specific embodiment of the present invention, especially useful in humidity absorbers 15 and central air conditioning units, the absorbent material may be a known desiccant, such as calcium chloride, magnesium chloride, magnesium sulphate, silica gel, silicates, celite, activated alumina, zeolites, activated charcoals and molecular sieves. These may optionally be admixed with malodor-absorbing materials such as metal salts, for example, aluminium sulphate or zinc ricinoleate, cyclodextrins and activated charcoal.

20

In another specific embodiment of the present invention, especially useful in humidity absorbers and central air conditioning units, the composition is compressed in order to form a tablet or any compact shape that may be desirable.

25 A further possible ingredient of the external absorber is fragrance. Although in many cases, it is desirable to have all the fragrance in the delivery system, in some cases, it is desirable to have some fragrance, typically up to 1.0 % by weight in the external absorber, preferably up to 0.5% by weight in the external absorber. The fragrance added to the external absorber need not be the same fragrance as used in the delivery system.

30

A preferred embodiment for animal litter is when the core material is an inorganic absorbent, especially when it is the same material as the external absorbent, as this has surprisingly been found to reduce clumping of the product. Preferred examples of core

materials and external absorbents include diatomaceous earth, sodium and calcium bentonites, sepiolites and kaolinite, all optionally chemically treated.

The invention is also directed to a method of forming a delivery system as hereinabove described, comprising the steps of spraying a fragranced material on to an absorbent material, which thereby becomes the internal absorbent material as hereinabove described. 5 Optionally, the resultant encapsulated material can be coated with a coating material as hereinabove defined.

The fragranced material may be sprayed on to particles, in the form of an emulsion, in order to build up compositions according to the invention. The fragranced material may be 10 applied to the core particles in an agglomeration process, for example in a fluidised bed. Preferably, the agglomeration is carried out in any of the well-known fluidised bed dryers equipped with a product container. The process is started with the fluidisation of the core material.

The fragranced material emulsion may be formed by mixing under high shear the 15 fragrance with an aqueous phase comprising water and the encapsulating materials, and optionally a dye to form an emulsion. The emulsion may thereafter be sprayed on to the fluidised core particles using a pressure, sonic or a pneumatic nozzle, preferably, a two-fluid nozzle, or a three-fluid nozzle which is inserted either on the top (top spray), lateral (lateral spray), tangential (tangential spray), or at the bottom (bottom spray) of the 20 fluidised bed.

Alternatively, the fragranced material emulsion may be applied to the core particles in a spray coating process, wherein the fragranced material is coated on to a core material having a particle size and particle size distribution commensurate with the desired final delivery system particle size and particle size distribution. The spray coating process may 25 be performed in a fluidised bed dryer, a drum coater, a pan coater or a Loedige mixer, or any mechanical device, where the particulate core material is put in motion in such a way that the surface of the particles is homogeneously exposed to the spray providing the atomized fragranced material emulsion.

After the agglomeration or spray coating process has been completed or after the emulsion 30 has been completely sprayed on the fluidised core particles, the coating material can be

optionally applied on the delivery system. Typically the coating material may be provided in the form of a melt, an aqueous solution, emulsion or dispersion and sprayed onto the delivery system using the same nozzle set-up as described above.

The present invention additionally provides an odor-control composition comprising
5 typically:

- 0.1 to 10%, preferably 0.25-10%, more preferably 0.5 to 5% of fragrance delivery system, comprising

- 50 to 90%, preferably 60 to 75%, of a core material and

- 10 to 50%, preferably 25 to 40% of a fragranced material containing

10 - 1 to 30%, preferably 10 to 20% of a fragrance or malodour-counteracting substance and

- 70 to 99%, preferably 80 to 90% of fragrance encapsulating material,

and, optionally,

15 - 0.01 to 5%, preferably 0.2 to 2%, more preferably 0.2 to 2.5% of a dye

and, optionally,

- 0.5 to 10%, preferably 1 to 5% of protective coating material, optionally containing from 0.01 to 5%, preferably 0.2 to 2.5% of a dye;

20 and,

- 90 to 99.9%, preferably 90-99.75%, more preferably 95 to 99.5% of an external absorbent material; all percentages being by weight.

The composition and method of the present invention is useful in many different applications, in which malodors or the potential for their generation must be prevented or
25 at least reduced. The invention therefore also provides a product that is adapted to be

exposed to an actual or potential source of malodor and to at least reduce that malodor or potential therefore, the product comprising a solid, free-flowing composition as hereinabove defined.

The types of products in which the present invention can be used includes, but is not limited to, animal litters, sanitary towels and incontinence pads, filters for central air conditioning units, and humidity absorbers. The invention is particularly effective in conjunction with animal litters, especially those for cats. The invention therefore also provides an animal litter, especially a cat litter, comprising a solid, free-flowing composition as hereinabove defined.

10 The invention is now further described with reference to the following non-limiting examples, which describe preferred embodiments, all percentages of materials being by weight.

Example 1: Preparation of absorbent material

800 g illite clay was poured into a Loedige laboratory wet granulator M 5 equipped with 15 three ploughshare shovels attached to a rotating horizontal shaft, and a side-mounted spinning chopper.

The chamber was heated by external oil bath at 70°C (product temperature was 55°C).

100 ml water was directly added to the clay in the mixing chamber. The ploughshare and chopper were started and the mixing process was performed for 10 minutes. A further 50 20 ml water was added and it was mixed for 2 minutes. Finally 280 g 10% w/w hydroxypropyl methyl cellulose in water was pumped into the chamber.

The granulated material was dried in an oven at 80 ±5°C for 20 minutes to yield a grey-brown granulated absorbent material of bulk density 1.03g/cm³.

Example 2: Preparation of delivery system with absorbent as core material

25 A fragranced material emulsion was prepared by emulsifying 2 kg of fragrance oil into an aqueous phase containing 10 kg of water, 2 kg of mannitol 60 (ex Roquette Frères), 6 kg of modified starch HiCap 100 (ex National Starch) and 0.07 kg of HeucosperseTM

pigment GS dispersion (ex Heubach International). The emulsion was prepared according to a procedure wherein the aforementioned encapsulating materials were slowly added together under vigorous stirring (15500rpm) with a polytron turbine (Ystral GmbH X 50710, Germany) until complete dissolution was reached. The fragrance was then added 5 under continuous stirring. The mixture was homogenised for an additional 10 minutes until a stable emulsion was obtained having a mean particle size below 1 micron.

20 kg of the absorbent material prepared according to Example 1 was placed in a conical fluidised bed granulator WS-GT-0.40 (Allgaier Werke GmbH, Germany) and fluidized by applying a air flux of 300 m³/h (as the process continued, it was found necessary to 10 increase progressively the pressure to 600 m³/h). 20 kg of said fragranced material emulsion was then sprayed on to the fluidized absorbent material by applying an atomisation air pressure of 2.5 bar with a spraying rate of up to 10 kg per hour, using a laterally-inserted two-fluid nozzle (Schlick Modell 0/2, Duesen-Schlick GmbH, Germany). The inlet temperature was 100°C, outlet temperature 45°C. Thereafter, an 15 aqueous suspenion of coating material (LustreClearTM LC 101, ex FMC BioPolymer Pharmaceutical) was sprayed on to the resultant composition to form a coated granulated material containing 2% of coating material. This yielded 25 kg of delivery system in granulated form. After screening (2.0 mm sieve), the bulk density was found to be 0.90 g/cm³, and the particulate material was dust-free and free-flowing.

20 Example 3: Preparation of delivery system with sugar as core material

The same procedure was applied as above but the absorbent core material was replaced with saccharose Middling Fine (ex Südzucker, Germany) having a particle size distribution between 0.7 and 1.3 millimetres and a bulk density of 0.79 g/cm³.

Example 4: Preparation of delivery system with sugar as core material, by spray coating

A fragranced material emulsion containing 18.7% perfume, 8.4% mannitol 60 (ex Roquette Frères), 33.6% Hi-CapTM 100 (ex National Starch) and 0.1% of HeucosperseTM

pigment dispersion (ex Heubach International) and 39.3% water was prepared as described in Example 1.

12 kg of coarse sugar core material (CarrareTM C10, ex Sucrerie Couplet, Belgium) was placed in a conical fluidised bed granulator WS-GT-0.40 (Allgaier Werke GmbH, 5 Germany) and fluidized by applying a air flux of 350 m³/h (as the process continued, it was found necessary to increase progressively the pressure to 600 m³/h). 4.9 kg of said fragranced material emulsion was then sprayed on to coarse sugar by applying an atomisation air pressure of 4 bar with a spraying rate of up to 4 kg per hour, using a laterally-inserted two-fluid nozzle (Schlick Modell 0/2, Duesen-Schlick GmbH, 10 Germany). The inlet temperature was 100°C, outlet temperature 45°C. This yielded a delivery system having particle size ranging from 2 mm to 3 mm and a bulk density of 0.74 g/cm³, which was free-flowing and dust free.

Example 5: Preparation of delivery system with corn cob as core material, using a drum coater

15 1.25 kg corn cob fraction A1 (ex Independence Corn By-Products, Iowa, USA) was brought into a DRC Vario 500/600 (ex DRIAM, Germany) with a 2.5 L drum. Settings: distance bed - nozzle 8-10 cm; nozzle: 1.2 mm; Spray pressure: 1.0 bar; Spray rate: 5 – 12 g/min.

0.83 kg fragrance material emulsion comprising 39.5 % water, 8.3 % mannitol, 33.0 % Hi-20 CapTM 100, 18.6 % perfume and 0.7 % dye was sprayed using a Schlick three-fluid nozzle fed at 0.55 kg/h with a peristaltic pump. The inlet temperature was set on 80°C and the outlet temperature at 50°C during spraying.

Finally, 0.313 kg of a dispersion containing 8.0% LustreClearTM LC 101 (ex FMC BioPolymer Pharmaceutical) and 92% water was sprayed on the coloured product. The 25 inlet temperature was hold at 80°C and the outlet temperature at 45°C during spraying.

This yielded 2.2 kg of delivery system having a bulk density of 0.56 g/cm³, and the particulate material was dust-free and free-flowing.

Example 6: Effect of coating on storage stability:

Various amounts of an aqueous suspension of coating material (LustreClearTM LC101, ex FMC BioPolymer Pharmaceutical) was sprayed on to the delivery system prepared according to Example 3. 1 g of delivery system, prepared according to example 3, was admixed with 49 g of absorbent material in an open Petri dish and placed under controlled 5 climatic conditions (37 °C and 70% relative humidity for up to 5 weeks and 75 °C and 80% relative humidity for 1 day). After a certain period of time, as indicated in Table 1, the stickiness of the samples, i.e. the extent of clumping with neighbouring absorbent particles, was assessed. The samples were rated as follows: ++ : not sticky, + : bit sticky, dust sticks, 0 : slightly sticky, only small particles stick, - : sticky.

Table 1.

Sample	37 °C and 70 %RH				75 °C and 80 %RH
Coating (%)	1 day	1 week	3 weeks	5 weeks	1 day
0.00	0	-	-	-	-
0.30	+	+	0	-	-
0.74	++	+	-	-	0
0.97	++	+	-	-	0
1.19	++	++	-	-	0
1.40	++	++	+	-	0
1.62	++	++	+	-	0
1.84	++	++	+/0	-	+
2.06	++	++	+/0	-	+
2.34	++	++	+/0	0	+

Example 7: Olfactive evaluations in litter:

The fragrance delivery system as prepared in Example 2 contained 7% fragrance. This
5 was dosed at 1%) into the absorbent material prepared in Example 1. An equivalent
amount of free fragrance oil (0.07%) was dosed into the absorbent material prepared in
example 1. 100 g of the respective mixtures was placed in 250 ml bottles. One set was
compared initially for odor intensity by adding 10 g of water. A panel of 5 people rated
the intensity of the odor on a 5 point scale (1 = very low intensity of odor and 5 = high
10 intensity of odor). A second set was placed into a storage oven at 37 C for seven days.

The samples were taken out of the oven and allowed to cool to room temperature. 10 g of water were poured on the respective products and the panel assessed them for odor intensity. The results were:

Sample	Initial Intensity Rating	Intensity Rating -7 days at 37 C.
Free Fragrance	2.2	1.4
Delivery System	3.8	4.5

5 The delivery system is clearly highly efficient in retaining volatile fragrance ingredients over a prolonged period of time compared to adding the free fragrance oil.

Example 8. Olfactive evaluation of different particles.

Using the process outlined in Example 3, two delivery systems were prepared. One had the internal sugar core material and a coating (2%) applied as described in Example 2. The 10 second system had internal sugar core material but no coating was applied. The delivery systems were added at 1% to the absorbent material of prepared in Example 1 and samples prepared as per Example 5. A free fragrance control was prepared as in Example 5. The samples were evaluated using the methodology given in Example 5. The results of the panel were:

Sample	Initial Intensity Rating	Intensity Rating -7 days at 37C.
Sugar-based delivery system with 2% coating	3.8	4.0
Sugar based delivery system	4.0	4.6
Free Fragrance	2.2	1.4

Example 9. Olfactive evaluation of different particles in Bentonite Clay

The fragrance delivery system as prepared in Example 2. An enrobed system was prepared according to US patent 6,803,833 with the following recipe: 69 parts zeolite, 10 parts bentonite clay, 1 part propylene glycol, 20 parts fragrance.

5

Samples of the delivery system and the free fragrance were prepared as per Example 5. Samples containing the enrobed fragrance were prepared by adding 0.35% (w/w) to the clay to have equal fragrance. The samples were evaluated as per Example 5. The results are shown below:

10

Sample	Initial Intensity Rating	Intensity Rating -7 days at 37C.
Delivery System Ex. 3	2.6	4.5
Free Fragrance	1.8	1.0
Enrobed Fragrance	2.8	3.4

The delivery system offers a performance benefit over the enrobed fragrance and a much larger one over the free fragrance after storage.

Example 10. Effect of Internal Absorbent Core on Clumping

15 Using the process outlined in Examples 2, 3 and 5, three delivery systems were prepared. One had the internal clay absorbent without external coating. The second system had an internal sugar core material, no coating was applied. The third system had an internal corn cob core material, no coating was applied. The delivery systems were added at 1% to the external absorbent material prepared in Example 1 and samples stored at 30C and 80%
20 relative humidity. The litters were assessed for clumping:

++ = not sticky + = bit sticky dust sticks 0 = bit sticky, small particles stick - = sticky.

The results are shown below:

Sample	Degree of clumping
Internal clay core – No coating	+
Internal sugar core – no coating	-
Internal corn cob core – no coating	+

The particles with an internal clay core clumped less than those with an internal sugar core.

5 Example 11. Olfactive evaluation of Delivery System in Incontinence Pads

The delivery system as prepared in Example 3 was added to *Serenity*® Extra absorbency incontinence pads manufactured by Tena. These pads were obtained as market samples. The incontinence pads were opened from the side and the inner absorbent layer separated to form a space for depositing the individual samples within. Two sets of samples were 10 prepared by adding 0.3 g of the delivery system prepared according to Example 3 to the center of the pad for sample 1 and 0.0021 g of fragrance the center of a pad. Set 1 had 10 g of water added and the intensity paneled as per Example 5. Set 2 were placed in an oven at 37 C for 7 days the pads were equilibrated to room temperature and 10 g of water added to the respective pads. The results of the paneling were:

15

Sample	Initial Intensity Rating	Intensity Rating -7 days at 37 C.
Delivery System Ex. 2	2.9	4.2
Free Fragrance	4.0	1.0

Clearly the system is delivering more fragrance from the delivery system on storage.

Claims:

1. A solid, free-flowing composition adapted to deliver fragrance or malodor counteractant in a consumer product that is subjected to actual or potential malodorous influences, comprising:

5 - a delivery system consisting of a core material surrounded by a fragranced material comprising microdroplets of a dispersed fragrance in a fragrance-encapsulating material, optionally surrounded by a protective coating,

and,

10 - an external absorbent material in which the fragrance delivery vehicle is dispersed.

2. A composition according to claim 1, consisting essentially of

15 - a delivery system consisting of a core material surrounded by a fragranced material comprising microdroplets of a dispersed fragrance in a fragrance-encapsulating material, optionally surrounded by a protective coating,

and,

- an external absorbent material in which the fragrance delivery vehicle is dispersed.

3. A composition according to claim 1, in which both delivery system and external
20 absorbent material are in free-flowing, granulated form, the particle size ranging from 0.2 to 10 millimetres, preferably 0.5 to 5 millimetres, whereas the delivery system has particle sizes preferably ranging from 0.5 to 4 millimetres, more preferably from 1.5 to 3 millimetres and most preferably from 0.8 to 3 millimetres.

4. A composition according to claim 3, in which delivery system and external
25 absorbent material are essentially spherical.

5. A composition according to claim 1, in which the delivery system has a bulk density of 0.4-2.0, preferably 0.5-1.5g/cm³, while the ratio of the bulk density of the delivery system to the bulk density of the external absorbent is between 0.5 and 1.5, preferably between 0.7 and 1.3 and most preferably between 0.8 and 1.2.

5

6 A composition according to claim 1, in which the delivery system and the external absorbent material are of different colors.

7 A composition according to claim 1, in which the external absorbent material comprises fragrance.

10 8. A composition according to claim 1, in which there is present a protective coating selected from microcrystalline cellulose and hydroxyethyl cellulose, and a mixture thereof with carrageenan, maltodextrin and polyethylene glycol.

9. A composition according to claim 1, in which the absorbent material is a desiccant, 15 preferably selected from the group consisting of calcium chloride, magnesium chloride, magnesium sulphate, silica gel, silicates, celite, activated alumina, zeolites, activated charcoals and molecular sieves, these being optionally admixed with malodor-absorbing materials, preferably malodour-absorbing materials selected from metal salts, cyclodextrins and activated charcoal.

20 10. An odor-controlling composition comprising:

- 0.1 to 10%, preferably 0.25-10%, more preferably 0.5 to 5% of fragrance delivery system, comprising

- 50 to 90%, preferably 60 to 75%, of a core material and

- 10 to 50%, preferably 25 to 40% of a fragranced material containing

25 - 1 to 30%, preferably 10 to 20% of a fragrance or malodour-counteracting substance and

- 70 to 99%, preferably 80 to 90% of fragrance encapsulating material,

and, optionally,

- 0.01 to 5%, preferably 0.2 to 2%, more preferably 0.2 to 2.5% of a
5 dye

and, optionally,

- 0.5 to 10%, preferably 1 to 5% of protective coating material, optionally containing from 0.01 to 5%, preferably 0.2 to 2.5% of a dye;

and,

10 - 90 to 99.9%, preferably 90-99.75%, more preferably 95 to 99.5% of an external absorbent material; all percentages being by weight.

11 A method of reducing or eliminating malodor, comprising the contacting of an actual or potential source of malodor with a free-flowing solid malodor counteractant composition according to claim 1.

15 12 A product that is adapted to be exposed to an actual or potential source of malodor and to at least reduce that malodor or potential therefore, the product comprising a solid, free-flowing composition according to claim 1.

13. A product according to claim 12, in which the product is an animal litter.

INTERNATIONAL SEARCH REPORT

International application No
PCT/CH2006/000187

A. CLASSIFICATION OF SUBJECT MATTER
INV. A01K1/015

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A01K A61L A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP '0 076 122 A (THE CLOROX COMPANY) 6 April 1983 (1983-04-06) claim 1; example I -----	1,2,9-13
X	WO 02/26272 A (SALVONA L.L.C) 4 April 2002 (2002-04-04) page 20, line 3 - line 6; examples 1,3 -----	1,2,9-12
X	PATENT ABSTRACTS OF JAPAN vol. 2003, no. 12, 5 December 2003 (2003-12-05) & JP 2004 033047 A (PEPAARETSUTO KK), 5 February 2004 (2004-02-05) abstract ----- -/-	1,2,9-13

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

27 June 2006

Date of mailing of the international search report

05/07/2006

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Saunders, T

INTERNATIONAL SEARCH REPORT

 International application No
 PCT/CH2006/000187

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 2003, no. 12, 5 December 2003 (2003-12-05) & JP 2005 021071 A (UNICHARM PETCARE CORP), 27 January 2005 (2005-01-27) abstract -----	1,2,9-13
A	US 5 290 547 A (BILBREY ET AL) 1 March 1994 (1994-03-01) column 5, line 29 - line 61; claim 20 -----	1-13
A	US 2003/072733 A1 (MCGEE THOMAS ET AL) 17 April 2003 (2003-04-17) examples 1,3 -----	1-13
A	US 5 662 067 A (STUBBS ET AL) 2 September 1997 (1997-09-02) claim 1 -----	1-13
A	EP 1 092 346 A (RETEC RECYCLING, ENTWICKLUNGS- UND TECHNOLOGIEGESELLSCHAFT MBH) 18 April 2001 (2001-04-18) claims 1,8 -----	1-6,9, 11-13
A	US 5 775 259 A (TUCKER ET AL) 7 July 1998 (1998-07-07) table A -----	1-5,9, 11-13
A	FR 2 794 994 A (HENKEL FRANCE) 22 December 2000 (2000-12-22) claims 1,6 -----	1-12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/CH2006/000187	
---	--

Patent document cited in search report	Publication date		Patent family member(s)	Publication date
EP 0076122	A 06-04-1983	CA DE ES JP JP JP US	1193200 A1 3268045 D1 8307444 A1 1616505 C 2041304 B 58078518 A 4407231 A	10-09-1985 30-01-1986 01-11-1983 30-08-1991 17-09-1990 12-05-1983 04-10-1983
WO 0226272	A 04-04-2002	AU EP	9310801 A 1322343 A1	08-04-2002 02-07-2003
JP 2004033047	A 05-02-2004	NONE		
JP 2005021071	A 27-01-2005	NONE		
US 5290547	A 01-03-1994	US	5489427 A	06-02-1996
US 2003072733	A1 17-04-2003	EP	1190725 A2	27-03-2002
US 5662067	A 02-09-1997	NONE		
EP 1092346	A 18-04-2001	AT DE	305215 T 59912607 D1	15-10-2005 03-11-2005
US 5775259	A 07-07-1998	CA EP US	2198583 A1 0862853 A1 5647300 A	26-08-1998 09-09-1998 15-07-1997
FR 2794994	A 22-12-2000	NONE		