

18



Europäisches Patentamt
European Patent Office
Office européen des brevets

11 Publication number:

**0 167 370
B1**

12

EUROPEAN PATENT SPECIFICATION

45 Date of publication of patent specification: **25.04.90**

51 Int. Cl.⁵: **A 24 B 3/14, A 24 B 15/28**

21 Application number: **85304645.6**

22 Date of filing: **28.06.85**

54 **Foamed, extruded tobacco-containing smoking articles.**

30 Priority: **03.07.84 US 627407**

43 Date of publication of application:
08.01.86 Bulletin 86/02

45 Publication of the grant of the patent:
25.04.90 Bulletin 90/17

64 Designated Contracting States:
CH DE FR GB IT LI NL

56 References cited:
**EP-A-0 056 308
EP-A-0 113 595
CA-A- 951 209
GB-A-1 055 445
US-A-2 433 877
US-A-4 233 993
US-A-4 333 484**

73 Proprietor: **Philip Morris Products Inc.
3601 Commerce Road
Richmond Virginia 23234 (US)**

72 Inventor: **Burnett, George Henry
802 Baldwin Road
Richmond Virginia 23229 (US)
Inventor: Keritsis, Gus Demitrios
104 Carbe Court
Richmond Virginia 23236 (US)
Inventor: Wayte, Alline Roger
4407 Archer Avenue
Richmond Virginia 23225 (US)
Inventor: Nepomuceno, Jose G.
4108 Forest Hill Avenue
Richmond Virginia 32225 (US)
Inventor: Gergely, Alex Sandor
1655 Mayway Drive
Powhatan Virginia 23139 (US)**

74 Representative: **Smith, Philip Antony et al
REDDIE & GROSE 16 Theobalds Road
London WC1X 8PL (GB)**

EP 0 167 370 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

EP 0 167 370 B1

Description

The present invention relates to the formation of smoking articles by extrusion and foaming of a tobacco-containing mixture.

5 U.S. Patent 4,510,950, issued 16th April 1985 and the corresponding European Patent Application, published under No. 0113595 on 18th July 1984, describe a method in which a substantially cylindrical smoking article is extruded under conditions such that the water in the wet blend fed to the extruder die is converted to steam, thereby foaming the article. The article is monolithic, that is, it is extruded as a single strand with a diameter of typically about 8 mm if the article is a cigarette.

10 Although that article represents an advance over the art, in certain cases the article has been found to soften sufficiently during smoking to cause the article to collapse. Additionally, in some cases the resistance-to-draw (RTD) of the article has been too high and/or difficult to control.

Accordingly, there is a continuing need for smoking articles that can be manufactured easily, whose RTD and other physical properties can be easily controlled within desired ranges, and which are well
15 accepted in the marketplace.

In accordance with the present invention there is provided a method of making a foamed, extruded, tobacco-containing smoking article comprising forming a wet blend containing 15% to 50% of water and the remainder, on a dry weight basis, comprising 5 to 98 weight % of tobacco particles having a particle size up to 4 mm, (5 mesh), from 0 to 60 weight % of a filler having a particle size of not more than 350 μm ,
20 and from 2 to 40 wt.% of a binder from the group consisting of cellulosic binders, natural binders, modified natural binders, synthetic binders, and mixtures thereof, extruding the wet blend through a die having a plurality of holes to form a plurality of strands and twisting the extruded strands together, the strands being foamed by the conversion of some of the moisture to steam and adhered together to form a smoking article.

25 The invention also provides a foamed extruded, tobacco-containing, smoking article comprising a plurality of co-extruded strands twisted together that extend generally along the longitude of the smoking article and are adhered to one another so as to leave tortuous flow passageways between the strands, which passageways extend generally along the longitude of the smoking article, the smoking article also comprising on a dry weight basis (a) from 5 to 98 wt.% of tobacco particles having a particle size of up to
30 about 4 mm (5 mesh), (b) from 0 to 60 wt.% of a filler having a particle size of up to about 350 μm , and (c) from about 2 to 40 wt.% of a binder selected from the group consisting of cellulosic binders, natural binders, modified natural binders, synthetic binders, and mixtures thereof, and further comprising (d) from about 5 to about 20 wt.% water calculated as a percentage of the total product weight, the article having a density within the range of from about 0.05 to about 1.5 g/cc.

35 The binder in the article may be selected from the groups of (1) cellulosic binders consisting of hydroxypropyl cellulose, carboxymethyl cellulose and its sodium, potassium, and ammonium salts, cross-linked carboxymethyl cellulose and its sodium, potassium, and ammonium salts, hydroxyethyl cellulose, ethyl hydroxyethyl cellulose, hydroxypropyl methyl cellulose, methyl cellulose, ethyl cellulose, and mixtures thereof; or (2) natural binders, modified natural binders, and synthetic binders consisting of
40 pectin and its ammonium, sodium, and potassium salts, starch, guar and derivatives thereof, hemicellulose, xanthan, curdlan, a salt of xanthomonas gum, carageenan, alginic acid and its ammonium, sodium, and potassium salts, chitosan and its water soluble salts oxycellulose, polyvinyl maleic acid polymer and its ammonium, sodium, and potassium salts, microcrystalline cellulose, dextran, dextrin, fibrous cellulose, and mixtures thereof; or (3) a mixture of cellulosic, natural, modified natural, or synthetic
45 binders.

In one embodiment, the method ("Method A") includes the steps of:

(a) dry blending (i) from about 5 to about 98 wt.% of tobacco particles having a particle size of up to about 5 mesh and an OV value of from about 3 to about 20% with (ii) from 0 to about 60 wt.% of a filler having a particle size of up to about 350 μm , and (iii) from about 2 to about 40 wt.% of a binder, all on a dry
50 weight basis and

(b) admixing the dry blend from step (a) with water to form a wet blend for extrusion containing from about 15 to about 50 wt.% of water.

In an alternative embodiment, the method ("Method B") includes the steps of:

(1) dry blending from about 5 to about 98 wt.% of tobacco particles having a particle size of up to about
55 5 mesh and an OV value of from about 3 to about 20% with from 0 to about 60 wt.% of a filler having a particle size of up to about 350 μm ;

(2) prehydrating from 2 to 40 wt.% of a binder by mixing the binder with water to activate the adhesive character of the binder;

(3) admixing the dry blend from step (1) and the prehydrated binder from step (2) to form a wet blend
60 for extrusion containing from about 15 to about 50 wt.% of water.

The smoking article of this invention is easy to manufacture and its TRD and other physical properties can be easily controlled within desired ranges. Additionally, the multistrand, coherent smoking article displays a surprising combination of properties. Its stiffness and resistance to collapse are significantly better than a single strand's but the RTD, density, taste, and other properties are still within commercially
65 favourable ranges.

EP 0 167 370 B1

That is surprising because the physical complexity of manufactured smoking articles is such that correcting one unfavorable product variable usually results in another becoming unfavorable. For example, the stiffness of the single strand smoking article could be rendered favorable by increasing the density or changing the composition but the former change would require excessive amounts of tobacco per article and raise its RTD and the latter change would probably change the taste of the article.

Other advantages of the present invention will be apparent from this specification.

Brief description of the drawings

To facilitate further discussion of the invention, the following drawings are provided in which:

Figure 1 is a perspective view of the end of the barrel of an extruder showing the preferred die of this invention;

Figure 2 is a side sectional view taken along line 2—2 of Figure 1;

Figure 3 is a perspective view of the die;

Figure 4 is a front view of the die;

Figure 5 is a side sectional view taken along line 5—5 of Figure 4;

Figure 6 shows the layout of the holes of the die;

Figure 7 is a perspective view showing the steaming strands of tobacco-containing material leaving the extruder barrel of Figure 1;

Figure 8 is a perspective view showing a smoking article of this invention;

Figure 9 is an end view of the distal end of the smoking article; and

Figure 10 is a side sectional view taken along line 10—10 of Figure 9.

Detailed description of the invention

The extruded, coherent, multistrand, generally cylindrical smoking article of this invention comprises a plurality of co-extruded strands that are adhered to one another as a result of the co-extrusion process used to make the article or during post-extrusion processing of the extruded strands. The adherence results in the article being "coherent", that is, a unitary structure of strands sufficiently joined to one another rather than being a mere assemblage of separate or insufficiently joined strands. The strands are "co-extruded" in the sense that they exit different holes of the same die, desirably at substantially the same linear velocity as one another. In the preferred embodiment, the strands are randomly adhered to one another leaving randomized pathways along the length of the article.

The configuration of the strands and passageways provides sufficient heat transfer area or sufficient residence time or both for the hot gases drawn towards the proximal end of the smoking article by a smoker to cool and to exit the proximal end at a comfortable temperature for the smoker. By "comfortable temperature" is meant less than 66°C (150°F), usually less than 57°C (135°F), preferably less than 49°C (120°F), and most preferably less than 38°C (100°F).

If the strands are separate or if they are insufficiently joined, strands may move longitudinally and fall out of the smoking article or the strands may move radially and the smoking article may lose its generally cylindrical shape. Furthermore, the random adherence in combination with the proper arrangement of the strands to form the randomized passageways between the strands prevents any extensive channeling of the gas/aerosol drawn by the smoker. Such channeling prevents the gas/aerosol from contacting sufficient surface area and/or from having sufficient residence time in the smoking article to cool the gas/aerosol sufficiently. The "coherent" nature of the multistrand smoking article is such that it has the look and feel of a smoking article (e.g., cigarette) made by a conventional process. The twisting of the coherent strands or rope across the channeling of the smoke through the passageways. This forms a more tortuous path, increasing the path length and increasing the relative RTD.

The tobacco used herein may be any type of tobacco and will generally be comminuted tobacco selected from the group consisting of bright, burley, oriental, and mixtures thereof, comminuted reconstituted tobacco, comminuted stems, tobacco dust or fines, and mixtures thereof. The tobacco may have been previously subjected to a stiffening or expansion process to increase its filling power. The smoking article contains from about 5 wt.% to about 98 wt.% tobacco and preferably from about 25—98 wt.%.

The tobacco is measured on a dry weight basis but in practice may, for example, contain 3 to 20% moisture. Where a dry tobacco dust is used some water may be added to increase the moisture content of the tobacco in order to facilitate mixing of the dry blend. The moisture in the dry blend, whether added or occurring in the constituent materials, is included as part of the water content of the wet blend.

Whatever the source of the tobacco particles, the particles employed in the present invention will have a particle size of up to about 5 mesh (4 mm). Preferably, substantially all the particles will be less than 35 mesh (500 μ m), and more preferably will be less than 50 mesh (300 μ m). When particle sizes greater than 35 mesh are employed, it may be necessary to add a polyfunctional acid, such as citric or phosphoric acid and their ammonium, sodium, and potassium salts, during formation of the wet blend in order to achieve the desired appearance and foaming of the extruded article. The polyfunctional acid or its salts is added in an amount such that the smoking article contains from about 0.1 to about 15 wt.% thereof, preferably from about 2 to about 10 wt.%.

The binder is preferably selected from the group consisting of cellulosic binder, natural binders,

EP 0 167 370 B1

modified natural binders, synthetic binders and mixtures thereof. The cellulosic binder is selected from the group consisting of hydroxypropyl cellulose, carboxymethyl cellulose and its sodium, potassium, and ammonium salts, cross-linked carboxymethyl cellulose and its sodium, potassium, and ammonium salts, hydroxyethyl cellulose, ethyl hydroxyethyl cellulose, hydroxypropyl methyl cellulose, methyl cellulose, ethyl cellulose, and mixtures thereof.

A mixture of carboxymethyl cellulose and hydroxypropyl cellulose is particularly preferred. The cellulosic binder is present in the smoking article in an amount of from 0 to about 40 wt.% and preferably from about 1 to about 30 wt.%.

The natural binders, modified natural binders, and synthetic binders are selected from the group consisting of pectin and its sodium, potassium, and ammonium salts, starch, guar, chitin, chitosan, xanthan, and derivatives thereof (e.g., hydroxypropyl guar), hemicellulose, curdlan, a salt of xanthomonas gum, carageenan, oxycellulose, polyvinyl alcohol, vinyl maleic anhydride polymer, vinyl maleic acid polymer and its sodium, potassium, and ammonium salts, microcrystalline cellulose, dextran, dextrin, fibrous cellulose, and mixtures thereof. The natural, modified natural, and synthetic binders are present in the smoking article in an amount from 0 to about 40 wt.%.

The total amount of binder present in the smoking article is in the range from about 2 to about 40 wt.%. A typical binder combination is 5 wt.% hydroxypropyl cellulose, 2.5 wt.% carboxymethyl cellulose, and 2.5 wt.% starch. Another typical combination is 1 wt.% hydroxypropyl cellulose, 4 wt.% hydroxypropyl guar and 5 wt.% starch.

The article may also include as a filler any particulate material having a particle size of up to about 350 μm that is compatible with the other components of the blend. The filler is preferably selected from the group consisting of calcium carbonate, magnesium carbonate, calcium oxide, magnesium oxide, calcium hydroxide, magnesium hydroxide, metallic aluminum, alumina, hydrated alumina, clay, silica, and mixtures thereof and preferably is calcium carbonate. When the filler is added, it is added in an amount so that it is from about 5 to about 60 wt.% of the smoking article.

The dried or equilibrated smoking article contains from about 5 to about 20 wt.% water calculated as a percentage of the total product weight, which is typically measured as oven volatiles (OV). Preferably, the smoking article remains from about 8 to about 17 wt.% water.

The smoking article has a density of from about 0.05 to about 1.5 g/cc, preferably from about 0.10 to about 1.0 g/cc. The articles comprise a porous structure that permits static burning and the passage of smoke (gas/aerosol) through the article to the smoker. The density of the article is related to the porous structure and the voids created between the strands, and an article having a density within the specified range and having the randomized passageways of this invention provides good burn rate and transmission of smoke to the smoker.

The smoking articles may also include from about 0.001 to about 1 wt.% of an alcohol compatible with the cellulosic binder, that is, an alcohol in which the cellulosic binder is soluble. That alcohol is selected from the group consisting of ethanol, methanol, isopropanol, n-propanol, and mixtures thereof. The alcohol present in the smoking article may result from adding alcohol during the formation of the article to lower the moisture content of the extrudate at the die or may be residual alcohol as a result of adding flavor casings.

The smoking article may also contain from about 0.1 to about 40 wt.%, preferably from about 0.5 to about 20 wt.%, of a cross-linking or stiffening agent. The stiffening agent which is added prior to extrusion and then cross-linked during extrusion is selected from the group consisting of alginic acid, carboxymethyl chitin, pectinic acid, chitosan, carboxymethyl chitosan, water soluble salts thereof, and mixtures thereof. From about 0.1 to 10.0 wt.% of a water soluble salt of calcium, magnesium, and/or aluminium may also be used.

The smoking articles are preferably formed as generally cylindrical, coherent, multistrand articles having a diameter of from about 2 to about 35 mm, preferably from about 4 to about 25 mm. Alternate cross-sectional configurations may be made with an appropriate die, for example, oval, star-shaped, cylindrical, and the like, or shaped appropriately in a post-extrusion process. These rods are typically made in conventional cigarette or cigar lengths and may be wrapped with cigarette paper, a cigar wrapper, or a co-extruded shell of combustible material or the like. The articles may be thus marketed as non-filtered "cigarettes" or as "cigars". A conventional filler may be joined to the "cigarette" by tipping paper to form a filtered smoking article.

Various flavorants and/or humectants that are commonly employed in the manufacture of smoking articles may be added prior to extrusion or may be subsequently added to the extruded article.

The method of the present invention comprises mixing or blending together tobacco particles with binder, filler, cross-linking or stiffening agent, and any other desired ingredient with water to form a wet blend, and extruding the wet blend through a die having a plurality of holes, thereby forming a plurality of strands, the extrusion conditions being such that the moisture in the blend is converted to steam so as to foam each strand as it exits the die of the extruder and the strands adhere to one another when they are twisted together. The strands may also be processed by the application of an adhesive, similar material, or other manufacturing process under conditions that will produce a tacky surface on the individual strands so that the strands will adhere to each other along their outer surfaces.

Mixing of the tobacco, cellulosic binder, filler, water, and other desired ingredients may be carried out

EP 0 167 370 B1

in any conventional mixing device. The resulting mixture is to be a wet blend containing from about 15 to about 50 wt.% of water.

One embodiment of the present invention, Method A, comprises the steps: (a) dry blending tobacco particles with binder, filler, and any other desired ingredient; (b) admixing this dry blend with water to form a wet blend; and (c) extruding the wet blend through a die having a plurality of holes in accordance with the extrusion conditions set forth above so as to foam each strand and adhere the strands to one another.

An alternate and preferred embodiment, Method B, comprises the steps (1) dry blending tobacco particles with filler, and any other desired ingredient, (2) prehydrating the binder material with water to activate the adhesive character of the binder, (3) admixing the dry blend and the prehydrated binder to form a wet blend, and (4) extruding the wet blend through a die having a plurality of holes under the extrusion conditions set forth above so as to foam each strand and adhere the strands to one another.

Referring to Method A, blending in step (a) may be carried out in any conventional mixing device. The dry blend from step (a) is then admixed in step (b) with water to form a wet blend containing from about 15 to about 50 wt.% of water. Step (b) is carried out in a conventional mixing device, such as a horizontal mixing cylinder, and it is preferred to employ a low shear mixing device.

Referring to Method B, step (2), prehydrating the binder and other desired materials with water can be carried out in any conventional mixing device. Similarly, step (1), dry blending of tobacco particles, filler, and other desired materials, can be carried out in any conventional mixing device. Step (3), admixing the prehydrated binder from step (2) and the dry blend from step (1) can also be done in a conventional mixing device. In this context, the resulting wet blend can then be fed to the feed chamber of the extruder as described in greater detail below. In a preferred embodiment, Method B is used in conjunction with a twin screw positive mass displacement extruder having multiple feed ports. Step (2) prehydration is performed by adding the binder materials to a first feed port of the extruder and by adding the water or similar solvent to a second feed port a distance downstream of the first feed port so that as a charge of binder is inserted, it is processed, sheared, and homogenized as it progresses down the extrusion barrels. Then it is admixed with the water as it passes the second port, prehydrating the binder as the materials are displaced down the extruder barrel. Step (1), dry blending the tobacco, filler, and other materials occurs in a conventional mixing device and is added in a blended state to the extruder barrel by a third feed port, a distance downstream of the second port. Thus the prehydrated binder material from step (2) is admixed with the tobacco and other materials from step (1) in a continuous feed process.

The amount of water present in the wet blend is important. If the water content is reduced to less than about 15 wt.%, shear at the die may increase so much that the surface of the extruded product becomes porous and rough and a less than desirable degree of foaming results. At water contents in excess of about 50 wt.% insufficient energy may be supplied to the formulation to generate sufficient foam as the product exits the die. Also, more energy may be required to dry the product to a useable condition or to cause the strands to foam. Too little or too much water also prevents the extruded strands from adhering to one another to the proper degree to form a coherent multistrand article with the desired, preferably randomized, passageways. A post-extrusion drying chamber may be provided for drying the product to the desired temperature and moisture level to achieve the desired porous structure. Preferably, the drying chamber comprises a microwave cavity and the product is exposed to microwaves for an appropriate time to obtain a smoking article having the desired density.

Tobacco particles typically are generally more hygroscopic than binder, absorbing water at a faster rate. Any water absorbed by the tobacco in excess of the desired final moisture content of between 5 and 20 wt.% must be removed, typically by drying, for example, using microwave energy. Further, the lower the moisture content of the resulting extrudate, the easier the extrudate will be to handle and the less energy will be required to dry the extrudate.

In Method A, water is added to a dry blend of binder and tobacco and other materials. In Method B, water is added to the dry binder first, before the bulk, if not all of the tobacco is added. Relatively less water may be required in Method B than in Method A to activate the adhesive character of the binder materials because in Method B, the binder materials may not have to compete with any or any significant amount of tobacco to utilize the water. Thus, Method B is preferred because by prehydrating the binder, the water is delivered to the binder where it is most needed, reducing the overall amount of water required to have the same strength product as obtained by Method A.

A further consequence of prehydration is that because the binder is exposed to most of the water without significant competition, it becomes more fully activated in both quantity and quality than the binder in accordance with Method A. Therefore the amount of binder required to hold the extrudate together may be significantly reduced to achieve the same strength extrudate as found by the application of Method A. Reducing the amount of binder used is not only more economical, but it also enhances the subjective factors of a smoking article, taste, feel, aroma, color, and quality of smoke. The less binder used, the more favorable the subjective factors will be.

Method B prehydration produces a significantly more activated binder material than Method A, and as a result the prehydrated binder is also more viscous. Because some extruder and mixing apparatus cannot generate the forces necessary to process and extrude the smoking article in accordance with this invention by the application of Method B, it may be advantageous to dry blend with the binder a small amount of tobacco particles, preferably an amount less than 5 wt.% of the tobacco, a small amount of filler, or other

EP 0 167 370 B1

added component, and then prehydrate the blended binder and tobacco or other components. The resultant wet blend will have a lower viscosity than if no tobacco or other component were present and may be more easily processed without significantly raising the moisture content of the mass.

Also, because the viscous prehydrated binder can become very sticky and adhere to the mixing equipment, it is advantageous to dry blend with the binder a small amount of tobacco particles, filler material, or both. The amount of tobacco added is preferably less than about 5 wt.% of the tobacco. The dry blend is then prehydrated, resulting in a wet blend that has a reduced tendency to stick to the processing equipment and is relatively easier to process uniformly, as the material progresses from one step to the next.

Alternately, a portion of the binder may be dry blended with the tobacco and the balance of the binder prehydrated. Because of the relative surplus of water (later taken up by the dry blended tobacco and binder), the viscosity will be lower and the mass easier to handle. Although having a somewhat higher moisture content than without cross mixing tobacco and binder in steps (1) and (2), the more efficient activation of the binder results in a dryer and stronger extrudate than that made by the application of Method A.

The wet blend is fed into an extruder and processed as set forth in greater detail below. The extruder may be a single screw cooking extruder, which is a high temperature/short residence time extruder that is essentially an Archimedean pump. That type of extruder has been employed in the food industry. Other suitable extruders are hydraulic piston extruders, ram extruders, extruders employing an extrusion chamber consisting of a male auger and a sleeve which incorporates a female auger, a spacer ring, and a face plate (or die) and extruders employing twin screws having a positive mass displacement extrusion action. It is important that the tobacco particles, the binder, and any additional ingredients be mixed to form a homogeneous mixture prior to extrusion. It may be desired to add water at one or more points along the extruder barrel to control the moisture content of the mass, for example, above 15% OV.

Optionally a foaming agent may be added to the blend in Method A or Method B. The foaming agent is preferably selected from the group consisting of air, nitrogen, carbon dioxide, nitrous oxide, ammonium carbonate, ammonium carbamate, an azide, a hydrazide, pentane, hexane, heptane, a halogenated fluoro-carbon, pyrrole, acetone, ethanol, a peroxide, and azodicarbonamide. Some of these foaming agent may require the addition of an acid or a base for decomposition. The foaming agent will supplement the foaming effect of the water in the wet blend and may allow the use of lower amounts of water. The final product should not contain more than 1 wt.% of residual foaming agent.

The feeding bin is a common starting point for extruder systems. It is usually located near the extruder and its purpose is to provide a continuous source of raw ingredients for the rest of the extruder system. The feeding bin receives material from a conventional mixer/surge system and it usually feeds a variable speed metering/feeding device. A simple gravity bin with bottom discharge may be used as the feeding bin for the ingredients employed in a dry blending step.

Referring to Method A, a variable speed metering/feeding device is usually employed to transport the dry blend from the feeding bin to the extruder. Water may then be added either at the point of entry to the extruder or at one or more locations along the extruder barrel. Vibratory feeders and variable speed screw feeders are two commonly used metering/feeding devices.

An intermediary processing device such as a horizontal mixing cylinder with either a single shaft or twin counter-rotating shafts, may be utilized to admix the water with the dry blend in step (b). Continuous mixing of the dry blend with the water is accomplished in the cylinder, and from this cylinder the wet blend is fed directly into the extruder barrel. Alternately, hydration of the dry blend from step (b) could occur within the extruder barrel by the addition of sufficient water at a controlled rate of feed, correlating with the rate of feed of the dry blend from step (b), either at the point of entry, or downstream of the dry blend feed.

Referring to Method B, when a multiple feed port extruder is selected, each of the mixing steps can be carried out in a separate conventional mixer/surge system having variable speed metering/feeding devices to provide the desired blend to the extruder. For example, in Method B, the binder materials could be mixed at one station and fed to a first port under a controlled rate of feed. At a second station, the tobacco, filler, and other material could be mixed and similarly fed to a second port downstream of the first port, also at a controlled rate of feed. Water could be added in controlled amounts to prehydrate the binder at a location before the tobacco blend material is introduced into the extruder barrel, and added elsewhere if necessary, to control the moisture content.

When a single feed port extruder is available, the binder could be first prehydrated in an intermediary processing device. Then the tobacco, filler, and other materials, having first been dry blended in a separate device are introduced to the intermediary processor for admixture, and the resulting wet blend then fed directly to the extruder barrel.

The extruder barrel may be built in segments or sections, with the individual screws being separated by steam locks. That gives each section its own discrete processing capability. Within the feed zone of the extruder barrel, the raw material exists as discrete particles. As these particles are transported forward in the feed zone, there is a positive pumping action with some compression of the material. This compression pushes the particles together into a more solid homogeneous mass.

As the material advances toward the die and into an additional zone or zones, this compression is continued and the material is subjected to mixing and mild shear, resulting in heating of the mixture until

EP 0 167 370 B1

the particles are transformed into a dough-like mass. There is still a positive pumping effect in these zones that is usually somewhat less positive than the feeding zone.

As the mixture advances toward the final zone before the die, the extruder barrel becomes completely filled with product. Leakage flow and pressure flow are greatest within this final zone, resulting in higher viscous shearing. That yields maximum heat generation. Heat is generated by the particles rubbing against one another and by the relative motion of the mixture against screw and wall surfaces.

The final die has two major functions. The first is to offer resistance to the upward flow of the mixture, thereby creating a condition where leakage flow and pressure flow may occur. The second is to shape the final product. Flow resistance of the die is the greatest factor in the heating of the mixture because the flow resistance has the greatest control over the pressure (and, therefore, the shear) within the barrel. Preferably, the pressure at the inlet of the die is from about 50 to about 2500 psig, (0.35 to 17.25 MPa) more preferably from about 150 to about 1500 psig, (1.04 to 10.35 MPa).

In the process of the present invention, it is preferred to employ a die having a plurality of holes, typically from about 10 to about 30 holes, each ranging in size from about 0.010 inches (.254 mm) to about 0.050 inches (1.27 mm) in diameter. The combination of the number of holes and size of each hole is chosen to give the desired diameter and shape of the smoking article. The holes need not be of the same size or shape. A typical hole pattern will be described below. A die having centrally located holes and an outer annular opening may be used. The material extruded through the annulus will form what may be considered a wrapper for the co-extruded strands.

Typically, foaming of the product occurs immediately after extrusion. Foaming is a result of the moisture, other foaming agent, or gas within the extrudate changing from a super-heated liquid or compressed gas to a gas at essentially atmospheric pressure as the extrudate leaves the high-pressure environment behind the die inside the extruder and enters the atmospheric environment just downstream of the die openings.

The process will be further described with reference to the preferred extruders although other types of extruders may be effectively employed. One preferred extruder is the Wenger Model X20, a six-zone extrusion screw/barrel unit, commercially available from Wenger Manufacturing, Sabetha, Kansas. Various parameters for each zone are set forth in the following table.

Zone	Screw type/Wenger No.	Barrel type/wenger No.
1	Inlet/68638	Inlet/68714
2	Single flight/68327	Straight rib/68318
3	Single flight/68327	Straight rib/68318
4	Double flight/68326	Spiral rib/68372
5	Double flight/68326	Spiral rib/68372
6	Tapered tip/68321 Low	Tapered spiral/68350

Zones 1, 2, and 3 knead the extrusion mixture to develop elasticity and hydrate the gum (binder). Zones 4, 5, and 6 work the mixture by shear. If the Zone 6 screw is not tapered, the mixture will be overworked. The multistrand die is attached to the end of Zone 6.

A 1/8-inch (3.175 mm) thick spacer having an inner diameter equal to that of the Zone 6 barrel is used between the exit of Zone 6 and the die inlet. If a 1/4-inch (6.35 mm) thick spacer is used, some of the mixture tends to collect in the spacer, and collected material will occasionally exit the die in the form of lumps. Furthermore, with the 1/4-inch (6.35 mm) spacer and for the preferred mixture, the extrudate will be underworked, appear wet, and expansion will be insufficient. If no spacer is used, it is possible the extrudate will be overworked and darkened by cooking caused by the overworking, and expansion will be decreased. Thus, there is an optimal range for working of any particular extrusion mixture, outside of which less desirable articles are produced.

The product is transported through the extruder barrel by the extruder screws, complemented by the closure around the screw. The extruder barrel is jacketed, and the jacket is designed for either electrical heating or the circulation of water, steam, or other liquid thermofluid. That permits adjustment of the temperature profile of the extruder barrel by, for example, controlling the flow of cooling water in the jacket. Most of the thermoenergy within the extruder is created by the conversion of the mechanical energy into heat.

For continuous operation it is preferred to establish and maintain a temperature gradient that increases along the length of the extruder barrel. The maximum temperature will be at or just before the die. The temperature gradient will be within the range of from about 10 to about 300°C and preferably from about 50 to about 250°C. Usually, thermocouples are inserted through the head into the flow channel and are connected to either temperature indicators or to automatic temperature control systems.

EP 0 167 370 B1

Each of the six zones of the Wenger X20 unit can be heated or cooled. The temperatures of Zones 1—5 are not critical, and should be high enough for the mixture to flow through the extruder but less than about 230°F (110°C). The temperature of Zone 6 should be between about 160°F (71°C) and 260°F (127°C). With the preferred extrusion mixture described below and when making a cigarette-type smoking article of this invention, the following cooling water exit temperatures have been measured:

Zone	Temperature (°F±10°F)
1	Not measured but <90
2	Not measured but <90
3	90
4	125
5	125
6	180

Turning to the drawings, Figure 1 shows the end of typical extrusion barrel 20 with preferred die 22 having holes 24. (For clarity the barrel is represented schematically and without the jacket, cooling water tubing, thermocouple wires, or the means for removing the head to change the die).

Figure 2 shows screw 28 schematically in barrel 20. Shoulder 26 on die 22 (having internal conical surface 30) mates with a corresponding lip on head 52 and prevents die 22 from being forced out of the head. Spacer 54 lies between head 52 and barrel 20.

Figures 3, 4, and 5 are perspective, end, and side sectional views of die 22, respectively.

Figure 6 shows the layout of holes 24 of preferred die 22 for making cigarettes from the preferred blend. There are twenty-two holes, each 0.033—0.035 inches in diameter. There is one hole in the center, an inner ring of seven holes, and an outer ring of fourteen holes. Angle A is 12°-51', angle B is 25°-43', and angle C is 51°-26'. As will be apparent, these values have been rounded to the nearest minute. The inner ring is offset from (rotated with respect to) the outer ring so that no outer ring holes and either of the two nearest inner ring holes falls on a line with the center hole. That is to prevent any excessive channeling in the final product. The centers of the holes in the inner and outer rings fall on the circumferences of imaginary circles 0.128 inches (3.25 mm) and 0.256 inches (6.5 mm) in diameter, respectively. The center of each imaginary circle is the center of the single central hole of the die, that is, the one central hole, the inner ring, and the outer ring are concentric. The preferred die has a land length (length of holes through the die face) of 1/8 inch (3.175 mm).

In Figure 7, strands 32 of extruded material are shown leaving die 22 through holes 24. Upon leaving the die, the strands expand and then contact and adhere to one another. The moist rope of the adhered strands cools and starts to harden quickly. The rope may be twisted to further increase the tortuosity of the passageways in the article. The rope may be collected on a non-stick surface and then sent to a drier.

Drying may be accomplished in any suitable manner. Microwave heating is preferred because of uniformity in drying along the radial direction. Drying desirably reduced the water content of the rope made by the application of Method A from about 25—35 wt.% at the die exit to about 12—15 wt.%.

In the application of Method B, the water content of the rope of strands is desirably reduced from about 20—35 wt.% at the die exit to about 12—15 wt.%.

After drying, the rope may be wrapped, cut, and tipped with a filter to produce a cigarette as shown in Figure 8. Cigarette 34 comprises tobacco rod 38 and filter 36.

Figure 9 is an end view of tobacco rod 38 of cigarette 34. Passageways 44 lie between strands 32. The circumference of strands 32 is not completely circular because of deformation at the points of contact (and adherence) of the strands to one another.

Because of microvariation in the composition and particle sizes of the mixture exiting each hole of the die and because of microvariations in the pressures just upstream of each die hole, the extruded, foamed strands in the preferred embodiment have generally smooth but slightly irregular surfaces. The irregularity is typically random and a principal cause of the randomness of contact of adjacent strands. Normally, the contact occurs almost immediately after the strands leave the die, and because of the tackiness of the material, adherence is immediate upon contact. If the strands do not expand sufficiently (e.g., because of over- or underworking or too much or too little water) or if the material does not have sufficient tackiness (e.g., because the strands are too dry, too cold, or the binder is not satisfactory), the desired contact and adherence will not occur and the article will not have the desired network of passageways without post-extrusion processing.

The holes of the die should not be too far apart, otherwise the extruded strands will not be able to contact one another soon enough after leaving the die for sufficient adherence to occur. If the velocity of the exiting strands is too high, the strands may cool too much before they can contact and adhere

EP 0 167 370 B1

sufficiently to one another. Also, the linear velocity of the strands exiting the die should be substantially uniform so that there is as little linear motion of the strands with respect to one another as possible. To achieve this uniform velocity may require the die having holes of different sizes, depending on the particular extruder used and its particular pressure profile just upstream of the die.

5 In accordance with the post-extrusion processing of the strands, the spacing of the holes and the temperature of the strands as extruded may be less important for causing the strands to adhere to each other because heat sufficient to cause the strands to become tacky and adhere is imparted to the product while it is heated in the drying chamber or, in other circumstances, an adhesive or other manufacturing condition is applied to cause the adjacent strands to adhere to one another.

10 Figure 10 is an enlarged view of a portion of tobacco rod 38 having wrapping paper 40, coal 42, and passageways 44. Arrow 48 indicates the flow of smoke to the end of the cigarette proximal to the smoker. When that smoke reaches an area of adherence 46 of one strand to another, the smoke finds passageway 44 blocked and may travel towards the smoker as indicated by arrows 50.

15 **Example I**

To illustrate preparation of smoking articles within this invention, the preferred extruding composition was prepared and extruded in accordance with Method A. That composition was made by first dry blending

20	90 wt.%	Tobacco dust
	5 wt.%	Hydroxypropyl cellulose (Klucel® HF from Hercules, Inc.)
	2.5 wt.%	Carboxymethyl cellulose (CMC 7 HF from Hercules, Inc.)
25	2.5%	Starch (Lincoln pre-gelatinized corn cereal binder #201F from Lincoln Grain, Inc. in Atchison, Kansas)

30 and loading that mixture into the feed hopper of a preferred extruder, the Wenger X20 unit described above. The tobacco dust was a mixture of burley, bright, and oriental tobacco particles, essentially all of which were less than 80 mesh in size.

The extruder feeder speed was set at 10 rpm, which corresponds to about 136 pounds per hour of dry mixture, and the mixing cylinder speed was set at 300 rpm. To show the effect on product properties of the amount of water used in making the wet blend, the effect of extruder barrel temperature, and the effect of 35 variations in extruder speed (working of the mixture), comparative runs were also performed. In all runs the Wenger X20 unit, the preferred die, and a 1/8 inch spacer between Zone 6 and the die were used.

The extruded ropes (if formed) were dried, wrapped (if possible), cut to rods 63 mm in length, and joined to a filter (if possible). The run conditions and results are shown in the table below.

40

45

50

55

60

65

EP 0 167 370 B1

TABLE I

Run	591	591A	591B	591C	591D	591E	591F	591G	591H
5	Temperature (°F)								
	121	108	108	101	101	101	111	105	100
	—Zone 2								
	129	125	140	142	142	142	143	143	143
	—Zone 3								
	104	104	102	107	107	107	106	106	106
	—Zone 4								
	190	192	194	181	181	181	180	184	184
	—Zone 5								
10	Water feed								
	57.5	54	50	74	70	68	65	62	60
	—rotameter								
	32.0	34.5	28.0	45.0	42.0	41.0	39.0	35.5	34.0
	—lbs/hr.								
15	Extruder								
	400	400	400	400	400	400	400	400	400
	—rpm								
	20	20	20	19	19	19	19	19	19
	—amps								
20	Moisture of extruder feed (% OV)								
	28.4	27.9	—	—	—	—	36.5	32.0	29.6
	Rope at die exit								
	129	126	—	—	—	—	132	135	132
	—lbs/hr								
	28.8	26.6	—	—	—	—	32.3	31.7	30.0
	—moisture (% OV)								
25	8.3	8.0	—	—	—	—	—	—	8.4
	—diameter (mm)								
	Yes	Yes	No	No	Some	Some	Yes	Yes	Yes
	—strands adhere?								
	Yes	Yes	Yes	Some	Some	Some	Some	Some	Yes
	—strands expand?								
	Dried product								
30	0.932	0.950	—	—	—	—	—	0.988	1.069
	—weight (g)								
	25.1	23.29	—	—	—	—	—	23.33	24.91
	—circum. (mm)								
	—RTD with filter								
	ca. 4.0	ca. 4.0	—	—	—	—	—	—	—
	(inches water)								
	Yes	Yes	—	—	—	—	Yes	Yes	Yes
	—acceptable?								
35									
40									
45									
50									
55									
60									
65									

EP 0 167 370 B1

TABLE I (cont'd)

Run	591I	591J	591K	591L	591M	591N	591O	591P
5	Temperature (°F)							
	114	116	116	102	123	138	117	113
	141	147	150	130	131	144	138	136
	109	112	116	105	104	113	109	110
	194	201	207	188	180	199	225	ca. 245
10	Water feed							
	58	58	58	58	58	58	58	58
	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5
15	Extruder							
	400	450	570	350	300	500	400	400
	20	20	—	20	20	19	20	20
20	Moisture of extruder feed (% OV)							
	35.5	—	—	—	—	—	—	30.3
	Rope at die exit		NP*					
	126	126	—	129	129	—	—	—
	29.0	—	—	—	—	—	29.7	—
25	—diameter (mm)							
	8.5	8.5	—	8.5	8.3	—	8.3	7.6
	—strands adhere?							
	Yes	Yes	—	Yes	Yes	No	Yes	Yes
	—strands expand?							
	Yes	Yes	—	Yes	Yes	—	Yes	Some
30	Dried product							
	0.977	0.959	—	1.053	1.077	—	0.948	0.887
	23.38	23.61	—	24.18	23.98	—	23.23	22.23
	—RTD with filter (inches water)							
	—	—	—	—	—	—	—	—
	—acceptable?							
	Yes	Yes	—	Yes	Yes	No	Yes	Yes

*"NP" means no product — insufficient flow of material from mixer to extruder.

Runs 591 and 591A—I show that either too much (591C, D, E) or too little water (591B) in the mixture in the die feed results in poor expansion and/or poor adhesion of the extruded strands. Comparison of Runs 591 and 591J—N show that too much working (591K) of the mixture in the extruder prevents proper expansion and/or adhesion of the strands.

A more preferred extruder is the commercially available Baker-Perkins Twin Screw extruder, Model No. MPF50D (or MPF50L). Baker-Perkins is located in Raleigh, North Carolina.

Example II

The following examples were extruded in a Baker-Perkins twin screw extruder, Model MPF-50D, having a 1263.6 mm long extrusion chamber, wherein the two screws had the same assemblage of components, as follows:

EP 0 167 370 B1

Screw assembly

	Length	Elements
5	6.325 mm	Spacer
	508 mm	Spacer
	152.4 mm	Feed screw
	63.5 mm	Five 45° forwarding paddles
	50.8 mm	Short pitch feed screw
10	177.8 mm	Feed screw
	12.7 mm	One paddle
	50.8 mm	Single lead screw
	63.5 mm	Five 45° forwarding paddles
	6.35 mm	One orifice plug
15	50.8 mm	Single lead screw
	6.35 mm	One paddle
	101.6 mm	Single lead
	multihole die	22 holes about .889 mm diameter in a die face about 25.4 mm in diameter

20

The screws were rotated so as to be 90° out of phase to prevent interfering with each other and to provide a tolerance between the screws of about 50/64 mm. The Baker-Perkins extruder has multiple feed ports along its length so auxiliary mixing equipment was not required as it was the case in the Wenger extruder. The binder was added at a distance 15:1 length:diameter ("L/D") screw length measured from the extrusion end (die), the water used to prehydrate the binder was added at a distance 12:1 (L/D) from the die, and the tobacco dust was added at a distance 10:1 (L/D) from the die. The binder mixture used consisted of the following blend:

25

	1 part	Hydroxypropyl cellulose (Klucel-H® from Hercules, Inc.)
30	4 parts	Hydroxypropyl guar (Galaxy 781® from Henkel Corp.)
	5 parts	Starch

The results of the various extrusions are set forth in Table II below.

The products of runs c, d, and e, made in accordance with Method B prehydration of binder technique, were much stronger and better in appearance than the product made by the non-prehydrated Method A, run a, even though they contained a significantly lesser amount of binder. In addition, using Method B and prehydrating the binder allowed for the extrusion of a drier extrudate by using a lesser amount of water. Run "a", made in accordance with Method A, could not produce a satisfactory product with a lesser amount of water or a lesser amount of binder than used in example.

40

45

50

55

60

65

EP 0 167 370 B1

TABLE II

Run	Screw speed (RPM)	Wt.% of binder	Feed rate of binder (Kg/min)	Feed rate of water (Kg/min)	Feed rate of tobacco dust (Kg/min)	OV in mixing chamber (%)****	OV of extrudate (%)	Weight of extrudate/ 63 mm
a*	490	12.7***	.1134	.2077	.816	28.4	18.7	1177
b*	490	10***	.0907	.2077	.816	28.4	**	**
c	490	10	.0907	.1837	.816	26.8	16.3	1241
d	490	9.1	.0816	.1700	.816	25.9	15.9	1251
e	490	8.2	.0816	.2009	.816	28.0	17.2	1204

* Runs a and b are the controls and were made in accordance with Method A, adding the tobacco and the binder blend to the extruder at the 15:1 L/D position and adding the water at the 12:1 L/D position (the same location as per examples c, d and e, made in accordance with Method B where the water was added to the binder blend in the prehydration mode).

** The amount of binder used in this run did not yield a strong enough product to collect for testing at these particular extrusion conditions.

*** The amount of binder used represents the minimum amount of binder that could be used to produce an acceptable result.

**** The OV values in the mixing chamber were calculated based on pump feed rates of the materials.

Claims

1. A method of making a foamed, extruded, tobacco-containing smoking article comprising forming a wet blend containing 15% to 50% of water and the remainder, on a dry weight basis, comprising 5 to 98 weight % of tobacco particles having a particle size up to 4 mm, (5 mesh), from 0 to 60 weight % of a filler having a particle size of not more than 350 μm , and from 2 to 40 wt. % of a binder from the group consisting of cellulosic binders, natural binders, modified natural binders, synthetic binders, and mixtures thereof, extruding the wet blend through a die having a plurality of holes to form a plurality of strands and twisting the extruded strands together, the strands being foamed by the conversion of some of the moisture to steam and adhered together to form a smoking article.

2. A method as claimed in claim 1 further comprising adhering the strands to each other by applying a material to the individual strands to produce a tacky surface on the strands before they are brought into contact.

3. A method as claimed in any of the preceding claims in which the filler is selected from the group consisting of calcium carbonate, magnesium carbonate, calcium oxide, magnesium oxide, calcium hydroxide, magnesium hydroxide, metallic aluminium, alumina, hydrated alumina, clay, silica, diatomaceous earth, and mixtures thereof.

4. A method as claimed in any of the preceding claims in which the binder is a cellulosic binder selected from the group consisting of hydroxypropyl cellulose, carboxymethyl cellulose and its ammonium, sodium, and potassium salts, cross-linked carboxymethyl cellulose and its ammonium, sodium, and potassium, salts, hydroxyethyl cellulose, ethyl hydroxyethyl cellulose, hydroxypropyl methyl cellulose, methyl cellulose, ethyl cellulose, and mixtures thereof.

5. A method as claimed in any of claims 1 to 3 in which the natural binders, modified natural binders, or synthetic binders are selected from the group consisting of pectin and its sodium, potassium, and ammonium salts, starch, guar and derivatives thereof, hemicellulose, xanthan, curdlan, a salt of xanthomonas gum, carageenan, alginic acid and its ammonium, sodium, and potassium salts, oxycellulose, polyvinyl alcohol, vinyl maleic anhydride polymer, vinyl maleic acid polymer and its sodium, potassium, and ammonium salts, microcrystalline cellulose, dextran, dextrin, fibrous cellulose, and mixtures thereof.

6. A method as claimed in any of the preceding claims in which from 0.1 to 15 wt.%, on a dry weight basis, of a polyfunctional acid or its ammonium, sodium or potassium salts is included in the wet blend.

7. A method as claimed in claim 6 in which the polyfunctional acid is citric acid.

8. A method as claimed in claim 6 in which the polyfunctional acid is phosphoric acid.

9. A method as claimed in any of the preceding claims in which from 0.1 to 40 wt.% on a dry weight basis of a cross-linking or stiffening agent selected from the group consisting of alginic acid, carboxymethyl chitin, pectinic acid, chitosan, water soluble salts thereof, and mixture thereof, is included in the wet blend.

EP 0 167 370 B1

10. A method as claimed in any of the preceding claims wherein from 2 to 40 wt.% on a dry weight basis of an alcohol selected from the group consisting of ethanol, methanol, isopropanol, n-propanol, and mixtures thereof is included in the wet blend.

11. A method as claimed in any of the preceding claims in which the tobacco particles comprise
5 between 50 and 98% of the dry mixture.

12. A method as claimed in any of the preceding claims in which the binder is pre-hydrated by admixture with water before being mixed with the other constituents of the mixture to form the wet blend.

13. A method as claimed in claim 12 in which a part of the binder is mixed dry with the other constituents and only the remaining part is pre-hydrated, thereby reducing the viscosity of the
10 pre-hydrated binder and reducing its tendency to stick to the processing equipment.

14. A method as claimed in claim 12 or 13 in which up to 5.0 wt.% of the tobacco particles is added to the binder to be pre-hydrated.

15. A foamed, extruded, tobacco-containing, smoking article comprising a plurality of co-extruded strands twisted together that extend generally along the longitude of the smoking article and are adhered
15 to one another so as to leave tortuous flow passageways between the strands, which passageways extend generally along the longitude of the smoking article, the smoking article also comprising on a dry weight basis (a) from 5 to 98 wt.% of tobacco particles having a particle size of up to about 4 mm (5 mesh), (b) from 0 to 60 wt.% of a filler having a particle size of up to about 350 µm, and (c) from about 2 to 40 wt.% of a binder selected from the group consisting of cellulosic binders, natural binders, modified natural binders,
20 synthetic binders, and mixtures thereof, and further comprising (d) from about 5 to about 20 wt.% water calculated as a percentage of the total product weight, the article having a density within the range of from about 0.05 to about 1.5 g/cc.

16. The smoking article of claim 15 wherein the filler is selected from the group consisting of calcium carbonate, magnesium carbonate, calcium oxide, magnesium oxide, calcium hydroxide, magnesium
25 hydroxide, metallic aluminium, alumina, hydrated alumina, clay, silica, diatomaceous earth and mixtures thereof.

17. The smoking article of claim 15 or 16 wherein the cellulosic binder included in the mixture in an amount from about 0 to about 40 wt.% is selected from the group consisting of hydroxypropyl cellulose, carboxymethyl cellulose and its ammonium, sodium, and potassium salts, cross-linked carboxymethyl
30 cellulose and its ammonium, sodium, and potassium salts, hydroxyethyl cellulose, ethyl hydroxyethyl cellulose, hydroxypropyl methyl cellulose, methyl cellulose, ethyl cellulose, and mixtures thereof.

18. The smoking article of any of claims 15 to 17 wherein the natural binders, modified natural binders, and synthetic binders included in the mixture in an amount from 0 to about 40 wt.% are selected from the group consisting of pectin and its sodium, potassium, and ammonium salts, starch, guar and derivatives
35 thereof, hemicellulose, xanthan, curdlan, a salt of xanthomonas gum, carageenan, alginic acid and its ammonium, sodium, and potassium salts, oxycellulose, polyvinyl alcohol, vinyl maleic anhydride polymer, vinyl maleic acid polymer and its sodium, potassium, and ammonium salts, microcrystalline cellulose, dextran, dextrin, fibrous cellulose, and mixtures thereof.

19. The smoking article of any of claims 15 to 18 further comprising from about 0.1 to about 15 wt.% of
40 a polyfunctional acid or its ammonium, sodium, and potassium salts.

20. The smoking article of claim 19 wherein the polyfunctional acid is citric acid or a citrate.

21. The smoking article of claim 19 wherein the polyfunctional acid is phosphoric acid or a phosphate.

22. The smoking article of any of claims 15 to 21 further comprising from about 0.1 to about 40 wt.% of
45 a cross-linking or stiffening agent selected from the group consisting of alginic acid, carboxymethyl chitin, pectinic acid, chitosan, water soluble salts thereof, and mixtures thereof.

23. The smoking article of any of claims 15 to 22 wherein the tobacco particles comprise about 25 to about 98 wt.% of the article.

24. The smoking article of any of claims 15 to 23 comprising in addition up to 1 wt.% of a residual
50 foaming agent other than water.

Patentansprüche

1. Verfahren zur Herstellung eines geschäumten extrudierten, tabakhaltigen Rauchartikels, welches das Bilden einer nassen Mischung mit 15% bis 50% Wasser, wobei der Rest, auf Trockengewichtsbasis, 5
55 bis 98 Gew.-% Tabakteilchen mit einer Teilchengröße bis zu 4 mm (5 mesh), 0 bis 60 Gew.-% eines Füllstoffs mit einer Teilchengröße von nicht mehr als 350 µm, und 2 bis 40 Gew.-% eines Bindemittels aus der aus Bindemitteln auf Cellulosebasis, natürlichen Bindemitteln, modifizierten natürlichen Bindemitteln, synthetischen Bindemitteln und Mischungen davon bestehenden Gruppe umfaßt, das Extrudieren der nassen Mischung durch eine Düse mit einer Vielzahl von Löchern unter Bildung einer Vielzahl von Strängen
60 und das Zusammendrehen der extrudierten Stränge umfaßt, wobei die Stränge durch die Umwandlung von einiger Feuchtigkeit in Dampf unter Bildung eines Rauchartikels geschäumt und zusammengeklebt werden.

2. Verfahren, wie in Anspruch 1 beansprucht, welches weiterhin das Aneinanderkleben der Stränge durch Anwenden eines Materials auf die einzelnen Stränge unter Bildung einer klebrigen Oberfläche auf
65 den Strängen umfaßt, bevor diese in Berührung gebracht werden.

EP 0 167 370 B1

3. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin der Füllstoff aus der aus Calciumcarbonat, Magnesiumcarbonat, Calciumoxid, Magnesiumoxid, Calciumhydroxid, Magnesiumhydroxid, metallischem Aluminium, Aluminiumoxid, hydratisiertem Aluminiumoxid, Tonerde, Siliciumdioxid, Diatomeenerde und Mischungen davon bestehenden Gruppe ausgewählt wird.
4. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin das Bindemittel ein Bindemittel auf Cellulosebasis ist, das aus der aus Hydroxypropylcellulose, Carboxymethylcellulose und ihren Ammonium-, Natrium- und Kaliumsalzen, vernetzter Carboxymethylcellulose und ihren Ammonium-, Natrium- und Kaliumsalzen, Hydroxyethylcellulose, Ethylhydroxyethylcellulose, Hydroxypropylcellulose, Methylcellulose, Ethylcellulose und Mischungen davon bestehenden Gruppe ausgewählt wird.
5. Verfahren wie in einem der Ansprüche 1 bis 3 beansprucht, worin die natürlichen Bindemittel, modifizierten natürlichen Bindemittel oder synthetischen Bindemittel aus der aus Pektin und seinen Natrium-, Kalium- und Ammoniumsalzen, Stärke, Guar und seinen Derivaten, Hemicellulose, Xanthan, Curdlan, einem Salz von Xanthomonasgummi, Carageenen, Alginsäure und ihren Ammonium-, Natrium- und Kaliumsalzen, Oxycellulose, Polyvinylalkohol, Vinyl-Maleinsäureanhydrid Polymer, Vinyl-Maleinsäure-Polymer und seinen Natrium-, Kalium- und Ammoniumsalzen, mikrokristalliner Cellulose, Dextran, Dextrin, faserförmiger Cellulose und Mischungen davon bestehenden Gruppe ausgewählt werden.
6. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin 0,1 bis 15 Gew.-% (Trockengewichtsbasis) einer polyfunktionellen Säure oder ihre Ammonium-, Natrium- oder Kaliumsalze in die nasse Mischung einbezogen werden.
7. Verfahren, wie in Anspruch 6 beansprucht, worin die polyfunktionelle Säure Zitronensäure ist.
8. Verfahren, wie in Anspruch 6 beansprucht, worin die polyfunktionelle Säure Phosphorsäure ist.
9. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin 0,1 bis 40 Gew.-%, auf Trockengewichtsbasis, eines Vernetzungs- oder Versteifungsmittels, ausgewählt aus der aus Alginsäure, Carboxymethylchitin, Pektinsäure, Chitosan, wasserlöslichen Salzen davon und Mischungen davon bestehenden Gruppe, in die nasse Mischung einbezogen werden.
10. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin 2 bis 40 Gew.-%, auf Trockengewichtsbasis, eines Alkohols, ausgewählt aus der aus Ethanol, Methanol, Isopropanol, n-Propanol und Mischungen davon bestehenden Gruppe, in die nasse Mischung einbezogen werden.
11. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin die Tabakteilchen zwischen 50 und 98% der trockenen Mischung ausmachen.
12. Verfahren, wie in einem der vorstehenden Ansprüche beansprucht, worin das Bindemittel durch Zumischen von Wasser vorhydratisiert wird, bevor es mit den anderen Bestandteilen der Mischung unter Bildung der nassen Mischung gemischt wird.
13. Verfahren, wie in Anspruch 12 beansprucht, worin ein Teil des Bindemittels trocken mit den anderen Bestandteilen gemischt wird und nur der verbleibende Teil vorhydratisiert wird, wodurch die Viskosität des vorhydratisierten Bindemittels erniedrigt wird und seine Neigung, an der Verarbeitungseinrichtung haften zu bleiben, vermindert wird.
14. Verfahren, wie in Anspruch 12 oder 13 beansprucht, worin bis zu 5 Gew.-% der Tabakteilchen dem vorzhydratisierenden Bindemittel zugefügt werden.
15. Geschäumter, extrudierter, tabakhaltiger Rauchartikel, der eine Vielzahl von vorextrudierten, zusammengedrehten Strängen aufweist, die sich im allgemeinen über die Länge des Räuchartikels erstrecken und aneinandergeliebt sind, so daß gewundene Strömungswege zwischen den Strängen bleiben, welche Strömungswege sich im allgemeinen über die Länge des Rauchartikels erstrecken, wobei der Rauchartikel weiterhin auf Trockengewichtsbasis (a) 5 bis 98 Gew.-% Tabkteilchen mit einer Teilchengröße von bis zu etwa 4 mm (5 mesh), (b) 0 bis 60 Gew.-% eines Füllstoffs mit einer Teilchengröße von bis zu etwa 350 µm und (c) etwa 2 bis 40 Gew.-% eines Bindemittels, ausgewählt aus der aus Bindemitteln auf Cellulosebasis, natürlichen Bindemitteln, modifizierten natürlichen Bindemitteln, synthetischen Bindemitteln und Mischungen davon bestehenden Gruppe umfaßt, sowie weiterhin (d) etwa 5 bis etwa 20 Gew.-% Wasser, berechnet als Prozentanteil des gesamten Produktgewichts, und der Artikel eine Dichte im Bereich von etwa 0,05 bis 1,5 g/cm³ aufweist.
16. Rauchartikel nach Anspruch 15, worin der Füllstoff aus der aus Calciumcarbonat, Magnesiumcarbonat, Calciumoxid, magnesiumoxid, Calciumhydroxid, Magnesiumhydroxid, metallischem Aluminium, Aluminiumoxid, hydratisiertem Aluminiumoxid, Tonerde, Siliciumdioxid, Diatomeenerde und Mischungen davon bestehenden Gruppe ausgewählt ist.
17. Rauchartikel nach Anspruch 15 oder 16, worin das in der Mischung in einer Menge von etwa 0 bis etwa 40 Gew.-% enthaltene Bindemittel auf Cellulosebasis aus der aus Hydroxypropylcellulose, Carboxymethylcellulose und ihren Ammonium-, Natrium- und Kaliumsalzen, vernetzter Carboxymethylcellulose und ihren Ammonium-, Natrium- und Kaliumsalzen, Hydroxyethylcellulose, Ethylhydroxyethylcellulose, Hydroxypropylmethylcellulose, Methylcellulose, Ethylcellulose und Mischungen davon bestehenden Gruppe ausgewählt ist.
18. Rauchartikel nach einem der Ansprüche 15 bis 17, worin die in der Mischung in einer Menge von 0 bis etwa 40 Gew.-% enthaltenen natürlichen Bindemittel, modifizierten natürlichen Bindemittel und synthetischen Bindemittel aus der aus Pectin und seinen Natrium-, Kalium- und Ammoniumsalzen, Stärke, Guar und seinen Derivaten, Hemicellulose, Xanthan, Curdlan, einem Salz von Xanthomonasgummi, Carageen, Alginsäure und ihren Ammonium-, Natrium- und Kaliumsalzen, Oxycellulose, Polyvinylalkohol,

EP 0 167 370 B1

Vinylmaleinsäureanhydrid-Polymer, Vinylmaleinsäurepolymer und seinen Natrium-, Kalium- und Ammoniumsalzen, mikrokristalliner Cellulose, Dextran, Dextrin, faserförmiger Cellulose und Mischungen davon bestehenden Gruppe ausgewählt ist.

19. Rauchartikel nach einem der Ansprüche 15 bis 18, welcher weiterhin etwa 0,1 bis etwa 5 Gew.-% einer polyfunktionellen Säure oder ihrer Ammonium-, Natrium- und Kaliumsalze umfaßt.

20. Rauchartikel nach Anspruch 19, worin die polyfunktionelle Säure Zitronensäure oder ein Citrat ist.

21. Rauchartikel nach Anspruch 19, worin die polyfunktionelle Säure Phosphorsäure oder ein Phosphat ist.

22. Rauchartikel nach einem der Ansprüche 15 bis 21, welcher weiterhin etwa 0,1 bis etwa 40 Gew.-% eines Vernetzungs- oder Versteifungsmittels, ausgewählt aus der aus Alginsäure, Carboxymethylchitin, Pectinsäure, Chitosan, wasserlöslichen Salzen davon sowie Mischungen davon bestehenden Gruppe, umfaßt.

23. Rauchartikel nach einem der Ansprüche 15 bis 22, worin die Tabakteilchen etwa 25 bis etwa 28% des Artikels ausmachen.

24. Rauchartikel nach einem der Ansprüche 15 bis 23, welcher zusätzlich bis zu 1 Gew.-% eines von Wasser verschiedenen residualen Schäumungsmittels umfaßt.

Revendications

1. Procédé de fabrication d'un article à fumer contenant du tabac, venu d'extrusion et expansé en mousse, dans lequel on forme un mélange humide contenant de 15% à 50% d'eau, le reste comprenant, par rapport au poids à sec, de 5 à 98% en poids de particules de tabac ayant une taille particulière allant jusqu'à 4 mm, de 0 à 60% en poids d'une charge ayant une taille particulière non supérieure à 350 µm, et de 2 à 40% en poids d'un liant choisi parmi les liants cellulotiques, les liants naturels, les liants naturels modifiés, les liants synthétiques et les mélanges de ceux-ci; on extrude le mélange humide à travers une filière comportant plusieurs orifices, pour former plusieurs cordons, et on retord ensemble les cordons venus d'extrusion, les cordons étant expansés en mousse sous l'effet de la conversion en vapeur d'une partie de l'humidité, et ils adhèrent ensemble pour former un article à fumer.

2. Procédé selon la revendication 1 dans lequel on fait en outre adhérer les cordons entre eux, en appliquant un matériau sur chaque cordon, pour procurer une surface adhésive sur les cordons, avant qu'ils ne rentrent en contact entre eux.

3. Procédé selon l'une quelconque des revendications précédentes, dans lequel la charge est choisie parmi le carbonate de calcium, le carbonate de magnésium, l'oxyde de calcium, l'oxyde de magnésium, l'hydroxyde de calcium, l'hydroxyde de magnésium, l'aluminium métallique, l'alumine, l'alumine hydratée, l'argile, la silice, la terre de diatomées, et les mélanges de ceux-ci.

4. Procédé selon l'une quelconque des revendications précédentes, dans lequel le liant, consiste en un liant cellulotique choisie parmi l'hydroxypropyl cellulose, la carboxyméthyl cellulose et ses sels d'ammonium, de sodium et de potassium, la carboxyméthyl cellulose réticulée et ses sels d'ammonium, de sodium et de potassium, l'hydroxyéthyl cellulose, l'éthyl hydroxyéthyl cellulose, l'hydroxypropyl méthyl cellulose, la méthyl cellulose, l'éthyl cellulose et les mélanges de ceux-ci.

5. Procédé selon l'une quelconque des revendications 1 à 3, dans lequel les liants naturels, les liants naturels modifiés ou les liants synthétiques sont choisis parmi la pectine et ses sels de sodium, de potassium et d'ammonium, l'amidon, le guar et ses dérivés, l'hémicellulose, le xanthane, le curdian, un sel de gomme de xanthomonas, la caragénine, l'acide alginique et ses sels d'ammonium, de sodium et de potassium, l'oxycellulose, un alcool polyvinylique, un polymère d'anhydride vinyl maléique, un polymère d'acide vinyl maléique et ses sels de sodium, de potassium et d'ammonium, la cellulose microcristalline, le dextrane, la dextrine, la cellulose fibreuse et les mélanges de ceux-ci.

6. Procédé selon l'une quelconque des revendications précédentes, dans lequel on incorpore dans le mélange humide, de 0,1 à 15% en poids, par rapport au poids à sec, d'un acide polyfonctionnel ou de son sel d'ammonium, de sodium ou de potassium.

7. Procédé selon la revendication 6, dans lequel l'acide polyfonctionnel, est l'acide citrique.

8. Procédé selon la revendication 6, dans lequel l'acide polyfonctionnel, est l'acide phosphorique.

9. Procédé selon l'une quelconque des revendications précédentes, dans lequel on incorpore dans le mélange humide, de 0,1 à 40% en poids, par rapport au poids à sec, d'un agent réticulant ou rigidifiant, choisi parmi l'acide alginique, la carboxyméthyl chitine, l'acide pectinique, le chitosane, leurs sels solubles dans l'eau, et les mélanges de ceux-ci.

10. Procédé selon l'une quelconque des revendications précédentes, dans lequel on incorpore dans le mélange humide, de 2 à 40% en poids, par rapport au poids à sec, d'un alcool choisi parmi l'éthanol, le méthanol, l'isopropanol, le n-propanol et les mélanges de ceux-ci.

11. Procédé selon l'une quelconque des revendications précédentes, dans lequel les particules de tabac, représentent de 50 à 98% du mélange sec.

12. Procédé selon l'une quelconque des revendications précédentes, dans lequel le liant est préhydraté, en le mélangeant avec de l'eau avant de le mélanger avec les autres constituants du mélange, pour former le mélange humide.

13. Procédé selon la revendication 12, dans lequel on mélange une partie du liant, avec les autres

EP 0 167 370 B1

constituants, et dans lequel on préhydrate seulement la partie restante, de façon à réduire ainsi la viscosité du liant préhydraté et à réduire sa tendance à adhérer sur le dispositif de traitement.

14. Procédé selon la revendication 12 ou 13, dans lequel on ajoute jusqu'à 5,0% en poids de particules de tabac, dans le liant destiné à être préhydraté.

5 15. Article à fumer contenant du tabac, venu d'extrusion est expansé en mousse, comprenant plusieurs cordons co-extrudés, retordus ensemble en s'étendant à peu près selon la longueur de l'article à fumer et adhérent entre eux en ménageant des conduits d'écoulement tortueux entre les cordons, ces conduits s'étendant à peu près selon la longueur de l'article à fumer, l'article à fumer comprenant également, par rapport au poids à sec, (a) de 5 à 98% en poids de particules de tabac ayant une taille particulière allant jusqu'à environ 4 mm, (b) de 0 à 60% en poids d'une charge ayant une taille particulière allant jusqu'à
10 environ 350 µm, et (c) de 2 à 40% en poids d'un liant choisi parmi les liants cellulosiques, les liants naturels, les liants naturels modifiés, les liants synthétiques et les mélanges de ceux-ci, et il comprend en outre (d) d'environ 5 à environ 20% en poids d'eau, par rapport au poids total du produit, l'article ayant une masse volumique d'environ 0,05 à environ 1,5 g/cm³.

15 16. Article à fumer selon la revendication 15, dans lequel la charge est choisie parmi le carbonate de calcium, le carbonate de magnésium, l'oxyde de calcium, l'oxyde de magnésium, l'hydroxyde de calcium, l'hydroxyde de magnésium, l'aluminium métallique, l'alumine, l'alumine hydratée, l'argile, la silice, la terre de diatomées et les mélanges de ceux-ci.

17. Article à fumer selon la revendication 15 ou 16, dans lequel le liant incorporé dans le mélange selon
20 une quantité d'environ 0 à environ 40% en poids, est choisi parmi l'hydroxypropyl cellulose, la carboxyméthyl cellulose et ses sels d'ammonium, de sodium et de potassium, la carboxyméthyl cellulose réticulée et ses sels d'ammonium, de sodium et de potassium, l'hydroxyéthyl cellulose, l'éthyl hydroxyéthyl cellulose, l'hydroxypropyl méthyl cellulose, la méthyl cellulose, l'éthyl cellulose et les mélanges de ceux-ci.

25 18. Article à fumer selon l'une quelconque des revendications 15 à 17, dans lequel les liants naturels, les liants naturels modifiés et les liants synthétiques, incorporés dans le mélange selon une quantité de 0 à environ 40% en poids, sont choisis parmi la pectine et ses sels de sodium, de potassium et d'ammonium, l'amidon, le guar et ses dérivés, l'hémicellulose, le xanthane, le curdlan, un sel de gomme de xanthomonas, la caragénine, l'acide alginique et ses sels d'ammonium, de sodium et de potassium, l'oxycellulose, un
30 alcool polyvinylique, un polymère d'anhydride vinyl maléique, un polymère d'acide vinyul maléique et ses sels de sodium, de potassium et d'ammonium, la cellulose microcristalline, le dextrane, la dextrine, la cellulose fibreuse et les mélanges de ceux-ci.

19. Article à fumer selon l'une quelconque des revendications 15 à 18, comprenant en outre d'environ 0,1 à environ 15% en poids d'un acide polyfonctionnel ou de son sel d'ammonium, de sodium ou de
35 potassium.

20. Article à fumer selon la revendication 19, dans lequel l'acide polyfonctionnel, est l'acide citrique ou un citrate.

21. Article à fumer selon la revendication 19, dans lequel l'acide polyfonctionnel, est l'acide phosphorique ou un phosphate.

40 22. Article à fumer selon l'une quelconque des revendications 15 à 21, comprenant en outre d'environ 0,1 à environ 40% en poids d'un agent réticulant ou rigidifiant, choisi parmi l'acide alginique, la carboxyméthyl chitine, l'acide pectinique, le chitosane, ses sels solubles dans l'eau, et les mélanges de ceux-ci.

45 23. Article à fumer selon l'une quelconque des revendications 15 à 22, dans lequel les particules de tabac, représentent d'environ 25 à environ 98% du poids de l'article.

24. Article à fumer selon l'une quelconque des revendications 15 à 23, comprenant en outre, jusqu'à 1% en poids d'un agent moussant résiduel autre que l'eau.

50

55

60

65



