



(51) International Patent Classification:

H04W 4/12 (2009.01) *H04M* 1/66 (2006.01)

(21) International Application Number:

PCT/CN2016/111612

(22) International Filing Date:

23 December 2016 (23.12.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant: **ORANGE** [FR/FR]; 78, rue Olivier de Serres
75015 Paris (FR).

(72) Inventor; and

(71) Applicant (for US only): **GUO, Zhihong** [CN/CN]; Orange
Labs International Centers, 23F, Tower A, Beijing Global
Trade Center, 36 North Third Ring Road East, Dongcheng
District, Beijing 100013 (CN).(74) Agent: **WAN HUI DA INTELLECTUAL PROPERTY**
AGENCY; Yiyuan Office Building, Friendship Hotel, No.
1, Zhongguancun Street South, Haidian District, Beijing
100873 (CN).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR,
KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

(54) Title: METHOD FOR OPERATING DEVICE DURING UNAVAILABILITY TIME PERIOD




FIG. 2

(57) Abstract: A method for operating a device (1) characterized in that it comprises the following steps of, performed by a processing unit (11) of the device (1): (a) determining that a notification is to be outputted through a user interface (13) of the device (1) during an unavailability time period; (b) postponing outputting said notification until after the occurrence of an event indicative of the availability of a user of the device (1).



Published:

— *with international search report (Art. 21(3))*

METHOD FOR OPERATING DEVICE DURING UNAVAILABILITY TIME PERIOD

FIELD OF THE INVENTION

5

The field of this invention is that of devices such as mobiles phones. More particularly, the invention relates to a method for operating such a device during an unavailability time period.

10 BACKGROUND OF THE INVENTION

With devices such as mobile phones, notifications of events such as an incoming call or reception of a SMS will raise sound, vibrations and/or light on the screen of the mobile phones. In some circumstances, such notification will
15 bring interference to users. For instance, if the notification occurs during the night, it could wake up the user. Furthermore, it has to be noted that generally if the user “ignores” a notification, it is outputted again 2 minutes later, and sometimes even several more times.

In order to avoid disturbance by such notifications, it has been proposed
20 (for example in iOS operating system) to provide the user with a “Do not Disturb” function which allows to schedule a time period during which disturbing notifications are forbidden. This function may be configured so as to allow some notifications, for example from a specific contact groups, or if someone calls you twice within three minutes.

25 However, such a system depends entirely on the user’s input and is thus prone to human errors. Besides, when a notification is raised during a scheduled “Do Not Disturb” time period, this notification is simply silenced and the user is thus not notified of the situation once the scheduled “Do not disturb” time period is over.

30 There is therefore a need for improving the user experience so as to avoid bothering him with notifications when he is not available, without risking him to miss some notifications.

SUMMARY OF THE INVENTION

For these purposes, the present invention provides a method for
5 operating a device characterized in that it comprises the following steps of,
performed by a processing unit of the device:

- (a) determining that a notification is to be outputted through a
user interface of the device during an unavailability time
period;
- 10 (b) postponing outputting said notification until after the
occurrence of an event indicative of the availability of a user
of the device.

Such postponement of notifications prevents that the user be bothered by
15 the notifications while he is unavailable, without having to purely silence them
as it is the case for the "Do Not Disturb" mode. The situation is simply resumed
when he is available again.

- Preferred but non limiting features of the present invention are as follow:
- 20 • said event indicative of the availability of a user of the device is chosen
among the expiration of said unavailability time period, and an interaction of a
user with the user interface;
 - step (b) further comprises a step (b1) of monitoring if there is an active
interaction of a user with the user interface during the unavailability time period;
 - 25 • the method comprises a previous step (a0) of automatically detecting said
unavailability time period;
 - said unavailability time period is detected by accessing an agenda of the
user stored in a memory unit of the device, or a set alarm clock;
 - the device is powered by a battery, step (a) comprising estimating a
30 remaining battery lifetime and a remaining duration of said unavailability time
period, step (b) being performed only if the remaining battery lifetime is greater
than the remaining duration of said unavailability time period;

- the remaining battery lifetime is estimated as a function of a current battery level and an average power consumption;
- step (a) further comprises determining whether the notification is assigned a low priority level, the step (b) being performed only if the notification is assigned a low priority level;
- step (a) further comprises determining whether the notification is assigned a high priority level, the step (b) being performed only if the notification is not assigned a high priority level;
- step (a) further comprises normally outputting said notification if step (b) is not performed;
- the device is powered by a battery, said notification being a low battery notification.

In a second aspect, the invention provides an electronic device comprising a user interface and a processing unit configured to implement:

- determining that a notification is to be outputted through the user interface during an unavailability time period;
- postponing outputting said notification until after the occurrence of an event indicative of the availability of a user of the device.

According to a third and a fourth aspects, the invention provides a computer program product, comprising code instructions for executing a method according to the first aspect for operating a device; and a computer-readable medium, on which is stored a computer program product comprising code instructions for executing a method according to the first aspect for operating a device.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of this invention will be apparent in the following detailed description of an illustrative

embodiment thereof, which is to be read in connection with the accompanying drawings wherein:

- figure 1 illustrates an example of architecture in which the method according to the invention is performed;
- 5 - figure 2 illustrates a first embodiment of the method according to the invention; and
- figure 3 illustrates a second embodiment of the method according to the invention.

10 DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Architecture

The present invention relates to a method for operating a device 1 as
15 represented by **figure 1**. As explained the device comprises a processing unit 11, i.e. a CPU (one of mode processors).

The device 1 typically further comprises a memory 12 (for example flash memory) and a user interface 13 which typically includes a screen (possibly touch sensitive), loudspeakers and a vibration module.

20 The device 1 also comprises a battery 14, in particular a rechargeable battery (for instance lithium polymer) for powering the processing unit 11 and other units.

The device 1 may further comprise others units such as a location unit for providing location data representative of the position of the device 1 (using for
25 example GPS, network triangulation, etc.), a communication unit for connecting (in particular wirelessly) the device 1 to a network 20 (for example WiFi, Bluetooth, and preferably a mobile network, in particular a GSM/UMTS/LTE network, see below), etc.

This device 1 is typically a smartphone, a tablet computer, a laptop, etc.
30 In the following description the example of a smartphone will be used.

We refer now to **figures 2 and 3** which illustrate two embodiments of the method according to the present invention.

Notification

5

In all the embodiments of the method according to the present invention, in a first step (a), the processing unit 11 determines that a notification is to be outputted (i.e. is being requested to output a notification) through the user interface 13 of the device 1 during a specific time period T_{unav} , designated
10 hereafter as “unavailability time period”, wherein a user of the device 1 is not available.

In other words, the processing unit 11 either receives this notification from the communication unit (the notification is thus a call, a SMS, an e-mail, an alert from an application etc.), i.e. is requested from another equipment to
15 output the notification, or detects that a given event triggering a notification is occurring (for instance the battery level is below a given threshold such as 10% or 20%, the notification being a “low battery” notification – such example will be illustrated as preferred example in the following description), i.e. generates itself the notification.

20 In both cases, in the conventional art, the processing unit 11 would normally output the notification on the spot in particular by raising sound through the loudspeakers, a vibrating alert through the vibration module and/or light on the screen of the user interface 13.

In the present invention, however, after having determined that a
25 notification is to be outputted (step (a1)), the processing unit 11 checks (step (a2)) if the moment t_{NOTIF} when the notification is to be outputted occurs during the unavailability time period T_{unav} .

In a first embodiment, this unavailability time period T_{unav} is manually configured and/or scheduled by the user (like the “Do not Disturb” mode), for
30 instance during the night.

In the second embodiment, this unavailability time period T_{unav} is automatically detected in a previous step (a0). For instance, this automatic detection can be performed in various ways:

- 5 - if the processing unit 11 is aware of a set alarm clock, it can be assumed that the time period between setting the alarm time and the alarm time defines the unavailability time period T_{unav} , especially if the alarm time is in the morning (this time period extending during the night) ;
- 10 - by having access to the user's agenda stored in the memory 12 (or accessible through the network 20), the processing unit 11 can be aware of planned events such as meetings during which the user should not be disturbed;
- 15 - the processing unit 11 can also determine that the user is currently driving (e.g. because the device 1 is plugged in the car or because the user has inputted a route on a navigation system of the device 1) and that the user should not be disturbed during this activity;
- 20 - using supervised learning algorithms, the processing unit 11 can infer the habits of the user and know at which moments of the day he is generally unavailable.

In the following description, the preferred example of a set alarm time will be used as an indication of an unavailability time period extending up to said alarm time.

25 It is to be noted that if it is determined that the moment t_{NOTIF} when the notification is to be outputted does not occur during an unavailability time period T_{unav} , the notification is normally outputted (i.e. at t_{NOTIF} , i.e. on the spot if the notification is to be outputted immediately).

Postponement of notification

30

When having determined that the moment t_{NOTIF} of the output of the notification occurs during the unavailability time period T_{unav} , the method

comprises a step (b) whereby the output of the notification is postponed until the occurrence of an event indicative of the availability of the user of device 1. In other words, the processing unit 11 is requested to output a notification, but do not fulfill it at once.

5 Various events could be indicative of the availability of a user of the device 1. In particular, there could be one or a plurality of events triggering the postponement of the notification outputting.

Advantageously, a set of said events indicative of the availability of a user of the device 1 comprises at least the expiration of said unavailability time period T_{unav} and/or an interaction of a user with the user interface 13 during the unavailability time period T_{unav} .

In a first embodiment more specifically illustrated by **figure 2**, such an event consists in the expiration of the unavailability time period T_{unav} (i.e. said set of possible events indicative of the availability of a user of the device 1 only comprises the expiration of said unavailability time period).

In the following step (b) of this embodiment, the outputting of said notification is postponed until after the expiration of this unavailability time period T_{unav} , that is to say either right after the expiration of this unavailability time period T_{unav} or at a later moment occurring at a predetermined time shortly after this expiration (for instance a few seconds after the expiration).

In other words, for a request at the moment t_{NOTIF} to output immediately a notification during the unavailability time period, instead of being immediately outputted, the notification is only outputted when the unavailability time period is over. Alternatively, for a request to output a notification at a later given time t_{NOTIF} occurring during the unavailability time period, the notification is not outputted at the given time t_{NOTIF} , but outputted after the unavailability time period is over.

For example, as explained when the battery power level of the device 1 drops below a threshold (such as 20%), a low battery notification is to be triggered. Outputting this notification would play sound and light on the screen to notify the user to charge the battery. If the user has set an alarm that will ring at 6:00 AM, but the low battery threshold is hit at 5:00 AM, the remaining power

of the phone is highly likely to be enough to sustain one more hour and thus the notification could be postponed after that alarm at 6:00 AM is triggered, so as to avoid bringing unnecessary interference to the user.

In other words, in this example the processing unit 11 detects an
5 unavailability time period T_{unav} extending up to the alarm time of 6:00 AM (step (a0)), and then is being requested to output the power battery notification at 5:00 AM (step (a)). Because this request occurs during said unavailability time period, the outputting of the notification is not immediately performed, but postponed up to the end of said unavailability time period, i.e. 6:00 AM (step
10 (b)).

Consequently, the user is not bothered by the notification when he is not available, but is informed when he is available again (and able to respond to the notifications). Furthermore, there is no more risks of missing some notifications like in the "Do Not Disturb" mode in which they were silenced. Finally, it even
15 saves battery as outputting a notification is often quite power consuming (because of sound/light/vibrations), in particular if the outputting is repeated because the user ignores the notification.

In another embodiment more specifically illustrated by **figure 3**, the event
20 indicative of the availability of a user of the device 1 may also consist in the detection of an interaction of a user with the user interface 13 during the unavailability time period T_{unav} .

During the following step (b) of this other embodiment, starting from the moment t_{NOTIF} when the notification should have being outputted if it was not
25 during the unavailability time period T_{unav} , there is a further step (b1) of monitoring if there is an interaction of a user with the user interface 13 during the unavailability time period T_{unav} . Such an interaction can be the user turning on the screen of the user interface 13, for instance.

When such an interaction is detected by the processing unit 11, the
30 notification is outputted after the occurrence of this interaction (and thus before the expiration of the unavailability time period), that is to say either right after this detected interaction or at a later moment occurring at a predetermined time

shortly after this detected interaction (for instance a few seconds after this interaction).

Such a monitoring (b1) is performed (continuously or at regular times) until the expiration of the unavailability time period T_{unav} .

5 In the embodiment represented by figure 3, in the case where no interaction of the user with the user interface 13 has been detected before the expiration of this unavailability time period T_{unav} , then the notification is outputted after the expiration of the unavailability time period T_{unav} , similarly to the first embodiment illustrated in figure 2. In other words in this embodiment,
10 both the detection of an interaction of a user with the user interface 13 during the unavailability time period T_{unav} , and the expiration of the unavailability time period T_{unav} , are events indicative of the availability of a user of the device 1 (i.e. there is a set of possible events indicative of the availability of a user of the device 1 comprising both the expiration of said unavailability time period and an
15 interaction of a user with the user interface 13 during the unavailability time period).

It is to be understood that it may alternatively be provided that said set of possible events indicative of the availability of a user of the device 1 only comprises an interaction of a user with the user interface 13 (i.e. if there is still
20 no interaction of the user after the end of the unavailability time period, the notification is not outputted until such an interaction is detected), in order to be sure not to bother the user if his/her unavailability happens to be longer than initially expected.

Moreover, in all embodiments the notification postponement may only be
25 performed for specific notifications, considered as relatively less important notifications, such as low battery notifications or application crash notifications. In another embodiment, some specific types of notifications, considered this time as relatively more important ones, such as calls, SMS or notifications from a given list of contacts for instance, are still to be outputted without delay by the
30 user interface 13, even when their notification moment T_{NOTIF} occur during the unavailability time period

For that purpose, a priority level (typically user-defined) may be assigned to notifications. A low priority level may thus be assigned to the above-mentioned relatively less important notifications while a high priority level may be assigned to the relatively more important notifications.

5 In such an embodiment, the method advantageously comprises, after having determined that a notification is to be outputted, a further step of determining whether the notification is assigned a low priority level, the step (b) of postponing being implemented only when that it is the case. Alternatively, the method advantageously comprises, after having determined that a notification is
10 to be outputted, a further step of determining whether the notification is assigned a high priority level, the step (b) of postponing being implemented only when that it is not the case.

Remaining battery lifetime

15 In a preferred embodiment (particularly advantageous if the notification is a low battery notification), the postponement of the notification should be carried out only if possible, i.e. only if the battery 14 can handle it.

 In other words, step (a) further comprises estimating a remaining battery
20 lifetime T_{BLife} and a remaining duration of said unavailability time period ΔT_{unav} , so as to have step (b) being performed only if the remaining battery lifetime T_{BLife} is greater than the remaining duration of said unavailability time period ΔT_{unav} . This embodiment allows ensuring that the notification is outputted before the device 1 runs out of battery.

25 More precisely, the processing unit 11 first checks if the notification can wait until the ending time of the unavailability time period T_{unav} by calculating the expected remaining battery lifetime T_{BLife} (for example from the operating system or an API such as the one available with Android OS) and by comparing it with the remaining duration of the unavailability time period ΔT_{unav} (i.e. the
30 difference between the end time of the unavailability time period T_{unav} and the present time).

If the system settings only shows the remaining battery level (i.e. the load percentage of the battery), a mechanism to calculate the remaining battery lifetime T_{BLife} from this remaining battery level can be used. In particular, the remaining battery lifetime can be estimated as a function of a current battery level and an average power consumption. The average power consumption in the past x hours can be used as a basis. Alternatively statistics data, for example the average consumption in the past 1 month during the same time, can be used as the basis.

In a preferred embodiment, in order to avoid possible fluctuations of the remaining battery lifetime T_{BLife} (if the user uses mobile applications which consume much more battery than planned in the meantime) as well as for allowing the user to respond the notification, a given time margin, for example 30 minutes, may be taken into account when deciding to postpone. In other words, step (b) is performed only if the remaining battery lifetime T_{BLife} is greater by such a margin than the remaining duration of said unavailability time period ΔT_{unav} . For instance, the notification can be postponed only if the end of the unavailability time period T_{unav} occurs more than 30 minutes before the expected end of the remaining battery lifetime T_{BLife} .

It has to be understood that said remaining duration of the unavailability time period is in most cases calculable from (at least an estimation of) the moment of the event ending the unavailability time period (the time of this event is either known, for instance if the unavailability is detected using a calendar, or it may be estimated, for instance if the user is driving and is using a navigation application). If it were not to be determinable at all (if for example the user has manually activated a "Do not Disturb" mode), it may be decided that the notification is postponed as soon as the battery level is above a given threshold (for example 50%).

Naturally, in the previously embodiment where there is a user activity monitoring by the processing unit 11 during the unavailability time period, when a user interaction on the device is detected, thereby meaning that the user becomes available, the postponed notifications will be outputted without waiting for the expiration of the unavailability time period.

Device and computer program

The present invention further proposes an electronic device 1 comprising
5 a user interface 13 and a processing unit 11, adapted for carrying out the
method for operating as previously described. This device 1 may also comprise
a memory 12, a battery 14. This processing unit 11 is configured to implement
the steps of:

- optionally, detecting an unavailability time period of the user;
- 10 - determining that a notification is to be outputted through the user
interface 13 during the unavailability time period;
- postponing outputting said notification until after the occurrence of an
event indicative of the availability of a user of the device 1 (in particular
only if the remaining battery lifetime is greater than the remaining
15 duration of said unavailability time period).

The present invention further proposes a computer program product,
comprising code instructions for executing (in particular with a processing unit
11 of the device 1) the previously described method as well as a computer-
20 readable medium (in particular a memory 12 of the device 1), on which is stored
a computer program product comprising code instructions for executing said
method. In particular, this computer program product may correspond to a
dedicated software application to be installed on said device 1.

CLAIMS

1. A method for operating a device (1) characterized in that it comprise the following steps of, performed by a processing unit (11) of the device (1):
- 5 (a) determining that a notification is to be outputted through a user interface (13) of the device (1) during an unavailability time period;
- 10 (b) postponing outputting said notification until after the occurrence of an event indicative of the availability of a user of the device (1).
2. A method according to claim 1, wherein said event indicative of the availability of a user of the device (1) is chosen among the expiration of said unavailability time period and an interaction of a user with the user interface (13).
- 15 3. A method according to claim 2, wherein step (b) further comprises a step (b1) of monitoring if there is an interaction of a user with the user interface (13) during the unavailability time period.
- 20 4. A method according to any one of claims 1 to 3, comprising a previous step (a0) of automatically detecting said unavailability time period.
- 25 5. A method according to claim 4, wherein said unavailability time period is detected by accessing an agenda of the user stored in a memory unit (12) of the device (1), or a set alarm clock.
- 30 6. A method according to any one of claims 1 to 5, wherein the device (1) is powered by a battery (14), step (a) comprising estimating a remaining battery lifetime and a remaining duration of said unavailability time

period, step (b) being performed only if the remaining battery lifetime is greater than the remaining duration of said unavailability time period.

7. A method according to claim 6, wherein the remaining
5 battery lifetime is estimated as a function of a current battery level and an average power consumption.

8. A method according to any one of claims 1 to 7, wherein
step (a) further comprises determining whether the notification is assigned a low
10 priority level, the step (b) being performed only if the notification is assigned a low priority level.

9. A method according to any one of claims 1 to 8, wherein
step (a) further comprises determining whether the notification is assigned a
15 high priority level, the step (b) being performed only if the notification is not assigned a high priority level.

10. A method according to any one of claims 6 to 9, wherein
step (a) further comprises normally outputting said notification if step (b) is not
20 performed.

11. A method according to any one of claims 1 to 10, wherein
the device (1) is powered by a battery (14), said notification being a low battery
notification.

25

12. An electronic device (1) comprising a user interface (13)
and a processing unit (11) configured to implement:

- determining that a notification is to be outputted through the user
interface (13) during an unavailability time period;
- 30 - postponing outputting said notification until after the occurrence of an
event indicative of the availability of a user of the device (1).

13. A computer program product, comprising code instructions for executing a method according to any one of claims 1 to 11 for operating a device (1).

5 **14.** A computer-readable medium, on which is stored a computer program product comprising code instructions for executing a method according to any one of claims 1 to 11 for operating a device (1).

1/3




FIG. 1

2/3




FIG. 2

3/3




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2016/111612

A. CLASSIFICATION OF SUBJECT MATTER		
H04W 4/12(2009.01)i; H04M 1/66(2006.01)i		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
H04W, H04M		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
CNPAT,CNKI,WPI,EPODOC,IEEE:message, notification, information, unavailable, postpone, suspend, delay, disturb, battery, interaction, agenda, clock		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CN 103561152 A (GUANGDONG OPPO MOBILE TELECOMMUNICATIONS CO., LTD.) 05 February 2014 (2014-02-05) description paragraphs [0002], [0059]-[0061], [0090]-[0104], figures 1, 4	1-14
X	CN 105117211 A (XIAOMI TECHNOLOGY CO., LTD.) 02 December 2015 (2015-12-02) description paragraphs [0057]-[0083], [0128]-[0139], figures 1, 6	1-14
A	US 2014181843 A1 (PANTECH CO., LTD.) 26 June 2014 (2014-06-26) the whole document	1-14
A	US 9357063 B1 (GOOGLE INC.) 31 May 2016 (2016-05-31) the whole document	1-14
☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
20 June 2017		27 September 2017
Name and mailing address of the ISA/CN		Authorized officer
STATE INTELLECTUAL PROPERTY OFFICE OF THE P.R.CHINA 6, Xitucheng Rd., Jimen Bridge, Haidian District, Beijing 100088 China		ZHOU,Yanan
Facsimile No. (86-10)62019451		Telephone No. (86-10)62413669

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CN2016/111612

Patent document cited in search report			Publication date (day/month/year)	Patent family member(s)			Publication date (day/month/year)
CN	103561152	A	05 February 2014	None			
CN	105117211	A	02 December 2015	None			
US	2014181843	A1	26 June 2014	KR	20140081944	A	02 July 2014
US	9357063	B1	31 May 2016	US	8909203	B1	09 December 2014
				US	8611272	B1	17 December 2013
				US	8385884	B1	26 February 2013
				US	8433291	B1	30 April 2013