

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number

WO 2014/060455 A1

(43) International Publication Date
24 April 2014 (24.04.2014)

WIPO | PCT

(51) International Patent Classification:
A24D 1/02 (2006.01)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:
PCT/EP2013/071592

(22) International Filing Date:
16 October 2013 (16.10.2013)

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
1218543.5 16 October 2012 (16.10.2012) GB
1314043.9 6 August 2013 (06.08.2013) GB

(71) Applicant: BRITISH AMERICAN TOBACCO (INVESTMENTS) LIMITED [GB/GB]; Globe House, 1 Water Street, London WC2R 3LA (GB).

(72) Inventors: HOLFORD, Steven; c/o British American Tobacco (Investments) Limited, Globe House, 1 Water Street, London WC2R 3LA (GB). MCKENZIE, Aaron; c/o Studio W, Clarendon Buildings, 25 Horsell Road, London N5 1XL (GB).

(74) Agents: BROWN, Alexander et al.; Venner Shipley LLP, 200 Aldersgate, London EC1A 4HD (GB).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SMOKING ARTICLE WRAPPER AND METHOD OF MAKING A SMOKING ARTICLE




FIG. 1

(57) Abstract: Smoking article wrapper and method of making a smoking article A smoking article component comprises a curved sheet wrapper of weight 40 gsm or more that includes a plurality of lines of strength discontinuity at which the wrapper presents a visually discernible non-uniformity in its curvature. The wrapper can be used for example to wrap the filter of a cigarette as a plug wrap for the filter so as to comprise a wrapper of weight 80 gsm or more.

Smoking article wrapper and method of making a smoking article

Field

This specification relates to a smoking article wrapper and a plug wrap that can be used

5 in a smoking article filter for use in a smoking article such as a cigarette.

Background

Smoking articles such as filter cigarettes generally have a smooth paper wrapper

around their outside. A typical cigarette structure comprises a rod of tobacco or like

10 smokeable material wrapped in a smooth paper wrapper, attached to the filter by a tipping paper. The filter may comprise filter material such as cellulose acetate tow with a wrapper termed a plug wrap.

Summary

15 Embodiments of the present invention described herein provide a smoking article component including a curved sheet wrapper of weight 40 gsm or more that includes a plurality of lines of strength discontinuity whereat the wrapper presents a visually discernable non-uniformity in its curvature.

20 The plurality of lines of strength discontinuity can comprise lines of weakness for example partial cuts into the thickness of the sheet material.

The wrapper may for example have a weight of at least 45, 50, 55, 60, 70, 80 or 90 gsm and up to a weight of up to about 120 gsm and may comprise a tipping paper.

25 The smoking article component may be incorporated as a wrapper over the filter of a filter cigarette. The filter may be located in a fixed position or may be included in a telescopic arrangement.

30 An example of a machine for making a smoking article is described herein which applies a wrapper with an embossed pattern to a smoking article and includes a curling station at which the wrapper is passed over a rotary curling roller that includes a surface pattern to correspond the embossed pattern on the wrapper, and configured to weaken the wrapper to promote curling of the wrapper around the smoking article.

Embodiments of a wrapper described herein for a smoking article filter comprise a sheet wrapper of weight 80 gsm or greater that includes a plurality of lines of embossing such that the wrapper presents a visually discernable non-uniformity in its curvature, and includes lap seams along opposite side edges that include lines of weakness that permit intimate abutment of side edges of the wrapper around the filter.

5 The wrapper may have a weight of at least 90, 100, 115, 120, 125, 130 gsm, for example in the range of 80 -150 gsm, 80 – 200 gsm, 90 – 150 gsm or 100 – 130 gsm. Its thickness may be in the range of 50 μm - 115 μm and conveniently not exceeding 200
10 μm .

In another embodiment a wrapper for a smoking article filter comprises a sheet wrapper of weight 80 gsm or greater that includes a plurality of lines of embossing such that the wrapper presents a visually discernable non-uniformity in its curvature.

15 In a further embodiment a wrapper for a smoking article filter comprises a sheet wrapper that includes a plurality of lines of embossing such that the wrapper presents a visually discernable non-uniformity in its curvature, and includes lap seams along opposite side edges that include lines of weakness that permit intimate abutment of
20 side edges of the wrapper around the filter.

The wrapper may comprise a generally rectangular web of sheet material embossed with a regular pattern of facets and side edges formed with line embossing in the regions of the lap seams.

25 Spaced bands of line embossing may extend transversely across the web so as to be suited to form a plug wrap for a filter.

Further specific features and advantages are embodied in and will be apparent from the claims set forth hereinafter.

30

Brief description of the drawings

In order that the invention may be more fully understood embodiments thereof will now be described by way of illustrative example with reference to the accompanying drawings in which:

Figure 1 is a side view of a smoking article comprising an extendible cigarette in an unextended configuration;

Figures 2a and 2b are longitudinal sectional views of the cigarette shown in Figure 1 in unextended and extended configurations respectively;

5 Figure 3 is a plan view of the inside surface of the wrapper used in the cigarette shown in Figures 1 and 2;

Figure 4 is a partial sectional view through the thickness of the wrapper shown in Figure 3 taken along line A-A';

10 Figure 5 is an enlarged sectional view of the wrapper taken along the line B-B' of Figure 2b, when formed into a tube;

Figures 6a-6e illustrate alternative patterned blanks for use as the wrapper with different facet designs that extend in an array over the entire blank;

Figures 7a-7e illustrate alternative patterned blanks for use as the wrapper with first and second arrays of facets in different regions of the blanks;

15 Figures 8a-8e illustrate alternative patterned blanks for use as the wrapper with an array of facets over only a part of the blanks;

Figure 9 is a schematic illustration of apparatus for forming the wrapper;

Figure 10 is a longitudinal sectional view of a further example of an extendible cigarette in an unextended configuration;

20 Figure 11 is a mouth end view of the cigarette shown in Figure 10;

Figure 12 is a side view of the cigarette shown in Figures 10 and 11;

Figure 13 is an enlarged view of a portion of a wrapper in which lines of weakness have been formed by pin embossing;

Figure 14 is a side view of a smoking article comprising a fixed filter cigarette;

25 Figure 15 is a longitudinal sectional view of the cigarette shown in Figure 14;

Figure 16 is a plan view of an embossed web for use in manufacture of the cigarette shown in Figures 14 and 15;

Figure 17 is a schematic side elevational view of a cigarette making machine;

Figures 18 and 19 are schematic illustrations of process steps performed by the

30 cigarette making machine shown in Figure 17;

Figure 20A is a schematic illustration of a curling station in the cigarette making machine of Figure 17;

Figure 20B illustrates a modification to the curling station;

Figures 21, 22 and 23A and B illustrate side and end views of different curling bars for

35 use in the curling station of Figure 20;

Figure 24 is a side view of another smoking article comprising a fixed filter cigarette;

Figure 25 is a longitudinal sectional view of the cigarette shown in Figure 24;

Figure 26 is a side view of a further smoking article comprising a fixed filter cigarette;

Figure 27 is a longitudinal sectional view of the cigarette shown in Figure 27;

Figure 28 is a schematic illustration of a process for making a filter rod to provide

5 filters for the cigarettes shown in Figures 24 – 27;

Figure 29 is a schematic plan view of a web for use as a plug wrap with a line embossed lap seam in filter rod making process;

Figure 30 illustrates the resulting filter rod;

Figure 31A also illustrates the resulting filter rod highlighting its pattern of embossed

10 facets;

Figure 31B illustrates the rod and its line embossed side edges that form a lap seam;

Figure 32A illustrates a cigarette manufactured using the filter rod of Figures 30 and

31;

Figure 32B illustrates the cigarette and the line embossed longitudinal side edges of the

15 plug wrap;

Figure 33 illustrates an alternative web with a lap seam for use as a plug wrap in a filter

rod making process shown in Figure 28;

Figure 34 illustrates the resulting filter rod produced from the plug wrap shown in

Figure 33;

20 Figure 35A illustrates the filter rod produced from the plug wrap shown in Figure 33;

Figure 35B illustrates the filter rod of Figure 35 and its glued overlapping, embossed

lap seams;

Figure 36A illustrates a filter cigarette made with the filter rod of Figures 34 and 35;

Figures 36B illustrates the filter cigarette of Figure 36A and the glued overlying lap

25 seams of the filter rod; and

Figures 36C – E are views corresponding to Fig. 36 B with different widths of tipping

paper connecting the filter segment to the tobacco rod.

Detailed description

30 Overview

Several examples of smoking article are described hereinafter which make use of a smoking article component comprising a curved sheet wrapper that provides a distinctive visual appearance to the exterior of the smoking article. As used herein, the term “smoking article” includes smokeable products such as cigarettes, cigars and

35 cigarillos whether based on tobacco, tobacco derivatives, expanded tobacco, reconstituted tobacco or tobacco substitutes and also heat-not-burn products, e-

cigarettes, pressurised canister devices and other forms of inhaler. The smoking article may be provided with a filter for the gaseous flow drawn by the smoker. Some of the examples of smoking article described herein comprise a cigarette with a filter in a fixed location on a rod of smokeable material such as tobacco whereas others are telescopic

5 in configuration. The curved sheet wrapper in the described embodiments is of a weight of 40 gsm or more, and includes a plurality of lines of strength discontinuity that may comprise lines of weakness configured so that the wrapper presents a visually discernable non-uniformity in its curvature. Sheet material such as a tipping paper with a weight of 40 gsm or more gives rise to a particularly well defined visually

10 discernable pattern when provided with the lines of strength discontinuity and formed into a curved wrapper, particularly above 40, 45, 50, 55, 60, 70, 80 and 90 gsm, and up to about 120 gsm in some embodiments. Conveniently, the thickness of the paper is within a range of 50 μm - 115 μm for the range of weights 40 – 90 gsm.

15 Further preferred ranges are 50 – 150 gsm for tipping paper and 80 – 150 gsm for plug wrap. Conveniently, the upper limit for the thickness of the wrapper is 200 μm .

The values of wrapper weight in gsm as discussed herein refer to the weight of the wrapper sheet prior to treatment to provide the lines of strength discontinuity therein 20 such as lines of weakness formed by line embossing, described in more detail hereinafter, which may alter the wrapper weight slightly.

Telescopic cigarette

Referring to Figures 1 and 2, an extendable smoking article in the form of a telescopic cigarette 1 comprises a tobacco rod 2 that comprises tobacco in a paper wrapper, with 25 an attached first filter section 3. The tobacco rod 2 and the first filter section 3 are attached to one another by a covering layer of sheet material e.g. paper, preferably tipping paper 4 as illustrated in Figure 2.

30 A first component part comprises a sleeve 5 in the form of a cylindrical tube that extends around the circumference of the tobacco rod 2 and the first filter section 3. The tobacco rod 2 and the first filter section 3 are dimensioned to slide as a unit longitudinally within the sleeve 5. The tobacco rod 2 and first filter section 3 may be referred to as a tobacco unit or as a second part of the smoking article 1.

The first part may further comprise a second filter section 6 at a mouth piece end of sleeve 5, distal from the first filter section 3. The second filter section is securely attached within the sleeve 5. The first and second filter sections 3,6 may be circular in cross section and of the same diameter and conveniently be made of conventional cellulose acetate tow with a plug wrap.

5 A chamber 7 is defined in the sleeve between the first and second filter sections 3, 6. The chamber 7 is of variable length and hence volume as the first filter section slides axially within the sleeve 5. Relative movement of the first and second parts i.e. between 10 the sleeve 5 and tobacco rod 2, beyond the maximum length is prevented by a re-entrant lip 8 formed at the distal end of the sleeve 5, which abuts a ridge on the tobacco rod 2 formed by the edge 4a of the tipping paper 4.

15 As shown in Figure 1, the exterior surface of the tubular sleeve 5 is embossed and presents an array of facets which on the exterior may be generally planar. The shape of the facets can be selected to achieve different visual effects and one example is illustrated in more detail in Figure 3, which shows a blank 9 of sheet material that can be rolled up to form the tubular sleeve 5 around the second filter section 6. The tube 5 may be formed by gluing lap seams provided by peripheral edges 9a, 9b with line 20 embossing as shown, to one another in an overlapping joint. Also, the re-entrant flap 8 can be created by folding region 9c of the blank inwardly.

25 The blank 9 includes a plurality of lines of strength discontinuity, in this example, lines of weakness 10, on the side of the blank 9 that forms the interior of tubular sleeve 5 so that the sleeve 5 when formed has a discontinuity in its radius at the lines of weakness 10. Thus, the wrapper blank 9 presents a visually discernable non-uniformity in its curvature when formed into the sleeve 5.

30 As illustrated in Figure 4, the lines of weakness 10 may be formed by partially cutting into the sheet material that forms the blank 9. The cutting may conveniently be performed by laser cutting with one or more laser cutters which oscillate over the surface of the sheet material that forms blank 9. The depth of the cuts may be typically 50% of the thickness of the sheet material although the invention is not restricted to this depth. Preferably, the depth of the cutting comprises between 10-90% of the 35 thickness of the blank. It will also be appreciated that the cutting can be performed using knife blades. The sheet material 9 that forms the blank may be used with the cuts

on an inner or outer surface when forming a wrapper such as the sleeve 5. The lines of weakness can alternatively be formed by creasing the sheet material, by pinching the sheet material from both sides, or with other techniques such as embossing, which is described in more detail below.

5

Blanks 9 made from sheet material such as paper e.g. tipping paper with a weight of 40 gsm or more give rise to a particularly well defined pattern when formed into a curved wrapper such as the sleeve 5, particularly above 40, 45, 50, 55, 60, 70, 80 and 90 gsm and up to about 120 gsm. Conveniently, the thickness of the paper is within a range of 10 50 µm - 115 µm for the range of weights 40 – 90 gsm.

As illustrated in Figure 5, upon formation of the tubular sleeve 5, with the blank 9 being wrapped around the cylindrical surfaces of the first and second filter units 3, 6, the wrapping process results in the slits 10 becoming closed so that the inner surface 11 15 conforms to the curvature of the cylindrical filter elements 3, 6, which are of the same diameter, whereas the outer surface of sleeve 5 comprises a series of facets 12 that are generally planar or at least have the radius of curvature different from that of the curvature of the inner surface 5a. Alternatively, the radius of curvature of the inner and outer surfaces can be constant. In either case, the facets may have a relatively large 20 radius of curvature e.g. approximately planar, with a sharp bend at their edges at the lines of weakness 10. This gives rise to an array of visually discernable facets 12 illustrated in Figure 1. The facets, for instance, result in the wrapper formed by the sheet material having a non-constant radius of curvature. It will be appreciated that the shape of the facets 5b can be selected depending on the pattern of the lines of 25 weakness 10. In the example illustrated in Figure 3, the pattern is generally similar to a fish net so that facets 12 have a generally ellipsoidal shape. However, many other different patterns can be envisaged, as illustrated in Figures 6, 7 and 8.

Referring to Figure 6A-E, facets 13 for a particular blank may be of identical shape 30 arrayed over the entire surface of the blank 9. Alternatively, as illustrated in Figure 7, the facets 13 can be configured in a first array that may extend over the major part of the blank and facets 14 of a different shape to facets 13 in the first array, may be configured in a second array over the mouthpiece end of the blank 9. The facets 13 may have a closed perimeter which may be curved or polygonal in shape, or the facets 35 may have an open shape such as parallel strips extending between spaced, parallel lines

of weakness, for example the facets 14 extending longitudinally of the cigarette in Figure 7 or in a zigzag or a spiral pattern (not shown).

As illustrated in Figures 6 and 7, longitudinal edge regions of the blank 9 may be

5 formed with parallel, closely spaced lines of weakness 15a, 15b conveniently formed by line embossing to provide lap seams which facilitate wrapping the longitudinal edges onto one another when forming and gluing the curved wrapper 9 into the tubular sleeve 5.

10 As illustrated in Figure 8, the mouthpiece end array of facets 14 may be omitted.

Figure 9 is a schematic illustration of apparatus for forming sheet material for use in the blanks 9. In this example a roll 16 of paper or like sheet material of the aforesaid weight is supplied as a continuous web 17 by means of two pairs of supply rollers 18

15 through a station 19 where the lines of strength discontinuity are formed. The station 19 may include one or more lasers that produce the lines of weakness 10 across the web 17. Alternatively the station 19 may include blades to cut the paper web 17 on one or both sides to form the lines 10, an arrangement to crease the paper web to form the lines of weakness or a pair of embossing rollers to apply the lines of weakness using pin embossing or other embossing techniques. The web 17 after leaving the station 19 may

20 be fed into a take up roll 20 which is then taken to a filter rod making machine or to cigarette making machine for incorporation into cigarettes. Thus the paper is prepared off-line from the cigarette making machine in a preparatory process. By way of background, an example of how the web 17 may be incorporated into a process for

25 forming the telescopic cigarette is described in our PCT/GB2011/050499. Alternatively, the web 17 and the station 19 may be provided on-line at the cigarette making machine for forming the lines of weakness in the web just before it is supplied into the making machine.

30 Whether prepared on or off-line from the cigarette making machine, the web 17 may also be printed or embossed with logo style or other information, and the printing or embossing may be performed in a predetermined registry with the pattern of facets 12, for example so that the printing or embossing is configured within individual ones of the facets.

Another example of extendible cigarette is illustrated in Figures 10 to 13. In this example the sleeve 5, instead of being made solely of the faceted blank 9 as in Figures 1 to 4, also includes an underlying support layer 21 to which the blank 9 may be affixed by gluing or other suitable means evident to those skilled in the art. The support layer 5 21 may comprise a rectangular, rolled blank of sheet material such as paper and is formed with the re-entrant lip 8 so as to limit the extension of the tobacco rod 2 along the sleeve 5 by engaging the edge 4a of tipping paper 4 which holds the filter 3 on the end of the tobacco rod 2, in a similar fashion to the lip 8 described with reference to Figures 1 to 4. The support layer 21 is glued to the filter 6. With the support layer 21, the 10 paper weight for the blank 9 can be in a range of 50-60 gsm to provide a good visual effect e.g. a tipping paper of weight 58 gsm.

In the example shown in Figures 10 to 13, the blank 9 is formed with a regular pattern of facets 12 that comprise irregular hexagons that resemble a fish net in a similar 15 pattern to that shown in Figure 1. However, unlike Figure 1, the blank 9 shown in Figure 10 has longitudinal side edges 22, one of which is shown more clearly in Figure 13, which follow the edges of the facets 12 so that they can be arranged in a butt joint 23 illustrated in Figures 11 and 12, with the advantage that the pattern of facets 12 can run continuously around the exterior of the sleeve without a discontinuity that can be felt in 20 the finger of the hand or which is visible to the user.

In the example shown in Figure 13, the lines of weakness 10 are formed by pin embossing, which produces a line of pin pricks 24 around the perimeter of the facets. The pin pricks 24 can be formed using a roller that has a pattern of pins around its 25 periphery, which is included in the station 19 shown in Figure 9, so that upon rotation of the roller in engagement with the web 16, the pattern of pin pricks shown in Figure 13 is produced.

Fixed filter cigarette
30 Some examples of smoking article with a fixed filter will now be described that utilise a wrapper with an embossed pattern.

Referring to Figures 14 and 15, a fixed filter cigarette comprises a tobacco rod 2, which in a conventional manner comprises smokeable material such as tobacco or tobacco 35 containing material 25 wrapped in a paper wrapper 26. A generally cylindrical filter segment 3 that comprises filter material, for example cellulose acetate 27 wrapped in a

paper plug wrap 28, is attached to the tobacco rod 2 by means of a tipping wrapper 29 which has been embossed with an array of facets 12 in the manner previously described with reference to Figure 9, such that the wrapper 29 can be formed as a cut segment from a web 17 that has been provided with the embossed pattern.

5

An example of the pattern formed on the web 17 is illustrated in Figure 16 and comprises lines weakness 10 which may be formed by laser cutting, embossing such as pin embossing or any other suitable method, as previously described. The web 17 is made from sheet material such as paper with a weight of 40 gsm or more which gives 10 rise to a particularly well defined pattern when formed into a curved wrapper, particularly above 40, 45, 50, 55, 60, 70, 80 and 90 gsm and up to about 120 gsm. Conveniently, the thickness of the paper is within a range of 50 μm - 115 μm for the range of weights 40 – 90 gsm.

15 The web is of a width suitable for forming two cigarettes back-to-back in a cigarette making machine as will be explained hereinafter. Each length L1, L2, L3, etc of the web 17 is utilised to form an individual back-to-back cigarette pair and in use, the web 17 is cut along lines 30-1, 30-2, etc. The web 17 is provided with a high level of embossing e.g. pin embossing in transverse regions 31-1, 31-2, etc. in order to make the web 20 compliant and easy to curl in its edge regions around the filter 3.

A cigarette making machine suitable for producing cigarettes as shown in Figures 14 and 15 will now be described with reference to Figure 17. The machine can be considered as a modification of a machine by Hauni Maschinenbau AG, which has been 25 adapted to utilise a roll 20 of a tipping material web 17 such as illustrated in Figure 16 in the manufacture fixed filter cigarettes. Reference is also made to Figures 18 and 19, which illustrate schematically the process steps performed by various parts of the machine illustrated in Figure 17.

30 Tobacco rods 32 of a length suitable for forming two cigarettes back-to-back are supplied to a tobacco rod in-feed 33 shown in Figure 17. Also, filter rods 34 are supplied from a hopper 35 into the machine. The filter rods 34 are of a length suitable for forming two cigarettes back-to-back.

35 The tobacco rods 32 are supplied onto a take over drum 36 and passed to a tobacco rod cutting drum 37 with an associated knife wheel 38 that cuts the rods 32 into two parts

32a, 32b which are then axially separated by means of a separating drum 39 and passed to a filter feed drum 40 where an individual filter rod 34 is placed between them as shown in Figure 18.

- 5 The filter rods are fed from hopper 35 by means of supply rollers 41-44 to the filter feed drum 40 and as shown in Figure 19, the filter feed drum 40 acts to abut the tobacco rods 32a, 32b against opposite ends of the filter rods 34 on a common longitudinally axis.
- 10 The abutting arrangement of rods 32a, 34, 32b is then transferred to a swash-plate drum 41 where they are joined together by means of wrapper 42 that comprises a cut portion of the web 17 shown in Figure 16, e.g. between lines 30-1 and 30-2. As will be explained later, the wrapper portion 42 is cut from the web 17 and is coated with glue so that when the arrangement is transferred to rolling drum 43, the wrapper portion 42 is wrapped around the filter rod 34 and is dimensioned to overlap the ends of the tobacco rods 32a, 32b so that they become joined together as illustrated by the arrangement 44 in Figure 19.
- 15 The joined rods 44 then pass on to a transfer drum 45 so as to be fed to a cutting drum 46 with an associated rotary knife 47 which cuts the joined rods into two separate cigarettes 1, 1' which are then fed via a transfer drum 48 to a turning drum 49 where the cigarettes 1, 1' of each pair are arranged to face in the same direction ready for packaging.
- 20 The joined rods 44 then pass on to a transfer drum 45 so as to be fed to a cutting drum 46 with an associated rotary knife 47 which cuts the joined rods into two separate cigarettes 1, 1' which are then fed via a transfer drum 48 to a turning drum 49 where the cigarettes 1, 1' of each pair are arranged to face in the same direction ready for packaging.
- 25 The web 17 of wrapper material is fed sequentially from a feed arrangement comprising two rolls 20a, 20b so that a continuous supply of the web 17 can be provided to a cigarette making machine. Thus, when one of the supply rolls 20 becomes exhausted, supply can continue from the other roll and the empty roll can be replaced.
- 30 In an alternative, a plain web roll is used and an embossing station for example as shown and described with reference to Figure 9 is included in the cigarette making machine. Also the web 17 may be embossed at a station adjacent the cigarette making machine and supplied from the adjacent station into the making machine.
- 35 Referring again to Figure 17, the web 17 is fed from one of the rolls 20 to a curling station 50 illustrated in more detail in Figure 20A. The curling station 50 operates on

the web 17 in order to weaken its structural integrity on one side to enable it to curl into a cylinder readily when wrapped around the rods 32a, 32b and 34 on the drums 41, 43 as shown in Figures 17 and 19. Hitherto, tipping paper in conventional cigarette making machines has been passed over a fixed curling edge to weaken the structural 5 integrity of the tipping paper slightly on one face. However, the web 17 is formed with an embossed pattern of facets 12 and so if a fixed edge were used, the facet pattern would be at least partially destroyed. In the arrangement shown in Figure 20, the web 17 passes over an inlet static bar 51 to a corresponding outlet static bar 52, via a freely 10 rotatable curling roller 53 which is formed with an external pattern of facets 54 shown in Figure 21A that correspond to the facets 12 on the web 17. The curling roller 53 is free to rotate about axis X-X' and the pattern of facets 54 tends to self-synchronise with facets 12 on the web 17. Also, as the web 17 changes its direction from the inlet (arrow A) to the outlet direction (arrow B) it undergoes a sharp change in direction 15 approaching 180°, which results in the structural integrity of the paper being changed so that it has a propensity to curl, but without destroying the embossed pattern of facets 12, which are maintained due to their synchronism with the facet pattern 54 on the curling roller 53. It will be understood that the rotary curling roller 53 can be retrofitted to a cigarette making machine instead of the conventional fixed blade arrangement used hitherto in such machines.

20

In a modification, a servo system (not shown) is provided to drive the curling roller 53 to rotate about the axis X-X' rather than allow it to be rotated solely by the passing web 17 as previously described, and an optical detector is provided (not shown) to detect the pattern of the facets 12 on the web 17 to allow the rotation phase of the pattern 54 on 25 curling roller 53 to be maintained in synchronism with the faceted pattern on the web 17, so as not to compromise the web pattern by the curling process.

Various patterns of facets may be provided on the curling roller 53, which may be 30 interchangeable, so that the chosen pattern 54 can be complementary to, and mesh in synchronism with the pattern of facets formed on the web 17, and alternative curling roller patterns can be provided to match different web patterns as shown in Figures 22 and 23.

In a modification shown in Figure 20B, further curling rollers 53 are included, in this 35 example 3, so that the web 17 passes back and forth over them in a serpentine pattern, to weaken the surface of the web 17 on both sides.

Referring to Figure 17, the web 17 passes from the curling station 50 to a gluing station 55. This includes a gluing roller 56 that applies to predetermined pattern of glue on to one side of the web 17, transferred by a transfer roller 57 from a tray 58. The web 17
5 with glue applied then passes over a feed roller 59 to a rotary patch cutter 60 that includes a plurality of radially extending blades that cut the web 17 into portions 42 to be applied to successive tobacco and filter rod arrangements as illustrated in Figure 19.

Referring to Figure 16, the patch cutter 60 cuts the web 17 along lines 30-1, 30-2, etc. to
10 form the individual wrapper portions 42. In the example shown in Figure 16, the leading and trailing edges 42a, 42b of each wrapper portion 42 have been heavily embossed e.g. with pin embossing to render the leading and trailing edges pliable so that they can easily be rolled on top of one another during the rolling process previously described that occurs on the rollers 41, 43. The cut lines 30-1, 30-2 may be arranged so
15 that the leading and trailing edges are of the same dimension, or the heavily embossed leading and trailing edges 42a, 42b may be made of different sizes e.g. with the leading edge being made wider than the trailing edge or *vice versa*. A registration servo system (not shown) ensures that the cutting blades of the cutter 60 accurately position the cuts 30-1, 30-2 etc in the web 17.

20 Another example of cigarette with a fixed filter is illustrated in Figures 24 and 25. In this example, an embossed wrapper 61 is used as a plug wrap for a filter segment 62 that contains any suitable filtration material such as cellulose acetate tow 63, with or without additives such as flavourants or adsorbents. The embossed wrapper 61 may be
25 made from sheet material such as paper e.g. tipping paper with a weight of 40 gsm or more to give rise to a particularly well defined pattern when formed into the curved wrapper, particularly above 40, 45, 50, 55, 60, 70, 80 and 90 gsm and up to about 120 gsm Conveniently, the thickness of the paper is within a range of 50 μm - 115 μm for the range of weights 40 – 90 gsm.

30 The filter segment 62 is abutted against one end of a tobacco rod 2 that contains tobacco or like smokeable material 25 which is wrapped by an outer wrapper 26. In the example illustrated in Figures 24 and 25, the filter segment 62 is attached to the rod 2 by means of an attachment strip 64 which is adhered to the abutting ends of the filter segment 62 and rod 2. The attachment strip 64 may be made of paper or other suitable
35

sheet material and may for example include embossing or printing (not shown) to identify a particular brand of cigarette.

Another example is shown in Figures 26 and 27 in which the filter segment 62
5 described with reference to Figures 24 and 25, with its embossed plug wrap 61, abuts tobacco rod 2 and is held in place by a thin wrapper 65 that extends the entire length of the embossed plug wrap 61 and over the abutting end of the tobacco rod 2. The wrapper 65 may be a relatively thin paper material that is sufficiently compliant to adhere closely to the embossed pattern of facets on the plug wrap 61 so that the pattern
10 shows through the paper 65 and is thereby visually discernable from the outside. For example, the paper 65 may comprise tissue paper that have been pre-soaked in an aqueous adhesive.

A schematic illustration of a method of manufacturing a filter rod with an embossed plug wrap 61 containing a cellulose acetate tow 63 is illustrated in Figure 28. A web 65 that is provided with an embossed pattern e.g. facets 12 and heavily pin embossed side edges 66, 67, is fed through a guide 68, for instance the 'garniture' section of a filter making apparatus, that wraps the plug wrap around the tow 63 to form a cylindrical rod 68 that moves on a continuous basis in the direction of arrow C. The side edges 66, 67 are glued to one another by means of a glue gun 69. Alternatively, the side edges 66, 67 can be coated with glue upstream. The resulting rod 68 can then be cut into segments for use with individual cigarettes. The segments can be either of a length suitable for an individual cigarette as shown in Figures 24-27 or, can be cut in length suitable for two cigarettes manufactured back-to-back in a manner previously described with reference
20 to Figure 17, in which case the machine of Figure 17 is modified to apply either the wrapper 64 or 65. In a modification, the tow 63 is initially wrapped with a relatively lightweight plug wrap and the web 17 is applied as shown in Figure 28 over the pre-wrapped tow.
25

30 An example of the web of embossed plug wrap 61 is illustrated with the heavily embossed side edge regions 66, 67 clearly shown, comprising longitudinal lines of embossing at the side edges more compliant and suited to gluing with a glue gun e.g. with PVA as shown in Figure 28.
35 Figure 29 illustrates another example of an embossed wrapper 61 that can be used to manufacture a filter rod of a length corresponding to 4 filter rod segments for

individual cigarettes, and Figure 30 illustrates the filter rod formed from the wrapper of Figure 29, with the pattern of facets 12 clearly shown. The facets 12 may be formed by the use of a die arrangement (not shown) comprising die members that can impress the pattern of facets 12 into web 61. The longitudinal side edges 66, 67 comprise lap seams that are line embossed for example by the use of a suitable die arrangement (not shown). To form the filter rod, the wrapper 61 of Figure 29 is wrapped around a tow of filter material and the lap seams 66, 67 are overlapped and glued to one another. A glue gun similar to that shown in Figure 28 may be used either with a PVA glue or a hot melt.

10

The resulting filter rod is also shown in Figure 31. Figure 31A shows the pattern of facets 12 clearly whereas Figure 31B illustrates the seam that results from the seam bonding produced by the glue gun of the heavily embossed lap seam edge regions 66, 67. In the example shown in Figures 29, 30 and 31, the rod is of the length $4xl$ corresponding to 4 filter rod segments of length l for individual cigarettes. The filter plug can be used to form individual cigarettes for example as illustrated in Figures 26 and 27 in which a filter segment 62 of length l is attached to a tobacco rod 2 by a thin, overlying wrapper of tipping paper 65. The arrangement is also shown in Figure 32A, and in Figure 32B, the seam formed by the line embossed lap seam edge regions 66, 67 is clearly shown. The line embossed edge regions are radially compliant in relation to the filter rod so that they can readily conform the curvature of the filter rod so as to provide a lap seam along their longitudinal side edges and provide a glue joint that is longitudinally consistent and airtight to provide a user acceptable filter action in the eventual cigarette. Also, the longitudinal line embossing in the lap seam edge regions 66, 67 permits a rod of improved circularity when viewed in transverse section, and due to the overlapping longitudinal side edges, is smooth to the touch for the user of a cigarette incorporating the filter. Also, there is no requirement to align the facets 12 and improved adhesion is achieved.

30 Figure 33 illustrates another example of plug wrap 61 that can be used. In this example, the plug wrap 61 is embossed as previously described to provide the pattern of facets 12 and the line embossed lap seam edge regions 66, 67. The plug wrap 61 of Figure 33 is also embossed with a transverse line embossed region 72 that extends transversely across the plug wrap so as to be repeated at a distance of $2l$. As previously explained with reference to Figures 18 and 19, the filter plug can be used to form pairs of cigarettes back-to-back and the transverse line embossed region 72 is configured so as

to provide an embossed region adjacent the join of the filter to the tobacco rod so as to provide a convenient grip for the fingers of the user. The resulting embossed filter rod is illustrated in more detail in Figure 34 and Figure 35A, with the lap seam edges 66, 67 shown in detail in Figure 35B.

5

The resulting filter cigarette is illustrated in Figures 36A, B with the line embossed regions 72 abutting the tobacco rod 2. The tipping paper 65 used to attach the filter segment 12 to the tobacco rod 2 can be of different widths to cover only a small extent of the filter segment as shown in Figure 36A or may extend over progressively larger 10 parts of the filter segment as shown in Figures 36C and D or to cover the entire filter surface as shown in Figure 36E.

The papers used in the production of the plug wraps 61 shown in Figures 29 and 34 may comprise a stiff, non-porous plug wrap having a weight in the range of 80-200 15 gsm, more particularly 80-150gsm or 90-150gsm and, by way of example 100-130gsm. Specific examples include 100gsm, 115gsm and 125gsm for papers supplied by Defort Feurstein to provide filter segments of length $l = 27\text{mm}$. With the circumference of 24.3mm, it has been found that an increase of the paper weight in gsm within the aforesaid ranges, results in a reduced likelihood of leak paths through the filter 20 occurring in the region 72 and providing a better adhesion of the plug wrap at the filter end. Also, the increased weight may tend to reduce bulging that can be caused by the pressure of compressed tow within the filter rod during manufacture of the rod.

The fixed filter cigarettes described above may comprise a combination of two or more 25 different segments of filtration material. For example, with reference to the cigarette of Figures 14 and 15, the generally cylindrical filter segment 3 may be formed of a charcoal filter segment abutting a segment of cellulose acetate, wrapped together in the plug wrap 28. Alternatively, each of the different segments of filtration material may be 30 separately wrapped in plug wrap, and the tipping wrapper 29 may attach the combined filtration segments to the tobacco rod 2.

Moreover, with reference to the cigarette of Figures 24 and 25, the filter segment 62 may be formed of two or more different segments of filtration material wrapped together in the embossed wrapper 61. Alternatively, each of the different segments of 35 filtration material may be separately wrapped in plug wrap, and held together by the embossed wrapper 61.

Furthermore, with reference to the cigarette of Figures 26, 27, 32A, 32B and 36A to 36E, the filter segment 62 may be formed of two or more different segments of filtration material wrapped together in the embossed wrapper 61. Alternatively, each of 5 the different segments of filtration material may be separately wrapped in plug wrap, and held together by the embossed wrapper 61. As a further alternative, each of the different segments of filtration material may be separately wrapped in embossed wrapper 61, and may be held together by the thin wrapper 65.

10 Many modifications and variations to the described smoking articles and their components fall within the scope of the invention. For example, the lines of weakness 10 can be formed on the outside of the wrapper to achieve the visually discernable facets 12.

15 The production of the lines of strength discontinuity may involve burning to produce a discernable pattern around the perimeters of the facets to enhance the visual effect. For example the cutting may involve burning. Also, the burning can mimic printing to permit logos and the like to be applied to the wrapper.

20 Also, a structural coating such as a varnish can be applied e.g. by printing onto the paper to rigidify the paper and thereby define the facets. This could be printed on the inside or outside depending on the finish required. Alternatively, the varnish can be printed in lines to form borders around the facets.

25 Also, the lines of strength discontinuity need not be lines of weakness and can be lines of strength formed for example by printing patterns of starch onto the sheet material in order to produce local stiffening.

In order to address various issues and advance the art, the entirety of this disclosure 30 shows by way of illustration various embodiments in which the claimed invention(s) may be practiced and provide for superior wrappers, plug wraps, filters and smoking articles and methods of making them. The advantages and features of the disclosure are of a representative sample of embodiments only, and are not exhaustive and/or exclusive. They are presented only to assist in understanding and teach the claimed 35 features. It is to be understood that advantages, embodiments, examples, functions, features, structures, and/or other aspects of the disclosure are not to be considered

limitations on the disclosure as defined by the claims or limitations on equivalents to the claims, and that other embodiments may be utilized and modifications may be made without departing from the scope and/or spirit of the disclosure. Various embodiments may suitably comprise, consist of, or consist essentially of, various 5 combinations of the disclosed elements, components, features, parts, steps, means, etc. In addition, the disclosure includes other inventions not presently claimed, but which may be claimed in future.

Claims

1. A smoking article component including a curved sheet wrapper of weight 40 gsm or more that includes a plurality of lines of strength discontinuity whereat the 5 wrapper presents a visually discernable non-uniformity in its curvature.
2. A smoking article component according to claim 1 wherein the wrapper has a weight of at least 45, 50, 55, 60, 70, 80 or 90 gsm.
- 10 3. A smoking article component according to claim 1 or 2 wherein the thickness of the wrapper is within a range of 50 µm - 115 µm.
4. A smoking article component according to claim 1 or 2 wherein the wrapper has a weight of up to about 120 gsm.
- 15 5. A smoking article including a smoking article component according to any preceding claim and comprising at least one of a filter and a tobacco rod with a curved surface that is wrapped with the sheet wrapper.
6. A smoking article according to claim 5 wherein the filter includes a plugwrap and the wrapper overlies at least part of the plugwrap and the tobacco rod to join them 20 together.
7. A smoking article according to claim 5 wherein the filter includes a plugwrap made of the sheet material.
8. A method of making smoking article including wrapping a sheet wrapper of 25 weight 40 gsm or more around the article, the wrapper including a plurality of lines of strength discontinuity such that the wrapper bends and presents a visually discernable non-uniformity in its curvature.
9. A method according to claim 8 including forming the lines of strength discontinuity.
- 30 10. A method of making smoking article including:
providing sheet wrapper material that includes a plurality of lines of strength discontinuity to define a visually discernable pattern;

passing the sheet material over a curling roller to weaken the wrapper to promote curling thereof around the smoking article, the curling roller including a curling roller surface pattern corresponding to the pattern of the wrapper sheet material, and being configured so that the patterns rotate in substantial synchronism;
5 and

wrapping the sheet wrapper around the article.

11. A method according to claim 10 wherein the curling roller is freely rotatable and said patterns engage one another to tend to rotate in synchronism.

10

12. A machine for making smoking articles including:
a curling station;
a feed arrangement to feed to the curling station a sheet wrapper material that includes a plurality of lines of strength discontinuity to define a visually discernable
15 pattern;

a rotary curling roller at the curling station, the curling roller being operable to weaken the wrapper to promote curling thereof around the smoking articles, the curling roller including a curling roller surface pattern corresponding to the pattern of the wrapper sheet material, and being configured so that the patterns rotate in substantial
20 synchronism; and

an arrangement to wrap the sheet material from the curling station around the smoking articles.

13. A method of configuring a machine for making smoking articles to operate with
25 a sheet wrapper material that includes a plurality of lines of strength discontinuity to define a visually discernable pattern, the machine including:
a curling station; a feed arrangement to feed to a sheet wrapper material to the curling station; and an arrangement to wrap the sheet material from the curling station around the smoking articles; and the method including:

30 fitting a rotary curling roller to the curling station, the curling roller being operable to weaken the wrapper to promote curling thereof around the smoking articles, the curling roller including a curling roller surface pattern corresponding to the pattern of the wrapper sheet material, and being configured so that the patterns rotate in substantial synchronism.

35

14. A machine for making smoking articles fitted with a curling roller by the method of claim 13.

15. A rotary curling roller for use at the curling station in a cigarette making machine, the curling roller being operable to weaken the wrapper to promote curling thereof around the smoking articles, the curling roller including a curling roller surface pattern for corresponding to the pattern of a wrapper sheet material, and being configured so that the patterns can rotate in substantial synchronism.

16. A wrapper for a smoking article filter comprising a curved sheet wrapper of weight 80 gsm or greater that includes a plurality of lines of embossing such that the wrapper presents a visually discernable non-uniformity in its curvature, and includes lap seams along opposite side edges that include lines of weakness that permit intimate abutment of side edges of the wrapper around the filter.

17. A wrapper according to claim 1 wherein the wrapper has a weight of at least 90, 100, 115, 120, 125, 130 gsm.

18. A wrapper according to claim 1 or 2 wherein the wrapper has a weight in the range of 80 – 150 gsm, 80 – 200 gsm, 90 – 150 gsm or 100 – 130 gsm.

19. A wrapper according to claim 1 or 2 wherein the thickness of the wrapper is within a range of 50 µm - 115 µm.

20. A wrapper according to claim 1 or 2 wherein the thickness of the wrapper is not more than 200 µm.

21. A smoking article component according to any one of claims 1 to 4 or a wrapper according to any one of claims 16 to 19 wherein the plurality of lines of strength discontinuity comprises lines of weakness.

22. A smoking article component according to any one of claims 1 to 4 or a wrapper according to claim 21 wherein the lines of weakness comprise partial cuts into the thickness of the sheet material.

23. A smoking article component according to any one of claims 1 to 4 or a wrapper according to claim 22 wherein the partial cuts are on the side of the sheet material that faces inside.
24. A smoking article component according to any one of claims 1 to 4 or a wrapper according to claim 21 or 22 wherein the partial cuts have been formed by laser cutting.
25. A smoking article component according to any one of claims 1 to 4 or a wrapper according to claim 21 wherein the lines of weakness comprise lines of embossing.
26. A smoking article component according to any one of claims 1 to 4 or a wrapper according to any one of claims 16 to 20 wherein the lines of strength discontinuity define an array of the facets over the sheet wrapper.
27. A smoking article component according to any one of claims 1 to 4 or a wrapper according to any one of claims 16 to 20 wherein the lines of strength discontinuity intersect or merge to define facets having a closed shape.
28. A smoking article component according to any one of claims 1 to 4 or a wrapper according to any one of claims 16 to 27 comprising a generally rectangular web of sheet material embossed with a regular pattern of facets and side edges formed with line embossing in the regions of the lap seams.
29. A smoking article component according to any one of claims 1 to 4 or a wrapper according to claim 28 including spaced bands of line embossing extending transversely across the web.
30. A filter rod including the smoking article component according to any one of claims 1 to 4 or a wrapper according to any one of claims 16 to 29 as a plug wrap.
31. A smoking article including a segment of filter rod according to claim 15 and a tobacco rod, wherein a wrapping overlies at least part of the plug wrap wrapper and the tobacco rod so as to join them together.
32. A method of making a filter including wrapping the smoking article component according to any one of claims 1 to 4 or a wrapper according to any one of claims 16 to 32 around filter material to form a filter rod.
33. A method according to claim 32 including cutting the filter rod into segments

34. A method according to claim 33 wherein at least one of the filter rod segments has line embossing extending longitudinally in a band that surrounds the filter segment at one end.

35. A wrapper for a smoking article filter comprising a sheet wrapper of weight 80 gsm or greater that includes a plurality of lines of embossing such that the wrapper presents a visually discernable non-uniformity in its curvature.

36. A wrapper according to claim 20 wherein the wrapper has a weight of at least 90, 100, 115, 120, 125, 130 gsm.

37. A wrapper according to claim 20 or 21 wherein the wrapper has a weight in the range of 80 – 150 gsm, 80 – 200 gsm, 90 – 150 gsm or 100 – 130 gsm.

38. A wrapper according to claim 20, 21 or 22 wherein the thickness of the wrapper is within a range of 50 μm - 115 μm .

39. A wrapper for a smoking article filter comprising a sheet wrapper that includes a plurality of lines of embossing such that the wrapper presents a visually discernable non-uniformity in its curvature, and includes lap seams along opposite side edges that include lines of weakness that permit intimate overlying abutment of side edges of the wrapper around the filter.

40. A wrapper according to claim 39 and comprising a plug wrap.




FIG. 1




FIG. 2a




FIG. 2b




FIG. 3




FIG. 4






FIG. 5






FIG. 8




FIG. 9

5 / 20




FIG. 10




FIG. 11




FIG. 12




FIG. 13

7 / 20




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 21A




FIG. 21B




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 24




FIG. 25




FIG. 26




FIG. 27






FIG. 28

16 / 20



17 / 20




FIG. 31A




FIG. 31B




FIG. 32A






FIG. 32B






FIG. 35A




FIG. 35B




FIG. 36A




FIG. 36B




FIG. 36C




FIG. 36D




FIG. 36E

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2013/071592

A. CLASSIFICATION OF SUBJECT MATTER
INV. A24D1/02
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A24D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|-----------|---|-----------------------|
| A | EP 1 475 003 A1 (JAPAN TOBACCO INC [JP]) 10 November 2004 (2004-11-10) the whole document ----- A GB 2 479 775 A (BRITISH AMERICAN TOBACCO CO [GB]) 26 October 2011 (2011-10-26) the whole document ----- A DE 20 2005 020337 U1 (HRUSCHKA ULRICH [DE]) 16 February 2006 (2006-02-16) the whole document ----- | 1-40 |
| | | 1-40 |
| | | 1-40 |



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

| | |
|--|--|
| Date of the actual completion of the international search | Date of mailing of the international search report |
| 8 January 2014 | 15/01/2014 |
| Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016 | Authorized officer Cardan, Cosmin |

INTERNATIONAL SEARCH REPORT

Information on patent family members

| |
|------------------------------|
| International application No |
| PCT/EP2013/071592 |

| Patent document cited in search report | Publication date | Patent family member(s) | | | Publication date |
|---|------------------|-------------------------|--|--|------------------|
| EP 1475003 | A1 10-11-2004 | AU 2003244460 A1 | | | 02-09-2003 |
| | | CA 2474924 A1 | | | 14-08-2003 |
| | | CN 1625349 A | | | 08-06-2005 |
| | | EP 1475003 A1 | | | 10-11-2004 |
| | | JP 3858024 B2 | | | 13-12-2006 |
| | | RU 2259153 C1 | | | 27-08-2005 |
| | | TW 592642 B | | | 21-06-2004 |
| | | UA 74737 C2 | | | 15-11-2004 |
| | | US 2005000533 A1 | | | 06-01-2005 |
| | | WO 03065828 A1 | | | 14-08-2003 |
| <hr style="border-top: 1px dashed black;"/> | | | | | |
| GB 2479775 | A 26-10-2011 | AR 083717 A1 | | | 20-03-2013 |
| | | CN 103108745 A | | | 15-05-2013 |
| | | EP 2563587 A1 | | | 06-03-2013 |
| | | GB 2479775 A | | | 26-10-2011 |
| | | KR 20130097641 A | | | 03-09-2013 |
| | | TW 201210519 A | | | 16-03-2012 |
| | | US 2013139837 A1 | | | 06-06-2013 |
| | | WO 2011131529 A1 | | | 27-10-2011 |
| <hr style="border-top: 1px dashed black;"/> | | | | | |
| DE 202005020337 U1 | 16-02-2006 | NONE | | | |
| <hr style="border-top: 1px dashed black;"/> | | | | | |

摘要

一种吸烟制品部件包括重量 40gsm 或以上的弯曲的片材包裹物，所述片材包裹物包括多根强度不连续线，在所述多根强度不连续线处，所述包裹物呈现出在其曲率上的视觉上可辨别的不均匀性。所述包裹物可用于例如作为用于过滤器的滤棒成型纸包裹香烟的过滤器，以便包括重量 80gsm 或以上的包裹物。