

(19) **DANMARK**

(10) **DK/EP 3085522 T3**



(12)

Oversættelse af europæisk patentskrift

Patent- og
Varemærkestyrelsen

-
- (51) Int.Cl.: **B 29 C 73/16 (2006.01)** *B 29 L 30/00 (2006.01)*
- (45) Oversættelsen bekendtgjort den: **2021-10-11**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2021-07-14**
- (86) Europæisk ansøgning nr.: **16166504.7**
- (86) Europæisk indleveringsdag: **2016-04-21**
- (87) Den europæiske ansøgnings publiceringsdag: **2016-10-26**
- (30) Prioritet: **2015-04-23 TW 104113113**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Chou, Wen-San, No. 1-25, Kangwei , An-Din District, Tainan City, Taiwan**
- (72) Opfinder: **Chou, Wen-San, No. 1-25, Kangwei , An-Din District, Tainan City, Taiwan**
- (74) Fuldmægtig i Danmark: **Budde Schou A/S, Dronningens Tværgade 30, 1302 København K, Danmark**
- (54) Benævnelse: **Luftkompressor**
- (56) Fremdragne publikationer:
EP-A1- 2 497 627
EP-A1- 2 657 008
CN-S- 303 169 442
DE-A1-102010 010 361
DE-A1-102011 018 927

DESCRIPTION

(a) Technical Field of the Invention

[0001] The present invention relates to an air compressor, which includes a box and a compressor unit installed in the box, wherein the box is provided with a connection socket, and the compressor unit has an outlet exposed to the connection socket, whereby an external device, such as a hose or a sealant bottle, can be firmly and detachably onto the connection socket of the box, and can be connected between the outlet of the compressor unit and the air nozzle of a tire, so that the tire can be inflated or repaired safely and effectively.

(b) Description of the Prior Art

[0002] Conventional air compressors for inflating and repairing tires generally include a box accommodating therein a compressor unit, a sealant bottle containing therein a chemical sealant for repairing punctures of tires and provided with a cap for sealing its mouth, and two hoses, wherein the cap is provided with an inlet connector and an outlet connector, one hose can be connected between the outlet of the compressor unit and the inlet connector of the sealant bottle, and the other hose can be connected between the outlet connector of the sealant bottle and the air nozzle of a punctured tire. For example, document DE 10 2010 010 361 A1 discloses a conventional device for introducing air and / or sealing agent in a tire, wherein said device comprises a container for the sealing means having an inlet and an outlet, wherein the outlet can be connected to the inlet end of a hose, whose outlet is connected to the tire to be filled. The device further comprises pressure generating means, such as an electric pump or a compressor, installed in a box, wherein the pressure generating means is selectively connectable to the inlet of the container or to the inlet end of the hose whose outlet is connected to the tire to be filled. The pressure generating means, the inlet and outlet of the sealant container and the inlet of the hose are therefore formed with corresponding coupling means.

[0003] DE 10 2011 018927 A1 discloses an air compressor according to the preamble of claim 1.

[0004] However, among those conventional air compressors, the compressor units thereof only allow a specific type of hose or sealant bottle to be applied for inflating or repairing a tire.

[0005] For solving the disadvantage of conventional air compressors, the applicant has contrived an improved air compressor, wherein the outlet of the compressor unit is exposed to a connection socket of the box, whereby an external device, such as a hose or a sealant bottle, can be firmly and detachably assembled onto the connection socket of the box and connected between the outlet of the compressor unit and the air nozzle of a tire for inflating or repairing

the tire.

SUMMARY OF THE INVENTION

[0006] One object of the present invention is to provide an air compressor, which comprises a box and a compressor unit installed in the box, wherein the box is provided with a connection socket, and the compressor unit has an outlet exposed to the connection socket of the box, whereby an external device can be firmly and detachably assembled onto the connection socket of the box and connected between the compressor unit and a tire, so that the tire can be inflated or repaired the tire effectively and safely.

[0007] According to one feature of the present invention, the external device assembled onto the connection socket of the box is a hose, one end of which is connected with the outlet of the compressor unit, and the other end of which is connected with a tire, so as to inflate the tire.

[0008] According to another feature of the present invention, the external device assembled onto the connection socket of the box is a sealant bottle having an inlet connector and an outlet connector, wherein the inlet connector of the sealant bottle is directly connected with the outlet of the compressor unit, and the outlet connector of the sealant bottle is connected to the air nozzle of a punctured tire by using a hose therebetween, whereby compressed air from the outlet of the compressor unit can be delivered into the sealant bottle to force the chemical sealant contained in the sealant bottle to flow into the punctured tire, thus inflating and repairing the punctured tire.

[0009] According to a further feature of the present invention, the external device assembled onto the connection socket of the box is a sealant bottle having an inlet connector and an outlet connector, wherein the inlet connector of the sealant bottle is connected to the outlet of the compressor unit by using a first hose therebetween, and the outlet connector of the sealant bottle is connected to the air nozzle of a punctured tire by using a second hose therebetween, whereby compressed air from the outlet of the compressor unit can be delivered into the sealant bottle to force the chemical sealant contained in the sealant bottle to flow into the punctured tire, thus inflating and repairing the punctured tire.

[0010] Other objects, advantages, and novel features of the present invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011]

FIG. 1 shows an exploded view of an air compressor according to a first example according to

the present disclosure, wherein a hose and a box accommodating therein a compressor unit are included.

FIG. 2 shows a working view of the first example of the air compressor, wherein the hose is connected to the outlet of the compressor unit inside the box.

FIG. 3 shows another working view of the first example of the air compressor, wherein the hose is stored at the back of the box.

FIG. 4 shows an exploded view of an air compressor according to a second example according to the present disclosure, wherein a sealant bottle, a hose, and a box accommodating therein a compressor unit are included.

FIG. 5 shows a working view of the second example of the air compressor, wherein the sealant bottle is directly connected to the outlet of the compressor unit inside the box.

FIG. 6 shows a front view of the second example of the air compressor, wherein the sealant bottle is directly connected to the outlet of the compressor unit inside the box.

FIG. 7 shows an exploded view of an air compressor according to a preferred embodiment of the present invention, wherein a sealant bottle, two hoses, and a box accommodating therein a compressor unit are included.

FIG. 8 shows a working view of the preferred embodiment of the air compressor, wherein the sealant bottle is connected to the outlet of the compressor unit inside the box by using a hose.

FIG. 9 shows another working view of the preferred embodiment of the air compressor, wherein the hose for connecting between the sealant bottle and the outlet of the compressor unit is stored at the back of the box.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0012] Referring to FIGS. 1 and 2, an air compressor according to a first example of the disclosure is shown, which generally comprises a box 1 and a compressor unit installed in the box 1. The box 1 is provided with a connection socket 11 defining a recessed space which vertically and horizontally opens onto ambient environment of the box 1. The compressor unit has an outlet 10 exposed to the connection socket 11 for being connected with an external device which can be in turn connected to the air nozzle of a tire for inflating or repairing the tire. The compressor unit can be electrically connected to a DC power supply, such as a cigarette lighter receptacle, in a vehicle or an individual DC power supply for starting the compressor unit.

[0013] Referring again to FIG. 1, the recessed space of the connection socket 11 is substantially U-shaped in horizontal cross section. As shown, the recessed space of the

connection socket 11 is defined by two opposite sides 110 and a bottom surface between the two opposite sides 110, wherein each side of the recessed space of the connection socket 11 is provided with a guiding means which defines a curved groove 13 extending generally towards the outlet 10 of the compressor unit. The two guiding means at the two opposite sides 110 of the recessed space of the connection socket 11 are opposite to each other. Specifically, the curved groove 13 of each guiding means is defined by a delimiting strip 14 which forms as a top of the corresponding side of the recessed space of the connection socket 11, wherein each delimiting strip 14 is provided with an engagement block 15 thereon. Furthermore, each side of the recessed space of the connection socket 11 defines an engagement recess 12 below the curved groove 13, so that the aforementioned external device can be firmly and detachably assembled onto the connection socket 11 more firmly. The bottom surface between the two opposite sides 110 of the connection socket 11 has a recessed surface 18. In addition, the box 1 defines a receiving space 17 at its back (see FIG. 3), and a passage 16 which communicates with the recessed space of the connection socket 11 and the receiving space 17.

[0014] In the first example, the external device is implemented as a hose 2 which has a first end 21 for being connected with the outlet 10 of the compressor unit. Particularly, the hose 2 is provided at its first end 21 with a bottom plate 211 which can be fitted onto the recessed surface 18 formed on the bottom surface of the connection socket 11. Thus, in connecting the hose 2 to the outlet 10 of compressor unit, the bottom plate 21 can guide the first end 21 of the hose 2 to move towards the outlet 10 of the compressor unit, so that the hose 2 can be connected to the outlet 10 of the compressor unit more easily. The hose 2 has a second end 22 which can be connected to the air nozzle of a tire for inflating the tire (not shown). After the inflation is completed, the hose 2 can be detached from the outlet 10 of the compressor unit, and then can be stored in the receiving space 17 at the back of the box 1 (see FIG. 3).

[0015] Referring to FIG. 4, there is shown a second example, wherein the external device is implemented as a sealant bottle 3, which includes a container body 31 containing therein a chemical sealant for repairing punctures of tires, and a cap 4 for sealing an opening of the container body 31. The cap 4 has an inlet connector 41 and an outlet connector 42, both of which communicate with an inner space of the container body 31. The cap 4 is provided with two opposite guiding means and two opposite resilient strips 46. Each guiding means is composed of two parallel, spaced projections, including a first projection 43 and a second projection 44 corresponding to the curved grooves 13 of the connection socket 11, wherein a channel 45 is defined between the two projections 43, 44 of each guiding means, and each resilient strip 46 is provided with an engagement protrusion 47 corresponding to the engagement recesses 12 of the connection socket 11. In use, the sealant bottle 3 can be inverted so that its bottom 32 is above the associated cap 4 for being assembled onto the connection socket 11 of the box 1 (see also FIGS. 5 and 6), wherein the inlet connector 41 of the cap 4 is directly connected to the outlet 10 of the compressor unit, the delimiting strips 14 of the connection socket 11 are inserted into the channels 45 between the two projections 43, 44 of the cap 4, the second projections 44 of the cap 4 are inserted into the curved grooves 13 of the connection socket 11, and the engagement protrusions 47 of the resilient strips 46 are

engaged with the engagement recesses 12 of the connection socket 11. Since the delimiting strips 14 of the two opposite guiding means of the connection socket 11 are inserted into the channels 45 between the two projections 43, 44, and the engagement protrusions 47 of the resilient strips 46 are engaged with the engagement recesses 12 of the connection socket 11, the sealant bottle 3 can be firmly assembled onto the connection socket 11 of the box 1, and thus can be prevented from felling off due to vibration or impact. Furthermore, the outlet connector 42 of the cap 4 can be connected to a punctured tire by using a hose 2 therebetween, wherein the first end 21 of the hose 2 can be connected with the outlet connector 42 of the cap 4, and the second end 22 of the hose 2 can be connected with the air nozzle of a punctured tire (not shown). When the air compressor is started, compressed air can be delivered into the sealant bottle 3 via the outlet 10 of the compressor unit, and thus the chemical sealant contained in the sealant bottle 3 can be forced to flow into the punctured tire via the hose 2, so that the punctured tire can be inflated and repaired. After the inflation and repair is completed, the user may depress the resilient strip 46 of the cap 4 and thus can remove the sealant bottle 3 together with the cap 4 out of the connection socket 11 of the box 1, so that the sealant bottle 3 can be disconnected from the outlet 10 of the compressor unit (see FIG. 4).

[0016] Referring to FIG. 7, there is shown a preferred embodiment of the present invention, wherein the external device is implemented as a sealant bottle 6, which includes a container body 51 containing therein a chemical sealant for repairing punctures of tires, and a cap 6 for sealing an opening of the container body 51. The cap 6 has an inlet connector 61 and an outlet connector 62, both of which communicate with an inner space of the container body 51. Furthermore, the cap 6 is provided with two opposite guiding means as the cap 3 of the second example. Each guiding means is composed of two parallel, spaced projections, including a first projection 63 and a second projection 64 corresponding to the curved grooves 13, wherein a channel 65 is defined between the two projections 63, 64 of each guiding means. In use, the sealant bottle 5 can be inverted so that its bottom 52 is above the associated cap 6. The inverted sealant bottle 5 can be placed on the ground to work with the compressor unit inside the box 1. Preferably, the inverted sealant bottle 5 can be assembled onto the connection socket 11 of the box 1 (see FIG. 8), wherein the inlet connector 61 is connected to the inlet 10 of the compressor unit by using a first hose 7 therebetween (i.e., one end of the hose 7 is connected with the outlet 10 of the compressor unit while the other end of the hose 7 is connected with the inlet connector 61 of the cap 6), the delimiting strips 14 of the two guiding means of the connection socket 11 are inserted into the channels 65 between the two projections 63, 64 of the cap 6, the second projections 64 of the cap 6 are inserted into the grooves 13 of the connection socket 11, and rear edges 631 of the first projection 63 of the cap 6 are engaged with the engagement blocks 15 provided on the delimiting strips 14 of the connection socket 11. Since the delimiting strips 14 of the two guiding means of the connection socket 11 are inserted into the channels 65 between the two projections 63, 64 of the cap 6, and the rear edges 631 of the first projections 63 are engaged with the engagement blocks 15 provided on the delimiting strips 14 of the two guiding means of the connection socket 11, the sealant bottle 5 can be firmly assembled onto the connection socket 11 of the box 1, and thus can be prevented from felling off due to vibration or impact. Furthermore, the outlet connector

62 of the cap 6 can be connected to a punctured tire by using a second hose 8 therebetween, wherein the first end 81 of the second hose 8 is connected with the outlet connector 62 of the cap 6, whereas the second end 82 of the second hose 8 is connected with the air nozzle of the punctured tire (not shown). When the air compressor is started, compressed air can be delivered into the sealant bottle 5 via the outlet 10 of the compressor unit and the first hose 7, and thus the chemical sealant contained in the sealant bottle 5 can be forced to flow into the tire via the second hose 8, so that the punctured tire can be inflated and repaired. After the inflation and repair is completed, the user can slightly lift the cap 6 to disengage the rear edges 631 of the first projections 63 from the engagement blocks 15 provided on the delimiting strips 14 of the connection socket 11, so that the sealant bottle 5 can be disassembled from the connection socket 11 of the box 1. Next, the user can detach the first hose 7 from the inlet connector 61 of the cap 6 (see FIG. 7). Finally, the first hose 7 can be routed through the passage 16 to be stored in the receiving space 17 at the back of the box 1 (see FIG. 9).

[0017] As a summary, the air compressor of the present invention includes a box 1 and a compressor unit installed in the box 1, wherein the box 1 is provided with a connection socket 11, and the compressor unit has an outlet 10 exposed to the connection socket 11. As such, an external device, such as a hose or a sealant bottle, can be firmly assembled onto the connection socket 11 of the box 1, and then the external device can be connected to a tire, so that the tire can be inflated or repaired safely and effectively.

REFERENCES CITED IN THE DESCRIPTION

Cited references

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- [DE102010010361A1](#) [0002]
- [DE102011018927A1](#) [0003]

PATENTKRAV

1. Luftkompressor, som omfatter et hus (1) og en kompressorenhed installeret i huset (1), hvor huset (1) er forsynet med en forbindelsessokkel (11), som afgrænser et udsparet rum, som vertikalt og horisontalt udmunder i omgivelserne for huset (1), og kompressorenheden har et luftudløb (10), som er eksponeret til forbindelsessoklen (11) i huset (1),
- 5 hvor det udsparede rum for forbindelsessoklen (11) er i det væsentlige U-formet i et horisontalt tværsnit og er afgrænset af to modstående sider (110) og en bundflade imellem de to modstående sider (110); hvor hver side af det udsparede rum for forbindelsessoklen (11) afgrænser en not (13), som strækker sig hovedsageligt imod udløbet (10) for kompressorenheden, og definerer en indgrebsudsparing (12) under noten (13), og noten (13) på hver side af det udsparede rum for forbindelsessoklen (11) er afgrænset af en begrænsningsstrimmel (14), som danner en overside af den tilsvarende
- 10 side af det udsparede rum for forbindelsessoklen (11); huset (1) definerer et modtagerum (17) ved sin bagside;
- luftkompressoren omfatter yderligere en udvendig indretning, som er fast og aftageligt forbundet med forbindelsessoklen (11) i huset (1), hvilken udvendig indretning er forbundet imellem udløbet (10) for kompressorenheden og en luftdyse til et dæk til oppustning eller reparation af dækket;
- 20 hvor den udvendige indretning er en forseglingsmiddelflaske (5), som omfatter et beholderlegeme (51) og en hætte (6) til forsegling af en åbning i beholderlegemet (51), hvilken hætte (6) har en indløbsforbindelse (61) og en udløbsforbindelse (62), som begge står i forbindelse med et indvendigt rum i beholderlegemet (51), hvilken hætte (6) er
- 25 forsynet med to modstående føringsorganer, som hver især er sammensat af to parallelle i afstand beliggende fremspring, som omfatter et første fremspring (63) og et andet fremspring (64), hvor en kanal (65) er afgrænset imellem de to fremspring (64, 65) i hvert føringsorgan;
- hvorved forseglingsmiddelflasken (5) inverteres til at blive fast forbundet på forbindelsessoklen (11) i huset (1), hvor begrænsningsstrimlerne (14) i forbindelsessoklen (11) indsættes i kanalerne (65) imellem fremspringene (63, 64) på hætten (6), hvorved de andre fremspring (64) på hætten (6) indsættes i noten (3) i forbindelsessoklen (11);
- kendetegnet ved, at**
- hver begrænsningsstrimmel (14) er yderligere forsynet med en indgrebsblok (15) derpå;
- 35 og

huset (1) afgrænser yderligere en passage (16) under det udsparede rum for forbindelsessoklen (11), hvilken passage (16) står i forbindelse med det udsparede rum for forbindelsessoklen (11) og modtagerummet (17);

- 5 hvor indløbsforbindelsen (61) for hættten (6) er forbundet med indløbet (10) for kompressorenheden ved anvendelse af en slange (7) imellem disse, og bagkanter (631) på det første fremspring (63) i hættten (6) er i indgreb med indgrebsblokkene (15), som er tilvejebragt på begrænsningsstrimlerne (14) i forbindelsessoklen (11) i huset (1).

DRAWINGS




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9