

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization

International Bureau

(43) International Publication Date  
19 March 2020 (19.03.2020)



(10) International Publication Number  
**WO 2020/053864 A1**

(51) International Patent Classification:

A61F2/16 (2006.01) G02B 5/18 (2006.01)

(21) International Application Number:

PCT/IL20 19/051025

(22) International Filing Date:

12 September 2019 (12.09.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/730,769 13 September 2018 (13.09.2018) US

(71) Applicant: HANITA LENSES R.C.A. [IL/IL]; 2288500 Kibbutz Hanita (IL).

(72) Inventors: ATTIA, Mickael; 19/27 Kovshei Hahermon Street, 7655521 Rehovot (IL). BRODSKY, Alexander; 4/12 Nachlat Zvi Street, 4942108 Petah Tikva (IL). KAPLAN, Natan; 28/1 1 Aharon Lublin Street, 714713 1 Lod (IL). GROSSINGER, Israel; 18 Gefen Street, 9979700 Karmei Yossef (IL).

(74) Agent: SHORR, Ron et al.; GEYRA KESTEN, 100 Ha-Hashmonaim Street, P.O.Box 52630, 67133 17 Tel Aviv (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,


OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: MULTIFOCAL INTRAOCULAR LENS



(57) Abstract: A multifocal IOL including at least one diffractive surface including a plurality of discrete, adjacent, diffractive, concentric rings, having a radial phase profile cross-section with a near-symmetrical diffractive surface topography, and an odd number, greater than three, of diffractive orders and an asymmetrical distribution of energy flux over the diffractive orders.



WO 2020/053864 A1

## MULTIFOCAL INTRAOCULAR LENS

### CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of priority to U.S. Provisional Patent Application No. 62/730,769 filed September 13, 2018, entitled "MULTIFOCAL INTRAOCULAR LENS" the contents of which are incorporated herein by reference in their entirety.

### FIELD OF THE INVENTION

[0002] The present invention, in some embodiments thereof, relates to multiple focus intraocular lenses in general and, more particularly, but not exclusively to multi-focal, diffractive, intraocular ophthalmic lenses.

### BACKGROUND

[0003] An intraocular lens (IOL) is a lens implanted in the eye as part of a treatment for cataracts or myopia. The multifocal intraocular lenses (IOLs) available are often able to restore visual function and allow eyeglasses independence after their implantation with great levels of patient satisfaction.

[0004] Multifocal IOLs correct far-vision, near-sightedness and all mid-range distances. Multifocal IOLs improve near vision by dividing light in different focuses, which changes the vision physiology because of the light dispersion that happens when it enters into the eye. Modern multifocal IOLs provide a more physiological division of light and, in this way, optimize the eyeglasses independence and also provide better vision quality and less visual symptoms for the patient.

[0005] The foregoing examples of the related art and limitations related therewith are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent to those of skill in the art upon a reading of the specification and a study of the figures.

## SUMMARY

[0006] The following embodiments and aspects thereof are described and illustrated in conjunction with systems, tools and methods which are meant to be exemplary and illustrative, not limiting in scope.

[0007] There is provided, in accordance with some embodiments of the invention, a multifocal IOL including at least one diffractive surface including a plurality of discrete, adjacent, diffractive, concentric rings, having a radial phase profile cross-section with a near-symmetrical diffractive surface topography, and an odd number, greater than three, of diffractive orders. In some embodiments, the IOL includes an asymmetrical distribution of energy flux over the diffractive orders.

[0008] In some embodiments, the IOL includes five diffractive orders. In some embodiments, the diffractive surface includes diffractive steps designed to maintain the diffractive profile unchanged in between the steps, and wherein the diffractive steps are partially inside and partially outside the base curvature of the IOL.

In some embodiments, the diffractive, concentric rings include a repetitive pattern of diffractive profiles. In some embodiments, the profiles are asymmetrical.

[0009] In some embodiments, the diffractive rings include a repetitive pattern of a single diffractive profile. In some embodiments, the diffractive rings include a repetitive pattern of two different diffractive profiles, and wherein the diffractive rings include a single transition from a first zone having a repetitive pattern of one diffractive profile to a second peripheral zone having a repetitive pattern of a second diffractive profile.

[0010] In some embodiments, height of the diffractive surface topography of the second peripheral zone is maintained constant when advancing radially outwards in respect to the center height of the IOL. In some embodiments, the radial phase profile cross-section has an asymmetrical double-peaked geometry.

[0011] In some embodiments, thickness of the IOL is variable and the curvature is maintained. In some embodiments, thickness of the IOL is variable and the curvature is variable.

[0012] In addition to the exemplary aspects and embodiments described above, further aspects and embodiments will become apparent by reference to the figures and by study of the following detailed description.

#### BRIEF DESCRIPTION OF THE FIGURES

[0013] The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

[0014] Exemplary embodiments are illustrated in referenced figures. Dimensions of components and features shown in the figures are generally chosen for convenience and clarity of presentation and are not necessarily shown to scale. The figures are listed below.

[0015] Fig. 1A is a plan view simplified illustration of a multifocal IOL; and

[0016] Fig. 1B is a cross-section view simplified illustration of a diffractive surface of a multifocal IOF according to some embodiments of the present invention;

[0017] Fig. 2A is a radial, cross-section, simplified illustration of a diffractive surface topography of a portion of the IOF; and

[0018] Fig. 2B is a graph of distribution of energy flux (power) levels over specific diffractive orders associated with the diffractive surface topography shown in Fig. 2A;

[0019] Fig. 3A is a radial, cross-section, simplified illustration of a diffractive surface topography of a portion of the IOF; and

[0020] Fig. 3B is a graph of distribution of energy flux (power) levels over specific diffractive orders associated with the diffractive surface topography shown in Fig. 3A;

[0021] Fig. 4 is a graph superimposing two radial phase profiles in accordance with some examples of the invention;

[0022] Fig. 5A is a radial, cross-section, simplified illustration of a diffractive surface topography of a portion of the IOF;

[0023] Fig. 5B is a graph of distribution of energy flux (power) levels over specific diffractive orders associated with the diffractive surface topography shown in Fig. 5A;

[0024] Fig. 6 is a graph of a simulation of a through-focus Modulation Transfer Function (MTF) of the IOF in accordance with some embodiments of the invention; and

[0025] Fig. 7 is a simplified graph illustration depicting a profile of a diffractive portion of an exemplary lens in accordance with some embodiments of the current invention.

## DETAILED DESCRIPTION

[0026] For purposes of better understanding some embodiments of the present invention, as illustrated in Figures 1A to 6 of the drawings, reference is first made to the construction and operation of a multifocal intraocular lens (IOL).

[0027] Multifocal Intraocular lenses (IOL) are designed such that to produce one, two, three or more diffractive orders or foci on the optical axis such that each image focal point is formed on the retina when an object associated with the image is located at a corresponding distance from the eye. Most of the intraocular lenses are designed to have a refractive (lens) focal point and energy flux (power) that corresponds to far vision i.e. the spherical/aspherical surfaces of the lens are designed to focus an image of an object on the retina when the object is located at the far-sighted distance from the eye (>5-6 meters). The diffractive surfaces in most bifocal and trifocal lenses create additional foci at the near (30-40cm) and intermediate distances (60-80cm).

[0028] Most refractive-diffractive IOLs have the same general structure - a lens comprising multiple rings, each ring having a diffractive profile that is scaled to the ring width. The diffractive profiles are repeated along the radius for each Fresnel zone. In some cases, the rings are also scaled vertically (apodization).

[0029] According to an aspect of the invention there is provided an IOL comprising diffractive steps which are partially inside and partially outside the base curvature of the IOL. In some embodiments, the thickness of the IOL is variable and the curvature is constant. In some embodiments, change in curvature is produced by optimization of the sphericity between steps.

[0030] According to an aspect of some embodiments of the present invention there is provided an IOL that has a spherical surface and an aspherical surface. In some embodiments, the IOL comprises an asymmetrical number of active diffractive orders along the optical axis of the eye. In some embodiments, the IOL comprises more than three diffractive orders on the optical axis of the eye. In some embodiments, the IOL comprises five diffractive orders on the optical axis.

[0031] In some embodiments, the IOL comprises a diffractive pattern on one or more surfaces of the lens. In some embodiments, the diffractive pattern comprises a repetitive pattern of diffractive profiles. In some embodiments, the profiles are asymmetrical.

[0032] Reference is now made to Figs. 1A and 1B (not drawn to scale), in which Fig. 1A is a plan view simplified illustration of a multifocal IOL and Fig. 1B is a cross-section view simplified illustration of a diffractive surface of a multifocal IOL according to some embodiments of the present invention.

[0033] As shown in the exemplary embodiment depicted in Fig. 1A, An IOL 100 comprises a diffractive surface having a plurality of discrete, adjacent, diffractive, concentric sections or rings 102.

[0034] In some embodiments, the IOL diffractive surface comprises diffractive steps which are partially inside and partially outside the base curvature of the IOL. This induces changes in diffractive status between two steps. In some embodiments, the thickness of the IOL is variable but the curvature is maintained. In some embodiments, change in curvature is produced by optimization of the sphericity between steps.

[0035] Potential advantages in the described design are in that:

1. The designing of the diffractive steps does not change the diffractive profile in between the steps. This allows to have multifocal IOL of any added power and more efficiency for near focal lengths without losing contrast for distance.

2. Design of diffractive steps allows rays of light to be parallel to the step which is the ideal condition for diffraction.

[0036] In some embodiments, the rings are distributed along Fresnel zones (102-1/102-2). In some embodiments, and as shown in Fig. 1B, an IOL surface topography features repetitive triangular forms, squared forms or parabolic forms depending on the type of lens.

[0037] Reference is now made to Fig. 2A which is a radial, cross-section, simplified illustration of a diffractive surface topography of a portion of the IOL and Fig. 2B, which is a graph of distribution of energy flux (power) levels over specific diffractive orders associated with the diffractive surface topography shown in Fig. 2A.

[0038] Fig. 2A depicts a radial cross-section or radial phase profile 200 of a diffractive surface topography through a concentric ring. The specific cross-section of the radial phase profile is generated by using a Gerchberg-Saxton (GS) iterative algorithm. Fig. 2A depicts

an exemplary embodiment of a radial phase profile cross-section showing an asymmetrical double-peaked cross-section having a near-symmetric local diffractive surface topography. Radial phase profile 200 is converted to a height profile which is radially and parabolically integrated to each of the Fresnel zones (rings) of the diffractive lens with a specific focal length.

[0039] The authors of this disclosure have come to learn that symmetric local diffractive surface topography function combined with an odd number of diffraction diffractive orders e.g., 1, 3, 5, 7 or 9 diffraction diffractive orders, and specifically a number of diffraction diffractive orders greater than three increase the overall light transmission efficiency of the IOL above 90% and in some cases up to at least 93%.

[0040] In some embodiments, IOL 100 comprises five diffractive orders on the optical axis. In some embodiments, one of the diffractive orders e.g., the far vision focal length has a high energy flux level. In some embodiments, one of the diffractive orders is entirely suppressed. In some embodiments, the five diffractive orders or foci correspond to the following five diffractive orders: -2, -1, +1 and +2 which are diffracted diffractive orders produced by the diffractive pattern and a single order 0 which is the refractive power produced by the spherical / aspherical surfaces of the IOL. In some embodiments, the spherical / aspherical surfaces of the lens are designed such as to focus an image on the retina when the imaged object is located at an intermediate distance from the eye, between near vision (~30-40cm) and far vision (several meters).

[0041] In some embodiments, and as depicted in Fig. 2B, of the five diffractive orders, the diffractive order -2, corresponds to far vision has the highest energy flux level. In some embodiments, of the remaining diffractive orders, the diffractive order +2, which corresponds to near vision has the highest energy flux level. In this embodiment, the diffractive order -1 is suppressed.

[0042] Reference is now made to Fig. 3A which is a radial, cross-section, simplified illustration of a diffractive surface topography of a portion of the IOL and Fig. 3B, which is a graph of energy flux levels distribution over specific diffractive orders associated with the diffractive surface topography shown in Fig. 3A.

[0043] Figures 3A and 3B show a design different than that illustrated in Figures 2A and 2B however both have been designed using the same method of profile generation by using

a Gerchberg-Saxton (GS) iterative algorithm and conversion of the phase profile to a height profile which is radially and parabolically integrated to each of the Fresnel zones (rings) of the diffractive lens with a specific focal length.

[0044] Fig. 3A depicts an additional example of a radial cross-section or radial phase profile 300 of a diffractive surface topography through a concentric ring. Fig. 3A depicts an exemplary embodiment of a radial phase profile showing an asymmetrical double-peaked cross-section having a near-symmetric local diffractive surface topography. Radial phase profile 300 is converted to a height profile which is radially and parabolically integrated to each of the Fresnel zones (rings) of the diffractive lens with a specific focal length.

[0045] In some embodiments, and as depicted in Fig. 3B, of the five diffractive orders, the diffractive order -2, corresponds to far vision has the highest energy flux level. In some embodiments, of the remaining diffractive orders, the diffractive order +2, which corresponds to near vision has the highest energy flux level and the energy flux level at order 0 is higher than the energy flux level at diffractive order +1. In this embodiment, the diffractive order -1 is suppressed.

[0046] As shown in Fig. 4, which is a graph superimposing radial phase profile 300 over radial phase profile 200 demonstrates phase differences between the designs in accordance with some examples of the invention. When using this technique with more than 5 foci (for example 7), the diffractive focal length determines the location of the far focus (diffractive order -3) and near focus (diffractive order +3) and the refractive focal length (spherical surfaces) determines the location of one of the intermediate foci (order 0). In the exemplary embodiment depicted in Fig. 4, radial phase profile 200 comprises phases: 1, 0, 0.333, 0.38 and 0.637, wherein radial phase profile 300 comprises phases: 1, 0, 0.6, 0.45 and 0.65. In some embodiments, the IOL comprises two zones - a central zone 102-1 (Figs. 1A and Fig. 1B) and a peripheral zone 102-2. In some embodiments, the diffractive pattern of central zone 102-1 is not apodized. In some environments, the diffractive pattern of the peripheral zone 102-2 is not apodized. The height of the diffractive surface topography of zone 102-2 is maintained constant and does not have a gradual step height reduction when advancing radially outwards in respect to the center height of the IOL. This arrangement and design are planned in diffractive order to vary the intensity distribution when increasing the

aperture and allow increased light flux, even if not optimally focused, with pupil dilation (low intensity environmental) light.

[0047] A potential advantage in this design is in that the apodization design allows for diffraction efficiency near 100% thus minimizing loss of light.

[0048] For modifying the intensity distribution according to the aperture size, the technique used here is to change the diffractive pattern at any radius of the intraocular lens or at one of the Fresnel Zone (or near one of them) for better performance. For this invention, the design transition occurred at radius  $\sim 1.228\text{mm}$ .

[0049] As shown in Figs. 5A and 5B, in which Fig. 5A depicts an example of a radial cross-section or radial phase profile 500 of a diffractive surface topography through a concentric ring of the peripheral zone of the IOL in accordance with some embodiments of the invention. Fig. 5A depicts an exemplary embodiment of a radial phase profile cross-section at the IOL peripheral zone 102-2 showing an asymmetrical single-peaked cross-section having a near-symmetric local diffractive surface topography.

[0050] In some embodiments, a radial phase profile cross-section at the IOL peripheral zone 102-2 comprises an asymmetrical double-peaked cross-section having a near-symmetric local diffractive surface topography. Radial phase profile 500 is converted to a height profile which is radially and parabolically integrated to each of the Fresnel zones (rings) of the diffractive lens with a specific focal length.

[0051] In some embodiments, and as depicted in Fig. 5B, the flux energy level declines from the far diffractive order to the near diffractive order with two suppressed orders at -1 and +1.

[0052] The phase obtained at the source plane and used in the design (at radius  $> 1.228\text{mm}$ ) depicted in Figs. 5A and 5B is obtained using normalized target intensity [1, 0, 0.5, 0, 0.34] in the Gerchberg-Saxton (GS) algorithm.

[0053] However, in some embodiments, the other diffractive profile (after transition) can be a different diffractive design based on three or more foci and can be also a monofocal design with full energy at far vision or bifocal with energy at far vision and other foci at intermediate or near vision

[0054] Also, for fine tuning of the intraocular lens, the entire diffractive height profile (before and after transition from IOL zone 102-1 to IOL zone 102-2) can be tunable. In the

exemplary embodiment depicted in Figs. 5A and 5B, the first diffractive profile before the transition has been increased by 5% and the second diffractive profile after the transition has been increased by 12%. Our multifocal IOL, based on zero order for intermediate vision, has a high efficiency- over 90% - in the used diffractive orders (-2, -1, 0, 1, 2).

[0055] Reference is now made to Fig. 6, which is a graph of a simulation of a through-focus Modulation Transfer Function (MTF) of the IOL in accordance with some embodiments of the invention. As shown in the exemplary embodiment depicted in Fig. 5, three graphs are drawn for three levels of eye pupil diameter: graph 602 for a 2mm pupil diameter (i.e., intense light condition), graph 604 for a 4.5 mm pupil diameter (i.e., low light condition) and graph 606 for a 3 mm pupil diameter (i.e., normal light condition).

[0056] The graphs depicted in Fig. 6 exhibit the biphasic nature of the IOL at all three shown levels of environmental light however, as the level of environmental light decreases changing the pupil diameter from 2mm to 4.5mm, the MTF value correspondingly increases on the far-sighted range of the IOL, even though it is limited from a diopter range between approximately 22 and 24.5 to a narrower diopter range between approximately 23 to 23.75 and allows for an improved low-light intensity vision.

[0057] Fig. 7 which is a simplified graph illustration depicting a profile of a diffractive portion of an exemplary lens in accordance with some embodiments of the current invention. As shown in Fig. 7, the depicted cross-section profile comprises an asymmetrical single-peaked topography comprising a plurality of peaks having a height of between 1.5 and 2.5  $\mu\text{M}$  dispersed along a portion of the lens radius between 0 and 3000  $\mu\text{M}$ .

[0058] Throughout this application, various embodiments of this invention may be presented in a range format. It should be understood that the description in range format is merely for convenience and brevity and should not be construed as an inflexible limitation on the scope of the invention. Accordingly, the description of a range should be considered to have specifically disclosed all the possible subranges as well as individual numerical values within that range. For example, description of a range such as from 1 to 6 should be considered to have specifically disclosed subranges such as from 1 to 3, from 1 to 4, from 1 to 5, from 2 to 4, from 2 to 6, from 3 to 6 etc., as well as individual numbers within that range, for example, 1, 2, 3, 4, 5, and 6. This applies regardless of the breadth of the range.

[0059] Whenever a numerical range is indicated herein, it is meant to include any cited numeral (fractional or integral) within the indicated range. The phrases “ranging/ranges between” a first indicate number and a second indicate number and “ranging/ranges from” a first indicate number “to” a second indicate number are used herein interchangeably and are meant to include the first and second indicated numbers and all the fractional and integral numerals therebetween.

[0060] In the description and claims of the application, each of the words “comprise” “include” and “have”, and forms thereof, are not necessarily limited to members in a list with which the words may be associated. In addition, where there are inconsistencies between this application and any document incorporated by reference, it is hereby intended that the present application controls.

[0061] The descriptions of the various embodiments of the present invention have been presented for purposes of illustration but are not intended to be exhaustive or limited to the embodiments disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the described embodiments. The terminology used herein was chosen to best explain the principles of the embodiments, the practical application or technical improvement over technologies found in the marketplace, or to enable others of ordinary skill in the art to understand the embodiments disclosed herein.

## WHAT IS CLAIMED IS:

1. A multifocal IOL comprising  
at least one diffractive surface including a plurality of discrete, adjacent, diffractive, concentric rings, having  
a radial phase profile cross-section with a near-symmetrical diffractive surface topography; and  
an odd number, greater than three, of diffractive orders.
2. The IOL according to claim 1, wherein said IOL comprises an asymmetrical distribution of energy flux over said diffractive orders.
3. The IOL according to any one of claims 1 and 2, wherein said IOL comprises 5 diffractive orders.
4. The IOL according to any one of claims 1-3, wherein said diffractive surface comprises diffractive steps designed to maintain the diffractive profile unchanged in between said steps.
5. The IOL according to claim 4, wherein said diffractive steps are partially inside and partially outside the base curvature of the IOL.
6. The IOL according to any one of claims 1-5, wherein said diffractive, concentric rings comprise a repetitive pattern of diffractive profiles.
7. The IOL according to claim 6, wherein said profiles are asymmetrical.
8. The IOL according to any one of claims 1-7, wherein said diffractive rings comprise a repetitive pattern of a single diffractive profile.

9. The IOL according to any one of claims 1-7, wherein said diffractive rings comprise a repetitive pattern of two different diffractive profiles.
10. The IOL according to claim 9, wherein said diffractive rings comprise a single transition from a first zone having a repetitive pattern of one diffractive profile to a second peripheral zone having a repetitive pattern of a second diffractive profile.
11. The IOL according to any one of claims 9 and 10, wherein height of the diffractive surface topography of said second peripheral zone is maintained constant when advancing radially outwards in respect to the center height of the IOL.
12. The IOL according to any one of claims 1-8, wherein said radial phase profile cross-section has an asymmetrical double-peaked geometry.
13. The IOL according to any one of claims 1-12, wherein thickness of the IOL is variable and the curvature is maintained.
14. The IOL according to any one of claims 1-13, wherein thickness of the IOL is variable and the curvature is variable.




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/IL20 19/05 1025

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC (20200101) A61F 2/16, G02B 5/18 CPC (20150401) A61F 2/1613, A61F 2/1654, A61F 2/1618, G02B 5/1876 According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC (20200101) A61F 2/16 CPC (20130101) A61F 2/1618, A61F 2/1613 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) Databases consulted: Google Patents, Orbit		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2009027438 A2 AMO REGIONAL HOLDINGS 05 Mar 2009 (2009/03/05) The whole document	1-14
X	WO 2012078763 A1 ABBOTT MEDICAL OPTICS INC 14 Jun 2012 (2012/06/14) The whole document	1-14
X	US 2009240328 A1 ICON LAB GMBH 24 Sep 2009 (2009/09/24) The whole document	1-14
A	US 6536899 B1 BIFOCON OPTICS GMBH 25 Mar 2003 (2003/03/25) The whole document	1-14
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "D" document cited by the applicant in the international application "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 21 Jan 2020		Date of mailing of the international search report 21 Jan 2020
Name and mailing address of the ISA: Israel Patent Office Technology Park, Bldg.5, Malcha, Jerusalem, 9695101, Israel Email address: pctoffice@justice.gov.il		Authorized officer Zreiqi Asia Telephone No. 972-73-3927231

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/IL2019/051025

Patent document cited search report	Publication date	Patent family member(s)	Publication Date
WO 2009027438 A2	05 Mar 2009	WO 2009027438 A2	05 Mar 2009
		WO 2009027438 A3	16 Apr 2009
		AT 523810 T	15 Sep 2011
		AU 2008292187 A1	05 Mar 2009
		AU 2008292187 B2	30 Jan 2014
		AU 2009214036 A1	20 Aug 2009
		AU 2009214036 A8	23 Sep 2010
		AU 2009214036 B2	17 Apr 2014
		AU 2009239649 A1	29 Oct 2009
		AU 2009239649 B2	13 Nov 2014
		AU 2009246734 A1	19 Nov 2009
		AU 2010330799 A1	12 Jul 2012
		AU 2010330799 B2	19 Feb 2015
		AU 2010330799 C1	01 Oct 2015
		AU 2010330809 A1	12 Jul 2012
		AU 2010330809 B2	22 Jan 2015
		AU 2010330826 A1	12 Jul 2012
		AU 2011246966 A1	22 Nov 2012
		AU 2011246966 B2	02 Apr 2015
		AU 2011276241 A1	07 Feb 2013
		AU 2011276241 B2	12 Mar 2015
		AU 2011343581 A1	11 Jul 2013
		AU 2011343581 B2	05 May 2016
		AU 2012298703 A1	06 Mar 2014
		AU 2012298703 B2	11 May 2017
		AU 2013308109 A1	19 Mar 2015
		AU 2013308109 B2	19 Apr 2018
		AU 2018204425 A1	05 Jul 2018
		AU 2018204425 B2	12 Dec 2019
		BR 112012014905 A2	14 Mar 2017

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/IL2019/051025

Patent document cited search report	Publication date	Patent family member(s)	Publication Date
		BR 112012014908 A2	21 Mar 2017
		BR 112015004617 A2	04 Jul 2017
		CA 2697969 A1	05 Mar 2009
		CA 2697969 C	07 Jun 2016
		CA 2715537 A1	20 Aug 2009
		CA 2715537 C	06 Sep 2016
		CA 2722274 A1	09 Oct 2009
		CA 2722274 C	02 Oct 2018
		CA 2731817 A1	19 Nov 2009
		CA 2784771 A1	23 Jun 2011
		CA 2784771 C	04 Dec 2018
		CA 2784782 A1	23 Jun 2011
		CA 2784782 C	27 Feb 2018
		CA 2784794 A1	23 Jun 2011
		CA 2784794 C	20 Feb 2018
		CA 2797924 A1	03 Nov 2011
		CA 2797924 C	16 Jul 2019
		CA 2804777 A1	12 Jan 2012
		CA 2821968 A1	21 Jun 2012
		CA 2821968 C	28 May 2019
		CA 2846235 A1	28 Feb 2013
		CA 2883712 A1	06 Mar 2014
		CN 102892380 A	23 Jan 2013
		CN 102892380 B	19 Oct 2016
		CN 102892381 A	23 Jan 2013
		CN 104755012 A	01 Jul 2015
		CN 104755012 B	12 Jan 2018
		CN 108013952 A	11 May 2018
		EP 2180849 A2	05 May 2010
		EP 2180849 B1	15 Oct 2014
		EP 2243052 A1	27 Oct 2010

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/IL2019/051025

Patent document cited search report	Publication date	Patent family member(s)	Publication Date
	EP 2243052	B1	07 Sep 2011
	EP 2283392	A2	16 Feb 2011
	EP 2334260	A2	22 Jun 2011
	EP 2365379	A1	14 Sep 2011
	EP 2365379	B1	27 Jan 2016
	EP 2512370	A1	24 Oct 2012
	EP 2512371	A2	24 Oct 2012
	EP 2512372	A1	24 Oct 2012
	EP 2564263	A1	06 Mar 2013
	EP 2590594	A2	15 May 2013
	EP 2651334	A1	23 Oct 2013
	EP 2651334	B1	20 Jun 2018
	EP 2747706	A1	02 Jul 2014
	EP 2890287	A2	08 Jul 2015
	JP 2013514833	A	02 May 2013
	JP 2013515284	A	02 May 2013
	KR 20150050588	A	08 May 2015
	US 2009268158	A1	29 Oct 2009
	US 7871162	B2	18 Jan 2011
	US 2009268155	A1	29 Oct 2009
	US 8231219	B2	31 Jul 2012
	US 2011109875	A1	12 May 2011
	US 8382281	B2	26 Feb 2013
	US 2011149236	A1	23 Jun 2011
	US 8430508	B2	30 Apr 2013
	US 2011317124	A1	29 Dec 2011
	US 8444267	B2	21 May 2013
	US 2011317126	A1	29 Dec 2011
	US 8480228	B2	09 Jul 2013
	US 2012307202	A1	06 Dec 2012
	US 8573775	B2	05 Nov 2013

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/IL2019/051025

Patent document cited search report	Publication date	Patent family member(s)	Publication Date
	US 2009234448	A1	17 Sep 2009
	US 8740978	B2	03 Jun 2014
	US 2009187242	A1	23 Jul 2009
	US 8747466	B2	10 Jun 2014
	US 2013293836	A1	07 Nov 2013
	US 8820927	B2	02 Sep 2014
	US 2011270596	A1	03 Nov 2011
	US 8862447	B2	14 Oct 2014
	US 2012320335	A1	20 Dec 2012
	US 8894204	B2	25 Nov 2014
	US 2013235338	A1	12 Sep 2013
	US 8926092	B2	06 Jan 2015
	US 2011166652	A1	07 Jul 2011
	US 9216080	B2	22 Dec 2015
	US 2014168602	A1	19 Jun 2014
	US 9335563	B2	10 May 2016
	US 2013060330	A1	07 Mar 2013
	US 9454018	B2	27 Sep 2016
	US 2014371850	A1	18 Dec 2014
	US 9557580	B2	31 Jan 2017
	US 2015205145	A1	23 Jul 2015
	US 9581834	B2	28 Feb 2017
	US 2013226294	A1	29 Aug 2013
	US 9931200	B2	03 Apr 2018
	US 2016100938	A1	14 Apr 2016
	US 9987127	B2	05 Jun 2018
	US 2017007396	A1	12 Jan 2017
	US 10034745	B2	31 Jul 2018
	US 2017156849	A1	08 Jun 2017
	US 10180585	B2	15 Jan 2019
	US 2016320633	A1	03 Nov 2016

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/IL2019/051025

Patent document cited search report	Publication date	Patent family member(s)	Publication Date
		US 10197815 B2	05 Feb 2019
		US 2017131565 A1	11 May 2017
		US 10288901 B2	14 May 2019
		US 2009210054 A1	20 Aug 2009
		US 2018256317 A1	13 Sep 2018
		US 2018333255 A1	22 Nov 2018
		US 2019171036 A1	06 Jun 2019
		WO 2009101202 A1	20 Aug 2009
		WO 2009130610 A2	29 Oct 2009
		WO 2009130610 A3	18 Feb 2010
		WO 2009140080 A2	19 Nov 2009
		WO 2009140080 A3	30 Dec 2009
		WO 2011075641 A2	23 Jun 2011
		WO 2011075641 A3	11 Aug 2011
		WO 2011075651 A1	23 Jun 2011
		WO 2011075668 A1	23 Jun 2011
		WO 2011135449 A1	03 Nov 2011
		WO 2012006385 A2	12 Jan 2012
		WO 2012006385 A3	29 Mar 2012
		WO 2012083143 A1	21 Jun 2012
		WO 2013028992 A1	28 Feb 2013
		WO 2014033543 A2	06 Mar 2014
		WO 2014033543 A3	26 Jun 2014
WO 2012078763 A1	14 Jun 2012	WO 2012078763 A1	14 Jun 2012
		AU 2011338464 A1	04 Jul 2013
		AU 2011338464 B2	24 Sep 2015
		AU 2013286703 A1	30 Oct 2014
		AU 2013286703 B2	25 May 2017
		CA 2820881 A1	14 Jun 2012
		CA 2820881 C	12 Feb 2019

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/IL2019/051025

Patent document cited search report	Publication date	Patent family member(s)	Publication Date
		CA 2880429 A1	09 Jan 2014
		EP 2649487 A1	16 Oct 2013
		EP 2649487 B1	22 Nov 2017
		EP 2870503 A1	13 May 2015
		US 2014009736 A1	09 Jan 2014
		US 9069185 B2	30 Jun 2015
		US 2013278891 A1	24 Oct 2013
		US 9304329 B2	05 Apr 2016
		US 2012140166 A1	07 Jun 2012
		US 2016216535 A1	28 Jul 2016
		WO 2014008343 A1	09 Jan 2014
US 2009240328 A1	24 Sep 2009	US 2009240328 A1	24 Sep 2009
<hr/>			
		AT 521305 T	15 Sep 2011
		DE 202008003859 U1	13 Aug 2009
		EP 2103279 A1	23 Sep 2009
		EP 2103279 B1	24 Aug 2011
US 6536899 B1	25 Mar 2003	US 6536899 B1	25 Mar 2003
<hr/>			
		AT 283498 T	15 Dec 2004
		AU 6008700 A	30 Jan 2001
		CA 2378730 A1	18 Jan 2001
		CA 2378730 C	19 Oct 2010
		DE 60016219 D1	30 Dec 2004
		DE 60016219 T2	03 Nov 2005
		EP 1194797 A1	10 Apr 2002
		EP 1194797 B1	24 Nov 2004
		IL 147598 D0	14 Aug 2002
		WO 0104667 A1	18 Jan 2001
		ZA 200200394 B	06 Feb 2003