



US 20170035564A1


(19) **United States**(12) **Patent Application Publication****Ryan et al.**(10) **Pub. No.: US 2017/0035564 A1**(43) **Pub. Date: Feb. 9, 2017**(54) **REPLACEMENT PROSTHETIC HEART VALVES AND METHODS OF IMPLANTATION**(71) Applicant: **Medtronic, Inc.**, Minneapolis, MN (US)(72) Inventors: **Timothy R. Ryan**, Minnetrista, MN (US); **Philipp Bonhoeffer**, London (GB)(21) Appl. No.: **15/296,469**(22) Filed: **Oct. 18, 2016****Related U.S. Application Data**

(63) Continuation of application No. 12/070,387, filed on Feb. 15, 2008, now Pat. No. 9,504,568.

(60) Provisional application No. 60/901,787, filed on Feb. 16, 2007.

Publication Classification(51) **Int. Cl.**
A61F 2/24 (2006.01)(52) **U.S. Cl.**
CPC **A61F 2/2418** (2013.01); **A61F 2/2433** (2013.01); **A61F 2/2409** (2013.01); **A61F 2210/0014** (2013.01); **A61F 2220/0075** (2013.01); **A61F 2220/005** (2013.01)(57) **ABSTRACT**

A replacement prosthetic heart valve for engagement with a structure of a previously implanted prosthetic heart valve. The replacement heart valve includes a stent structure including a generally tubular body portion with an interior area and a series of wire portions arranged in a mesh-like configuration, and at least one stent post engaging structure extending radially outwardly from the body portion for engaging with an outer surface of a stent post of the previously implanted prosthetic heart valve. The stent structure further includes at least two leaflets attached within the interior area of the tubular body portion of the stent structure.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 12

Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 37




Fig. 38




Fig. 39




Fig. 40








Fig. 41






Fig. 46




Fig. 47




Fig. 48




Fig. 49




Fig. 50




Fig. 52




Fig. 51

REPLACEMENT PROSTHETIC HEART VALVES AND METHODS OF IMPLANTATION

CROSS-REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority to U.S. Provisional Application No. 60/901,787, filed Feb. 16, 2007, and titled "Replacement Prosthetic Heart Valve Including Delivery System and Method of Implantation", the entire contents of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The present invention relates to prosthetic heart valves. More particularly, it relates to devices, methods, and delivery systems for percutaneously implanting prosthetic heart valves.

BACKGROUND

[0003] Various types and configurations of prosthetic heart valves are used to replace diseased natural human heart valves. The actual shape and configuration of any particular prosthetic heart valve is dependent to some extent upon the valve being replaced (i.e., mitral valve, tricuspid valve, aortic valve, or pulmonary valve). In general, the prosthetic heart valve designs attempt to replicate the function of the valve being replaced and thus will include valve leaflet-like structures used with either bioprostheses or mechanical heart valve prostheses.

[0004] As used throughout this specification a "prosthetic heart valve" is intended to encompass bioprosthetic heart valves having leaflets made of a biological material (e.g., harvested porcine valve leaflets, or bovine or equine pericardial leaflets), along with synthetic leaflet materials or other materials. These bioprosthetic heart valves typically include a stent having a substantially circular base (or stent ring), around which an annular suture material is disposed for suturing the prosthesis to heart tissue. The stent further typically includes at least two, but typically three, support structures extending from the stent ring. These support structures are commonly referred to as stent posts or commissure posts. These posts typically are rigid yet somewhat flexible structures extending from the stent ring, which are covered by a cloth-like material similar to that of the annular suture material. The stent or commissure posts define the juncture between adjacent tissue or synthetic leaflets otherwise secured thereto. Examples of bioprosthetic heart valves are described in U.S. Pat. No. 4,106,129 (Carpentier et al.), and U.S. Pat. No. 5,037,434 (Lane), the entire disclosures of which are incorporated herein by reference. These disclosures describe a conventional configuration of three leaflets, with one leaflet disposed between each pair of stent or commissure posts. Regardless of whether a stent is provided, however, bioprosthetic heart valves are generally tubular so that when the leaflets are in an open position, an internal passage is defined through which blood can flow.

[0005] The bioprosthetic heart valves further typically include a sewing ring or suture ring that provides a means for fixing the prosthetic heart valve to the patient's native heart valve orifice tissue (e.g., native annulus or valvular rim) that is associated with the native heart valve being repaired or replaced. In particular, an exacting surgical

implantation technique is traditionally employed whereby the heart is stopped (i.e., cardiopulmonary bypass) and opened, which is followed by surgical removal of damaged or diseased natural valve structure. A prosthetic heart valve can then be oriented within the native valvular area, with the sewing ring being seated against or at the native annulus or valvular rim. Sutures are then used to affix the sewing ring to the natural tissue. Obviously, the risks associated with this invasive type of surgery are numerous, particularly when cardiopulmonary bypass procedures are used:

[0006] A successfully implanted prosthetic heart valve will normally function without problems for many years. In certain instances, however, deficiencies may become evident shortly after implant or within a few years, particularly in younger patients. Common functional deficiencies include the calcification of the prosthetic heart valve leaflets, stenosis, and prosthetic heart valve insufficiency. Under these and other circumstances, the prosthetic heart valve does not function properly and conventionally requires surgical removal and replacement. Surgical removal of such a previously implanted prosthetic heart valve entails the same invasive surgical intervention described above, coupled with the need to remove the old prosthetic valve and implant a new prosthetic heart valve. In addition, the risk of mortality is often higher when performing a second surgery in the same area of the body, particularly when performing heart-related surgeries. Another disadvantage to this additional surgery is that the reopening of a sternotomy has been known to have a relatively high risk of causing an infection.

[0007] Thus, while these types of surgeries are well-accepted, the conventional surgical intervention described above is difficult to perform and can result in patient injury or more severe complications. In fact, due to physical weakness of a patient, implantation of a prosthetic heart valve via the conventional surgical technique may be considered too high-risk or contra-indicated for certain patients. Further, removal of a previously implanted prosthetic heart valve requires cutting of the sutures that secure the prosthesis to the native annulus/valvular rim, and attachment of a new sewing ring via stitching, which can further compromise the integrity of the valvular rim and lead to recovery complications, morbidity, and mortality.

[0008] Although not necessarily related to the specific prosthetic heart valve replacement concerns described above, efforts have also been made to devise a prosthetic heart valve capable of being delivered percutaneously via transcatheter implantation, thereby avoiding the complications and risks associated with conventional surgical intervention. For example, in U.S. Pat. No. 6,168,614 (Andersen et al.), a heart valve prosthesis is described for implantation in the body by use of a catheter. The valve prosthesis consists of a support structure with a tissue valve connected to it, whereby the support structure is delivered in a collapsed state through a blood vessel and secured to a desired valve location with the support structure in an expanded state.

[0009] Other percutaneously-delivered prosthetic heart valves have been suggested having a generally similar configuration, such as by Bonhoeffer, P. et al., "Transcatheter Implantation of a Bovine Valve in Pulmonary Position." *Circulation*, 2002; 102:813-816, and by Cribier, A. et al. "Percutaneous Transcatheter Implantation of an Aortic Valve Prosthesis for Calcific Aortic Stenosis." *Circulation*, 2002; 106:3006-3008, the disclosures of which are incor-

porated herein by reference. These techniques rely at least partially upon a frictional type of engagement between the expanded support structure and the native tissue to maintain a position of the delivered prosthesis, although the stents can also become at least partially embedded in the surrounding tissue in response to the radial force provided by the stent and any balloons used to expand the stent. Thus, with these transcatheter techniques, conventional sewing of the prosthetic heart valve to the patient's native tissue is not necessary. Similarly, in an article by Bonhoeffer, P. et al. titled "*Percutaneous Insertion of the Pulmonary Valve*," J Am Coll Cardiol, 2002; 39:1664-1669, the disclosure of which is incorporated herein by reference, percutaneous delivery of a biological valve is described. The valve is sutured to an expandable stent within a previously implanted valved or non-valved conduit, or a previously implanted valve. Again, radial expansion of the secondary valve stent is used for placing and maintaining the replacement valve.

[0010] Devices and methods have more recently been developed for percutaneously replacing deficient, previously implanted prosthetic heart valves, which are described, for example, in U.S. Patent Publication No. 2006/0052867 (Revueta et al.), the entire disclosure of which is incorporated herein by reference. Other transcatheter technologies for delivering replacement valves are described in PCT Application Nos. WO 2007/053243-A2, WO 2007/130537-A1, and WO 2007/081820-A1; United States Patent Application Publication Nos. 2005/0251251-A1, 2007/0043435-A1, and 2008/0004696-A1; and U.S. Pat. No. 7,195,641. However, a need exists for additional prosthetic heart valves, delivery systems, and related methods of implantation that are conducive to percutaneous delivery for replacing a deficient, previously implanted bioprosthetic heart valve.

SUMMARY

[0011] The replacement valves of the invention are configured to provide complimentary features that promote physical docking or connection of the replacement heart valve to a previously implanted prosthetic heart valve, such as the aortic valve, mitral valve, pulmonic valve, and tricuspid valve. In some embodiments, the replacement heart valve and related methods of implantation of the invention utilize a previously implanted prosthetic heart valve as a platform to facilitate mounting relative to a native heart valve. Thus, the replacement heart valves of the invention are highly amenable to percutaneous delivery, although delivery of the heart valves using an apical approach (either with or without cardiopulmonary bypass) is also contemplated. Further, in cases where a previously implanted prosthetic heart valve is being functionally replaced, the deficient prosthetic heart valve need not be physically removed from the patient. Thus, the prosthetic heart valve and related method of implantation of the present invention can be used at any point during the "useful life" of a conventional prosthetic heart valve. Further, the methodology associated with the present invention can be repeated multiple times, such that several prosthetic heart valves of the present invention can be mounted on top of or within one another, if necessary or desired.

[0012] The replacement heart valves of the invention each include a stent to which a valve structure is attached. The stents of the invention include a wide variety of structures and features that can be used alone or in combination with features of other stents of the invention. In particular, these

stents provide a number of different docking and/or anchoring structures that cooperate with the structure of a previously implanted prosthetic heart valve, and are conducive to percutaneous delivery thereof. Many of the structures are thus compressible to a relatively small diameter for percutaneous delivery to the heart of the patient, and then are expandable either via removal of external compressive forces (e.g., self-expanding stents), or through application of an outward radial force (e.g., balloon expandable stents). In a further alternative, some portions of a stent may be self-expanding while other portions of the same stent are expandable through application of an externally applied force.

[0013] Insertion or implantation of the replacement heart valves of the invention can be accomplished using delivery systems that can maintain the stent structures in their compressed state during their insertion and allow or cause all or specific features of the stent structures to expand once they are in their desired location. In addition, some stents of the invention can further include features that allow them to be retrieved for removal or relocation thereof after they have been deployed from the stent delivery systems. The methods may include implantation of the stent structures using either an antegrade or retrograde approach. Further, in many of the delivery approaches of the invention, the stent structure is rotatable in vivo to allow the stent structure to be positioned in a desired orientation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The present invention will be further explained with reference to the appended Figures, wherein like structure is referred to by like numerals throughout the several views, and wherein:

[0015] FIG. 1 is a perspective view of a prosthetic heart valve with a stent of a replacement prosthetic heart valve of the invention positioned therein;

[0016] FIG. 2 is a top view of the stent of FIG. 1 as positioned relative to the outflow end of a prosthetic heart valve;

[0017] FIG. 3 is a bottom view of the stent of FIG. 1 as positioned relative to the inflow end of a prosthetic heart valve;

[0018] FIG. 4 is a perspective view of the stent of FIG. 1 as it can be used as a component of a replacement prosthetic heart valve;

[0019] FIG. 5 is a perspective view of another embodiment of a stent of the invention as it can be used as a component of a replacement prosthetic heart valve;

[0020] FIG. 6 is a side, partial cross-sectional view of one embodiment of a delivery system of the invention for implanting a balloon-expandable stent of a replacement prosthetic heart valve;

[0021] FIGS. 7-10 are sequential perspective views of the implantation of a self-expanding stent in a prosthetic heart valve, utilizing a retrograde approach of implantation;

[0022] FIG. 11 is a perspective view of a prosthetic heart valve with another exemplary embodiment of a stent of a replacement prosthetic heart valve of the invention positioned therein;

[0023] FIG. 12 is a top view of the stent of FIG. 11 as positioned relative to the outflow end of a prosthetic heart valve;

[0024] FIG. 13 is a bottom view of the stent of FIG. 11 as positioned relative to the inflow end of a prosthetic heart valve;

[0025] FIG. 14 is a perspective view of the stent of FIG. 11 as it can be used as a component of a replacement prosthetic heart valve;

[0026] FIG. 15 is a side view of the stent and prosthetic heart valve of FIG. 11;

[0027] FIG. 16 is a perspective view of another exemplary embodiment of a stent of a replacement heart valve of the invention, with the stent in a partially compressed state;

[0028] FIG. 17 is a perspective view of the stent of FIG. 16 positioned within a prosthetic heart valve;

[0029] FIG. 18 is a side view of the stent and heart valve of FIG. 17;

[0030] FIG. 19 is a top view of the stent of FIG. 16 as positioned relative to the outflow end of a prosthetic heart valve, with the stent in its expanded state;

[0031] FIG. 20 is a bottom view of the stent of FIG. 16 as positioned relative to the inflow end of a prosthetic heart valve, with the stent in its expanded state;

[0032] FIG. 21 is a perspective view of the stent of FIG. 16 in its expanded state;

[0033] FIG. 22 is a perspective view of the stent of FIGS. 16-21 as positioned relative to a prosthetic heart valve;

[0034] FIG. 23 is a perspective view of another exemplary embodiment of a stent of a replacement valve of the invention, positioned within a prosthetic heart valve;

[0035] FIG. 24 is a perspective view of the stent of FIG. 23;

[0036] FIG. 25 is a perspective view of another exemplary embodiment of a stent of a replacement valve of the invention, positioned within a prosthetic heart valve;

[0037] FIG. 26 is a top view of the stent of FIG. 25 as positioned relative to the outflow end of a prosthetic heart valve;

[0038] FIG. 27 is a bottom view of the stent of FIG. 25 as positioned relative to the inflow end of a prosthetic heart valve;

[0039] FIG. 28 is a perspective view of the stent of FIG. 25;

[0040] FIG. 29 is a side view of the stent of FIG. 28 positioned relative to a prosthetic heart valve;

[0041] FIG. 30 is a perspective view of another exemplary embodiment of a stent of a replacement valve of the invention positioned within a prosthetic heart valve;

[0042] FIG. 31 is a top view of the stent of FIG. 30, as positioned relative to the outflow end of a prosthetic heart valve;

[0043] FIG. 32 is a bottom view of the stent of FIG. 30, as positioned relative to the inflow end of a prosthetic heart valve;

[0044] FIG. 33 is a perspective view of the stent of FIG. 30;

[0045] FIG. 34 is a side view of the stent positioned within a prosthetic heart valve of FIG. 30;

[0046] FIG. 35 is a perspective view of another exemplary embodiment of a stent of a replacement valve of the invention positioned within a prosthetic heart valve, with the stent in its partially compressed state;

[0047] FIG. 36 is a perspective view of the stent of FIG. 35 in its partially compressed state;

[0048] FIG. 37 is a side view of the stent positioned within a prosthetic heart valve of FIG. 35;

[0049] FIG. 38 is a perspective view of the stent of FIGS. 35-37 positioned within a prosthetic heart valve, with the stent in its expanded state;

[0050] FIG. 39 is a perspective view of the stent of FIG. 38;

[0051] FIG. 40 is a top view of the stent of FIG. 38, as positioned relative to the outflow end of a prosthetic heart valve;

[0052] FIG. 41 is a bottom view of the stent of FIG. 38, as positioned relative to the inflow end of a prosthetic heart valve;

[0053] FIG. 42 is a perspective view of another exemplary embodiment of a stent of a replacement valve of the invention positioned within a prosthetic heart valve;

[0054] FIG. 43 is a perspective view of the stent of FIG. 42;

[0055] FIG. 44 is a top view of the stent of FIG. 42, as positioned relative to the outflow end of a prosthetic heart valve;

[0056] FIG. 45 is a bottom view of the stent of FIG. 42, as positioned relative to the inflow end of a prosthetic heart valve;

[0057] FIG. 46 is a perspective view of another exemplary embodiment of a stent of a replacement valve positioned within a prosthetic heart valve, with the stent in its partially compressed state;

[0058] FIG. 47 is a perspective view of the stent of FIG. 46;

[0059] FIG. 48 is a top view of the stent of FIG. 47 positioned within a prosthetic heart valve, with the stent in its partially compressed state;

[0060] FIG. 49 is a perspective view of the stent of FIG. 47 in its expanded state as positioned within a prosthetic heart valve;

[0061] FIG. 50 is a perspective view of the stent of FIG. 47 in its expanded state; and

[0062] FIGS. 51 and 52 are perspective views of a prosthetic heart valve with a stent of a replacement prosthetic heart valve of the invention positioned therein, where FIG. 52 also shows the leaflets of the original prosthetic heart valve.

DETAILED DESCRIPTION

[0063] Referring now to the Figures, wherein the components are labeled with like numerals throughout the several Figures, and initially to FIG. 1, a prosthetic heart valve 10 is illustrated with a stent 30 of the invention positioned therein, which will be described in further detail below. However, referring specifically to the prosthetic heart valve 10, this valve 10 is a typical configuration of a valve that can be implanted within the heart of a patient, such as by suturing or otherwise securing the valve 10 into the area of a native heart valve of a patient. The native heart valves referred to herein can be any of the human heart valves (i.e., mitral valve, tricuspid valve, aortic valve, or pulmonary valve), wherein the type and orientation of an implanted (e.g., surgically implanted) prosthetic heart valve 10 will correspond with the particular form, shape, and function of the native heart valve in which it is implanted. Although valve 10 would typically include multiple leaflets attached within its interior area, such leaflets are not shown in many of the illustrated embodiments for clarity purposes.

[0064] Valve 10 generally includes a valve structure 12 including a stent ring 14 from which three stent posts or

commissure posts 16 extend. All or a portion of the valve structure 12, including the stent ring 14 and stent posts 16, can be covered by a flexible covering 18, which may be a tissue, polymer, fabric, cloth material, or the like to which leaflets (not shown) of the heart valve 10 are attached, such as by sewing. Further, as is known in the art, the internal structure of each of the stent posts 16 can be formed of a stiff but somewhat resiliently bendable material. This construction allows the stent posts 16 to be moved from the orientation shown in FIG. 1 to a deflected orientation by the application of an external force. Once this external force is removed or reduced, the stent posts 16 can then move back toward the orientation shown in FIG. 1.

[0065] The valve structure 12 is generally tubular in shape, defining an internal area 20 (referenced generally) that extends from an inflow end 22 to an outflow end 24. The internal area 20 is essentially surrounded by the valve structure 12, and the leaflets attached within the valve structure 12 selectively allow for fluid flow into or out of the lumen of the natural heart valve in which it is implanted. That is, the internal area 20 is alternatively open and closed to the lumen of the natural heart valve in which it is inserted via movement of leaflets. In some patients, the prosthetic heart valve 10 will have previously been implanted in a patient using typical surgical techniques, whereby the stent ring 14 is sewn or attached to the annulus or valvular rim of the native heart valve. Alternatively, the prosthetic valve could have been previously placed in the patient using minimally invasive techniques for holding the valve in place, such as U-clips, for example, or a wide variety of other techniques and features used for minimally invasive and/or percutaneous implantation of the initial prosthetic heart valve.

[0066] The prosthetic heart valves (e.g., heart valve 10) used in accordance with the devices and methods of the invention may include a wide variety of different configurations, such as a prosthetic heart valve that has tissue leaflets, or a synthetic heart valve that has polymeric leaflets. In this way, the prosthetic heart valves can be specifically configured for replacing any heart valve. That is, while much of the description herein refers to replacement of aortic valves, the stents (and their associated leaflets) of the invention can also generally be used for replacement of tricuspid valves, for use as a venous valve, or to replace a failed bioprosthesis, such as in the area of an aortic valve or mitral valve, for example. The replacement prosthetic heart valves of the present invention can be employed to functionally replace stentless prosthetic heart valves as well.

[0067] The replacement prosthetic heart valves of the present invention can facilitate an implantation technique whereby a replacement prosthetic heart valve is situated or placed relative to a previously implanted prosthetic heart valve, which may be configured as the heart valve 10 shown and described herein. This would become a desirable procedure in cases where it is determined that a previously implanted prosthetic heart valve is functionally deficient due to one or more of a variety of factors, such as stenosis, valve failure, inflammation, native valve insufficiency, etc. Regardless of the cause of the deficiency, rather than removing the previously implanted prosthetic heart valve and implanting a second, similarly formed prosthetic heart valve via relatively complicated and invasive open heart surgical techniques, the methods and devices of the present invention leave the deficient previously implanted prosthetic heart

valve in place, and deploy the new prosthetic heart valve so that it functionally replaces the previously implanted prosthetic heart valve. Prior to implanting the new prosthetic valve, the leaflets of the previously implanted and deficient prosthetic heart valve can either be removed using a variety of techniques such as cutters, lasers, and the like, or the leaflets may instead be left in place within the deficient valve, where they will likely be pushed toward the walls of the vessel upon implantation of the new valve.

[0068] One embodiment of a stent 30, which can be used as a component of a prosthetic heart valve in accordance with the present invention, is shown in FIGS. 1-4. Stent 30 includes a support structure 31 comprising a number of strut or wire portions arranged relative to each other to provide secure coupling between the stent 30 and a prosthetic heart valve 10 in which it is located. In addition, stent 30 provides a semi-rigid frame for the leaflets of the replacement heart valve, which will be attached in some way within the interior portion of stent 30. For ease and clarity of illustration, the leaflets associated with the replacement heart valves of the invention are not shown in the embodiments of the stents of the invention illustrated herein. Details of several configurations of the stents of the invention are described below; however, in general terms, the stents of the invention are generally a series of wires arranged into a tubular support structure, and leaflets can be secured to the interior of the support structure. The leaflets can be formed from a variety of materials, such as autologous tissue, xenograph material, synthetics, or the like, as known in the art. The leaflets may be provided as a homogenous, biological valve structure, such as a porcine, bovine, or equine valve. Alternatively, the leaflets can be provided independent of one another (e.g., bovine or equine pericardial leaflets) and subsequently assembled and attached to a stent support structure. The support structures shown and described relative to the Figures are generally configured to accommodate three leaflets and replace a heart valve (e.g., heart valve 10) that has three commissure posts that accommodate a three-leaflet structure. However, the replacement prosthetic heart valves of the invention can incorporate more or less than three leaflets.

[0069] In more general terms, the combination of a support structure with one or more leaflets can assume a variety of other configurations that differ from those shown and described, including any known prosthetic heart valve design. In one embodiment, a stent support structure with leaflets can be any known expandable prosthetic heart valve configuration, whether balloon expandable, self-expanding, or unfurling (as described, for example, in U.S. Pat. Nos. 3,671,979; 4,056,854; 4,994,077; 5,332,402; 5,370,685; 5,397,351; 5,554,185; 5,855,601; and 6,168,614; U.S. Patent Application Publication No. 2004/0034411; Bonhoeffer P., et al., "Percutaneous Insertion of the Pulmonary Valve", *Pediatric Cardiology*, 2002; 39:1664-1669; Andersen H R, et al., "Transluminal Implantation of Artificial Heart Valves", *EUR Heart J.*, 1992; 13:704-708; Andersen, H. R., et al., "Transluminal Catheter Implantation of New Expandable Artificial Cardiac Valve", *EUR Heart J.*, 1990, 11: (Suppl) 224a; Hilbert S. L., "Evaluation of Explant Polyurethane Trileaflet Cardiac Valve Prosthesis", *J Thorac Cardiovascular Surgery*, 1989; 94:419-29; Block P C, "Clinical and Hemodynamic Follow-Up After Percutaneous Aortic Valvuloplasty in the Elderly", *The American Journal of Cardiology*, Vol. 62, Oct. 1, 1998; Boudjemline, Y., "Steps Toward Percutaneous Aortic Valve Replacement", *Circulation*, 2002;

105:775-558; Bonhoeffer, P., "Transcatheter Implantation of a Bovine Valve in Pulmonary Position, a Lamb Study", *Circulation*, 2000:102:813-816; Boudjemline, Y., "Percutaneous Implantation of a Valve in the Descending Aorta In Lambs", *EUR Heart J*, 2002; 23:1045-1049; and Kulinski, D., "Future Horizons in Surgical Aortic Valve Replacement: Lessons Learned During the Early Stages of Developing a Transluminal Implantation Technique", *ASAIO J*, 2004; 50:364-68).

[0070] Referring again to FIGS. 1-4, the stent 30 comprises a support structure 31 that is made up of a number of struts or wire segments arranged to provide desired docking or engagement features. As will be described in further detail below, the support structure 31 may either be made up of a number of individual struts or wire segments arranged and secured to each other, or the support structure 31 may instead be formed from a single piece of material (e.g., a tube of material that is machined to provide the structure shown). With particular regard to FIG. 1, stent 30 is positioned within a heart valve 10, which typically would have been previously implanted in a patient. Stent 30 comprises a support structure 31 having multiple upper vertical members 32 spaced apart from each other around the perimeter of the support structure 31, and a corresponding number of lower vertical members 34. Both the upper and lower vertical members 32, 34 extend in a direction that is generally parallel to a longitudinal axis 40 of the support structure 31, and help to define the generally cylindrical shape of the support structure 31. Upper vertical members 32 extend generally toward the outflow end 24 of the valve structure 12, and the lower vertical members 34 extend in a direction that is generally opposite to the direction of the upper vertical members 32, which is toward the inflow end 22 of the valve structure 12.

[0071] Each of these upper and lower vertical members 32, 34 are preferably spaced from adjacent upper and lower vertical members 32, 34, respectively, by a distance that is similar or identical to the distance that the stent posts (e.g., stent posts 16) are spaced from each other in a corresponding implanted heart valve (e.g., heart valve 10). Thus, both the number of upper vertical members 32 and the number of lower vertical members 34 are typically the same as the number of stent posts. However, it is possible that the number of upper and lower vertical members 32, 34 are not the same as each other and/or not the same as the number of stent posts.

[0072] The upper vertical members 32 are designed to have a height that allows them to have a desired amount of contact with a corresponding stent post. The upper vertical members 32 may extend at least slightly beyond the tops of the stent posts, or may be at least slightly shorter than the stent posts. The lower vertical members 34 may also have any length that allows them to have a desired amount of contact with their corresponding stent posts 16 and other portions of the stent structure 12 with which they come into contact. Again, the lower vertical members 34 may extend at least slightly below the bottom of the stent structure (i.e., stent ring 14 of FIG. 1), or may be at least slightly shorter so that they do not extend below any portion of the stent structure. The selection of the length of these upper and lower vertical members 32, 34 can vary widely, depending on the configuration of the valve structure and the amount of contact desired between the support structure 31 and the interior portion of the stent or valve structure. In any case,

the height of upper and lower vertical members 32, 34 should be adequate to provide sufficient contact between the support structure 31 and the corresponding heart valve in which it is positioned to keep the stent 30 in place relative to the heart valve. In addition, the arrangement of upper and lower vertical members 32, 34 should provide sufficient structural integrity to the support structure 31 so that it is resistant to deformation or other changes that impact its effectiveness as a stent structure.

[0073] The upper and lower vertical members 32, 34 may be generally "U" or "V" shaped, as illustrated, with the distance between opposite "legs" or extending portions of the members being chosen to provide desired characteristics to the support structure 31. For example, in FIG. 1, the upper vertical members 32 are preferably narrow enough that they will not unintentionally engage with the top edge of corresponding stent posts 16, but are preferably wide enough that they provide adequate contact with the interior portion of the stent posts 16 to help keep the stent 30 in place. In other words, the distance between opposite legs of the "U" or "V" shaped structure is preferably not so large that the members 32 can latch onto the stent posts 16, but is preferably large enough to provide contact between the members 32 and some portion of the interior surface of the stent posts 16. This "U" or "V" shaped structure of these members 32, 34 is particularly adaptable to the configuration where the support structure 31 is essentially a continuous wire structure; however, if the support structure is configured in another manner (e.g., with separate components that are not wire-like), each of the members 32, 34 may essentially consist of a single, relatively solid extending structure, for example. These structures may be arranged and connected relative to each other in a similar configuration to that described relative to a wire structure.

[0074] As shown in FIG. 1, heart valve 10 includes three stent posts 16 that are spaced generally at an equal distance from each other around the perimeter of the valve 10 (i.e., approximately 120 degrees apart). These stent posts 16 will generally correspond with the commissures of leaflets of the valve (not shown). It is understood, however, that the stent posts 16 may instead be unevenly spaced from each other. In one example of such an embodiment, first and second stent posts 16 may be spaced from each other by approximately 120 degrees, second and third stent posts 16 may be spaced from each other by approximately 115 degrees, so that first and third stent posts 16 would be spaced from each other by approximately 125 degrees. Other arrangements that vary slightly or substantially from this arrangement may alternatively be used; particularly in cases where more or less than two stent posts 16 are used. One example of such an arrangement would be in the case of a two-leaflet valve (e.g., the mitral valve), which would only include two stent posts arranged at approximately 180 degrees from each other and a corresponding arrangement for its support structure 31.

[0075] Support structure 31 further includes multiple upper flange or petal portions 36, each of which is located generally between two adjacent upper vertical members 32, and multiple lower flange or petal portions 38, each of which is located generally between two adjacent lower vertical members 34. As is best shown in FIG. 4, the upper and lower flange portions 36, 38 both extend from a common area 42 of the support structure 31, which generally corresponds with the area where the upper and lower vertical members 32, 34 meet. However, the upper and lower flange portions

36, 38 may instead extend from the vertical members **32, 34** at locations that are spaced further from each other. In any case, the upper and lower flange portions **36, 38** are provided for engagement with the stent or valve structure **12** on generally opposite edges (i.e., top and bottom edges) of the stent ring **14** when positioned within a heart valve **10**. That is, the upper flange portions **36** will be positioned in the area between adjacent stent posts **16** on the outflow end **24** of the valve structure **12**, and the lower flange portions **38** will be positioned generally below the upper flange portions **36**, but on the opposite side of the valve structure **12** (i.e., along the bottom edge of the stent ring **14** on the inflow end **22** of the valve structure **12**).

[0076] Orientation and positioning of the stents of the invention may be accomplished either by self-orientation of the stents (such as by interference between features of the stent and a previously implanted stent or valve structure) or by manual orientation of the stent to align its features with anatomical or previous bioprosthetic features, such as can be accomplished using fluoroscopic visualization techniques, for example. For example, when aligning the stents of the invention with a previously implanted bioprosthetic valve, features of the stents can align with the stent rail and/or commissures of the valve. It is desirable that the stents be locked in place both rotationally and axially.

[0077] Referring again to FIGS. 1-4, the length and shape of each of these upper and lower flange portions **36, 38** can be the same or different from each other within a single support structure **31**, as desired. For example, if the stent posts of a corresponding heart valve are spaced evenly from each other, it may be desirable for the flange portions to be identically spaced, although they may be different from each other in size and/or shape. In any case, it is desirable for the upper and lower flange portions **36, 38** to extend at least slightly beyond the outer perimeter of the valve structure **12** when the stent is deployed in order to insure adequate contact between the valve structure **12** and the stent **30**. However, the amount of extension of the upper and lower flanges beyond the outer surface of the valve structure **12** should not be so large that it interferes with any surrounding structure of the heart, as will be discussed in further detail below.

[0078] The upper and lower flange portions **36, 38** may be generally “U” or “V” shaped, as illustrated, although the distance between opposite “legs” or extending portions of the members will generally be larger than the distance between the legs of the upper and lower vertical members **32, 34** within the same stent **30**, particularly when the stent **30** is in its expanded state. Each upper flange portion **36** includes a distal tip **44** and each lower flange member **38** includes a distal tip **46**. The tips **44, 46** may have a tighter curvature than the rest of their respective flange portions **36, 38**, if desired. In any case, the tips **44, 46** preferably will contact the upper and lower edges of a stent ring of a heart valve when implanted therein. The tips **44, 46** may also serve as interfaces or connecting portions with a corresponding delivery system, as will be explained in further detail below.

[0079] The lower flange portions **38** are configured to engage with the lower surface of a sewing ring **14** of a previously implanted prosthetic heart valve (e.g., heart valve **10**) when the stent **30** is in its expanded condition. Alternatively, the lower flange portions **38** can be configured to engage other structure(s) of the previously implanted pros-

thetic heart valve. Referring to FIG. 1, in order to engage with a previously implanted heart valve, one exemplary embodiment of a lower flange portion **38** includes a wire structure that extends generally from a common area **42** on one upper vertical member **32** toward the tip **46** of the flange portion **38**, then toward another common area **42** on an adjacent upper vertical member **32**. The curvature or contours of each flange portion **38** can be designed so that it closely matches the shape of the stent or valve structure **12** in which it will be implanted, such as at its inflow end **22**. That is, there is preferably minimal to no gap between the flange **38** and the interior surface of the valve structure **12**.

[0080] As shown in FIG. 3, each of the tips **46** of the flange portions **38** are positioned approximately 120 degrees from each other around the periphery of the sewing ring **14**, although they can be spaced differently from each other, depending on the locations of the stent posts of the heart valve. When the stent **30** is in an expanded condition, the lower flange portions **38** are preferably biased toward the sewing ring **14** to keep the flange portion **38** in place relative to the heart valve **10**.

[0081] The upper flange portions **36** are configured to engage with the spaces between stent posts **16** of a previously implanted heart valve (e.g., heart valve **10**) when the stent **30** is in its expanded condition. Alternatively, the upper flange portions **36** can be configured to engage other structure(s) of the previously implanted prosthetic heart valve. Referring to FIG. 1, in order to engage with a previously implanted heart valve, one exemplary embodiment of an upper flange portion **36** includes a wire structure that extends generally from a common area **42** on one upper vertical member **32** toward the tip **44** of the flange portion **36**, then toward another common area **42** on an adjacent vertical member **32**. The curvature or contours of each flange portion **36** can be designed to closely match the shape of the stent or valve structure **12** in which it will be implanted. As shown in FIG. 2, each of the tips **44** of the flange portions **36** are positioned approximately 120 degrees from each other around the periphery of the sewing ring **14**, although they can be spaced differently from each other, depending on the locations of the stent posts of the heart valve. In any case, the tip **44** of flange portion **36** will preferably fit between adjacent stent posts **16** in order to help physically dock or connect the stent **30** to the previously implanted heart valve **10**. When the stent **30** is in an expanded condition, the upper flange portions **36** are preferably biased toward the sewing ring **14** (and preferably toward a corresponding lower flange portion **38**) to keep each flange portion **36** in place relative to the heart valve **10**.

[0082] The support structure **31** of the stent **30** is, in one embodiment, a wire stent capable of transitioning from a collapsed state to an expanded state, where a number of individual wires comprising the support structure **31** are formed of a metal or other material. These wires are arranged in such a way that a support structure **31** is provided that allows for folding or compressing to a contracted state in which its internal diameter is at least somewhat smaller than its internal diameter in an expanded state. In its contracted state, such a support structure **31** with attached valves can be mounted relative to a delivery device, such as a balloon catheter, for example. The support structure **31** is configured so that it can be changed to its expanded state when desired, such as by the expansion of a balloon catheter. The delivery systems used for such replace-

ment heart valve can optionally be provided with degrees of rotational and axial orientation capabilities in order to properly position the new heart valve within the previously implanted heart valve.

[0083] The wires of the support structure **31** can alternatively be formed from a shape memory material such as a nickel titanium alloy (e.g., Nitinol). With this configuration, the support structure **31** is self-expandable from a contracted state to an expanded state, such as by the application of heat, energy, and the like, or by the removal of external forces (e.g., compressive forces). In addition, the support structure **31** of this embodiment may be laser cut from a single piece of material or may be assembled from a number of different components. For these types of stent structures, one example of a delivery system that can be used includes a catheter with a retractable sheath that covers a compressed stent (thereby providing external compressive forces on the stent) until it is to be deployed, at which point the sheath can be retracted to allow the stent to expand.

[0084] The support structure **31** can include features not specifically described or shown instead of, or in addition to, the various coupling structures and methods described herein. For example, the support structure **31** can have a non-expandable design, but can instead be sized and shaped to nest within a previously implanted heart valve (not shown) in a manner that presses features of the previously implanted heart valve (e.g., leaflets) outwardly relative to the native conduit.

[0085] The height and diameter of the stent **30** in its expanded state is preferably chosen and/or designed for use with a previously implanted prosthetic heart valve having a particular size and shape. Thus, the stent **30** can assume a variety of different longitudinal heights and/or diameters. In one embodiment, for example, the support structure **31** has a height in its expanded state that is slightly greater than a height of the previously implanted prosthetic heart valve, and/or has a free-standing outer diameter that is greater than an inner diameter of the previously implanted prosthetic heart valve. With this embodiment, upon transitioning toward the expanded state, the support structure **31** (including the vertical members **32**, **34**) presses against an inner diameter of the previously implanted prosthetic heart valve. The overall shape of the support structure **31** is cylindrical in many cases; however, other shapes are also contemplated, such as elliptical, oval, or the like. For example, portions of the support structure **31** can define an enlarged diameter as compared to other portions. Further, depending upon the previously implanted heart valve being functionally replaced, the support structure **31** can be less uniform along a height thereof.

[0086] One method of delivering the stent **30** to the location of a previously implanted heart valve (e.g., heart valve **10**) is performed percutaneously, as represented in simplified form in FIG. 6. In general terms for this exemplary delivery system, a transcatheter assembly **70** is provided, including a delivery catheter **72**, a balloon catheter **74**, and a guide wire **76**. The delivery catheter **72** is of a type known in the art, and defines a lumen **78** within which the balloon catheter **74** is received. The balloon catheter **74**, in turn, defines a lumen (not shown) within which the guide wire **76** is slidably disposed. Further, the balloon catheter **74** includes a balloon **80** that is fluidly connected to an inflation source (not shown). It is noted that if the stent being implanted is a self-expanding type of stent, the balloon

would not be needed and a sheath or other restraining means would instead be used for maintaining the stent in its compressed state until deployment of the stent. In any case, in this embodiment, the transcatheter assembly **70** is appropriately sized for a desired percutaneous approach to the prosthetic heart valve **10** that was previously implanted in a native heart valve **79**. For example, the transcatheter assembly **70** can be sized for delivery to the heart valve **10** via an opening at a carotid artery, a jugular vein, a sub-clavian vein, femoral artery or vein, or the like. Essentially, any percutaneous intercostals penetration can be made to facilitate use of the transcatheter assembly **70**.

[0087] Prior to delivery, the stent **30** is mounted over the balloon **80** in a contracted state to be as small as possible without causing permanent deformation of the stent structure. As compared to the expanded state, the support structure **31** is compressed onto itself and the balloon **80**, thus defining a decreased inner diameter as compared to an inner diameter in the expanded state. Further, the vertical members **32**, **34** and flange portions **36**, **38** are compressed toward the longitudinal axis **40** when in the contracted state. While this description is related to the delivery of a balloon-expandable stent, the same basic procedures can also be applicable to a self-expanding stent, where the delivery system would not include a balloon, but would preferably include a sheath or some other type of configuration for maintaining the stent in its compressed condition until its deployment.

[0088] With the stent **30** mounted to the balloon **80**, the transcatheter assembly **70** is delivered through a percutaneous opening (not shown) in the patient via the delivery catheter **72**. The previously implanted heart valve **10** is located by inserting the guide wire **76** into the patient, which guide wire **76** extends from a distal end **82** of the delivery catheter **72**, with the balloon catheter **74** otherwise retracted within the delivery catheter **72**. Once the previously implanted heart valve **10** has been located, the balloon catheter **74** is advanced distally from the delivery catheter **72** along the guide wire **76**, with the balloon **80** and stent **30** positioned relative to the previously implanted heart valve **10**. More particularly, the balloon **80** and stent **30** are positioned within the internal region of the previously implanted prosthetic heart valve **10**, with the lower flange portions **38** positioned adjacent the sewing ring **14** of the heart valve **10**, and the upper flange portions **36** are positioned adjacent the outflow end **24** of the previously implanted prosthetic heart valve **10**.

[0089] In an alternative embodiment, the stent **30** is delivered to the previously implanted prosthetic heart valve **10** via a minimally invasive surgical incision (i.e., non-percutaneously). In another alternative embodiment, the stent **30** is delivered via open heart/chest surgery. Regardless, with the stent **30** in the contracted state, the support structure **31** can readily move within the internal area **20** of the previously implanted prosthetic heart valve **10**, and the vertical members **32**, **34** and flange portions **36**, **38**, which are otherwise retracted or compressed, do not unintentionally contact or engage portions of the previously implanted prosthetic heart valve **10**. In one embodiment, the stent **30** includes a radiopaque, echogenic, or MRI visible material to facilitate visual confirmation of proper placement of the stent **30** relative to the previously implanted prosthetic heart valve **10**. Alternatively, other known surgical visual aids can be incorporated into the stent **30**.

[0090] The techniques described above relative to placement of the stent 30 within the heart can be used both to monitor and correct the placement of the stent 30 in a longitudinal direction relative to the length of the anatomical structure in which it is positioned and also to monitor and correct the orientation of the stent 30 relative to the stent posts 16 of the previously implanted heart valve 10. In particular, it is desirable for the stent 30 to be positioned so that each of the upper flange portions 36 are between two adjacent stent posts 16 when they are expanded outwardly.

[0091] Once the stent 30 is properly positioned, the balloon catheter 74 is operated to inflate the balloon 80, thus transitioning the stent 30 to the expanded state shown in FIG. 1. Alternatively, if the support structure 31 is formed of a shape memory material, the stent can be allowed to self-expand to the expanded state of FIG. 1. Thus, a self-expanding stent structure can be percutaneously delivered by an appropriate catheter device other than a balloon catheter, as will be described in further detail below. In either case, the support structure 31 expands within the internal region 20 of the previously implanted heart valve 10, radially pressing against the valve structure 12. Because the previously implanted prosthetic heart valve 10 would have included leaflets (not shown), radial expansion of the stent 30 would press against these leaflets, thereby lodging them against the valve structure 12.

[0092] FIG. 5 illustrates an exemplary embodiment of a stent 50 that includes a number of eyelets or apertures 52 that can be used for maintaining the various components of stent 50 in a compressed state when desired. These eyelets 52 would be particularly useful in the case where the stent 50 is a self-expanding stent, since this type of structure needs external forces to keep it in its compressed state. In particular, an eyelet 52 may be located at the end of at least one of the multiple upper vertical members 54 and/or one or more of the upper and lower flange portions 56, 58 and the lower vertical members 55. Each eyelet 52 is preferably sized for accepting an elongated thread-like material, such as suture material or a thin wire, and/or sized for engagement with a hook or other engagement feature of a delivery device. If a thread-like material is used, it can be threaded through at least one of the eyelets 52 in such a way that when the material is pulled tight, the eyelets 52 are pulled toward the central axis of the stent 50. If a wire-like material is used, it may be configured as a metal snare or other configuration that pulls the eyelets 52 toward the central axis of the stent 50. If a delivery device having such engagement features is used, it may be configured in such a way that the engagement features can be moved toward and away from the central axis of the stent, as desired for insertion and deployment of the stent.

[0093] Other arrangements of pulling the various portions of a stent toward a central stent axis are also contemplated, which preferably are relatively easy to operate for compression and release of the stent structures. In any case, once the stent structure is compressed to its desired configuration, the feature used to pull the stent into its compressed configuration is capable of being secured or fastened in some way to keep the stent from unintentionally expanding. This same feature can have its operation reversed to allow the various structures of the stent to move toward their expanded state.

[0094] FIGS. 7-10 illustrate one exemplary system of delivering a stent of the type illustrated in FIG. 5, for example, into a heart valve 10, which would have previously

been implanted in a patient. One feature provided by the delivery system of this embodiment is that a self-expanding stent is retrievable after its initial deployment if it is not positioned correctly in the heart. The stent then could be redeployed into the proper position, using the same or a different delivery system. With particular reference to the Figures, a distal portion of a delivery system 90 is illustrated, which includes a tip portion 92 and a sheath 94. The system further includes a plurality of hooks or engagement features 96 that can engage with eyelets 52 of stent 50, for example. While this delivery system 90 can generally be used for more procedures than the described implantation procedure, the procedure illustrated relative to FIGS. 7-10 is particularly directed to percutaneous delivery of a stent to a previously implanted aortic heart valve via a retrograde approach. For purposes of this description of an implantation method, the exemplary stent 50 of FIG. 5 is used in the implantation description; however, a number of different stent embodiments may utilize these same procedures, such as other stent embodiments described relative to the present invention.

[0095] As illustrated in FIG. 7, delivery system 90 is being advanced toward heart valve 10 as such a heart valve would have been previously implanted in a patient. A compressed replacement valve (not shown) is encompassed within sheath 94 for insertion into the patient so that there is no contact between the replacement valve and any portion of the patient's internal anatomy during the insertion process.

[0096] FIG. 8 illustrates delivery system 90 as it has been further advanced into heart valve 10, and wherein the sheath 94 has been partially retracted away from the tip 92 to expose the stent 50 that was previously compressed therein. Because the upper flange portions 56 were no longer constrained by the sheath 94, these portions 56 were able to move away from a central member 100 of the delivery system 90 as the sheath 94 was retracted. Further, eyelets 52 that extend from the ends of upper vertical members 54 are each engaged by a hook 96 of the delivery system 90. These hooks 96 can be attached to a mechanism within the interior portion of the sheath 94, for example, or may be attached to some other structure that extends through the sheath 94. In either case, hooks 96 can maintain the upper vertical members 54 in their compressed state until they are disengaged from the hooks 96. That is, the delivery system can control the diameter of the stent inflow structures, the stent outflow structures, or both the stent inflow and outflow structures independently or together. As is also illustrated in FIG. 8, the lower flange portions 58 are held in their compressed state with a snare 98 that engages with eyelets 52 that extend from each of the flange portions 58. Snare 98 is shown as a single, shaped piece of elongated material; however, the lower flange portions 58 may instead be held in their compressed state via an alternative structure or system, such as by a suture, or by a moveable sleeve attached to the delivery system, for example.

[0097] As shown in FIG. 9, the delivery system 90 is further advanced into valve 10 until the upper flange portions 56, which are extending radially away from the central member 100 of the delivery system 90, become engaged with the valve structure 12 of the heart valve 10. In particular, each of the upper flange portions 56 are preferably positioned to be in contact with the surface of the stent ring 14 between two adjacent stent posts 16. In order to verify that the flange portions 56 are properly positioned relative to

the valve structure 12 (e.g., flange portions 56 are not resting on the top of the stent posts 16), the entire delivery system 90 can be rotated slightly in either direction while pressing downwardly toward the valve structure 12. The system 90 can also be advanced axially to the desired position. In this way, the flange portions 56 can be moved into the area between adjacent stent posts 16 if they are not already in this position.

[0098] Once the delivery system 90 and its stent 50 are properly oriented, the snare 98, sheath, or other structure holding the lower flange portions 58 in their compressed state is released or retracted, thereby allowing the lower flange portions 58 to deploy or radially extend, as illustrated in FIG. 10. The lower flange portions 58 can then contact the surface of the stent ring 14 that is opposite the surface that is contacted by the upper flange portions 56. The hooks 96 can then be disengaged from the eyelets 52 of stent 50, such as by further advancing the delivery system 90 into the opening of the valve 10, or by activating a mechanism associated with the hooks 96 that can move the hooks 96 relative to the eyelets 52 until they become disengaged from the eyelets 52. It is noted that the stent is retrievable at any point prior to the hooks 96 being disengaged from the stent 50 with use of the hooks 96 and/or the sheath 94. The upper and lower vertical members 54, 55 are then free to expand radially until they contact the inner surface of the stent or valve structure 12. The upper and lower vertical members 54, 55 preferably are configured so that they will press against the inner surface of the valve structure 12 with sufficient force to provide further anchoring of the stent 50 within the previously implanted heart valve 10.

[0099] After the stent 50 is implanted and its various portions are deployed or released from a compressed state to an expanded state, the delivery system 90 can be removed from the patient. The stent 50 will then be in its deployed or expanded state, as is generally illustrated in FIG. 5, or in a similar manner to that illustrated in FIG. 1 relative to a stent 30.

[0100] FIGS. 11-15 illustrate another exemplary embodiment of a stent 110 that has a similar structure to the stent 30 of FIG. 1, but further includes at least one stent post engaging structure 112. Relative to the specific embodiment of the stent 110 that is illustrated, this structure also does not include upper flange portions (such as upper flange portions 36 of stent 30), since such portions could be redundant and/or interfere with the specific structure of the structures 112 shown. However, it is contemplated that upper flange portions could also be provided with this embodiment, if they are configured to not interfere with any stent post engagement structures 112. Further, in the embodiment shown in the Figures, three structures 112 are provided to correspond with a like number of stent posts 16 of heart valve 10; however it is contemplated that the stent 110 includes less than three structures 112, even if three stent posts are provided. If less than three structures 112 are provided, it may be desirable to additionally provide at least one upper flange portion to engage with the heart valve 10.

[0101] Each stent post engaging structure 112 is configured to partially surround a portion of a stent post 16, thereby providing another way of anchoring the stent 110 in place. These structures 112 can cooperate with one or more lower flange portions 114 to provide anchoring on both the inflow and outflow ends of the previously implanted heart valve 10. The structures 112 can be individual structures that

are each secured to upper vertical members 116, or may be formed as a single structure having multiple loops that are secured to the structure of the stent 110. Alternatively, these structures 112 can be integrally formed with the structure of the stent 110. Stent 110 can be a self-expanding stent or may be a balloon-expandable stent structure.

[0102] FIGS. 16-22 illustrate another exemplary embodiment of a stent 120 for use with a replacement prosthetic heart valve in accordance with the present invention. Stent 120 includes a number of strut or wire portions arranged relative to each other to provide secure coupling between the stent 120 and a previously-implanted prosthetic heart valve, such as heart valve 10. In addition, stent 120 provides a semi-rigid frame for the leaflets of the replacement heart valve, which will be attached to the interior portion of stent 120, as will be described in further detail below.

[0103] Stent 120 includes multiple upper vertical members 122 spaced apart from each other around the perimeter of the stent 120, and a corresponding number of lower vertical members 124. It is understood that the number of upper and lower vertical members can be different from each other, however. Both the upper and lower vertical members 122, 124 extend in a direction that is generally parallel to a longitudinal axis of the stent 120, thereby partially defining the generally cylindrical shape of the stent 120. Upper vertical members 122 extend generally toward the outflow end of the stent structure 12, and the lower vertical members 124 extend in a direction that is generally opposite to the direction of the upper vertical members 122, which is toward the inflow end of the stent structure 12. As with previously described embodiments, the number of upper and lower vertical members 122, 124 may or may not be the same as the number of stent posts of the stent structure 12. In addition, the length of upper and lower vertical members 122, 124 should be adequate to provide sufficient contact between the stent 120 and the stent structure 12 to help keep the stent 120 in place relative to the heart valve 10.

[0104] Stent 120 further includes upper and lower flange portions 126, 128, respectively. Flange portions 126, 128 are configured for positioning on opposite sides of a stent ring 14 of stent structure 12 when the stent is in its expanded state. Through the design and manufacturing of the stent 120, the flange portions 126, 128 can be biased toward each other when the stent is in its expanded condition in order to keep the stent 120 positioned properly relative to the stent structure 12.

[0105] Stent 120 includes components that can be made of materials that perform differently relative to deployment thereof. In particular, a portion of stent 120 can be expandable from its compressed state via the application of an internal radial force (e.g., inflation of a balloon), while another portion of stent 120 can be self-expandable such that the removal of radial compressive forces will allow that portion of stent 120 to expand without application of additional forces. Alternatively, different portions of the stent 120 can be made of different materials that are both self-expanding, or of different materials that are expandable via the application of an internal radial force. Although the components that comprise these two structures can vary, the stent 120 illustrated in FIGS. 16-22 includes a first component that is expandable through application of a radial force. This component may be made of a material such as stainless steel, for example. The first component includes the upper vertical members 122, lower vertical members 124, and

lower flange portions **128**, and can include a number of components attached to each other, or can be a single machined piece. This first component is illustrated in its compressed state in FIGS. **16-18** and in its expanded state in FIGS. **21** and **22**. The stent **120** further includes a second component that is self-expandable and may be made of a shape memory material such as a nickel titanium alloy (e.g., Nitinol). This second component includes the upper flange portions **126** and also a second lower vertical member **130** that can at least roughly duplicate the shape of the lower vertical member **124** of the first component.

[0106] When this stent **120** is implanted into a patient, a sheath or other mechanism will be holding the self-expandable portions of the stent in a compressed state until such a mechanism is retracted or removed, thereby allowing the upper flange portions **126** to extend radially from the stent structure, as is illustrated in FIG. **17**. These upper flange portions **126** are preferably positionable between adjacent stent posts of a previously implanted heart valve for proper orientation of the stent **120**. Because the first component is not made from a self-expandable material, the first component of stent **120** will remain in its compressed state, as shown in FIG. **17**, until it is expanded radially, such as via expansion by a balloon catheter that is positioned in its central opening. When fully inflated, such a balloon will be constrained by the stent structure **12** along a portion of its length, but portions of the balloon that are above and below the stent structure **12** can be allowed to expand further so that the balloon takes on an “hourglass” type of shape, thereby pressing the lower flange portions **128** outward and under the stent ring **14**, as illustrated in FIG. **22**. These lower flange portions **128** can thereby help to anchor the stent **120** relative to the heart valve in which it is positioned. Thus, FIGS. **21** and **22** illustrate the stent **120** in its expanded state, where the upper and lower flange portions **126**, **128** are positioned on opposite sides of stent ring **14**, and where the vertical members **122**, **124**, **130** are positioned adjacent to the internal portion of stent structure **12**.

[0107] FIGS. **23** and **24** illustrate another exemplary embodiment of a stent **140** for use as a replacement prosthetic heart valve in accordance with the invention. This stent **140** includes similar structures to that of the stent **30** of FIG. **1**; however, stent **140** does not include lower vertical members that correspond to and extend in the opposite direction from upper vertical members **142**. Otherwise, stent **140** can include any of the features described above relative to the stents of the invention. Stent **140** can be self-expanding or expandable with application of a radial force, and pericardial tissue or other materials may be attached to its structure to provide a prosthetic heart valve.

[0108] FIGS. **25-29** illustrate another exemplary embodiment of a stent **150** for use as a replacement prosthetic heart valve in accordance with the present invention. Stent **150** includes similar structures to the stent **110** of FIG. **11**, including upper vertical members **152** and corresponding lower vertical members **154**, stent post engagement structures **156**, and lower flange members **158**. In an embodiment where the number of stent post engagement structures **156** is optionally less than the number of corresponding stent posts of the previously implanted heart valve, upper flange members may be included on stent **150**, if desired. Alternatively, upper flange members may be included on stent **150** in a configuration that does not interfere with the structures **156**.

[0109] Stent **150** further includes “W” shaped structures **160** positioned along the stent ring **14** between adjacent stent posts **16** in the interior area of the stent structure **12**. Each structure **160** is positioned generally between adjacent lower flange members **158** and provides additional contact surfaces between the stent **150** and the interior portion of the stent structure **12**. In addition, any or all of the structures **160** can be used to hold a leaflet of the failed bioprosthesis against the stent ring of the failed bioprosthesis (such as stent ring **14**) so that the leaflets of the failed bioprosthesis do not interfere with the valve leaflets of the newly implanted valved stent. That is, it may be desirable to hold the leaflets of the failed bioprosthesis toward the stent ring in order to minimize the potential for formation of thrombus between the failed leaflets and the new leaflets. In addition, holding the leaflets against the stent ring can prevent abrasion and/or tearing of the new leaflets that can occur during repeated contact with the old leaflets. The structures **160** may take a “W” type shape, as shown, or may instead have a different shape, such as one or more “U” or “V” shapes, a series of extensions, a sinusoidal shape, or any desired configuration that can hold leaflets against the stent ring of the failed bioprosthesis, when desired.

[0110] The stent **150** may comprise any desired number of components that are connected or attached to each other; however, the exemplary embodiment of stent **150** illustrated in FIG. **28** provides an embodiment with two separate structures attached or arranged relative to each other. That is, a first component is a formed structure that includes the stent post engagement structures **156** and the “W” shaped structures **160**, while a second component is a formed structure that includes the upper and lower vertical members **152**, **154** and the lower flange members **158**.

[0111] FIGS. **30-34** illustrate another exemplary embodiment of a stent **170** for use as a prosthetic heart valve in accordance with the present invention. Stent **170** generally includes upper vertical members **172** and corresponding lower vertical members **174**, upper flange members **176**, lower flange members **178**, and upper connecting members **182**. In this embodiment, the upper flange members **176** are offset relative to lower flange members **178** such that each of the upper flange members **176** is positioned generally between adjacent stent posts **16** of stent structure **12**, and each of the lower flange members **178** is generally aligned with the stent posts **16**. Upper connecting members **182** extend between adjacent upper vertical members **172** and are provided for tying together the upper vertical members **172** to carry the valve hydrodynamic closing loads, which can thereby reduce various stresses in the stent. The upper connecting members **182** can also provide interface points for connection of the stent **170** with the delivery system used for the implantation process. Stent **170** further includes optional lower connecting members **184** that extend between adjacent lower vertical members **174**. Lower connecting members **184** are provided for attachment of the material that makes up the leaflets of the replacement heart valve. That is, pericardial or another valve material may be sewn or otherwise attached to the lower connecting members **184** and may further be sewn or otherwise attached to the upper vertical members **172**.

[0112] The upper connecting members **182** are shown as a single curved member; however, the connecting members can have any desired structure or configuration that provides the desired support for the upper vertical members **172**.

Further, the connecting members **182** may be made of the same or a different material than the other portions of the stent.

[0113] One or more of the lower flange members **178** may further include an eyelet or aperture **180** for engagement with a structure for use during the implantation of the stent **170** (e.g., sutures or a hook structure that can pull the stent structure toward its central axis). One or more of the upper vertical members **172** may similarly include an eyelet or aperture **185** for use during the implantation of the stent **170** and/or for use as an anchor point for attachment of valve material to the stent **170**.

[0114] FIGS. **35-41** illustrate another exemplary embodiment of a stent **200** for use as a replacement prosthetic heart valve in accordance with the present invention. Stent **200** is similar to stent **120** of FIG. **16** in that stent **200** also includes a portion that is made of a material that is expandable (e.g., stainless steel) with a device such as a balloon catheter, for example, and a portion that is made of a material that is self-expanding (e.g., Nitinol) when external forces are removed. In particular, a self-expanding portion of stent **200** may include upper flange portions **202** that can be generally positioned between adjacent stent posts **16** of a stent structure **12**, and bracing portions **204** that can be generally aligned with stent posts **16** of a stent structure **12**. The other portion (i.e., the portion that is not self-expanding) of the stent **200** may include any or all of the following structures: upper vertical members **206**; lower vertical members **208**; upper support structures **210** extending between adjacent upper vertical members **206**; lower support structures **212** extending between adjacent lower vertical members **208**; lower flange portions **220**; and intermediate lower flange portions **214** located between adjacent lower flange portions **220**. The lower flange portions **214** can provide additional anchoring force for the stent **200** against the stent structure **12** in the areas generally adjacent to the stent posts **16**. The lower support structures **212** may be used for securing the valve structure to the stent **200**, if desired.

[0115] FIGS. **42-45** illustrate another exemplary embodiment of a stent **230** for use as a prosthetic heart valve in accordance with the present invention. Stent **230** includes multiple upper vertical members **232** and optional corresponding lower vertical members **234**, and multiple lower flange members **236**. The number of upper vertical members **232** and lower vertical members **234** preferably correspond to the number of stent posts of the previously implanted heart valve. In addition, the number of lower flange members **236** also preferably corresponds to the number of stent posts **16** of the previously implanted heart valve **10** so that one lower flange member **236** can be positioned generally between two adjacent stent posts **16**, but on the opposite side of the stent structure **12** from the stent posts **16**. The stent **230** further includes multiple upper flange members **238**, which are positionable in the space between every two adjacent stent posts **16**, but on the same side of the stent structure **12** as the stent posts **16**. In this embodiment illustrated in FIGS. **42-45**, two upper flange members **238** are positioned in each of the spaces between two adjacent stent posts **16**, which thereby provide additional anchoring points for the stent **230** within the stent structure **12**. In addition, these flange members **238** can function similarly to the structures **160** described above relative to FIGS. **25-29** in that one or more of the flange members **238** can help to hold the leaflets of the failed bioprosthesis generally against

the stent ring of the bioprosthesis so that they do not interfere with the leaflets of the new valved stent. The stent **230** can be configured so that each of the upper flange members **238** of the pair of upper flange members are angled at least slightly toward their adjacent stent posts **16** so that they are facing in at least slightly opposite directions from each other.

[0116] FIGS. **46-50** illustrate another exemplary embodiment of a stent **250** for use as a prosthetic heart valve in accordance with the invention. Stent **250** is similar to stent **120** of FIG. **16** in that stent **250** also includes a portion that is made of an expandable material (e.g., stainless steel) with a balloon catheter, for example, and a portion that is made of a material that is self-expanding (e.g., Nitinol) when external forces are removed. In particular, a self-expanding portion of stent **250** may include multiple stent post engagement structures **252**, which are shown in this embodiment as being part of a continuous unit or piece that is configured to include three stent post engagement structures **252**. Each of the structures **252** is provided to engage with a stent post **16** of a stent structure **12**. The other portion (i.e., the portion that is not self-expanding) of the stent **250** comprises a mesh-like stent structure **254** that includes a number of wire portions arranged as best illustrated in the expanded version of the stent **250** in FIG. **50**. Although this embodiment does not illustrate particular flange portions that extend above or below the stent structure **12**, it is contemplated that any of the anchoring structures discussed above may be incorporated into the stent **250** to provide additional anchoring mechanisms for the stent **250**.

[0117] FIGS. **51** and **52** illustrate another stent **360** of the invention as it can be implanted within a previously implanted heart valve, such as a heart valve **362**. FIG. **52** illustrates an exemplary positioning of the leaflets **370** of the previously implanted heart valve **362** and FIG. **51** does not show these leaflets. Stent **360** includes a split petal structure for its upper flange member that is positioned between stent posts **364**, as shown with petals **366**, **368**. These petals **366**, **368** provide two structures for holding the leaflets **370** of the heart valve **362** against the stent rail of that heart valve **362** so that the leaflets **370** do not interfere with the implantation and/or functioning of the newly implanted heart valve. The petals **366**, **368** may have the same configuration as each other, as shown, or may instead be differently sized and/or shaped than each other. It is also contemplated that other structures may be used, such as a series of barbs or extending members, and it is further understood that more or less than two structures can be used for holding the leaflets **370** against the rail of the heart valve **362**. The petal structures could also be used to hold native leaflets outward for the stented valve implanted in a native valve.

[0118] As discussed herein, the various stent embodiments of the invention can all be used with a valve structure for replacement of a previously implanted prosthetic heart valve. A number of different delivery systems can be used for implantation of such devices, including the delivery systems described above, along with other exemplary delivery systems, such as those described in U.S. Patent Application Publication No. 2003/0199963-A1; U.S. patent application Ser. No. _____, entitled "DELIVERY SYSTEMS AND METHODS OF IMPLANTATION FOR REPLACE-
MENT PROSTHETIC HEART VALVES", Attorney Docket No. MT10038/US/2 (P0026773.02), filed on even date herewith; U.S. patent application Ser. No. _____, entitled

“DELIVERY SYSTEMS AND METHODS OF IMPLANTATION FOR REPLACEMENT PROSTHETIC HEART VALVES”, Attorney Docket No. MTI0038/US/3 (P0026773.03), filed on even date herewith, and U.S. patent application Ser. No. _____, entitled “REPLACEMENT PROSTHETIC HEART VALVES AND METHODS OF IMPLANTATION”, Attorney Docket No. MTI0038/US (P0026773.01), filed on even date herewith, all of which are incorporated by reference in their entireties.

[0119] Referring again to FIG. 1, the stent or valve structure 12 includes a sewing ring 14 and stent posts 16 and is covered by a covering 18, such as is included in the stented tissue valves commercially available from Medtronic, Inc. of Minneapolis, Minn. under the trade designations “Hancock II” and “Mosaic”. A wide variety of other stented tissue valves, such as those described in U.S. Pat. Nos. 4,680,031, 4,892,541, and 5,032,128, the teachings of which are incorporated herein by reference, can be employed as the stent or valve structure 12. Alternatively, the structure 12 can be stentless, such as, for example, a Freestyle stentless bioprosthesis, commercially available from Medtronic, Inc. under the trade designation “Freestyle”. Other acceptable stentless configurations are described in U.S. Pat. Nos. 5,156,621; 5,197,979; 5,336,258; 5,509,930; 6,001,126; 6,254,436; 6,342,070; 6,364,905; and 6,558,417, the teachings of which are incorporated herein by reference. Regardless, the leaflets (not shown) are attached to the structure 12 by sewing, crimping, adhesive, etc., for example, and can assume a variety of forms (e.g., autologous tissue, xenograph tissue, or synthetic material, such as polymers, metals, combinations thereof, and the like).

[0120] With any of the embodiments of the invention described herein, the valved stents can be placed inside of a failed valve with leaflets, as described herein, or the leaflets of the failed valve can be removed prior to implantation of the new valved stents, in accordance with known procedures for leaflet removal. Exemplary procedures for leaflet removal are described, for example, in U.S. Patent Publication No. 2004/0034380 (Woolfson et al.), and exemplary devices and methods of filtering in conjunction with leaflet removal are described, for example, in U.S. Pat. No. 6,896,690 (Lambrecht et al.) and U.S. Pat. No. 6,692,513 (Streeter et al.), all of which are incorporated herein by reference. In this way, the leaflets of the failed bioprosthesis cannot interfere with the leaflets of the newly implanted valved stent and particulates from the leaflet removal can be filtered from the blood of the patient.

[0121] Stents described herein may further include at least one location of a radiopaque, echogenic, or MRI visible material to facilitate visual confirmation of proper placement of the stent relative to the previously implanted prosthetic heart valve. Alternatively, other known surgical visual aids can be incorporated into the stent. Such visual aids can be included on at least one flange of the replacement heart valve and at least one stent post of the previously implanted heart valve to provide indicators for proper placement of the stent.

[0122] It is further noted that the stent embodiments described herein can also include a tubular structure that is generally positioned within the previously implanted heart valve, wherein the various flanges and stent post engagement features can extend from the body of the tubular structure. In addition, the stents described herein may include a gasket material around all or a portion of the

perimeter to provide for enhanced sealing between the new prosthetic valve and the previously implanted heart valve.

[0123] The present invention has now been described with reference to several embodiments thereof. The foregoing detailed description and examples have been given for clarity of understanding only. No unnecessary limitations are to be understood therefrom. It will be apparent to those skilled in the art that many changes can be made in the embodiments described without departing from the scope of the invention. Thus, the scope of the present invention should not be limited to the structures described herein, but only by the structures described by the language of the claims and the equivalents of those structures.

1-12. (canceled)

13: A replacement prosthetic heart valve for engagement with a previously implanted prosthetic heart valve having a plurality commissure posts, the replacement heart valve comprising:

- a stent structure comprising:
 - a generally tubular body portion;
 - a plurality of vertical members that are spaced apart from each other around a perimeter of the body portion and that extend in a direction that is generally parallel to a longitudinal axis of the body portion; and
 - a plurality of commissure post engagement members that are spaced apart from each other around a perimeter of the body portion and extending radially outwardly from the body portion;
- a plurality of leaflets attached within the tubular body portion;
- wherein the number of vertical members and the number of commissure post engagement members matches the number of commissure posts of the previously implanted heart valve;
- wherein the commissure post engagement members are configured to contact an exterior portion of the commissure posts of the previously implanted heart valve;
- wherein the vertical members are configured to contact an interior portion of the previously implanted heart valve; and
- wherein the commissure post engagement members and the vertical members are configured to capture the commissure posts of the previously implanted heart valve therebetween.

14: The replacement heart valve of claim 13, wherein each vertical member is configured to contact an interior portion of a commissure post of the previously implanted heart valve.

15: The replacement heart valve of claim 13, wherein the previously implanted prosthetic heart valve comprises three commissure posts.

16: The replacement heart valve of claim 13, wherein the previously implanted prosthetic heart valve comprises two commissure posts.

17: The replacement heart valve of claim 13, wherein the previously implanted prosthetic heart valve comprises a ring member, wherein the stent structure further comprises a plurality of flange members that extend outwardly from the body portion, the flange members spaced between adjacent vertical members, the flange members configured to contact a portion of the ring member.

18: The replacement heart valve of claim 5, wherein the flange members each comprise a generally U-shaped structure or a generally V-shaped structure.

19: The replacement heart valve of claim **13**, wherein the stent structure further comprises a plurality of flange members that extend outwardly from the body portion, the flange members spaced between adjacent vertical members, the flange members configured to contact an inflow portion of the previously implanted heart valve.

20: The replacement heart valve of claim **13**, wherein at least a portion of the stent structure is expandable.

21: The replacement heart valve of claim **13**, wherein at least a portion of the stent structure is self-expandable from a collapsed position to an expanded position in response to removal of an external compressive force.

22: The replacement heart valve of claim **13**, wherein at least a portion of the stent structure is expandable with the application of an outward radial force.

23: The replacement heart valve of claim **13**, further comprising a visually detectable marker.

24: The replacement heart valve of claim **13**, further comprising a sealing gasket surrounding at least a portion of a perimeter of the generally tubular body portion.

25: The replacement heart valve of claim **13**, wherein the vertical members each comprise a generally U-shaped structure or a generally V-shaped structure.

26: The replacement heart valve of claim **13**, wherein the stent structure further comprises a plurality of upper vertical members and a plurality of lower vertical members, wherein each of the upper vertical members extend in a direction opposite the plurality of lower vertical members.

27: The replacement heart valve of claim **26**, wherein each upper vertical member is longitudinally aligned with a corresponding one of the plurality of lower vertical members.

28: The replacement heart valve of claim **13**, wherein the vertical members are configured to align with the commissure posts of the previously implanted heart valve.

29: The replacement heart valve of claim **13**, wherein the previously implanted prosthetic heart valve comprises a ring member and a plurality of leaflets, wherein the stent structure further comprises a plurality of leaflet engagement members configured to hold the leaflets of the previously implanted prosthetic heart valve against the ring member.

30: The replacement heart valve of claim **29**, wherein leaflet engagement members each comprise a generally W-shaped structure, a generally U-shaped structure, or a generally V-shaped structure.

* * * * *