



(43) International Publication Date
7 May 2015 (07.05.2015)

(10) International Publication Number
WO 2015/065801 A1

- (51) **International Patent Classification:**
C10M 145/38 (2006.01) *C10M 129/76* (2006.01)
- (21) **International Application Number:**
PCT/US2014/061964
- (22) **International Filing Date:**
23 October 2014 (23.10.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/896,990 29 October 2013 (29.10.2013) US
- (71) **Applicant:** CRODA, INC. [US/US]; 300 Columbus Circle, Edison, NJ 08837-3907 (US).
- (72) **Inventors:** CHEN, Xin; 6 Phebe Court, Hockessin, DE 19707 (US). KURCHAN, Alexei, Nikolaevich; 204 Governors Drive, Wallingford, PA 19086 (US).
- (74) **Agents:** LEWIS, Christopher, R. et al.; RatnerPrestia, P.O. Box 980, Valley Forge, PA 19482 (US).
- (81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,

HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))

(54) **Title:** LUBRICANT COMPOSITION COMPRISING HYDROXYCARBOXYLIC ACID DERIVED FRICTION MODIFIER

(57) **Abstract:** The present invention relates to a lubricant composition containing a base stock and at least 0.01 wt% of a friction reducing additive which is a compound of the Formula (I): $R^1[(AO)_n-R^2]_m$ (I) wherein R^1 is the residue of a group having at least 2 active hydrogen atoms; m is at least 2; AO is an alkylene oxide residue; each n is independently from 0 to 100; and each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and on average at least 0.5 of R^2 groups are R^3 . The lubricant composition is suitable for use in an engine oil, a hydraulic oil or fluid, a gear oil and/or a metal-working fluid.



WO 2015/065801 A1

LUBRICANT COMPOSITION COMPRISING HYDROXYCARBOXYLIC ACID DERIVED FRICTION MODIFIER

This application is related to, and claims the benefit of priority of, U.S. Provisional Application No. 61/896,990, entitled LUBRICANT COMPOSITION, filed on 29 October 2013, the contents of which are incorporated herein by reference in their entirety for all purposes.

5 Field of Invention

The present invention relates to a lubricant composition comprising a base stock and a friction reducing additive. The lubricant composition may be used as an engine oil, a hydraulic oil or fluid, a gear oil and/or a metal-working fluid. The invention also relates to the use of the friction reducing additive and a method of reducing friction.

10 Background

Friction reducing additives that have been used to improve fuel economy in automotive engine oils fall into three main chemically-defined categories, which are organic, metal organic and oil insoluble. The organic friction-reducing additives themselves fall within four main categories which are carboxylic acids or their derivatives, nitrogen-containing compounds such as amides, imides, amines and their derivatives, phosphoric or phosphonic acid derivatives and organic polymers.

Automotive engine oils typically comprise a lubricant base stock and an additive package, both of which can contribute significantly to the properties and performance of the automotive engine oil.

20 The choice of lubricant base stock can have a major impact on properties such as oxidation and thermal stability, volatility, low temperature fluidity, solvency of additives, contaminants and degradation products, and traction. The American Petroleum Institute (API) currently defines five groups of lubricant base stocks (API Publication 1509).

Groups I, II and III are mineral oils which are classified by the amount of saturates and sulphur they contain and by their viscosity indices. Table 1 below illustrates these API classifications for Groups I, II and III.

Table 1

<u>Group</u>	<u>Saturates</u>	<u>Sulphur</u>	<u>Viscosity Index (VI)</u>
I	<90%	>0.03%	80-120
II	At least 90%	Not more than 0.03%	80-120
III	At least 90%	Not more than 0.03%	At least 120

Group I base stocks are solvent refined mineral oils, which are the least expensive base stock to produce, and currently account for the majority of base stock sales. They provide satisfactory oxidation stability, volatility, low temperature performance and traction properties and have very good solvency for additives and contaminants. Group II base stocks are mostly hydroprocessed mineral oils, which typically provide improved volatility and oxidation stability as compared to Group I base stocks. The use of Group II stocks has grown to about 30% of the US market. Group III base stocks are severely hydroprocessed mineral oils or they can be produced via wax or paraffin isomerisation. They are known to have better oxidation stability and volatility than Group I and II base stocks but have a limited range of commercially available viscosities.

Group IV base stocks differ from Groups I to III in that they are synthetic base stocks e.g. polyalphaolefins (PAOs). PAOs have good oxidative stability, volatility and low pour points. Disadvantages include moderate solubility of polar additives, for example antiwear additives.

Group V base stocks are all base stocks that are not included in Groups I to IV. Examples include alkyl naphthalenes, alkyl aromatics, vegetable oils, esters (including polyol esters, diesters and monoesters), polycarbonates, silicone oils and polyalkylene glycols.


To create a suitable engine oil, additives are blended into the chosen base stock. The additives either enhance the stability of the lubricant base stock or provide additional protection to the engine. Examples of engine oil additives include antioxidants, antiwear agents, detergents, dispersants, viscosity index improvers, defoamers, pour point depressants and friction reducing additives.

One area of concern for automotive engines is around reduction of fuel consumption and increasing energy efficiency. It is well known that the automotive engine oil has a significant part to play in the overall energy consumption of automotive engines. Automotive engines can be thought of as consisting of three discreet but connected mechanical assemblies which together make up the engine, the valve train, the piston assembly, and the bearings. Energy losses in mechanical components can be analysed according to the nature of the friction regime after the well-known Stribeck curve. Predominant losses in the valve train are boundary and elastohydrodynamic, in the bearings are hydrodynamic, and the pistons hydrodynamic and boundary. Hydrodynamic losses have been gradually improved by the reduction of automotive engine oil viscosity. Elastohydrodynamic losses can be improved by selection of the base stock type, taking into account the traction coefficient of the base stock. Boundary losses can be improved by careful selection of a friction reducing additive.

Summary of the Invention

We have now surprisingly discovered a lubricant composition which overcomes or significantly reduces at least one of the aforementioned problems.

Accordingly, the present invention provides a lubricant composition comprising a base stock and at least 0.01 wt% of a friction reducing additive which comprises a compound of the Formula (I):



wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

m is at least 2;


AO is an alkylene oxide residue;

each n is independently from 0 to 100; and

each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and

on average at least 0.5 of R^2 groups are R^3 .

The present invention also provides a method of reducing friction in an engine which comprises using an engine oil comprising a base stock and at least 0.01 wt% of a friction reducing additive which comprises a compound of the Formula (I):



wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

m is at least 2;


AO is an alkylene oxide residue;

each n is independently from 0 to 100; and

each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and

on average at least 0.5 of R^2 groups are R^3 .

The present invention further provides the use of a compound of the Formula (I):



wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

m is at least 2;

5 AO is an alkylene oxide residue;

each n is independently from 0 to 100; and

each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and


10 on average at least 0.5 of R^2 groups are R^3 ,

to reduce the co-efficient of friction of a lubricant composition.

The friction reducing additive described herein may advantageously improve the performance of the lubricant composition by reducing friction losses in a system to which the lubricant composition is applied.

The friction reducing additive described herein can be used as a friction reducing additive in engine oils and in particular in automotive engine oils, automotive gear and transmission oils, industrial gear oils, hydraulic oils, compressor oils, turbine oils, cutting oils, rolling oils, drilling oils, lubricating greases and the like.

20 The friction reducing additive comprises or consists of a compound or composition of the Formula (I):



wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

25 m is at least 2;

AO is an alkylene oxide residue;

each n is independently from 0 to 100; and

each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and

30 on average at least 0.5 of R^2 groups are R^3 .

The friction reducing additive is at least notionally built up from the group R¹ that can be considered as the "core group" of the compound. This core group is the residue (after removal of m active hydrogen atoms) of a compound containing at least 2 active hydrogen atoms, preferably present in hydroxyl and/or amino groups, and more preferably present in hydroxyl groups only. Preferably the core group is the residue of a substituted hydrocarbyl group, particularly a C₃ to C₃₀ substituted hydrocarbyl compound.

Examples of R¹ core groups include the residues of the following compounds after removal of m active hydrogen atoms:

1 glycerol and the polyglycerols, especially diglycerol and triglycerol, the partial esters thereof, or any triglycerides containing multiple hydroxyl groups, for example castor oil;

2 tri- and higher polymethylol alkanes such as trimethylol ethane, trimethylol propane and pentaerythritol, and the partial esters thereof;

3 sugars, particularly non-reducing sugars such as sorbitol, mannitol, and lactitol, etherified derivatives of sugars such as sorbitan (the cyclic dehydro-ethers of sorbitol), partial alkyl acetals of sugars such as methyl glucose and alkyl (poly-) saccharides, and other oligo-/poly-mers of sugars such as dextrans, partially esterified derivatives of sugars, such as fatty acid esters, for example of lauric, palmitic, oleic, stearic and behenic acid, esters of sorbitan, sorbitol, and sucrose, aminosaccharides such as N-alkylglucamines and their respective N-alkyl-N-alkenoyl glucamides;

4 polyhydroxy carboxylic acids especially citric and tartaric acids;

5 amines including di- and poly-functional amines, particularly alkylamines including alkyl diamines such as ethylene diamine (1,2-diaminoethane);

6 amino-alcohols, particularly the ethanolamines, 2-aminoethanol, di-ethanolamine and triethanolamine;

7 carboxylic acid amides such as urea, malonamide and succinamide; and

8 amido carboxylic acids such as succinamic acid.

Preferred R¹ core groups are residues of groups having at least three, more preferably in the range from 4 to 10, particularly 5 to 8, and especially 6 free hydroxyl and/or amino groups. The R¹ group preferably has a linear C₄ to C₇, more preferably C₆ chain. The hydroxyl or amino groups are preferably directly bonded to the chain carbon atoms. Hydroxyl groups are preferred.

R¹ is preferably the residue of an open chain tetratol, pentitol, hexitol or heptitol group or an anhydro, e.g. cycloether anhydro, derivative of such a group. In a particularly preferred embodiment, R¹ is the residue of, or a residue derived from, a sugar, more preferably a

monosaccharide such as glucose, fructose or sorbitol, a disaccharide such as maltose, palitose, lactitol or lactose or a higher oligosaccharide. R^1 is preferably the residue of a monosaccharide, more preferably of glucose, fructose or sorbitol, and particularly of sorbitol.

The open chain form of R^1 groups is preferred, however groups including internal cyclic ether functionality can be used, and may be obtained inadvertently if the synthetic route exposes the group to relatively high temperatures or other conditions, which promote such cyclisation.

The index m is a measure of the functionality of the R^1 core group and the alkoxylation reactions will replace some or all of the active hydrogen atoms (dependent on the molar ratio of core group to alkoxylation group) in the molecule from which the core group is derived.

Reaction at a particular site may be restricted or prevented by steric hindrance or suitable protection. The terminating hydroxyl groups of the polyalkylene oxide chains in the resulting compounds are then available for reaction with the above defined acyl compounds. The index m will preferably be at least 3, more preferably in the range from 4 to 10, particularly 5 to 8, and especially 5 to 6. Mixtures may be, and normally are, employed, and therefore m can be an average value and may be non-integral.

The alkylene oxide groups AO are typically groups of the formula: $-(C_rH_{2r}O)-$ where r is 2, 3 or 4, preferably 2 or 3, i.e. an ethyleneoxy $-(C_2H_4O)-$ or propyleneoxy

$-(C_3H_6O)-$ group, and it may represent different groups along the alkylene oxide chain.

Generally, it is desirable that the chain is a homopolymeric ethylene oxide chain. However, the chain may be a homopolymer chain of propylene glycol residues or a block or random copolymer chain containing both ethylene glycol and propylene glycol residues. Usually, where co-polymeric chains of ethylene and propylene oxide units are used the molar proportion of ethylene oxide units used will be at least 50% and more usually at least 70%.

The number of alkylene oxide residues in the (poly)alkylene oxide chains, i.e. the average value of the parameter n , will suitably be in the range from 1 to 50, preferably 2 to 20, more preferably 4 to 15, particularly 7 to 10, and especially 8 to 9. The total of the indices n , or the product of indices $n \times m$, is suitably in the range from 5 to 300, preferably 10 to 100, more preferably 25 to 65, particularly 40 to 60, and especially 45 to 55. The value of the index n is an average value, which includes statistical variation in the chain length.

The groups R^2 are the "terminating groups" of the (poly)alkylene oxide chains. The terminating groups are hydrogen or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl carboxylic acid or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid. Preferably each R^3 is independently a residue of a polyhydroxyalkyl carboxylic acid, a residue of a hydroxyalkyl carboxylic acid and/or a residue

of an oligomer of the hydroxyalkyl carboxylic acid, more preferably a residue of a polyhydroxyalkyl carboxylic acid.

On average, suitably at least 1.0, preferably at least 1.5, more preferably at least 2.0, particularly at least 2.2, and especially at least 2.4 of the R^2 groups are R^3 . In addition, on
5 average suitably up to 6.0, preferably up to 4.0, more preferably up to 3.0, particularly up to 2.7, and especially up to 2.5 of the R^2 groups are R^3 .

The hydroxyalkyl and hydroxyalkenyl carboxylic acids are of formula $HO-X-COOH$ where X is a divalent saturated or unsaturated, preferably saturated, aliphatic radical containing at least 8 carbon atoms and no more than 20 carbon atoms, typically from 11 to 17 carbons and in
10 which there are at least 4 carbon atoms directly between the hydroxyl and carboxylic acid groups.

Desirably the hydroxyalkyl carboxylic acid is 12-hydroxystearic acid. In practice such hydroxyalkyl carboxylic acids are commercially available as mixtures of the hydroxyl acid and the corresponding unsubstituted fatty acid. For example 12-hydroxystearic acid is typically
15 manufactured by hydrogenation of castor oil fatty acids including the C18 unsaturated hydroxyl acid and the non-substituted fatty acids (oleic and linoleic acids) which on hydrogenation gives a mixture of 12-hydroxystearic and stearic acids. Commercially available 12-hydroxystearic acid typically contains about 5 to 8% of unsubstituted stearic acid.

The polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid may be manufactured by
20 polymerising the above hydroxyalkyl or hydroxyalkenyl carboxylic acid. The presence of the corresponding unsubstituted fatty acid acts as a terminating agent and therefore limits the chain length of the polymer. Desirably the number of hydroxyalkyl or hydroxyalkenyl units is on average from 2 to 12, preferably from 3 to 10, more preferably from 4 to 9, particularly from 5 to 8, and especially 6 to 7. The molecular weight of the polyacid is typically from 600
25 to 3,000, particularly from 900 to 2,700, more particularly from 1,500 to 2,400 and especially about 2,100.

The residual acid value for the polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid typically is less than 50 mgKOH/g and a preferable range is 30 to 35 mgKOH/g. Typically the hydroxyl value for the polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid is a maximum of 40
30 mgKOH/g and a preferable range is 20 to 30 mgKOH/g.

The oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid may differ from the polymer in that termination is not by the unsubstituted corresponding fatty acid. Desirably it is a dimer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid.

In one preferred embodiment, on average suitably at least 1.0, preferably at least 1.5, more preferably at least 2.0, particularly at least 2.3, and especially at least 2.4 of the R^2 groups are
35

R³ groups which are polyhydroxyalkyl carboxylic acid residues. In addition, on average suitably up to 4.0, preferably up to 3.5, more preferably up to 3.0, particularly up to 2.7, and especially up to 2.5 of the R² groups are R³ groups which are polyhydroxyalkyl carboxylic acid residues. These polyhydroxyalkyl carboxylic acid residues suitably contain on average from 3
5 to 10, preferably from 4 to 9, more preferably from 5 to 8, particularly from 6 to 7, and especially 7 hydroxyalkyl monomer units.

The polyhydroxyalkyl carboxylic acid residues are preferably terminated with an unsubstituted carboxylic acid, more preferably with stearic acid.

In another preferred embodiment, when the R³ groups comprise hydroxyalkyl carboxylic acid
10 residues, preferably polyhydroxyalkyl carboxylic acid residues, the total number of all of the hydroxyalkyl carboxylic acid residues present in the compound of Formula (I) defined herein is suitably on average in the range from 5 to 30, preferably 8 to 20, more preferably 10 to 17, particularly 12 to 15, and especially 13 to 14 hydroxyalkyl monomer units.

In a further preferred embodiment, on average suitably at least 2.0, preferably at least 2.5,
15 more preferably at least 3.0, particularly at least 3.3, and especially at least 3.5 of the R² groups are H. In addition, on average suitably up to 5.0, preferably up to 4.5, more preferably up to 4.0, particularly up to 3.7, and especially up to 3.6 of the R² groups are H.

When the core group is derived from, for example, pentaerythritol, alkoxylation of the core residue may be evenly distributed over the four available sites from which an active hydrogen
20 can be removed and on esterification of the terminal hydroxyl functions the distribution of acyl groups will be close to the expected random distribution. However, when the core group is derived from compounds, such as sorbitol, where all of the active hydrogen atoms are not equivalent, alkoxylation may give unequal chain lengths for the polyalkyleneoxy chains.

The friction reducing additive can be made by firstly alkoxyating R¹ core groups containing m
25 active hydrogen atoms, by techniques well known in the art, for example by reacting with the required amounts of alkylene oxide, for example ethylene oxide and/or propylene oxide. The second stage of the process preferably comprises reacting the aforementioned alkoxyated species with a polyhydroxyalkyl (alkenyl) carboxylic acid and/or a hydroxyalkyl(alkenyl) carboxylic acid under standard catalysed esterification conditions at temperatures up to
30 250°C.

Thus, the friction reducing additive of Formula (I) can be produced by reacting the group R¹ with alkylene oxide and then esterifying the alkoxyated product of this reaction with a polyhydroxyalkyl (alkenyl) carboxylic acid, a hydroxyalkyl(alkenyl) carboxylic acid, or a mixture thereof.

35 In one preferred embodiment, the friction reducing additive is prepared by reaction of the

alkoxylated core group R¹ with a polyhydroxyalkyl carboxylic acid where the molar ratio of alkoxylated core group to polyacid preferably ranges from 1: 1 to 1: 4, more preferably from 1: 2 to 1: 2.8. Preferably the friction reducing additive prepared by this route has a molecular weight (Mn) between 3,000 to 10,000, more preferably 4,000 to 7000, and particularly 5,000 to 6,000.

The lubricant composition of the present invention comprises a base stock. The lubricant composition may comprise at least 50 wt%, preferably at least 60 wt%, more preferably at least 70 wt%, even more preferably least 80 wt% of base stock based on the total weight of the composition. The lubricant composition may comprise up to 98 wt%, preferably up to 95 wt%, more preferably up to 90 wt% base stock based on the total weight of the composition.

The lubricant composition may comprise at least 0.02 wt%, suitably at least 0.05 wt%, preferably at least 0.1 wt%, more preferably at least 0.5 wt%, even more preferably at least 1 wt% of the friction reducing additive based on the total weight of the composition. The lubricant composition may comprise at least 5 wt%, or even at least 10 wt% of the friction reducing additive. The lubricant composition may comprise up to 20 wt%, preferably up to 15 wt% of the friction reducing additive based on the total weight of the composition.

In one embodiment, the lubricant composition is non-aqueous. However, it will be appreciated that components of the lubricant composition may contain small amounts of residual water (moisture) which may therefore be present in the lubricant composition. The lubricant composition may comprise less than 5% water by weight based on the total weight of the composition. More preferably, the lubricant composition is substantially water free, i.e. contains less than 2%, less than 1%, or preferably less than 0.5% water by weight based on the total weight of the composition. Preferably the lubricant composition is substantially anhydrous.

The lubricant composition may be an engine oil, hydraulic oil or fluid, gear oil or metal working fluid. To adapt the lubricant composition to its intended use, the lubricant composition may comprise one or more of the following further additive types.

1. Dispersants: for example, alkenyl succinimides, alkenyl succinate esters, alkenyl succinimides modified with other organic compounds, alkenyl succinimides modified by post-treatment with ethylene carbonate or boric acid, pentaerythritols, phenate-salicylates and their post-treated analogs, alkali metal or mixed alkali metal, alkaline earth metal borates, dispersions of hydrated alkali metal borates, dispersions of alkaline-earth metal borates, polyamide ashless dispersants and the like or mixtures of such dispersants.

2. Anti-oxidants: Anti-oxidants reduce the tendency of mineral oils to deteriorate in service which deterioration is evidenced by the products of oxidation such as sludge and varnish-like

deposits on the metal surfaces and by an increase in viscosity. Examples of anti-oxidants include phenol type (phenolic) oxidation inhibitors, such as 4,4'-methylene-bis(2,6-di-tert-butylphenol), 4,4'-bis(2,6-di-tert-butylphenol), 4,4'-bis(2-methyl-6-tert-butylphenol), 2,2'-methylene-bis(4-methyl-6-tert-butyl-phenol), 4,4'-butylidene-bis(3-methyl-6-tert-butylphenol),
5 4,4'-isopropylidene-bis(2,6-di-tert-butylphenol), 2,2'-methylene-bis(4-methyl-6-nonylphenol), 2,2'-isobutylidene-bis(4,6-dimethylphenol), 2,2'-methylene-bis(4-methyl-6-cyclohexylphenol), 2,6-di-tert-butyl-4-methylphenol, 2,6-di-tert-butyl-4-ethylphenol, 2,6-di-tert-butylphenol, 2,4-dimethyl-6-tert-butyl-phenol, 2,6-di-tert-butyl-dimethylamino-p-cresol, 2,6-di-tert-butyl-4-(N,N'-dimethylamino-methylphenol), 4,4'-thiobis(2-methyl-6-tert-butylphenol), 2,2'-thiobis(4-methyl-6-tert-butylphenol), bis(3-methyl-4-hydroxy-5-tert-butylbenzyl)-sulfide, and bis(3,5-di-tert-butyl-4-hydroxybenzyl). Other types of oxidation inhibitors include alkylated diphenylamines (e.g., Irganox L-57 from Ciba-Geigy), metal dithiocarbamate (e.g., zinc dithiocarbamate), and methylenebis(dibutyldithiocarbamate).

3. Antiwear agents: As their name implies, these agents reduce wear of moving metallic
15 parts. Examples of such agents include phosphates, phosphites, carbamates, esters, sulfur containing compounds, and molybdenum complexes.

4. Emulsifiers: for example, linear alcohol ethoxylates.

5. Demulsifiers: for example, addition products of alkylphenol and ethylene oxide, polyoxyethylene alkyl ethers, and polyoxyethylene sorbitan esters.

20 6. Extreme pressure agents (EP agents): for example, zinc dialkyldithiophosphate (primary alkyl, secondary alkyl, and aryl type), sulfurized oils, diphenyl sulfide, methyl trichlorostearate, chlorinated naphthalene, fluoroalkylpolysiloxane, and lead naphthenate. A preferred EP agent is zinc dialkyl dithiophosphate (ZnDTP), e.g. as one of the co-additive components for an antiwear hydraulic fluid composition.

25 7. Multifunctional additives: for example, sulfurized oxymolybdenum dithiocarbamate, sulfurized oxymolybdenum organo phosphorodithioate, oxymolybdenum monoglycethide, oxymolybdenum diethylate amide, amine-molybdenum complex compound, and sulfur-containing molybdenum complex compound.

8. Viscosity index improvers: for example, polymethacrylate polymers, ethylene-propylene
30 copolymers, styrene-isoprene copolymers, hydrogenated styrene-isoprene copolymers, polyisobutylene, and dispersant type viscosity index improvers.

9. Pour point depressants: for example, polymethacrylate polymers.

10. Foam inhibitors: for example, alkyl methacrylate polymers and dimethyl silicone polymers.

The lubricant composition may comprise at least 0.5 wt% of a further additive or a mixture of further additives, preferably at least 1 wt%, more preferably at least 5 wt% based on the total weight of the composition. The lubricant composition may comprise up to 30 wt% of a further additive or a mixture of further additives, preferably up to 20 wt%, more preferably up to 10 wt% based on the total weight of the composition.

The additive or additives may be available in the form of a commercially available additive pack. Such additive packs vary in composition depending on the required use of the additive pack. A skilled person may select a suitable commercially available additive pack for each of: an engine oil, a gear oil, a hydraulic fluid and a metal working fluid. An example of a suitable additive pack for an engine oil is Hitec 11100 ex. Afton Chemical Corporation, US which is recommended to be used at about 10 wt% of the lubricant composition. An example of a suitable additive pack for a gear oil is Additin RC 9451 ex. Rhein Chemie Rheinau GmbH, Germany which is recommended to be used at between 1.5 to 3.5 wt% of the lubricant composition. An example of a suitable additive pack for a hydraulic oil or fluid is Additin RC 9207 ex. Rhein Chemie Rheinau GmbH, Germany which is recommended to be used at about 0.85 wt% of the lubricant composition. An example of a suitable additive pack for a metal working fluid is Additin RC 9410 ex. Rhein Chemie Rheinau GmbH, Germany which is recommended to be used at between 2 to 7 wt% of the lubricant composition.

In this specification, base stock Group nomenclatures as defined by the American Petroleum Institute (API) will be used. The base stock may be selected based on the intended use of the lubricant composition.

Preferably the base stock is selected from the group consisting of an API Group I, II, III, IV, V base stock or mixtures thereof. If the base stock includes a polyalphaolefin (PAO) from Group IV then the base stock may also include a mineral oil from Group I, II or III or an ester from Group V to improve the solubility of the friction reducing additive in the base stock. The ester from Group V may be present at between 5 to 10 wt% of the lubricant composition to improve the solubility of the friction reducing additive in the base stock. The base stock may be a mixture of Group IV and Group V base stocks or Group IV and Group I, II or III base stocks.

In one embodiment, the lubricant composition of the present invention is used as an engine oil, preferably an automotive engine oil. When the lubricant composition is an engine oil, the friction reducing additive is preferably present at a concentration in the range from 0.1 to 10 wt% based on the total weight of the engine oil.

For an automotive engine oil the term base stock includes both gasoline and diesel (including heavy duty diesel (HDDEO)) engine oils. The base stock may be chosen from any of the

Group I to Group V base oils (which includes Group III+ gas to liquid) or a mixture thereof. Preferably the base stock has one of Group II, Group III or a Group IV base oil as its major component, especially Group III. By major component is meant at least 50%, preferably at least 65%, more preferably at least 75%, especially at least 85% by weight of base stock.

- 5 The base stock may also comprise as a minor component, preferably less than 30%, more preferably less than 20%, especially less than 10% by weight of base stock of any or a mixture of Group III+, IV and/or Group V base stocks which have not been used as the major component in the base stock. Examples of such Group V base stocks include alkyl naphthalenes, alkyl aromatics, vegetable oils, esters, for example monoesters, diesters and
10 polyol esters, polycarbonates, silicone oils and polyalkylene glycols. More than one type of Group V base stock may be present. Preferred Group V base stocks are esters, particularly polyol esters.

For engine oils, the friction reducing additive may be present at levels of at least 0.2 wt%, preferably at least 0.3 wt%, more preferably at least 0.5 wt% based on the total weight of the
15 engine oil. The friction reducing additive may be present at levels of up to 5 wt%, preferably up to 3 wt %, more preferably up to 2 wt% based on the total weight of the engine oil.

The automotive engine oil may also comprise other types of additives of known functionality at levels between 0.1 to 30 wt%, more preferably between 0.5 to 20 wt%, yet more preferably between 1 to 10 wt% based on the total weight of the engine oil. These further additives can
20 include detergents, dispersants, oxidation inhibitors, corrosion inhibitors, rust inhibitors, anti-wear additives, foam depressants, pour point depressants, viscosity index improvers and mixtures thereof. Viscosity index improvers may include polyisobutenes, polymethacrylate acid esters, polyacrylate acid esters, diene polymers, polyalkyl styrenes, alkenyl aryl conjugated diene copolymers and polyolefins. Foam depressants may include silicones and
25 organic polymers. Pour point depressants may include polymethacrylates, polyacrylates, polyacrylamides, condensation products of haloparaffin waxes and aromatic compounds, vinyl carboxylate polymers, terpolymers of dialkylfumarates, vinyl esters of fatty acids and alkyl vinyl ethers. Ashless detergents may include carboxylic dispersants, amine dispersants, Mannich dispersants and polymeric dispersants. Antiwear additives may include ZDDP,
30 ashless and ash containing organic phosphorous and organo-sulphur compounds, boron compounds, and organo-molybdenum compounds. Ash-containing dispersants may include neutral and basic alkaline earth metal salts of an acidic organic compound. Oxidation inhibitors may include hindered phenols and alkyl diphenylamines. Additives may include more than one functionality in a single additive.

For an engine oil, the base stock may range from SAE viscosity grade 0W to 15W. The viscosity index is preferably at least 90 and more preferably at least 105. The base stock preferably has a viscosity at 100°C of 3 to 10 mm²/s, more preferably 4 to 8 mm²/s. The Noack volatility, measured according to ASTM D-5800 is preferably less than 20%, more preferably less than 15%.

The lubricant composition of the present invention may be used as a gear oil. The gear oil may be an industrial, automotive and/or marine gear oil. When the lubricant composition is a gear oil, the friction reducing additive is preferably present in the range between 0.1 to 10 wt% based on the total weight of the gear oil.

For gear oils, the friction reducing additive may be present at levels of at least 0.2 wt%, preferably at least 0.3 wt%, more preferably at least 0.5 wt% based on the total weight of the gear oil. The friction reducing additive may be present at levels of up to 5 wt%, preferably up to 3 wt %, more preferably up to 2 wt% based on the total weight of the gear oil.

The gear oil may have a kinematic viscosity according to an ISO grade. An ISO grade specifies the mid-point kinematic viscosity of a sample at 40°C in cSt (mm²/s). For example, ISO 100 has a viscosity of 100 ± 10 cSt and ISO 1000 has a viscosity of 1000 ± 100 cSt. The gear oil preferably has a viscosity in the range from ISO 10 to ISO 1500, more preferably ISO 68 to ISO 680.

Gear oils according to the invention preferably have good low temperature properties. For example, the viscosity of such formulations at -35°C is less than 120,000 centipoise (cP), more preferably less than 100,000 cP, especially less than 90,000 cP.

Industrial gear oils include those suitable for use in gear boxes with spur, helical, bevel, hypoid, planetary and worm gears. Suitable applications include use in mining; mills such as paper, textile and sugar mills; steel production and in wind turbines. One preferred application is in wind turbines where the gear boxes typically have planetary gears.

In a wind turbine, the gear-box is typically placed between the rotor of a wind turbine blade assembly and the rotor of a generator. The gear-box may connect a low-speed shaft turned by the wind turbine blade(s) rotor at about 10 to 30 rotations per minute (rpm), to one or more high speed shafts that drive the generator at about 1000 to 2000 rpm, the rotational speed required by most generators to produce electricity. The high torque exerted in the gear-box can generate huge stress on the gears and bearings in the wind turbine. A gear oil of the present invention may enhance the fatigue life of the gear-box of a wind turbines by reducing the friction between the gears.

Lubricants in wind turbines gearboxes are often subjected to prolonged periods of use between maintenance, i.e. long service intervals. Therefore a long lasting lubricant

composition with high stability may be required, so as to provide suitable performance over lengthy durations of time.

Automotive gear oils include those suitable for use in manual transmissions, transfer cases and differentials which all typically use a hypoid gear. By transfer case we mean a part of a four wheel drive system found in four wheel drive and all wheel drive systems. It is connected to the transmission and also to the front and rear axles by means of driveshafts. It is also referred to in the literature as a transfer gearcase, transfer gearbox, transfer box or jockey box.

Marine thruster gearboxes have specific gear oils that include a higher proportion of additives, e.g. dispersants, anticorrosives, to deal with corrosion and water entrainment compared to industrial and automotive gear oils. There are also outboard gear oils used for the propeller unit which may be more relevant for smaller vessels.

A gear oil according to the invention may comprise one or more of the further additives described herein. The gear oil preferably comprises one or more additive(s) which may include at least one species of extreme-pressure agent selected from the group consisting of sulfur-based additives and phosphorus-based additives, or at least one species of the extreme-pressure agents and at least one species of additive selected from the group consisting of solubilizing agent, ashless dispersant, pour point depressant, antifoaming agent, antioxidant, rust inhibitor, and corrosion inhibitor.

Other additives may be present in the gear oils of known functionality at levels between 0.01 to 30 wt%, more preferably between 0.01 to 20 wt% more especially between 0.01 to 10 wt% based on the total weight of the gear oil. These can include detergents, extreme pressure/antiwear additives, dispersants, corrosion inhibitors, rust inhibitors, friction modifiers, foam depressants, pour point depressants, and mixtures thereof. Extreme pressure/antiwear additives include ZDDP, tricresyl phosphate, amine phosphates. Corrosion inhibitors include sarcosine derivatives, for example Crodasinic O available from Croda Europe Ltd. Foam depressants include silicones and organic polymers. Pour point depressants include polymethacrylates, polyacrylates, polyacrylamides, condensation products of haloparaffin waxes and aromatic compounds, vinyl carboxylate polymers, terpolymers of dialkylfumarates, vinyl esters of fatty acids and alkyl vinyl ethers. Ashless detergents include carboxylic dispersants, amine dispersants, Mannich dispersants and polymeric dispersants. Friction modifiers include amides, amines and partial fatty acid esters of polyhydric alcohols. Ash-containing dispersants include neutral and basic alkaline earth metal salts of an acidic organic compound. Additives may have more than one functionality in a single material.

The gear oil may further comprise an antioxidant preferably in the range 0.2 to 2 wt%, more preferably 0.4 to 1 wt% by weight based on the total weight of the gear oil. Antioxidants include hindered phenols, alkyl diphenylamines and derivatives and phenyl alpha naphthylamines and derivatives of. Gear oil compositions with the presence of the
5 antioxidant preferably exhibit a percentage viscosity loss, measured using a modified version of CEC L-40-A-93, over a 100 hour period of less than 20%, more preferably less than 15% and especially less than 10%.

The gear oil preferably comprises at least 0.05 wt%, more preferably at least 0.5 wt%, particularly at least 1 wt%, and especially at least 1.5 wt% of further additive(s) (additive pack)
10 based upon the total weight of the gear oil. The gear oil preferably comprises up to 15 wt%, more preferably up to 10 wt%, particularly up to 4 wt%, and especially up to 2.5 wt% of further additive(s) (additive pack) based upon the total weight of the gear oil.

Suitable commercially available additive packs for industrial gear oils include Hitec 307 (for wind turbines), 315, 317 and 350 (ex Afton); Irgalube ML 605 A (ex BASF); Lubrizol IG93MA,
15 506, 5064 and 5091 (ex Lubrizol); Vanlube 0902 (ex Vanderbilt); RC 9330, 9410 and 9451 (ex Rhein Chemie); NA-LUBE BL-1208 (ex King Industries).

One use of the gear oil is in a wind turbine gear box. A gear box is typically placed between the rotor of a wind turbine blade assembly and the rotor of a generator. The gear box may connect a low-speed shaft turned by the wind turbine blade(s) rotor at about 10 to 30
20 rotations per minute (rpm), to one or more high speed shafts that drive the generator at about 1000 to 2000 rpm, the rotational speed required by most generators to produce electricity. The high torque exerted in the gear-box can generate huge stress on the gears and bearings in the wind turbine. A gear oil described herein may enhance the fatigue life of the gear box of a wind turbine by reducing the friction between the gears.

25 Gear oils in wind turbine gear boxes are often subjected to prolonged periods of use between maintenance, i.e. long service intervals. Therefore a long lasting gear oil with high stability may be required, so as to provide suitable performance over lengthy durations of time.

The lubricant composition of the present invention may be used as a hydraulic oil or fluid. When the lubricant composition is a hydraulic oil or fluid, the friction reducing additive is
30 suitably present in the range from 0.1 to 10 wt% based on the total weight of the hydraulic fluid.

For hydraulic fluids, the friction reducing additive may be present at levels of at least 0.2 wt%, preferably at least 0.3 wt%, more preferably at least 0.5 wt% based on the total weight of the hydraulic fluid. The friction reducing additive may be present at levels of up to 5 wt%,

preferably up to 3 wt %, more preferably up to 2 wt% based on the total weight of the hydraulic fluid.

The hydraulic fluid may have a viscosity from ISO 10 to ISO 100, preferably from ISO 32 to ISO 68.

- 5 Hydraulic fluids find use wherever there is a need to transfer pressure from one point to another in a system. Some of the many commercial applications where hydraulic fluids are utilized are in aircraft, braking systems, compressors, machine tools, presses, draw benches, jacks, elevators, die-castings, plastic moldings, welding, coal-mining, tube reducing machines, paper-machine press rolls, calendar stacks, metal working operations, fork lifts,
10 and automobiles.

A hydraulic oil or fluid according to the invention may comprise one or more of the further additives described herein.

- The lubricant composition of the present invention may be used as a metalworking fluid. When the lubricant composition is a metal working fluid, the friction reducing additive is
15 preferably present in the range between 1 to 20 wt% based on the total weight of the metal working fluid.

- For metal working fluids, the friction reducing additive may be present at levels of at least 2 wt%, preferably at least 3 wt%, more preferably at least 5 wt% based on the total weight of the metal working fluid. The friction reducing additive may be present at levels of up to 15
20 wt%, preferably up to 10 wt % based on the total weight of the metal working fluid.

The metal working fluid may have a viscosity of at least ISO 10, preferably at least ISO 100.

- Metalworking operations include for example, rolling, forging, hot-pressing, blanking, bending, stamping, drawing, cutting, punching, spinning and the like and generally employ a lubricant to facilitate the operation. Metalworking fluids generally improve these operations in that they
25 can provide films of controlled friction or slip between interacting metal surfaces and thereby reduce the overall power required for the operations, and prevent sticking and decrease wear of dies, cutting bits and the like. Sometimes the lubricant is expected to help transfer heat away from a particular metalworking contact point.

- Metal working fluids often comprise a carrier fluid and one or more additives. The carrier fluid
30 imparts some general lubricity to the metal surface and carries/delivers the specialty additives to the metal surfaces. Additionally, the metal working fluid may provide a residual film on the metal part thereby adding a desired property to the metal being processed. The additives can impart a variety of properties including friction reduction beyond hydrodynamic film lubrication,

metal corrosion protection, extreme pressure or anti-wear effects. The carrier fluid may be a base stock.

Carrier fluids include various petroleum distillates including American Petroleum Institute Group I to V base stocks. The additives can exist within the carrier fluid in a variety of forms including as dissolved, dispersed in, and partially soluble materials. Some of the metal working fluid may be lost to or deposited on the metal surface during the working process; or may be lost to the environment as spillage, sprays, etc; and may be recyclable if the carrier fluid and additives have not degraded significantly during use. Due to entry of a percentage of the metal working fluid into process goods and industrial process streams, it is desirable if the components to the metal working fluid are eventually biodegradable and pose little risk of bioaccumulation to the environment

The metalworking fluid may comprise up to 90 wt% of base stock, more preferably up to 80 wt% based on the total weight of the metal working fluid.

A metalworking fluid according to the invention may comprise one or more of the further additives described herein. The metalworking fluid may comprise at least 10 wt% of further additives based on the total weight of the metal working fluid.

The lubricant composition of the present invention may comprise friction reducing agents other than those defined herein such as esters, partial esters, phosphonates, organomolybdenum-based compounds, fatty acids, higher alcohols, fatty acid esters, sulfur containing esters, phosphate esters, acid phosphoric acid esters, and amine salts of phosphoric acid esters.

In one preferred embodiment, the lubricant composition according to the present invention comprises only friction reducing agents which are compounds of Formula (I). Thus, one preferred lubricant composition consists essentially of, or consists of, friction reducing agents which are compounds of Formula (I) defined herein.

The compounds of Formula (I) may reduce the coefficient of friction of a lubricant composition, particularly when measured using a mini-traction machine (MTM), when compared to an equivalent lubricant composition comprising no friction reducing additive. The coefficient of friction may be a kinetic coefficient of friction.

The compounds of Formula (I) defined herein may be capable of reducing the coefficient of friction of a lubricant composition, preferably an engine oil, when compared to an equivalent composition comprising no friction reducing additive, by at least 15%, preferably by at least 30%, more preferably by at least 40%, particularly by at least 45%, and especially by at least 50% when using a mini-traction machine, in the test described herein, preferably using Group II mineral oil, at a temperature of 100°C, load of 1.0 GPa and a speed of rotation of 0.02 m/s.

The coefficient of friction may be reduced, as described herein, over the temperature range 0 to 200°C, preferably over the range 20 to 180°C, more preferably over the range 40 to 150°C.

The coefficient of friction may be reduced, as described herein, when measured at a speed of rotation of 0.002 m/s, 0.02 m/s, 0.2 m/s and/or at 2 m/s.

- 5 The invention has been illustrated by the following non-limiting examples.

The following test procedure was used.

Mini-Traction Machine (MTM)

The coefficient of friction of a lubricant composition (control composition with no friction-reducing additive) containing 100 wt% of Group II mineral oil (Pure Performance 110N,
10 Phillips 66 company) was determined at 40°C, 100°C and 150°C using a MTM with a ¾ inch ball on a smooth disc. The measurements were repeated using the control composition above containing an additional 0.5 wt% of the friction reducing additive being evaluated (test composition).

The MTM was supplied by PCS Instruments of London, UK. This machine provides a method
15 for measuring the coefficient of friction of a given lubricant using a ball-on-disc configuration whilst varying several properties such as speed, load and temperature. The MTM is a computer controlled precision traction measurement system whose test specimens and configuration have been designed such that realistic pressures, temperatures and speeds can be attained without requiring large loads, motors or structures. The disc was AISI 52100
20 hardened bearing steel with a mirror finish ($R_a < 0.01 \mu\text{m}$) and the ball was AISI 52100 hardened bearing steel. The load applied was 36 N (1 GPa contact pressure) and the speed of rotation was varied from 0.001m/s to 2 m/s. Approximately 50 ml of the lubricant composition was then added. The ball was loaded against the face of the disc and the ball and disc were driven independently to create a mixed rolling/sliding contact with a slide-roll
25 ratio of 50%. The frictional force between the ball and disc was measured by a force transducer. Additional sensors measured the applied load and lubricant temperature.

Examples

Example 1

100 g of sorbitol and 0.1 g of NaOH (0.007% by wt) were added to a pressurized stainless-
30 steel reactor. The reaction mixture was heated with vigorous mixing to 120°C. 1,222 g of ethylene oxide was then added in portions and allowed to react, so that the total pressure of the gases did not exceed 35 psi. After addition of the last portion of the ethylene oxide, the reaction mixture was heated to 150°C and stirred at this temperature for two additional hours to complete the ethoxylation reaction.

453 g of ethoxylated sorbitol (produced above), 997 g of poly(12-hydroxystearic acid) and 0.3 g of tin oxalate catalyst were mixed together and heated to 230°C. Vacuum and slight nitrogen sparge (0.1 cfm) were applied, and the reaction was carried out until the acid number of the mixture was below 2 mgKOH/g. The reaction was then cooled to 80-90°C, and 4 g phosphoric acid (75 wt%) was added in order to neutralise the catalyst. The product was then filtered to remove solid impurities. If required, a deodorisation process was performed by applying live steam to the product at 125-135°C for about 2 hours. The final product had a saponification value of 143 mgKOH/g, an acid value of 1.1 mgKOH/g, an iodine value of 1.7 gl/100g, a hydroxyl value of 25.4 mgKOH/g, and a viscosity of 22,000 Cp at 20°C.

Example 2

The procedure of Example 1 was repeated except that 293 g of ethylene oxide and 185 g of the resultant ethoxylated sorbitol were used. The final product had a saponification value of 143 mgKOH/g, an acid value of 1.4 mgKOH/g, an iodine value of 1.7 gl/100g, and a hydroxyl value of 25.4 mgKOH/g.

Example 3

The procedure of Example 1 was repeated except that 997 g of 12-hydroxystearic acid was used instead of poly(12-hydroxystearic acid). The final product had a saponification value of 143 mgKOH/g, an acid value of 1.6 mgKOH/g, an iodine value of 1.7 gl/100g, and hydroxyl value of 26.1 mgKOH/g.

Example 4

The friction reducing additives (FRA) produced in Examples 1 to 3 were evaluated using the MTM test procedure described above and the results for Group II mineral oil are shown in Tables 2 to 4.

Table 2. Coefficient of Friction at 40°C

Speed (m/s)	Control Composition	Test Composition		
		+0.5 wt% of FRA of Example 1	+0.5 wt% of FRA of Example 2	+0.5 wt% of FRA of Example 3
0.002	0.100	0.060	0.092	0.037
0.020	0.070	0.057	0.073	0.520
0.200	0.060	0.059	0.063	0.570
2.000	0.052	0.053	0.054	0.540

Table 3. Coefficient of Friction at 100°C

Speed (m/s)	Control Composition	Test Composition		
		+0.5 wt% of FRA of Example 1	+0.5 wt% of FRA of Example 2	+0.5 wt% of FRA of Example 3
0.002	0.104	0.044	0.101	0.065
0.020	0.081	0.042	0.087	0.061
0.200	0.054	0.039	0.058	0.054
2.000	0.040	0.037	0.041	0.041

Table 4. Coefficient of Friction at 150°C

Speed (m/s)	Control Composition	Test Composition		
		+0.5 wt% of FRA of Example 1	+0.5 wt% of FRA of Example 2	+0.5 wt% of FRA of Example 3
0.002	0.106	0.016	0.099	0.070
0.020	0.079	0.018	0.079	0.057
0.200	0.041	0.021	0.041	0.038
2.000	0.020	0.016	0.019	0.020

5 Example 5

The friction reducing additives (FRA) produced in Examples 1 to 3 were evaluated using the MTM test procedure described above except that a commercially available conventional automotive engine oil (GF-5 approved , viscosity grade 10W-30) was used at 135°C, instead of Group II mineral oil. The results are shown in Table 5.

10

Table 5. Coefficient of Friction at 135°C

Speed (m/s)	Control Composition	Test Composition		
		+0.5 wt% of FRA of Example 1	+0.5 wt% of FRA of Example 2	+0.5 wt% of FRA of Example 3
0.002	0.132	0.095	0.116	0.106
0.020	0.141	0.094	0.114	0.086
0.200	0.109	0.072	0.105	0.071
2.000	0.042	0.032	0.047	0.061

Example 6

The friction reducing additive (FRA) produced in Example 1 was evaluated for its performance as an additive in a metal working fluid. A Microtap II thread tapping machine supplied by Microtap USA, Inc. is used to measure the tapping torque of metal working fluids. The Microtap II machine cuts threads in pre-drilled holes at a selected set of operating parameters. Tests were performed on 50 mm x 200 mm x 8 mm mild steel bars containing 3.7 mm diameter holes. They were supplied by the company Robert Speck Ltd.

20

For this Example, the following parameters were used:

1 ml of metal working fluid is added to the Microtap II machine using a pipette

Ambient temperature

6.0 mm depth of hole

5 4 mm forming tap

Maximum torque set at 220 Ncm

Cutting speed 1000rpm

After applying the metal working fluid, the holes were threaded and the amount of torque required was recorded. If the metal working fluid isn't adequate to allow the thread to be
10 formed within the set maximum torque of 220 Ncm then multiple attempts are made by the machine and then declared as a fail. The results are given in Table 6 below.


Table 6. Micro Tap Test Results

Metal Working Fluid	Control Composition of ISO 22 S/N 100 Group 1 Mineral Oil	Control Composition + 2wt% of FRA of Example 1
Torque required (Ncm)	220 - FAIL	156

The above examples illustrate the improved properties of a lubricant composition according to
15 the present invention.

CLAIMS

1. A lubricant composition comprising a base stock and at least 0.01 wt% of a friction reducing additive which comprises a compound of the Formula (I):



5 wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

m is at least 2;

AO is an alkylene oxide residue;

each n is independently from 0 to 100; and

10 each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and

on average at least 0.5 of R^2 groups are R^3 .

15 2. The lubricant composition according to claim 1 wherein R^1 is the residue of glucose, fructose and/or sorbitol.

3. The lubricant composition according to claim 1 or 2 wherein m is 5 to 6 and/or n is 2 to 20.

4. The lubricant composition according to any one of the preceding claims wherein $n \times m$ is 10 to 100.

5. The lubricant composition according to any one of the preceding claims wherein at least 2.0 of the R^2 groups are R^3 .

6. The lubricant composition according to any one of the preceding claims wherein R^3 is the residue of a polyhydroxyalkyl carboxylic acid.

25 7. The lubricant composition according to claim 6 wherein the number of hydroxyalkyl monomers in the polyhydroxyalkyl carboxylic acid residue is 3 to 10.

8. The lubricant composition according to any one of the preceding claims wherein at least 2.0 of the R^2 groups are H.

9. The lubricant composition according to any one of the preceding claims wherein AO is an ethylene oxide residue.

10. The lubricant composition according to any one of the preceding claims wherein the friction reducing additive reduces the coefficient of friction by at least 20%.

11. The lubricant composition according to any one of the preceding claims wherein the friction reducing additive is an ethoxylated sorbitol ester of a polyhydroxyalkyl carboxylic acid.


12. The lubricant composition according to any one of the preceding claims wherein the base stock is selected from the group consisting of an API Group I, II, III, IV, V base oil or mixtures thereof.

13. The lubricant composition according to any one of the preceding claims which is a gear oil.

14. The lubricant composition according to any one of claims 1 to 12 which is an engine oil.

15. An engine comprising the engine oil according to claim 14.

16. A method of reducing friction in an engine which comprises using an engine oil comprising a base stock and at least 0.01 wt% of a friction reducing additive which comprises a compound of the Formula (I):



wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

m is at least 2;

AO is an alkylene oxide residue;


each n is independently from 0 to 100; and

each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and

on average at least 0.5 of R^2 groups are R^3 .

17. The method according to claim 11 wherein the coefficient of friction of the engine oil is reduced by at least 20%.

18. The use of a compound of the Formula (I):



wherein:

R^1 is the residue of a group having at least 2 active hydrogen atoms;

m is at least 2;

AO is an alkylene oxide residue;

each n is independently from 0 to 100; and

each R^2 is independently H or R^3 , where each R^3 is independently a residue of a polyhydroxyalkyl or polyhydroxyalkenyl carboxylic acid, a residue of a hydroxyalkyl or hydroxyalkenyl carboxylic acid and/or a residue of an oligomer of the hydroxyalkyl or hydroxyalkenyl carboxylic acid; and

on average at least 0.5 of R^2 groups are R^3 ,

to reduce the co-efficient of friction of a lubricant composition.

19. The use according to claim 18 wherein the coefficient of friction of the lubricant composition is reduced by at least 20%.

20. The use according to claim 18 or 19 wherein the lubricant composition is an engine oil.

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2014/061964

A. CLASSIFICATION OF SUBJECT MATTER

INV. C10M145/38 C10M129/76
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C10M C10N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2012/161065 A1 (WEI LIWEN [US] ET AL) 28 June 2012 (2012-06-28) claims 1,14; examples 4,5,; table 1 -----	1,3,5,9, 12-15
X	GB 514 461 A (DU PONT) 8 November 1939 (1939-11-08)	1,5,10, 12-15, 18,19
Y	page 3, line 60 - line 73; table 2 -----	2,6-8
X	WO 2011/022317 A1 (LUBRIZOL CORP [US]; BARTON WILLIAM R S [GB]; CRAWLEY SETH L [US]; MOSI) 24 February 2011 (2011-02-24)	1,5,10, 12-20
Y	paragraphs [0090], [0104]; claims 14,15,30; examples L1, EX1; table tab. on pg. 25 ----- -/-	2,6-8



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 January 2015

Date of mailing of the international search report

26/01/2015

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Pöllmann, Klaus

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2014/061964

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2012/056191 A1 (CASTROL LTD [GB]; WEST KEVIN RICHARD [GB]) 3 May 2012 (2012-05-03) claims 1,2,3,4,7; tables 8,9 -----	1-20
X,P	EP 2 746 372 A1 (AFTON CHEMICAL CORP [US]) 25 June 2014 (2014-06-25) paragraph [0215] - paragraph [0221]; examples 19,20,21,Blend 9,10,15-17; tables 4,5 -----	1,6,9, 10,12-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2014/061964

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2012161065	A1	28-06-2012	CN 101535739 A	16-09-2009
			CN 102851105 A	02-01-2013
			EP 2095039 A1	02-09-2009
			JP 2010503757 A	04-02-2010
			US 2008083900 A1	10-04-2008
			US 2011068292 A1	24-03-2011
			US 2012025129 A1	02-02-2012
			US 2012161065 A1	28-06-2012
			WO 2008034088 A1	20-03-2008

GB 514461	A	08-11-1939	GB 514461 A	08-11-1939
			US 2150156 A	14-03-1939

WO 2011022317	A1	24-02-2011	CA 2772226 A1	24-02-2011
			CN 102575184 A	11-07-2012
			EP 2467457 A1	27-06-2012
			US 8530395 B1	10-09-2013
			US 2012202726 A1	09-08-2012
			US 2013157914 A1	20-06-2013
			US 2013296208 A1	07-11-2013
			US 2013303417 A1	14-11-2013
			WO 2011022317 A1	24-02-2011

WO 2012056191	A1	03-05-2012	CN 103314084 A	18-09-2013
			EP 2633009 A1	04-09-2013
			US 2013167431 A1	04-07-2013
			WO 2012056191 A1	03-05-2012

EP 2746372	A1	25-06-2014	BR 102013032930 A2	02-12-2014
			CA 2836632 A1	21-06-2014
			CN 103881790 A	25-06-2014
			EP 2746372 A1	25-06-2014
			JP 2014132076 A	17-07-2014
			KR 20140081744 A	01-07-2014
			US 2014179572 A1	26-06-2014
