




(22) Date de dépôt/Filing Date: 2001/03/05
(41) Mise à la disp. pub./Open to Public Insp.: 2001/09/09
(30) Priorité/Priority: 2000/03/09 (65048/2000) JP

(51) Cl.Int.⁷/Int.Cl.⁷ B24B 53/12, B23H 1/04
(71) Demandeur/Applicant:
RIKEN, JP
(72) Inventeur/Inventor:
OHMORI, HITOSHI, JP
(74) Agent: DENNISON ASSOCIATES

(54) Titre : ELECTRODE AMOVIBLE
(54) Title: REMOVABLE ELECTRODE



(57) **Abrégé/Abstract:**

There is disclosed a removable electrode for electrolytic dressing grinding in which the electrode is disposed opposite to a processing surface of a conductive grinding wheel via a gap, a conductive liquid is passed through between the electrode and the conductive grinding wheel to apply a voltage thereto, the grinding wheel is dressed by electrolysis and a workpiece is simultaneously ground, the electrode comprising: an electrode support member 12 having a surface 12a disposed opposite to the processing surface of the grinding wheel via a constant gap; a conductive foil 14 detachably attached to and along the opposite surface of the electrode support member; and a conductive terminal 16 for contacting the conductive foil to apply the voltage to the conductive foil. Even when a deposit is built up on a cathode surface, the cathode surface can be cleaned in a short time. Even after repeated use, an electrode shape does not change. Therefore, an ELID grinding apparatus can steadily be operated in an unmanned manner for a long time.

ABSTRACT OF THE DISCLOSURE

There is disclosed a removable electrode for electrolytic dressing grinding in which the electrode is disposed opposite to a processing surface of a conductive grinding wheel via a gap, a conductive liquid is passed through between the electrode and the conductive grinding wheel to apply a voltage thereto, the grinding wheel is dressed by electrolysis and a workpiece is simultaneously ground, the electrode comprising: an electrode support member 12 having a surface 12a disposed opposite to the processing surface of the grinding wheel via a constant gap; a conductive foil 14 detachably attached to and along the opposite surface of the electrode support member; and a conductive terminal 16 for contacting the conductive foil to apply the voltage to the conductive foil. Even when a deposit is built up on a cathode surface, the cathode surface can be cleaned in a short time. Even after repeated use, an electrode shape does not change. Therefore, an ELID grinding apparatus can steadily be operated in an unmanned manner for a long time.

REMOVABLE ELECTRODE

BACKGROUND OF THE INVENTION5 Field of the Invention

The present invention relates to an electrode for electrolytic dressing grinding, more particularly to a removable electrode whose surface can be exchanged in a short time.

10

Description of the Related Art

In recent years, with development of scientific technique, a demand for superfine processing has rapidly escalated, and as mirror surface grinding means for satisfying the demand, an electrolytic in-process dressing grinding method (ELID grinding method) has been developed, and presented by the present applicant, et al. ("Trend of Latest Technique of Mirror Surface Grinding" of Riken symposium held on March 5, 1991).

20

As schematically shown in Fig. 1, the ELID grinding method includes: using a conductive grinding wheel 1 instead of an electrode in conventional electrolytic grinding; disposing an electrode 2 opposite to the grinding wheel via a gap; passing a conductive liquid 3 through between the grinding wheel and the electrode while applying a voltage to between the grinding wheel 1 and the electrode 2; dressing the grinding wheel by electrolysis; and simultaneously

25

- 2 -

grinding a workpiece by the grinding wheel. That is to say,
in the grinding method, the metal bond grinding wheel 1 is
used as an anode, the electrode 2 disposed opposite to the
surface of the grinding wheel via the gap is used as a
5 cathode, and electrolytic dressing of the grinding wheel is
performed simultaneously with a grinding operation, so that
grinding properties can be maintained and stabilized.
Additionally, in Fig. 1, reference numeral 4 is a workpiece
(material to be ground), 5 is an ELID power supply, 6 is a
10 power supply member, and 7 is a nozzle of the conducive
solution.

In this ELID grinding method, even when an abrasive
grain is fine, the grinding wheel is dressed through
electrolytic dressing and prevented from being clogged.
15 Therefore, with the fine abrasive grain, a processed surface
remarkably superior like a mirror surface can be obtained by
a grinding process. Therefore, in the ELID grinding method,
sharpness of the grinding wheel can be maintained both of
highly efficient grinding and mirror surface grinding, and
20 the method is expected to be applied to various grinding
processes as means able to create a highly precise surface in
a short time, which has been impossible in a conventional art.

In the aforementioned ELID grinding, a metal
component of a grinding wheel bonding material is deposited
25 on the surface of the cathode 2 disposed opposite to the
metal bond grinding wheel 1 as the anode based on an electric
plating principle, contrary to an anode reaction which is

- 3 -

electrolytic eluation of the grinding wheel bonding material.

Since the deposit on the surface of the cathode has a composition close to that of a pure metal in principle, conductivity is not lost. However, when the ELID grinding process is performed over a long time, following problems would occur. 1. The gap between the cathode and the grinding wheel is filled with the deposit, the surface of the electrode becomes irregular, and electrolytic dressing of the grinding wheel becomes unstable. 2. A sufficient amount of grinding solution cannot steadily be supplied after a long time. To solve the problems, in the conventional art, the apparatus would be stopped every several days (about one to seven days), a distance between the electrode and the grinding wheel is enlarged, or the electrode is removed from the apparatus, and the deposit sticking to the surface of the electrode is removed with a sand paper or the like. As a result, however, following other problems would occur. 3. An apparatus maintenance time is lengthened, continuous operation is limited and operating efficiency is deteriorated. 4. After repeated maintenance, an electrode surface shape changes, the entire electrode needs to be exchanged, much time is therefore required for changing the electrode and readjusting the entire apparatus, and the operating efficiency is further deteriorated. Consequently, an ELID grinding effect cannot be maintained during continuous unmanned operation, and it has been recognized that these problems have to be overcome for complete automatic operation.

SUMMARY OF THE INVENTION

The present invention has been developed to solve the problems. That is to say, an object of the present invention is to provide an electrode for electrolytic dressing grinding, in which even with a deposit built up on a cathode surface the cathode surface can be cleaned in a short time, even after repeated use an electrode shape does not change, and an ELID grinding apparatus can therefore steadily be operated in an unmanned manner for a long time.

According to the present invention, there is provided a removable electrode for electrolytic dressing grinding in which the electrode is disposed opposite to a processing surface of a conductive grinding wheel via a gap, a conductive liquid is passed through the gap to apply a voltage to the gap, the grinding wheel is dressed by electrolysis and a workpiece is simultaneously ground, the electrode comprising: an electrode support member (12) having a surface (12a) disposed opposite to the processing surface of the grinding wheel via a constant gap; a conductive foil (14) detachably attached to and along the opposite surface of the electrode support member; and a conductive terminal (16) for contacting the conductive foil to apply the voltage to the conductive foil.

According to the aforementioned constitution of the present invention, since the electrode support member (12) is provided with the opposite surface (12a), the conductive foil

can be disposed opposite to the processing surface of the
conductive grinding wheel via the gap simply by attaching the
conductive foil (14) to and along the opposite surface.
Therefore, in this state, it is possible to perform the
5 electrolytic dressing grinding (ELID grinding) by applying
the voltage to the conductive foil via the conductive
terminal (16), passing the conductive liquid through between
the conductive foil and the conductive grinding wheel,
dressing the grinding wheel by electrolysis, and
10 simultaneously grinding the workpiece.

Moreover, the conductive foil (14) is detachably
attached to the opposite surface of the electrode support
member. Therefore, even when the deposit is built up on the
electrode surface, the electrode surface can be cleaned in a
15 short time simply by changing the conductive foil.
Furthermore, even when the conductive foil is repeatedly
exchanged, the electrode shape does not change, so that the
ELID grinding apparatus can steadily be performed in the
unmanned manner for the long time.

20 According to a preferred embodiment of the present
invention, the conductive foil (14) is applied to the
opposite surface (12a) in a single layer or laminated layers.

When the conductive foil is of the single layer, the
conductive foil can be exchanged and the electrode surface
25 can be cleaned only by stripping the conductive foil (14)
from the electrode support member (12) and attaching another
new conductive foil to the electrode support member.

Moreover, when the conductive foil is of multiple layers, the surface conductive foil with the deposit thereon is simply stripped from the multiple layers, and the underlying conductive foil is in turn disposed opposite to the processing surface of the conductive grinding wheel via the gap, so that ELID grinding can be performed.

When the conductive foil (14) is formed in a tape shape, the conductive foil is preferably intermittently or continuously moved along the opposite surface (12a).

In this constitution, a portion of the conductive foil with the deposit built up thereon can intermittently or continuously be replaced with a new portion on which no deposit is built up, and the ELID grinding apparatus can steadily be operated in the unmanned manner for a long time.

Furthermore, the electrode support member (12) is preferably formed of an insulating material, and may be provided with a guide groove (13) via which the conductive foil is movably guided along the opposite surface (12a).

According to this constitution, while the conductive foil (14) is disposed opposite to the processing surface of the conductive grinding wheel via the constant gap, the portion of the conductive foil with the deposit built up thereon can be replaced with the new portion via the guide groove (13).

Other objects and advantages of the present invention will be apparent from the following description with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic view of an ELID grinding apparatus.

5 Figs. 2A to 2D are structure diagrams of a removable electrode for a straight grinding wheel according to the present invention.

10 Figs. 3A to 3C are structure diagrams of the removable electrode for a cup type grinding wheel according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Preferred embodiments of the present invention will be described hereinafter with reference to the accompanying drawings. Additionally, a portion common to the respective diagrams is denoted with the same reference numeral, and redundant description thereof is omitted.

20 Figs. 2A to 2D are structure diagrams of a removable electrode for a straight grinding wheel according to the present invention. In the drawings, Fig. 2A shows a first embodiment, Fig. 2B shows a second embodiment, Fig. 2C shows a third embodiment, and Fig. 2D shows a fourth embodiment. As shown in Figs. 2A to 2D, a removable electrode 10 of the
25 present invention is disposed opposite to a processing surface 1a of a conductive grinding wheel 1 (straight grinding wheel in this example) via a gap. This electrode 10

is for use in electrolytic dressing grinding in which a
conductive liquid is passed through the gap to apply a
voltage to the gap, the grinding wheel 1 is dressed by
electrolysis and a workpiece is simultaneously ground. In
5 this respect, the electrode has the same function as that of
the conventional electrode 2 shown in Fig. 1.

In the first embodiment of Fig. 2A, the removable
electrode 10 of the present invention is provided with an
electrode support member 12, conductive foil 14 and
10 conductive terminal 16.

The electrode support member 12 has an opposite
surface 12a which is disposed opposite to the processing
surface 1a of the straight grinding wheel 1 via a constant
gap. The constant gap is, for example, of the order of 0.1
15 mm to 0.3 mm. Moreover, the electrode support member 12 is
preferably formed of an insulating material (e.g., plastic).

The conductive foil 14 is detachably attached to and
along the opposite surface 12a of the electrode support
member 12. This conductive foil 14 is a foil, for example,
20 of copper, brass, aluminum, gold, stainless steel, or the
like. A thickness of the conductive foil 14 is arbitrary,
but is, for example, of the order of 10 μm to 50 μm .

In this example, the conductive terminal 16 is fixed
to the electrode support member 12 with a screw or the like
25 so as to contact the conductive foil 14. A negative (minus)
voltage is applied to the conductive terminal 16 from a power
supply (not shown). Additionally, in this example, a pair of

conductive terminals 16 are attached to upper and lower surfaces of the electrode support member, the same voltage is applied to the conductive terminals, and a voltage between the conductive terminals is equalized. However, the
5 conductive terminal 16 may be disposed on either one surface.

Moreover, different from the embodiment shown in the drawing, for example, the conductive terminal may be passed through the electrode support member 12 to contact the conductive foil 14. Alternatively, a part or the whole of
10 the electrode support member 12 is constituted of a conductive material, and a part of the electrode support member is brought in contact with the conductive foil 14. In this case, the conductive terminal may be omitted.

Furthermore, in the first embodiment of Fig. 2A, the
15 single-layer conductive foil 14 is applied to the opposite surface 12a of the electrode support member 12 using a removable adhesive.

According to the aforementioned constitution of the present invention, the electrode support member 12 is
20 provided with the opposite surface 12a. Therefore, when the conductive foil 14 is applied to and along the opposite surface 12a, the conductive foil 14 can be disposed opposite to the processing surface 1a of the conductive grinding wheel via an appropriate gap (e.g., about 0.1 mm to 0.3 mm).
25 Therefore, in this state, the voltage is applied to the conductive foil 14 via the conductive terminal 16, the conductive liquid is passed through between the conductive

- 10 -

foil and the conductive grinding wheel 1, and the grinding wheel is dressed by electrolysis, while the workpiece can be ground with the grinding wheel.

Moreover, the single-layer conductive foil 14 is detachably attached to the opposite surface 12a of the electrode support member 12 with the adhesive. Therefore, even when a deposit is built up on the surface of the electrode, the conductive foil can be exchanged, and the electrode surface can be cleaned in a short time simply by stripping the conductive foil 14 from the electrode support member 12 and attaching another new conductive foil 14 to the electrode support member. Moreover, even when replacement of the conductive foil 14 is repeated, an electrode shape does not change, and an ELID grinding apparatus can therefore steadily be operated in an unmanned manner for a long time.

In the second embodiment of Fig. 2B, the electrode support member 12 is formed of a thin (e.g., 2 to 5 mm thick) metal plate, and the single-layer conductive foil 14 is detachably attached to an inner surface (opposite surface 12a) of the electrode support member with the adhesive. Moreover, in the present embodiment, the grinding wheel 1 is enclosed with a grinding wheel cover 17, and the electrode support member 12 is detachably attached to an inner surface of the grinding wheel cover with a bolt, and the like. The other constitution is similar to that of the first embodiment.

According to this constitution, similarly as the first embodiment, the conductive foil 14 is disposed opposite

- 11 -

to the processing surface 1a of the conductive grinding wheel via the appropriate gap (e.g., about 0.1 mm to 0.3 mm), and the grinding wheel is dressed by electrolysis while the workpiece can be ground.

5 Moreover, since the electrode support member 12 is detachably attached to the inner surface of the grinding wheel cover 17, the electrode support member 12 is detached from the cover, and the conductive foil 14 is simply replaced with another new conductive foil 14, so that the conductive
10 foil can easily be exchanged.

In the third embodiment of Fig. 2C, the conductive foils 14 are laminated and attached onto the opposite surface 12a of the electrode support member 12. The other constitution is similar to that of the first embodiment.

15 According to this constitution, when the surface conductive foil 14 with the deposit built up thereon by ELID grinding is simply stripped, the underlying conductive foil 14 is in turn disposed opposite to the processing surface 1a of the conductive grinding wheel 1 via the gap, so that the
20 ELID grinding can continuously be performed. Additionally, in this case, when a thick conductive foil (e.g., 30 to 50 μm) is used, the gap between the conductive foil and the processing surface 1a slightly changes, but the ELID grinding is only slightly influenced. Therefore, on the same
25 conditions, or by automatically controlling the voltage or the like of ELID power supply, the ELID grinding apparatus can steadily be operated in the unmanned manner for a long

time.

In the fourth embodiment of Fig. 2D, the conductive foil 14 is formed in a tape shape. Moreover, the electrode support member 12 is constituted of the insulating material (e.g., plastic), and is intermittently or continuously moved between a pair of reels 15. Furthermore, the electrode support member 12 is provided with a guide groove 13 via which the tape-shaped conductive foil 14 is movably guided along the opposite surface 12a. For example, the guide groove 13 is a groove having a circular arc shape via which both ends of a width direction of the tape-shaped conductive foil 14 are guided along the opposite surface 12a. The other constitution is similar to that of the first embodiment.

According to this constitution, the conductive foil 14 is intermittently or continuously moved via the guide groove 13 while the conductive foil is disposed opposite to the processing surface of the conductive grinding wheel via the constant gap. Moreover, when the deposit is built up on a portion of the conductive foil 14, the portion can intermittently or continuously be replaced with a new portion, and the ELID grinding apparatus can steadily be operated in the unmanned manner for a long time.

Figs. 3A to 3C are structure diagrams of the removable electrode for a cup type grinding wheel according to the present invention. In the drawings, Fig. 3A shows a fifth embodiment, Fig. 3B shows a sixth embodiment, and Fig. 3C shows a seventh embodiment. Additionally, as shown in

Figs. 3A to 3C, the removable electrode 10 of the present invention is disposed opposite to the processing surface 1a of the conductive grinding wheel 1 (cup type grinding wheel in this example) via the gap. This electrode is for use in electrolytic dressing grinding in which the conductive liquid is passed through the gap to apply the voltage to the gap, the grinding wheel 1 is dressed by electrolysis and the workpiece is simultaneously ground. In this respect, the electrode has the same function as that of the conventional electrode 2 shown in Fig. 1.

In the fifth embodiment of Fig. 3A, the removable electrode 10 of the present invention is provided with the electrode support member 12, conductive foil 14 and conductive terminal 16.

The electrode support member 12 has the opposite surface 12a which is disposed opposite to the processing surface 1a of the grinding wheel 1 via the constant gap. The constant gap is, for example, of the order of 0.1 mm to 0.3 mm. Moreover, the electrode support member 12 is preferably formed of the insulating material (e.g., plastic).

The conductive foil 14 is detachably attached to and along the opposite surface 12a of the electrode support member 12. This conductive foil 14 is a foil, for example, of copper, brass, aluminum, gold, stainless steel, or the like. The thickness of the conductive foil 14 is arbitrary, but is, for example, of the order of 10 μm to 50 μm .

In this example, the conductive terminal 16 is fixed

- 14 -

to the electrode support member 12 with the screw or the like so as to contact the conductive foil 14. The negative (minus) voltage is applied to the conductive terminal 16 from the power supply (not shown). Additionally, in this example, 5 a pair of conductive terminals 16 are attached to opposite surfaces of the electrode support member, the same voltage is applied to the respective conductive terminals, and the voltage between the conductive terminals is equalized. However, the conductive terminal 16 may be disposed on either 10 one surface.

Moreover, different from the embodiment shown in the drawing, for example, the conductive terminal may be passed through the electrode support member 12 to contact the conductive foil 14. Alternatively, a part or the whole of 15 the electrode support member 12 is constituted of a conductive metal, and a part of the electrode support member is brought in contact with the conductive foil 14. In this case, the conductive terminal may be omitted.

Furthermore, in the fifth embodiment of Fig. 3A, the 20 single-layer conductive foil 14 is applied to the opposite surface 12a of the electrode support member 12 using the removable adhesive.

According to the aforementioned constitution of the present invention, the electrode support member 12 is 25 provided with the opposite surface 12a. Therefore, when the conductive foil 14 is applied to and along the opposite surface 12a, the conductive foil 14 can be disposed opposite

- 15 -

to the processing surface 1a of the conductive grinding wheel via the appropriate gap (e.g., about 0.1 mm to 0.3 mm). Therefore, in this state, the voltage is applied to the conductive foil 14 via the conductive terminal 16, the
5 conductive liquid is passed through between the conductive foil and the conductive grinding wheel 1, and the grinding wheel is dressed by electrolysis, while the workpiece can be ground with the grinding wheel.

Moreover, the single-layer conductive foil 14 is
10 detachably attached to the opposite surface 12a of the electrode support member 12 with the adhesive. Therefore, even when the deposit is built up on the surface of the electrode, the conductive foil can be exchanged, and the electrode surface can be cleaned in a short time simply by
15 stripping the conductive foil 14 from the electrode support member 12 and attaching another new conductive foil 14 to the electrode support member. Moreover, even when replacement of the conductive foil 14 is repeated, the electrode shape does not change, and the ELID grinding apparatus can therefore
20 steadily be operated in the unmanned manner for a long time.

In the sixth embodiment of Fig. 3B, the conductive foils 14 are laminated and attached onto the opposite surface 12a of the electrode support member 12. The other constitution is similar to that of the fifth embodiment.

25 According to this constitution, when the surface conductive foil 14 with the deposit built up thereon by ELID grinding is simply stripped, the underlying conductive foil

14 is in turn disposed opposite to the processing surface 1a of the conductive grinding wheel 1 via the gap, so that the ELID grinding can continuously be performed. Additionally, in this case, when the thick conductive foil (e.g., 30 to 50
5 μm) is used, the gap between the conductive foil and the processing surface 1a slightly changes, but the ELID grinding is only slightly influenced. Therefore, on the same conditions, or by automatically controlling the voltage or the like of the ELID power supply, the ELID grinding
10 apparatus can steadily be operated in the unmanned manner for a long time.

In the seventh embodiment of Fig. 3C, the conductive foil 14 is formed in the tape shape. Moreover, the electrode support member 12 is constituted of the insulating material
15 (e.g., plastic), and is intermittently or continuously moved between a pair of reels 15. The other constitution is similar to that of the first embodiment.

According to this constitution, the conductive foil 14 is intermittently or continuously moved between the pair
20 of reels 15 while the conductive foil is disposed opposite to the processing surface 1a of the conductive grinding wheel 1 via the constant gap. Moreover, when the deposit is built up on a portion of the conductive foil 14, the portion can intermittently or continuously be replaced with a new portion,
25 and the ELID grinding apparatus can steadily be operated in the unmanned manner for a long time.

As described above, according to the removable

- 17 -

electrode of the present invention, even when the deposit is built up on a cathode surface, the cathode surface can be cleaned in a short time. Moreover, even after repeated use, the electrode shape does not change. Therefore, the ELID
5 grinding apparatus can steadily be operated in the unmanned manner for a long time, and other superior effects can be produced.

Additionally, the present invention is not limited to the aforementioned embodiments or examples, and these can
10 of course be modified in various ways without departing from the scope of the present invention. For example, the removable electrode of the present invention is not limited to the electrode for electrolytic dressing grinding illustrated in Fig. 1, and the present invention can be
15 applied to any electrode for electrolytic dressing grinding.

WHAT IS CLAIMED IS:

1. A removable electrode for electrolytic dressing grinding in which the electrode is disposed opposite to a processing surface of a conductive grinding wheel via a gap, a conductive liquid is passed through between the electrode and the conductive grinding wheel to apply a voltage to between the electrode and the conductive grinding wheel, the grinding wheel is dressed by electrolysis and a workpiece is simultaneously ground, the removal electrode comprising:

an electrode support member (12) having a surface (12a) disposed opposite to the processing surface of the grinding wheel via a constant gap; a conductive foil (14) detachably attached to and along the opposite surface of the electrode support member; and a conductive terminal (16) for contacting the conductive foil to apply the voltage to the conductive foil.

2. The removable electrode according to claim 1 wherein the conductive foil (14) is detachably attached to the opposite surface (12a) in a single layer or laminated layers.

3. The removable electrode according to claim 1 wherein the conductive foil (14) is formed in a tape shape, and is intermittently or continuously moved along the opposite surface (12a).

- 19 -

4. The removable electrode according to claim 3
wherein the electrode support member (12) is formed of an
insulating material, and includes a guide groove (13) via
5 which the conductive foil is movably guided along the
opposite surface (12a).

Fig. 1




Fig.2A




Fig.2B




Fig.2C




Fig.2D




Fig.3A




Fig.3B




Fig.3C

