




(12) **DEMANDE DE BREVET CANADIEN  
CANADIAN PATENT APPLICATION**

(13) **A1**

(22) Date de dépôt/Filing Date: 2019/07/08  
(41) Mise à la disp. pub./Open to Public Insp.: 2020/01/30  
(30) Priorité/Priority: 2018/07/30 (IT102018000007630)

(51) Cl.Int./Int.Cl. *B65G 59/00* (2006.01)  
(71) Demandeur/Applicant:  
FIVES INTRALOGISTICS S.P.A. CON SOCIO UNICO, IT  
(72) Inventeurs/Inventors:  
FILELLA, CARMINE, IT;  
CASTELLI, MARCO, IT  
(74) Agent: MBM INTELLECTUAL PROPERTY LAW LLP

(54) Titre : APPAREIL DE DESEMPILEMENT  
(54) Title: A DESTACKER APPARATUS



(57) **Abrégé/Abstract:**

The destacker apparatus (1), comprises: a succession of conveyors (10, 11, 12) arranged inclined relative to the horizon, each comprising a mobile surface (S) for receiving and supporting articles (J, K) carried upwards by the conveyors (10, 11, 12); and a

(57) **Abrégé(suite)/Abstract(continued):**

device for varying the pressure of a fluid (2). The surface (S) of the conveyors (10, 11, 12) has through holes and the pressure varying device (2) is fluid dynamically connected to this surface (S).

## **ABSTRACT**

The destacker apparatus (1), comprises: a succession of conveyors (10, 11, 12) arranged inclined relative to the horizon, each comprising a mobile surface (S) for receiving and supporting articles (J, K) carried upwards by the conveyors (10, 11, 12); and a device for varying the pressure of a fluid (2).

The surface (S) of the conveyors (10, 11, 12) has through holes and the pressure varying device (2) is fluid dynamically connected to this surface (S).

## A DESTACKER APPARATUS

### DESCRIPTION

The present invention relates to a perfected destacker apparatus, especially intended for use in sorter systems for leaflets, envelopes, parcels or other articles.

5 Destackers are known which are constituted by a series of inclined motorised belts, to define a sort of ramp, at the base of which stacks or piles of articles are fed, which are gripped and carried upwards from the first belt of the series.

The destacking is performed by exploiting the force of gravity, allowing the groups of articles that are carried upwards to separate when one or more  
10 of them slides downwards and exploiting variable speeds or accelerations between two subsequent belts, so that different movement conditions are created between different articles that can promote their separation.

These known systems operate with a certain efficacy in destacking parcels or other articles that are not very light, but are much less effective when  
15 used to separate leaflets or similar.

In this context, the technical task underpinning the present invention is to propose a destacker apparatus able to overcome the drawbacks of the cited prior art.

The technical task is reached by the machine realised in accordance with  
20 claim 1.

Further characteristics and advantages of the present invention will become more apparent from the approximate and thus non-limiting description of a preferred, but not exclusive, embodiment of an apparatus of the invention, as illustrated in the accompanying drawings, in which:

25 - figures 1 and 2 are schematic views of the apparatus of the invention, showing two modes of operation;

- figure 3 is a schematic view of the apparatus of the preceding claim, in which an adjustment valve is shown;
- figures 4 and 5 are schematic views showing possible configurations of the conveyors of the proposed apparatus; and
- 5 - figures 6 - 8 are schematic views showing a sequence of operation of the invention.

With reference to the above-mentioned figures, reference number 1 indicates a destacker apparatus realised according to the invention.

The proposed apparatus 1 firstly comprises a succession of conveyors 10, 11, 12, arranged inclined relative to the horizon, to define a ramp, each  
10 comprising a mobile surface S, preferably flat, for receiving and supporting articles K, J that are carried upwards.

In practice, the conveyors are arranged at increasing heights, preferably with the same inclination, to define an upwards transport path; for  
15 example, three conveyors 10, 11, 12 can be provided.

These articles, for example leaflets, but also parcels, envelopes or others, are transported from the bottom of the apparatus 1 towards the top, through subsequent delivery passages between the various conveyors 10, 11, 12.

20 The output of the apparatus 1 is at the top of the ramp 10, 11, 12, through which the articles are delivered to the other stations of the system.

Preferably, the conveyors 10, 11, 12 each include a belt closed in a loop around end drives, at least one of which is motorised; the belt 10, 11, 12 is equipped with a contact surface S defined by the upper ramp of the belt  
25 itself.

According to one possible configuration of the ramp 10, 11, 12, the contact surfaces S of the conveyors 10, 11, 12 are arranged substantially on a same plane (see figure 4), while according to a different configuration, the conveyors 10, 11, 12 are mutually arranged in pairs in such a way that the  
30 downstream end of the conveyors further upstream is higher than and

overlapping the upstream end of the conveyor further downstream (see figure 5).

According to an important aspect of the invention, the apparatus 1 includes a pressure varying device 2 and the contact surface S of the conveyors 10, 11, 12 has through holes which are designed to be placed in fluid communication with this pressure varying device 2.

In detail, the pressure varying device 2 can include both a negative pressure source and an overpressure source, which can possibly coincide and be defined by a compressor/aspirator, for example, equipped with an impeller or other devices known on the market.

Thanks to this expedient, the adherence of certain articles can be increased by creating a negative pressure at the contact surface S (see the arrows in figures 1 and 3), or the adherence of certain articles can be decreased by creating an overpressure at the surface S (see for example figure 2), to make it possible, in cooperation with the force of gravity, to more effectively separate the stacked or piled articles.

For example, the adherence of a belt 11 (or another conveyor) which receives an article J from the adjacent belt 10 placed upstream can be increased, to define a gradient of adherence between it and the other articles K of the stack, to favour the unstacking or destacking (see figures 6 and 7).

Conversely, the adherence of the belt upstream 10 can be decreased during the transfer of one or more articles J on a belt downstream 11, so that the force of gravity favours the downstream sliding, separating the pile.

The two modes of use described in the preceding paragraphs can be used together or in a selective manner; moreover, further modes of use will be illustrated in the description of the operation of the invention.

Holes can be formed on a majority portion of the mobile contact surface S and, preferably, they are distributed in a uniform manner.

Preferably, inside the conveyor belts 10, 11, 12, a perforated box-shaped element is placed which is designed to communicate fluid dynamically with the pressure varying device 2.

5 Even more in detail, between the pressure varying device 2 and the interior of the conveyors 10, 11, 12, communication ducts 21 can be provided, preferably with the interposition of valves 22 to adjust the fluid communication (see figures 1 - 3).

For example, it is possible to select the conveyors 10, 11, 12 affected by the pressure variation, providing a respective adjustment valve 22 for each  
10 of them.

According to an important aspect of the invention, the apparatus 1 comprises one or more acquisition devices 3, designed to detect the arrangement of the articles J, K moved on one or more of the conveyors 10, 11, 12.

15 Each acquisition device 3, which can for example comprise a camera, is designed to produce arrangement signals that depend on the acquired configuration of the articles.

Furthermore, the apparatus 1 includes a processing unit, connected to the acquisition device 3 and configured to control the operation of the  
20 pressure varying device 2 based on the above-mentioned arrangement signals.

In practice, based on the fact that the camera 3 (or other device designed for the purpose) detects individual or stacked articles, the aspirator/compressor 2 is consequently activated or deactivated or the  
25 above-mentioned valves 3 are opened or closed, which are subject to the processing unit.

For example, as shown in figures 6 - 8, if the camera 3 detects a group of two stacked articles J, K, the processing unit can control an aspiration on the contact surface S of the belt 11 further downstream, i.e. the one which  
30 is higher, which with the aid of the force of gravity, produces a separation

of the two articles J, K, especially if the contact surface S of the belt further upstream 10 is air blown.

Once the separation has been performed, the adherence on both belts 10, 11 can be increased through aspiration, so that the products J, K do not  
5 slip downwards.

According to a particular embodiment of the invention, at the contact surface S of each conveyors 10, 11, 12 a conveying surface is defined along which the articles are moved, which is divided into a plurality of operating areas designed to be selectively positioned in fluid  
10 communication with the pressure varying device 2.

In practice, multiple zones or quadrants are identified on the upper branch of the belt 10, 11, 12 (or another conveyor) that can suck/blow independently from each other.

For example, two or more perforated box-shaped elements can be  
15 provided inside the belt 10, 11, 12 or the perforated box-shaped structure can be internally compartmentalised by dividers.

In any case, each operational area can be connected to the aspirator/compressor 2 with the interposition of a respective valve 22 controlled by the processing unit.

20 In detail, the processing unit comprises a position module configured to determine the relative position of the articles on the conveyor surface, as a function of the arrangement signals received from the camera 3 and also comprises a selection module configured in such a way as to select which of said operating areas is put in communication with the pressure varying  
25 device 2.

In other words, the processing unit, based on the position of the articles J, K on the belt 10, 11, 12, can decide to produce a variation of the surface pressure at a specific area, for example to increase adherence of a specific article placed at the same area and can decrease that of another  
30 article stacked on the first, so as to cause the separation thereof.

The invention, in its general aspects, operates as described below.

The proposed apparatus 1 is fed with loose articles, stacked or piled, at the bottom of the ramp.

The first belt 10 carries the products J, K upwards, which begin to be subject to the force of gravity.

- 5 Particularly at the transition zones of the belts 10, 11, 12, an adherence differential is produced, according to the already explained methodologies, so as to separate or otherwise scatter the overlapping articles.

This operation is repeated several times, in order to have a destacking of the articles so as to eliminate mutual overlapping.

- 10 It can thus be understood how the invention is capable of effectively destacking also leaflets or other very light articles, thus overcoming the limitations of the prior art.

**CLAIMS**

1. A destacker apparatus (1), comprising:  
a succession of conveyors (10, 11, 12) arranged inclined relative to the horizon, each comprising a mobile surface (S) for receiving and supporting  
5 articles (J, K) carried upwards by the conveyors (10, 11, 12); and  
at least one device for varying the pressure of a fluid (2);  
wherein the surface (S) of at least one of the conveyors (10, 11, 12) has through holes and wherein the pressure varying device (2) is fluid dynamically connectable to the surface (S).
- 10 **2** The apparatus (1) according to the preceding claim, wherein the holes are distributed on a majority portion of the mobile surface (S).
- 3.** The apparatus according to any one of the preceding claims, wherein the conveyors (10, 11, 12) each comprise a conveyor belt closed in a loop around end drives, equipped with a contact surface (S) defined by the  
15 upper ramp of the belt.
- 4.** The apparatus (1) according to the preceding claim, comprising, in one or more belts (10, 11, 12) a perforated box-shaped element designed to communicate fluid dynamically with the pressure varying device (2).
- 5.** The apparatus (1) according to any one of the preceding claims,  
20 wherein the contact surfaces (S) of two or more conveyors (10, 11, 12) are positioned substantially on a same plane.
- 6.** The apparatus (1) according to any one of the preceding claims, wherein at least one pair of conveyors (10, 11, 12) is mutually positioned in such a way that the downstream end of the conveyor further upstream  
25 is higher than the upstream end of the conveyor downstream.
- 7.** The apparatus (1) according to any one of the preceding claims, wherein the pressure varying device (2) is designed to produce a negative pressure.
- 8.** The apparatus (1) according to any one of the preceding claims,  
30 wherein the pressure varying device (2) is designed to produce an overpressure.

**9.** The apparatus (1) according to any one of the preceding claims, comprising:

at least one acquisition device (3) designed to detect the arrangement of the articles (J, K) moved on at least one conveyor (10, 11, 12) and to

5 produce arrangement signals; and

at least one processing unit connected to the acquisition device (3) and configured to control the operation of the pressure varying device (2) according to the arrangement signals.

**10.** The apparatus (1) according to the preceding claim, wherein the  
10 contact surface (S) defines a conveying surface along which the articles are moved, divided into a plurality of operating areas designed to be selectively positioned in fluid communication with the pressure varying device (2), the processing unit comprising a position module for determining the relative position of the articles (J, K) on the conveyor  
15 surface, as a function of the arrangement signals and a selection module configured in such a way as to select which of the operating areas is put in fluid communication with the pressure varying device (2), as a function of the position signals.

Fig.1




Fig.2




Fig.3




Fig.4





Fig.5






Fig.6




Fig.7




Fig.8

