

(12) **United States Patent**  
**Vandeven et al.**

(10) **Patent No.:** **US 11,064,654 B2**  
(45) **Date of Patent:** **Jul. 20, 2021**

(54) **FLOAT ADJUSTMENT**

(71) Applicant: **DEERE & COMPANY**, Moline, IL (US)

(72) Inventors: **Michael L. Vandeven**, Princeton, IA (US); **Alex Brimeyer**, Bettendorf, IA (US); **Benjamin M. Lovett**, Colona, IL (US); **Duane M. Bomleny**, Geneseo, IL (US); **Bryan R. Yanke**, Eldridge, IA (US); **Joshua R. Pierson**, Bettendorf, IA (US); **Anthony M. Hasenour**, Port Byron, IL (US)

(73) Assignee: **DEERE & COMPANY**, Moline, IL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 180 days.

(21) Appl. No.: **16/400,097**

(22) Filed: **May 1, 2019**

(65) **Prior Publication Data**  
US 2020/0344951 A1 Nov. 5, 2020

(51) **Int. Cl.**  
**A01D 41/14** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A01D 41/141** (2013.01)

(58) **Field of Classification Search**  
CPC .... A01D 41/14; A01D 41/141; A01D 41/145; A01D 41/16  
USPC ..... 56/11.9, 208, 209  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,535,577 A	7/1996	Chmielewski et al.	
7,222,475 B2 *	5/2007	Bomleny .....	A01D 41/141 56/10.2 E
7,918,076 B2 *	4/2011	Talbot .....	A01D 41/14 56/208
2013/0255214 A1 *	10/2013	Nafziger .....	A01D 47/00 56/208
2016/0316624 A1 *	11/2016	Ritter .....	A01D 41/127
2018/0153102 A1 *	6/2018	Dunn .....	A01D 41/127
2019/0053429 A1 *	2/2019	Cook .....	A01D 41/06
2019/0082598 A1 *	3/2019	Seiders, Jr. ....	A01D 75/287
2019/0110402 A1 *	4/2019	Vandeven .....	A01D 41/14
2020/0000032 A1 *	1/2020	Shearer .....	A01D 41/144
2020/0375107 A1 *	12/2020	Duerksen .....	A01D 57/20

\* cited by examiner

*Primary Examiner* — Thomas B Will


*Assistant Examiner* — Matthew Ian Neal

(74) *Attorney, Agent, or Firm* — Taft Stettinius & Hollister LLP; Stephen F. Rost

(57) **ABSTRACT**

A system for a header assembly that has a center frame configured to pivot relative to an adapter frame about at least one center axis, a center actuator coupled to the center frame to selectively provide a biasing force thereto, a first arm assembly configured to pivot relative to the center frame about at least a first arm axis, a first actuator coupled to the first arm assembly to selectively provide a biasing force thereto, a controller in communication with the center actuator and the first actuator to selectively alter performance characteristics of the center actuator and the first actuator, and a user interface in communication with the controller and having at least a first option and a second option. Wherein, the controller adjusts the performance characteristics of both the center actuator and the first actuator when the user interface is transitioned between the first option and the second option.

**20 Claims, 13 Drawing Sheets**








Fig. 2




Fig. 3




Fig. 4




Fig. 5






Fig. 7




Fig. 8




Fig. 9






Fig. 11

1200 ↗




Fig. 12




Fig. 13

## FLOAT ADJUSTMENT

## FIELD OF THE DISCLOSURE

The present disclosure related to a float adjustment system and method and more particularly to a single input float adjustment system for an agricultural harvesting head.

## BACKGROUND

Agricultural harvesters, such as agricultural combines, are designed to travel through agricultural fields harvesting crops. Agricultural combines receive crop severed from the ground and convey it to threshing, separating, and cleaning devices within the agricultural combine. In a typical arrangement, the agricultural harvesting head severs the crop from the ground and conveys it to the central region of the harvesting head where it is then conveyed rearward into a central and forwardly opening aperture in the front of the agricultural combine.

Agricultural harvesting heads are quite long, on the order of 10-15 meters in overall length. In order to accurately follow the contours of the ground and sever crop at the appropriate point on the stem, agricultural harvesting heads have been made in sections that are generally hinged with respect to each other. A typical agricultural harvesting head of this type is formed in two or three sections that are pivotable with respect to each other. They pivot with respect to each other about a generally horizontal and fore-and-aft extending axis. Thus, a two section agricultural harvesting head would have one pivot axis, and a three-section agricultural harvesting head would have two pivot axes.

To better follow the contours of the ground, the agricultural harvesting head is mounted to the front of the feederhouse such that it can move with respect to the feederhouse. In one arrangement the agricultural harvesting head is a draper head having three frame sections (a center section, a left-wing section and a right wing section). The frame sections can pivot up and down with respect to one another and thereby follow the contours of the ground.

In addition to that contour-following capability, the center frame section is mounted on an "adapter" that is fixed to the front of the feederhouse. This adapter permits the center frame section to move up and down with respect to the front of the feederhouse. It also permits the wing sections to move up and down with respect to the front of the feederhouse, since they are attached to and supported on the center frame section.

An adjustable mechanism is often positioned between the adapter frame and the center frame section to hold the center frame section up in the air at an optimum cutting height with respect to the adapter. The adjustable mechanism is often manually adjusted to alter the cutting height of the center frame.

## SUMMARY

One embodiment is a system for a header assembly that has a center frame configured to pivot relative to an adapter frame about at least one center axis, a center actuator coupled to the center frame to selectively provide a biasing force thereto, a first arm assembly configured to pivot relative to the center frame about at least a first arm axis, a first actuator coupled to the first arm assembly to selectively provide a biasing force thereto, a controller in communication with the center actuator and the first actuator to selectively alter performance characteristics of the center actuator

and the first actuator, and a user interface in communication with the controller and having at least a first option and a second option. Wherein, the controller adjusts the performance characteristics of both the center actuator and the first actuator when the user interface is transitioned between the first option and the second option.

In one example of this embodiment, the center actuator is a hydraulic actuator fluidly coupled to an accumulator, wherein at least one of the performance characteristics altered by the controller is the hydraulic pressure provided to the hydraulic actuator. In another example, the first actuator is a first hydraulic actuator fluidly coupled to an accumulator, wherein at least one of the performance characteristics altered by the controller is the hydraulic pressure provided to the first hydraulic actuator.

In yet another example, the center actuator is a center hydraulic actuator and the first actuator is a first hydraulic actuator, wherein the performance characteristics altered by the controller include hydraulic pressure provided to the center hydraulic actuator and the first hydraulic actuator. One aspect of this example has a center valve fluidly coupled to the center hydraulic actuator and a first valve fluidly coupled to the first hydraulic actuator, wherein the controller communicates with both the center valve and the first valve to selectively provide hydraulic fluid to the corresponding hydraulic actuator at the hydraulic pressure identified by the performance characteristic. In another aspect of this example the hydraulic pressure provided to the center hydraulic actuator is different from the hydraulic pressure provided to the first hydraulic actuator.

In another example, the user interface has a third option, a fourth option, and a fifth option, wherein each of the options corresponds with different performance characteristics. Yet another example has a second arm assembly pivotally coupled to the center frame about at least a second arm axis, a second actuator coupled to the center frame on one end and to the second arm assembly on the other end, wherein the controller is in communication with the second actuator to selectively alter performance characteristics of the second actuator and the controller adjusts the performance characteristics of the second actuator when the user interface is transitioned between the first option and the second option. In another example, the center axis and the first arm axis are about ninety degrees offset from one another.

Another example of this embodiment has a first arm assembly sensor that identifies an arm position relative to the center frame, and a center frame sensor that identifies a center frame position relative to the adapter frame. In one aspect of this example, the performance characteristics include threshold position ranges for the arm position and the center frame position and the controller repositions the first actuator and the center actuator to position the corresponding center frame and first arm assembly into the threshold position ranges.

Another embodiment is a system for adjusting a header assembly of a combine where the system has a center frame pivotally coupled to an adapter frame about at least one center axis, a center actuator configured to reposition the center frame, a first arm assembly configured to be pivotal relative to the center frame about at least a first arm axis, a first actuator configured to reposition the first arm assembly, a second arm assembly configured to be pivotal relative to the center frame about at least a second arm axis, a second actuator configured to reposition the second arm assembly, a controller in communication with the center actuator, the first actuator, and the second actuator to selectively alter

performance characteristics of the center actuator, first actuator, and second actuator, and a user interface in communication with the controller and having at least a first option and a second option. Wherein, the controller adjusts the performance characteristics of at least one of the center actuator, the first actuator, and the second actuator when the user interface is transitioned between the first option and the second option.

In one example of this embodiment, each of the center actuator, the first actuator, and the second actuator are hydraulic actuators, wherein at least one of the performance characteristics altered by the controller is the hydraulic pressure provided to at least one of the center actuator, the first actuator, and the second actuator. One aspect of this example includes at least one accumulator fluidly coupled to at least one of the center actuator, the first actuator, and the second actuator. In another aspect of this example the performance characteristics altered by the controller is the hydraulic pressure provided to each of the center actuator, the first actuator, and the second actuator. Yet another aspect of this example includes a valve assembly that selectively provides hydraulic fluid to each of the center actuator, the first actuator, and the second actuator from a hydraulic source, wherein the controller communicates with the valve assembly to selectively provide hydraulic fluid to each of the center actuator, the first actuator, and the second actuator at a hydraulic pressure identified by the performance characteristics associated with the selected option.

Another example of this embodiment, the first arm axis and the second arm axis are about ninety degrees offset from the center axis.

Yet another embodiment is a method for adjusting a header assembly of a combine, that includes providing a center frame pivotally coupled to an adapter frame about at least one center axis, a center actuator coupled to the center frame, a first arm assembly pivotally coupled to the center frame about at least a first arm axis, a first actuator coupled to the first arm assembly, a second arm assembly pivotally coupled to the center frame about at least a second arm axis, a second actuator coupled to the second arm assembly, a controller in communication with the center actuator, the first actuator, and the second actuator, a user interface, and a sensor assembly, providing, with the user interface, at least a first option and a second option that is selectable by a user, storing, in the controller, a first set of performance characteristic thresholds associated with the first option and a second set of performance characteristic thresholds associated with the second option, identifying, with the user interface, when the first option or the second option are selected, identifying current values for the center frame, first frame assembly, and second frame assembly with the sensor assembly and communicating the current values to the controller, comparing the current values with the performance characteristic thresholds associated with the selected first option or second option, altering a corresponding one or more of the center actuator, the first actuator, and the second actuator with the controller when the current values are not within the performance characteristics thresholds of the selected first or second option.

In one example of this embodiment, the center actuator, the first actuator, and the second actuator are hydraulic actuators and the first set of performance characteristic thresholds and the second set of performance characteristic thresholds are hydraulic pressure thresholds that correspond with each of the center actuator, the first actuator, and the second actuator. In another example, the first and second set

of performance characteristic thresholds are determined by the controller with reference to a float curve chart.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above-mentioned aspects of the present disclosure and the manner of obtaining them will become more apparent and the disclosure itself will be better understood by reference to the following description of the embodiments of the disclosure, taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a side view of an agricultural harvester;

FIG. 2 is a perspective view of an agricultural harvesting head of the harvester of FIG. 1;

FIG. 3 is a partial front perspective view of the frames of the agricultural harvester of FIG. 2 with conveyors removed;

FIG. 4 is a partial front perspective view of the view of the center frame and adapter frame shown in FIG. 3;

FIG. 5 is a slightly elevated fractional rear view of the frames shown in FIGS. 3-4;

FIG. 6 is a fractional front perspective view of FIG. 3 with the left and right frames and linkages removed;

FIG. 7 is a left side view of the arrangement illustrated in FIG. 6;

FIG. 8 is a fragmentary left side view of a linkage taken at section line 8-8 in FIG. 5; and

FIG. 9 is a schematic side view of one embodiment of an adapter frame coupled to a center frame;

FIG. 10 is a schematic back view of the center frame of FIG. 9 coupled to a first and second frame arm assembly;

FIG. 11 is a schematic top view of the center frame and arm assemblies of FIG. 10;

FIG. 12 is a schematic view of one embodiment of an electrical system; and

FIG. 13 is one embodiment of a logic flow chart.

Corresponding reference numerals are used to indicate corresponding parts throughout the several views.

#### DETAILED DESCRIPTION

For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the embodiments described herein and illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the present disclosure is thereby intended, such alterations and further modifications in the illustrated devices and methods, and such further applications of the principles of the present disclosure as illustrated therein being contemplated as would normally occur to one skilled in the art to which the present disclosure relates.

FIG. 1 illustrates an agricultural harvester **100** that has an agricultural combine **102** and an agricultural harvesting head **104**. The agricultural combine **102** comprises a chassis **106** which is supported on four ground supports **108**, as well as a threshing and separating system **112**, a cleaning system **114**, and a feederhouse **110** extending forward from the front of the agricultural combine **102**. The agricultural combine **102** further comprises a grain storage chamber (also known as a "grain tank" or "grain reservoir") that is disposed at the top of the agricultural combine **102** and receives grain that has been threshed, separated, and cleaned.

The agricultural combine **102** is a self-propelled vehicle which is driven over the ground by a power source such as an electric motor or motors or an internal combustion engine. The ground supports **108** are preferably wheels or

tracks. At least one of them are driven in rotation by motors to propel the agricultural combine **102** over the ground.

The feederhouse **110** is pivotally connected to the front of the agricultural combine and extends forward therefrom. The feederhouse **110** is generally in the form of a hollow and generally rectangular box having an endless belt conveyor disposed inside. The hollow rectangular box has an open forward end and an open rear end. The forward end of the feederhouse **110** defines a generally rectangular frame **116** that is configured to support the agricultural harvesting head **104**. A front roller **118** is disposed immediately inside the frame **116**. A corresponding rear roller **120** is disposed at the rear end of the feederhouse **110**. The front roller **118** and the rear roller **120** support opposing ends of a conveyor belt **122**. Each of the front roller **118** and the rear roller **120** may be in the form of a narrow shaft with a plurality of sprockets or gears that engage the inner surface of the conveyor belt **122**. A rotary motor (electric, hydraulic, or pneumatic) is coupled to the rear roller **120** to drive the rear roller **120** in rotation. This rotation causes the conveyor belt **122** to recirculate in an endless fashion around the front roller **118** and the rear roller **120**. The conveyor belt **122** has protrusions, such as cleats or lugs that engage a top surface of a mat of cut crop (not shown) that is presented to the frame **116**. The movement of the conveyor belt **122** draws the mat into the feederhouse and carries it upward on the floor of the feederhouse until it is conveyed through the open rear end of the feederhouse **110** and sent to the threshing, separating and cleaning systems of the agricultural combine **102**.

The frame **116** is generally rectangular and includes a top member and a bottom member that are generally parallel to each other, are spaced apart, and extend generally parallel to the longitudinal extent of the agricultural harvesting head **104**. The frame **116** also includes a left side member and a right side member that are parallel to each other, spaced apart, and extend vertically.

The agricultural harvesting head **104** includes a laterally extending main frame **124** that extends perpendicular to a fore-and-aft harvesting direction of travel "V" of the agricultural harvester **100** and perpendicular to the longitudinal axis of the agricultural combine **102**. The agricultural harvesting head **104** further includes an elongate reciprocating knife **128** that extends across almost the entire width of the agricultural harvesting head **104**. This reciprocating knife is disposed immediately in front of three cut crop conveyors. These three cut crop conveyors include a left side conveyor **130** that carries cut crop from the left side of the agricultural harvesting head **104** to a central region of the agricultural harvesting head **104**, a right side conveyor **132** that carries crop from the right side of the agricultural harvesting head **104** to the central region of the agricultural harvesting head **104**, and a central conveyor **134** that receives crop from the left side conveyor **130** and the right side conveyor **132**, and conveys the cut crop rearward and underneath a drum conveyor **136**. Each of these three conveyors is an endless belt conveyor and is disposed immediately behind the reciprocating knife **128** to receive crop cut by the reciprocating knife **128**.

The laterally extending main frame **124** includes three frame sections that are coupled together to pivot with respect to each other about fore-and-aft extending axes. Left frame section **138** extends from the outer left end of the agricultural harvesting head to a central region of the agricultural harvesting head **104**. Center frame section **140** extends across a middle portion of the agricultural harvesting head **104**. Right frame section **142** extends from the outer right

end of the agricultural harvesting head **104** to the central region of the agricultural harvesting head **104**.

The left side of conveyor **130** is supported on the left frame section **138**. Several rollers, including a proximal roller **202** adjacent to the center frame section **140** and distal roller **204** adjacent to the leftmost end of the left frame section **138** are provided to support an endless belt **206**. A motor drives the proximal roller **202** in rotation. The proximal roller **202** recirculates in turn the endless belt **206** about the proximal roller **202** and the distal roller **204**. Crop material cut by the reciprocating knife **128** in front of the left frame section **138** falls upon the top surface of the endless belt **206** and is drawn toward the center frame section **140**.

The inner end of the left frame section **138** is connected to the center frame section **140** to pivot up and down at its outer end with respect to the center frame section **140**. The inner end of the right frame section **142** is connected to the center frame section **140** to pivot up and down at its outer end with respect to the center frame section **140**.

An upper left link **144** and a lower left link **146** extend between and couple the left frame section **138** and the center frame section **140**. An identically constructed and mirror image upper right link **144'** and a lower right link **146'** extend between and couple the right frame section **142** in the center frame section **140**.

A proximal end of the upper left link **144** is coupled to the center frame section **140** by a first pivot joint **148** and is configured to pivot with respect to the center frame section **140** about a first axis **150** that extends generally in the direction of travel "V".

An opposing distal end of the upper left link **144** is coupled to the left frame section **138** by a second pivot joint **152** and is configured to pivot with respect to the left frame section **138** about a second axis **154** that extends in the direction of travel "V".

A proximal end of the lower left link **146** is coupled to the center frame section **140** by a third pivot joint **156** and is configured to pivot with respect to the center frame section **140** about a third axis **158** that extends in the direction of travel "V".

An opposing distal end of the lower left link **146** is coupled to the left frame section **138** by a fourth pivot joint **160** and is configured to pivot with respect to the left frame section **138** about a second axis **162** that extends in the direction of travel "V".

A hinge joint **164** is disposed adjacent to the reciprocating knife **128** at a forward edge of the agricultural harvesting head **104**. The hinge joint **164** couples a forwardly extending member **166** of the center frame section **140** to a forwardly extending member **168** of the left frame section **138**.

An identically constructed and mirror image hinge joint **164'** is disposed adjacent to the reciprocating knife **128** and forward edge of the agricultural harvesting head **104**. The hinge joint **164'** couples a forwardly extending member of the center frame section **140** a forwardly extending member of the right frame section **138**.

The attachment points of the proximal ends of the upper left link **144** and the lower left link **146** are closer together (as measured in a vertical direction) than the attachment points of the distal ends of the upper left link **144** and the lower left link **146**.

The two attachment points of the upper left link **144** define a first construction line **174** extending through both of the attachment points of the upper left link **144**. The two attachment points of the lower left link **146** define a second construction line **176** extending through the attachment points of the lower left link **146**.

The first construction line and the second construction line are not parallel. When viewed from the rear of the agricultural harvesting head **104** they intersect each other at a point of intersection **170**. Whenever the left frame section **138** pivots up and down with respect to the center frame section **140**, these sections pivot with respect to each other about the point of intersection **170**.

Since the right side of the agricultural harvesting head **104** is identically constructed (but in mirror image fashion) as the left side, the same intersection, pivot line, 1st construction line, and second construction line are also provided on the right side of the agricultural harvesting head **104** and are denoted with the numbers **170'**, **172'**, **174'** and **176**.

In the illustrated example, the point of intersection **170** is located closer to the longitudinal and vertical midplane of the center frame section **140** than all four of the attachment points of the upper left link **144** and the lower left link **146** to the left frame section **138** and the center frame section **140**.

The pivoting axis of the hinge joint **164** is disposed forward of and slightly below the point of intersection **170** of the two construction lines. Thus, the left frame section **138** is constrained by the hinge joint **164**, the upper left link **144** and the lower left link **146** to pivot with respect to the center frame section **140** about a pivot line **172** that extends through the point of intersection **170** and through the pivoting axis of the hinge joint **164**. The pivot line **172** also extends through or immediately adjacent to the reciprocating knife **128**. In this manner, whenever the left frame section **138** pivots with respect to the center frame section **140**, the reciprocating knife **128** (which extends across both the left frame section **138** and the center frame section **140**) can flex without being damaged.

The reciprocating knife **128** is typically close to the ground where it can sever plant stalks close to the ground. The rear portion of the three frame sections, the upper left link **144** and the lower left link **146** are commonly elevated above the ground to provide ground clearance. For this reason, the pivot line **172** extends forward and slightly downwardly from the point of intersection **170** to the hinge joint **164**.

The pivot line **172** extends through the proximal roller **202**. The rotational axis of the proximal roller **202** is collinear with the pivot line **172**. Thus, when the left frame section **138** pivots up and down with respect to the center frame section **140**, the proximal roller **202** does not move with respect to the left frame section **138** and the center frame section **140**.

The center frame section **140** is illustrated coupled to and supported on an adapter frame **300**. The adapter frame **300** is in turn coupled to and supported on the feederhouse frame **116**. Four links, including an upper left link **302**, an upper right link **304**, a lower left link **306**, and a lower right link **308** are coupled to and between the center frame section **140** and the adapter frame **300**. A forward end of each of the four links is coupled to the center frame section **140** and a rear end of each of the four links is coupled to the adapter frame **300**. The four links extend at least partially fore-and-aft.

The center frame section **140** is generally rectangular and extends vertically and transverse to the direction of travel "V". It has two laterally spaced apart vertical side members **310**, **312**, an upper horizontal member **314** that is fixed at both ends to an upper portion of the side members **310**, **312**, and a lower horizontal member **316** that is fixed at both ends to a lower portion of the side members **310**, **312**. The lower horizontal member **316** is spaced apart and disposed below the upper horizontal member **314**. The side members **310**,

**312** are parallel to each other. The upper horizontal member **314** and the lower horizontal member **316** are parallel to each other. These four members **310**, **312**, **314**, **316** are fixed together to define a rigid rectangular frame having a central aperture **317** configured to receive and transmit all the cut crop harvested by the agricultural harvesting head **104**.

The adapter frame **300** is generally rectangular and extends vertically and transverse to the direction of travel "V". It has two laterally spaced apart vertical side members **318**, **320**, an upper horizontal member **322** that is fixed at both ends to an upper portion of the side members **318**, **320**, and lower horizontal member **324** that is fixed at both ends to a lower portion of the side members **318**, **320**. The lower horizontal member **324** is spaced apart and disposed below the upper horizontal member **322**. The side members **318**, **320** are parallel to each other. The upper horizontal member **322** and the lower horizontal member **324** are parallel to each other. These four members **318**, **320**, **322**, **324** are fixed together to define a rigid rectangular frame having a central aperture **326** that is configured to receive and transmit all the cut crop material harvested by the agricultural harvesting head **104**, and in particular to receive all the cut crop material conveyed through the central aperture **317** of the center frame section **140**.

The four links **302**, **304**, **306**, **308** extend between and are coupled to the center frame section **140** and the adapter frame **300**. The two lower links **306**, **308** have the same length. Each of the four links **302**, **304**, **306**, **308** may be formed as turnbuckles with threaded ball joints at each end to permit the length of the links (and thus the angle of the mainframe **124**) to be readily adjusted for a variety of crops. Alternatively, the four links **302**, **304**, **306**, **308** may have a fixed length.

The four links are coupled at their forward ends to the center frame section **140** and at their rear ends to the adapter frame **300**. The pivot joints that couple the links to the frames permit the frames to move up and down with respect to each other, and permit the frames to rotate with respect to each other about an axis **408** that extends in a fore-and-aft direction. This axis extends through the central apertures of both the center frame section **140** and the adapter frame **300**.

The upper links (links **302**, **304**) are spaced apart and are pivotally coupled at their forward ends to brackets **410**, **412**, respectively. Brackets **410**, **412** are fixed to and extend upward from the upper horizontal member **314**. The brackets are spaced apart on the upper horizontal member **314**. Bracket **410** is fixed to the upper horizontal member **314** adjacent to the upper end of the vertical side member **310**. Bracket **412** is fixed to the upper horizontal member **314** adjacent to the upper end of the vertical side member **312**.

The upper links (links **302**, **304**) are spaced apart and are pivotally coupled at their rear ends to brackets **414**, **416**, respectively. Brackets **414**, **416** are fixed to and extend upward from the upper horizontal member **322** of the adapter frame **300**. The brackets are spaced apart on the upper horizontal member **322**. Bracket **414** is fixed to the upper horizontal member **322** adjacent to the upper end of the vertical side member **318**. Bracket **416** is fixed to the upper horizontal member **322** adjacent to the upper end of the vertical side member **320**.

The two upper links **302**, **304** have the same length between their pivot connections to the frames at each end. The two upper links **302**, **304** lie in a first common plane "P1" (see FIG. 7).

The lower links (links **306**, **308**) are spaced apart and are pivotally coupled at their forward ends to brackets **418**, **420**, respectively. Bracket **418** is fixed to and extends laterally

outward from a lower portion of vertical side member **310** adjacent to the left end of lower horizontal member **316**. Bracket **420** is fixed to and extends laterally outward from a lower portion of vertical side member **312** adjacent to the right end of lower horizontal member **316**.

The lower links (links **306**, **308**) are spaced apart and are pivotally coupled at their rear ends to brackets **422**, **424**, respectively. Bracket **422** is fixed to and extends upward from a lower left portion of adapter frame **300**. Bracket **424** is fixed to and extends upward from a lower right portion of adapter frame **300**. The two lower links **306**, **308** have the same length between their pivot connections to the frame at each end. The two lower links **306**, **308** lie in a second common plane.

When viewing the center frame section **140** and the adapter frame **300** from the rear, the links **302**, **304**, **306**, **308** are disposed at the upper left, upper right, lower left, and lower right corners of the apertures **317**, **326**. The links collectively surround the apertures **317**, **326**.

All four of the links **302**, **304**, **306**, **308** extend generally fore-and-aft and are generally parallel. However, they are not perfectly parallel, nor do they extend perfectly fore-and-aft. In fact, they are slightly nonparallel in order to provide particular benefits that four perfectly parallel links would not provide.

In particular, the two upper links **302**, **304** extend forward and outward. Thus, the distance between the two upper links at their pivotal attachment points on the center frame section **140** is greater than the distance between the two upper links at their pivotal attachment points on the adapter frame **300**. The two lower links **306**, **308** extend forward and inward. Thus, the distance between the two lower links at their attachment points on the center frame section **140** is less than the distance between the two lower links at their attachment points on the adapter frame **300**.

By arranging the spacing of the attachment points (and therefore the direction the two upper links and the two lower links extend) as shown, the center frame section **140** and the adapter frame **300** cannot be translated side to side with respect to each other. If a great force was applied to force side to side (lateral) translation of the two frames with respect to the other, either one or more of the links will break and/or one or more of the frames will break. The links and the frames are robust enough that during normal operation no such lateral translation nor any link or frame breakage will occur under normal operational loading.

While four links **302**, **304**, **306**, **308** are illustrated and described herein, the adapter frame **300** may also be coupled to the center frame section **140** with only three links as is known in the art. Accordingly, this disclosure contemplates utilizing any number of links, or no links at all, in order to pivotally couple the frame section **140** to the adapter frame.

An actuator or the like couples the adapter frame **300** to the center frame section **140**. The actuator may support the weight of the center frame section **140** and the components coupled thereto, such that the center frame section is partially or fully suspended in a floating position on links **302**, **304**, **306**, **308**.

As is discussed in more detail herein, in one aspect of this disclosure the operator can adjust actuator (see center actuator **902** of FIG. **9**) to provide a large lifting force on the center frame section **140** that support substantially the entire weight of the agricultural harvesting head **104**. The operator will adjust this large lifting force such that the ground force acting upward against the bottom of the agricultural harvesting head **104** is quite small.

The operator desires that the ground force stays relatively constant. If the ground force increases, it may cause the reciprocating knife **128** to dig into the ground. If the ground force decreases the reciprocating knife **128** may be lifted entirely off the ground, away from the plant stalks it is supposed to cut.

The center actuator **902** applies a constant upward force against the main frame **124** in a wide range of operating positions, and therefore maintains a constant ground force against the ground. The center actuator **902** may include a left side center actuator **902** and a right side center actuator **902**. The left side center actuator **902** extends between and couples the adapter frame **300** and the center frame section **140** on the left side of the adapter frame **300**. The right side center actuator **902** extends between and couples the adapter frame **300** and the center frame section **140** on the right side of the adapter frame **300**. The two actuators **902** and corresponding linkages are similarly constructed and are substantially mirror images of each other. Therefore the construction and operation of the left side center actuator **902** is substantially the same as the right side center actuator **902**.

Similarly, the right and left frame section **142**, **138** may implement one or more actuator (see first actuator **1008** and second actuator **1016** of FIG. **10**) to modify the ground force experienced by the corresponding right and left frame sections **142**, **138** as the agricultural harvesting head **104** travels there along. Accordingly, as discussed in more detail herein the agricultural harvesting head **104** may require adjustments to both the center actuators **902** to modify the center frame section **140** and the first and second actuators **1008**, **1016** to modify the response of the right and left frame section **142**, **138** to properly adjust the way the agricultural harvesting head **104** responds to ground force changes.

Referring now to FIG. **9**, a schematic side view **900** of one embodiment of this disclosure is illustrated. The schematic side view **900** is meant to generally illustrate one example of a coupling configuration between the adapter frame **300** and the center frame **140**. While FIGS. **1-8** show and describe a very specific way to pivotally couple the agricultural harvesting head **104** to the agricultural combine **102**, a person skilled in the art understands the teaching discussed herein can be applied to any configuration that has an adjustable center section and at least one arm assembly regardless of the exact methodology used to pivotally couple the assemblies to one another.

Accordingly, this disclosure contemplates coupling the adapter frame **300** to the center frame **140** utilizing any mechanical configuration known in the art wherein an actuator, spring, or the like can be implemented to reposition the center frame **140** relative to the adapter frame **300**. Further, while the center frame **140** is illustrated and discussed herein as being coupled to the feederhouse frame **116** of the feederhouse **110**, in other embodiments the center frame **140** is pivotally coupled directly to the chassis **106**. Accordingly, the center frame **140** can be pivotally coupled to any portion of the harvester **100**.

In the schematic side view **900**, the upper right link **304** and lower right link **308** are illustrated extending from the adapter frame **300** to the center frame **140**. Similarly, upper and lower left links may extend from the adapter frame **300** to the center frame **140** although the left links are not visible in the side view of FIG. **9**. Further, left and right frame sections **138**, **142** may be pivotally coupled to the center frame **140** as discussed herein (left frame section not visible in FIG. **9**).

In one aspect of this disclosure, one or more center actuator **902** may be positioned between the adapter frame **300** and the center frame **140** to cause the center frame **140** to move relative to the adapter frame **300**. While only one center actuator **902** is illustrated and discussed with reference to FIG. 9, one embodiment of this disclosure implements a left and right side center actuator **902**. Further, in one non-exclusive example, the center actuator **902** may be a linear actuator such as a hydraulic cylinder. In this example, the center actuator **902** can extend and contract to thereby alter the positioned of the center frame **140** relative to the adapter frame **300**. More specifically, the center frame **140** may be coupled to the adapter frame utilizing a four-bar or the like linkage assembly as discussed herein. In this configuration, the center actuator **902** may be repositioned to pivot the center frame **140** partially around a center axis **904** defined by a pivot point of the lower link **308**. Accordingly, as the center actuator **902** is repositioned, the center frame **140** may raise and lower correspondingly relative to the adapter frame **300**.

In one aspect of this disclosure, there may be two center actuators **902** coupled between the adapter frame **300** and the center frame **140**. Further still, on other embodiments there may be more than two center actuators **902**. Accordingly, this disclosure contemplates utilizing any number of center actuators **902** required to address the expected loads on the center frame **140**.

The center actuator **902** may be any known type of actuator. More specifically, the center actuator **902** may be a pneumatic or hydraulic actuator that utilizes a piston and rod at least partially within a cylinder to accommodate linear displacement based on a fluid provided to chambers of the cylinder at a pressure and volume. Further still, the center actuator **902** may be an electrically powered linear actuator that is capable of linear displacement based on the electrical power provided thereto. Accordingly, this disclosure contemplates utilizing any type of actuator capable of linear displacement known in the art as the center actuator **902**.

Regardless the type of actuator, the center actuator **902** may be controlled by a controller **906**. For example, if the center actuator **902** is a hydraulic or pneumatic actuator, the controller **906** may selectively change the fluid pressure provided to the center actuator **902** through a center valve **908**. More specifically, the center valve **908** may be a variable valve that allows the controller to selectively couple the center actuator **902** to a fluid source **910** at varying pressures. Alternatively, if the center actuator **902** is an electrical actuator, the controller **906** may control the electrical power provided to the center actuator **902**.

In one embodiment of FIG. 9, the center actuator **902** is a hydraulic actuator coupled to a hydraulic source **910**, such as a pump, through the center valve **908**. As discussed herein, the center valve **908** may be a variable valve controlled by the controller **906** to selectively fluidly couple the center actuator **902** to the hydraulic source **910** at a fluid pressure that corresponds with performance characteristics identified by the controller **906**. Further still, in one embodiment an accumulator **912** may be fluidly coupled to a fluid line **914** that fluidly couples the center valve **908** to the center actuator **902**. The accumulator **912** may be any known type of hydraulic accumulator that allows the center actuator **902** to springedly support the center frame **140**. More specifically, while the controller **906** may alter the fluid pressure provided to the center actuator **902** with the center valve **908** to raise or lower the center frame **140** relative to the adapter frame **300**, the accumulator **912** may allow the center actuator **902** to address force changes with

a spring like response. In other words, if the center actuator experiences an excessive compressive force, the fluid therein may be forced into an expanding fluid chamber of the accumulator **912** allowing the center actuator to be linearly displaced by the compressive force.

In another aspect of this disclosure, a center frame sensor **916** may be in communication with the controller **906** to identify a value. In the example where the center actuator **902** is a hydraulic or pneumatic actuator, the center frame sensor **916** may be a pressure sensor fluidly coupled to the center actuator **902** or other portion of the fluid line **914** to identify a fluid pressure therein. Alternatively, in another example the center frame sensor **916** may be a position sensor that identifies the position of an actuator rod relative to an actuator cylinder. In other embodiments the center frame sensor **916** is a position sensor coupled to a linkage or the like to identify the position of the center frame **140** relative to the adapter frame **300**. Further still, one embodiment considered herein includes both a position sensor and a pressure sensor as part of the center frame sensor **916**.

Regardless of the type or location of the center frame sensor **916**, the controller **906** may utilize the values identified by the center frame sensor **916** to indicate the performance characteristics of the center frame **140** relative to the adapter frame **300**. More specifically, if the center frame sensor **916** is a pressure sensor, the values identified by the controller **906** may indicate the load on the center actuator **902**. Further still, higher pressures may indicate to the controller **906** that the center frame **140** is at least partially raised relative to the underlying surface. In yet another embodiment, higher pressures may indicate a softer response (or softer ground force response) of the center actuator **902** to movement of the center frame **140** relative to the adapter frame **300**. That is to say, the center actuator **902** may provide a biasing force to the agricultural harvesting head **104** away from the underlying surface.

Similarly, when the center frame sensor **916** is a position sensor, the values communicated to the controller **906** may indicate the position of the center frame **140** relative to the adapter frame **300**. In other words, the center frame sensor **916** may be utilized by the controller **906** to identify a height **918** of the center frame **140** above an underlying surface. More specifically, in one non-exclusive embodiment the height of the adapter frame **300** above the underlying surface **920** may be substantially constant but the height **918** of the center frame **140** may vary based on the position of the center actuator **902**.

Referring now to FIG. 10, a schematic front view **1000** of the agricultural harvesting header **104** is illustrated. More specifically, the center frame **140** is illustrated pivotally coupled to a first arm assembly **1002** and a second arm assembly **1004**. The first arm assembly **1002** may be comprised of the right frame section **142** and other portions associated therewith as discussed herein. The first arm assembly **1002** may be pivotally coupled to the center frame **140** via a first linkage assembly **1006**. Further, the first linkage assembly **1006** may include the upper right link **144'** and the lower right link **146'** as discussed herein. However, any pivotal coupling assembly known in the art may be implemented for the first linkage assembly **1006**. Further still, in one non-exclusive example the first arm assembly **1002** may be pivotally coupled directly to the center frame **140** without utilizing the first linkage assembly **1006** at all.

In one aspect of this disclosure, a first actuator **1008** may be coupled to the first arm assembly **1002** on one end and to the center frame **140** on the other end. Further, the first actuator **1008** may be repositionable to pivot the first arm

## 13

assembly **1002** at least partially about a first arm axis **1010**. A first arm sensor **1012** may also be positioned to identify a value indicating the relationship of the first arm assembly **1002** relative to the center frame **140**. The first arm sensor **1012** may be a pressure sensor or a position sensor, among other types of sensors, similar to the center frame sensor **916**.

In another aspect of this disclosure, the first actuator **1008** may not be coupled to the center frame **140** at all. Rather, in this embodiment the first actuator **1008** may be coupled to the first arm assembly **1002** or a linkage thereof on one end, and to the adapter frame **300** on the other. Alternatively, the first actuator **1008** may be coupled to any other portion of the agricultural harvester **100**. A person skilled in the relevant art understands the many different locations wherein the first actuator **1008** may be coupled between the first arm assembly **1002** and other components of the agricultural harvester **100** to allow the first arm assembly **1002** to be pivotal relative to the center frame **140**. Accordingly, this disclosure contemplates positioning the first actuator **1008** in any location that allows the first actuator **1008** to reposition the first arm assembly **1002** or provide different float force characteristics thereto.

Similarly, the second arm assembly **1004** may be comprised of the left frame section **138** and other portions associated therewith as discussed herein. The second arm assembly **1004** may be pivotally coupled to the center frame **140** via a second linkage assembly **1014**. Further, the second linkage assembly **1014** may include the upper left link **144** and the lower left link **146** as discussed herein. However, any pivotal coupling assembly known in the art may be implemented for the second linkage assembly **1014**. Further still, in one non-exclusive example the second arm assembly **1004** may be pivotally coupled directly to the center frame **140** without utilizing the second linkage assembly **1014** at all.

In one aspect of this disclosure, a second actuator **1016** may be coupled to the second arm assembly **1004** on one end and to the center frame **140** on the other end. Further, the second actuator **1016** may be repositionable to pivot the second arm assembly **1004** at least partially about a second arm axis **1018**. A second arm sensor **1020** may also be positioned to identify a value indicating the relationship of the second arm assembly **1004** relative to the center frame **140**. The second arm sensor **1020** may be a pressure sensor or a position sensor, among other types of sensors, similar to the center frame sensor **916**. In another aspect of this disclosure, the second actuator **1016** may not be coupled to the center frame **140** at all. Rather, in this embodiment the second actuator **1016** may be coupled to the second arm assembly **1004** or a linkage thereof on one end, and to the adapter frame **300** on the other. Alternatively, the second actuator **1016** may be coupled to any other portion of the agricultural harvester **100**. A person skilled in the relevant art understands the many different locations wherein the second actuator **1016** may be coupled between the second arm assembly **1004** and other components of the agricultural harvester **100** to allow the second arm assembly **1004** to be pivotal relative to the center frame **140**. Accordingly, this disclosure contemplates positioning the second actuator **1016** in any location that allows the second actuator **1016** to reposition the second arm assembly **1004** or provide different float force characteristics thereto.

In one embodiment of FIG. **10**, the first and second actuators **1008**, **1016** are hydraulic actuators coupled to the hydraulic source **910**, through a valve assembly **1022**. The valve assembly **1022** may have a first valve **1024** that

## 14

selectively controls the fluid pressure provided to the first actuator **1008** and a second valve **1026** that selectively controls the fluid pressure provided to the second actuator **1016**. Each of the first and second valves **1024**, **1026** may be variable valves controlled by the controller **906** to selectively fluidly couple the corresponding actuators **1008**, **1016** to the hydraulic source **910** at a fluid pressure that corresponds with performance characteristics identified by the controller **906**.

In one embodiment, accumulators **1028**, **1030** may be fluidly coupled to fluid lines **1032**, **1034** that fluidly couple the valves to the corresponding actuators **1008**, **1016**. The accumulators **1028**, **1030** may be any known type of hydraulic accumulator that allows the corresponding actuators **1008**, **1016** to springily support the corresponding arm assembly **1002**, **1004**. More specifically, while the controller **906** may alter the fluid pressure provided to the actuators **1008**, **1016** with the valve assembly **1022** to raise or lower the corresponding arm assemblies **1002**, **1004** relative to the center frame **140**, the accumulators **1028**, **1030** may allow the actuators **1008**, **1016** to address force changes with a spring like response. In other words, if the actuators **1008**, **1016** experiences an excessive compressive force, the fluid therein may be forced into an expanding fluid chamber of the accumulators **1028**, **1030** similar to the accumulator **912**.

In the example where the actuators **1008**, **1016** are hydraulic or pneumatic actuators, the sensors **1012**, **1020** may be pressure sensors fluidly coupled to the actuators **1008**, **1016** or other portion of the fluid lines **1032**, **1034** to identify a fluid pressure therein. Alternatively, in another example the sensors **1012**, **1020** may be position sensors that identify the position of an actuator rod relative to an actuator cylinder. In other embodiments the sensors **1012**, **1020** are position sensors coupled to a linkage or the like to identify the position of the corresponding arm assembly **1002**, **1004** relative to the center frame **140**. Further still, one embodiment considered herein includes both a position sensor and a pressure sensor as part of the sensors **1012**, **1020**.

Regardless of the type or location of the sensors **1012**, **1020**, the controller **906** may utilize the values identified by the sensors **1012**, **1020** to indicate the performance characteristics of the of the corresponding arm assembly **1002**, **1004** relative to the center frame **140**. More specifically, if the sensors **1012**, **1020** are pressure sensors, the values identified by the controller **906** may indicate the load on the corresponding arm assembly **1002**, **1004** or the expected ground force response. Further still, higher pressures may indicate to the controller **906** that the corresponding arm assembly **1002**, **1004** is at least partially raised relative to the underlying surface or will have a softer ground force response. In yet another embodiment, lower pressures may indicate a stiffer ground force response of the actuators **1008**, **1016** when the corresponding arm assembly **1002**, **1004** experiences a ground force input.

Similarly, when the sensor **1012**, **1020** are position sensors, the values communicated to the controller **906** may indicate the position of the corresponding arm assembly **1002**, **1004** relative to the center frame **140**. In other words, the sensors **1012**, **1020** may be utilized by the controller **906** to identify the orientation of the arm assemblies **1002**, **1004** relative to the center frame **140**. In this embodiment, both the height of the center frame **140** and the orientation of the arm assemblies **1002**, **1004** may be monitored by the controller **906** to identify the cutting height of the reciprocating knife **128** among other things.

While FIG. **10** illustrates the first and second arm assemblies **1002**, **1004** as being pivotally coupled to the center

15

frame **140** via linkage assemblies **1006**, **10014**, in other embodiments considered herein the arm assembly **1002**, **1004** may not be pivotally coupled to the center frame **140** at all. For example, in one non-exclusive embodiment the arm assemblies **1002**, **1004** may be pivotally coupled to the adapter frame **300** instead to the center frame **140**. Accordingly, this disclosure contemplates implementing the teachings discussed herein regardless of the particular locations with which the components **110**, **140**, **300**, **1002**, **1004** are coupled to one another.

Referring now to FIG. **11**, a top view of a schematic representation **1100** of the adapter frame **300**, the center frame **140**, and the arm assemblies **1002**, **1004** is illustrated. More specifically, the relationship of the center axis **904** relative to the first and second arm axes **1010**, **1018** is illustrated. As can be seen in FIG. **11**, the first and second arm axes **1010**, **1018** are about ninety degrees offset from the center axis **904**. In this configuration, the center actuator **902** alters the height of the center frame **140** by pivoting partially about the center axis **904**. Further, the center axis **904** may extend transverse to a longitudinal axis **1104** which extends along the general direction of travel of the agricultural harvester **100**.

While the center frame **140** is described as pivoting partially about the center axis **904**, in one aspect of this disclosure the center frame **140** is pivotally coupled to the adapter frame **300** via a four-bar linkage as shown and described herein. Accordingly, the center axis **904** may be defined through the pivoting coupling point of the lower links **306**, **308** to the adapter frame **300**. Similarly, the arm assemblies **1002**, **1004** may be coupled to the center frame via one or more linkage. In one non-exclusive example, the first arm axis **1010** is defined through the pivotal coupling point of the lower link **146'** to the center frame **140** and the second arm axis **1018** is defined through the pivotal coupling point of the lower link **146** to the center frame **140**.

Further still, while the first and second arm axis **1010**, **1018** are discussed herein as being about ninety degrees offset from the center axis **904**, in one embodiment the first and second arm axis **1010**, **1018** may be offset slightly less or more than ninety degrees from the center axis **904**. However, when the center frame **140** rotates at least partially about the center axis **904**, the orientation of both the first and second arm assemblies **1002**, **1004** is affected since both the first and second arm assemblies **1002**, **1004** are pivotally coupled to the center frame **140**. Accordingly, as discussed herein, often adjusting the orientation of the center frame **140** relative to the adapter frame **300** also requires adjustments to the first and second arm assemblies **1002**, **1004** as well.

Referring now to FIG. **12**, a schematic view **1200** of some of the electrical components is illustrated. More specifically, the controller **906** is illustrated in communication with several electrical systems of the agricultural harvesting machine. While only one controller **906** is illustrated, this disclosure contemplates implementing the logic discussed herein utilizing multiple controllers as well. The controller **906** may have a processor and a memory unit among other components that enable the controller **906** to process information and implement algorithms, programmed responses, logic, and the like. Further, the controller **906** may be located on the agricultural harvester **100** or remotely therefrom and communicate wirelessly with the agricultural harvester **100** utilizing known wireless communication protocols.

In one aspect of this disclosure, the controller **906** communicates with the valve assembly **1022** to at least partially

16

control the center actuator **902**, first actuator **1008**, and second actuator **1016** among other things. The valve assembly **1022** may be a valve block that has the first valve **1024**, second valve **1026**, and center valve **908** coupled to one another. Alternatively, each of the first valve **1024**, second valve **1026**, and center valve **908** can be located separate from one another. The controller **906** may communicate with each valve **1024**, **1026**, **908** of the of the valve assembly **1022** via a communication protocol **1202**. The communication protocol **1202** may be electrical signals sent through a wire harness electrically coupling the valve assembly **1022** to the controller **906**. Alternatively, the communication protocol **1202** may also be wireless signals that allow the controller **906** and valve assembly **1022** to communicate with one another using known wireless capabilities.

Each valve **1024**, **1026**, **908** of the of the valve assembly **1022** may be a variable valve capable of varying the flow rate, pressure, or the like provided to the corresponding actuator **1008**, **1016**, **902**. In this example, the controller **906** may send signals to the valve assembly **1022** indicating the desired flow rate and pressure to be provided through the corresponding valve **1024**, **1026**, **908** to thereby alter the position and response characteristics of the agricultural harvesting head **104**.

Similarly, the controller **906** may communicate with a sensor assembly **1204** via a communication protocol **1202**. The sensor assembly **1204** may include any known type of sensor they may identify conditions of the agricultural head **104** among other things. In the non-exclusive example of FIG. **12**, the sensor assembly **1204** may include the first arm assembly sensor **1012** which may be a position sensor **1012a** and a pressure sensor **1012b** that indicate the position of the first arm assembly **1002** relative to the center frame **140** and the fluid pressure provided to the first actuator **1008**. The sensor assembly **1204** may also include the second arm assembly sensor **1020** which may be a position sensor **1020a** and a pressure sensor **1020b** that indicate the position of the second arm assembly **1004** relative to the center frame **140** and the fluid pressure provided to the second actuator **1016**. Further still, the sensor assembly **1204** may also include the center frame sensor **916** which may be a position sensor **916a** and a pressure sensor **916b** that indicate the position of the center frame **140** relative to the adapter frame **300** and the fluid pressure provided to the center actuator **902**.

While several specific types of sensors are discussed herein for the sensor assembly **1204**, this disclosure contemplates utilizing any type of sensor known in the art to communicate values to the controller **906**. Accordingly, the sensors discussed herein are meant only as some non-exclusive examples considered for this disclosure.

The controller **906** may also communicate with a user interface **1206** via a communication protocol **1202**. The user interface **1206** may be any type of user interface that allows a user to indicate a preference to the controller **906**. More specifically, the user interface **1206** may be a touchscreen or the like positioned within a cab of the agricultural combine **102**. The touch screen may be capable of displaying many icons thereon and identifying to the controller **906** when one of the displayed icons is selected by the user. In one non-exclusive example, the user interface **1206** may have at least five icons or options that may be selected by the user. Option1 **1208** may correspond with a very firm configuration, Option2 **1210** may correspond with a firm configuration, Option3 **1212** may correspond with a typical configuration, Option4 **1214** may correspond with a soft configuration, and Option5 **1216** may correspond with a very soft configuration.

While the user interface **1206** is described as being a touchscreen, this disclosure contemplates any known type of user interface **1206**. More specifically, in another embodiment, each of the options **1208**, **1210**, **1212**, **1214**, **1216** may be a toggle switch or button that is selectable from within the cab. Alternatively, the user interface **1206** can be voice commands wherein the user verbally expresses the desired option. Further still, in one embodiment, the user interface is displayed on a remote device such as a laptop, tablet, smartphone, or the like. Accordingly, this disclosure contemplates utilizing many different forms for a user interface **1206**.

Referring now to FIG. **13**, a logic flow chart **1300** of one embodiment of this disclosure is illustrated. Initially in box **1302**, the options **1208**, **1210**, **1212**, **1214**, **1216** for the user interface **1206** may be provided. As discussed herein, the way the options are provided may depend on the type of user interface **1206** being implemented. If the user interface **1206** is a touchscreen display, the options may be provided as icons on the touchscreen display. Alternatively, the options may be provided by switches or buttons in the cab. Further still, the options may be provided audibly to incite a verbal response.

In box **1304**, the controller **906** may associate performance characteristics with each of the options **1208**, **1210**, **1212**, **1214**, **1216** provided on the user interface **1206**. The performance characteristics may be threshold values associated with the fluid pressure provided to each actuator **902**, **1008**, **1016**, position thresholds of the arm assemblies **1002**, **1004** relative to the center frame **140** and the center frame **140** relative to the adapter frame **300**, or any combination thereof. The performance characteristics associated with each option may be stored in a memory unit or the like that the controller **906** may access as needed. In one embodiment the performance characteristics are identified by the controller **906** with reference to a graph of float curves. In this embodiment, the float curves may be predefined values that have been established from field testing or virtual performance data to indicate the desired performance characteristics that should be associated with each option.

In box **1306**, the controller **906** identifies which option was selected via the user interface **1206**. The user interface **1206** may send signals to the controller **906** through the communication protocol **1202** indicating the option selected by the user.

In box **1308**, the controller **906** may identify the current values of the sensor assembly **1204**. The current values may include the current fluid pressure being applied to each actuator **902**, **1008**, **1016**, the position of the components **300**, **140**, **1002**, **1004** relative to one another, or any combination thereof among other things. Next, in box **1310**, the controller **906** may compare the current values identified in box **1308** with the performance characteristics of the option selected in box **1306**. This portion may involve determining whether the center frame sensor **916** is identifying a pressure that is within a center frame pressure threshold range of the selected performance characteristics, whether the first arm assembly sensor **1012** is identifying a pressure that is within a first arm assembly pressure threshold range of the selected performance characteristics, and whether the second arm assembly sensor **1020** is identifying a pressure that is within a second arm assembly pressure threshold range of the selected performance characteristics among other things. Additionally, the position of the components **300**, **140**, **1002**, **1004** may be compared to expected position thresholds in box **1310** as well.

In box **1312**, the controller **906** may utilize the valve assembly **1022** to alter any of the actuators **902**, **1008**, **1016** that were not within the performance characteristics thresholds identified in box **1310**. More specifically, if the center frame sensor **916** is indicating values that are not within the performance characteristics associated with the selected option, the controller **906** may alter the center valve **908** until the center frame sensor **916** indicates a value within the performance characteristics of the selected option. The controller **906** may implement a similar procedure for the first and second actuators **1008**, **1016** to ensure all of the performance characteristic values are met by all of the actuators **902**, **1008**, **1016**. In one aspect of this disclosure, the controller **906** may continue to compare the values of the sensor assembly **1204** to the performance characteristics to ensure that the sensor values remain within thresholds for the selected option.

In one aspect of this disclosure, a user may utilize the user interface **1206** to select a desired option therefrom. In one non-exclusive example, the options **1208**, **1210**, **1212**, **1214**, **1216** may refer to a float response of the agricultural harvesting header **104**. In other words, each option may provide different float responses for the agricultural harvesting header **104**. If the user selects Option1 **1208**, the controller **906** identifies that the user desires a very firm float response of the agricultural harvesting header **104** and identifies the performance characteristics associated therewith (such as desired fluid pressure thresholds for the actuators **902**, **1008**, **1016**). The very firm Option1 **1208** may have relatively low pressure value thresholds associated therewith as part of the performance characteristics for Option1 **1208**. The controller **906** may then utilize the valve assembly **1022** and the sensor assembly **1204** to independently adjust the fluid pressure provided to each of the actuators **902**, **1008**, **1016** until the current fluid pressure identified by the controller **906** for each actuator **902**, **1008**, **1016** is within the pressure thresholds of Option1 **1208**. The controller **906** may then utilize the valve assembly **1022** and sensor assembly **1204** to maintain the pressure values within the pressure threshold values of the performance characteristics for that option.

Alternatively, if the user selects Option5 **1216**, the controller **906** identifies that the user desires a very soft float response of the agricultural harvesting header **104** and identifies the performance characteristics associated therewith (such as desired fluid pressure thresholds for the actuators **902**, **1008**, **1016**). The very soft Option5 **1216** may have relatively high pressure value thresholds (compared to Option1 **1208**) associated therewith as part of the performance characteristics for Option5 **1216**. The controller **906** may then utilize the valve assembly **1022** and the sensor assembly **1204** to adjust the fluid pressure provided to the actuators **902**, **1008**, **1016** until the current fluid pressure identified by the controller is within the pressure thresholds of Option5 **1216**. The controller **906** may then utilize the valve assembly **1022** and sensor assembly **1204** to maintain the pressure values within the pressure threshold values of the performance characteristics for that option.

In another embodiment, the options may correspond with desired cutting heights. In this example, Option1 **1208** may correspond with performance characteristics that allow a very tall cutting height. When the controller **906** identifies Option1 **1208** is selected, the controller **906** may utilize the sensor assembly **1204** to identify the position of the corresponding components **140**, **300**, **1002**, **1004** relative to one another. Further, the controller **906** may have stored therein as the performance characteristics for Option1 **1208** position

sensor values that correspond with the a very tall cutting height. The controller 906 may then monitor the sensor assembly 1204 and manipulate the valve assembly 1022 to alter the actuators 902, 1008, 1016 until the sensor value readings of the sensor assembly 1204 are within the position thresholds for Option1, 1208. A similar methodology can be implemented for any number of cutting heights for the remaining options.

As discussed herein, the user may select one option from the user interface 1206 and the controller 906 may adjust all of the actuators of the agricultural harvesting head 104 substantially simultaneously. That is to say, the controller 906 manipulates the center actuator 902 to adjust the center frame 140 while simultaneously adjusting the first and second actuators 1008, 1016 to alter the corresponding arm assemblies 1002, 1004 as well. Further, the performance characteristics stored in the controller 906 correspond with the desired final position/response characteristics of the center frame 130, first arm assembly 1002, and second arm assembly 1004 such that the performance characteristics account for the position of the adjacent component. For example, if the center frame 140 is raised from the underlying surface, the position and pressures of the first and second arm assemblies 1002, 1004 may be different than when the center frame 140 is traveling along the underlying surface. Accordingly, each of the options 1208, 1210, 1212, 1214, 1216 have performance characteristics associated therewith that consider the orientation of several other components of the agricultural harvesting head 104.

In the discussion above, various components and axes are described as extending in a fore-and-aft direction, or extending in a direction parallel to a direction of travel "V", or extending horizontally or longitudinally, or extending laterally. During normal operation, these components are expected to move. Typically, they can be pivoted or tilted with respect to each other, with respect to the ground, or with respect to the combine during normal operation and therefore are not precisely horizontal, vertical, longitudinally extending or laterally extending in all positions during operation.

Although the disclosure is illustrated as being used one type of combine, the present disclosure can be used on other combine types including conventional straw walker combines and hybrid combines having transverse threshing cylinders and rotary separators among other work machine types altogether.

While exemplary embodiments incorporating the principles of the present disclosure have been described herein, the present disclosure is not limited to such embodiments. Instead, this application is intended to cover any variations, uses, or adaptations of the disclosure using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this disclosure pertains.

The invention claimed is:

1. A system for a header assembly, comprising:

a center frame configured to pivot relative to an adapter frame about at least one center axis;

a center actuator coupled to the center frame to selectively provide a biasing force thereto;

a first arm assembly configured to pivot relative to the center frame about at least a first arm axis;

a first actuator coupled to the first arm assembly to selectively provide a biasing force thereto;

a controller in communication with the center actuator and the first actuator to selectively alter performance

characteristics of both of the center actuator and the first actuator substantially simultaneously, wherein the performance characteristics include a float response based on a float response threshold range of values for each of the center actuator and the first actuator or a cutting height based on a cutting height threshold range of values for each of the center actuator and the first actuator; and

a user interface in communication with the controller and having at least a first option to select a first performance characteristic including a first float response threshold range of values for each of the center actuator and the first actuator and a second option to select a second performance characteristic including a second float response threshold range of values for each of the center actuator and the first actuator;

wherein, the controller adjusts the first and second performance characteristics of both the center actuator and the first actuator substantially simultaneously when the user interface is transitioned between the first option and the second option.

2. The system of claim 1, further wherein the center actuator is a hydraulic actuator fluidly coupled to an accumulator, wherein the performance characteristic of the float response altered by the controller is the hydraulic pressure provided to the hydraulic actuator.

3. The system of claim 1, further wherein the first actuator is a first hydraulic actuator fluidly coupled to an accumulator, wherein the performance characteristic of the float response altered by the controller is the hydraulic pressure provided to the first hydraulic actuator.

4. The system of claim 1, further wherein the center actuator is a center hydraulic actuator and the first actuator is a first hydraulic actuator, wherein the performance characteristic of the float response altered by the controller includes hydraulic pressure provided to the center hydraulic actuator and the first hydraulic actuator.

5. The system of claim 4, further comprising a center valve fluidly coupled to the center hydraulic actuator and a first valve fluidly coupled to the first hydraulic actuator, wherein the controller communicates with both the center valve and the first valve to selectively provide hydraulic fluid to the corresponding hydraulic actuator at the hydraulic pressure identified by the performance characteristic.

6. The system of claim 4, further wherein the hydraulic pressure provided to the center hydraulic actuator is different from the hydraulic pressure provided to the first hydraulic actuator.

7. The system of claim 1, further wherein the user interface has a third option, a fourth option, and a fifth option, wherein each of the options corresponds with different performance characteristics identified respectively as a third, a fourth, and a fifth float response threshold range of values for each of the center actuator and the first actuator.

8. The system of claim 1, further comprising:

a second arm assembly configured to pivot relative to the center frame about at least a second arm axis;

a second actuator coupled to the second arm assembly to selectively provide a biasing force thereto;

wherein, the controller is in communication with the second actuator to selectively alter performance characteristics of the second actuator;

further wherein, the controller adjusts the performance characteristics of the second actuator substantially simultaneously with the adjusting of the first and second performance characteristics of both the center

21

actuator and the first actuator when the user interface is transitioned between the first option and the second option.

9. The system of claim 1, further wherein the center axis and the first arm axis are about ninety degrees offset from one another.

10. The system of claim 1, further comprising:  
 a first arm assembly sensor that identifies an arm position relative to the center frame; and  
 a center frame sensor that identifies a center frame position relative to the adapter frame.

11. The system of claim 10, further wherein the performance characteristics include cutting height threshold position ranges for the arm position and the center frame position and the controller repositions the first actuator and the center actuator to position the corresponding center frame and first arm assembly into the cutting height threshold position ranges.

12. A system for adjusting a header assembly of a combine, comprising:

- a center frame pivotally coupled to an adapter frame about at least one center axis;
  - a center actuator configured to reposition the center frame;
  - a first arm assembly configured to be pivotal relative to the center frame about at least a first arm axis;
  - a first actuator configured to reposition the first arm assembly;
  - a second arm assembly configured to be pivotal relative to the center frame about at least a second arm axis;
  - a second actuator configured to reposition the second arm assembly;
  - a controller in communication with the center actuator, the first actuator, and the second actuator to selectively alter performance characteristics, wherein the performance characteristics include a float response based on a float response threshold range of values for each of the center actuator, the first actuator, and the second actuator, or a cutting height based on a cutting height threshold range of values for each of the center actuator, first actuator, and second actuator; and
  - a user interface in communication with the controller and having at least a first option to select a performance characteristic based on a first float response threshold range of values for each of the center actuator, the first actuator, and the second actuator, or a first cutting height threshold range of values for each of the center actuator, the first actuator, and the second actuator, and a second option to select a performance characteristic based on a second float response threshold range of values for each of the center actuator, the first actuator, and the second actuator, and the second cutting height threshold range of values for each of the center actuator, the first actuator, and the second actuator;
- wherein, the controller adjusts the performance characteristics of at least one of the center actuator, the first actuator, and the second actuator when the user interface is transitioned between the first option and the second option.

13. The system of claim 12, further wherein each of the center actuator, the first actuator, and the second actuator are hydraulic actuators, wherein the performance characteristic of the float response altered by the controller is the hydraulic pressure provided to at least one of the center actuator, the first actuator, and the second actuator.

22

14. The system of claim 13, further comprising at least one accumulator fluidly coupled to at least one of the center actuator, the first actuator, and the second actuator.

15. The system of claim 13, further wherein the performance characteristics altered by the controller is the hydraulic pressure provided to each of the center actuator, the first actuator, and the second actuator.

16. The system of claim 13, further comprising valve assembly that selectively provides hydraulic fluid to each of the center actuator, the first actuator, and the second actuator from a hydraulic source, wherein the controller communicates with the valve assembly to selectively provide hydraulic fluid to each of the center actuator, the first actuator, and the second actuator at a hydraulic pressure identified by the performance characteristics associated with the selected option.

17. The system of claim 12, further wherein the first arm axis and the second arm axis are about ninety degrees offset from the center axis.

18. A method for adjusting a header assembly of a combine, comprising:

- providing a center frame pivotally coupled to an adapter frame about at least one center axis, an center actuator coupled to the center frame, a first arm assembly pivotally coupled to the center frame about at least a first arm axis, a first actuator coupled to the first arm assembly, a second arm assembly pivotally coupled to the center frame about at least a second arm axis, a second actuator coupled to the second arm assembly, a controller in communication with the center actuator, the first actuator, and the second actuator, a user interface, and a sensor assembly;
- providing, with the user interface, at least a first option and a second option that is selectable by a user;
- storing, in the controller, a first set of performance characteristic thresholds associated with the first option and a second set of performance characteristic thresholds associated with the second option;
- identifying, with the user interface, when the first option or the second option are selected;
- identifying current values for the center frame, first frame assembly, and second frame assembly with the sensor assembly and communicating the current values to the controller;
- comparing the current values with the performance characteristic thresholds associated with the selected first option or second option;
- altering a corresponding one or more of the center actuator, the first actuator, and the second actuator with the controller when the current values are not within the performance characteristics thresholds of the selected first or second option.

19. The method of claim 18, further wherein the center actuator, the first actuator, and the second actuator are hydraulic actuators and the first set of performance characteristic thresholds and the second set of performance characteristic thresholds are hydraulic pressure thresholds that correspond with each of the center actuator, the first actuator, and the second actuator.

20. The method of claim 18, further wherein the first and second set of performance characteristic thresholds are determined by the controller with reference to a float curve chart.