(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 1 March 2001 (01.03.2001)

PCT

(10) International Publication Number WO 01/13980 A1

IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,

RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,

KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,

(84) Designated States (regional): ARIPO patent (GH, GM,

CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,

(51) International Patent Classification⁷: A61M 16/04

(21) International Application Number: PCT/GB00/03045

(22) International Filing Date: 7 August 2000 (07.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 9920098.2 26 August 1999 (26.08.1999) GF

(71) Applicant (for all designated States except US): SMITHS INDUSTRIES PUBLIC LIMITED COMPANY [GB/GB]; 765 Finchley Road, London NW11 8DS (GB).

11/2

Published:

With international search report.

UG, US, UZ, VN, YU, ZA, ZW.


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and

(75) Inventor/Applicant (for US only): COLLINS, Michael, Norman [GB/GB]; Hollydene, Canterbury road, Lyminge, Folkestone, Kent CT18 8HD (GB).

(74) Agent: FLINT, Jonathan, McNeill; 765 Finchley Road, London NW11 8DS (GB).

(54) Title: LARYNGEAL MASK AIRWAY



(57) Abstract: A laryngeal mask airway has a main tubular shaft (1) with a mask portion (5) attached at its patient end (3). The mask portion (5) comprises a mount (50) and a sealing cuff (60) attached to the mount. The interior of the mount (50) defines a large volume atrium (54) communicating with the bore of the shaft (1) at one end and with an opening (61) through the cuff (60) at its other end. The join between the shaft (1) and the mount (50) is located above the rear part (63) of the cuff (60). The height of the atrium (54) is between 2.5 and 3.5 the internal diameter of the shaft. The volume of the atrium (54) is such that the ratio of the internal diameter of the shaft cubed to the internal volume of the atrium is between 50 and 68.





1

LARYNGEAL MASK AIRWAY

This invention relates to apparatus in the form of a laryngeal mask airway including a tubular portion and a mask portion at its patient end having a sealing cuff of generally oval shape defining an opening within its centre and adapted to seal with patient tissue around the larnygeal inlet, the mask portion defining a recess extending from the opening to the patient end of the tubular portion.

Laryngeal mask airways are used to ventilate and to supply anaesthetic gas to a patient during surgery. Laryngeal mask airways differ from endotracheal tubes, which extend into the trachea and terminate beyond the vocal folds. By contrast, laryngeal mask airways have a tubular shaft opening into the centre of a generally elliptical mask or cuff, which is inflated to seal in the region of the hypopharnyx, at the top of the trachea. The cuff is inflated with air supplied along a small-bore inflation line communicating with the interior of the cuff. Laryngeal masks are described in, for example: US 5355879, US 5305743, US 5297547, US 5282464, GB 2267034, US 5249571, US 5241956, US 5303697, GB 2317830, GB 2249959, GB 2111394, EP 448878, US 4995388, GB 2205499, GB 2128561, GB 2298797, GB 2321854, GB 2334215, GB 2323289, GB 2323290, GB 2318735 and GB 2330312.

One problem with laryngeal masks is that there is a risk that the air passage along the mask may be blocked by the epiglottis during insertion. Attempts have been made to reduce this risk by means of bars extending across the opening to the mask but this has the disadvantage of making it more difficult to insert instruments along the airway.

It is an object of the present invention to provide alternative medico-surgical apparatus.

According to one aspect of the present invention there is provided apparatus of the above-specified kind, characterised in that the patient end of the tubular portion is located above and to the rear of the rear side of the opening such as to space it away from the epiglottis.

The patient end of the tubular portion is preferably located substantially midway across the width of the rear side of the sealing cuff. The tubular portion may be a separate tube bonded into a collar on the mask portion. The longitudinal centre line along the internal surface of the roof of the recess is preferably substantially straight. The height of the recess may be between 2.5 and 3.5 the internal diameter of the tubular portion. The ratio of the internal diameter of the tubular portion cubed to the volume of the recess is preferably between 50 and 68.

According to another aspect of the present invention there is provided a laryngeal mask airway including a tubular portion and a mask portion at its patient end having a sealing cuff of generally oval shape defining an opening within its centre and adapted to seal with patient tissue around the larnygeal inlet; the mask portion defining a recess extending from the opening to the patient end of the tubular portion, characterised in that the height of the recess is between 2.5 and 3.5 the internal diameter of the tubular portion.

The height of the recess is preferably between 2.96 and 3.27 the internal diameter of the tubular portion.

According to a further aspect of the present invention there is provided a laryngeal mask airway including a tubular portion and a mask portion at its patient end having a sealing cuff of generally oval shape defining an opening within its centre and adapted to seal with patient tissue around the larnygeal inlet, the mask portion defining a recess extending from the opening to the patient end of the tubular portion, characterised in that the ratio of the internal diameter of the tubular portion cubed to the volume of the recess is between 50 and 68.

Preferably, the ratio of the internal diameter of the tubular portion cubed to the internal volume of the recess is between 50 and 60.

A medico-surgical tube in the form of a laryngeal mask airway according to the present invention, will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1	is a perspective view of the airway;
Figure 2	is a sectional side elevation view of the airway;
Figure 3	is a transverse section across the airway along the line III-III of Figure 2 to an enlarged scale;
Figure 4	is a view of the airway from below; and
Figure 5	is a sectional side elevation view of an alternative airway.

With reference to Figures 1 to 4, the airway includes a curved tube or shaft 1 of a bendable plastics material having a channel 2 in the form of a groove extending along its length on its outside surface and on the inside of its curve. The shaft 1 is preferably made by extrusion and may be reinforced by means of an embedded helical element, such as of metal or plastics. At its patient end 3, the shaft 1 is attached to a mask portion 5.

The mask portion 5 comprises a mount member 50 of a relatively stiff but compliant plastics material and an inflatable cuff 60 attached to the mount member. The mount member 50 is hollow and of generally shoe shape, having a tubular extension or collar 51 at its upper or posterior side located at the rear, left-hand or machine end of the mount. The patient end 3 of the shaft 1 is bonded into one end of the collar 51. The other end of the collar 51 opens into a central recess or atrium 54 within the mount 50. The internal, anterior surface of the roof 40 of the atrium 54 is arched transversely but is substantially straight, or is slightly concave, along its longitudinal centre line. The roof 40 is uninterrupted by any surface projections or formations that would impede free movement of the epiglottis over the roof. Viewed in plan, the mount 50 is oval with its lower or anterior side 53 lying on a flat plane extending at an angle of about 30° to the axis of the patient end 3 of the collar 51. A channel

55 in the form of a groove extends along the inside of the mount member 50 in line with the groove 2 along the shaft 1 and this opens through a hole 56 into the cuff 60.

The cuff 60 may be of any conventional form, such as described in GB 2323291 or GB 2321854. The cuff 60 is only shown schematically in the drawings but is of annular, elliptical shape, being attached to the forward end surface 53 of the mount member 50 and having a central opening 61 into the atrium 54. The cuff 60 is of a thin, flexible plastics material so that it can be deflated to a low profile for insertion and can be inflated to seal with surrounding tissue when correctly positioned.

The roof 40 of the mount 50 is relatively high compared with previous laryngeal mask airways, especially its central region A and its rear region B adjacent the tubular portion or collar 51. The height H of the atrium ranges from about 2.5 to 3.5 times the internal diameter ID of the shaft 1, or its equivalent where the shaft does not have a circular section - preferably the ratio H/ID is between 2.96 and 3.27. In this way, the atrium 54 has a relatively large volume compared with previous airways. In particular, the ratio of ID³/Volume is in the range 50 to 68 where Volume is the volume of the atrium 54 defined by a plane of the lower, sealing surface of the cuff 61 when inflated, and a vertical, transverse surface through the highest point of the rear region B. For a typical tube having an internal diameter of 8.5mm, the ratio H/ID might be 3.06 and the ratio of ID³/Volume might be 61.82.

The smallest part of the atrium 54, where the patient end of the collar 51 opens into the atrium, is the part most likely to be blocked by the epiglottis during insertion. The collar 51 positions the patient end 3 of the shaft 1 to the rear of the rear part 62 of the opening 61 and, more particularly, positions it directly above the rear part 63 of the cuff 60 so that it is located as far away as possible from the epiglottis, thereby minimizing the risk of blockage. The large volume of the atrium 54 also ensures that the epiglottis can move freely within the mask, should it enter, so that there is less risk of it catching on the interior of the mask. The present construction avoids the need for any obstruction across the opening of the mask in order to prevent blockage by the epiglottis.

In general, the patient end of the tubular portion 1 is located to the rear of the rear side 62 of the opening 61, that is, on the side towards the machine end of the airway, and is preferably located approximately midway across the width of the sealing cuff. Instead of the tube and mount being separate components, they could be provided by one integral moulded component, with the location where the tubular portion increases in internal diameter being regarded as the patient end of the tubular portion.

The airway also includes an inflation line 70 in the form of a small-diameter flexible plastics tube extending along the groove 2 in the shaft 1, with the patient end of the tube extending along the groove 55 in the mount member 50 and projecting through the hole 56 into the cuff 60. The cuff 60 is sealed with the outside of the inflation line 70 so that it opens into the interior of the cuff. The rear, machine end of the inflation line 70 is attached to a combined inflation indicator balloon and connector 71 of conventional kind. The groove 2 in section forms the major part of a circle, being open on the surface of the shaft through a slit so that the inflation line 70 is retained in the groove mechanically, although it is preferably also bonded into the groove close to the patient end of the shaft 1, such as by means of a solvent or adhesive. A number of lateral notches 20 are spaced from one another along the machine end of the groove 2. The size of the notches 20 is such as to allow the inflation line 70 to extend out of the groove 2 through a notch. The airway is supplied with the inflation line 70 extending out of the groove 2 through the notch 20 closest to the machine end of the shaft 1. If the user wishes to cut the shaft 1 shorter, at a location forwardly of where the inflation line 70 extends from the shaft, he simply pulls the inflation line away from the shaft so that it peels out of the groove 2 to the next notch 20, or to any other notch, thereby reducing the length of the inflation line attached with the shaft. In this way, the inflation line 70 is kept neatly with the shaft along most of the length of the shaft 1 but the shaft can be cut to any desired length. There are other ways in which the inflation line could be attached with the shaft, such as by means of a rupturable adhesive or other bond. It will be appreciated that this form of peelable attachment of a small-bore line could have applications in other tubes having a minor lumen and where it is desirable to be able to alter the length of the small-bore line attached with the main shaft, such as endotracheal tubes.

Securing the inflation line 70 to the shaft 1 along most of its length avoids any loose tube within the patient's mouth and ensures that the inflation indicator and connector 71 are readily accessible outside the mouth. Reliable assembly of the airway is facilitated by this arrangement compared with alternative arrangements employing an extruded small-bore lumen within the wall of the shaft since, in such arrangements, connection needs to be made to both ends of the bore. The present invention can also be used with shafts that are reinforced.

It is not essential that the channel in the mount member extend along its inner surface; it could extend along an outer surface, as shown in Figure 5, where similar features to those in Figures 1 to 4 are given the same numbers with the addition of a prime '. In this arrangement, the groove 55' extends along the outside of the mount member 50' so that the inflation line 70' can run along the groove and open into the cuff 60'.

7


PCT/GB00/03045


CLAIMS


- 1. A laryngeal mask airway including a tubular portion (1) and a mask portion (5) at its patient end (3) having a sealing cuff (60) of generally oval shape defining an opening (61) within its centre and adapted to seal with patient tissue around the larnygeal inlet, the mask portion (5) defining a recess (54) extending from the opening (61) to the patient end (3) of the tubular portion (1), characterised in that the patient end (3) of the tubular portion (1) is located above and to the rear of the rear side (62) of the opening (61) such as to space it away from the epiglottis.
- 2. An airway according to Claim 1, characterised in that the patient end (3) of the tubular portion (1) is located substantially midway across the width of the rear side (62) of the sealing cuff (60).
- 3. An airway according to Claim 1 or 2, characterised in that the tubular portion is a separate tube (1) bonded into a collar (51) on the mask portion (5).
- 4. An airway according to any one of the preceding claims, characterised in that the longitudinal centre line along the internal surface of the roof (40) of the recess (54) is substantially straight.
- 5. An airway according to any one of the preceding claims, characterised in that the height (H) of the recess (54) is between 2.5 and 3.5 the internal diameter of the tubular portion (1).
- 6. An airway according to any one of the preceding claims, characterised in that the ratio of the internal diameter of the tubular portion (1) cubed to the volume of the recess (54) is between 50 and 68.
- 7. A laryngeal mask airway including a tubular portion (1) and a mask portion (5) at its patient end (3) having a sealing cuff (60) of generally oval shape defining an opening (61) within its centre and adapted to seal with patient tissue around the larnygeal inlet,

- the mask portion (5) defining a recess (54) extending from the opening (61) to the patient end (3) of the tubular portion (1), characterised in that the height (H) of the recess (54) is between 2.5 and 3.5 the internal diameter of the tubular portion (1).
- 8. An airway according to Claim 7, characterised in that the height (H) of the recess (54) is between 2.96 and 3.27 the internal diameter of the tubular portion (1).
- 9. A laryngeal mask airway including a tubular portion (1) and a mask portion (5) at its patient end (3) having a sealing cuff (60) of generally oval shape defining an opening (61) within its centre and adapted to seal with patient tissue around the larnygeal inlet, the mask portion (5) defining a recess (54) extending from the opening (61) to the patient end (3) of the tubular portion (1), characterised in that the ratio of the internal diameter of the tubular portion (1) cubed to the volume of the recess (54) is between 50 and 68.
- 10. An airway according to Claim 9, characterised in that the ratio of the internal diameter of the tubular portion (1) cubed to the internal volume of the recess is between 50 and 60.

Fig.1.







INTERNATIONAL SEARCH REPORT

Interr nal Application No PCT/GB 00/03045

		PCT/GB 0	00/03045
CLASSIFIC PC 7	CATION OF SUBJECT MATTER A61M16/04	- ter	
	nternational Patent Classification (IPC) or to both national classification	tion and IPC	
FIELDS SI	EARCHED Imentation searched (classification system followed by classification	an evimbale)	
:PC 7	A61M		
	n searched other than minimum documentation to the extent that si		
	a base consulted during the international search (name of data bas	se and, where practical, search terms us	ed)
EPO-Int	ernal		
DOCUME!	NTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the rele	evant passages	Relevant to claim No.
X	GB 2 323 289 A (SMITHS INDUSTRIES 23 September 1998 (1998-09-23) cited in the application	PLC)	1-5,7,8
A	page 3, paragraph 2; figure 2		6,9,10
x	US RE35531 E (CALLAGHAN ERIC B E 17 June 1997 (1997-06-17)		1-4
A	column 2, line 17 - line 26; figu	ire 5	6,9,10
X	GB 2 321 854 A (SMITHS INDUSTRIES 12 August 1998 (1998-08-12) cited in the application page 3, last paragraph -page 4, p	7,8	
Α	1; figure 1		3,5,6,9, 10
		-/	
X Furth	er documents are listed in the continuation of box C.	χ Patent family members are lis	ted in annex.
"A" docume	regories of cited documents : nt defining the general state of the art which is not ered to be of particular relevance	"T" later document published after the or priority date and not in conflict v cited to understand the principle o invention	vith the application but
filing da "L" docume which is citation "O" docume other n "P" docume	nt which may throw doubts on priority claim(s) or is cited to establish the publication date of another in or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means ent published prior to the international filing date but	"X" document of particular relevance; the cannot be considered novel or car involve an inventive step when the "Y" document of particular relevance; the cannot be considered to involve an document is combined with one or ments, such combination being ob in the art.	not be considered to edocument is taken alone edocument is taken alone e claimed invention ninventive step when the more other such docu-vivious to a person skilled
	nan the priority date claimed actual completion of the international search	"&" document member of the same pat Date of mailing of the international	
3	November 2000	10/11/2000	
Name and r	nailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer	

1

European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo nl, Fax: (+31–70) 340–3016

Lakkis, A

INTERNATIONAL SEARCH REPORT

Intern 1al Application No PCT/GB 00/03045

		PC1/GB 00/03045
C.(Continua	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 935 971 A (SMITHS INDUSTRIES PLC) 18 August 1999 (1999-08-18) cited in the application paragraph '0010!; figures	7,8 3,5,6,9, 10
P,X P,A	WO 00 20062 A (BRAIN ARCHIBALD IAN JEREMY) 13 April 2000 (2000-04-13) page 13, line 9 - line 15; figure 5	1-5,7,8

1

INTERNATIONAL SEARCH REPORT

...ormation on patent family members

Intern: al Application No PCT/GB 00/03045

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
GB 2323289	Α	23-09-1998	AU JP	5644498 A 10263083 A	24-09-1998 06-10-1998
			US	6003514 A	21-12-1999
US RE35531	E	17-06-1997	US	5477851 A	26-12-1995
GB 2321854	 А	12-08-1998	AU	5208398 A	13-08-1998
			EΡ	0857492 A	12-08-1998
			JP	10216233 A	18-08-1998
			US	6021779 A	08-02-2000
			ZA	9800334 A	27-07-1998
EP 0935971	 А	18-08-1999	AU	1212099 A	02-09-1999
			GB	2334215 A	18-08-1999
WO 0020062	A	13-04-2000	AU	6113399 A	26-04-2000