



US006847519B2

(12) **United States Patent**
Arbisi et al.

(10) **Patent No.:** **US 6,847,519 B2**
(45) **Date of Patent:** **Jan. 25, 2005**

(54) **PHONE WITH AUTOMATIC LINKED QWERTY KEYBOARD**

(75) Inventors: **Tom Arbisi**, Ventura, CA (US);
Michael McKay, Calabasas, CA (US);
Rhys Newman, Woodland Hills, CA (US);
Nikolaj Bestle, Calabasas, CA (US)

(73) Assignee: **Nokia Corporation**, Espoo (FI)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 15 days.

(21) Appl. No.: **10/184,551**

(22) Filed: **Jun. 28, 2002**

(65) **Prior Publication Data**

US 2004/0223295 A1 Nov. 11, 2004

(51) **Int. Cl.**⁷ **G06F 1/16**

(52) **U.S. Cl.** **361/680; 361/686; 345/903**

(58) **Field of Search** **361/686, 679-681, 361/683; 345/903, 904**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,126,725 A * 6/1992 Yanagisawa
5,189,632 A * 2/1993 Paajanen et al. 364/705.05
6,047,196 A 4/2000 Mäkelä et al.

6,243,595 B1 6/2001 Lee et al.
6,370,362 B1 4/2002 Jansen et al.
6,480,372 B1 * 11/2002 Vong et al. 361/680
6,542,721 B2 4/2003 Boesen
2001/0027121 A1 10/2001 Boesen

FOREIGN PATENT DOCUMENTS

WO WO 01777786 A3 10/2001
WO WO 01777786 A2 10/2001
WO WO 03/021408 A2 3/2003

OTHER PUBLICATIONS

Lee et al. (US 2002/0186206 A1), "Computer With a Hidden Keyboard", Nov. 12, 2002.*
Hsieh et al. (US 2003/0048595 A1), "Collapsible Keyboard", May 13, 2003.*


* cited by examiner

Primary Examiner—Yean-Hsi Chang

(57) **ABSTRACT**

A portable device having a main unit and a keyboard unit. The main unit includes a display and the keyboard unit includes a full alphabet keyboard. Furthermore, the keyboard unit has a closed position and an open position. In the closed position a portion of the display is obstructed by the keyboard unit, and in the open position the display is unobstructed by the keyboard unit. The full alphabet keyboard is operable in both the closed position and the open position.

11 Claims, 4 Drawing Sheets






Fig.1




Fig.2




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 3D




Fig.4

1

PHONE WITH AUTOMATIC LINKED QWERTY KEYBOARD

FIELD OF THE INVENTION

The present invention relates generally to portable electronic devices, and more specifically to a portable electronic device with a full alphabet keyboard.

BACKGROUND

As society becomes increasingly mobile, there is an ever-growing demand for electronic devices that are more powerful and more portable. In general, technology has answered this demand with lighter and stronger materials, and miniaturized electronics. For example, modern cellular telephones are small enough to be carried in a shirt pocket and powerful enough to send and receive electronic mail.

One drawback, however, of creating smaller devices is the decreasing amount of surface area on which to locate a convenient user interface. From an ergonomic point of view, the smaller the human interface is on a portable device, the harder it is to operate. Moreover, as a portable device becomes more capable, a more complex interface for the device is typically needed. Thus, there is increasing difficulty in portable device design to achieve devices that are smaller and more powerful, yet convenient to use.

SUMMARY OF THE INVENTION

Accordingly, the present invention provides a highly portable device having a full alphabet keyboard and display. The full alphabet keyboard can be operated when the device is in a compact "closed" configuration and in an ergonomic opens configuration. By providing a full alphabet keyboard usable in both the open and closed positions, data entry is easier and faster.

Thus, one aspect of the invention is a portable device having a main unit and a keyboard unit. The main unit includes a display and the keyboard unit includes a full alphabet keyboard. Furthermore, the keyboard unit has a closed position and an open position. In the closed position, a portion of the display is obstructed by the keyboard unit. In the open position, the display is unobstructed by the keyboard unit. The full alphabet keyboard is operable in both the closed position and the open position.

Another aspect of the invention is a portable device having a main unit, a keyboard unit, and a kickstand linking the main unit and the keyboard unit. The main unit includes a display and the keyboard unit includes a full alphabet keyboard. The keyboard unit has a closed position and an open position, wherein in the closed position a portion of the display is obstructed by the keyboard unit and in the open position the display is unobstructed by the keyboard unit. The kickstand is configured to guide the keyboard unit as it moves between its open position and its closed position.

The foregoing and other features, utilities and advantages of the invention will be apparent from the following more particular description of various embodiments of the invention as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an exemplary portable device in an open position.

FIG. 2 shows the exemplary portable device in a closed position.

2

FIGS. 3A-3D illustrate the motion of the exemplary portable device as it moves from the closed position to the open position.

FIG. 4 shows another view of the exemplary portable device in the closed position.

DETAILED DESCRIPTION OF THE INVENTION

The invention is described in detail below with reference to FIGS. 1-4. When referring to the figures, like structures and elements shown throughout are indicated with like reference numerals.

FIG. 1 shows an exemplary portable device 102, as contemplated by the present invention, in an open position and FIG. 2 shows the device 102 in a closed position. As discussed in more detail below, the device 102 includes a full alphabet keyboard 104 and a display 106, and is beneficially configured such that the keyboard 104 and display 106 are operable in both the closed position and the open position. This arrangement greatly enhances the usability of the device 102 without sacrificing its mobility. Furthermore, the use of a single display and keyboard for both the closed position and open position helps decrease manufacturing costs and simplifies construction.

The device 102 includes a main unit 108 housing the display 106. It is contemplated that the display may include a touch-sensitive or pen-sensitive screen. Furthermore, the main unit 108 may contain other interface mechanisms, such as a speaker 112 and a microphone 114. In a particular embodiment of the invention, the main unit 108 includes a cellular communication system (not shown), such as a mobile phone. In another embodiment of the invention, the main unit 108 can contain a computer system (not shown), including a microprocessor, memory, a motherboard, and a power source. Implementations of these, and other embodiments of the invention, can be tailored by those skilled in the art to meet the specific needs of end users.

The keyboard unit 110 includes the full alphabet keyboard 104, and may additionally include a navigation pad 116, menu keys 118, and other input interfaces known to those skilled in the art. For example, the keyboard unit 110 may include a touch-sensitive surface or a joystick (not shown). As used herein, the term "full alphabet keyboard" refers to a keyboard containing individual input keys for the major characters or letters of a language. For example, a full alphabet keyboard for the English language includes individual input keys for the letters A through Z. The full alphabet keyboard may additionally include keys for inputting numbers (i.e., 0 through 9), commonly used symbols (i.e., \$, %, &, etc.), and function keys (i.e., a shift key). In a particular embodiment of the invention, the full alphabet keyboard layout is a Remington typewriter layout, popularly known as a "QWERTY" keyboard layout.

As shown in the figures, the keyboard unit 110 is movable from a closed position (see FIG. 2) to an open position (see FIG. 1), and vice-versa. In the closed position, the keyboard unit 110 lies on top of the main unit 108 and obstructs a portion of the display 106. In one embodiment of the invention, the keyboard unit 110 defines a display opening 120 which exposes a portion of the display 106 in the closed position, allowing limited readability of the display 106. In a particular embodiment of the invention, the display opening 120 is substantially curvilinear. The closed position therefore provides a highly compact arrangement which greatly enhances portability of the device 102, while still maintaining the convenience of an operative full alphabet

keyboard **104** for data input. Furthermore, the keyboard unit **110** helps protect the display **106** against damage and foreign particles in the closed position.

In the open position, the keyboard unit **110** is positioned away from the main unit **108** and the display **106** is unobstructed by the keyboard unit **110**. In this arrangement, the full alphabet keyboard **104** is usable for data input and the entire display **106** is readable, thus providing a more robust and ergonomic user interface. Therefore, the present invention beneficially provides a highly portable configuration of the device in the closed position, and a more ergonomic configuration in the open position. Furthermore, the full alphabet keyboard **104** is operable in both the open and closed positions of the keyboard unit **110**.

It is contemplated that the device **102** adjusts the manner in which information is presented on the display **106** according to whether the keyboard unit **110** is in the open position or the closed position. For example, when the keyboard unit **110** is in the open position, information may be displayed using the entire screen and messages are scrolled up and down. When the keyboard unit **110** is in the closed position, for example, information is displayed only on a few lines and messages are scrolled left and right in ticker-tape fashion.

The device **102** also includes a kickstand **122** having a left kickstand member **124** and a right kickstand member **126** (see FIG. 4) on opposite sides of the device. The kickstand **122** links the main unit **108** and the keyboard unit **110**, and guides the opening and closing motion of the keyboard unit **110**. Moreover, the kickstand **122** acts as a base, providing upright support and stability when the keyboard unit **110** is in the open position.

FIGS. 3A, 3B, 3C, and 3D show the device **102** moving from the closed position to the open position. As illustrated in the sequence, the keyboard unit **110** moves away from the main unit **108** as the device moves from the closed position to the open position. In addition, as the device moves from the closed position to the open position, the kickstand **112** rotates behind the main unit **108**. This action allows the kickstand **112** to support the device in an upright position by moving the device's center of gravity toward the keyboard unit **110**.

Referring back to FIG. 1 and FIG. 2, it is contemplated that the keyboard unit **110** is lockable in the closed position and that the kickstand **122** includes torsion springs **128** which bias the keyboard unit **110** to the open position. In this manner, the keyboard unit **110** is spring-loaded in the closed position. The device **102** is further configured with a release button **130** (see FIG. 4) which releases the keyboard unit **110** from the closed position when activated. Since the keyboard unit **110** is biased to the open position, the release button **130** causes the keyboard unit **110** to move to the open position when activated. Such an arrangement advantageously allows the device **102** to be opened using only one hand.

It is contemplated that the keyboard unit **110** and the main unit **108** may be electrically coupled in several ways. For example, the main unit **108** may include connectors (not shown) on its top and bottom, and the keyboard unit **110** may also include a back connector (not shown) that engages the top connector in the closed position and the bottom connector in the open position. In another embodiment of the invention, the device **102** may include flexible wiring (not shown) electrically coupling the main unit **108** and the keyboard unit **110**. The wiring may be positioned within the kickstand **122** or behind the keyboard unit **110**.

The foregoing description of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed, and other modifications and varia-

tions may be possible in light of the above teachings. Thus, the embodiments disclosed were chosen and described in order to best explain the principles of the invention and its practical application to thereby enable others skilled in the art to best utilize the invention in various embodiments and various modifications as are suited to the particular use contemplated. It is intended that the appended claims be construed to include other alternative embodiments of the invention except insofar as limited by the prior art.

What is claimed is:

1. A portable device, the portable device comprising:
a main unit including a display; and

a keyboard unit including a keyboard, the keyboard unit adjustably linked so as to be adjustable between a closed position and an open position relative to the main unit, wherein the keyboard is operable when the keyboard unit is in either the closed position or the open position;

wherein the keyboard unit includes a keyboard unit connector and the main unit includes a first connector and a second connector such that the keyboard unit connector and the first connector electrically engage when the keyboard unit is in the closed position, and the keyboard unit connector and the second connector electrically engage when the keyboard unit is in the open position.

2. A portable device, the portable device comprising:
a main unit including a display;

a keyboard unit including a keyboard, the keyboard unit adjustably linked so as to be adjustable between a closed position and an open position relative to the main unit, wherein the keyboard is operable when the keyboard unit is in either the closed position or the open position; and

a linking member for adjustably linking the main unit and the keyboard unit, wherein the linking member extends beyond the main unit so as to form a support for the portable device when the keyboard unit is in the open position.

3. The portable device of claim 2, wherein the keyboard unit is biased to the open position.

4. The portable device of claim 3, further comprising a release means configured to release the keyboard unit from the closed position.

5. The portable device of claim 2, wherein the linking member includes a first member and a second member, the first member and the second member being disposed on substantially opposite sides of the portable device.

6. The portable device of claim 2, further comprising at least one spring for biasing the keyboard unit to the open position.

7. The portable device of claim 2, wherein the linking member includes at least one conductor for electrically coupling the main unit to the keyboard unit.

8. The portable device of claim 2, wherein the keyboard unit defines a display opening for exposing the unobstructed portion of the display when the keyboard unit is in the closed position.

9. The portable device of claim 8, wherein the display is operable to present visual information on the unobstructed portion of the display when the keyboard unit is in the closed position.

10. The portable device of claim 2, wherein the portable device is a mobile telephone for communicating via a cellular communication system.

11. The portable device of claim 2, wherein the portable device is a node operable within a computer network.