




(22) Date de dépôt/Filing Date: 2002/02/20
(41) Mise à la disp. pub./Open to Public Insp.: 2002/09/07
(30) Priorité/Priority: 2001/03/07 (A 357/2001) AT

(51) Cl.Int.⁷/Int.Cl.⁷ B61B 3/00, B61B 7/00
(71) Demandeur/Applicant:
INNOVA PATENT GMBH, AT
(72) Inventeur/Inventor:
ALBRICH, REINHARD, AT
(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : INSTALLATION DE TRANSPORT DE PERSONNES D'UNE STATION PLUS ELEVEE A UNE STATION MOINS ELEVEE
(54) Title: INSTALLATION FOR CARRYING PERSONS FROM A HIGHER STATION TOWARDS A LOWER STATION



(57) Abrégé/Abstract:

Persons can be carried downhill from a mountain station to a valley station. A guide rail is fastened on a supporting cable at a distance above the ground. The guide rail is formed of a multiplicity of sub-rails and carriages with a chair, a cabin, or the like can be displaced along the rail. The sub-rails are connected to one another such that they can be displaced in the longitudinal direction of the guide rail.

Abstract of the Disclosure:

Persons can be carried downhill from a mountain station to a valley station. A guide rail is fastened on a supporting cable at a distance above the ground. The guide rail is formed of a multiplicity of sub-rails and carriages with a chair, a cabin, or the like can be displaced along the rail. The sub-rails are connected to one another such that they can be displaced in the longitudinal direction of the guide rail.

WRA-33199

INSTALLATION FOR CARRYING PERSONS FROM
A HIGHER STATION TOWARDS A LOWER STATION

5

Background of the Invention:

Field of the Invention:

The present invention relates to an installation for carrying individuals down from a higher station (a mountain station) towards a lower station (a valley station). The installation has a guide rail which is fastened on a supporting cable at a distance above the ground. The guide rail comprises a multiplicity of sub-rails. Carriages with a chair, a cabin, or the like can be displaced along the guide rail.

15

A system of that type is described in my earlier specification application No. 09/488,741, published as European application ^{US} EP 1 026 061 A2. There, the guide rail comprises a multiplicity of sub-rails which are connected rigidly to one another and are fastened on a supporting cable by means of brackets. Since, in the case of a rigid guide rail, those locations at which the carriages are located are subjected to very high loading in each case, the sub-rails and the connections thereof have to be of very large dimensions. In addition, such rails are also subjected to high levels of

25

stressing, and resulting loading, on account of the heat expansion.

Summary of the Invention:

5 It is accordingly an object of the invention to provide an installation for the downhill transportation of persons from a higher station to a lower station, which overcomes the above-mentioned disadvantages of the heretofore-known devices and methods of this general type and which reduces the loading to
10 which the guide rail is subjected, for which reason the guide rail may be of smaller dimensions.

With the foregoing and other objects in view there is provided, in accordance with the invention, an installation
15 for downhill transportation of persons from a higher station to a lower station, comprising:

a guide rail extending between the higher station and the lower station and along which carriages are displaceable;

a supporting cable fastening the guide rail at a distance
20 above ground;

the guide rail being formed of a multiplicity of sub-rails connected to one another and displaceable relative to one another in a longitudinal direction of the guide rail.

In other words, the objects of the invention are achieved in that the sub-rails are connected to one another such that they can be displaced in the longitudinal direction of the guide rail.

5

The sub-rails, i.e., the rail sections, are preferably designed as tubular elements which are designed in their interior, at their ends, with in each case at least one crosspiece passing through the interior, one of the
10 crosspieces being provided with a slot and the crosspieces overlapping one another, it being the case that at least one screw which connects the crosspieces is provided between two sub-rails. According to a preferred embodiment, each sub-rail is designed, at one end, with a first crosspiece which is
15 provided with a slot, and is designed, at its other end, with two further crosspieces, on which a screw is fastened, the two further crosspieces butting against the first crosspiece on both sides and the screw passing through the slot.

Furthermore, the sub-rails are preferably fastened on the
20 supporting cable by means of supporting brackets, it being possible for these to be displaced in relation to the supporting cable.

In accordance with an additional feature of the invention, the
25 sub-rails are designed, on their outer sides, with at least one projecting bar along which guide rollers arranged on the

carriage run, and projecting from the sub-rails is at least
one further bar, which forms one of the two interacting
elements of an electromagnetic braking arrangement. In this
case, the at least one guide bar and the at least one braking
5 bar may project more or less diametrically from the sub-rails.

Other features which are considered as characteristic for the
invention are set forth in the appended claims.

10 Although the invention is illustrated and described herein as
embodied in an installation for carrying individuals down from
a mountain station into a valley station, it is nevertheless
not intended to be limited to the details shown, since various
modifications and structural changes may be made therein
15 without departing from the spirit of the invention and within
the scope and range of equivalents of the claims.

The construction and method of operation of the invention,
however, together with additional objects and advantages
20 thereof will be best understood from the following description
of specific embodiments when read in connection with the
accompanying drawings.

Brief Description of the Drawings:

25 Fig. 1 is a schematic plan view of an installation according
to the invention;

Fig. 2 is a partial side view illustrating the connection of two subrails in a first operating position;

5 Fig. 2a is a section taken along the line A-A in Fig. 2, illustrating the connection of the sub-rails in the first operating position;

Fig. 3 is a partial side view illustrating the connection of
10 the two sub-rails in a second operating position;

Fig. 3a is a section taken along the line B-B in Fig. 3, illustrating the connection of the sub-rails in the second operating position;

15

Fig. 4 is a cross-sectional view through two sub-rails in the region of their connection;

Fig. 5 is a side view of the end surfaces of two sub-rails;
20 and

Fig. 5a is a plan view onto the end surfaces of the two sub-rails.

Description of the Preferred Embodiments:

Referring now to the figures of the drawing in detail and first, particularly, to Fig. 1 thereof, there is shown an installation according to the invention with a higher station 1 (also referred to as a mountain station 1) and a lower station 1a (also referred to as a valley station 1a), between which a guide rail 2 extending from the mountain station 1 to the valley station 1a is located. The guide rail 2 has rectilinear segments 2a and curved segments 2b. Fastened on supports, columns and the like are supporting cables 3, on which the guide rail 2 is fastened at a distance above the ground. Carriages 4, on which chairs, suspension gear, cabins or the like are fastened, can be displaced along the guide rail 2 from the mountain station 1 towards the valley station 1a.

With reference to Figs. 2 and 2a, the guide rail 2 comprises a multiplicity of sub-rails 21, which are fastened on the cable 3 by means of supporting brackets 20. The sub-rails 21, which, by way of for example, are of hollow-cylindrical design, are designed in the interior, at one end, with a more or less diagonally running crosspiece 22, which projects beyond the surface of the sub-rails 21 and which is formed with an elongated hole or slot 22a. At their other end, they are designed with two diagonally running crosspieces 23 and 24, which likewise project beyond the end surface of the sub-rails

21 and on which there is fastened at least one bolt 25, which passes through the slot 22a. The sub-rails 21 are connected to one another by means of the crosspieces 22, 23 and 24 and the bolts 25, it being possible for the sub-rails to be displaced
5 in relation to one another by the length of the slot 22a. Since the supporting brackets 20 can be displaced in the longitudinal direction on the cable 3, this allows the sub-rails 21 to move in relation to one another in the longitudinal direction of the guide rail 2 in dependence on
10 the loading to which they are subjected.

Figs. 2 and 2a illustrate the position of the guide rail 2 in the non-loaded state. In this case, the ends of the sub-rails 21 butt against one another. In contrast, Figs. 3 and 3a
15 illustrate the sub-rails 21 in the position they assume when a carriage 4 is located in the region thereof. The resulting loading causes the guide rail 2 to bend, as a result of which the sub-rails 21 move apart from one another to the extent which is determined by the length of the slot 22a. Since the
20 tensile forces acting on the guide rail 2 are thus reduced to a considerable extent, it is possible for the sub-rails 21 and the crosspieces 22, 23 and 24 connecting the same to be of far smaller dimensions than if the sub-rails 21 were connected rigidly to one another. In addition, the guide rail 2 can
25 expand as a result of heat.

With reference to Fig. 4, supporting rollers 41 of the
carriages 4 run on the surface of the sub-rails 21.

Furthermore, the sub-rails 21 are designed, both on their top
side and on their underside, with radially projecting
5 continuations 56 which form abutment surfaces for guide
rollers 42 of the carriages 4. Also projecting from the bottom
continuation 56 are bars 57 which form constituent parts of an
electromagnetic braking assembly. Additional information with
regard to the electromagnetic braking assembly may be found in
10 my copending patent application [Attorney Docket No. WRA-
33127], the disclosure of which is herewith incorporated by
reference.

Figs. 5 and 5a, furthermore, illustrate the configuration of
15 the end surfaces of the sub-rails 21. As can be seen from Fig.
5, the continuations 56 are designed, in the longitudinal
direction of the sub-rails 21, with mating bevels 56a and 56b.
This ensures that the running surfaces for the guide rollers
42 are designed with a joint which runs obliquely in relation
20 to the running direction, as a result of which the necessary
smooth running of the guide rollers 42 is ensured.

Analogously, the lateral surfaces of the sub-rails 21 are also
designed, in the regions of the running surfaces for the
supporting rollers 41, with mating protrusions 27, which are
25 oriented in the running direction, and with mating recesses 28

assigned to said protrusions, as a result of which smooth rolling of the supporting rollers 41 is likewise ensured. The mutually assigned end surfaces of the sub-rails 21 are advantageously designed as annular, mating components 26 which
5 are welded onto the end sides of the sub-rails 21.

I Claim:

1. An installation for downhill transportation of persons from a higher station to a lower station, comprising:

a guide rail extending between the higher station and the lower station and along which carriages are displaceable;

a supporting cable fastening said guide rail at a distance above ground;

said guide rail being formed of a multiplicity of sub-rails connected to one another and displaceable relative to one another in a longitudinal direction of the guide rail.

2. The installation according to claim 1, wherein said sub-rails are tubular elements with ends and an interior, said ends are each formed with at least one crosspiece passing through said interior, one of said crosspieces is formed with an elongated hole and the crosspieces overlap one another, and wherein at least one screw connects said crosspieces between two respective said sub-rails.

3. The installation according to claim 2, wherein each said sub-rail has a first crosspiece at one end thereof, formed with an elongated hole, and two further crosspieces at another end thereof, said two further crosspieces butting against said

first crosspiece on both sides when two sub-rails are connected to one another and said screw passing through said elongated.

4. The installation according to claim 1, which comprises supporting brackets fastening said sub-rails on said supporting cable, said supporting brackets being displaceably attached to said supporting cable.

5. The installation according to claim 1, wherein said sub-rails are formed, on an outer side thereof, with at least one projecting bar for running support of guide rollers arranged on the carriage.

6. The installation according to claim 5, which comprises at least one further bar projecting from said sub-rails, said further bar forming one of two interacting elements of an electromagnetic braking assembly.

7. The installation according to claim 6, wherein said at least one guide bar and said at least one braking bar project substantially diametrically from said sub-rails.

8. The installation according to claim 1, wherein said sub-rails are formed with running surfaces for supporting running rollers and for guide rollers of the carriages running along

said guide rail in a running direction, and wherein said joints run in a step-like manner relative to the running direction.

9. The installation according to claim 1, wherein said sub-rails are formed with running surfaces for supporting running rollers and for guide rollers of the carriages running along said guide rail in a running direction, and wherein said joints are oriented obliquely relative to the running direction.

10. The installation according to claim 1, wherein said sub-rails have mutually assigned end surfaces formed with mating components welded onto respective ends of said sub-rails.

**Ridout & Maybee LLP
Suite 2400
One Queen Street East
Toronto, Canada M5C 3B1
Patent Agents of the Applicant**

FIG.1




FIG.2




FIG.2a




FIG.3




FIG.3a




FIG.4




FIG.5




FIG.5a

