




|                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>(22) Date de dépôt/Filing Date: 2014/09/23</p> <p>(41) Mise à la disp. pub./Open to Public Insp.: 2015/03/24</p> <p>(45) Date de délivrance/Issue Date: 2018/05/01</p> <p>(30) Priorité/Priority: 2013/09/24 (US14/034,673)</p> | <p>(51) Cl.Int./Int.Cl. <i>H01M 10/44</i> (2006.01),<br/><i>H01M 10/48</i> (2006.01)</p> <p>(72) Inventeurs/Inventors:<br/>SENGUPTA, SURAJIT, CA;<br/>FENG, YU WILLIAM, CA;<br/>BRUBACHER, JONATHAN QUINN, CA;<br/>PATINO, JOSEPH, US</p> <p>(73) Propriétaire/Owner:<br/>BLACKBERRY LIMITED, CA</p> <p>(74) Agent: RIDOUT &amp; MAYBEE LLP</p> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

(54) Titre : SYSTEME ET PROCEDE POUR REDUIRE LE GONFLEMENT DE GAZ A CHARGE ET TEMPERATURE ELEVEES D'UNE PILE D'UN APPAREIL ELECTRONIQUE PORTATIF

(54) Title: SYSTEM AND METHOD OF MITIGATING HIGH-TEMPERATURE, HIGH-CHARGE GAS SWELLING OF BATTERY OF PORTABLE ELECTRONIC DEVICE



(57) Abrégé/Abstract:

A method mitigates or even prevents gas swelling of a battery of a portable electronic device at high temperatures and states of charge of the battery. The method comprises: receiving "temperature" and "state of charge" signals, which are functions of a temperature and state of charge of the battery, respectively; determining, as corresponding functions of the "temperature" and "state of charge" signals, whether the temperature is within an elevated operating-temperature range and the state of charge is within an elevated state-of-charge range; cycle-forming the battery a predetermined number of cycles; and terminating the "cycle-forming" operation of the battery when the pre-determined number of cycles is reached.

## ABSTRACT

A method mitigates or even prevents gas swelling of a battery of a portable electronic device at high temperatures and states of charge of the battery. The method comprises: receiving “temperature” and “state of charge” signals, which are functions of a temperature and state of charge of the battery, respectively; determining, as corresponding functions of the “temperature” and “state of charge” signals, whether the temperature is within an elevated operating-temperature range and the state of charge is within an elevated state-of-charge range; cycle-forming the battery a predetermined number of cycles; and terminating the “cycle-forming” operation of the battery when the pre-determined number of cycles is reached.

## **System and Method of Mitigating High-Temperature, High-Charge Gas Swelling of Battery of Portable Electronic Device**

### **BACKGROUND**

**[0001]** A user of a portable electronic device (PED) can often expose the device to high or elevated temperatures. For example, during a hot summer day, the user may leave the PED on a dashboard of a vehicle and leave the vehicle parked outside for an extended period of time. As such, the temperature inside the vehicle and, in turn, of the PED may be elevated due to a “greenhouse” or other effect.

### **BRIEF DESCRIPTION OF DRAWING**

**[0002]** For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawing and detailed description, wherein like reference numerals represent like parts.

**[0003]** FIG. 1 is a block diagram of a portable electronic device (PED) according to an embodiment;

**[0004]** FIG. 2 is a block diagram that includes a “cycle-forming” application of a battery or battery pack of the PED of FIG. 1;

**[0005]** FIG. 3 is a flow diagram that illustrates a method of cycle-forming the battery pack of the PED of FIG. 1 according to an embodiment;

**[0006]** FIG. 4 is a graph that illustrates a relationship between a number of “forming” cycles and percentage of gas swelling of the battery pack of the PED of FIG. 1 according to the embodiment of the method of FIG. 3, wherein the battery pack was stored at a predetermined high or elevated temperature for a predetermined amount of time and was at a predetermined voltage and state of charge of one-hundred percent;

**[0007]** FIG. 5 is a flow diagram that illustrates implementation by the PED of FIG. 1 of a “smart” charge/discharge” sequence to complete a “forming” process of the battery pack of the PED and mitigate or even prevent a possibility of gas swelling at high temperatures and state of charge of the battery pack;

**[0008]** FIG. 6 is a block diagram that includes an “active discharging” application of a battery pack of the PED of FIG. 1;

**[0009]** FIG. 7 is a flow diagram that illustrates a method of actively discharging the battery pack of the PED of FIG. 1 according to an embodiment; and

**[0010]** FIG. 8 is a graph that illustrates a relationship between a percentage of state of charge and percentage of swelling of a fresh (without “forming” cycles) battery pack of a PED according to the embodiment of the method of FIG. 6, wherein the battery pack was charged at various percentages of states of charge and stored at a predetermined elevated temperature for a predetermined amount of time.

## DETAILED DESCRIPTION

**[0011]** A lithium polymer battery is typically used as a non-removable battery or embedded battery of a PED. The battery consists of volatile material that, under certain conditions, allows for generation of gas within the battery, which results in gas swelling of the battery. Abnormal gas swelling is exacerbated by two primary factors—elevated temperature and amount of charge of the battery. In particular, when the PED is stored at conditions of high temperature (such as due to the “greenhouse” or other effect described above) and high state of charge of the PED, a rate of decomposition of chemicals within the battery is increased, thereby breaking down electrolytes thereof. In fact, it has been observed that the gas swelling increases exponentially with an increase in percentage of the state of charge. (Test data has shown that swelling within the same period of time is considerably higher when the battery is stored at a maximum state of charge than when the battery is stored at lower states of charge.) In this regard, it has been found that, when the PED is charged to a high state, gas within a fresh battery of this type and, thus, the battery itself can swell about thirty percent while the PED is stored at an elevated temperature of more than 50° C (thermistors disposed within the PED detect the temperature.)

**[0012]** A gap is designed in the PED to account for the solid swelling of the battery. In other words, a typical PED may incorporate some empty space within its body to accommodate expansion of the battery, but it may be undesirable for the battery to swell beyond the limits of the accommodation. Solid swelling results from normal use and cycling of the battery, and it is typically less than ten percent after more than fifty cycles of use. In known PEDs, the gap is designed to account for swelling of only about eight percent. Therefore, swelling of a high percentage is not being accounted for in the known PEDs. Build-up of swelling of the gas within a limited amount of space defined by the gap can be undesirable. More specifically, such build-up can lead to a broken pouch of the battery, or may adversely affect the body or structure of the PED and may contribute to one or more hazards.

**[0013]** It has been observed also that the gas swelling is more likely to occur during a period of time from when the battery is fresh to when it has undergone about five cycles of use or “forming” cycles (a single “forming” cycle being defined as a state of charge of the PED starting from a substantially “minimum” level, increasing to a substantially “maximum” level, and returning to the substantially “minimum” level). After this period, the risk of the gas swelling is diminished within a reasonable high-temperature range [at 110° C or 130° C (gas swelling occurs even if cycled)].

**[0014]** However, although a manufacturer of the PED can determine the state of charge of the PED, the manufacturer cannot control the temperature at

which the battery is stored. The battery is typically supplied to a manufacturer of the PED without the PED ever having undergone any “forming” cycles. And, the manufacturer has no control over use of the PED by the user and cannot urge or require the user to use the PED only at or about room temperature for the first few cycles. Consequently, the gas swelling is especially possible during these first few cycles, which raises the risk of an undesirable degree of swelling.

**[0015]** Described below are systems and methods by which gas swelling can be controlled or reduced, especially swelling that may be related to high temperatures and high states of charge of the battery.

**[0016]** It should be understood at the outset that although illustrative implementations of at least one embodiment of the present disclosure are provided below, the disclosed systems and/or methods may be implemented using any number of techniques, whether currently known or in existence. The disclosure should in no way be limited to the illustrative implementations, drawing, and techniques illustrated below, including the exemplary designs and implementations illustrated and described herein.

**[0017]** Referring now to FIG. 1, a portable electronic device (PED) **10** according to an embodiment is generally indicated at **10**. The concepts described in further detail below may be applied with a variety of devices, and the concepts are not restricted to application with the illustrative PED **10**. The PED **10** includes data-communication capabilities and may communicate with other electronic

devices directly or through a wireless network. The PED **10** is based upon a computing environment and functionality of a handheld computer, such as a wireless personal digital assistant (PDA). It should be appreciated, however, that the PED **10** is not limited to a wireless PDA and other PEDs—such as (but limited to) cellular telephones, smart telephones, electronic messaging devices, and laptop computers—are possible.

**[0018]** The PED **10** includes several components, including a processor **14**, which controls overall operation of the PED **10**. Although depicted for simplicity as a single unit, the processor **14** can be embodied as a plurality of processors **14**, each processor **14** controlling (or participating in control of) at least one operation of the PED **10**. A communication sub-system **40** controls data and voice-communication functions—such as e-mail, PIN (Personal Identification Number) message, SMS (Short Message Service) message, and cellular-telephone functions. The communication sub-system **40** is in communication with a wireless network **12**, which may be a data-centric wireless network, a voice-centric wireless network, or a dual-mode wireless network.

**[0019]** In FIG. 1, the communication sub-system **40** is a dual-mode wireless network that supports both voice and data communications. The communication sub-system **40** is configured in accordance with the “Global System for Mobile Communication” (GSMC) and “General Packet Radio Services” (GPRS) standards. The communication sub-system **40** may be configured alternatively in accordance with “Enhanced Data GSM Environment” (EDGE) or “Universal Mobile

Telecommunications Service” (UMTS) standards. Other wireless networks may also be associated with the PED **10**, including “Code Division Multiple Access” (CDMA) or “CDMA2000” networks. Examples of data-centric networks include “WiFi 802.11,” “Mobitex™” and “DataTAC™” communication systems. Examples of voice-centric networks include “Personal Communication Systems (PCS)” networks like “GSM” and “Time Division Multiple Access (TDMA)” communication systems.

**[0020]** The wireless network **12** includes base stations (not shown) that provide a wireless link to the PED **10**. Each base station defines a cell that, in turn, defines a coverage area within which communications between the base station and PED **10** can be effected. It should be appreciated that the PED **10** is movable within the cell and can be moved to respective coverage areas defined by other cells. Data is delivered to the PED **10** via wireless transmission from the base station. Similarly, data is sent from the PED **10** via wireless transmission to the base station.

**[0021]** The communication sub-system **40** further includes a “short-range communications” function, which enables the device **10** to communicate directly with other devices and computer systems without use of the wireless network **12** through, for example, infrared or “Bluetooth™” technology.

**[0022]** Prior to the PED **10** being able to send and receive communication signals over the wireless network **12**, network registration or activation procedures must have been completed. To enable network communication, an “SIM

(Subscriber Identity Module)” card **24** is inserted into a card interface **26**. The “SIM” card (or “Removable User Identity Module” card) is used to identify a user of the mobile device, store personal-device settings, and enable access to network services (such as e-mail and voicemail) and is not bound to a particular PED **10**.

**[0023]** The processor **14** is also connected to a random-access memory (RAM) **16** and flash memory **18**. An operating system and a device software are typically stored in the flash memory **18** and executable by the processor **14**. Some components of the device software may, in turn, be stored in the RAM **16**. The PED **10** includes computer-executable programmed instructions for directing the PED **10** to implement various applications. Some examples of applications that may be stored on and executed by the PED **10** include electronic messaging, games, a calendar, an address book, and a music player. Software applications that control basic operation of the PED **10**, such as voice and data communication, are typically installed during manufacture of the PED **10**. For a PED **10** that does not include an “SIM” card **24**, user-identification information may be programmed into the flash memory **18**. The flash memory **18** may alternatively be a persistent storage, a read-only memory (ROM), or other non-volatile storage.

**[0024]** The processor **14** receives input from a keypad **38** and other various input devices **36**. The keypad **38** may be completely alphanumeric or of a “telephone” type. The other input devices **36** may replace or complement the keypad **38** to facilitate input and include devices such as single or multi-function buttons and a touch screen, mouse, trackball, capacitive touch sensor, or roller

wheel with dynamic button-pressing capability. The PED **10** of FIG. 1 is shown by way of example, and it should be appreciated that many different types, shapes, and input-device configurations of the PED **10** are possible.

**[0025]** The processor **14** outputs to various output devices, such as a display **20**. In an embodiment, the display **20** is an LCD screen **20**. A microphone **32** and speaker **22** are connected to the processor **14** for cellular-telephone functions. A data port **34** is connected to the processor **14** for enabling data communication between the PED **10** and another computing device. The data port **34** may include data lines for data transfer and a supply line for charging a rechargeable lithium-polymer battery, cell, or battery pack **30** of the PED **10**. The battery pack **30** or a component thereof may not be removed from the PED **10** and is, therefore, a non-removable battery or embedded battery. A power-management sub-system **28** may be electrically coupled to the battery pack **30** and provide an interface between an auxiliary charging device and the battery pack **30**. The power-management sub-system **28** may perform any of several functions pertaining to power management, including controlling recharging of the battery pack **30** or regulating power delivery to other components in the PED **10**. Some of these functions **28** are discussed below.

**[0026]** It should be appreciated that the battery pack **30** or a component thereof may be removed from the PED **10**. It should be appreciated also that the battery pack **30** may include a housing (not shown). The battery pack **30** stores energy chemically, but it should be appreciated also that such chemistry is not

necessarily limited to a particular type and includes that which is capable of high-temperature, high-charge gas swelling. Other types may include, for example, nickel-cadmium, nickel-metal-hydride, and silver- or zinc-based.

**[0027]** It should be appreciated also that the battery pack **30** may include any power pack that has at least one energy-storage element and is capable of high-temperature, high-charge gas swelling. It should be appreciated also that such power pack may include a housing for the energy-storage element. It should be appreciated also that the power pack may, in addition to or alternatively, include a fuel cell that uses hydrogen (from hydrides), methanol, ethanol, or butane as fuel.

**[0028]** The PED **10** is operable in “data communication” and “voice communication” modes. In the “data communication” mode, a received data signal representing information (such as a text message, an e-mail message, a media file to be transferred, or a webpage download) is processed by the communication sub-system **40** and input to the processor **14**. The processor **14** further processes the signal and renders images for display on the display screen **20**. Alternatively, the processed signals may be output to another computing device through the data port **34**. To transmit information in the “data communication” mode, the user of the PED **10** composes information for transmission (such as e-mail messages) using the keypad **38** and other input devices **36** in conjunction with the display screen **20**. The composed information is transmitted through the communication sub-system **40** over the wireless network **12** or via short-range communications.

Operation of the PED **10** in the “voice communication” mode is similar to that of the “data communication” mode except that the received signals are output to the speaker **22** or an auxiliary device (such as a headset or headphones) and signals for transmission are generated by the microphone **32**. The PED **10** may also include other voice sub-systems, such as a voice-message-recording sub-system. An audio jack **42** is provided for receiving an audio accessory, such as headphones, a headset, or amplified speakers or headphones. The audio jack **42** may also receive other accessories, such as a multi-media accessory including “Play,” “Pause,” “Stop,” and “Rewind” buttons or a “TV Out” accessory that allows for connection of the PED **10** to a television.

**[0029]** Components and sub-systems such as those shown in FIG. 1 may be housed, partly or completely, in a body **43** that may (for example) protect the components, give a desirable appearance, and give the PED **10** some structural integrity. Only a limited number of sub-systems of the PED **10** have been described. It should be appreciated that additional sub-systems corresponding to additional features of the PED **10** may also be connected to the processor **14**.

**[0030]** Referring to FIG. 2, the power-management sub-system **28**, which regulates and distributes power throughout the PED **10**, includes a charging interface **46** for communicating with the battery pack **30**. The power-management sub-system **28** may operate under direction of the processor **14**. In a typical implementation, the power-management sub-system **28** includes at least one integrated circuit. The power-management sub-system **28** may operate under the

control of the processor **14** when the processor **14** executes a “cycle-forming” application **48**, which is stored on the PED **10** (e.g., in the flash memory **18**) and executable by the processor **14**. (A single “forming” cycle is defined as a state of charge of the PED **10** starting from a substantially “minimum” level, increasing to a substantially “maximum” level, and returning to the substantially “minimum” level).

**[0031]** A temperature sensor **44** is coupled to the battery pack **30** to sense a temperature of the battery pack **30**. For simplicity, a single temperature sensor **44** is depicted in FIG. 2, but the concept may be adapted to a plurality of temperature sensors **44**. As used herein, “couple” refers to a physical relation of two components with each other such that a condition of one component affects function of the other. In the case of the temperature sensor **44** and battery pack **30**, the components may be physically coupled to each other in that they are proximate to one another such that the temperature sensor **44** can sense a temperature of the battery pack **30**. The temperature sensor **44** may be physically close to the battery pack **30**, abutting the battery pack **30**, or a component of the battery pack **30** (such as affixed to or embedded in a housing of the battery pack **30**). The temperature sensor **44** may be electrically coupled to one or more components. For example, the temperature sensor **44** may be electrically coupled to the processor **14** by supplying or providing a “temperature” indication in the form of an electrical signal (a “temperature” signal), which is received by the processor **14**.

**[0032]** As used herein, “electrical coupling” refers to a relation of two components with each other such that one component can communicate with the other by way of an electrical signal. The electrical signal may be an essentially continuous signal (such as a modulated voltage or current signal) or discrete signal (such as an “on/off” or “high/low” voltage or current signal). The electrical signal may also include delivery of power. Two components may be electrically coupled to one another even if they are not connected directly to one another and even if the electrical signal passes through at least one intermediary element. The temperature sensor **44** may be coupled electrically to the processor **14** without necessarily being physically close to or abutting the processor **14**.

**[0033]** The temperature sensor **44** senses a temperature of the battery pack **30** by receiving as input a sensed temperature of the battery pack **30** and issuing as output a “temperature” signal. The “temperature” signal is generally a function of the temperature of the battery pack **30**. The “temperature” signal may (but need not) be an electrical signal that changes as a function of the sensed temperature of the battery pack **30**. In some embodiments, there may be a range of “temperature” signals. In other embodiments, the “temperature” signal may be a simple logical signal that, for example, goes high when the sensed temperature is in a high or an elevated operating-temperature range and otherwise low. The “temperature” signal may also be represented as a signal that represents a numerical value. The “temperature” signal may then be received by the processor **14**, which determines whether the temperature is within the elevated operating-

temperature range as a function of the “temperature” signal. As discussed below, this determination may affect an “active discharging” application **72**, which may control the power-management sub-system **28**.

**[0034]** In one embodiment, the temperature sensor **44** is a thermistor. Other suitable temperature sensors **44** may alternatively be used (for example, a thermocouple or CMOS on-chip temperature sensor). The temperature sensor **44** may be deployed anywhere on, in, or proximate to the battery pack **30** (including, but not limited to, places in the battery pack **30** that tend to be hotter or cooler than other places during use or recharging of the PED **10**). In some embodiments, the temperature sensor **44** may be a component of the battery pack **30** such that removal of the battery pack **30** or a component thereof disengages the temperature sensor **44** from the PED **10**. In other embodiments, the temperature sensor **44** remains coupled to other components in the PED **10**. In other words, the temperature sensor **44** may be coupled to a non-removable component of the PED **10** (including, but not limited to, a non-removable component of the battery pack **30** such that removal of the battery pack **30** or a component thereof does not disengage the temperature sensor **44** from the PED **10**).

**[0035]** Cycle-forming of the battery pack **30** may be performed at normal operating temperatures and states of charge of the battery pack **30**. In an embodiment, the cycle-forming is performed during a first night of use of the PED **10** and in “room temperature” conditions. If “high temperature” and “high SOC” conditions are detected, then it is too late to perform the cycle-forming.

**[0036]** In contrast, the power-management sub-system **28** may actively discharge the battery pack **30** when the battery pack **30** is above the normal operating temperature and within an elevated operating-temperature range and the state of charge of the battery pack **30** is above the normal state of charge and within an elevated range. Generally speaking, active discharge is when charging is actively terminated. In a typical implementation, for example, a battery of the battery pack **30** may be charged substantially continuously until full charge is reached and actively discharged substantially continuously until zero charge is reached. At any point, charging may be stopped.

**[0037]** It should be appreciated that the power-management sub-system **28** may still increase or maintain an amount of charge when the battery pack **30** is above the normal operating temperature and within an elevated operating-temperature range and the state of charge of the battery pack **30** is above the normal state of charge and within an elevated range. It should be appreciated also that the battery pack **30** can be charged and actively discharged in any suitable manner involving charge current and charge-termination voltage of the battery pack **30**.

**[0038]** The processor **14** receives also a “state of charge” indication in the form of an electrical signal. The “state of charge” signal is generally a function of the state of charge of the battery pack **30** and may (but need not) be an electrical signal that changes as a function of the state of charge of the battery pack **30**. In some embodiments, there may be a range of “state of charge” signals. In other

embodiments, the “state of charge” signal may be a simple logical signal that, for example, goes high when the state of charge is in an elevated range and otherwise low. The “state of charge” signal may then be received by the processor **14**, which determines whether the state of charge is within the elevated range as a function of the “state of charge” signal. As used herein, being “within a state-of-charge range” includes, but is not limited to, these concepts. Being “within a state-of-charge range” generally refers to meeting or satisfying a criterion or criteria related to particular state of charge or range of state of charge, and being within an “elevated state-of-charge range” generally refers to being in a state-of-charge range that indicates or corresponds to an elevated state of charge. As discussed below, this determination may affect the “active discharging” application **72**, which may control the power-management sub-system **28**.

**[0039]** What constitutes an elevated operating temperature or state of charge may be defined differently for different circumstances. Stated another way, what constitutes an elevated operating temperature or state of charge for one battery pack **30** might not constitute an elevated operating temperature or state of charge for another battery pack **30**. An elevated operating-temperature range may be defined as 40° C and higher (104° F and higher), and an elevated state of charge may be defined as below, but approaching, eighty percent. A range of elevated temperatures and states of charge may also be defined that are extra-elevated. For example, an extra-elevated temperature range may be defined as 60° C and higher (140° F and higher), and an extra-elevated state of charge may

be defined as ninety to one-hundred percent. Control of active discharging may be changed if sensed temperatures and states of charge reach the extra-elevated temperature range and state of charge. Charging may be terminated entirely when sensed temperatures reach the extra-elevated temperature range.

**[0040]** In operation, the battery pack **30** is electrically coupled to an auxiliary charging device and receives power therefrom. Referring to FIGS. 2 and 3, an embodiment of the following method is executed while the battery pack **30** is being charged. Although described as being carried out by the processor **14**, the embodiment may be carried out by a plurality of processors **14** in the PED **10**. The embodiment includes, at steps **50**, **52**, the processor **14** receiving a “temperature” signal as a function of the temperature of the battery pack **30** and a “state of charge” signal as a function of the state of charge of the battery pack **30**. At step **58**, the processor **14** cycle-forms the battery pack **30** a predetermined number of cycles. The number of cycles is predetermined in the sense that it is settled upon, determined, constrained or otherwise made reasonably definite, expressly or impliedly, at some time before the cycle-forming is carried out. At step **60**, the processor **14** terminates the “cycle-forming” operation of the battery pack **30** when the pre-determined number of cycle-forms is reached. The processor **14** may control the power-management sub-system **28** to terminate the “cycle-forming” operation.

**[0041]** The embodiment of FIGS. 2 and 3 may be embodied as computer-readable instructions, such as instructions included in the “cycle-forming”

application **48**. The “cycle-forming” application may be stored in the flash memory **18** or another computer-readable medium of the PED **10** and is executable by the processor **14**. The “cycle-forming” application **48** may control the power-management sub-system **28** to carry out the operations illustrated in FIGS. 2 and 3.

**[0042]** In an embodiment, the predetermined number of cycles is between about one and about four “0.7C Charge” and “1C Discharge.” (The “C” rate is a theoretical amount of current that the battery pack **30** can deliver to discharge one-hundred percent within one hour. In general, the maximum charging current may not be able to reach 1C because it is limited by the auxiliary charging device. A typical auxiliary charging device imposes a 700 mA maximum on the charging current. However, different auxiliary charging devices may impose higher or lower limits). Also in the embodiment, the elevated operating-temperature range is about 80° C to 90°C, and the elevated range of the state of charge is about ninety percent to about one-hundred percent.

**[0043]** In FIG. 4, a graph shows a relationship between the number of “forming” cycles and percentage of swelling of the battery pack **30** of the PED **10**. In this case, the battery pack **30** was stored at 85° C for four hours, was at 4.35 V and a state of charge of one-hundred percent, and underwent four “0.7C Charge” and “1C Discharge” “forming” cycles. From the figure, it is observed that the battery pack **30** showed a decrease in the percentage of gas swelling over the number of “forming” cycles. More specifically, it is observed that gas swelling

below about five percent can be obtained if the battery pack **30** is cycle-formed at least twice.

**[0044]** Furthermore and as shown in FIG. 5, in another embodiment of the method of FIG. 3, the PED **10** can implement a “smart” charge/discharge” sequence to complete the “forming” process of the battery pack **30** and mitigate or even prevent a possibility of gas swelling at high temperatures and state of charge. More specifically, at step **62**, the method is performed on a first “charge” sequence of the battery pack **30** (e.g. during a first night of use of the PED **10** by the user) and/or when the battery pack **30** has not been used for an extended period of time (e.g., a few days, weeks, months, etc.). At step **64**, the PED **10** advises the user of the PED **10** to electrically couple the battery pack **30** to the auxiliary charging device such that the battery pack **10** is receiving power therefrom. At step **66**, the user inputs into the PED **10** a period of time (e.g., number of hours of sleep) for charging and discharging of the battery. At step **68**, the PED **10** charges and discharges the battery pack **30** as many cycles as possible during that time period. At step **70**, the PED **10** targets to have the battery pack **30** fully charged upon termination of the time period (e.g., the user awakening from the sleep).

**[0045]** It should be appreciated that the battery pack **30** can be stored at any suitable elevated temperature for any suitable period of time, at any suitable voltage and elevated state of charge, and undergo any suitable number of “forming” cycles.

**[0046]** Referring now to FIGS. 6 and 7, another embodiment of the method is executed also while the battery pack **30** is being charged. Again, although described as being carried out by the processor **14**, the embodiment may be carried out by a plurality of processors **14** in the PED **10**. The embodiment includes, at steps **50**, **52**, the processor **14** receiving a “temperature” signal as a function of the temperature of the battery pack **30** and a “state of charge” signal as a function of the state of charge of the battery pack **30**. At steps **54**, **56**, the processor **14**, which executes the “active discharging” application **72** and may control the power-management sub-system **28**, determines, as corresponding functions of the “temperature” and “state of charge” signals, whether the temperature is within an elevated operating-temperature range and the state of charge is within an elevated range. At step **74**, the processor **14** actively discharges the battery pack **30** to a predetermined amount of charge in response to the temperature being within the elevated operating-temperature range and the state of charge being within the elevated range. At step **76**, the processor **14** terminates the “active discharging” operation of the battery pack **30** when the predetermined amount of charge is reached. The processor **14** may control the power-management sub-system **28** to terminate the “active discharging” operation.

**[0047]** In the embodiment, the active discharge is carried out by the PED **10** running an application or a task on the processor **14** so that the state of charge of the battery pack **30** is maintained at or below a certain level. Some examples of such application that may be carried out by the processor **14** include electronic

messaging, games, a calendar, an address book, and a music player. It should be appreciated, however, that the application can be any suitable application. It should be appreciated also that the active discharge can be carried out in any suitable manner.

**[0048]** Similar to the embodiment of FIGS. 2 and 3, the embodiment of FIGS. 6 and 7 may be embodied as computer-readable instructions. In an embodiment, the elevated operating-temperature range is about 80° C to 90°C.

**[0049]** In FIG. 8, a graph shows a relationship between a percentage of state of charge and percentage of swelling of a fresh (without “forming” cycles) battery pack **30** of the PED **10**. In this case, the battery pack **30** was charged at various percentages of states of charge and stored at 85° C for four hours. From the figure, it is observed that the gas swelling increases exponentially with an increase in the percentage of the state of charge. More specifically, it is observed that the battery pack **30** should be kept charged at about seventy percent or below to avoid risk of the gas swelling. Generally, mitigation or even prevention of swelling of this type is required only when the battery pack **30** is fresh to its having undergone about five “forming” cycles. After then, as discussed above, the risk of the gas swelling is diminished at a reasonable high-temperature range.

**[0050]** It should be appreciated that the battery pack **30** can be charged at any suitable various percentages of states of charge, stored at any suitable elevated temperature for any suitable period of time, and undergo any suitable number of “forming” cycles.

**[0051]** The embodiments account for a high percentage of gas swelling of the battery pack **30** in the PED **10**. More specifically, the embodiments mitigate or even prevent such swelling at high temperatures and high states of charge of the battery pack **30** [and not merely reduce the swelling after the fact (i.e., after the swelling is detected)].

**[0052]** While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods may be embodied in many other specific forms without departing from the scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details given herein. For example, the various elements or components may be combined or integrated with another system, or certain features may be omitted or not implemented.

**[0053]** Also, techniques, systems, sub-systems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating with each other through some interface, device, or intermediate component, whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the scope disclosed herein.

## CLAIMS

What is claimed is:

1. A method of mitigating gas swelling of a battery of a portable electronic device comprising:

receiving a temperature signal that is a function of a temperature of the battery;

receiving a state of charge signal that is a function of a state of charge of the battery;

determining whether the temperature is within an elevated operating-temperature range;

determining whether the state of charge is within an elevated state-of-charge range in response to determining that the temperature is within the elevated operating-temperature range;

responsive to determining that the temperature is within the elevated operating-temperature range and the state of charge of the battery is within the elevated state-of-charge range, cycle forming the battery a predetermined number of cycles to mitigate gas swelling of the battery;

terminating the cycle-forming operation of the battery when the predetermined number of cycles is reached; and

maintaining the state of charge at or below a normal state of charge so long as the temperature is within or above the elevated operating-temperature range, the normal state of charge being about seventy percent and the elevated operating-temperature range being about 80° C to 90° C.

2. The method of claim 1, wherein the predetermined number of cycles is between one and about four 0.7C Charge and 1C Discharge.

3. The method of claim 1, wherein receiving the temperature signal includes receiving the temperature signal from a temperature sensor coupled to the battery.
4. The method of claim 1, further comprising preventing the battery from exceeding the normal state of charge when the temperature is within or above the elevated operating-temperature range.
5. The method of claim 1, further comprising:
  - responsive to determining that the battery's state of charge is within the elevated state of charge range, automatically terminating charging the battery if the battery's temperature exceeds 80° C, wherein the elevated state-of-charge range is ninety percent to one-hundred percent; and
  - maintaining the battery at or below the normal state of charge so long as the temperature is at or above 80° C.
6. The method of claim 1, wherein the battery is a lithium-polymer battery, the lithium-polymer battery being one of a removable battery or a non-removable battery embedded in the portable electronic device.
7. The method of claim 1, wherein a voltage of the battery is about 4.35 V.
8. The method of claim 1, wherein the method is performed at least one of on a first charge sequence of the battery and when the battery has not been used for an extended period of time lasting at least three consecutive days, a user of the personal electronic device is advised to electrically couple the battery to an auxiliary charging device such that the battery is receiving power from the auxiliary charging device, the user inputs a desired period of time for cycle-forming of the battery, the battery is charged and discharged as many cycles as possible during the time period, and the battery is targeted to be fully charged upon termination of the time period.
9. The method of claim 8, wherein the first charge sequence of the battery substantially coincides with a first night of use of the personal electronic device by

the user, the desired time period substantially coincides with a number of hours of sleep by the user through the first night, and the termination of the time period substantially coincides with awakening of the user from the sleep.

10. The method of claim 8, wherein each cycle of cycle-forming the battery comprises charging the battery:

starting from a substantially minimum state of charge;

increasing to a substantially maximum state of charge; and

returning to the substantially minimum state of charge.

11. The method of claim 1, further comprising, when five or less cycle-forming operations have been performed on the battery since being installed on the portable electronic device, preventing the battery's state of charge from exceeding 70% when the battery's temperature exceeds 50° C.

12. A portable electronic device comprising:

a processor electrically coupled to a temperature sensor;

a battery electrically coupled to the processor and temperature sensor; and

a power-management sub-system controlled by the processor,

wherein, to mitigate gas swelling of the battery, the processor:

receives a temperature signal that is a function of a temperature of the battery and a state of charge signal that is a function of a state of charge of the battery;

determines whether the temperature is within an elevated operating-temperature range and whether the state of charge is within an elevated state-of-charge range;

controls the power-management sub-system to cycle-form the battery a predetermined number of cycles in response to determining that the temperature is within the elevated operating-temperature range and the state of charge is within the elevated state-of-charge range;



terminates the cycle-forming operation of the battery when the predetermined number of cycles is reached; and

maintains the state of charge at or below a normal state of charge so long as the temperature is within or above the elevated operating-temperature range, the normal state of charge being about seventy percent and the elevated operating-temperature range being about 80° C to 90° C.

13. The portable electronic device of claim 12, wherein the portable electronic device comprises further the temperature sensor.

14. A computer-readable medium having computer-readable instructions stored on the computer-readable medium for execution of the computer-readable instructions by a processor to mitigate gas swelling of a battery of a portable electronic device by performing the method of any one of claims 1 to 11.

1/4

**FIG. 1****FIG. 2**

2/4




FIG. 3




FIG. 4

3/4




FIG. 5




FIG. 6

4/4




FIG. 7




FIG. 8

