



US011605235B2

(12) **United States Patent**
Karpas et al.

(10) **Patent No.:** **US 11,605,235 B2**

(45) **Date of Patent:** **Mar. 14, 2023**

(54) **DETECTING ONE OR MORE OBJECTS IN AN IMAGE, OR SEQUENCE OF IMAGES, AND DETERMINING A CATEGORY AND ONE OR MORE DESCRIPTORS FOR EACH OF THE ONE OR MORE OBJECTS, GENERATING SYNTHETIC TRAINING DATA, AND TRAINING A NEURAL NETWORK WITH THE SYNTHETIC TRAINING DATA**

(58) **Field of Classification Search**
CPC G06V 20/64; G06V 20/20; G06T 7/80; G06T 7/73; G06T 7/13; G06T 19/20; (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,708,223 B2 4/2014 Gates et al.
8,928,695 B2 1/2015 Fein et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 106103861 A 11/2016
KR 20110132031 A 12/2011
(Continued)

OTHER PUBLICATIONS

International Bureau, "International Preliminary Report on Patentability from PCT Application No. PCT/US2018/052310", from Foreign Counterpart to U.S. Appl. No. 16/138,918, filed Apr. 2, 2020, pp. 1 through 14, Published: WO.

(Continued)

Primary Examiner — Michael R Neff

(74) *Attorney, Agent, or Firm* — Volpe Koenig

(57) **ABSTRACT**

In an embodiment, an image-capture system, includes an image-capture device and computing circuitry. The image-capture device is configured to capture an image of a region of space that includes an object. And the computing circuitry is coupled to the image-capture device and is configured to detect a representation of the object in the image, to determine a representation of a boundary of the detected representation, to provide image information corresponding to the detected representation to an image-analysis system, to receive, from the image-analysis system, an identifier of a category to which the object belongs, and a descriptor of the object, and to generate a representation of a list that includes the identifier and the descriptor.

27 Claims, 9 Drawing Sheets

(71) Applicant: **LexSet.ai Inc.**, Brooklyn, NY (US)

(72) Inventors: **Leslie Karpas**, Los Angeles, CA (US);
Francis Bitonti, Brooklyn, NY (US);
Azam Khan, Seattle, WA (US)

(73) Assignee: **LexSet.ai Inc.**, Brooklyn, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 35 days.

(21) Appl. No.: **17/145,041**

(22) Filed: **Jan. 8, 2021**

(65) **Prior Publication Data**

US 2021/0133426 A1 May 6, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/138,918, filed on Sep. 21, 2018, now Pat. No. 10,915,730.

(Continued)

(51) **Int. Cl.**

G06V 20/64 (2022.01)


G06T 19/20 (2011.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06V 20/64** (2022.01); **G06F 30/23** (2020.01); **G06K 9/6262** (2013.01);

(Continued)



Related U.S. Application Data

		9,665,800 B1 *	5/2017	Kuffner, Jr.	G06V 20/653
		9,671,863 B2	6/2017	Fein et al.	
(60)	Provisional application No. 62/561,295, filed on Sep. 21, 2017.	9,674,047 B2	6/2017	Fein et al.	
		9,734,369 B2	8/2017	Gerrity et al.	
		9,734,614 B2	8/2017	Chan et al.	
(51)	Int. Cl.	10,007,820 B2	6/2018	Gerrity et al.	
		10,019,654 B1	7/2018	Pisoni	
	G06N 3/084 (2023.01)	2013/0106682 A1	5/2013	Davis et al.	
	G06T 7/13 (2017.01)	2013/0106683 A1	5/2013	Davis et al.	
	G06T 7/73 (2017.01)	2013/0106893 A1	5/2013	Davis et al.	
	G06T 7/80 (2017.01)	2013/0106894 A1	5/2013	Davis et al.	
	G06K 9/62 (2022.01)	2013/0110804 A1	5/2013	Davis et al.	
	G06N 3/08 (2023.01)	2013/0127893 A1	5/2013	Gokturk et al.	
	G06N 3/04 (2023.01)	2013/0135332 A1	5/2013	Davis et al.	
	G06F 30/23 (2020.01)	2014/0091829 A1	4/2014	Yamayose et al.	
	G06V 20/20 (2022.01)	2014/0098133 A1	4/2014	Fein et al.	
		2014/0098136 A1	4/2014	Fein et al.	
(52)	U.S. Cl.	2014/0098137 A1	4/2014	Fein et al.	
	CPC G06K 9/6274 (2013.01); G06N 3/0454 (2013.01); G06N 3/08 (2013.01); G06N 3/084 (2013.01); G06T 7/13 (2017.01); G06T 7/73 (2017.01); G06T 7/80 (2017.01); G06T 19/20 (2013.01); G06V 20/20 (2022.01); G06T 2207/20081 (2013.01)	2014/0307129 A1	10/2014	Feng	
		2015/0269746 A1	9/2015	Chan et al.	
		2016/0225053 A1	8/2016	Romley et al.	
		2017/0083752 A1	3/2017	Saberian et al.	
		2017/0154302 A1	6/2017	Streebin et al.	
		2017/0169620 A1 *	6/2017	Bleiweiss	G06V 20/64
		2017/0220887 A1	8/2017	Fathi et al.	
		2017/0315613 A1	11/2017	Fein et al.	
		2017/0345199 A1	11/2017	Chan et al.	
(58)	Field of Classification Search	2017/0357844 A1 *	12/2017	Comanicu	G16H 50/20
	CPC G06T 2207/20081 ; G06F 30/23 ; G06K 9/6262 ; G06K 9/6274 ; G06N 3/0454 ; G06N 3/08 ; G06N 3/084	2018/0077376 A1 *	3/2018	Armeni	G06T 19/20
	See application file for complete search history.	2018/0260843 A1	9/2018	Hiranandani et al.	
		2019/0102601 A1	4/2019	Karpas et al.	

FOREIGN PATENT DOCUMENTS

(56)	References Cited	KR	20140077066 A	6/2014
	U.S. PATENT DOCUMENTS	WO	2014126998 A1	8/2014
		WO	2015143130 A1	9/2015

8,941,689 B2	1/2015	Fein et al.
8,959,082 B2	2/2015	Davis et al.
9,077,647 B2	7/2015	Fein et al.
9,105,126 B2	8/2015	Fein et al.
9,111,383 B2	8/2015	Fein et al.
9,111,384 B2	8/2015	Fein et al.
9,141,118 B2	9/2015	Yang et al.
9,141,188 B2	9/2015	Fein et al.
9,170,656 B2	10/2015	Gates et al.
9,230,261 B2	1/2016	Gates et al.
9,235,571 B2	1/2016	Gerrity et al.
9,317,950 B2	4/2016	Chan et al.
9,448,623 B2	9/2016	Fein et al.
9,477,864 B2	10/2016	Gerrity et al.
9,569,439 B2	2/2017	Davis et al.

OTHER PUBLICATIONS

International Searching Authority, "International Search Report and Written Opinion from PCT Application No. PCT/US2018/052310 dated Mar. 4, 2019", from Foreign Counterpart to U.S. Appl. No. 16/138,918, pp. 1-18, Published: WO.
 U.S. Patent and Trademark Office, "Office Action", U.S. Appl. No. 16/138,918, dateds Mar. 13, 2020, pp. 1-28, Published: US.
 U.S. Patent and Trademark Office, "Notice of Allowance", U.S. Appl. No. 16/138,918, dated Oct. 6, 2020, pp. 1 through 11, Published: US.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9

1

DETECTING ONE OR MORE OBJECTS IN AN IMAGE, OR SEQUENCE OF IMAGES, AND DETERMINING A CATEGORY AND ONE OR MORE DESCRIPTORS FOR EACH OF THE ONE OR MORE OBJECTS, GENERATING SYNTHETIC TRAINING DATA, AND TRAINING A NEURAL NETWORK WITH THE SYNTHETIC TRAINING DATA

PRIORITY CLAIM(S) AND RELATED PATENT APPLICATION(S)

The present patent application is a continuation of U.S. Non-Provisional patent application Ser. No. 16/138,918, titled DETECTING ONE OR MORE OBJECTS IN AN IMAGE, OR SEQUENCE OF IMAGES, AND DETERMINING A CATEGORY AND ONE OR MORE DESCRIPTORS FOR EACH OF THE ONE OR MORE OBJECTS, GENERATING SYNTHETIC TRAINING DATA, AND TRAINING A NEURAL NETWORK WITH THE SYNTHETIC TRAINING DATA, which was filed 21 Sep. 2018, which is incorporated by reference herein, and which claims priority to U.S. Provisional Patent App. Ser. No. 62/561,295, titled SEMANTIC WEBS FOR 3D CAD DATA AND KINEMATIC, which was filed 21 Sep. 2017, and which is incorporated by reference herein.

SUMMARY

Choosing furniture and other décor for a space can be expensive and time-consuming, particularly for one having little or no interior-design or interior-decorating experience.

For example, if an inexperienced person wishes to add one or more items of furniture to a space, or to refurnish a space, then he/she typically spends countless hours visiting brick-and-mortar furniture stores, or perusing online furniture catalogues, to learn the types of furniture styles (e.g., contemporary, art deco, rustic) and the respective items of furniture (e.g., tables, chairs, sofas, entertainment centers, armoires) in each style, and to determine the style of the furniture currently in the space or to decide in what style and with what items he/she wishes to refurnish the space. And determining an overall style of furniture in a space in which the items of furniture do not all have the same style can be particularly challenging to an inexperienced person.

Alternatively, the inexperienced person may hire an interior decorator or interior designer at a significant cost in addition to the cost of the furniture. And even the interior designer may need to spend significant time visiting brick-and-mortar furniture stores or perusing online furniture catalogues with his/her client to show the client what furniture styles and items are available.

Therefore, a need has arisen for a technique that reduces the time and cost for both inexperienced consumers and experienced interior designers and decorators to furnish or to refurnish, and otherwise to decorate or redecorate, a space.

An embodiment of a system that allows a reduction in the time and cost to furnish, refurnish, decorate, or redecorate a space includes an image-capture subsystem and an image-analysis subsystem. The image-capture subsystem includes first computing circuitry configured to detect a representation of an object (e.g., an item of furniture) in an image of a space (e.g., a common area of an apartment building). And the image-analysis subsystem includes second computing circuitry configured to determine, in response to image information corresponding to the detected representation

2

(e.g., the pixels that form at least a portion of the detected representation), a category (e.g., chair) to which the object belongs, and at least one descriptor (e.g., color, style) of the object.

5 For example, assume that the image-capture subsystem is disposed on a smartphone, and that the image-analysis subsystem is disposed on one or more cloud servers.

A customer captures, with the smartphone's camera, a video sequence of frames (hereinafter "images"), of a space that includes one or more items of furniture. For example, the customer may be a person having little or no experience with interior design or decoration, or may be an experienced interior designer or decorator.

For each image, the smartphone detects the items of furniture, generates a respective bounding box for each detected item of furniture, and sends the respective set of pixels that represents at least a portion of each detected item of furniture to the cloud.

In response to each set of pixels, the one or more cloud servers determine a respective category, and a respective one or more descriptors, for a corresponding one of the detected items of furniture, and return, to the smartphone, the determined categories and descriptors.

The smartphone displays each image, and, for each detected item of furniture, displays the respective bounding box, category, and descriptor(s) overlaying the image and "anchored" to the item of furniture. Herein, "anchored" means that the bounding box is displayed around at least a portion of the furniture item, and that the category and descriptor(s) are displayed adjacent to the furniture item in a manner that conveys, to a viewer, that the category and descriptor(s) correspond to the furniture item. For example, the image may include a tag that points to the furniture item to which a list of the category and the other descriptor(s) is anchored.

Alternatively, the smartphone can display, for each detected item of furniture, the respective bounding box, category, and other descriptor(s) overlaying an image captured subsequent to the image that includes the set of pixels; overlaying a subsequent image with the bounding box(es), category(ies), and other descriptor(s) typically is due to a combined delay (e.g., one to five video images) of the smartphone and the one or more cloud servers in generating the representation(s) of the boundary and in determining the category(ies) and one or more other descriptors. That is, the combined delay is such that the smartphone and one or more cloud servers do not generate the boundary, category, and other descriptor(s) fast enough for the smart phone to display them over the image including the pixel representation of the item from which the boundary, category, and descriptor(s) are determined.

Although described above in terms of light-based images of items of furniture in a living or work space, one or more embodiments apply to, and can be used for or with, other types of images, other types of objects, and other types of spaces. For example, one or more embodiments apply to other types of images (e.g., sonographs, infrared images), other types of spaces (e.g., outdoors, outer space, underwater), and other types of objects (e.g., buildings, trees, planets, water craft) in a space.

In another embodiment, the image-analysis subsystem resides (e.g., is run or implemented by) a non-cloud server.

In yet another embodiment, one or both of the image-capture subsystem and the image-analysis subsystem each run a respective one or more neural networks.

Yet another embodiment is method for training the one or more neural networks.

Still another embodiment is directed to generating synthetic training images for training the one or more neural networks. That is, the training images are constructed and are not merely captured images that are marked up to show objects.

In an embodiment, an image-capture subsystem, includes an image-capture device and computing circuitry. The image-capture device is configured to capture an image of a region of space that includes an object. And the computing circuitry is coupled to the image-capture device and is configured to detect a representation of the object in the image, to determine a representation of a boundary of the detected representation, to provide image information corresponding to the detected representation to an image-analysis system, to receive, from the image-analysis system, an identifier of a category to which the object belongs, and a descriptor of the object, and to generate a representation of a list that includes the identifier and the descriptor.

In another embodiment, an image-capture-and-analysis system includes first computing circuitry and second computing circuitry. The first computing circuitry is configured to detect a representation of an object in a first image. And the second computing circuitry is configured to determine, in response to image information corresponding to the detected representation, a category to which the object belongs, and a descriptor of the object.

In yet another embodiment, an image-analysis subsystem includes computing circuitry configured to receive a portion of an image, the portion representing an object, and to implement a tree of neural networks configured to determine, in response to the portion of the image, a category and a descriptor corresponding to the object.

Another embodiment is a method for training at least one neural network and includes the following. Generating respective image segments of each of one or more objects (e.g., items of furniture) in response to respective electronic representations (e.g., three-dimensional computer-aided-design electronic files) of the one or more objects. Combining a respective image segment of each of at least one of the one or more objects with an image of a space (e.g., a room in a house or other building) to generate a first combined (e.g., synthetic training) image of the objects in the space. Changing at least one parameter of the first combined image to generate a second combined (e.g., synthetic training) image of the objects in the space. And training at least one neural network with the first and second combined images.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an image of a region of a space that includes one or more items of furniture.

FIG. 2 is an image of same region of space as in the image of FIG. 1, and the image is overlaid with bounding boxes and category names for some of the items of furniture, according to an embodiment.

FIG. 3 is an image of the same region of space as in the image of FIGS. 1 and 2, wherein the image is overlaid with bounding boxes and category names for some of the items of furniture, and overlaid with a list of the category name and descriptors for another of the items of furniture, according to an embodiment.

FIG. 4 is a circuit diagram of an image-analysis subsystem and of a network via which the subsystem can communicate with a remote device, subsystem, or system, according to an embodiment.

FIG. 5 is a circuit diagram of an image-capture subsystem and of a network via which the subsystem can communicate with a remote device, subsystem, or system, according to an embodiment.

FIG. 6 is a combination circuit and flow diagram of a system that includes the image-analysis subsystem of FIG. 4 and the image-capture subsystem of FIG. 5, according to an embodiment.

FIG. 7 is a combination circuit and flow diagram of a neural-net-inferencing-service portion of the system of FIG. 6, according to an embodiment.

FIG. 8 is a combination circuit and flow diagram of a cluster-neural-network portion of the system of FIG. 6, according to an embodiment.

FIG. 9 is a diagram of the image-analysis-and-capture system where the image-analysis subsystem resides in the cloud, according to an embodiment.

DETAILED DESCRIPTION

Each value, quantity, or attribute herein preceded by “substantially,” “approximately,” “about,” a form or derivative thereof, or a similar term, encompasses a range that includes the value, quantity, or attribute $\pm 20\%$ of the value, quantity, or attribute, or a range that includes $\pm 20\%$ of a maximum difference from the value, quantity, or attribute. For example, “two planes are approximately orthogonal to one another” encompasses an angle $72^\circ \leq \alpha \leq 108^\circ$ between the two planes (90° is the angular difference between the two planes when they are orthogonal to one another, and $\pm 20\%$ of 90° is $\pm 18^\circ$).

Furthermore, any described function, operation, or functional block is performed by a circuit configured to perform the function or operation, or to implement the functional block. Such a circuit, and any other disclosed, can be so configured by executing software instructions, in response to configuration data (e.g., firmware), or by hard-wired connections.

FIG. 1 is a two-dimensional image **10** of a region of a space **12**, which here is a room that includes one or more items of furniture. For example, the space **12** includes a sofa **14**, chairs **16**, **18**, and **20**, and tables **22** and **24**. Although the image **10** is light image of the space **12** (i.e., the pixels of the image represent attributes of light, such as intensity and color, reflected from objects within the space), which includes items of furniture, the below description applies to other types of images (e.g., sonographs, infrared images), other types of spaces (e.g., outdoors, outer space, underwater), and other types of objects (e.g., buildings, trees, planets, water craft) in a space.

The image **10** was captured by an image-capturing subsystem, which is not shown in FIG. 1 but which is described below in conjunction with FIGS. 5-7. Examples of the image-capturing subsystem include a smartphone or tablet computer that incorporates a still-image or video camera, or a still-image or video camera electrically and communicatively coupled to a laptop, desktop, or other computer system or computer circuitry.

If a person inexperienced in interior design and interior decorating wishes to replace some or all of the furniture in the space **12**, then he/she typically would spend many hours researching decorating styles and themes, furniture styles (e.g., rustic, American artisan, art deco), furniture types (e.g., chair, sofa, table), and furniture items (e.g., specific furniture pieces by stock-keeper units (SKUs)) online and in brick-and-mortar furniture stores.

Alternatively, the person could hire, at a significant cost, an experienced interior designer or interior decorator to research and propose a decorating theme, a furniture style, and furniture items for the space **12**.

Although hiring an interior designer or decorator would tradeoff a savings in time for an added expense, the person would still need to spend a significant amount of time working with the interior designer or decorator to select a decorating theme, furniture style, and specific furniture items.

Described below in conjunction with FIGS. 2-9 is a system that can help a person inexperienced in interior design and interior decorating to perform one or more of the above tasks in a shorter amount of time and without the expense of an experienced interior designer or decorator. And such a system also can help an experienced interior designer or decorator perform one or more of the above tasks in a shorter amount of time.

FIG. 2 is an image **30** of a region of the space **12** of FIG. 1, where the system (not shown in FIG. 2) generates, and lays over the image, bounding boxes **32**, **34**, and **36**, and category names **38**, **40**, and **42**, for the sofa **14**, the chair **16**, and the chair **20**, respectively, according to an embodiment.

Each bounding box bounds all, or at least a major portion of, a respective object in the image **30**. For example, the bounding box **32** includes, within its interior, almost the entire sofa **14**, the bounding box **34** includes the seat and back, but excludes portions of the legs, of the chair **16**, and the bounding box **36** includes most of the seat and back, but excludes most of the legs, of the chair **20**.

And the category names (e.g., "sofa," "chair," and "chair") serve to identify the type of the furniture item.

FIG. 3 is an image **50** of a region of the space **12** of FIGS. 1 and 2, where the system (not shown in FIG. 3) generates, and lays over the image, the bounding boxes **32** and **36** and the category names **38** and **42** for the sofa **14** and the chair **20**, respectively, a bounding box **52** and a category name **54** for a chair **56**, and a list **58** including the category name **40**, other descriptors **60** (the category name also can be considered one of the descriptors), and a relative location **62** for the chair **16**, according to an embodiment. For example, the relative location **62** can be a center point of the bounding box **34** (FIG. 2) for the chair **16**, can be a center of mass of the bounding box, or can be a center of a three-dimensional representation of the chair that the system generates and stores.

The list **58** is anchored to the chair **16** with an anchor icon **64**, and each of the descriptors **60** describes a style or another attribute of the chair. For example, the descriptors **60** indicate that the chair **16** is of a contemporary style, has a black finish, a sleek design, nail-head trim, is paired, in the space **12**, with a Persian rug and an end table **64** that can support a table lamp (not shown in FIG. 3), and is suitable for use in an entertainment space and in a breakfast nook. The system (not shown in FIG. 3) is able to indicate that the chair **16** is paired with a Persian rug and an end table **64** because the system also detected, categorized, and described (with descriptors) these items.

A person can use the list **58** in a number of ways.

For example, he/she can perform a manual search in brick-and-mortar furniture stores, in paper catalogues, or online for chairs that have the same style, and that have one or more of the same, or similar, attributes as indicated by the other descriptors **60**.

Alternatively, the system can be configured to perform, automatically or at the request of the person, an online search for chairs that have attributes the same as, or similar

to those, indicated by the descriptors **60**. And the person can weight the influence of the descriptors **60** on the search in response to spatial information regarding the space **12**. For example, one may want a large item of furniture (e.g., a large banquet table) in the center of the space **12** to dictate the style and the other characteristics of furniture in the space. Therefore, for purposes of the search, the one can weight the descriptors for the large item of furniture more heavily than the descriptors of the other items of furniture in the space so that the search tends to return items of furniture having descriptors that trend closer to the descriptors of the large item of furniture than they do to the descriptors of the other items of furniture.

In another alternative, the person or the system can upload the list **58** to a furniture provider's webserver, which then returns a list of all of the provider's furniture items having attributes that match the attributes indicated by the descriptors **60**. The person, or the furniture provider's webserver, can adjust, in a conventional manner, the level of similarity between the attributes of a furniture item and the attributes indicated by the descriptors **60** needed to yield a match.

Still referring to FIGS. 2-3, alternate embodiments of the image-capture-and-analysis system (not shown in FIGS. 2-3), and methods that the system is configured to perform, are contemplated. For example, the shapes of one or more of the bounding boxes **32**, **34**, **36**, and **52** can be other than rectangular (e.g., circular, triangular). Furthermore, the system can display one or more of the bounding boxes **32**, **34**, **36**, and **52** without the corresponding category names **38**, **40**, **42**, and **54** or list **58**; conversely, the system can display one or more of the category names or list without the corresponding bounding box. Moreover, the system can capture and display a video sequence of images of the space **12**, even as the system camera moves (e.g., pans across the space), and the system can display one or more of bounding boxes, category names, and lists in each of the images such that the one or more bound boxes, category names, and lists each "follows" its respective object as the camera moves. The system can do this by determining one or more of a bounding box, category name, and a list for each item of furniture in each image. Alternatively, the system can generate a three-dimensional map (i.e., point cloud) of the space **12**, determine a respective centroid for each item of furniture, track the respective relative locations of each item of furniture from image to image, and, for each item of furniture, the system can display a previously determined bounding box centered about the centroid of a respective item of furniture. For example, the system may track the relative locations in response to one or more sensors onboard the camera, where each sensor generates a respective signal including information (e.g., acceleration, GPS location) related to the movement of the camera. In yet another alternative, the system can determine the bounding box of a furniture item in one image and display the bound box at the same location in a subsequent image. As long as the subsequent image is not too distant, in time, from the one image, and the camera does not move too great of a distance from the time that the system captures the one image to the time that the system captures the subsequent image, the bounding box will at least approximately bound the furniture item in the subsequent image such that any misalignment is barely noticeable to a viewer.

FIG. 4 is a circuit diagram of an image-analysis subsystem **70** of the image-capture-and-analysis system described above in conjunction with FIGS. 2-3 and below in conjunction with FIGS. 6-8, according to an embodiment.

The image-analysis subsystem **70** is configured to analyze images of spaces, to detect objects, such as furniture items, in the images, and to determine categories and other descriptors for the detected objects as described above in conjunction with FIGS. 2-3 and below in conjunction with FIGS. 5-8.

The image-analysis subsystem **70** includes computing circuitry **72**, at least one communication port **74**, one or more input devices **76**, one or more output devices **78**, and one or more data-storage devices **80**.

The computing circuitry **72** includes one or more computing circuits, such as a microprocessor or microcontroller **82**, or a field-programmable-gate array (FPGA), and is configured to execute program instructions, to be topologically configured in response to configuration data (e.g., firmware), and to implement data and software architectures in response to the program instructions, the configuration data, or both the program instructions and configuration data. For example, the computing circuitry **72** can be configured to implement one or more neural networks (NNs) as described below in conjunction with FIGS. 6-8.

The communication port **74** is configured to allow bidirectional communication between a device, subsystem, or system (not shown in FIG. 4) remote from the subsystem **70**, and the computing circuitry **72** and other circuits and components of the subsystem **70** via a communications network **84** such as the internet or a cellular network. For example, the port **74** can be a wired port (e.g., Ethernet, Universal Serial Bus (USB)) or a wireless port (e.g., Bluetooth®, WiFi®) configured to communicate with an image-capture subsystem (see FIG. 5) as described above in conjunction with FIGS. 2-3 and below in conjunction with FIGS. 6-8.

Each of the one or more input devices **76** is configured to generate or to acquire information, and to provide the information to the computing circuitry **72**. Examples of an input device **76** include a still-image camera or a video camera respectively configured to capture an image or a video sequence or series of images, a motion sensor (e.g., an accelerometer or GPS locator circuit) configured to generate data related to a movement or a location of the image-analysis subsystem **70**, and a key pad configured to allow one to generate or to input, manually, commands, data, etc.

Each of the one or more output devices **78** is configured to receive and to consume information from the computing circuitry **72**. Examples of an output device **78** include an image display device **86**, a printer, and a speaker.

And each of the one or more data-storage devices **80** is configured to store data in a volatile or non-volatile manner. Examples of the data-storage devices **80** include a memory circuit **88** (e.g., a volatile memory circuit such as random-access memory (RAM), static RAM (SRAM), or dynamic RAM (DRAM), a non-volatile memory circuit such as electrically erasable and programmable read-only memory (EEPROM)), a magnetic-disk drive, a solid-state drive, and an optical-disk drive (e.g., a digital-versatile disk (DVD)). For example, one or more of the data-storage devices **80** can implement one or more databases for the image-analysis subsystem **70**, can store program instructions of one or more software applications for execution by the computing circuitry **72**, can store configuration data (e.g., firmware) for configuring the computing circuitry (e.g., FPGA circuitry), and can serve as volatile working memory for the computing circuitry.

In an operative example of the image-analysis subsystem **70**, the computing circuitry **72** receives, via the port **74**, image information regarding objects detected in images by

an image-capture subsystem (see FIG. 5), determines a respective category and respective other descriptors for each object, and provides the determined categories and other descriptors to the image-capture subsystem via the port.

In a further operative example, the image-analysis subsystem **70** generates training images from electronic representations of objects, implements one or more neural networks, trains the neural networks with the training images, and stores the electronic representations of objects in a database for comparing to objects that the image-analysis subsystem categorizes and otherwise describes as described above in conjunction with FIGS. 2-3 and below in conjunction with FIGS. 6-8.

Still referring to FIG. 4, alternate embodiments of the image-analysis subsystem are contemplated. For example, the subsystem **70** can include one or more circuit or other components not disclosed above or shown in FIG. 4, and can omit one or more of the components disclosed above in conjunction with, or shown, in FIG. 4.

FIG. 5 is a circuit diagram of an image-capture subsystem **90** of the image-capture-and-analysis system described above in conjunction with FIGS. 2-3 and below in conjunction with FIGS. 6-9, according to an embodiment.

The image-capture subsystem **90** is configured for use by an individual inexperienced in interior design and interior decorating, or by an interior designer or interior decorator of whom the individual is a client, to take one or more images (e.g., still images, a sequence of video images) of a space that the individual wishes to furnish, or in which the individual wishes to replace one or more items of existing furniture.

The image-capture subsystem **90** includes computing circuitry **92**, at least one communication port **94**, one or more image-capture devices and sensors **96**, one or more motion sensors **98**, one or more image display devices **100**, and one or more data-storage devices **102**.

The computing circuitry **92** includes one or more computing circuits, such as a microprocessor or microcontroller **104**, or an FPGA, and is configured to execute program instructions, to be topologically configured in response to configuration data (e.g., firmware, data stream), and to implement data and software architectures in response to the program instructions, the configuration data, or both the program instructions and configuration data. For example, the computing circuitry **92** can be configured to implement one or more neural networks (NNs) as described below in conjunction with FIGS. 6-8.

The communication port **94** is configured to allow bidirectional communication between a device, subsystem, or system (not shown in FIG. 5) remote from the subsystem **90** and the computing circuitry **92** and other circuits and components of the subsystem via the communications network **84** such as the internet or a cellular network. For example, the port **94** can be a wired port (e.g., Ethernet, Universal Serial Bus (USB)), or a wireless port (e.g., Bluetooth®, WiFi®).

Each of the one or more image-capture devices and sensors **96** is configured to generate or to capture light images or other types (e.g., sound, infrared, thermal) of images, and to provide information (e.g., pixels) representing the images to the computing circuitry **92**. For example, a still-image or video camera **96** is configured to capture a light image or a video sequence or series of light images, an array of microphones is configured to capture a sound image or a video sequence or series of sound images, and a thermal sensor is configured to capture a heat or infrared image or a video sequence or series of heat or infrared images.

Each of the one or more motion sensors **98** (e.g., an accelerometer, gyroscope, or GPS locator circuit) is configured to generate data related to a movement or location of the image-capture subsystem **90**.

Each of the one or more display devices **100** is configured to receive image data (e.g., a pixel map) from the computing circuitry **92**, or directly from an image-capture device or image-capture sensor **96**, and to display one or more images (e.g., a still image or a video sequence of images) in response to the image data.

And each of the one or more data-storage devices **102** is configured to store data in a volatile or non-volatile manner. Examples of the data-storage devices **102** include a memory circuit **108** (e.g., a volatile memory circuit such as random-access memory (RAM), static RAM (SRAM), or dynamic RAM (DRAM), a non-volatile memory circuit such as electrically erasable and programmable read-only memory (EEPROM)), a magnetic-disk drive, a solid-state drive, and an optical-disk drive (e.g., a digital-versatile disk (DVD)). For example, one or more of the data-storage devices **102** can implement one or more databases for the image-capture subsystem **90**, can store program instructions of one or more software applications for execution by the computing circuitry **92**, can store configuration data for configuring the computing circuitry, and can serve as volatile working memory for the computing circuitry.

Although not shown in FIG. 5, the image-capture subsystem **90** can also include one or more input devices configured for providing information to the computing circuitry **92**, and one or more output devices for consuming data from the computing circuitry. An example of an input device (other than an image-capture device and image-capture sensor **96**, and other than a motion sensor **98**) is a key pad configured to allow one to generate, manually, e.g., commands or other input data, for the computing circuitry **92**. And examples of an output device (other than a display device **100**) include a printer, a speaker, and a haptic (e.g., vibratory) generator.

In an operative example of the image-capture subsystem **90**, a camera **96** captures one or more images, and provides these images to the computing circuitry **92**, which routes the images for display by a display device **100**, which processes the images, and which sends one or more segments of the images to the image-analysis subsystem **70** of FIG. 4 (see also FIG. 6) via the port **94** and the internet **84**. Alternatively, the camera **96** can be configured to send the captured one or more images directly to the display device **100** for display.

Still referring to FIG. 5, alternate embodiments of the image-analysis subsystem **90** are contemplated. For example, the subsystem **90** can include one or more circuit or other components not disclosed above or shown in FIG. 5, and can omit one or more of the components disclosed above in conjunction with, or shown, in FIG. 5.

FIG. 6 is a combination circuit and flow diagram **120** of an image-capture-and-analysis system **122**, which includes the image-analysis subsystem **70** of FIG. 4 and the image-capture subsystem **90** of FIG. 5, according to an embodiment.

FIG. 7 is a combination circuit and flow diagram **124** of a neural-net inferencing-service portion **126** of the image-analysis subsystem **70**, and the image-capture subsystem **90**, of the combination circuit and flow diagram **120** of FIG. 6, according to an embodiment.

FIG. 8 is a combination circuit and flow diagram **128** of a cluster neural network **150** of the combination circuit and flow diagram **120** of FIG. 6, according to an embodiment.

The structure and operation of the image-capture-and-analysis system **122** of FIG. 6 during a neural-network training operation is described in conjunction with the combination circuit and flow diagrams **120**, **124**, and **128** of FIGS. 6-8, according to an embodiment.

First, the image-capture-and-analysis system **122** generates training images, according to an embodiment.

A 3D rendering engine circuit **130** receives a three-dimensional CAD (or other) representation **132** of an object, which is, for example an item of furniture such as a chair that is available for purchase from the furniture manufacturer or a furniture retailer. For example, the chair manufacturer may provide, as the 3D CAD representation of the chair, an electronic 3D CAD file of the chair, which the system **122** can store in a data-storage device **80** of FIG. 4. And the 3D CAD file may be configured to allow the circuit **130** to position a virtual representation of the chair into a number of different poses, hereinafter orientations. Although a chair is the object featured in following description, it is understood that the following description, and the principles included therein, can apply to any other item of furniture, and to any other object. Furthermore, the computing circuit **72** of FIG. 4 can be configured to be, or to implement, the 3D rendering engine circuit **130**.

The 3D rendering engine circuit **130** also receives one or more texture maps **134** for the chair. For example, a seat of the chair may be available in wood (a first texture) or upholstered with leather (a second texture) or with a particular upholstery pattern (a third texture).

Next, the 3D rendering engine circuit **130** generates a number of versions of the chair in different orientations (one orientation per version), and having different textures (one texture per one chair portion per version). Furthermore, the circuit **130** is configured to add to the versions of the chair other real-world features such as fabric wrinkles, scratches, fabric tears, missing upholstery buttons, and stains. For example, the circuit **130** is configured to generate these versions randomly to obtain a statistically independent set of versions of the chair. The goal is to generate enough real-world versions of the chair to train the system so that the system will be able to recognize the chair in a variety of real-world settings.

Then, the 3D rendering engine circuit **130** repeats the above steps for one or more other items of furniture.

Next, the 3D rendering engine circuit **130** receives one or more high-dynamic-range (HDR) images **136** of empty spaces such as rooms or other areas in a house or other building in which one would expect to find items of furniture. The HDR images **136** lend themselves to adjusting the lighting conditions of the spaces in the images because an HDR image is, generally, a photon (i.e., a light-based) representation of a scene; therefore, the HDR images allow the circuit **130** to adjust lighting conditions of a space in an image by adjusting, e.g., the effective light-source location, color temperature, and light intensity, so as to represent a real-world lighting condition dependent upon these parameters.

The 3D rendering engine circuit **130** may also receive one or more camera conditions **138** (e.g., f-stop, shutter speed, color balance, white temperature) according to which the rendering engine circuit can further adjust the lighting conditions of the HDR images.

Then, the 3D rendering engine circuit **130** renders a number of training images **140** (e.g., one thousand or more) by populating the HDR images of spaces with one or more versions of the one or more pieces of furniture. The circuit **130** generates the training images randomly to obtain a

statistically independent (i.e., a statistically diverse) spread of parameters such as types of spaces, number of furniture items in a space, furniture orientations, space lighting conditions, furniture textures, and other furniture features, to obtain training images that, as a set, represent an unbiased

representation of all considered image and furniture-item parameters. Next, the circuitry (e.g., the computing circuit **72** of FIG. **4**) of the image-analysis subsystem **70** associates respective metadata **142** with each object in each of the rendered training images **140**. For example, metadata **142** for an item of furniture includes, for example, a category (e.g., chair), one or more other descriptors (e.g., style, color, texture, size, material (e.g., metal, wood), finish), and an identifier such as an SKU. That is, for each item of furniture in each training image, the circuitry generates a list such as the list **58** of FIG. **3**. The metadata **142** for an object may be included with the 3D CAD file **132** for the object, or the object manufacturer may provide the metadata in a file separate from the 3D CAD file. Furthermore, if, for example, items of furniture from different manufacturers have different categories or descriptor names, then one can reconcile the different categories and descriptor names to a set of common categories and descriptor names. For example, if one manufacturer has a category “couch” and another manufacturer has a corresponding category “sofa,” then one can create a common category (e.g., “couch,” “sofa,” or davenport) and can convert the category for each sofa/couch to the common category. Further in example, if the metadata from one manufacturer has a descriptor (e.g., “leather upholstery”) that the metadata from another manufacturer does not have, then the descriptor from the one manufacturer can be added to the metadata for a furniture item from the other manufacturer, where the added descriptor has, or effectively has, a value of null or zero.

Then, each of the rendered training images **140** and the respective associated metadata **142** are stored in a database **144**, which may be disposed on one or more of the data-storage devices **80** of FIG. **4**.

Next, the image-analysis subsystem **70** groups the objects (e.g., items of furniture) in the rendered training images **140** into hierarchal clusters **146** in the following manner.

Referring to FIG. **8**, the subsystem **70** first trains a convolutional-neural-network (CNN) feature extractor **148** of neural networks **150** (FIG. **6**) with the rendered training images **140**.

For each object (e.g., item of furniture) in the training images **140**, the synapse weightings of the CNN feature extractor **148** converge to a set of values over the course of the training.

Using a conventional comparison algorithm, the image-analysis subsystem **70** compares the sets of values for all of the objects to see which sets of synapse-weighting values are similar. For example, the subsystem **70** can indicate that two sets of synapse-weighting values are similar if the mean distance between the sets is below a particular threshold. In non-mathematical terms, objects with similar features (e.g., shape, contours, size) and metadata descriptors (e.g., category), as detected by the CNN feature extractor **148**, tend to be in a same cluster, and objects with diverse features tend to be in different clusters.

The subsystem **70** groups all objects that yield similar sets of synapse-weighting values into a respective cluster. Where the objects are items of furniture, ideally a cluster includes all items of furniture of a same category. For example, ideally all chairs would be in a same cluster, all sofas in a same cluster, all tables in a same cluster, all lamps in a same

cluster, etc. But this is not always the case. For example, both rectangular tables and flat-screen televisions have the prominent feature of a large, flat, smooth surface. Therefore, the image-analysis subsystem **70** may group rectangular tables and flat-screen televisions into a same cluster even though they are in different furniture categories. Similarly, the image-analysis subsystem **70** may group sofas and loveseats into a same cluster because they are typically similar but for length. Said another way, the subsystem **70** does not necessarily generate the same cluster groupings that a human might generate, and, therefore, cluster groupings that the subsystem **70** generates may seem strange, or even illogical, to a human not versed in neural-network theory.

Next, referring to FIG. **6**, an image-analysis-and-natural-language-processing unit **151** associates, with each identified cluster **146**, the metadata **142** for each object belonging to the cluster. For example, if an object belonging to a cluster is a sofa, then the unit **151** associates with the cluster all the metadata **142** (e.g., category “sofa” or “couch,” other descriptors for color and texture) for that particular object. Sometimes, as described above, the correspondence between a cluster/category and objects may not be this “clean.” For example, a clean correspondence, at least from a human perspective, might be that each cluster/category corresponds to a single respective type of furniture, like table, chair, and sofa. But as described in the previous paragraph, because it is the image-analysis subsystem **70** that determines the clusters, not a human, the correspondence between clusters and objects may not be “clean.” For example, a cluster/category may be “item of furniture with large flat surface,” which may include multiple furniture categories such as tables, flat-screen televisions, mirrors, large pictures, and desks. Further to this example, if an object belonging to such a multi-category cluster is a table, then the unit **151** associates with the cluster all metadata **142** (e.g., category “table”, descriptors for size, color, distance from the floor) for that object. The image-analysis-and-natural-language-processing unit **151** can be the computing circuitry **72** (FIG. **4**) configured by software or configuration data to perform the above functions, and any other functions described herein, that are attributed to the unit **151**. If the cluster hierarchy includes cluster “trees” that include sub-clusters, then the unit **151** can also associate, with each identified subcluster, metadata **142** for each object belonging to the subcluster.

Then, the image-analysis subsystem **70** stores the cluster hierarchy and associated metadata **142** in a database **152**. That is, the database **152** stores information identifying the clusters and identifying the object category(ies) (typically the metadata category names) belonging to each identified cluster, and the metadata **142** associated with all of the objects in each identified cluster. Furthermore, the databases **144** and **152** can be, or can be merged into, a same database.

Next, the image-analysis subsystem **70** trains the neural networks **150** for each cluster, and each subcluster within each cluster. For example, the computing circuitry **72** (FIG. **4**) of the image-analysis subsystem **70** may train the neural networks **150** by executing neural-network training software **154**, which implements a back-propagation training algorithm that can be conventional.

Referring to FIGS. **6** and **8**, the image-analysis subsystem **70** uses the training images **140** to train the CNN feature extractor **148** to detect objects on the cluster level. That is, the subsystem **70** trains the CNN feature extractor **148** to generate, for each detected object, one or more confidence levels that are indicative as to which of the identified clusters the object belongs. For example, the subsystem **70** may train

the CNN feature extractor **148** by feeding to the feature extractor the segments of a training image **140** that include the objects, one segment at a time.

And after the image-analysis subsystem **70** trains the CNN feature extractor **148**, it uses the training images **140** to train respective feed-forward neural networks **156** to detect subclusters within each cluster; that is, there is one feed-forward neural network **156** per cluster. The subsystem **70** trains a respective feed-forward neural network **156** to generate one or more confidence levels that are indicative as to which subcluster an object belongs by generating the one or more confidence levels that are indicative of the metadata descriptors of the object. As described below, the feed-forward network **156** may generate confidence levels corresponding to addresses of the database **152** containing the descriptors for the object.

Each feedforward neural network **156** includes a tree of neural networks **158**, where the number of layers **160** (two layers shown in FIG. **8**), and the number of neural networks **158** within each layer, can be different from neural network **156** to neural network **156**. Using conventional mathematical techniques, the image-analysis subsystem **70** determines the number of layers **160** and the number of neural networks **158** within each of the layers in response to parameters such as the number of objects (e.g., items of furniture), also called "data sets," that belong to the cluster for which the feed-forward neural network **156** is being trained, and the classification complexity (e.g., number of metadata descriptors an object in the cluster can have) of the cluster.

Each of the neural networks **158** is a non-convolutional neural network, and effectively functions as a non-recursive (non-feedback) filter.

Consequently, the combination of the CNN feature extractor **148** and the feedforward neural network **156** often can render a result faster than a conventional neural network such as a single-shot detector (SSD) CNN having both an object detector and a feature extractor (also called a classifier).

Referring to FIGS. **6-8**, during training of the feedforward neural networks **156**, the image-analysis subsystem **70** provides a training image **140** to the already-trained CNN feature extractor **148**, which generates, for each object in the training image, an indication as to what cluster the object belongs. In more detail, the subsystem **70** may provide to the feature extractor **148** only the segments (e.g., the two-dimensional arrays of pixels) of the training image **140** including the respective objects, and may provide these segments to the feature extractor one image segment at a time.

Next, for each object in the training image **140**, the CNN feature extractor **148** generates an indication of the cluster to which the object belongs. As stated above, this indication may include a vector of confidence levels, one confidence level per cluster. The cluster having the highest confidence level above a threshold is the cluster to which the feature extractor **148** indicates the object belongs.

Then, the image-analysis subsystem **70** provides the image segment for the object to the feedforward neural network **156** configured for the cluster to which the feature extractor **148** indicated the object belongs, for the purpose of training that particular feedforward neural network.

The image-analysis subsystem **70** repeats the above steps for each object in the training image **140**.

Next, the image-analysis subsystem repeats the above steps with additional training images **140** until all of the feedforward neural networks **156** are trained.

Referring again to FIGS. **6-7**, the image-analysis subsystem **70** also trains a single-shot-detector (SSD) neural network (NN) model **162**, which is disposed on (e.g., run, implemented, or executed by) the image-capture subsystem **90**, according to an embodiment. The subsystem **70** may train the SSD model **162** before (not shown in FIGS. **6-7**) or after (shown in FIGS. **6-7**) the image-capture subsystem **90** downloads the SSD model software that the computing circuitry **92** (FIG. **5**) executes to implement the SSD model. Furthermore, the computing circuitry **72** (FIG. **4**) of the image-analysis subsystem **70** may train the SSD NN model **162** by executing neural network training software **154**, which implements a back-propagation training algorithm that can be conventional.

In general, a conventional SSD CNN includes an object-detector front end, and an object-classifier back end.

Because the neural networks **150** effectively perform object feature detection and classification, in an embodiment the image-capture-and-analysis system **122** does not need the SSD NN model **162** to classify objects.

Therefore, in an embodiment, the SSD model **162** includes only an object-detector front end, and omits an object-classifier back end. Alternatively, the SSD NN model **162** includes an object-classifier back end but the image-capture-and-analysis system **122** effectively ignores object classifications that the SSD NN model generates. Or, the system **122** can feed the classifications from the SSD NN model **162** to the CNN feature extractor **148** (FIG. **8**), which can accept the SSD NN model classifications as inputs.

During training of the SSD NN model **162**, the neural net training software **154** receives, from the data base **144**, the clusters, categories, or both the clusters and categories **164** of the objects that the SSD NN model **162** is to be configured to detect. For example, if the objects are furniture items, then the software **154** receives the categories **164** (e.g., sofa, chair, table) of the furniture items that the SSD NN model **162** is being trained to detect. Consequently, the training software **154** does not train the SSD NN model **162** to detect objects (e.g., windows) that do not fall into one of the categories (clusters) **164**.

The object-detector front end of the SSD NN model **162** detects, in a conventional manner, the one or more objects in a training image (only the objects that fall into the categories **164**), and generates representations of bounding boxes (e.g., similar to the bounding boxes **32**, **34**, and **36** of FIG. **2**) for each detected object.

The image-analysis subsystem **70** continues feeding training images **140** to the SSD NN model **162** until the SSD NN model is trained to detect, and to generate bounding boxes for, objects belonging to all clusters of the cluster hierarchy **146** and categories **164**, and is trained to perform such detecting and generating within a range of error suitable for the application (e.g., detecting and identifying items of furniture) for which the image-capture-and-analysis system **122** is, or is being, configured.

Still referring to FIGS. **6-8**, alternate embodiments of the training of neural networks of the image-capture-and-analysis system **122** are contemplated. For example, the system **122** can train its neural networks with conventional training images (i.e., images captured of actual spaces with actual objects in the spaces, and manually marked up with bounding boxes, metadata, etc.).

Referring again to FIGS. **6-8**, the structure and operation of the image-capture-and-analysis system **122** is described while the system is capturing and analyzing images of objects, according to an embodiment.

15

First, a user of the image-capture subsystem **90** captures, with a camera or other image-capture device **96**, an image of a region of a space that includes one or more objects such as items of furniture. An example of such an image and a space is the image **10** and space **12** of FIG. 1. The image-capture subsystem **90** can be, for example, a smart phone or tablet.

Next, the computing circuitry **72** provides the captured image for display on the display device **100**. For example, the display device **100** can be a display screen of a smart phone or tablet.

Then, the SSD NN model **162** detects, within the image, one or more objects that the SSD NN model has been trained to detect. For example, the SSD NN model **162** is trained to detect, and does detect, one or more items of furniture in the image.

The SSD NN model **162** also generates a representation of a respective bounding box for each detected object. The representation may include a location of the bounding box within the image, and the dimensions (e.g., width and length) of the bounding box. As described above, a bounding box bounds a segment of the image that includes some or all of the pixels that form the detected object. An example of a bounding box is the bounding box **36** of FIG. 2.

Then, the computing circuitry **92** (FIG. 5) executing instructions of a software application, here software from a software developer kit (SDK) **170**, extracts, from the image, the one or more image segments **172** respectively bounded by the one or more bounding boxes that the SSD NN model **162** generated. As described above, each image segment **172** includes pixels (e.g., numerical representations of the pixels) that form an image representation of a respective detected object.

The SDK **170** also generates image representations of the one or more bounding boxes, sends these image representations to the display **100** such that the displayed bounding boxes overlay the displayed image, and such that each bounding box bounds at least a portion of a respective object in the image, for example as shown in, and described in conjunction with, FIGS. 2-3.

Next, the SDK **170** provides each of the one or more image segments **172** to a neural net inferencing service **174** via the ports **94** (FIG. 5) and **74** (FIG. 4) and a communication network **84** such as the internet or a cellular network. The computing circuitry **72** (FIG. 4) implements the neural net inferencing service **174**, for example, by executing respective software code.

Then, the neural net inferencing service **174** reshapes each of the image segments **172** to a common set of dimensions that is compatible with the CNN feature extractor **148**. Because the CNN feature extractor **148** has a fixed number of neurons in its first layer, it “expects” to receive an image segment of particular dimensions. For example, the CNN feature extractor **148** may be configured to receive a vector of 2500 pixels generated from a 50 pixel×50 pixel image segment. Therefore, if an image segment **172** has dimensions other than 50 pixels×50 pixels, then the inferencing service **174** converts the image segment **172** into a corresponding reshaped image segment **176** having dimensions of 50 pixels×50 pixels. For example, the inferencing service **174** can use conventional interpolation or extrapolation techniques, in two dimensions, to perform such a conversion. Although an example of a reshaped image segment **176** is described as having dimensions of 50 pixels×50 pixels, the reshaped image segment can have a shape other than square, and can have any suitable size in either of its two dimensions.

16

Next, the inferencing service **174** provides the reshaped image segments **176**, one at a time, to the CNN feature extractor **148**.

Then, the CNN feature extractor **148** generates, for a reshaped image segment **176**, a respective set of confidence values for the clusters that the CNN feature extractor is trained to detect (e.g., the clusters in the hierarchy of clusters **146**).

Next, the neural net inferencing service **174** identifies the cluster to which the object represented by the reshaped image segment **176** belongs as the cluster corresponding to the highest confidence value over a threshold confidence value.

Then, the inferencing service **174** effectively “swaps in,” or “activates,” the feedforward network **156** trained for the identified cluster. That is, the inferencing service **174** provides the reshaped image segment **172** to the one of the feedforward networks **156** that is configured to determine a category and other descriptors for objects belonging to the identified cluster. Using a respective feedforward network **156** for objects belonging to each cluster increases the speed at which the image-analysis subsystem **72** can generate the category and descriptors for a detected object as compared to using a single, more complex, neural network for all objects.

Next, the activated feedforward network **156** analyzes the reshaped image segment **176** and, in response to the reshaped image segment, generates the category and one or more other descriptors for the object represented by the analyzed reshaped image segment. Each neural network **158** in the bottom layer **160** of the feedforward neural network **156** corresponds to a respective descriptor for the object, and generates a respective confidence value **178** for each of one or more addresses in the database **152** that store descriptor values for the respective descriptors; the address having the highest confidence value above a threshold is typically the address holding the correct value of the descriptor and, therefore, is typically the address that the neural network **156** determines for the corresponding respective descriptor. Further in example, if a neural network **158** in the bottom layer **160** corresponds to the descriptor “color” and the feedforward neural network **156** determines that the color of the object is likely blue, then the neural network **158** in the bottom layer **160** generates a highest confidence value for an address of the database **152** in which is stored a value representing the color blue.

The inferencing service **174** receives the database addresses from the feedforward neural network **156**, and downloads, from the database **152**, the contents of these addresses, as well as the descriptors for all of the objects used for training the neural network **156**.

Then, the inferencing service **174** determines whether the detected object corresponding to the reshaped image segment **176** analyzed by the feedforward neural network **156** is the same as one of the training objects. The inferencing service **174** makes this determination by comparing, using a conventional comparison algorithm, the descriptor values for the training objects to the descriptor values that the feedforward neural network **156** returned for the detected object. If the descriptor values for the detected object match the descriptor values for one of the training objects, then the inferencing service **174** identifies the detected object as being the same as the corresponding training object. For example, if the corresponding training object is a bunkbed from a particular manufacturer and with a particular SKU, then the inferencing service **174** identifies the detected

object as being the same bunched from the same manufacturer and having the same SKU.

If the inferring service **174** determines that the detected object is likely the same as one of the training objects, then the inferring service provides, to the image-capture subsystem **90** via the ports **74** (FIG. **4**) and **94** (FIG. **5**) and the communication network **84** (FIGS. **4-5**) such as the internet or a cellular network, an object identifier that includes, for example, the likely manufacturer and the likely SKU of the detected object. The inferring service **174** may also provide, to the image-capture subsystem **90** via the ports **74** and **94** and the communication network **84**, a list of the likely descriptors for the detected object. An example of such a list is the list **58** of FIG. **3**.

If, however, the inferring service **174** determines that the detected object is unlikely to be the same as one of the training objects, then the inferring service provides, to the image-capture subsystem **90** via the ports **74** (FIG. **4**) and **94** (FIG. **5**) and the communication network **84** (FIGS. **4-5**), a list of the likely descriptors for the detected object. An example of such a list is the list **58** of FIG. **3**.

The inferring service **174** may also save **180** the object identifier, the list of likely descriptors, or both the object identifier and the list of likely descriptors in the database **152** for later reference. For example, as described above, if the detected object is an item of furniture, then the image-analysis subsystem **70** may perform an internet search for items of furniture having one or more descriptors that are similar to the stored (in the database **152**) likely descriptors of the detected object.

In response to either or both of the object identifier and the list of likely descriptors from the inferring service **174**, the SDK **170** generates an image representation of one or both of the object identifier and the list, and provides the image representation to the display device **100**, which effectively overlays the image representation onto the image. FIG. **3** is an example of a list **58** of descriptors overlaying an image **50**. Furthermore, the SDK **170** may also overlay the boundary box for the detected object onto the image displayed by the display device **100**.

The inferring service **174**, neural network **150**, and SDK **170** repeat the above object-detection procedure for each of the remaining image segments **172** in the image.

And the camera **96**, SSD NN model **162**, SDK **170**, inferring service **174**, and neural network **150** repeat the above image-capture-and-object-detection procedure for each subsequent image, regardless of whether the subsequent image is a still image or is part of a sequence of video images.

Referring to FIGS. **6-7**, the SDK **170** may also generate, and maintain, a "point cloud" (i.e., a three-dimensional map) of the space (e.g., the space **12** of FIGS. **1-3**) and of the detected objects within the space at a particular scale factor, such as the relative scale factor of the initial image.

From the relative locations, within an initial captured image, of the bounding boxes generated by the SSD NN model **162**, the SDK **170** generates an initial version of the point cloud, which includes the detected objects respectively corresponding to the bounding boxes.

The SDK **170** also tracks the movement of the camera **96**, for example, in response to an accelerometer (not shown in FIGS. **6-7**) or other sensor (also not shown in FIGS. **6-7**) that can measure and indicate camera movement, and tracks the zoom setting of the camera (if the camera has a zoom setting). The SDK **170** can use a conventional algorithm to track the camera movement in response to one or more

sensor signals from one or more of the sensors, and can receive the zoom setting from the camera **96** if the camera has a zoom setting.

From the relative locations, within a subsequent captured image, of the bounding boxes generated by the SSD NN model **162**, from the camera-movement information, and from the camera zoom setting, the SDK **170** updates the point cloud. For example, if the camera **96** moves out from the space, or zooms out, the objects in the space appear smaller, and more objects may enter the subsequent image. By tracking the camera movement and zoom setting, the SDK **170** can determine, for each detected object in the subsequent image, whether the object is the same as, or is different from, an object already in the point cloud. Consequently, the SDK **170** adds truly new objects to the point cloud, and is less likely to add "false" (already existing) objects to different locations in the point cloud due to mistaking an object already represented in the point cloud for a new object.

The SDK **170** further generates a geometric centroid for each object in the point cloud.

The SDK **170** can provide the point cloud to the image-analysis subsystem **70** via the ports **94** (FIG. **5**) and **74** (FIG. **4**) and a communication network **84** (FIGS. **4-5**), and the image-analysis subsystem **70** can use the point cloud to perform operations such as to propose furniture items and arrangements for the space represented by the point cloud.

The SDK **170** can also use the point cloud in a situation in which the neural net inferring service **174** does not provide an object identifier or object descriptors corresponding to a video image captured by the camera **96** until after the corresponding image is no longer displayed by the display device **100**. Assume that a subsequent captured image currently displayed by the display device **100** also includes the object, but at a different location. By tracking movement and zoom of the camera **96**, the SDK **170** can determine which detected object in the subsequent image corresponds to the object in the point cloud that also corresponds to the received object identifier or object descriptors, can generate an image representation of the object identifier, object descriptors, or both object identifier and descriptors, and can overlay the image representation anchored to the corresponding detected object in the currently displayed image.

Referring again to FIGS. **6-8**, alternate embodiments of the image-capture-and-analysis system **122**, and its functions and operation, are contemplated. For example, the system **122** may perform some or all of the above-described functions and operations with types of images other than light images; examples of such other images include sound images (e.g., sonograms), thermal images, vibration images, and infrared images. Furthermore, although described as detecting and analyzing items of furniture in images, the system **122** can be configured to detect and to analyze any other types of objects in images.

FIG. **9** is a diagram of the image-analysis-and-capture system **122** where the image-analysis subsystem **70** and the image-capture subsystem **90** are remote from one another, and the image-analysis subsystem resides in the "cloud" **180** on one or more "cloud" servers, according to an embodiment. The subsystems **70** and **90** communicate with one another via the port **94** and a communication network **182** such as the internet. The connection between the network **182** and the port **94** can be any type of conventional connection, such as a wired (e.g., Ethernet) or wireless (e.g., Bluetooth®, Wi-Fi®) connection. Furthermore, one or

more components, such as one or more routers, may be disposed between the port **94** and the network **182**.

From the foregoing it will be appreciated that, although specific embodiments have been described herein for purposes of illustration, various modifications may be made without deviating from the spirit and scope of the disclosure. Furthermore, where an alternative is disclosed for a particular embodiment, this alternative may also apply to other embodiments even if not specifically stated. In addition, a described component or operation may be implemented/ performed in hardware, in a circuit that executes software, in a circuit that is configured with firmware, or a combination of any two or more of hardware, circuit that executes software, and circuit that is configured with firmware. Furthermore, one or more components of a described apparatus or system may have been omitted from the description for clarity or another reason. Moreover, one or more components of a described apparatus or system that have been included in the description may be omitted from the apparatus or system.

Example 1 includes an image-capture subsystem, comprising: an image-capture device configured to capture a first image of a region of space that includes an object; and computing circuitry coupled to the image-capture device and configured to detect a representation of the object in the first image, to determine a representation of a boundary of the detected representation, to provide image information corresponding to the detected representation to an image-analysis system, to receive, from the image-analysis system, an identifier of a category to which the object belongs, and a descriptor of the object, and to generate a representation of a list that includes the identifier and the descriptor.

Example 2 includes the image-capture subsystem of Example 1 wherein the image-capture device includes a camera configured to capture a video sequence of images, the video sequence including the first image.

Example 3 includes the image-capture subsystem of any of Examples 1-2 wherein the computing circuitry is configured to implement a single-shot-detector convolutional neural network: to detect the representation of the object in the first image; and to determine a representation of a boundary of the detected representation.

Example 4 includes the image-capture subsystem of any of Examples 1-3, further comprising a display device coupled to the computing circuitry and configured: to display the first image; and to display the boundary and the list over the displayed first image.

Example 5 includes the image-capture subsystem of any of Examples 1-4, further comprising: wherein the image-capture device is configured to capture a second image of the region, the second image being subsequent to the first image; and a display device coupled to the computing circuitry and configured to display the second image; and to display the boundary and the list over the displayed second image.

Example 6 includes the image-capture subsystem of any of Examples 1-5 wherein the computing circuitry is configured to generate a representation of the region of space in response to the first image.

Example 7 includes the image-capture subsystem of any of Examples 1-6, further comprising: wherein the image-capture device is configured to capture a second image of the region, the second image being subsequent to the first image; and wherein the computing circuitry is configured to generate a representation of the region of space in response to the first and second images.

Example 8 includes an image-analysis subsystem, comprising: computing circuitry configured to receive a portion

of an image, the portion representing an object, and to implement a tree of neural networks configured to determine, in response to the portion of the image, a category and a descriptor corresponding to the object.

Example 9 includes the image-analysis subsystem of Example 8 wherein the computing circuitry is configured to receive the portion of the image from an image-capture system.

Example 10 includes the image-analysis subsystem of any of Examples 8-9 wherein each of the neural networks includes a respective feed-forward neural network.

Example 11 includes the image-analysis subsystem of any of Examples 8-10 wherein the computing circuitry is configured to implement the neural networks such that the neural networks are configured to identify the object in response to the portion of the image.

Example 12 includes the image-analysis subsystem of any of Examples 8-11 wherein the computing circuitry is configured to implement the neural networks such that the neural networks are configured to determine, in response to the portion of the image, a stock-keeper's unit for the object.

Example 13 includes the image-capture subsystem of any of Examples 8-12 wherein the computing circuitry is configured: to receive the portion of the image from an image-capture system; and to provide a name of the category, and the descriptor, to the image-capture system.

Example 14 includes a system, comprising: first computing circuitry configured to detect a representation of an object in a first image; and second computing circuitry configured to determine, in response to image information corresponding to the detected representation, a category to which the object belongs, and a descriptor of the object.

Example 15 includes the system of Example 14 wherein the first computing circuitry is configured to implement a single-shot-detector convolutional neural network to detect the representation of an object.

Example 16 includes the system of any of Examples 14-15 wherein the image information describes pixels that form the detected representation of the object.

Example 17 includes the system of any of Examples 14-16 wherein the second computing circuitry is configured to implement feed-forward neural networks to determine the category to which the object belongs and the descriptor of the object.

Example 18 includes the system of any of Examples 14-17, further comprising: a display device; wherein the second computing circuitry is configured to provide an identifier of the category and the descriptor to the first computing circuitry; and wherein the first computing circuitry is configured to cause the display to display a combination of the first image and a list that includes the identifier and the descriptor.

Example 19 includes the system of any of Examples 14-18 wherein: the first computing circuitry is configured to determine a boundary of the detected representation of the object; the second computing circuitry is configured to provide an identifier of the category and to provide the descriptor to the first computing circuitry; and the first computing circuitry is configured to generate a representation of a second image that includes, the detected representation of the object; a representation of the determined boundary; and a representation of a list corresponding to the detected representation of the object and including the identifier and the descriptor.

Example 20 includes the system of any of Examples 14-19, further comprising: a display device; wherein the second computing circuitry is configured to provide an

identifier of the category, and the descriptor, to the first computing circuitry; and wherein the first computing circuitry is configured to determine a boundary of the detected representation of the object, to generate a representation of the determined boundary, to generate a representation of a list corresponding to the detected representation of the object and including the identifier and the descriptor, and to cause the display device to display the first image and to display, over the first image, the determined boundary and the list.

Example 21 includes a method, comprising: detecting a first representation of an object in a first image; and determining, in response to image information corresponding to the detected first representation, a category to which the object belongs, and a descriptor of the object.

Example 22 includes the method of Example 21 wherein detecting includes detecting a representation of an object using a neural network.

Example 23 includes the method of any of Examples 21-22 wherein detecting includes detecting a representation of an object using a single-shot-detector convolutional neural network.

Example 24 includes the method of any of Examples 21-23 wherein the image information includes information describing pixels that form the detected representation of the object.

Example 25 includes the method of any of Examples 21-24 wherein the image information includes a pixel map of the detected representation of the object.

Example 26 includes the method of any of Examples 21-25 wherein determining includes determining the category to which the object belongs and the descriptor of the object using neural networks.

Example 27 includes the method of any of Examples 21-26 wherein determining includes determining the category to which the object belongs and the descriptor of the object using feed-forward neural networks.

Example 28 includes the method of any of Examples 21-27, further comprising generating a representation of the first image that includes: the first representation of the object; and a list corresponding to the detected first representation of the object and including the determined category and the determined descriptor.

Example 29 includes the method of any of Examples 21-28, further comprising: capturing a second image of the object; detecting a second representation of the object in the second image; and generating a representation of the second image that includes the second representation of the object; and a list corresponding to the detected first representation of the object and including the determined category and the determined descriptor.

Example 30 includes the method of any of Examples 21-29, further comprising: determining a boundary of the detected first representation of the object; and generating a representation of the first image that includes, the detected first representation of the object, a representation of the determined boundary, and a representation of a list corresponding to the detected first representation of the object and including the determined category and the determined descriptor.

Example 31 includes the method of any of Examples 21-30, further comprising: determining a boundary of the detected first representation of the object; capturing a second image of the object; detecting a second representation of the object in the second image; and generating a representation of the second image that includes, the detected second representation of the object, a representation of the deter-

mined boundary, and a representation of a list corresponding to the detected first representation of the object and including the determined category and the determined descriptor.

Example 32 includes the method of any of Examples 21-31, further comprising: determining a boundary of the detected first representation of the object; generating a representation of the determined boundary; generating a representation of a list corresponding to the detected first representation of the object and including the determined category and the determined at least one descriptor; displaying the first image; and displaying over the first image the determined boundary and the list.

Example 33 includes the method of any of Examples 21-32, further comprising: determining a boundary of the detected first representation of the object; generating a representation of the determined boundary; capturing a second image of the object; detecting a second representation of the object in the second image; generating a representation of a list corresponding to the detected first representation of the object and including the determined category and the determined at least one descriptor; displaying the second image; and displaying over the second image the determined boundary and the list.

Example 34 includes the method of any of Examples 21-33, further comprising: generating, in response to the first image and the detected representation of the object, a three-dimensional representation of the region including the object; detecting a representation of an object in a second image of the region of space subsequent to the first image; determining a relative distance between the representation of the object in the first image and the representation of the object in the second image; determining whether the object in the first image is the same object in the second image in response to the relative distance; updating the three-dimensional representation of the region in a first manner if the object in the first image is determined to be the same as the object in the second image; and updating the three-dimensional representation of the region in a second manner if the object in the first image is determined to be different from the object in the second image.

Example 35 includes the method of any of Examples 21-34 wherein the object includes an item of furniture.

Example 36 includes a method, comprising: capturing a first image of a region of space that includes an object; detecting a representation of the object in the first image; determining a representation of a boundary of the detected representation; providing image information corresponding to the detected representation to an image-analysis system; receiving, from the image-analysis system, an identifier of a category to which the object belongs, and a descriptor of the object; and generating a representation of a list that includes the identifier and the descriptor.

Example 37 includes a method, comprising: receiving a portion of an image, the portion representing an object; and implementing a tree of neural networks configured to determine, in response to the portion of the image, a category and a descriptor corresponding to the object.

Example 38 includes a non-transitory computer-readable medium storing instructions that, when executed by one or more computing circuits, cause the one or more computing circuits, or one or more other circuits under control of the one or more computing circuits: to detect a first representation of an object in a first image; and to determine, in response to image information corresponding to the detected first representation, a category to which the object belongs, and a descriptor of the object.

23

Example 39 includes a non-transitory computer-readable medium storing instructions that, when executed by one or more computing circuits, cause the one or more computing circuits, or one or more other circuits under control of the one or more computing circuits: to capture a first image of a region of space that includes an object; to detect a representation of the object in the first image; to determine a representation of a boundary of the detected representation; to provide image information corresponding to the detected representation to an image-analysis system; to receive, from the image-analysis system, an identifier of a category to which the object belongs, and a descriptor of the object; and to generate a representation of a list that includes the identifier and the descriptor.

Example 40 includes a non-transitory computer-readable medium storing instructions that, when executed by one or more computing circuits, cause the one or more computing circuits, or one or more other circuits under control of the one or more computing circuits: to receive a portion of an image, the portion representing an object; and to implement a tree of neural networks configured to determine, in response to the portion of the image, a category and a descriptor corresponding to the object.

Example 41 includes a method, comprising: generating respective image segments of each of one or more objects in response to respective electronic representations of the one or more objects; combining a respective image segment of each of at least one of the one or more objects with an image of a space to generate a first combined image; changing at least one parameter of the first combined image to generate a second combined image; and training at least one neural network with the first and second combined images.

Example 42 includes the method of Example 41 wherein at least two of the respective image segments of one of the one or more objects represent respective orientations of the one of the one or more objects.

Example 43 includes the method of any of Examples 41-42 wherein at least two of the respective image segments of one of the one or more objects represent respective textures of the one of the one or more objects.

Example 44 includes the method of any of Examples 41-43 wherein at least one of the respective electronic representations includes an electronic drawing file for the corresponding object.

Example 45 includes the method of any of Examples 41-44 wherein at least one of the respective electronic representations includes an electronic computer-aided-design file for the corresponding object.

Example 46 includes the method of any of Examples 41-45 wherein the image of the space includes a high-dynamic-range image of the space.

Example 47 includes the method of any of Examples 41-46 wherein the at least one parameter includes a lighting condition of the combined image, the lighting condition including at least one of a lighting-source location, a lighting intensity, a lighting pattern, and a number of lighting sources.

Example 48 includes the method of any of Examples 41-47 wherein the at least one parameter includes a camera condition of the combined image, the camera condition including at least one of a camera angle, camera zoom, f-stop, color balance, contrast, focus, and color temperature.

Example 49 includes the method of any of Examples 41-48 wherein the at least one neural network includes a convolutional-neural-network feature detector.

24

Example 50 includes the method of any of Examples 41-49 wherein the at least one neural network includes a single-shot-detector.

Example 51 includes the method of any of Examples 41-50 wherein the at least one neural network includes a feedforward neural network.

The invention claimed is:

1. A method for generating at least one synthetic training image, the method comprising:

receiving an image;

receiving at least one three-dimensional representation of an object;

implementing, using a rendering engine, at least one instruction for altering at least one parameter of the at least one three-dimensional representation of the object;

generating at least one synthetic training image that includes at least the altered parameter of the three-dimensional representation of the object;

associating metadata with the at least one synthetic training image;

populating the image with the synthetic training image that includes at least the altered parameter of the three-dimensional representation of the object;

generating a second synthetic training image using at least the populated image; and

storing the associated metadata and the second synthetic training image in memory.

2. The method of claim 1, wherein the three-dimensional representation of an object is at least one of a computer-aided-design (CAD) electronic file, a point cloud, or a portion of a first synthetic training image.

3. The method of claim 1, wherein altering at least one parameter comprises adjusting at least one lighting condition of the three-dimensional representation of the object.

4. The method of claim 1, wherein altering at least one parameter comprises adjusting a sensor parameter.

5. The method of claim 4, wherein the adjusting the sensor parameter includes altering at least one of a light, sound, infrared, or thermal parameter.

6. The method of claim 1, wherein altering at least one parameter comprises adjusting an orientation of the three-dimensional representation of the object.

7. The method of claim 5, further comprising creating a two-dimensional representation of the three-dimensional representation of the object having an adjusted orientation.

8. The method of claim 4, wherein the adjusting the sensor parameter replicates a camera condition, the camera condition including at least one of a camera angle, a resolution, a bit depth, a dynamic range, a camera zoom, f-stop, color balance, contrast, focus, and color temperature.

9. The method of claim 1, wherein the at least one instruction for altering the at least one parameter alters one or more of a space between the object and a second object, a number of objects within a space, an object orientation, a lighting condition, a texture of the object, and a feature of the object.

10. The method of claim 1, further comprising:

a. storing the associated metadata and the at least one synthetic training image using at least the populated image in memory.

11. The method of claim 1, wherein the received image is at least one of a still image, a sequence of images, a satellite image, or a high-dynamic-range (HDR) image.

12. The method of claim 1, wherein generating the second synthetic training image further comprises:

a. receiving at least one sensor condition; and

25

b. adjusting at least one image parameter based at least in part on the received at least one sensor condition.

13. The method of claim 1, further comprising:

a. implementing at least one instruction for altering at least one parameter of the at least one three-dimensional representation of the object of the at least one synthetic training image to generate at least one second synthetic training image;

b. associating metadata with the at least one second synthetic training image;

c. storing the associated metadata and the at least one second synthetic training image in memory; and

d. training at least one neural network to recognize at least one portion of the object using the at least one synthetic training image and the at least one second synthetic training image.

14. The method of claim 13, wherein the at least one altered parameter is a texture of the first synthetic training image.

15. The method of claim 13, wherein the at least one altered parameter includes at least one lighting condition of the first synthetic training image.

16. The method of claim 13, wherein the at least one altered parameter includes at least one camera condition of the synthetic training image.

17. The method of claim 13, wherein implementing the at least one instruction generates a substantially random set of statistically independent parameters of the object.

18. The method of claim 17, wherein the at least one instruction includes at least a user input.

19. The method of claim 13, wherein generating the at least one second synthetic training image includes applying a texture map to the object.

20. The method of claim 1, wherein the associated metadata further comprises a category, a common category, one or more descriptors, an object identifier, a list of objects within the first synthetic training image, a pixel map, or an object pairing.

21. A method for randomly generating a plurality of synthetic training images, the method comprising:

receiving an image;

receiving at least one three-dimensional representation of an object;

implementing at least one instruction for altering one or more parameters of the at least one three-dimensional representation of the object;

26

generating at least one synthetic training image that includes at least the altered parameter of the three-dimensional representation of the object, wherein the at least one synthetic training image includes a statistically independent spread of the one or more parameters amongst the plurality of synthetic training images;

associating metadata with the at least one synthetic training image; populating the image with the synthetic training image that includes at least the altered parameter of the three-dimensional representation of the object; and

generating a second synthetic training image using at least the populated image receiving at least one three-dimensional representation of an object; and

storing the associated metadata and the second synthetic training image in memory.

22. The method of claim 21, wherein the associating metadata further comprises extracting the metadata from at least one of a list, embedded metadata within a file containing the at least one three-dimensional representation of the object, or metadata from a server.

23. The method of claim 21, further comprising: receiving image data relating to the at least one three-dimensional representation of the object;

altering at least one parameter of the image data relating to the at least one three-dimensional representation of the object;

generating at least one synthetic image that includes at least the altered parameter of the image data relating to the at least one object; and

associating metadata with the at least one synthetic image.

24. The method of claim 21, wherein the received image is at least one of a still image, a sequence of images, a satellite image, or a high-dynamic-range (HDR) image.

25. The method of claim 21, further comprising receiving image information including one or more of: a category of at least one object within the image, at least one descriptor of the at least one object within the image, an identifier, or sensor information of the received image.

26. The method of claim 21, further comprising training at least one neural network to recognize at least one portion of the object using at least the first synthetic training image.

27. The method of claim 21, wherein the at least one neural network further performs a grouping action of at least one object in a plurality of synthetic training images into at least one hierarchal cluster.

* * * * *