



US010390676B2

(12) **United States Patent**
Woo et al.

(10) **Patent No.:** **US 10,390,676 B2**
(45) **Date of Patent:** **Aug. 27, 2019**

(54) **DISH WASHER INCLUDING A SWITCHING UNIT FOR DIVERTING WATER FLOW**

(56) **References Cited**

(71) Applicant: **LG Electronics Inc.**, Seoul (KR)
(72) Inventors: **Seyoung Woo**, Seoul (KR); **Joonho Pyo**, Seoul (KR); **Daegy Kim**, Seoul (KR)
(73) Assignee: **LG Electronics Inc.**, Seoul (KR)

U.S. PATENT DOCUMENTS
5,464,482 A 11/1995 Michael et al.
8,210,191 B2* 7/2012 Gnadinger A47L 15/23
134/172
8,578,954 B2* 11/2013 Rappette A47L 15/22
134/172

(Continued)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 651 days.

CN 103356143 A 10/2013
CN 105266736 1/2016

(Continued)

(21) Appl. No.: **15/013,049**

OTHER PUBLICATIONS

(22) Filed: **Feb. 2, 2016**

Chinese Office Action in Chinese Application No. 201610065270. X, dated Feb. 23, 2018, 23 pages.

(65) **Prior Publication Data**

US 2016/0220090 A1 Aug. 4, 2016

(Continued)

(30) **Foreign Application Priority Data**

Feb. 2, 2015 (KR) 10-2015-0016157
Feb. 2, 2015 (KR) 10-2015-0016158
Apr. 15, 2015 (KR) 10-2015-0053149

Primary Examiner — Rita P Adhlakha
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A dishwasher may include a tub configured to accommodate one or more items to be washed, a spray arm rotatably mounted to the tub, and configured to spray water onto the one or more items to be washed, a sump disposed at a bottom surface of the tub and configured to store water and to supply stored water to the spray arm, a fixed gear unit fixed to the tub with gear teeth arranged along an outer circumferential surface of the fixed gear unit, a rotary gear unit rotatably mounted on the spray arm and configured to engage the gear teeth of the fixed gear unit, and a link member connected to the rotary gear unit and the spray arm, where the spray arm may include, a main arm with a pair of arms, and a pair of auxiliary arms rotatably connected to the main arm.

(51) **Int. Cl.**

A47L 15/23 (2006.01)
A47L 15/22 (2006.01)
A47L 15/42 (2006.01)


(52) **U.S. Cl.**

CPC *A47L 15/23* (2013.01); *A47L 15/22* (2013.01); *A47L 15/4282* (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

15 Claims, 33 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0146734 A1 6/2011 Rappette et al.
2012/0279536 A1 11/2012 Adams et al.
2013/0091908 A1 4/2013 Lee
2013/0276841 A1 10/2013 Han
2015/0230687 A1* 8/2015 Dries A47L 15/4221
134/200

FOREIGN PATENT DOCUMENTS


CN 105266739 1/2016
DE 102010038184 6/2011
EP 1040787 10/2000
EP 2522268 11/2012
JP 08089467 4/1996
JP 2782943 8/1998
JP 3437241 6/2003
JP 2015-009011 1/2015
KR 10-2012-0078276 7/2012
KR 10-2012-0134370 12/2012
KR 10-2013-0110867 10/2013
KR 10-2013-0119086 10/2013
KR 10-2014-0039747 4/2014

OTHER PUBLICATIONS

Extended European Search Report in European Application No. 1605080.1, dated Mar. 6, 2017, 7 pages (with English translation).
Extended European Search Report in European Application No. 16205085.0, dated Mar. 6, 2017, 6 pages (with English translation).
Extended European Search Report in European Application No. 16205082.7, dated Feb. 24, 2017, 7 pages (with English translation).
Chinese Office Action in Chinese Application No. 201710152474.1, dated Aug. 29, 2018, 9 pages.

* cited by examiner

FIG. 1



S

FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36





FIG. 37



**DISH WASHER INCLUDING A SWITCHING
UNIT FOR DIVERTING WATER FLOW****CROSS-REFERENCE TO RELATED
APPLICATION(S)**

The present application claims priority under 35 U.S.C. 119 and 35 U.S.C. 365 to Korean Patent Application No. 10-2015-0016157 (filed on Feb. 2, 2015), No. 10-2015-0016158 (filed on Feb. 2, 2015) and No. 10-2015-0053149 (filed on Apr. 15, 2015), which are hereby incorporated by references in their entirety.

BACKGROUND

A dishwasher is a household appliance which uses detergent and water to wash food scraps off dirty dishes and cooking utensils.

Generally, a dishwasher includes a tub, a dish rack disposed in the tub to accommodate objects to be washed, a spray arm to spray wash water to the dish rack, a sump to store the wash water, and a supply flow passage to supply the wash water stored in the sump to the spray arm.

An idea related to the dishwasher is disclosed in Korean Patent Application Publication No. 10-2012-0126598, which is a related art document.

The dishwasher disclosed in the related art document has a structure for spraying wash water upward by a nozzle of a spray arm accommodated in a tub.

SUMMARY

According to one aspect, a dishwasher may include a tub configured to accommodate one or more items to be washed, a spray arm rotatably mounted to the tub and configured to spray water onto the one or more items to be washed, a sump disposed at a bottom surface of the tub and configured to store water and to supply stored water to the spray arm, a fixed gear unit fixed to the tub with gear teeth arranged along an outer circumferential surface of the fixed gear unit, a rotary gear unit rotatably mounted on the spray arm and configured to engage the gear teeth of the fixed gear unit, and a link member connected to the rotary gear unit and the spray arm, where the spray arm may include a main arm including a pair of arms, and a pair of auxiliary arms rotatably connected to the main arm, where the rotary gear unit may be configured to rotate based on engagement with the gear teeth of the fixed gear unit by rotation of the main arm, and where the link member may be configured to move by rotation of the rotary gear unit and rotate the pair of auxiliary arms.

Implementations according to this aspect may include one or more of the following features. For example, the dishwasher may include one or more power transfer units configured to extend from bottom surfaces of the pair of auxiliary arms and configured to be inserted into the link member, where one or more locking parts may be located at the link member, and where one or more power transfer units may be configured to be inserted into the one or more locking parts to transfer power to the power transfer units. The dishwasher may include a protrusion provided at an eccentric position from a center of rotation of the rotary gear unit and configured to be inserted into the link member, where the link member may include an insertion part, and where the protrusion may be configured to be inserted into the insertion part. The protrusion may be configured to move in a circular motion by the rotation of the rotary gear unit to

move the link member. The dishwasher may include a guide protrusion inserted into the link member and configured to guide the link member to move back and forth in a linear motion, where a guide unit, into which the guide protrusion is inserted, may be located at a main extension part. The link member may include a main extension part disposed at lower portions of the pair of arms disposed at the main arm and one or more auxiliary extension parts disposed at lower portions of the pair of auxiliary arms. Each of the one or more auxiliary extension parts may be elastically deformed in a direction of a movement of the link member. The one or more auxiliary extension parts may be configured to be bent several times. One or more stoppers may be disposed at the auxiliary extension parts, and may be configured to limit rotational ranges of the pair of auxiliary arms. The gear teeth disposed at the fixed gear unit and the rotary gear unit may have asymmetrical shapes and may include a vertical portion and an inclined portion which extends from an upper end of the vertical portion at a predetermined angle. The spray arm may be configured to rotate by a repulsive force generated based on water being sprayed through spray holes in the main arm or each of the pair of the auxiliary arms.

According to another aspect, a dishwasher may include a sump configured to store water, an arm holder rotatably mounted on the sump, a spray arm connected to the arm holder and configured to spray the stored water from the sump, a fixed gear unit fixed to the sump and with gear teeth arranged along an outer circumferential surface of the fixed gear unit, a rotary gear unit rotatably mounted on the spray arm, and configured to rotate based on engagement with the gear teeth of the fixed gear unit, and a link member connected to the rotary gear unit and the spray arm, where the spray arm includes a main arm with a lower frame connected to the arm holder and an upper frame disposed at an upper side of the lower frame, and a pair of auxiliary arms rotatably disposed at both sides of the main arm and having a plurality of auxiliary spray holes, where inlets through which the water is introduced are formed at the lower frame, wherein a main flow passage is formed in the main arm and may be in fluid communication with the inlets, where a plurality of upper spray holes may be formed in the upper frame, and where the plurality of spray holes may be configured to spray the water in the main flow passage, where the plurality of upper spray holes may be radially disposed in the upper frame.

Implementations according to this aspect may include one or more of the following features. For example, the plurality of upper spray holes may be biased to one side of the main arm, and where the spray arm may be configured to rotate in one direction by a repulsive force generated when the water is sprayed through the main spray holes and the plurality of auxiliary spray holes may be biased to the other side of the main arm, and where the spray arm may be configured to rotate in an opposite direction by the repulsive force generated when the water is sprayed. A subset of the plurality of upper spray may be parallel to a direction in which the water is sprayed. A subset of the plurality of auxiliary spray holes may be parallel to the direction in which the water is sprayed. The dishwasher may include lower spray holes formed in a bottom surface of the lower frame, and configured to spray the water flowing in the main flow passage. A transfer flow passage may be formed in the main arm and may be in fluid communication with the inlets, where auxiliary flow passages may be formed in the auxiliary arms and may be in fluid communication with the transfer flow passage, and where the auxiliary flow passages may be in fluid communication with the auxiliary spray holes. The

3

dishwasher may include a flow passage switching unit accommodated in the arm holder, and configured to selectively open and close the main flow passage and the transfer flow passage.

The flow passage switching unit may include a switching unit main body, an upper gear formed at the switching unit main body, and opening holes through which the water flows, where an upper gear engaging unit may be disposed at the bottom surface of the main arm, and may be configured to engage with the upper gear, where the flow passage switching unit may be configured to be engaged with the upper gear engaging unit when a flow amount of the water introduced into an arm holder chamber is increased, where one of the main flow passage and the transfer flow passage may be configured to communicate with the opening holes to have the water introduced and the other one of the main flow passage and the transfer flow passage may be closed by the switching unit main body when the upper gear is engaged with the upper gear engaging unit. A lower gear protruding downward may be disposed at the flow passage switching unit, and where a lower gear engaging unit may be disposed at a bottom surface of the arm holder chamber, and may be configured to be engaged with the lower gear. A rotary unit configured to provide a rotary force to the flow passage switching unit may be disposed at a bottom surface of the flow passage switching unit. The main arm may include a gear rotation shaft onto which the rotary gear unit is inserted, where the rotary gear unit may be configured to move vertically based on insertion into the gear rotation shaft so that the gear teeth of the fixed gear unit and the gear teeth of the rotary gear unit are selectively engaged with each other. The dishwasher may include an elastic unit disposed at the rotary gear unit, and configured to press the rotary gear unit toward the fixed gear unit. The gear teeth of the rotary gear unit may be configured to come in close contact with the gear teeth of the fixed gear unit by the hydraulic pressure of the water when the water is sprayed through the spray holes. The dishwasher may include a mounting unit at which the gear rotation shaft may be disposed and with a bottom surface portion configured to selectively make contact with an upper surface portion of the rotary gear unit, where the bottom surface portion of the mounting unit may be formed in a shape gradually inclined more upward from the gear rotation shaft toward the fixed gear unit. The spray holes may be disposed in the gear rotation shaft so that the wash water sprayed through the spray holes heads toward an inside of the rotary gear unit. The gear rotation shaft may be disposed at a place where a portion of a bottom surface of the main arm is recessed by a predetermined depth, where the gear rotation shaft may be inserted into the rotary gear unit and a rotation shaft accommodation unit may be disposed at the rotary gear unit, where at least a portion of the rotation shaft accommodation unit may be accommodated in the recessed place.

According to yet another aspect, a dishwasher may include a sump configured to store water, an arm holder rotatably mounted on the sump, a spray arm connected to the arm holder, and configured to rotate by a repulsive force generated when the stored water introduced from the sump is sprayed, a fixed gear unit fixed to the sump and with gear teeth arranged along an outer circumferential surface of the fixed gear unit, a rotary gear unit rotatably mounted on the spray arm, and configured to rotate based on engagement with the gear teeth of the fixed gear unit by rotation of the spray arm, and a link member connected to the rotary gear unit and the spray arm, where the spray arm includes a main arm including an arm holder coupling unit connected to the

4

arm holder, a first arm extending to one side of the arm holder coupling unit, and a second arm extending to the other side of the arm holder coupling unit, and a first auxiliary arm and a second auxiliary arm disposed at the main arm in opposite directions from each other, and each of the first auxiliary arm and the second auxiliary arm is configured to rotate with respect to a longitudinal direction.

Implementations according to this aspect may include one or more of the following features. For example, the first auxiliary arm may be configured to form an acute angle with the first arm, and the second auxiliary arm may be configured to form an acute angle with the second arm. The link member may be configured to move back and forth by the rotary gear unit when the spray arm rotates, and the back and forth movements of the link member may be converted to rotary movements of the auxiliary arms. A plurality of auxiliary spray holes may be formed in the first auxiliary arm and the second auxiliary arm, where at least one of the plurality of auxiliary spray holes formed in the first auxiliary arm and at least one of the plurality of auxiliary spray holes formed in the second auxiliary arm are parallel to a direction in which the water is sprayed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an example of a dishwasher implementation;

FIG. 2 is a view illustrating an example of a coupling structure between a sump of FIG. 1 and a spray arm assembly;

FIG. 3 is an exploded perspective view of an example of the spray arm assembly of FIG. 2;

FIG. 4 is a cross-sectional view of an example of the spray arm assembly of FIG. 2 taken along line I-I';

FIG. 5 is a view illustrating an example of a bottom surface of the spray arm of FIG. 3;

FIG. 6 is an exploded view of an example of the spray arm of FIG. 5;

FIG. 7 is a plan view of an example of a fixed gear unit of FIG. 3;

FIG. 8 illustrates an example of the fixed gear unit of FIG. 7;

FIG. 9 is a perspective view of an example of an arm holder of FIG. 3;

FIG. 10 is a plan view of an example of the arm holder of FIG. 9;

FIG. 11 is a side view of an example of the arm holder of FIG. 10;

FIG. 12 is a perspective view of an example of a flow passage switching unit of FIG. 3;

FIG. 13 illustrates an example of the flow passage switching unit of FIG. 12;

FIG. 14 is a perspective view of an example of a rotary gear unit of FIG. 3;

FIG. 15 is a perspective view of an example of a link member of FIG. 3;

FIG. 16 is a plan view of an example of the link member of FIG. 15;

FIGS. 17 to 20 are views illustrating an example of an order of assembling the spray arm assembly of FIG. 3;

FIG. 21 is a view illustrating an example of a state in which an upper gear of the flow passage switching unit is engaged with the spray arm;

FIG. 22 is a view illustrating an example of a state in which a lower gear of the flow passage switching unit is engaged with the arm holder;

5

FIG. 23 is a view illustrating an example of the bottom surface of the spray arm assembly in accordance with a rotational angle of the rotary gear unit;

FIG. 24 is a side view of an example of the spray arm assembly of FIG. 23;

FIG. 25 is a view illustrating an example of a state in which wash water is sprayed through a main arm;

FIG. 26 is a view illustrating an example of a state in which the wash water is sprayed through auxiliary arms;

FIG. 27 is a cross-sectional view taken along line II-II' of FIG. 25;

FIG. 28 is a view illustrating an example of a state in which the wash water is sprayed through the auxiliary arm and the auxiliary arm rotates back and forth at the same time;

FIG. 29 is a view illustrating an example of a state in which a link member of a spray arm assembly implementation is mounted on a spray arm;

FIG. 30 is a view illustrating an example of a state in which a link member of a spray arm assembly implementation is mounted on a spray arm;

FIG. 31 is a view illustrating an example of a state in which a fixed gear unit and a rotary gear unit of a spray arm assembly implementation are engaged with each other;

FIG. 32 is a view illustrating an example of a state in which a fixed gear unit and a rotary gear unit of a spray arm assembly implementation are engaged with each other;

FIG. 33 is a view illustrating an example of a state in which a fixed gear unit and a rotary gear unit of a spray arm assembly implementation are engaged with each other;

FIG. 34 is a view illustrating an example of a state in which the gear coupling between the fixed gear unit and the rotary gear unit of FIG. 33 is released;

FIG. 35 is a longitudinal cross-sectional view of an example of the spray arm assembly of FIG. 33;

FIG. 36 is a view illustrating an example of a state in which a fixed gear unit and a rotary gear unit of a spray arm assembly implementation are engaged with each other; and

FIG. 37 is a longitudinal cross-sectional view of an example of the spray arm assembly of FIG. 36.

DETAILED DESCRIPTION

Referring to FIGS. 1 and 2, a dishwasher 1 may include a tub 2 in which a washing space is formed, a door 3 which may be configured to selectively open and close the washing space, a rack 4 disposed in the tub 2 to accommodate an object to be washed, a sump 5 disposed in the tub 2 to store wash water, and a spray arm assembly 10 disposed in the tub 2 to spray the wash water onto the object to be washed accommodated in the rack 4.

The rack 4 may be mounted to be withdrawn to the front of the tub 2. A user may withdraw the rack 4 to the front of the tub 2 to accommodate the object to be washed.

The sump 5 may include a sump cover 20 and a sump discharge unit 30 disposed at the sump cover 20. The sump 5 may receive the wash water from the outside through a water supply unit 6, and may discharge the wash water sprayed in the tub 2 through the sump discharge unit 30. A water supply pump to transfer the wash water stored in the sump 5 to the spray arm assembly 10 may be disposed in the sump 5.

A wash water recovery unit 33 to recover the wash water sprayed in the tub 2 may be disposed at the sump discharge unit 30. Foreign substances such as food scraps contained in the wash water may be filtered by a filter disposed in the wash water recovery unit 33. The wash water recovered in the sump 5 through the wash water recovery unit 33 may be

6

resupplied to the spray arm assembly 10 by the water supply pump disposed in the sump 5. The wash water supplied through the water supply unit 6 may be reused several times.

The spray arm assembly 10 may be mounted on the sump cover 20 to spray the wash water stored in the sump 5 onto the object to be washed accommodated in the rack. The spray arm assembly 10 may include a spray arm 100 to spray the wash water, a fixed gear unit 200 mounted on the sump cover 20 to rotatably support the spray arm 100, and an arm holder 300.

The wash water introduced through the water supply unit 6 may flow through the sump 5 to be introduced into the spray arm assembly 10, and the wash water introduced into the spray arm assembly 10 may be sprayed by the spray arm 100 onto the object to be washed. The spray arm assembly 10 may be directly connected to the water supply unit 6 and directly spray the wash water onto the object to be washed without passing through the sump 5.

The spray arm assembly 10 may not only be disposed below the rack 4 as illustrated, but also be disposed above the rack 4. Also, the spray arm assembly 10 may be disposed in a plurality to spray the wash water from above and below the rack 4.

As illustrated in FIG. 3, the spray arm assembly 10 may include the spray arm 100, the fixed gear unit 200, the arm holder 300, a flow passage switching unit 400, a rotary gear unit 500, and a link member 600.

The spray arm 100 may include a main arm 110 and auxiliary arms 140 and 150 which may be rotatably connected to the main arm 110. The auxiliary arms 140 and 150 may be provided as one pair as illustrated. A plurality of flow passages through which the wash water provided from the sump 5 flows may be formed in the main arm 110.

Upper spray holes 123 and 124 through which the wash water introduced into the main arm 110 is sprayed, may be formed in an upper portion of the main arm 110. The wash water introduced into the main arm 110 from the sump 5 may be sprayed above the main arm 110 through the upper spray holes 123 and 124. The wash water sprayed through the upper spray holes 123 and 124 may head toward the object to be washed.

The main arm 110 may include an arm holder coupling unit 180 disposed at a bottom surface of the main arm 110 and may include at least a portion of the arm holder 300.

The auxiliary arms 140 and 150 may be rotated by the link member 600 within a predetermined angle range. Upper auxiliary spray holes 143 and 153 may be configured to spray the wash water introduced into the main arm 110. Upper auxiliary spray holes 143 and 153 may also be formed in the auxiliary arms 140 and 150.

The main arm 110 may include a first extension part 111 and a second extension part 112 radially extending with respect to the arm holder coupling unit 180. The auxiliary arms 140 and 150 may be respectively and rotatably mounted on the first extension part 111 and the second extension part 112.

A first transfer flow passage and a second transfer flow passage through which the wash water introduced from the sump 5 flows may be respectively formed in the first extension part 111 and the second extension part 112. The wash water flowing through the first transfer flow passage and the second transfer flow passage may flow to the auxiliary arms 140 and 150.

The auxiliary arms 140 and 150 may include a first auxiliary arm 140 rotatably connected to the first extension part 111, and a second auxiliary arm 150 rotatably connected to the second extension part 112. Some of the wash water

introduced into the main arm 110 may flow to a first auxiliary flow passage formed in the first auxiliary arm 140, and a second auxiliary flow passage formed in the second auxiliary arm 150.

A first upper auxiliary spray hole 143 may be formed in the first auxiliary arm 140, and a second upper auxiliary spray hole 153 may be formed in the second auxiliary arm 150. The wash water introduced into the first auxiliary flow passage formed in the first auxiliary arm 140 may be sprayed through the first upper auxiliary spray hole 143, and the wash water introduced into the second auxiliary flow passage formed in an inner space of the second auxiliary arm 150 may be sprayed through the second upper auxiliary spray hole 153.

The spray arm 100 may be rotated by a separate driving device. However, the spray arm 100 may be rotated by a repulsive force generated when the wash water is sprayed through upper spray holes 123 and 124 or the upper auxiliary spray holes 143 and 153. The spray arm 100 may be rotated by the repulsive force generated by spraying the wash water without a separate driving device such as a motor.

The rotation of the spray arm 100 by the spraying of the wash water will be described below. The main arm 110 may include a first arm 113 extending along one direction from a center of the main arm 110, and a second arm 114 extending along the opposite direction of the first arm 113. A first upper spray hole 123 may be formed in the first arm 113, and a second upper spray hole 124 may be formed in the second arm 114.

The first upper spray hole 123 may be formed in a plurality along a longitudinal direction of the first arm 113. The second upper spray hole 124 may be formed in a plurality along a longitudinal direction of the second arm 114.

The wash water introduced into the spray arm 100 may flow to the main arm 110, and be sprayed through the upper spray holes 123 and 124. The wash water introduced into the spray arm 100 may flow to the auxiliary arms 140 and 150, and be sprayed through the upper auxiliary spray holes 143 and 153.

The fixed gear unit 200 may be fixed to the sump cover 20 by a gear fixing unit 22 disposed at the sump cover 20. The fixed gear unit 200 is disposed to be engaged with the rotary gear unit 500.

The arm holder 300 may be coupled to the spray arm 100 and be fixed to the spray arm 100. Accordingly, the arm holder 300 may rotate together with the spray arm 100, and may serve as a central axis of rotation of the spray arm 100.

The arm holder 300 may be rotatably fixed to the sump cover 20 while being coupled to the spray arm 100. The wash water supplied from the sump 5 is supplied to the spray arm 100 after being introduced into the arm holder 300.

The arm holder 300 may be integrally formed with the main arm 110. In some examples, the main arm 110 may be rotatably fixed to the sump cover 20.

The flow passage switching unit 400 may be accommodated in the arm holder 300, and serve to switch the flow passage of the wash water supplied to the spray arm 100 from the arm holder 300. A detailed function of the flow passage switching unit 400 is described below.

The rotary gear unit 500 may be rotatably mounted on a bottom surface of the spray arm 100. When the spray arm 100 rotates, the rotary gear unit 500 may simultaneously move in a circular direction along a circumference of the fixed gear unit 200 fixed to the sump cover 20, and rotate by being engaged with the fixed gear unit 200.

The link member 600 may be mounted on the spray arm 100. The link member 600 may reciprocally rotate the auxiliary arms 140 and 150 about the longitudinal direction as the rotary gear unit 500 rotates. Referring to FIG. 4, the spray arm assembly 10 may be fastened to the sump cover 20. The arm holder 300 may be rotatably fixed to the sump cover 20 as a departure prevention part 315 disposed at the arm holder 300 may be fastened to an arm holder fastening part 23 disposed at the sump cover 20.

A fastening part 223 disposed at the fixed gear unit 200 may be fastened to the gear fixing unit 22 disposed at the sump cover 20. The fixed gear unit 200 may be coupled to the sump cover 20. Unlike the arm holder 300, the fixed gear unit 200 is non-rotatably fixed.

The rotary gear unit 500 may be inserted into a gear rotation shaft 135 disposed at the spray arm 100. The rotary gear unit 500 may be coupled to the spray arm 100, and may rotate about the gear rotation shaft 135.

The link member 600 may be supported by guide protrusions 136 and 137 disposed at the spray arm 100. An eccentric protrusion 530 disposed at the rotary gear unit 500 may be inserted into the link member 600. By the rotation of the fixed gear unit 200, the eccentric protrusion 530 may be configured to rotate the link member 600 back and forth within a predetermined range.

A fastening protrusion 182 disposed at the spray arm 100 may be inserted into a fastening protrusion accommodation unit 332 disposed at the arm holder 300. The arm holder 300 is coupled to the spray arm 100.

Main flow passages 117 and 118 through which the wash water introduced from the arm holder 300 flows may be formed in the spray arm 100. Specifically, the main flow passages 117 and 118 may include a first main flow passage 117 formed in the first arm 113, and a second main flow passage 118 formed in the second arm 114. The first main flow passage 117 and the second main flow passage 118 may be divided from each other by a partition 116. The wash water flowing through the first main flow passage 117 may be sprayed to the outside through the first upper spray hole 123, and the wash water flowing through the second main flow passage 118 may be sprayed to the outside through the second upper spray hole 124. The main flow passages 117 and 118 may be referred to as 'wash water flow passages.'

The flow passage switching unit 400 may be accommodated in an arm holder chamber 320 disposed in the arm holder 300. The flow passage switching unit 400 may move upward when the hydraulic pressure in the arm holder chamber 320 increases due to the wash water being introduced into the arm holder chamber 320, and the flow passage switching unit 400 may move downward when the hydraulic pressure in the arm holder chamber 320 decreases due to the introduction of the wash water into the arm holder chamber 320 being stopped.

In addition, the wash water accommodated in the arm holder chamber 320 may be introduced into the main arm 110.

Referring to FIGS. 5 and 6, the spray arm 100 may include the main arm 110, the auxiliary arms 140 and 150, and auxiliary arm connection members 160 to connect the main arm 110 to the auxiliary arms 140 and 150. The main arm 110 may include an upper frame 120 and a lower frame 130.

Lower spray holes 133 and 134 through which the wash water introduced into the main arm 110 is sprayed may be formed in the lower frame 130. The wash water introduced into the main arm 110 may be sprayed below the main arm 110 through the lower spray holes 133 and 134. The upper

spray holes **123** and **124** and the lower spray holes **133** and **134** may be collectively referred to as ‘main spray holes.’

A repulsive force may be generated below the main arm **110** when the wash water is sprayed upward from the upper spray holes **123** and **124**, and the repulsive force may be generated above the main arm **110** when the wash water is sprayed downward from the lower spray holes **133** and **134**. Thus, since the repulsive force acts above or below the main arm **110** when the wash water is sprayed through only one among the upper or lower spray holes, coupling of the spray arm assembly **10** may be difficult. The wash water introduced into the main arm **110** may be simultaneously sprayed through the upper spray holes **123** and **124** and the lower spray holes **133** and **134**, thereby offsetting the repulsive forces in the upper and lower directions acting on the main arm **110** due to the spraying of the wash water.

The main arm **110** may include a first outlet **111a** formed at the first extension part **111**, and a second outlet **112b** formed at the second extension part **112**. A portion of the wash water introduced into the main arm **110** through the sump **5** may be introduced into the first auxiliary arm **140** through the first outlet **111a**, and a portion may be introduced into the second auxiliary arm **150** through the second outlet **112b**.

As illustrated, the first auxiliary arm **140** may be disposed to form an acute angle with the first arm **113**, and the second auxiliary arm **150** may be disposed to form an acute angle with the second arm **114**. However, implementations are not limited to this shape, and the shape may be appropriately changed according to a design. For example, the first arm **113** and the second arm **114** may be disposed to form an acute angle, and the first auxiliary arm **140** and the second auxiliary arm **150** may be disposed to form an acute angle.

Lower auxiliary spray holes **144** and **154** may be formed in bottom surfaces of the auxiliary arms **140** and **150**. A first lower auxiliary spray hole **144** may be formed in the first auxiliary arm **140**, and a second lower auxiliary spray hole **154** may be formed in the second auxiliary arm **150**.

The wash water introduced into the auxiliary arms **140** and **150** may be simultaneously sprayed through the upper auxiliary spray holes **143** and **153** and the lower auxiliary spray holes **144** and **154**, thereby offsetting the repulsive forces in the upper and lower directions acting on the auxiliary arms **140** and **150** due to the spraying of the wash water.

The upper auxiliary spray holes **143** and **153** and the lower auxiliary spray holes **144** and **154** may be collectively referred to as ‘auxiliary spray holes.’

The main arm **110** may include the gear rotation shaft **135** inserted into the rotary gear unit **500** to serve as a rotation shaft of the rotary gear unit **500**. The gear rotation shaft **135** may protrude from the lower frame **130**. The gear rotation shaft **135** may be disposed at the bottom surface of the first arm **113** as illustrated, but the implementations are not limited thereto.

The spray arm **100** may include the guide protrusions **136** and **137** to guide a movement of the link member **600**. The guide protrusions **136** and **137** may include a first guide protrusion **136** disposed at the bottom surface of the first arm **113**, and a second guide protrusion **137** disposed at the bottom surface of the second arm **114**. The first guide protrusion **136**, the gear rotation shaft **135**, and the second guide protrusion **137** may be placed on one straight line.

The auxiliary arms **140** and **150** may include power transfer units **146** and **156** to receive power from the link member **600**. The power transfer units **146** and **156** may be formed of protrusions that protrude downward from the

bottom surfaces of the auxiliary arms **140** and **150**. A first power transfer unit **146** may be disposed at the first auxiliary arm **140**, and a second power transfer unit **156** may be disposed at the second auxiliary arm **150**.

The link member **600** may be configured to transfer the power received from the rotary gear unit **500** to the power transfer units **146** and **156**, thereby enabling the auxiliary arms **140** and **150** to rotate back and forth. The reciprocating movement of the link member **600** may be converted to the rotary movement of the auxiliary arms **140** and **150**.

The main arm **110** may include the arm holder coupling unit **180** disposed at the lower frame **130**. The arm holder coupling unit **180** may include an arm holder accommodation tube **181** into which the arm holder **300** is inserted, and the fastening protrusion **182** fastened to the arm holder **300**. The fastening protrusion **182** is fastened to the arm holder **300**, thereby enabling the main arm **110** to be fixed to the arm holder **300**.

The arm holder accommodation tube **181** may extend downward from the lower frame **130**. The arm holder accommodation tube **181** may be formed in a cylindrical shape, and may come in contact with the arm holder **300**.

The fastening protrusion **182** may be fastened to the arm holder **300**, thereby enabling the main arm **110** to be fixed to the arm holder **300**. The fastening protrusion **182** may be disposed in a plurality along an outer circumferential surface of the arm holder coupling unit **180**.

The main arm **110** may include a plurality of inlets **138a**, **138b**, **138c**, and **138d** through which the wash water supplied from the arm holder **300** is introduced. The plurality of inlets **138a**, **138b**, **138c**, and **138d** may be disposed at the lower frame **130**.

The plurality of inlets **138a**, **138b**, **138c**, and **138d** may include a first inlet **138a** communicating with the first main flow passage **117**, and a second inlet **138b** communicating with the second main flow passage **118**. The wash water introduced through the first inlet **138a** flows to the first main flow passage **117** to be sprayed through the spray holes **123** and **133** disposed in the first arm **113**, and the wash water introduced through the second inlet **138b** flows to the second main flow passage **118** to be sprayed through the spray holes **124** and **134** disposed in the second arm **114**.

The plurality of inlets **138a**, **138b**, **138c**, and **138d** may include a third inlet **138c** communicating with the first outlet **111a**, and a fourth inlet **138d** communicating with the second outlet **112b**.

The first transfer flow passage may be formed by the communication between the first outlet **111a** and the third inlet **138c**, and the second transfer flow passage may be formed by the communication between the second outlet **112b** and the fourth inlet **138d**. The first transfer flow passage and the second transfer flow passage may be divided from each other by the partition **116**.

The wash water introduced through the third inlet **138c** flows to the first auxiliary arm **140** via the first transfer flow passage to be sprayed through the spray holes **143** and **144** disposed in the first auxiliary arm **140**, and the wash water introduced through the fourth inlet **138d** flows to the second auxiliary arm **150** via the second transfer flow passage to be sprayed through the spray holes **153** and **154** disposed in the second auxiliary arm **150**.

An upper gear engaging unit **139** to which an upper gear of the flow passage switching unit **400** is engaged may be disposed at the lower frame **130**. The upper gear engaging unit **139** may be configured to rotate the flow passage switching unit **400** by a predetermined angle. The flow passage switching unit **400** may open or close each of the

inlets **138a**, **138b**, **138c**, and **138d** as the flow passage switching unit **400** is engaged with the upper gear engaging unit **139**. A principle of the flow passage switching unit **400** opening or closing the plurality of inlets **138a**, **138b**, **138c**, and **138d** will be described in detail below.

The auxiliary arm connection member **160** may include an insertion tube **162** inserted into the main arm **110**, an extension tube **164** communicating with the insertion tube **162** to have the wash water introduced from the insertion tube **162** flow therethrough, a shaft **166** connected to the extension tube **164**, and a protrusion **168** protruding from the shaft **166**.

A flow hole **167** may be formed between the extension tube **164** and the shaft **166**. The wash water introduced into the insertion tube **162** may be discharged through the flow hole **167** via the extension tube **164**. The wash water discharged through the flow hole **167** may flow to the inner spaces of the auxiliary arms **140** and **150** to be sprayed through the spray holes.

The spray arm **100** may not include the auxiliary arm connection member **160**. In this example, the auxiliary arms **140** and **150** may be directly and rotatably connected to the main arm **110**. The sagging of the auxiliary arms **140** and **150** may be prevented since loads of end portions thereof are supported by the auxiliary arm connection members **160**.

Referring to FIGS. **7** and **8**, the fixed gear unit **200** may include a rim part **210** including a plurality of gear teeth **213**, and a support part **220** extending downward from the rim part **210**. The arm holder coupling unit **180** may be inserted into the rim part **210**. The plurality of gear teeth **213** may be referred to as a first gear unit **213**.

The rim part **210** may include a gap reduction protrusion **215** to reduce a gap between the rim part **210** and the arm holder coupling unit **180**. The gap reduction protrusion **215** may be provided in a plurality and may protrude toward a center of the rim part **210**.

The support part **220** may be disposed at both sides of the rim part **210**. The support part **220** may include the fastening part **223** coupled to the sump cover **20**. The fastening part **223** may be formed of a protrusion protruding from a side surface of the support part **220**. The fastening part **223** may be fastened to the sump cover **20**, thereby enabling the fixed gear unit **200** to be fixed to the sump cover **20**.

The support part **220** may further include a handle part **225** that may be gripped when coupling or detaching the fixed gear unit **200** to or from the sump cover **20**. The handle part **225** may extend in a radial direction of the fixed gear unit **200**. At least a portion of a surface of the handle part **225** may be protruded or recessed for a user to easily grip the handle part **225**.

Referring to FIGS. **9** to **11**, the arm holder **300** may include an introduction unit **310** into which the wash water stored in the sump **5** is introduced, the arm holder chamber **320** communicating with the introduction unit **310**, and supplying the wash water introduced from the introduction unit **310** to the spray arm **100**, and a coupling unit **330** for coupling to the spray arm **100**.

A wash water inlet **313** through which the wash water stored in the sump **5** is supplied may be formed at the introduction unit **310**. Accordingly, the wash water stored in the sump **5** may be introduced into the arm holder **300** via the wash water inlet **313**.

The introduction unit **310** may include the departure prevention part **315** to prevent the arm holder **300** from departing from the sump cover **20**. The departure prevention part **315** may be formed by an end portion of the introduction unit **310** being flared. The departure prevention part **315**

may be fastened to the sump cover **20** by the arm holder fastening part **23** (refer to FIG. **20**) to be described below. The introduction unit **310** may be rotatably fixed to the sump cover **20**.

The introduction unit **310** may further include a sealing unit **317** to prevent the leakage of the wash water introduced from the sump **5**. The sealing unit **317** may be formed of ribs formed along an outer circumferential surface of the introduction unit **310**. By the sealing unit **317**, most of the wash water supplied from the sump **5** may be introduced into the arm holder **300**.

The arm holder chamber **320** may include an inlet tube **321**. The inlet tube **321** may be formed in a cylindrical shape, as illustrated. A hole communicating with the wash water inlet **313** may be formed on a bottom surface of the arm holder chamber **320**. The arm holder chamber **320** may be accommodated in the arm holder coupling unit **180**. An outer circumferential surface of the arm holder chamber **320** may come in contact with an inner circumferential surface of the arm holder coupling unit **180**. A space between the arm holder coupling unit **180** and the arm holder chamber **320** may be sealed, thereby preventing the leakage of the wash water introduced into the spray arm **100** from the arm holder **300**.

The flow passage switching unit **400** may be accommodated in the arm holder chamber **320**. The wash water introduced into the arm holder chamber **320** may be selectively introduced through the plurality of inlets **138a**, **138b**, **138c**, and **138d** by the flow passage switching unit **400**.

A lower gear engaging unit **323** engaged with a lower gear of the flow passage switching unit **400** may be disposed at the arm holder chamber **320**. The lower gear engaging unit **323** may be coupled to the lower gear of the flow passage switching unit **400** and serve to rotate the flow passage switching unit **400** by a predetermined angle.

The lower gear engaging unit **323** may be disposed in a plurality along an edge of a bottom surface **322** of the arm holder chamber **320**. Specifically, four lower gear engaging units **323** may be provided and may be disposed at 90° intervals with respect to the wash water inlet **313**.

The coupling unit **330** may be disposed at the outer circumferential surface of the arm holder chamber **320**. The coupling unit **330** may include a seating unit **331** on which the arm holder coupling unit **180** is seated, the fastening protrusion accommodation unit **332** disposed at the seating unit **331** and coupled to the fastening protrusion **182**, and a gap reduction protrusion **334** disposed at an outer circumferential surface of the coupling unit **330** to reduce a gap with the fixed gear unit **200**.

Referring to FIGS. **12** and **13**, the flow passage switching unit **400** according to an implementation includes a switching unit main body **410**, an upper gear disposed at an upper surface of the switching unit main body **410**, and a lower gear **430** disposed at a lower surface of the switching unit main body **410**. The upper gear may include a plurality of upper gears **421**, **422**, **423**, and **424**.

The switching unit main body **410** may be accommodated in the inlet tube **321** of the arm holder chamber **320**, and may vertically move back and forth in the arm holder chamber **320** in accordance with the hydraulic pressure in the arm holder chamber **320**. The switching unit main body **410** may be formed in a disk shape to correspond to a cross-sectional shape of the inlet tube **321**.

Opening holes **413** and **414** through which the wash water introduced into the arm holder chamber **320** flows may be disposed in the switching unit main body **410**. When the plurality of upper gears **421**, **422**, **423**, and **424** are engaged

with the upper gear engaging unit **139**, the opening holes **413** and **414** may communicate with any one of the plurality of inlets **138a**, **138b**, **138c**, and **138d**.

The plurality of upper gears **421**, **422**, **423**, and **424** being provided may be disposed at 90° intervals with respect to a center **C** of the switching unit main body **410**.

In addition, the plurality of upper gears **421**, **422**, **423**, and **424** may be spaced a predetermined distance apart from the center **C** of the switching unit main body **410**, and an edge portion of the switching unit main body **410**. The opening holes **413** and **414** may be respectively formed between the two upper gears **421** and **423** facing each other and the edge portion of the switching unit main body **410**.

The plurality of upper gears **421**, **422**, **423**, and **424** may include first and third upper gears **421** and **423** disposed adjacent to the opening holes **413** and **414**, and second and fourth upper gears **422** and **424** disposed to face each other between the first and third upper gears **421** and **423**.

Introduction prevention units **422a** and **424a** may be configured to come in close contact with the plurality of inlets **138a**, **138b**, **138c**, and **138d** to prevent the wash water from being introduced through the plurality of inlets **138a**, **138b**, **138c**, and **138d** may be formed at one side of each of the second and fourth upper gears **422** and **424**.

The lower gear **430** may be engaged with the lower gear engaging unit **323** disposed at the arm holder chamber **320**. Four lower gears **430** may be provided, and may be disposed at 90° intervals with respect to the center **C** of the switching unit main body **410**.

Each of the lower gears **430** may include two inclined surfaces **433** and **434** and a peak **435** formed between the two inclined surfaces **433** and **434**. Each of the inclined surfaces **433** and **434** may extend by 45° from a circumference of the switching unit main body **410**.

The flow passage switching unit **400** may further include a protrusion **436** disposed at a side surface portion of the switching unit main body **410** to prevent a foreign substance from being caught between the flow passage switching unit **400**, and the inner circumferential surface of the arm holder chamber **320**. The protrusion **436** may be provided in a plurality. The protrusion **436** may also be disposed at a side surface portion of the lower gear **430**.

The flow passage switching unit **400** may include a rotary unit **440** disposed at a bottom surface portion of the switching unit main body **410**. The rotary unit **440** may be configured to enable the flow passage switching unit **400** to rotate by the wash water introduced through the bottom surface of the flow passage switching unit **400**. The flow passage switching unit **400** may rotate by predetermined angle units by the hydraulic pressure without a separate driving device and selectively open and close the plurality of inlets **138a**, **138b**, **138c**, and **138d**. The rotary unit **440** may include a shaft **441** and an impeller **443** disposed at the shaft **441**.

Referring to FIG. **14**, the rotary gear unit **500** may include a rim part **510** having a plurality of gear teeth **513** disposed along an outer circumferential surface thereof, a rotation shaft accommodation unit **520** in which the gear rotation shaft **135** may be accommodated, and the eccentric protrusion **530** inserted into the link member **600** to move the link member **600** back and forth. The plurality of gear teeth **513** may be referred to as a second gear unit **513**.

The rotation shaft accommodation unit **520** may be disposed in the rim part **510**, and have the gear rotation shaft **135** inserted therein. The rotation shaft accommodation unit **520** may extend toward an upper side of the rotary gear unit **500** (a lower side of the rotary gear unit in FIG. **14**).

The eccentric protrusion **530** may be disposed at a bottom surface of the rotation shaft accommodation unit **520** (the upper side of the rotary gear unit in FIG. **14**). The eccentric protrusion **530** may extend from the bottom surface of the rotary gear unit **500** in a direction of a rotation axis **s** of the rotary gear unit **500**. The rotation axis **s** corresponds to a center of rotation of the rotary gear unit **500**, and may be provided at the center of the rim part **510**. In some examples, the eccentric protrusion **530** may also be disposed at the rim part **510**.

Referring to FIGS. **15** and **16**, the link member **600** may include a ring-shaped rim part **610**, and a plurality of extension parts **620**, **630**, **640**, and **650** extending in a radial direction from the rim part **610**.

An insertion hole **612** into which the arm holder coupling unit **180** may be inserted may be formed at the rim part **610**. The insertion hole **612** may be formed in an oval shape. The arm holder coupling unit **180** may move along a direction of a longitudinal axis **612a** of the insertion hole **612**.

Notch units **614** and **615** may be formed in an outer circumferential surface of the rim part **610**. The notch units **614** and **615** may be formed such that the shape of the link member **600** corresponds to the shape of the spray arm **100**. Also, by forming the notch units **614** and **615**, a user is enabled to easily grip the link member **600**.

The rim part **610** may further include a reinforcement rib **617** to reinforce the strength of the rim part **610**. The reinforcement rib **617** may be formed along a circumferential direction of the rim part **610** and may protrude upward.

The plurality of extension parts **620**, **630**, **640**, and **650** may include a first main extension part **620** located below the first arm **113**, a second main extension part **630** located below the second arm **114**, a first auxiliary extension part **640** located below the first auxiliary arm **140**, and a second auxiliary extension part **650** located below the second auxiliary arm **150**.

A first guide part **623** into which the first guide protrusion **136** may be inserted may be formed in the first main extension part **620**, and a second guide unit **633** into which the second guide protrusion **137** may be inserted may be formed in the second main extension part **630**. The first and second guide protrusions **136** and **137** respectively, may move back and forth along directions of longitudinal axes **623a** and **633a** of the first and second guide parts **623** and **633**, while being inserted into the first and second guide parts **623** and **633**.

A first locking part **643** into which the first power transfer unit **146** may be inserted may be formed in the first auxiliary extension part **640**, and a second locking part **653** into which the second power transfer unit **156** may be inserted may be formed in the second auxiliary extension part **650**. Since the first and second power transfer units **146** and **156** are respectively inserted into the first and second locking parts **643** and **653**, the movement of the link member **600** may be transferred to the auxiliary arms **140** and **150** via the power transfer units **146** and **156**.

The first main extension part **620** may further include a recessed part **624** configured to avoid interfering with the rotary gear unit **500**. An insertion part **625** into which the eccentric protrusion **530** of the rotary gear unit **500** may be inserted may be formed in the recessed part **624**. The insertion part **625** may be formed in a shape of a long hole as illustrated. In some examples, the insertion part **625** may be formed in a shape of a long groove.

The first main extension part **620** may further include contact units **627a**, **627b**, and **627c** coming in contact with the rim part **510** of the rotary gear unit **500**. The contact units

627a, 627b, and 627c may be formed of a rib protruding from a surface of the recessed part 624. The contact units 627a, 627b, and 627c may be disposed such that a contact area between the rotary gear unit 500 and the first main extension part 620 is reduced. Accordingly, friction generated between the rotary gear unit 500 and the first main extension part 620 when the rotary gear unit 500 rotates may be decreased.

Referring to FIGS. 17 to 20, the spray arm 100 may be first coupled to the rotary gear unit 500 (refer to FIG. 17). The rotary gear unit 500 may be inserted into the gear rotation shaft 135 disposed at the spray arm 100.

The link member 600 may be additionally mounted on the spray arm 100 (refer to FIG. 18). The link member 600 may be first connected to the power transfer units 146 and 156, and then connected by the guide protrusions 136 and 137. The link member 600 may be connected to four points of the spray arm 100. The eccentric protrusion 530 of the rotary gear unit 500 may be inserted into the insertion part 625 of the recessed part 624.

The first power transfer unit 146 may be inserted into the first locking part 643. The first power transfer unit 146 may include a departure prevention rib 146a to prevent the power transfer unit 146 from departing from the first locking part 643. The departure prevention rib 146a may extend toward the center of the spray arm 100 as illustrated. The second power transfer unit 156 may include a departure prevention rib with the same shape as the departure prevention rib 146a disposed in the first power transfer unit 146.

The second guide protrusion 137 may be inserted into the second guide unit 633. The second guide protrusion 137 may be formed of two elastic bodies 137a and 137b as illustrated. End portions of the two elastic bodies 137a and 137b may extend along a horizontal direction to prevent the second guide protrusion 137 from departing from the second guide unit 633. When the second guide protrusion 137 is inserted into the second guide unit 633, the two elastic bodies 137a and 137b may be bent in directions approaching each other. After the second guide protrusion 137 is inserted into the second guide unit 633, the two elastic bodies 137a and 137b are restored to original states due to elasticity. The first guide protrusion 136 may be formed with the same shape as the second guide protrusion 137.

The fixed gear unit 200 may be additionally coupled to the spray arm 100 (refer to FIG. 19). The fixed gear unit 200 may be mounted to surround the circumference of the arm holder coupling unit 180. The arm holder coupling unit 180 may be inserted into the rim part 210 of the fixed gear unit 200. The gear teeth of the fixed gear unit 200 may be engaged with the gear teeth of the rotary gear unit 500. The fastening part 223 may be fastened to the sump cover 20 such that the fixed gear unit 200 is fixed to the sump cover 20.

The number of the gear teeth of the fixed gear unit 200 and the number of the gear teeth of the rotary gear unit 500 may be designed to be relatively prime. Accordingly, after the rotary gear unit 500 makes one revolution around the circumference of the fixed gear unit 200, the rotary gear unit 500 and the fixed gear unit 200 are not engaged with each other at the same position.

The arm holder 300 may be additionally coupled to the spray arm 100 (refer to FIG. 20). First, after the arm holder 300 is inserted into the arm holder coupling unit 180, the fastening protrusion 182 may be accommodated in the fastening protrusion accommodation unit 332 when the arm

holder 300 is rotated by a predetermined angle. Accordingly, the arm holder 300 may be coupled to the arm holder coupling unit 180.

Referring to FIGS. 21 and 22, the flow passage switching unit 400 may be moved upward by the hydraulic pressure of the wash water introduced through the wash water inlet 313, and the plurality of upper gears 421, 422, 423, and 424 disposed at the flow passage switching unit 400 may be engaged with the upper gear engaging unit 139 disposed at the bottom surface of the spray arm 100. The wash water introduced into the inlet tube 321 may be introduced into the first main flow passage 117 via the first opening hole 413.

Simultaneously, the wash water introduced into the inlet tube 321 may be introduced into the second main flow passage 118 via the second opening hole 414. When the opening holes 413 and 414 communicate with the first and second inlets 138a and 138b, the wash water introduced into the inlet tube 321 may be simultaneously introduced into the main flow passages 117 and 118. Here, the third and fourth inlets 138c and 138d are closed by the switching unit main body 410. Accordingly, the introduction of the wash water through the first and second transfer flow passages is blocked. Simultaneously, the introduction of the wash water through the first and second auxiliary flow passages is also blocked.

When the introduction of the wash water through the wash water inlet 313 is stopped, force acting on the upper side of the flow passage switching unit 400 is removed and the flow passage switching unit 400 descends. Accordingly, the lower gear 430 disposed at the flow passage switching unit 400 is engaged with the lower gear engaging unit 323 disposed at the arm holder 300.

The flow passage switching unit 400 is rotated clockwise (or counterclockwise) by a predetermined angle due to the lower gear 430 being engaged with the lower gear engaging unit 323. Here, the flow passage switching unit 400 may be rotated by approximately 45°. This is due to the inclined surface 433 disposed at the lower gear 430 occupying as much as 45° of the circumference of the switching unit main body 410.

When the wash water is reintroduced through the wash water inlet 313 after the flow passage switching unit 400 descends, the flow passage switching unit 400 may ascend, causing the plurality of upper gears 421, 422, 423, and 424 to be re-engaged with the upper gear engaging unit 139. Here, the opening holes 413 and 414 may communicate with the third and fourth inlets 138c and 138d instead of the first and second inlets 138a and 138b. Accordingly, the wash water introduced into the inlet tube 321 is introduced through the third and fourth inlets 138c and 138d via the opening holes 413 and 414. The first and second inlets 138a and 138b are closed by the switching unit main body 410. Accordingly, the introduction of the wash water through the main flow passages 117 and 118 is blocked.

The sump 5 may intermittently supply the wash water when supplying the wash water through the wash water inlet 313. Specifically, the sump 5 may stop supplying the wash water for a predetermined amount of time after supplying the wash water to the arm holder 300 for a predetermined amount of time. That is, the sump 5 alternately performs the supplying of the wash water and the stopping of the supplying of the wash water. Consequently, as the flow passage switching unit 400 rotates while ascending and descending, the flow passage switching unit 400 may alternately open and close the main flow passages 117 and 118 and the first and second transfer flow passages.

In addition, a time during which the wash water is supplied to the main flow passages **117** and **118** through the sump and a time during which the wash water is supplied to the first and second transfer flow passages may be equally set.

Referring to FIGS. **23(a)** and **24(a)**, when the rotary gear unit **500** is in an initial unrotated state, the eccentric protrusion **530** is located at one side in the insertion part **625**. Here, the first auxiliary arm **140** is disposed parallel to the main arm **110**.

Referring to FIGS. **23(b)** and **24(b)**, when the rotary gear unit **500** has rotated counterclockwise by 90°, the link member **600** moves along a direction A among directions of the longitudinal axis **612a** by the eccentric protrusion **530**.

The first auxiliary extension part **640** applies a force to the first power transfer unit **146** due to the link member **600** moving along a direction of the longitudinal axis **612a**. Accordingly, the first auxiliary arm **140** may be rotated clockwise by a predetermined angle. A rotational angle of the first auxiliary arm **140** is approximately 20°.

Referring to FIGS. **23(c)** and **24(c)**, when the rotary gear unit **500** has further rotated counterclockwise by 90°, the link member **600** moves along a direction B which is opposite from the direction A of the longitudinal axis **612a**. Accordingly, the link member **600** may be restored to the position illustrated in FIGS. **23(a)** and **24(a)**. Simultaneously, the first auxiliary arm **140** may be restored to an original position after rotating counterclockwise by the first auxiliary extension part **640**.

Referring to FIGS. **23(d)** and **24(d)**, when the rotary gear unit **500** has further rotated counterclockwise by 90°, the link member **600** moves along the direction B among the directions of the longitudinal axis **612a** by the eccentric protrusion **530**. Here, the first auxiliary arm **140** may be rotated counterclockwise by a predetermined angle. The rotational angle of the first auxiliary arm **140** is approximately 20°.

Meanwhile, the second auxiliary arm **150** may simultaneously rotate by the same angle as the first auxiliary arm **140** due to the link member **600**. However, when viewed from the side, the second auxiliary arm **150** rotates along a direction opposite from the first auxiliary arm **140**.

Thus, the link member **600** may move back and forth within a distance between a top dead point and a bottom dead point of the eccentric protrusion **530** due to the rotation of the rotary gear unit **500**.

Since the fixed gear unit **200**, the rotary gear unit **500**, and the link member **600** interact with each other to rotate the auxiliary arms **140** and **150** back and forth, the fixed gear unit **200**, the rotary gear unit **500**, and the link member **600** may be collectively referred to as a 'rotation driving unit.'

Referring to FIGS. **25** to **28**, the main arm **110** may include the plurality of upper spray holes. Specifically, the first arm **113** may include a plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d**. The second arm **114** may also include a plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d**. When the main flow passages **117** and **118** are opened by the flow passage switching unit **400**, the wash water may be simultaneously sprayed through the plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d** and the plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d**.

At least a subset of the spray holes (**123a** and **123b**) of the plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d** may be biased such that a direction in which the wash water is sprayed forms an acute angle with the main arm **110**.

Accordingly, the spray arm **100** may rotate by a repulsive force generated due to the wash water being sprayed through the biased spray holes **123a** and **123b**. That is, a predetermined torque value may be generated at the spray arm **100** due to the wash water being sprayed through the biased spray holes **123a** and **123b**.

The other spray holes **123c** and **123d** among the plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d** are not biased and may spray the wash water in the vertical direction.

At least a few of the spray holes (**124a** and **124b**) of the plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d** may be biased such that the direction in which the wash water is sprayed forms an acute angle with the main arm **110**.

Accordingly, the spray arm **100** may rotate by a repulsive force generated due to the wash water being sprayed through the biased spray holes **124a** and **124b**. That is, a predetermined torque value may be generated at the spray arm **100** due to the wash water being sprayed through the biased spray holes **124a** and **124b**.

The torque acting on the spray arm **100** due to the wash water being sprayed through the biased spray holes **123a** and **123b** of the plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d** and the torque acting on the spray arm **100** due to the wash water being sprayed through the biased spray holes **124a** and **124b** of the plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d** have the same direction.

Meanwhile, the biased spray holes **123a** and **123b** of the plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d** and the biased spray holes **124a** and **124b** of the plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d** may be biased to spray the wash water in a tangential direction of a rotational trajectory of the spray arm **100**. In some examples, a rotary force caused by the spraying of the wash water may further increase.

The other spray holes **124c** and **124d** among the plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d** are not biased and may spray the wash water in the vertical direction.

The plurality of first upper spray holes **123a**, **123b**, **123c**, and **123d** and the plurality of second upper spray holes **124a**, **124b**, **124c**, and **124d** may be biased at different angles to spray the wash water at various angles. When the transfer flow passages are opened by the flow passage switching unit **400**, the wash water is sprayed through a plurality of first upper auxiliary spray holes **143a**, **143b**, **143c**, and **143d** and a plurality of second upper auxiliary spray holes **153a**, **153b**, **153c**, and **153d**.

Similar to the main arm **110**, the first auxiliary arm **140** may also include biased spray holes **143a** and **143b** and unbiased spray holes **143c** and **143d**. The second auxiliary arm **150** may also include biased spray holes **153a** and **153b** and unbiased spray holes **153c** and **153d**.

The biased spray holes **143a** and **143b** disposed in the first auxiliary arm **140** may be referred to as first biased spray holes **143a** and **143b**, and the biased spray holes **153a** and **153b** disposed in the second auxiliary arm **150** may be referred to as second biased spray holes **153a** and **153b**. The unbiased spray holes **143c** and **143d** disposed in the first auxiliary arm **140** may be referred to as first vertical spray holes **143c** and **143d**, and the unbiased spray holes **153c** and **153d** disposed in the second auxiliary arm **150** may be referred to as second vertical spray holes **153c** and **153d**.

A torque generated due to the wash water being sprayed through the first biased spray holes **143a** and **143b** may act

on the spray arm 100. A torque generated due to the wash water being sprayed through the second biased spray holes 153a and 153b may act on the spray arm 100.

Since the first auxiliary arm 140 and the second auxiliary arm 150 rotate in the same direction, a magnitude and a direction of the torque caused by the spraying of the wash water may change.

The biased spray holes are referred to as the first upper spray holes 123 and the second upper spray holes 124 for convenience. FIG. 27 illustrates a direction in which the wash water is sprayed through the second upper spray holes 124 of the second arm 114.

The second main flow passage 118 formed between the upper frame 120 and the lower frame 130 may be formed in the second arm 114. The wash water introduced through the arm holder 300 may flow to the second main flow passage 118, and be sprayed to the outside through the second upper spray holes 124.

The second upper spray holes 124 may be biased to face a left upper portion. Accordingly, a direction A1 of the wash water being sprayed through the second upper spray holes 124 may also face the left upper portion.

The direction A1 in which the wash water is sprayed through the second upper spray holes 124 is biased to form an acute angle with a rotation axis v of the spray arm 100 as illustrated. Accordingly, the spray arm 100 may rotate by the torque generated due to the wash water being sprayed through the second upper spray holes 124.

The first upper spray holes 123 disposed in the first arm 113 may also be biased similar to the second upper spray holes 124. The torques generated due to the wash water being sprayed through the first upper spray holes 123 and the second upper spray holes 124 simultaneously act on the spray arm 100.

Since the wash water is sprayed through the plurality of spray holes, a plurality of torques act on the spray arm 100. Consequently, a rotational direction of the spray arm 100 may change in accordance with a resultant force of the torques caused by the wash water sprayed through the first upper spray holes 123 and the second upper spray holes 124. However, when directions of the torque caused by the wash water being sprayed through the first upper spray holes 123 and the torque caused by the wash water sprayed through the second upper spray holes 124 are the same, the rotary force of the spray arm 100 may be further reinforced.

Referring to FIG. 28(a), the wash water is simultaneously sprayed through the first upper auxiliary spray hole 143 and the first lower auxiliary spray hole 144. A direction A2 in which the wash water is sprayed through the first upper auxiliary spray hole 143, and a direction A3 in which the wash water is sprayed through the first lower auxiliary spray hole 144 may face a right upper portion based on the drawings.

The directions A2 and A3 in which the wash water is sprayed through the first upper auxiliary spray hole 143, and the first lower auxiliary spray hole 144 may form acute angles with the rotation axis v of the spray arm 100. A clockwise torque may be applied to the spray arm 100 due to the wash water being sprayed through the first upper auxiliary spray hole 143 and the first lower auxiliary spray hole 144.

Referring to FIG. 28(b), even when the first auxiliary arm 140 has maximally rotated clockwise, the directions A2 and A3 in which the wash water is sprayed through the first upper auxiliary spray hole 143 and the first lower auxiliary spray hole 144 may face a right side with respect to the rotation axis v of the spray arm 100. Consequently, even

when the first auxiliary arm 140 has rotated clockwise, the clockwise torque may be applied to the spray arm 100.

Referring to FIG. 28(c), even when the first auxiliary arm 140 has maximally rotated counterclockwise, the directions A2 and A3 in which the wash water is sprayed through the first upper auxiliary spray hole 143 and the first lower auxiliary spray hole 144 may face a right side with respect to the rotation axis v of the spray arm 100. Consequently, even when the first auxiliary arm 140 has rotated counterclockwise, the clockwise torque may be applied to the spray arm 100.

However, the direction A2 in which the wash water is sprayed through the first upper auxiliary spray hole 143 may be almost parallel to the rotation axis v of the spray arm 100. In some examples, a problem is caused since a direction of the torque acting on the spray arm 100 may change.

Consequently, a rotational angle of the first auxiliary arm 140 should be smaller than a spraying angle of the first upper auxiliary spray hole 143. The spraying angle of the first upper auxiliary spray hole 143 refers to an angle formed by the direction A2 in which the wash water is sprayed through the first upper auxiliary spray hole 143 and the rotation axis v of the spray arm 100 when the first auxiliary arm 140 is unrotated.

In addition, the rotational angle of the first auxiliary arm 140 should be smaller than a spraying angle of the first lower auxiliary spray hole 144. The spraying angle of the first lower auxiliary spray hole 144 refers to an angle formed by the direction A3 in which the wash water is sprayed through the first lower auxiliary spray hole 144 and the rotation axis v of the spray arm 100 when the first auxiliary arm 140 is unrotated.

When the wash water is sprayed through the first vertical spray holes 143c and 143d, the rotation of the spray arm 100 may be almost unaffected. However, when the first auxiliary arm 140 rotates, a torque may act on the spray arm 100 due to the spraying of the wash water since a direction in which the wash water is sprayed through the first vertical spray holes 143c and 143d forms an acute angle with the spray arm 100.

Since the second auxiliary arm 150 also rotates by the same angle when the first auxiliary arm 140 rotates, directions in which the wash water is sprayed through the first vertical spray holes 143c and 143d and the wash water sprayed through the second vertical spray holes 153c and 153d may form the same angle. Consequently, even when the first auxiliary arm 140 and the second auxiliary arm 150 rotate, a torque value caused by the wash water being sprayed through the first vertical spray holes 143c and 143d and a torque value caused by the wash water being sprayed through the second vertical spray holes 153c and 153d are offset by each other.

Furthermore, since the first auxiliary arm 140 and the second auxiliary arm 150 simultaneously rotate by the same angle, the torque values may be offset by each other when the wash water sprayed through the first vertical spray holes 143c and 143d and the wash water sprayed through the second vertical spray holes 153c and 153d are parallel to each other. That is, the torque values acting on the spray arm 100 may be offset even when the wash water sprayed through the first vertical spray holes 143c and 143d and the wash water sprayed through the second vertical spray holes 153c and 153d are not perpendicular to each other as long as they are parallel to each other.

When the first auxiliary arm **140** and the second auxiliary arm **150** rotate, a spraying angle of the wash water decreases such that the maximum spraying height of the wash water may also decrease.

Consequently, the spray arm **100** may rotate counter-clockwise (this is referred to as ‘forward rotation’ or ‘one-way rotation’) when the wash water is sprayed through the main spray holes **123** and **124**, and the spray arm **100** may rotate clockwise (this is referred to as ‘reverse rotation’ or ‘other-way rotation’) when the wash water is sprayed through the auxiliary spray holes **143** and **153**.

Referring to FIG. **29**, the link member **1600** may include the ring-shaped rim part **610**, and a plurality of extension parts **620**, **630**, **1640**, and **1650** extending in the radial direction from the rim part **610**.

The plurality of extension parts **620**, **630**, **1640**, and **1650** may include a first auxiliary extension part **1640** and a second auxiliary extension part **1650** to rotate the auxiliary arms **140** and **150** back and forth. The first auxiliary extension part **1640** may include a first link **1641** extending from the rim part **610** and a second link **1642** connected to the first link **1641**. That is, the first auxiliary extension part **1640** may be formed in a shape that may be bent several times.

A connection unit **1643** for connecting the first link **1641** to the second link **1642** may be elastically deformed so that an angle θ between the first link **1641** and the second link **1642** changes by increasing or. Accordingly, the first auxiliary extension part **1640** may be elastically deformed within a predetermined angle range in a horizontal direction.

The first link **1641** or the second link **1642** may be formed of a material that may be elastically deformed. For example, the first link **1641** or the second link **1642** may be formed of an engineering resin material. The first auxiliary extension part **1640** may be elastically deformed within the predetermined angle range in the horizontal direction.

The rotation of the first auxiliary arm **140** may not be possible due to the sedimentation of foreign substances. When the rotation of the first auxiliary arm **140** is not possible, the movement of the link member **1600** may be limited, and thus the rotation of the spray arm **100** itself may also stop. When the first auxiliary extension part **1640** is elastically deformed by an angle of a predetermined range, a situation in which the rotation of the spray arm **100** itself is also stopped may be prevented even when the rotation of the first auxiliary arm **140** is not impossible.

The first auxiliary extension part **1640** may further include stoppers **1645a** and **1645b** to limit a rotational range of the first auxiliary arm **140**. The stoppers **1645a** and **1645b** respectively, may be disposed at both sides of the first auxiliary extension part **1640**.

The second auxiliary extension part **1650** may be formed in the same shape as the first auxiliary extension part **1640**.

Referring to FIG. **30**, the link member **2600** may include the ring-shaped rim part **610**, and a plurality of extension parts **620**, **630**, **2640**, and **2650** extending in the radial direction from the rim part **610**.

The plurality of extension parts **620**, **630**, **2640**, and **2650** may include a first auxiliary extension part **2640** and a second auxiliary extension part **2650** to rotate the auxiliary arms **140** and **150** back and forth. The first auxiliary extension part **2640** may include an elastic link **2641** extending from the rim part **610** and a power transfer unit **2643** disposed at an end portion of the elastic link **2641**.

The elastic link **2641** may be formed of a material that may be elastically deformed. The coefficient of elasticity of the elastic link **2641** may be set to be deformed by a torque amount generated due to the wash water being sprayed from

the first auxiliary arm **140**. The elastic link **2641** may be elastically deformed within a predetermined angle range in the horizontal direction. The elastic link **2641** may be elastically deformed in a direction parallel to a reciprocating direction in which the link member **2600** moves. When the rotations of the auxiliary arms **140** and **150** are not possible, the main arm **110** may be rotatable since the rotation of the rotary gear unit **500** is possible.

The first auxiliary extension part **2640** may further include stoppers **2645a** and **2645b** to limit the rotational range of the first auxiliary arm **140**. The stoppers **2645a** and **2645b** respectively, may be disposed at both sides of the power transfer unit **2643**.

The stoppers **2645a** and **2645b** may be formed of a rib that is formed by an extension of a portion of the first auxiliary extension part **2640**. When the first auxiliary arm **140** is rotated more than a predetermined range, the stoppers **2645a** and **2645b** come in contact with the first auxiliary arm **140** from both sides to limit the rotational range of the first auxiliary arm **140**.

The second auxiliary extension part **2650** may be formed in the same shape as the first auxiliary extension part **2640**.

Referring to FIG. **31**, a fixed gear unit **1200** and a rotary gear unit **1500** may be disposed to be engaged with each other.

The rotary gear unit **1500** includes a rotation shaft accommodation unit **1520** into which the gear rotation shaft **135** disposed at the spray arm **100** is inserted, and an eccentric protrusion **1530**. Unlike the above-mentioned implementations, the rotation shaft accommodation unit **1520** may protrude further upward.

The rotation shaft accommodation unit **1520** may include an elastic unit **1523**. The elastic unit **1523** may be compressed more than what is illustrated. Accordingly, gear coupling between the fixed gear unit **1200** and the rotary gear unit **1500** may be released due to the fixed gear unit **1200** being spaced apart upward.

The separation of the fixed gear unit **1200** and the rotary gear unit **1500** makes it possible to enable the spray arm **100** to be rotatable even when the rotation of the rotary gear unit **1500** is not possible due to a foreign substance being caught. This is because the rotary gear unit **1500** may limit the rotation of the spray arm **100** when the fixed gear unit **1200** and the rotary gear unit **1500** are engaged while the rotation of the rotary gear unit **1500** is not possible. In this specification, a separation of engaged gears to enable the spray arm **100** to be rotatable even when driving a particular element is not possible as above is referred to as ‘decoupling.’

The elastic unit **1523** may serve to press the rotary gear unit **1500** toward the fixed gear unit **1200** so that the rotary gear unit **1500** comes in close contact with the fixed gear unit **1200**. Accordingly, the gear coupling between the rotary gear unit **1500** and the fixed gear unit **1200** may become more firm.

The fixed gear unit **1200** may include a plurality of gear teeth **1213** formed in asymmetrical shapes. The gear teeth **1213** may include an inclined portion **1214** and a vertical portion **1215**. The rotary gear unit **1500** also includes a plurality of gear teeth **1513** formed in asymmetrical shapes. That is, the gear teeth **1513** include an inclined portion **1514** and a vertical portion **1515**.

Due to the gear teeth **1213** and **1513** disposed at the fixed gear unit **1200** and the rotary gear unit **1500** formed in the asymmetrical shapes, decoupling is possible when the rotary gear unit **1500** rotates clockwise around the fixed gear unit **1200** since the inclined portions **1214** and **1514** are engaged with each other, the decoupling is not possible when the

23

rotary gear unit **1500** rotates clockwise around the fixed gear unit **1200** since the vertical portions **1215** and **1515** are engaged with each other.

Referring to FIG. **32**, the fixed gear unit **1200** and the rotary gear unit **1500** may be disposed to be engaged with each other.

The rotary gear unit **1500** may include the rotation shaft accommodation unit **1520** into which the gear rotation shaft **135** disposed at the spray arm **100** is inserted, and the eccentric protrusion **1530**. Unlike the above-mentioned implementations, the rotation shaft accommodation unit **1520** may protrude further upward.

In addition, the rotation shaft accommodation unit **1520** may include an elastic unit **1540**.

The elastic unit **1540** may be vertically compressed. Accordingly, the rotary gear unit **1500** may vertically move. The gear coupling between the fixed gear unit **1200** and the rotary gear unit **1500** may be released due to the rotary gear unit **1500** being spaced apart at an upper side.

The separation of the fixed gear unit **1200** and the rotary gear unit **1500** makes it possible to enable the spray arm **100** to be rotatable even when the rotation of the rotary gear unit **1500** is not possible due to a foreign substance being caught.

This is because the rotation of the spray arm **100** may be limited due to the non-rotation of the rotary gear unit **1500** when the fixed gear unit **1200** and the rotary gear unit **1500** are engaged while the rotation of the rotary gear unit **1500** is not possible.

The elastic unit **1540** may serve to press the rotary gear unit **1500** toward the fixed gear unit **1200** so that the rotary gear unit **1500** comes in close contact with the fixed gear unit **1200**. Accordingly, the gear coupling between the rotary gear unit **1500** and the fixed gear unit **1200** may become more firm.

Meanwhile, the elastic unit **1540** may protrude upward from an upper surface of the rotary gear unit **1500** and may be configured in a plurality. A shape of the elastic unit **1540** is not limited.

Referring to FIGS. **33** to **35**, the spray arm assembly may include a main arm **2110**, a rotary gear unit **2500** rotatably mounted on the main arm **2110**, and a fixed gear unit **2200** engaged with the rotary gear unit **2500**.

Gear teeth **2513** may be disposed at the rotary gear unit **2500**, and gear teeth **2213** engaged with the gear teeth **2513** of the rotary gear unit **2500** may be disposed at the fixed gear unit **2200**.

An eccentric protrusion **2530** inserted into the link member **600** may be disposed at the rotary gear unit **2500**.

A mounting unit **2130** may be disposed at a lower portion of the main arm **2110**. A gear rotation shaft **2135** into which the rotary gear unit **2500** is inserted may be disposed at a bottom surface portion **2133** of the mounting unit **2130**. The gear rotation shaft **2135** may protrude downward from the bottom surface portion **2133** of the mounting unit **2130**.

The bottom surface portion **2133** of the mounting unit **2130** may selectively come in contact with an upper surface portion of the rotary gear unit **2500**.

The bottom surface portion **2133** of the mounting unit **2130** may be formed to become gradually higher from the gear rotation shaft **2135** toward the fixed gear unit **2200**. That is, the bottom surface portion **2133** of the mounting unit **2130** may be formed of a shape gradually inclined more upward toward a center of the main arm **2110**.

The rotary gear unit **2500** becomes vertically rotatable within a predetermined range by the above-mentioned shape of the bottom surface portion **2133** of the mounting unit **2130**, and accordingly, the gear coupling between the rotary

24

gear unit **2500** and the fixed gear unit **2200** may be released. That is, the decoupling may occur between the fixed gear unit **2200** and the rotary gear unit **2500**.

A height of the bottom surface portion **2133** of the mounting unit **2130** may be uniform along a direction becoming farther from the fixed gear unit **2200** at the gear rotation shaft **2135**.

The mounting unit **2130** may further include a spray hole **2137** through which a fluid such as the wash water is sprayed.

Some of the wash water flowing in a flow passage formed in the main arm **2110** may be discharged downward through the spray hole **2137**.

The spray hole **2137** may be disposed above a place P at which the gear teeth **2213** of the fixed gear unit **2200** and the gear teeth **2513** of the rotary gear unit **2500** are engaged with each other. Accordingly, the gear teeth **2213** of the fixed gear unit **2200** may receive a downward force by the hydraulic pressure of the wash water sprayed through the spray hole **2137**.

The spray hole **2137** may be disposed between the gear rotation shaft **2135** and the fixed gear unit **2200**. Accordingly, a gear coupling force may be reinforced at the place P due to the gear teeth **2213** of the fixed gear unit **2200** receiving a force biased toward the fixed gear unit **2200** by the hydraulic pressure of the wash water sprayed through the spray hole **2137**.

The hydraulic pressure caused by the wash water discharged through the spray hole **2137** may press the gear teeth **2513** of the rotary gear unit **2500** downward. Accordingly, the gear teeth **2513** of the rotary gear unit **2500** may come in close contact with the gear teeth **2213** of the fixed gear unit **2200**.

The spray arm assembly may reinforce the gear coupling force between the rotary gear unit **2500** and the fixed gear unit **2200** using the hydraulic pressure of the wash water discharged through the spray hole **2137**.

Referring to FIGS. **36** and **37**, the spray arm assembly may include a main arm **3110**, a rotary gear unit **3500** rotatably mounted on the main arm **3110**, and a fixed gear unit **3200** engaged with the rotary gear unit **3500**.

Gear teeth **3513** may be disposed at the rotary gear unit **3500**, and gear teeth **3213** engaged with the gear teeth **3513** of the rotary gear unit **3500** are disposed at the fixed gear unit **3200**.

An eccentric protrusion **3530** inserted into the link member **600** may be disposed at the rotary gear unit **3500**.

A gear rotation shaft **3135** onto which the rotary gear unit **3500** is inserted may be disposed at a lower portion of the main arm **3110**. The gear rotation shaft **3135** may protrude downward from a bottom surface of the main arm **3110**.

The rotary gear unit **3500** may include a rotation shaft accommodation unit **3520** in which the gear rotation shaft **3135** is accommodated. The rotation shaft accommodation unit **3520** may protrude above the rotary gear unit **3500**.

The gear rotation shaft **3135** may be disposed at a place where a portion of the bottom surface of the main arm **3110** is recessed by a predetermined depth. At least a portion of the rotation shaft accommodation unit **3520** may be accommodated in the recessed place.

Accordingly, the rotary gear unit **3500** may be prevented from departing from the gear rotation shaft **3135** while vertically moving.

The rotary gear unit **3500** may further include the elastic unit **1540** of FIG. **32**. The elastic unit **1540** may be disposed at the rotation shaft accommodation unit **3520**.

The rotary gear unit **3500** may vertically move while being inserted into the gear rotation shaft **3135**. Accordingly, the gear coupling between the rotary gear unit **3500** and the fixed gear unit **3200** may be released. That is, the rotary gear unit **3500** and the fixed gear unit **3200** may be decoupled.

Spray holes **3137** and **3138** through which a fluid such as the wash water is sprayed may be formed in the gear rotation shaft **3135**.

A flow passage of the main arm **3110** and a flow passage **3136** communicating with the spray holes **3137** and **3138** may be formed in the gear rotation shaft **3135**. Accordingly, the wash water flowing in the main arm **3110** may be sprayed through the spray holes **3137** and **3138** via the flow passage **3136** of the gear rotation shaft **3135**.

Some of the wash water flowing in the flow passage formed at the main arm **3110** may be discharged downward through the spray holes **3137** and **3138**.

The spray holes **3137** and **3138** may be formed in a lower portion of the gear rotation shaft **3135** to be disposed at an inner side **3540** of the rotary gear unit **3500**.

The hydraulic pressure caused by the wash water discharged through the spray holes **3137** and **3138** may press the inner side **3540** of the rotary gear unit **3500** downward.

The wash water sprayed to the inner side **3540** of the rotary gear unit **3500** may be discharged through an outlet formed at the rotary gear unit **3500**.

Accordingly, the rotary gear unit **3500** may be closely attached in a downward direction, and the gear teeth **3513** of the rotary gear unit **3500** may come in close contact with the gear teeth **3213** of the fixed gear unit **3200**.

That is, the spray arm assembly may reinforce the gear coupling force between the rotary gear unit **3500** and the fixed gear unit **3200** using the hydraulic pressure of the wash water discharged through the spray holes **3137** and **3138**.

The spray holes **3137** and **3138** may be disposed in a plurality. Specifically, the spray holes **3137** and **3138** may include a first spray hole **3137** and a second spray hole **3138**.

The first spray hole **3137** may be formed at a position near the gear teeth **3213** of the fixed gear unit **3200**, and the second spray hole **3138** may be disposed at a position distant from the gear teeth **3213** of the fixed gear unit **3200**.

In the dishwasher **1**, the non-rotation of the spray arm **100** may be prevented by the decoupling between the rotary gear unit and the fixed gear unit when the rotation of the rotary gear unit is not possible, thereby preventing a decline in washing efficiency.

Simultaneously, the gear coupling force between the rotary gear unit and the fixed gear unit is reinforced using the hydraulic pressure of the wash water sprayed through the spray hole, thereby preventing the gear coupling force between the rotary gear unit and the fixed gear unit from decreasing due to a structure for decoupling.

In this way, a spray angle in the dishwasher **1** may be varied due to the auxiliary arms **140** and **150** rotatably mounted on the main arm **110** and separately rotating from the rotation of the main arm **110**. Accordingly, the washing efficiency of the dishwasher **1** increases.

In addition, the spray arm **100** may be rotated by the repulsive force generated due to the wash water being sprayed through the spray hole, thereby not requiring a separate driving source.

In addition, the rotary force of the spray arm **100** may be converted to a force for rotating the auxiliary arms **140** and **150** back and forth by the interaction between the fixed gear unit **200**, the rotary gear unit **500**, and the link member **600**.

Consequently, there is an advantage of not requiring a separate driving source for rotating the auxiliary arms **140** and **150**.

Although implementations have been described with reference to a number of illustrative implementations thereof, it should be understood that numerous other modifications and implementations can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

What is claimed is:

1. A dishwasher comprising:

a sump configured to store water;

an arm holder rotatably mounted on the sump;

a spray arm connected to the arm holder and configured to spray the stored water from the sump;

a fixed gear unit fixed to the sump and with gear teeth arranged along an outer circumferential surface of the fixed gear unit;

a rotary gear unit rotatably mounted on the spray arm, and configured to rotate based on engagement with the gear teeth of the fixed gear unit; and

a link member connected to the rotary gear unit and the spray arm,

wherein the spray arm comprises:

a main arm provided on the sump, that is configured to extend in a first direction for spraying wash water, and that includes a lower frame connected to the arm holder, an upper frame disposed at an upper side of the lower frame and a transfer flow passage is formed in the main arm,

a pair of auxiliary arms configured to extend in a second direction while being spaced apart from the main arm by a predetermined angle for spraying wash water while rotating about a rotation axis defined by the second direction in which the auxiliary arms extend and including a plurality of auxiliary spray holes, and auxiliary flow passages are formed in the auxiliary arms and are in fluid communication with the transfer flow passage and the auxiliary spray holes,

wherein inlets through which the water is introduced are formed at the lower frame in fluid communication with the transfer flow passage,

wherein a main flow passage is formed in the main arm and is in fluid communication with the inlets,

wherein a plurality of upper spray holes are formed in the upper frame, and wherein the plurality of spray holes are configured to spray the water in the main flow passage, and

wherein the plurality of upper spray holes are radially disposed in the upper frame,

wherein the dishwasher further comprises a flow passage switching unit accommodated in the arm holder, and that is configured to selectively open and close the main flow passage and the transfer flow passage, and that includes a switching unit main body, an upper gear formed at the switching unit main body, and opening holes through which the water flows,

wherein an upper gear engaging unit is disposed at the bottom surface of the main arm, and is configured to engage with the upper gear, and

wherein the flow passage switching unit is configured to be engaged with the upper gear engaging unit when a flow amount of the water introduced into an arm holder chamber is increased.

2. The dishwasher according to claim 1, wherein the plurality of upper spray holes are biased to one side of the main arm, and wherein the spray arm is configured to rotate in one direction by a repulsive force generated when the water is sprayed through the upper spray holes; and the plurality of auxiliary spray holes are biased to the other side of the main arm, and wherein the spray arm is configured to rotate in an opposite direction by the repulsive force generated when the water is sprayed.

3. The dishwasher according to claim 2, wherein a subset of the plurality of upper spray holes are parallel to a direction in which the water is sprayed through the upper spray holes.

4. The dishwasher according to claim 2, wherein a subset of the plurality of auxiliary spray holes are parallel to the direction in which the water is sprayed through the upper spray holes.

5. The dishwasher according to claim 1, further comprising lower spray holes formed in a bottom surface of the lower frame, and configured to spray the water flowing in the main flow passage.

6. The dishwasher according to claim 1, wherein one of the main flow passage and the transfer flow passage is configured to communicate with the opening holes to have the water introduced and the other one of the main flow passage and the transfer flow passage is closed by the switching unit main body when the upper gear is engaged with the upper gear engaging unit.

7. The dishwasher according to claim 6, wherein a lower gear protruding downward is disposed at the flow passage switching unit, and

wherein a lower gear engaging unit is disposed at a bottom surface of the arm holder chamber, and is configured to be engaged with the lower gear.

8. The dishwasher according to claim 7, wherein a rotary unit configured to provide a rotary force to the flow passage switching unit is disposed at a bottom surface of the flow passage switching unit.

9. The dishwasher according to claim 1, wherein the main arm comprises a gear rotation shaft onto which the rotary gear unit is inserted,

wherein the rotary gear unit is configured to move vertically based on insertion into the gear rotation shaft so that the gear teeth of the fixed gear unit and gear teeth of the rotary gear unit are selectively engaged with each other.

10. The dishwasher according to claim 9, further comprising an elastic unit disposed at the rotary gear unit, and configured to press the rotary gear unit toward the fixed gear unit.

11. The dishwasher according to claim 9, wherein the gear rotation shaft is disposed at a place where a portion of a bottom surface of the main arm is recessed by a predetermined depth,

wherein the gear rotation shaft is inserted into the rotary gear unit and a rotation shaft accommodation unit is disposed at the rotary gear unit,

wherein at least a portion of the rotation shaft accommodation unit is accommodated in the recessed place.

12. The dishwasher according to claim 1, wherein the main arm comprises a gear rotation shaft onto which the rotary gear unit is inserted, and spray holes through which the wash water flowing in the main flow passage is sprayed, wherein the spray holes are disposed above the rotary gear unit so that a hydraulic pressure of the wash water discharged through the spray holes acts on the rotary gear unit.

13. The dishwasher according to claim 12, wherein gear teeth of the rotary gear unit are configured to come in close contact with the gear teeth of the fixed gear unit by the hydraulic pressure of the water when the water is sprayed through the spray holes.

14. The dishwasher according to claim 12, further comprising a mounting unit at which the gear rotation shaft is disposed and having a bottom surface portion configured to selectively make contact with an upper surface portion of the rotary gear unit,

wherein the bottom surface portion of the mounting unit is formed in a shape gradually inclined more upward from a gear rotation shaft toward the fixed gear unit.

15. The dishwasher according to claim 12, wherein the spray holes are disposed in a gear rotation shaft so that the wash water sprayed through the spray holes heads toward an inside of the rotary gear unit.

* * * * *