



(51) International Patent Classification:

A61B 18/00 (2006.01) A61B 17/28 (2006.01)

(21) International Application Number:

PCT/US2017/046019

(22) International Filing Date:

09 August 2017 (09.08.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/374,989 15 August 2016 (15.08.2016) US
15/671,200 08 August 2017 (08.08.2017) US

(71) Applicant: COVIDIEN LP [US/US]; 15 Hampshire Street, Mansfield, Massachusetts 02048 (US).

(72) Inventors: FRUSHOUR, Scott E.M.; 1805 Balsam Avenue, Boulder, Colorado 80304 (US). LARSON, Eric R.; 7355 Yucca Court, Boulder, Colorado 80301 (US).

(74) Agent: BEATON, Thomas A.; Attn: IP Legal, 5920 Longbow Drive, Boulder, Colorado 80301 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: ELECTROSURGICAL FORCEPS FOR VIDEO ASSISTED THORACOSCOPIC SURGERY AND OTHER SURGICAL PROCEDURES




FIG. 1

(57) Abstract: A surgical instrument includes a shaft defining an axis, an end effector coupled to a distal portion thereof, a fixed handle coupled to a proximal portion thereof, a drive bar, a movable handle, and a linkage. The drive bar is disposed within the shaft and operably coupled to the end effector. The movable handle is movable relative to the fixed handle between open and closed positions and is coupled to the drive bar via a first pin on the axis. The linkage includes a first end portion coupled to the movable handle via a second pin and a second end portion coupled to the shaft via a third pin on the axis. In the closed position of the movable handle, the second pin is disposed in a near-over-center position relative to the axis to reduce a force necessary to maintain the movable handle in the closed position.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

ELECTROSURGICAL FORCEPS FOR VIDEO ASSISTED THORACOSCOPIC SURGERY AND OTHER SURGICAL PROCEDURES

BACKGROUND

Technical Field

[0001] The present disclosure relates to surgical instruments and, more particularly, to an electrosurgical forceps configured for treating and/or cutting tissue in Video Assisted Thoracoscopic Surgery and other surgical procedures.

Background of Related Art

[0002] In minimally-invasive surgical procedures, operations are carried out within the body by elongated instruments inserted through small entrance openings in the body, either directly or through one or more access ports positioned within the entrance openings. Because the instrumentation and any required punctures or incisions are relatively small, minimally-invasive surgery is less invasive compared to conventional open surgical procedures. As a result, minimally-invasive surgery tends to minimize trauma to the patient, reduce patient recovery time, and minimize hospital costs.

[0003] In minimally-invasive thoracic surgery, for example, access to the thoracic cavity as well as maneuverability within the thoracic cavity is limited since the access port is typically placed within the confined intercostal space between a patient's ribs. Such procedures, commonly referred to as Video Assisted Thoracoscopic Surgery (VATS), aim to reduce patient recovery time by accessing the thoracic cavity through the natural intercostal space without

spreading the ribs as in open procedures. Procedures performed in this manner may include, for example, lung resection procedures.

[0004] Electrosurgical forceps utilize both mechanical clamping action and energy to treat, e.g., coagulate, cauterize, and/or seal, tissue. Typically, once tissue is treated, the treated tissue is divided by way of a knife or blade member incorporated into the electrosurgical forceps. Electrosurgical forceps are useful in VATS procedures such as, for example, lung resection procedures, where electrosurgical forceps may be utilized to treat and cut surrounding tissue, thus facilitating the isolation of lung tissue to be removed and reducing bleeding during the lung resection procedure.

[0005] It would therefore be advantageous to provide an electrosurgical forceps configured for use in VATS procedures and other surgical procedures, for example, to facilitate lung resection procedures.

SUMMARY

[0006] As used herein, the term “distal” refers to the portion that is being described which is further from a user, while the term “proximal” refers to the portion that is being described which is closer to a user. Further, to the extent consistent, any of the aspects described herein may be used in conjunction with any or all of the other aspects described herein.

[0007] In accordance with aspects of the present disclosure, a surgical instrument is provided. The surgical instrument includes an elongated shaft defining a longitudinal axis and including a proximal portion and a distal portion, an end effector assembly coupled to the distal portion of the elongated shaft, a fixed handle coupled to the proximal portion of the elongated shaft, a drive bar, a

movable handle, and a linkage. The drive bar is slidably disposed within the elongated shaft and operably coupled to the end effector assembly such that translation of the drive bar through the elongated shaft manipulates the end effector assembly. The movable handle is movable relative to the fixed handle between an open position and a closed position to translate the drive bar through the elongated shaft. The movable handle, more specifically, is pivotably coupled to the drive bar via a first pivot pin. The first pivot pin is aligned on the longitudinal axis. The linkage includes a first end portion and a second end portion. The first end portion of the linkage is pivotably coupled to the movable handle via a second pivot pin, while the second end portion of the linkage is pivotably coupled to the elongated shaft via a third pivot pin. The third pivot pin is aligned on the longitudinal axis. In the closed position of the movable handle, the second pivot pin is disposed in a near-over-center position relative to the longitudinal axis to reduce a force necessary to maintain the movable handle in the closed position.

[0008] In an aspect of the present disclosure, the elongated shaft defines a cut-out disposed therein configured to receive at least a portion of the second pivot pin in the near-over-center position of the second pivot pin.

[0009] In another aspect of the present disclosure, the movable handle, the fixed handle, and/or the elongated shaft inhibits the second pivot pin from reaching an over-the-center position relative to the longitudinal axis.

[0010] In yet another aspect of the present disclosure, the end effector assembly includes first and second jaw members. In such aspects, translation of

the drive bar through the elongated shaft moves the first and second jaw members between a spaced-apart position and an approximated position.

[0011] In still another aspect of the present disclosure, the near-over-center position of the second pivot pin corresponds to the approximated position of the first and second jaw members.

[0012] In still yet another aspect of the present disclosure, each of the first and second jaw members defines an electrically-conductive tissue-contacting surface adapted to connect to a source of energy. The tissue-contacting surfaces are configured to grasp tissue therebetween.

[0013] In another aspect of the present disclosure, the movable handle includes a clevis configured to couple at least a portion of the elongated shaft with at least a portion of the linkage. The first and second pivot pins extend within the clevis.

[0014] In another aspect of the present disclosure, the elongated shaft includes a pair of opposed slots defined therethrough. The first pivot pin extends through the opposed slots of the elongated shaft.

[0015] In still another aspect of the present disclosure, an activation assembly is disposed on the fixed handle or the movable handle. The activation assembly is selectively activatable to supply energy to the end effector assembly.

[0016] In yet another aspect of the present disclosure, the activation assembly is positioned such that the activation assembly is activated upon movement of the movable handle to the closed position.

[0017] In still yet another aspect of the present disclosure, the fixed handle and/or the movable handle includes a finger ring.

[0018] Another surgical instrument provided in accordance with aspects of the present disclosure includes an elongated shaft, an end effector assembly, a drive bar, a movable handle, and a linkage. The elongated shaft includes a proximal portion and a distal portion. The end effector assembly is coupled to the distal portion of the elongated shaft and includes first and second jaw members movable between a spaced-apart position and an approximated position. The drive bar is slidably disposed within the elongated shaft and operably coupled to the first jaw member and/or the second jaw member such that translation of the drive bar through the elongated shaft moves the first and second jaw members between the spaced-apart position and the approximated position. The movable handle is pivotably coupled to the drive bar via a first pivot pin and is movable between an open position and a closed position to translate the drive bar through the elongated shaft to thereby move the first and second jaw members between the spaced-apart position and the approximated position. The linkage includes a first end portion and a second end portion. The first end portion of the linkage is pivotably coupled to the movable handle via a second pivot pin. The second end portion of the linkage is pivotably coupled to the elongated shaft via a third pivot pin. In the closed position of the movable handle, the second pivot pin is disposed in a near-over-center position relative to the first pivot pin and the third pivot pin to reduce a force necessary to maintain the movable handle in the closed position.

[0019] In an aspect of the present disclosure, the elongated shaft defines a cut-out disposed therethrough configured to receive at least a portion of the second pivot pin in the near-over-center position of the second pivot pin.

[0020] In another aspect of the present disclosure, a fixed handle fixed relative to the elongated shaft is provided. In such aspects, the movable handle is movable relative to the fixed handle between the open and closed positions.

[0021] In still another aspect of the present disclosure, each of the first and second jaw members defines an electrically-conductive tissue-contacting surface adapted to connect to a source of energy. The tissue-contacting surfaces are configured to grasp tissue therebetween in the approximated position.

[0022] In yet another aspect of the present disclosure, the movable handle includes a clevis configured to couple at least a portion of the elongated shaft with at least a portion of the linkage. In such aspects, the first and second pivot pins extend within the clevis.

[0023] In another aspect of the present disclosure, the elongated shaft includes a pair of opposed slots defined therethrough. The first pivot pin extends through the opposed slots of the elongated shaft.

[0024] In still yet another aspect of the present disclosure, an activation assembly is disposed on the movable handle. The activation assembly is selectively activatable to supply energy to the first and second jaw members.

[0025] In another aspect of the present disclosure, the activation assembly is positioned such that the activation assembly is activated upon movement of the movable handle to the closed position.

[0026] In an aspect of the present disclosure, the movable handle includes a finger ring.

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] Various aspects and features of the present disclosure are described herein with reference to the drawings, wherein:

[0028] FIG. 1 is a side view of an electrosurgical forceps provided in accordance with aspects of the present disclosure;

[0029] FIG. 2 is a side view of a proximal portion of the forceps of FIG. 1;

[0030] FIG. 3A is an enlarged, side view of the area of detail indicated as "3A" in FIG. 1;

[0031] FIG. 3B is an enlarged, side view of the area of detail indicated as "3A" in FIG. 1, with parts removed;

[0032] FIG. 3C is an enlarged, side view of the area of detail indicated as "3A" in FIG. 1, with other parts removed;

[0033] FIG. 4 is a side view of a distal portion of the forceps of FIG. 1;

[0034] FIG. 5A is a side view of the distal portion of the forceps of FIG. 1, with an elongated shaft and one jaw member removed;

[0035] FIG. 5B is a side view of the distal portion of the forceps of FIG. 1, with the elongated shaft and another jaw member removed;

[0036] FIG. 6A is a transverse, cross-sectional view of an end effector assembly of the forceps of FIG. 1;

[0037] FIG. 6B is a perspective view of a cam pin of the end effector assembly of FIG. 6A including a clip engaged about the cam pin;

[0038] FIG. 7 is a top view of one of jaw members of the end effector assembly of the forceps of FIG. 1;

[0039] FIG. 8 is a side view of a proximal portion of the forceps of FIG. 1, with the elongated shaft and a portion of a housing of a fixed handle removed;

[0040] FIG. 9 is a side view of a trigger assembly and a knife assembly of the forceps of FIG. 1;

[0041] FIG. 10 is a side view of the end effector assembly of the forceps of FIG. 1 including a knife of the knife assembly of FIG. 8 operably positioned relative thereto; and

[0042] FIG. 11 is a side view of a distal portion of the forceps of FIG. 1, with a portion of the elongated shaft removed.

DETAILED DESCRIPTION

[0043] Turning to FIG. 1, an electrosurgical forceps provided in accordance with the present disclosure is shown generally identified by reference numeral 10. Forceps 10 is configured for use in VATS procedures and other surgical procedures and generally includes an elongated shaft 20, a handle assembly 30, a drive assembly 50 (FIGS. 3A-3C), a trigger assembly 70, a knife assembly 80 (FIGS. 8 and 9), an activation assembly 90, and an end effector assembly 100 which mutually cooperate to grasp, treat, and/or cut tissue. Forceps 10 further includes an electrosurgical cable (not shown) adapted to connect forceps 10 to a source of energy, e.g., a generator (not shown), although forceps 10 may alternatively be configured as a battery-powered instrument.

[0044] With additional reference to FIG. 2, handle assembly 30 is operably coupled to a proximal portion of elongated shaft 20 and includes a pair of handle members: a fixed handle 32 and a movable handle 42. Fixed handle 32 is fixedly engaged with elongated shaft 20 and extends proximally therefrom. Fixed

handle 32 includes a body 34 formed from first and second housing components that cooperate to house the internal components of trigger assembly 70 (FIG. 8) as well as knife drive bar 82 of knife assembly 80 (FIG. 9). Fixed handle 32 further includes a finger ring 36 disposed on a proximal portion of body 34. Finger ring 36 is configured to receive one or more fingers of a user to facilitate grasping and manipulating forceps 10.

[0045] Movable handle 42 of handle assembly 30 includes a body 44 formed from first and second housing components that cooperate to retain activation assembly 90 partially within body 44 and in operable position relative to fixed handle 32, as detailed below. The electrosurgical cable (not shown) of forceps 10 is configured to operably couple to movable handle 42 while the internal wires (not shown) thereof are configured to extend through body 44 of movable handle 42 and elongated shaft 20 to end effector assembly 100 (FIG. 1) to electrically couple end effector assembly 100 (FIG. 1) and activation assembly 90 with the source of energy (not shown). Movable handle 42 further includes a finger ring 46 disposed on a proximal portion of body 44. Finger ring 46 is configured to receive one or more fingers of a user to facilitate grasping and manipulating forceps 10.

[0046] Referring to FIGS. 3A-3C, movable handle 42 additionally includes a clevis 48 extending distally from a distal portion of body 44. Clevis 48 defines a bifurcated configuration including first and second spaced-apart clevis members. The first and second spaced-apart clevis member of clevis 48 are configured for positioning on either side of elongated shaft 20 such that elongated shaft 20 is at least partially received within clevis 48. Clevis 48 is configured to operably

couple movable handle 42 with elongated shaft 20 and drive assembly 50. Distal and proximal pins 49a, 49b are fixed relative to clevis 48 and extend transversely between the first and second spaced-apart clevis members of clevis 48. Distal pin 49a is configured to pivotably couple clevis 48 to a proximal portion of drive bar 52 of drive assembly 50. Elongated shaft 20 defines a pair of opposed slots 22 (only one is shown) through which distal pin 49a extends to enable coupling of clevis 48 and drive bar 52 with elongated shaft 20 disposed therebetween. Proximal pin 49b is configured to pivotably couple clevis 48 to a distal portion of linkage 54 of drive assembly 50. Elongated shaft 20 defines a cut-out 24 configured to enable pivoting of movable handle 42 relative to fixed handle 32 and elongated shaft 20, as detailed below.

[0047] Drive assembly 50 of forceps 10, as noted above, includes drive bar 52 and linkage 54. Drive bar 52 is slidably disposed within elongated shaft 20 and includes a proximal portion that is pivotably coupled to clevis 48 of movable handle 42 via distal pin 49a. A distal portion of linkage 54 extends through cut-out 24 of elongated shaft 20 and is pivotably coupled to clevis 48 via proximal pin 49b. A proximal portion of linkage 54 extends through cut-out 24 into elongated shaft 20 and is pivotably coupled to elongated shaft 20 within elongated shaft 20 via a linkage pin 55. Linkage pin 55 and distal pin 49a are both aligned on a longitudinal axis "X-X" of elongated shaft 20.

[0048] As a result of the above-detailed configuration of movable handle 42 and drive assembly 50, pivoting of movable handle 42 relative to fixed handle 32 between an open position and a closed position translates drive bar 52 through elongated shaft 20. More specifically, pivoting of movable handle 42

towards fixed handle 32, e.g., towards the closed position, translates drive bar 52 distally through elongated shaft 20, while pivoting of movable handle 42 away from fixed handle 32, e.g., towards the open position, translates drive bar 52 proximally through elongated shaft 20.

[0049] As movable handle 42 is pivoted towards the closed position, the distal portion of linkage 54 is pivoted towards an aligned orientation relative to elongated shaft 20 and, thus, proximal pin 49b is moved towards longitudinal axis “X-X” of elongated shaft 20. The configuration of handle assembly 30, elongated shaft 20, and/or drive assembly 50 inhibits linkage 54 from reaching an aligned position relative to longitudinal axis “X-X” of elongated shaft 20 and, thus, inhibits proximal pin 49b from reaching an over-center position relative to linkage pin 55, distal pin 49a, and longitudinal axis “X-X” of elongated shaft 20. As such, movable handle 42 remains freely movable relative to fixed handle 32 and is not locked in position relative thereto, as is the case when an over-center position is achieved.

[0050] Despite being inhibited from reaching an over-center position, proximal pin 49b is configured to move at least partially into cut-out 24 of elongated shaft 20 as movable handle 42 is moved to the closed position to achieve a near-over-center position. This near-over-center position reduces the forces necessary to pivot movable handle 42 towards fixed handle 32 as movable handle 42 approaches the closed position without permitting locking of the movable handle 42. The term near-over-center position, for the purposes herein, corresponds to a position wherein proximal pin 49b is disposed at least partially within cut-out 24 of elongated shaft 20 and, thus, is at least partially

inside the outer diameter of elongated shaft 20. As such, the near-over-center position of proximal pin 49b corresponds to a radial distance between longitudinal axis "X-X" of elongated shaft 20 and proximal pin 49b that is equal to or less than the radius of elongated shaft 20 plus the diameter of proximal pin 49b. In embodiments where elongated shaft 20 defines a rectangular or other non-cylindrical configuration, the near-over-center position of proximal pin 49b corresponds to a radial distance between longitudinal axis "X-X" of elongated shaft 20 and proximal pin 49b that is equal to or less than half of the corresponding transverse dimension of elongated shaft 20 (taken along a line perpendicular to longitudinal axis "X-X" and intersecting proximal pin 49b) plus the diameter of proximal pin 49b.

[0051] Referring to FIGS. 1 and 4-5B, end effector assembly 100 is coupled to a distal portion of elongated shaft 20 and includes first and second jaw members 110, 120. One or both of jaw members 110, 120 is pivotable relative to the other and the elongated shaft 20 about a pivot pin 102. Each jaw member 110, 120 includes a proximal flange 111, 121 and a distal jaw body 112, 122 supporting an electrically-conductive tissue-contacting surface 114, 124. Tissue-contacting surfaces 114, 124 are electrically coupled to activation assembly 90 (FIG. 1) and the source of energy (not shown), e.g., via the wires (not shown) extending through the electrosurgical cable (not shown), movable handle 42, and elongated shaft 20, such that energy may be selectively supplied to tissue-contacting surface 114 and/or tissue-contacting surface 124 and conducted through tissue grasped between jaw members 110, 120 to treat, e.g., seal, tissue.

[0052] Proximal flanges 111, 121 of jaw members 110, 120 are pivotably coupled to one another via pivot pin 102. End effector assembly 100 is configured as a unilateral assembly, wherein jaw member 120 is fixed relative to elongated shaft 20 and jaw member 110 is pivotable about pivot pin 102 relative to elongated shaft 20 and fixed jaw member 120. However, end effector assembly 100 may alternatively be configured as a bilateral assembly, where both jaw member 110 and jaw member 120 are movable about pivot pin 102 relative to one another and elongated shaft 20. For the purposes herein, the terms “movement of the jaw members,” “pivoting of the jaw members,” and like terms are understood to encompass both unilateral and bilateral configurations. In the illustrated unilateral configuration, proximal flange 121 of jaw member 120 may be fixedly engaged to elongated shaft 20 via welding or other suitable engagement. Pivot pin 102 may be welded, on either side thereof, to proximal flange 121 of jaw member 120 and pivotably disposed within an aperture defined through proximal flange 111 of jaw member 110. Other configurations are also contemplated, for example, using a clip similar to that detailed below with respect to cam pin 104 and clip 106 (FIGS. 6A-6B).

[0053] Proximal flanges 111, 121 of jaw members 110, 120 define oppositely-oriented U-shaped configurations. One of the proximal flanges, e.g., proximal flange 121 of jaw member 120, may surround the proximal flange, e.g., proximal flange 111 of jaw member 110, of the other jaw member, as illustrated (see FIG. 6A). Alternatively, proximal flanges 111, 121 may be disposed in an overlapping, offset configuration. Each proximal flange 111, 121 defines a pair of cam slots 116, 126 therethrough. Cam slots 116 of proximal flange 111 of jaw

member 110 are angled relative to cam slots 126 of proximal flange 121 of jaw member 120. Cam slots 116, 126 are configured to receive a cam pin 104 that extends through an aperture defined through a distal portion of drive bar 52. As a result of this configuration, translation of drive bar 52 through elongated shaft 20, e.g., in response to pivoting of movable handle 42 (FIG. 1) between the open and closed positions, pivots jaw members 110, 120 between spaced-apart and approximated positions for grasping tissue therebetween. More specifically, cam slots 116, 126 are oriented such that distal translation of drive bar 52 and, thus, cam pin 104, effects pivoting of jaw members 110, 120 from the spaced-apart position towards the approximated position, and such that proximal translation of drive bar 52 and, thus, cam pin 104 pivots jaw members 110, 120 towards the spaced-apart position.

[0054] Referring to FIGS. 6A and 6B, a clip 106 is provided to operably couple cam pin 104 with jaw members 110, 120 and drive bar 52, and to retain cam pin 104 in position without the need for welding (or otherwise affixing) cam pin 104 to drive bar 52. Such a configuration is advantageous in that welding (or otherwise affixing) cam pin 104 to drive bar 52 is difficult due to the necessity for drive bar 52 to be operably positioned between jaw members 110, 120 and cam pin 104 inserted therebetween prior to welding cam pin 104 thereto.

[0055] Clip 106 includes a body 107a having a pair of resilient, semi-annular side fingers 107b (only one is shown) extending from either side thereof and a central finger 107c extending between side fingers 107b. Cam pin 104 defines an annular groove 105 to facilitate engagement of clip 106 thereabout. Side fingers 107b, at the free ends thereof and in their at-rest position, are

spaced-apart a distance smaller than the diameter of the portion of clip 106 that defines groove 105.

[0056] In order to operably couple jaw members 110, 120 and drive bar 52 with one another via cam pin 104, jaw members 110, 120 are first aligned such that cam slots 116, 126 of proximal flanges 111, 121 of jaw members 110, 120, respectively, are aligned with one another. Drive bar 52 is inserted between proximal flanges 111, 121 such that the aperture defined within drive bar 52 is aligned with cam slots 116, 126. Once cam slots 116, 126 are aligned with one another and the aperture of drive bar 52, cam pin 104 may be inserted, from either side of end effector assembly 100, through cam slots 116, 126 and the aperture of drive bar 52. In the inserted position of cam pin 104, groove 105 is exposed between drive bar 52 and flanges 111, 121 to enable distal insertion of clip 106 between drive bar 52 and flanges 111, 121 and into engagement with cam pin 104.

[0057] In order to engage clip 106 about cam pin 104, clip 106 is aligned with groove 105 of cam pin 104 and moved transversely towards clip 106. As clip 106 is moved into contact with cam pin 104, side fingers 107b contact the inner surface of cam pin defining groove 105 and are flexed outwardly relative to one another to widen the gap therebetween and permit cam pin 104 to pass therebetween. Once cam pin 104 is positioned more than halfway within clip 106, e.g., once side fingers 107b clear the diameter of cam pin 104, side fingers 107b are returned under bias inwardly into engagement within groove 105, thereby retaining clip 106 about cam pin 104. Upon engagement of clip 106 about cam pin 104, central finger 107c is also disposed within groove 105.

[0058] With clip 106 engaged about cam pin 104, cam pin 104 is inhibited from sliding laterally out of engagement with cam slots 116, 126 and/or the aperture of drive bar 52. Thus, cam pin 104 is retained in operable engagement within cam slots 116, 126 and the aperture of drive bar 52 such that translation of drive bar 52 relative to end effector assembly 100 translates cam pin 104 through cam slots 116, 126 to pivot jaw members 110, 120 between the spaced-apart and approximated positions.

[0059] With reference to FIGS. 4-5B, distal jaw bodies 112, 122 of jaw members 110, 120 extend distally from proximal flanges 111, 121, respectively, and, as noted above, support respective electrically-conductive tissue-contacting surfaces 114, 124 thereon. Distal jaw bodies 112, 122 and, thus, tissue-contacting surfaces 114, 124, define curved configurations, although other configurations may also be provided. In the approximated position of jaw members 110, 120, tissue-contacting surfaces 114, 124 are configured to grasp tissue therebetween and, upon activation of activation assembly 90 (FIG. 1), conduct energy therebetween and through grasped tissue to treat, e.g., seal, tissue. Either or both tissue-contacting plates 114, 124 may further define a longitudinally-extending knife channel 117, 127 extending therethrough. Knife channel(s) 117, 127 are configured to receive a knife 84 of knife assembly 80 (FIG. 9) to facilitate reciprocation of knife 84 (FIG. 9) between jaw members 110, 120 to cut tissue disposed therebetween, e.g., upon actuation of rotatable trigger 72 of trigger assembly 70 (see FIG. 9).

[0060] Referring additionally to FIG. 7, the distal jaw body 112, 122 of one or both of jaw members 110, 120 further includes a plurality of vent holes 118,

128 defined therethrough (only vent holes 118 of jaw member 110 are shown in FIG. 7; the vent holes of jaw member 120 may be similar in embodiments where so provided). Vent holes 118, 128 are arranged longitudinally along jaw member 110 and extend completely through distal jaw bodies 112, 122. More specifically, vent holes 118, 128 are aligned with and disposed in communication with knife channels 117, 127 of jaw members 110, 120. As such, steam generated during tissue treatment may escape the area between jaw members 110, 120 via knife channels 117, 127 and vent holes 118, 128.

[0061] Turning to FIGS. 8-11, trigger assembly 70 and knife assembly 80 cooperate to enable selective deployment of knife 84 between a retracted position, wherein knife 84 is disposed proximally of jaw members 110, 120, and an extended position, wherein knife 84 extends at least partially through knife channels 117, 127 (FIGS. 5A-5B) between jaw members 110, 120. Trigger assembly 70 is operably coupled to and partially disposed within body 34 of fixed handle 32. Trigger assembly 70 includes a rotatable trigger 72, a first linkage 74, a second linkage 76, and a spring 78. Rotatable trigger 72 defines a bifurcated configuration and extends from body 34 of fixed handle 32 towards movable handle 42. In the closed position of handle assembly 30, the bifurcated rotatable trigger 72 at least partially surrounds body 44 of movable handle 42, thus enabling actuation of rotatable trigger 72 from either side of forceps 10 (FIG. 1). Rotatable trigger 72 is pivotably coupled to fixed handle 32 about a pivot 73.

[0062] First linkage 74 of trigger assembly 70 is disposed within body 34 of fixed handle 32. First linkage 74 is pivotably coupled to fixed handle 32 about pivot 73 towards a first end of first linkage 74 and is engaged with rotatable

trigger 72 such that pivoting of rotatable trigger about pivot 73 likewise pivots first linkage 74 about pivot 73. The second end of first linkage 74 defines a Y-connector 75. Spring 78 is disposed within body 34 of fixed handle 32 and includes a first end that is fixed relative to body 34 and a second end that is engaged with one of the prongs of Y-connector 75. Spring 78 is configured to bias first linkage 74 and, thus, rotatable trigger 72, towards an un-actuated position. Spring 78 also biases knife 84 towards the retracted position.

[0063] Second linkage 76 operably couples first linkage 74 and, thus, rotatable trigger 72, with knife assembly 80. More specifically, second linkage 76 is coupled to the other prong of Y-connector 75 of first linkage 74 towards the proximal end of second linkage 76, and is coupled to a proximal portion of knife drive bar 82 towards the distal end of second linkage 76. As a result, pivoting of rotatable trigger 72 about pivot 73 pivots first linkage 74 about pivot 73 to urge second linkage 76 distally through body 34 of fixed handle 32.

[0064] Knife assembly 80 includes knife drive bar 82 and knife 84. A proximal portion of knife drive bar 82 is pivotably coupled to a distal portion of second linkage 76, and a distal portion of knife drive bar 82 is fixedly engaged with a proximal portion of knife 84 with knife 84 extending distally therefrom. Knife drive bar 82 defines a slot 83 configured to receive distal pin 49a and linkage pin 55 (see FIGS. 3A-3C) to enable knife drive bar 82 to slide relative thereto. Knife 84 defines a distal cutting edge 86. In operation, pivoting of rotatable trigger 72 from an un-actuated position to an actuated position pivots first linkage 74 to urge second linkage 76 distally through body 34 of fixed handle 32, thereby urging knife drive bar 82 distally through elongated shaft 20 and

translating knife 84 from the retracted position to the extended position. Release of rotatable trigger 72 returns rotatable trigger 72 back towards the un-actuated position under the bias of spring 78, thereby returning first linkage 74, second linkage 76, and knife drive bar 82 such that knife 84 is returned to the retracted position.

[0065] Referring again to FIGS. 1 and 2, activation assembly 90, as noted above, is at least partially retained within body 44 of movable handle 42. Activation assembly 90 includes an activation button 92 and a base 94. Activation button 92 is selectively depressible relative to base 94 to initiate the supply of energy to tissue-contacting surfaces 114, 124 of jaw members 110, 120 (see FIGS. 5A-5B), respectively. More specifically, upon achieving the fully closed position of handle assembly 30, activation button 92 is urged into the opposed surface of body 34 of fixed handle 32 so as to depress activation button 92 and initiate the supply of energy to tissue-contacting surfaces 114, 124 of jaw members 110, 120 (see FIGS. 5A-5B).

[0066] The various aspects and features provided herein may also be configured to work with robotic surgical systems and what is commonly referred to as "Telesurgery." Such systems employ various robotic elements to assist the surgeon in the operating room and allow remote operation (or partial remote operation) of surgical instrumentation. Various robotic arms, gears, cams, pulleys, electric and mechanical motors, etc. may be employed for this purpose and may be designed with a robotic surgical system to assist the surgeon during the course of an operation or treatment. Such robotic systems may include remotely steerable systems, automatically flexible surgical systems, remotely

flexible surgical systems, remotely articulating surgical systems, wireless surgical systems, modular or selectively configurable remotely operated surgical systems, etc.

[0067] The robotic surgical systems may be employed with one or more consoles that are next to the operating theater or located in a remote location. In this instance, one team of surgeons or nurses may prep the patient for surgery and configure the robotic surgical system with one or more of the instruments provided herein while another surgeon (or group of surgeons) remotely control the instruments via the robotic surgical system. As can be appreciated, a highly skilled surgeon may perform multiple operations in multiple locations without leaving the remote console, which can be both economically advantageous and a benefit to the patient or a series of patients.

[0068] The robotic arms of the surgical system are typically coupled to a pair of master handles by a controller. The handles can be moved by the surgeon to produce a corresponding movement of the working ends of any type of surgical instrument (e.g., end effectors, graspers, knives, scissors, etc.) which may complement the use of one or more of the aspects and features described herein. The movement of the master handles may be scaled so that the working ends have a corresponding movement that is different, smaller or larger, than the movement performed by the operating hands of the surgeon. The scale factor or gearing ratio may be adjustable so that the operator can control the resolution of the working ends of the surgical instrument(s).

[0069] The master handles may include various sensors to provide feedback to the surgeon relating to various tissue parameters or conditions, e.g.,

tissue resistance due to manipulation, cutting, or treating, pressure by the instrument onto the tissue, tissue temperature, tissue impedance, etc. As can be appreciated, such sensors provide the surgeon with enhanced tactile feedback simulating actual operating conditions. The master handles may also include a variety of different actuators for delicate tissue manipulation or treatment further enhancing the surgeon's ability to mimic actual operating conditions.

[0070] From the foregoing and with reference to the various figure drawings, those skilled in the art will appreciate that certain modifications can also be made to the present disclosure without departing from the scope of the same. While several embodiments of the disclosure have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

WHAT IS CLAIMED IS:

1. A surgical instrument, comprising:

an elongated shaft defining a longitudinal axis and including a proximal portion and a distal portion;

an end effector assembly coupled to the distal portion of the elongated shaft;

a fixed handle coupled to the proximal portion of the elongated shaft;

a drive bar slidably disposed within the elongated shaft and operably coupled to the end effector assembly such that translation of the drive bar through the elongated shaft manipulates the end effector assembly;

a movable handle movable relative to the fixed handle between an open position and a closed position to translate the drive bar through the elongated shaft, the movable handle pivotably coupled to the drive bar via a first pivot pin, the first pivot pin aligned on the longitudinal axis; and

a linkage including a first end portion and a second end portion, the first end portion of the linkage pivotably coupled to the movable handle via a second pivot pin, the second end portion of the linkage pivotably coupled to the elongated shaft via a third pivot pin, the third pivot pin aligned on the longitudinal axis,

wherein, in the closed position of the movable handle, the second pivot pin is disposed in a near-over-center position relative to the longitudinal axis to reduce a force necessary to maintain the movable handle in the closed position.

2. The surgical instrument according to claim 1, wherein the elongated shaft defines a cut-out disposed therein configured to receive at least a portion of the second pivot pin in the near-over-center position of the second pivot pin.
3. The surgical instrument according to claim 1, wherein at least one of the movable handle, the fixed handle, or the elongated shaft inhibits the second pivot pin from reaching an over-the-center position relative to the longitudinal axis.
4. The surgical instrument according to claim 1, wherein the end effector assembly includes first and second jaw members, and wherein translation of the drive bar through the elongated shaft moves the first and second jaw members between a spaced-apart position and an approximated position.
5. The surgical instrument according to claim 4, wherein the near-over-center position of the second pivot pin corresponds to the approximated position of the first and second jaw members.
6. The surgical instrument according to claim 4, wherein each of the first and second jaw members defines an electrically-conductive tissue-contacting surface adapted to connect to a source of energy, the tissue-contacting surfaces configured to grasp tissue therebetween in the approximated position.
7. The surgical instrument according to claim 1, wherein the movable handle includes a clevis configured to couple at least a portion of the elongated shaft with at least a portion of the linkage, the first and second pivot pins extending within the clevis.
8. The surgical instrument according to claim 1, wherein the elongated shaft includes a pair of opposed slots defined therethrough, and wherein the first pivot pin extends through the opposed slots of the elongated shaft.

9. The surgical instrument according to claim 1, further comprising an activation assembly disposed on one of the fixed handle or the movable handle, the activation assembly selectively activatable to supply energy to the end effector assembly.

10. The surgical instrument according to claim 9, wherein the activation assembly is positioned such that the activation assembly is activated upon movement of the movable handle to the closed position.

11. The surgical instrument according to claim 1, wherein at least one of the fixed handle or the movable handle includes a finger ring.

12. A surgical instrument, comprising:

- an elongated shaft including a proximal portion and a distal portion;

- an end effector assembly coupled to the distal portion of the elongated shaft, the end effector assembly including first and second jaw members movable between a spaced-apart position and an approximated position;

- a drive bar slidably disposed within the elongated shaft and operably coupled to at least one of the first jaw member or the second jaw member such that translation of the drive bar through the elongated shaft moves the first and second jaw members between the spaced-apart position and the approximated position;

- a movable handle pivotably coupled to the drive bar via a first pivot pin, the movable handle movable between an open position and a closed position to translate the drive bar through the elongated shaft to thereby move the first and second jaw members between the spaced-apart position and the approximated position; and

a linkage including a first end portion and a second end portion, the first end portion of the linkage pivotably coupled to the movable handle via a second pivot pin, the second end portion of the linkage pivotably coupled to the elongated shaft via a third pivot pin,

wherein, in the closed position of the movable handle, the second pivot pin is disposed in a near-over-center position relative to the first pivot pin and the third pivot pin to reduce a force necessary to maintain the movable handle in the closed position.

13. The surgical instrument according to claim 12, wherein the elongated shaft defines a cut-out disposed therein configured to receive at least a portion of the second pivot pin in the near-over-center position of the second pivot pin.

14. The surgical instrument according to claim 12, further comprising a fixed handle fixed relative to the elongated shaft, wherein the movable handle is movable relative to the fixed handle between the open and closed positions.

15. The surgical instrument according to claim 12, wherein each of the first and second jaw members defines an electrically-conductive tissue-contacting surface adapted to connect to a source of energy, the tissue-contacting surfaces configured to grasp tissue therebetween in the approximated position.



16. The surgical instrument according to claim 12, wherein the movable handle includes a clevis configured to couple at least a portion of the elongated shaft with at least a portion of the linkage, the first and second pivot pins extending within the clevis.




17. The surgical instrument according to claim 12, wherein the elongated shaft includes a pair of opposed slots defined therethrough, and wherein the first pivot pin extends through the opposed slots of the elongated shaft.

18. The surgical instrument according to claim 12, further comprising an activation assembly disposed on the movable handle, the activation assembly selectively activatable to supply energy to the first and second jaw members.

19. The surgical instrument according to claim 18, wherein the activation assembly is positioned such that the activation assembly is activated upon movement of the movable handle to the closed position.

20. The surgical instrument according to claim 12, wherein the movable handle includes a finger ring.








FIG. 4




FIG. 5A




FIG. 5B




FIG. 7




FIG. 6A




FIG. 6B

FIG. 8




FIG. 9




FIG. 10





FIG. 11



A. CLASSIFICATION OF SUBJECT MATTER**A61B 18/00(2006.01)i, A61B 17/28(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B 18/00; A61B 18/14; A61B 17/295; A61B 18/18; A61B 18/12; A61B 17/28

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords:elongated shaft, end effector assembly, jaw members, fixed handle, drive bar, movable handle, linkage, first pivot pin, second pivot pin, third pivot pin, closed position, open position

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2016-015233 A1 (COVIDIEN LP) 04 February 2016 See abstract; page 14, lines 20-22; page 20, line 22 - page 21, line 5; claim 1; and figures 1-3.	1-20
A	US 2010-0179540 A1 (MARCZYK, S. et al.) 15 July 2010 See the whole document.	1-20
A	US 2015-0223874 A1 (COVIDIEN LP) 13 August 2015 See the whole document.	1-20
A	US 2013-0296843 A1 (ETHICON ENDO-SURGERY, INC.) 07 November 2013 See the whole document.	1-20
A	US 2005-0119655 A1 (MOSES, M. C. et al.) 02 June 2005 See the whole document.	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

22 November 2017 (22.11.2017)

Date of mailing of the international search report

22 November 2017 (22.11.2017)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea




Facsimile No. +82-42-481-8578

Authorized officer

KIM, Sun Hee

Telephone No. +82-42-481-5405



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/046019

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2016-015233 A1	04/02/2016	CN 107072706 A US 2017-0181789 A1	18/08/2017 29/06/2017
US 2010-0179540 A1	15/07/2010	AU 2007-307082 A1 AU 2007-307082 B2 AU 2007-307084 A1 AU 2007-307084 B2 CA 2664111 A1 CA 2664111 C CA 2664167 A1 CN 101522127 A CN 101522127 B CN 101522128 A CN 101522128 B CN 102512240 A CN 102512240 B EP 2081512 A2 EP 2086439 A2 EP 2086439 B1 EP 2403421 A1 EP 2578174 A1 EP 3189807 A1 JP 2010-505521 A JP 2010-505522 A JP 5143840 B2 JP 5225996 B2 US 2010-0076433 A1 US 2010-0094289 A1 US 2013-0274741 A1 US 8475453 B2 US 8685019 B2 US 8721640 B2 US 9204924 B2 WO 2008-045348 A2 WO 2008-045348 A3 WO 2008-045350 A2 WO 2008-045350 A3 WO 2010-104755 A1	17/04/2008 24/01/2013 17/04/2008 23/05/2013 17/04/2008 16/02/2016 17/04/2008 02/09/2009 16/11/2011 02/09/2009 15/02/2012 27/06/2012 08/07/2015 29/07/2009 12/08/2009 13/03/2013 11/01/2012 10/04/2013 12/07/2017 25/02/2010 25/02/2010 13/02/2013 03/07/2013 25/03/2010 15/04/2010 17/10/2013 02/07/2013 01/04/2014 13/05/2014 08/12/2015 17/04/2008 12/06/2008 17/04/2008 17/07/2008 16/09/2010
US 2015-0223874 A1	13/08/2015	AU 2011-226838 A1 AU 2011-226838 B2 CA 2753649 A1 EP 2436327 A1 EP 2436327 B1 EP 3034026 A1 JP 2012-075899 A JP 2015-163312 A JP 2016-193233 A JP 5784446 B2	19/04/2012 24/04/2014 01/04/2012 04/04/2012 14/12/2016 22/06/2016 19/04/2012 10/09/2015 17/11/2016 24/09/2015

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/046019

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2013-0296843 A1	07/11/2013	US 2012-0083827 A1	05/04/2012
		US 2015-0223873 A1	13/08/2015
		US 2016-0106496 A1	21/04/2016
		US 9017372 B2	28/04/2015
		US 9381060 B2	05/07/2016
US 2013-0296843 A1	07/11/2013	CN 105007850 A	28/10/2015
		EP 2844172 A1	11/03/2015
		JP 2015-517329 A	22/06/2015
		WO 2013-166115 A1	07/11/2013
US 2005-0119655 A1	02/06/2005	AU 2004-231212 A1	02/06/2005
		AU 2004-231212 B2	24/06/2010
		AU 2005-202706 A1	12/01/2006
		AU 2005-202706 B2	30/06/2011
		AU 2005-220187 A1	27/04/2006
		AU 2005-220187 B2	15/09/2011
		AU 2005-220251 A1	27/04/2006
		AU 2005-220251 B2	28/07/2011
		AU 2010-224379 A1	14/10/2010
		AU 2010-224379 B2	04/07/2013
		CA 2487914 A1	19/05/2005
		CA 2487914 C	08/10/2013
		CA 2510247 A1	22/12/2005
		CA 2510247 C	13/08/2013
		CA 2522317 A1	08/04/2006
		CA 2522317 C	23/06/2015
		CA 2522633 A1	08/04/2006
		CA 2522633 C	28/04/2015
		CA 2815779 A1	08/04/2006
		CA 2815779 C	19/05/2015
		EP 1532932 A1	25/05/2005
		EP 1532932 B1	09/09/2015
		EP 1609430 A1	28/12/2005
		EP 1609430 B1	10/08/2011
		EP 1645238 A1	12/04/2006
		EP 1645238 B1	24/03/2010
		EP 1645240 A2	12/04/2006
		EP 1645240 A3	26/04/2006
		EP 1645240 B1	27/05/2009
		EP 1769764 A2	04/04/2007
		EP 1769764 A3	31/10/2007
		EP 2039314 A2	25/03/2009
		EP 2039314 A3	02/09/2009
		EP 2039314 B1	07/01/2015
		EP 2942026 A1	11/11/2015
		JP 2005-144193 A	09/06/2005
		JP 2006-006942 A	12/01/2006
		JP 2006-102514 A	20/04/2006
		JP 2006-102515 A	20/04/2006

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/046019Patent document
cited in search reportPublication
datePatent family
member(s)Publication
date

JP 2011-045746 A	10/03/2011
JP 2011-125731 A	30/06/2011
JP 2011-235118 A	24/11/2011
JP 2011-235119 A	24/11/2011
JP 4804863 B2	02/11/2011
JP 5116219 B2	09/01/2013
JP 5137303 B2	06/02/2013
JP 5160669 B2	13/03/2013
JP 5214706 B2	19/06/2013
JP 5237521 B2	17/07/2013
US 2005-0107784 A1	19/05/2005
US 2005-0154387 A1	14/07/2005
US 2006-0074417 A1	06/04/2006
US 2006-0079891 A1	13/04/2006
US 2007-0088356 A1	19/04/2007
US 2008-0312653 A1	18/12/2008
US 2009-0149854 A1	11/06/2009
US 2010-0023009 A1	28/01/2010
US 2011-0238067 A1	29/09/2011
US 7131970 B2	07/11/2006
US 7252667 B2	07/08/2007
US 7500975 B2	10/03/2009
US 7811283 B2	12/10/2010
US 7922718 B2	12/04/2011
US 7955332 B2	07/06/2011
US 8123743 B2	28/02/2012
US 8303586 B2	06/11/2012
US 8394096 B2	12/03/2013
US 8623017 B2	07/01/2014