

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
11 November 2004 (11.11.2004)

PCT

(10) International Publication Number
WO 2004/096069 A1

(51) International Patent Classification⁷: **A61B 17/88**, B25B 15/04

(74) Agent: **MOETTELI, John**; Moetteli & Associés, Case postale 486, CH-1211 Genève 12 (CH).

(21) International Application Number: PCT/IB2004/001244

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 60/465,758 25 April 2003 (25.04.2003) US

(71) Applicant (for all designated States except US): **PRECIMED S.A. [CH/CH]**; 7, l'Echelette, CH-2534 Orvin (CH).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **LECHOT, André [CH/CH]**; 24, Sous l'Eau-Belle, CH-2534 Orvin (CH). **FEHLBAUM, Philippe [CH/CH]**; Fin de Forel 4, CH-2523 Lignières (CH).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DETACHABLE SURGICAL RATCHET



WO 2004/096069 A1

(57) **Abstract:** A surgical ratchet assembly (10) includes a handle (12), a driver (14), a ratcheting mechanism (16) and a locking mechanism (20). The driver is received within the handle in a rotatable relationship with respect thereto. The ratcheting mechanism is interposed between the handle and the driver. A locking mechanism releasably holds the handle to the ratcheting mechanism. Unlocking of the locking mechanism enables ready disassembly of the assembly for cleaning and component sterilization.

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*
- *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *with international search report*
- *with amended claims*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DETACHABLE SURGICAL RATCHET

Background of the Invention

This invention relates to drivers for rotary surgical cutting tools, and, more particularly, to drivers used in maxillo-facial, neuro, dental, trauma and orthopedic surgery, including reamer drivers.

Surgical ratchets are complicated mechanical devices which have crevices and recesses that, heretofore, have been difficult, if not almost impossible to clean with ease. Devices that are not properly cleaned and sterilized run the risk of disease transfer from patient to patient following the emergence of certain "prions" that are not killed by normal hospital sterilisation and need to be physically removed by washing / rinsing. For this reason, in the prior art, ratchet mechanisms have been hermetically sealed to prevent contamination. However, the seals are not 100% reliable.

What is needed therefore is a surgical ratchet that is easily disassemblable for cleaning, so 15 as to better ensure sterilization.

Summary of the Invention

A surgical ratchet assembly includes a handle, a driver, a ratcheting mechanism and a locking mechanism. The driver is received within the handle in a rotatable relationship with 20 respect thereto. The ratcheting mechanism is interposed between the handle and the driver. The ratcheting mechanism includes pawls which can be selectively locked out of engagement with a toothed hub via a selector. A locking mechanism releasably holds the handle to the ratchet mechanism. Unlocking of the locking mechanism enables ready disassembly of the assembly for cleaning and component sterilization.

25 Although the term "driver" is used herein, this term is meant to encompass drills, taps, guide pins, screwdrivers (for example, straight, cross-head, Allen key and Torx), reamer drivers, and wire introducers and any tool to which rotation and torque need be applied.

In another feature, the selector includes a position in which both pawls are in an engaged position, thus locking the ratchet mechanism against free movement in either direction.

In another feature, the selector includes a position in which both pawls are in a released, nonengaged position, disengaging the ratchet mechanism, thus permitting free motion in either direction.

An object of the invention is to provide a surgical ratchet that is readily disassembled for
5 cleaning and sterilization.

Another object of the invention is to provide a reliable ratchet that is easy to operate.

Brief Description of the Drawings

FIG. 1 is a perspective view of the ratchet of the invention.

10 FIG. 2A is cross sectional view of the ratchet of the invention.

FIG. 2B is a cross sectional detail of the upper right corner of the ratchet of FIG. 2A.

FIG. 3 is a partially disassembled view of the ratchet of the invention.

FIG. 4 is a perspective, partially disassembled view of the ratchet of the invention.

15 FIG. 5 is a perspective, cross sectional view taken along plane A of FIG. 1, showing the components of the ratchet mechanism of the invention.

FIG. 6 is a perspective view of a kit of the invention.

Detailed Description of the Preferred Embodiment

In a preferred embodiment, as shown in Figs. 1 to 3, a surgical ratchet assembly 10
20 includes a handle 12, a driver 14, a ratcheting mechanism 16 and a locking mechanism 20. The driver 14 is received within the handle 12 in a rotatable relationship with respect thereto. The ratcheting mechanism 16 is interposed between the handle 12 and the driver 14. The locking mechanism 20 releasably holds the handle 12 to the ratcheting mechanism 16. Unlocking of the locking mechanism 20 enables ready disassembly of the assembly 10 for cleaning and component
25 sterilization.

The locking mechanism 20 includes a ring 24 which is mounted over an annular surface on a hub 28 non-rotatably affixed to the handle 12. The ring 24 has an external surface which is preferably polygonal in cross section in order to provide a grip to facilitate operation by the user. The ring 24 is locked by a retainer ring, set screw or other fastener (not shown) so as to be

restrained to axially rotate about the handle 12. The inner surface of the ring 24 includes equally spaced apart balls 32 restrained in recesses 33 of the hub 28. The balls 32 are selectively biased into or out of an annular recess 34 in the annular rearward end 36 of the driver 14.

5 The driver 14 includes the end 36 affixed to a central shaft 38 on which is formed a toothed hub 52. The end 36 is formed of a material that can withstand impaction of a mallet and effectively transmit the forces so input through the driver 14 to the object being impacted.

Referring now to FIGs. 4 – 5, the ratcheting mechanism 16 is made up of an internal housing 22, left and right hand pawls 44, 46, a selector 50, the toothed hub 52, biasing springs 40, and cam portions 53.

10 The selector 50 rotates about the axis 54 of the driver 14, about an end 56 of the handle 12, and selectively locks, via a spring detent 60 (best shown in FIG. 2B) in one of two recesses 62 in the internal housing 22, at two extreme positions. The spring detent 60 is made up of a plunger 60, spring 51, enclosed by a plug 55. The selector 50 has an internal surface 64 having cam portions 53 (referring in particular to FIG. 4, adjacent the right ends 66, 67 of the pawls 44, 15 46, respectively) which selectively engage the end of either the left or right hand pawls. In toothed hub 52, and therefore the driver 14, is keyed against rotation relative to the handle 12 and therefore moves with the handle. In other words, when the handle 12 is rotated, the toothed hub 52 and driver 14 rotates.

20 It should be noted that the handle 12 is generally formed of a polymeric material that is comfortable to grip, but which includes inserts 18 to add structural rigidity.

Referring again to FIG. 2A, the pawls 44, 46 are formed so as to engage with the symmetrical, circumferential teeth 80 of the toothed hub 52, thus preventing motion in one direction, while permitting rotation in the opposite rotation. In the present embodiment, the pawls 44, 46 have fingers presenting a flat, locking surface 44', 46' which, when the cam places 25 them in an operational position, engages and therefore blocks a tooth 80 of the toothed hub 52 when the hub is urged in one rotational direction with respect to the handle 12, and an opposing angled surface 44'', 46'', which does not lockingly engage a tooth of the toothed hub, but enables relative rotation of the pawl and toothed hub, when urged in the opposite direction. The pawls 44, 46 are supported against bending in channels 82 of the housing 22.

The pawls 44, 46 are pivotally mounted in the housing 22 on pins 84 and normally urged into an engaging relationship by springs 40, the cam portions 53 of the selector 50 selectively moves one or the other out of engagement with the toothed hub 52, thus enabling a user to drive the driver 14 in one direction by turning the handle 12, while permitting relative movement of the 5 toothed hub and the pawls when the handle is turned in the other direction. Thus, movement of the selector 50 in one or the other extreme positions allows the user to select a ratcheting direction.

In a mid position, in which there may optionally be a spring detent, the internal surface 64 is at a low point 64', and thus the cam portions 53 of the selector 50 place both pawls 44, 46 in 10 an operational position so as to block rotation in both directions, enabling a functioning just as a normal, non-ratcheting driver.

In another mid position, the cam of the selector 50 optionally moves both pawls 44, 46 out of engagement with the toothed hub 52, thus providing a neutral position in which the handle 12 is free to turn in either direction.

15 The driver 14 includes a fitting interface 90 on an end of the central shaft 38. The shaft 38 extends from the front to the rearward end of the ratchet 10. The fitting interface 90 interfaces with an AO fitting, a Snyder fitting, or another known fitting 58. A fitting locking mechanism 94 locks the fitting (not shown) into engagement with the driver 14. The fitting locking mechanism 94 includes a locking sleeve 100, axially biased by a spring 96 acting against a recess 94 in the 20 selector 50.

The ratchet 10 enables easy disassembly for cleaning, which involves the following steps. In a first disassembly step, the locking ring 24 is twisted to an unlocked position. In a second disassembly step, the internal ratchet body 108 (the assembled-together driver 14 and ratchet mechanism 16) is removed for cleaning.

25 Further, a simple method of assembly is provided which includes the following steps. In a first assembly step, the ratchet body 108 is inserted into the handle 12. In a second assembly step, an alignment pin (not shown) is aligned with a slot 102 in the handle 12 in order that the user properly aligns the ratchet body with the handle. In a third assembly step, the body 108 is pushed into the handle 12 until it can go no further. In a fourth assembly step, the locking ring

24 is then twisted into a locking position. In an optional fifth assembly step, a tool 58 is selected from a kit 150, and inserted into the driver 14. The ratchet assembly 10 is now ready for use.

Referring now to FIG. 6, the kit 150 is shown, including the ratchet 10, a tool 130, 132, 134, 136, a T-bar 138 and a guide pin 139. The components of the kit 150 are organized in a case 160 for convenience.

The T-bar 138 includes a square plug drive that mates with the end 36 having a corresponding female socket 140. In this alternate embodiment, the end 36 is either integral with or firmly affixed to the other components of the driver 14 so as to be able to effectively transmit torque therethrough.

10 In an advantage of the invention, a surgical ratchet is provided that is readily disassembled for cleaning and sterilization.

In another advantage of the invention, a reliable ratchet is provided that is easy to operate.

In another advantage, an assembly method is provided involving only a few simple steps.

15 In another advantage, a kit is provided which presents the ratchet 10 and related components to the surgeon in a convenient, organized fashion.

In another advantage, a T-bar attachment enables increased torque to be transmitted through to the object being driven, by virtue of the large lever arm distance afforded by the T-bar.

Convenience is gained because it is not necessary to re-grip the T-bar each time torque is to be input—rather, the ratchet mechanism enables easy and advantageous repositioning.

20 Multiple variations and modifications are possible in the embodiments of the invention described here. Although certain illustrative embodiments of the invention have been shown and described here, a wide range of modifications, changes, and substitutions is contemplated in the foregoing disclosure. In some instances, some features of the present invention may be employed without a corresponding use of the other features. Accordingly, it is appropriate that the 25 foregoing description be construed broadly and understood as being given by way of illustration and example only, the spirit and scope of the invention being limited only by the appended claims.

What is Claimed is:

- 1 A surgical ratchet having a handle, a driver received within the handle in a rotatable relationship with respect thereto, a ratcheting mechanism interposed between the handle and driver, and a locking mechanism releasably holding the handle to the ratchet mechanism, wherein unlocking of the locking mechanism enables ready disassembly of the ratchet mechanism from the handle.
- 2 The ratchet of claim 1, wherein the locking mechanism comprises a ring rotatable on the handle, the ring having a surface selectively biasing a ball into or out of a recess to engage or disengage the ratchet mechanism to lock or unlock the assembly.
- 3 The ratchet of claim 1, wherein the locking mechanism comprises a surface against which a user may apply pressure to effectuate a change in interactivity of components in order to engage or disengage the ratchet mechanism to lock or unlock the assembly.
- 4 The ratchet of claim 1, wherein a selector enables a user to activate, deactivate, or lock the ratcheting mechanism.
- 5 The ratchet of claim 1, wherein the locking mechanism is comprised of a selector having a position in which at least one pawl is in an engaged position, wherein, when the selector is in the engaged position, the at least one pawl locks the ratchet mechanism against free movement in a selected direction.
- 6 The ratchet of claim 1, wherein the locking mechanism is comprised of a selector having a position in which at least one pawl is in a released position, wherein, when the selector is in the released position, the at least one pawl disengages the ratchet mechanism, thus permitting free motion in either direction.

- 7 The ratchet of claim 1, wherein a portion of the driver protrudes from an end of the handle, thereby presenting an impaction surface enabling the ratchet to be used as an impactor.
- 8 The ratchet of claim 1, wherein the ratcheting mechanism comprises
 - (a) a housing in which left and right hand pawls are pivotably connected and selectively pivotably engageable by a cam selection device for selection of a ratcheting direction; and
 - (b) a toothed hub connected, at least indirectly, to the handle.
- 9 The ratchet of claim 8, wherein the cam selection device comprises a cam having a cam surface against which an end of the at least one pawl rides and wherein relative movement of the cam surface to the end of the at least one pawl causes the pawl to pivot in a prescribed manner.
- 10 The ratchet of claim 8, wherein an end of the at least one pawl engaging the toothed hub is formed so as to permit relative rotation with respect to the hub in one rotational direction, and to block rotation in the opposite rotational direction.
- 11 A surgical ratchet having a handle, a driver received within the handle in a rotatable relationship with respect thereto, a ratcheting mechanism interposed between the handle and driver, and a locking mechanism releasably holding the handle to the ratchet mechanism,
wherein the locking mechanism comprises a ring rotatable on the handle, the ring having a surface which selectively biases a ball into or out of a recess to engage or disengage the ratchet mechanism to lock or unlock the assembly, whereby unlocking of the locking mechanism enables ready disassembly of the ratchet mechanism from the handle,

wherein the ratcheting mechanism comprises

- (a) a housing in which left and right hand pawls are pivotably connected and selectively pivotably engageable by a cam selection device for selection of a ratcheting direction, the cam selection device comprising a cam having a cam surface against which an end of the at least one pawl rides and wherein relative movement of the cam surface to the end of the at least one pawl causes the pawl to pivot in a prescribed manner;
- (b) a toothed hub connected, at least indirectly, to the handle, and
- (c) a selector which has a position in which at least one pawl is in an engaged position, wherein, when the selector is in the engaged position, the at least one pawl locks the ratchet mechanism against free movement in a selected direction, thus enabling a user to activate, deactivate, or lock the ratcheting mechanism.

- 12 The ratchet of any of the foregoing claims, wherein the handle is a T-bar.
- 13 The ratchet of any one of claims 1-11, wherein the handle includes an interface for receiving a T-bar attachment.
- 14 A tool kit for surgical use, the tool kit including at least the following components:
 - (a) a surgical ratchet having a handle, a driver received within the handle in a rotatable relationship with respect thereto, a ratcheting mechanism interposed between the handle and driver, and a locking mechanism releasably holding the handle to the ratchet mechanism, wherein unlocking of the locking mechanism enables ready disassembly of the ratchet mechanism from the handle;
 - (b) at least one tool bit selected from a group of tool bits consisting of drills, taps, guide pins, screwdrivers, reamer drivers, and wire introducers; and
 - (c) a case for receiving the ratchet and the at least one tool bit.

AMENDED CLAIMS

[received by the International Bureau on 04 October 2004 (04.10.2004);
original claims 1-14 replaced by amended claims 1-14 (3 pages)]

- 1 A surgical ratchet (10) having a handle (10), a driver (14) received within the handle in a rotatable relationship with respect thereto, a ratcheting mechanism (16) interposed between the handle and driver, and a locking mechanism (20) releasably holding the handle to the ratchet mechanism, wherein displacing of the locking mechanism to an unlock position moves a locking obstruction (32) out of an obstructing position thereby permitting easy release of the ratchet mechanism from the handle and ready disassembly of the ratchet mechanism from the handle.
- 2 The ratchet (10) of claim 1, wherein the locking mechanism (20) comprises a ring (24) rotatable on the handle (12), the ring having a surface selectively biasing a ball (32) into or out of a recess (34) to engage or disengage the ratchet mechanism (16) to lock or unlock the assembly.
- 3 The ratchet (10) of claim 1, wherein the locking mechanism (20) comprises a surface against which a user may apply pressure to effectuate a change in interactivity of components in order to engage or disengage the ratchet mechanism (16) to lock or unlock the assembly.
- 4 The ratchet (10) of claim 1, wherein a selector (50) enables a user to activate, deactivate, or lock the ratcheting mechanism (16).
- 5 The ratchet (10) of claim 1, wherein the locking mechanism (20) is comprised of a selector (50) having a position in which at least one pawl (44, 46) is in an engaged position, wherein, when the selector is in the engaged position, the at least one pawl locks the ratchet mechanism against free movement in a selected direction.
- 6 The ratchet (10) of claim 1, wherein the locking mechanism (16) is comprised of a selector (50) having a position in which at least one pawl (44, 46) is in a released position, wherein, when the selector is in the released position, the at least one pawl disengages the ratchet mechanism, thus permitting free motion in either direction.

- 7 The ratchet (10) of claim 1, wherein a portion of the driver (14) protrudes from an end (36) of the handle (12), thereby presenting an impaction surface enabling the ratchet to be used as an impactor.
- 8 The ratchet (10) of claim 1, wherein the ratcheting mechanism (16) comprises
 - (a) a housing (22) in which left and right hand pawls (44, 46) are pivotably connected and selectively pivotably engageable by a cam selection device (50) for selection of a ratcheting direction; and
 - (b) a toothed hub (52) connected, at least indirectly, to the handle.
- 9 The ratchet (10) of claim 8, wherein the cam selection device (50) comprises a cam having a cam surface (53) against which an end (66, 67) of the at least one pawl (44, 46) rides and wherein relative movement of the cam surface to the end of the at least one pawl causes the pawl to pivot in a prescribed manner.
- 10 The ratchet (10) of claim 8, wherein an end (66, 67) of the at least one pawl (44, 46) engaging the toothed hub (52) is formed so as to permit relative rotation with respect to the hub in one rotational direction, and to block rotation in the opposite rotational direction.
- 11 A surgical ratchet (10) having a handle (12), a driver (14) received within the handle in a rotatable relationship with respect thereto, a ratcheting mechanism (16) interposed between the handle and driver, and a locking mechanism (20) releasably holding the handle to the ratchet mechanism,
wherein the locking mechanism (20) comprises a ring (24) rotatable on the handle, the ring having a surface (53) which selectively biases a ball (32) into or out of a recess (34) to engage or disengage the ratchet mechanism (16) to lock or unlock the assembly, whereby displacing of the locking mechanism (20) into an unlock position moves a locking obstruction (32) out of an obstructing position thereby permitting easy release of the ratchet mechanism from the handle and ready disassembly of the ratchet mechanism from the handle,
wherein the ratcheting mechanism (16) comprises

(a) a housing (22) in which left and right hand pawls (44, 46) are pivotably connected and selectively pivotably engageable by a cam selection device (50) for selection of a ratcheting direction, the cam selection device comprising a cam having a cam surface against which an end of the at least one pawl rides and wherein relative movement of the cam surface to the end of the at least one pawl causes the pawl to pivot in a prescribed manner;

(b) a toothed hub (52) connected, at least indirectly, to the handle, and

(c) a selector (50) which has a position in which at least one pawl (44, 46) is in an engaged position, wherein, when the selector is in the engaged position, the at least one pawl locks the ratchet mechanism against free movement in a selected direction, thus enabling a user to activate, deactivate, or lock the ratcheting mechanism.

12 The ratchet (10) of any of the foregoing claims, wherein the handle (12) is a T-bar (138).


13 The ratchet (10) of any one of claims 1-11, wherein the handle (12) includes an interface (140) for receiving a T-bar attachment (138).

14 A tool kit (150) for surgical use, the tool kit including at least the following components:

(a) a surgical ratchet (10) having a handle (12), a driver (14) received within the handle in a rotatable relationship with respect thereto, a ratcheting mechanism (16) interposed between the handle and driver, and a locking mechanism (20) releasably holding the handle to the ratchet mechanism, wherein displacing of the locking mechanism to an unlock position moves a locking obstruction (32) out of an obstructing position, thereby permitting easy release of the ratchet mechanism from the handle and ready disassembly of the ratchet mechanism from the handle;

(b) at least one tool selected from a group of tools consisting of drills (134), taps (136), guide pins (130), screwdrivers (132), reamer drivers, and wire introducers; and

(c) a case (160) for receiving the ratchet and the at least one tool.








FIG. 1B







FIG. 3

**FIG. 4**





FIG. 5



INTERNATIONAL SEARCH REPORT

In nal Application No
PCT/1B2004/001244

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B17/88 B25B15/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61B B25B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 299 616 B1 (BEGER JENS) 9 October 2001 (2001-10-09) column 9, line 20 – line 30; figures ___	1-14
A	DE 201 06 370 U (HUANG CHIN TAN) 21 June 2001 (2001-06-21) figures -----	1-14

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

◦ Special categories of cited documents:

- **A*** document defining the general state of the art which is not considered to be of particular relevance
- **E*** earlier document but published on or after the international filing date
- **L*** document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- **O*** document referring to an oral disclosure, use, exhibition or other means
- **P*** document published prior to the international filing date but later than the priority date claimed

- T** later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- X** document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- Y** document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- &** document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
26 July 2004	04/08/2004
Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Held, G

INTERNATIONAL SEARCH REPORTInt'l Application No
PCT/IB2004/001244

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 6299616	B1	09-10-2001	DE 19851370 A1	18-05-2000
DE 20106370	U	21-06-2001	DE 20106370 U1	21-06-2001