



- (51) **International Patent Classification:**
H04N 21/436 (201 1.01) *H04L 12/28* (2006.01)
G06F 3/06 (2006.01)
- (21) **International Application Number:**
PCT/EP2012/075710
- (22) **International Filing Date:**
17 December 2012 (17. 12.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
11306695.5 19 December 2011 (19. 12.2011) EP
- (71) **Applicant:** THOMSON LICENSING [FR/FR]; 1-5 rue Jeanne d'Arc, F-92130 Issy-les-Moulineaux (FR).
- (72) **Inventors:** VANDERHALLEN, Frank; Pater Verboislaan 23, B-3621 Lanaken (BE). CHANET, Dominique; Leopoldlaan 32B bus 9, B-9300 Aalst (BE). FREDERLX, Guy; Kerkstraat 12 bus 401, B-8560 Gullegem (BE). HAESAERTS, Kristl; Hoogveldweg 8, B-1820 Melsbroek (BE).

- (74) **Agent:** ARNOLD, Klaus-Peter; Deutsche Thomson OHG, European Patent Operations, Karl-Wiechert-Allee 74, 30625 Hannover (DE).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on nextpage]

(54) **Title:** METHOD FOR OPERATING A UNIVERSAL PLUG AND PLAY AV SYSTEM, RESPECTIVE SYSTEM AND CONTROL DEVICE




Fig. 4

(57) **Abstract:** The method relates to a Universal Plug and Play AV system, which comprises server device (13), a display device (15) and a control device (14) including a control point (2) for controlling the server device and the display device via Universal Plug and Play AV actions. The method comprises the steps of arranging an unmount icon (21, 22) in the display (17) of the control device (14), unmounting the storage device (11, 12) in case said unmount icon (21, 22) is operated, and providing a feedback on the display device (15) and/or the control device (14) after said unmount action was performed on the server device (13).

WO 2013/092459 A1

Published:

— *with international search report (Art. 21(3))*

**METHOD FOR OPERATING A UNIVERSAL PLUG AND PLAY AV SYSTEM,
RESPECTIVE SYSTEM AND CONTROL DEVICE**

TECHNICAL FIELD

5

The present invention relates to a Universal Plug and Play AV system comprising a media server, a media renderer and a control point for controlling the media server and the media renderer and for providing defined actions for rendering pictures, music and videos via Universal Plug and Play AV actions.

BACKGROUND OF THE INVENTION

15 USB (Universal Serial Bus) and Firewire, IEEE 1394, are standard digital interfaces for connecting devices to a personal computer. These interfaces are hot-pluggable, which means that devices can be plugged in and unplugged from the interface without rebooting the personal computer, and connected devices are automatically recognized by the personal computer, which is described as "Plug and Play". One class of available USB or Firewire devices are storage devices like hard disks, memory sticks or other flash memory devices. USB and Firewire storage devices should always be unmounted before they are disconnected from the interface to avoid any data loss during a not finished operation. However, the USB and the Firewire interface have no mechanism to prevent users from disconnecting a storage device which is still mounted. In most user scenarios, the unmount action has to be triggered by the end user. Therefore, performing this unmount action should be as less cumbersome as possible.

An extension of "Plug and Play" is UPnP, "Universal Plug and Play", which is defined by an International Standard, ISO/IEC 29341. UPnP defines control points which are

35

devices using UPnP protocols to control UPnP devices and defines actions for rendering pictures, music and videos. Although a control point can manage multiple UPnP devices, all interactions occur in isolation between the control
5 point and each UPnP device. The individual UPnP devices do not interact directly with each another. In particular residential gateways usually include a UPnP architecture to allow device-to-device networking with personal computers, networked home appliances, removable storage devices or
10 other consumer electronics devices.

An audio and video extension of UPnP is UPnP AV (UPnP for Audio/Video) , which allows a higher level of interoperability between UPnP devices. UPnP AV allows to
15 deliver streaming media, for example real-time audio/video streams, for which it is critical to be delivered within a specific time, or the stream is interrupted. The current UPnP AV v2 specification is defined by the UPnP Forum, which is a group of companies and individuals across
20 multiple industries that play a leading role in the authoring of specifications for UPnP devices and services.

UPnP AV defines three services: a media server for serving media content, a media renderer capable of playing one or
25 more media formats, and a control point for controlling the media server and the media renderer. An environment with a UPnP AV media server 1, a control point 2 and a media renderer 3 is shown in Fig. 1, wherein the media server, the media renderer and the control point are separate
30 devices according to a 3-Box model. The media server 1 may have for example a USB or Firewire digital interface, via which a removable storage device containing audio/video media can be connected to the media server 1. The control point 2 coordinates the operation of the media server 1 and
35 the media renderer 3 to achieve an overall, synchronized end-user effect. The media server 1 and the media renderer

3 do not interact directly with each another, all of the coordination between the two devices is performed by the control point 2.

5 In Fig. 2 a situation is shown wherein the media server 1 is implemented in a residential gateway 13, to which two USB storage disks 11, 12 are attached. On a smartphone 14 an UPnP AV control point application has been installed, so that the smartphone 14 can operate as a control point 2 as
10 described with regard to Fig. 1. The media renderer 3 is a flat-screen TV 15, which is capable of playing movies, music and pictures. The residential gateway 13 comprises a webserver 16 for providing Internet services, which webserver includes a webpage as a user interface to be used
15 by a user for configuring the residential gateway 13. The user browses through the media file collection on the media server 1 by making use of the control point software of his smartphone 14.

20 The media files are organized in a hierarchy of file containers, which is similar to a file system organizing files in directories, which can be displayed in a display 17 of the smartphone 14. The file containers are arranged for example in a root container or root container of the
25 smartphone 14, and for each media category "music", "movies" and "pictures" advantageously a dedicated file container is provided. The user can navigate with the smartphone 14 through the media just like with a file system explorer. When the user selects a media file on the media
30 server 1 to play, step A, a play action message is send from the smartphone 14 to the media server 1, step B. The media server 1 acts on the play message by streaming the selected media file towards the media renderer 3, step C.

35 Now, the user wants to disconnect one of the storage disks 11, 12. Before disconnecting a disk, the user has to

5 unmount the disk in order to avoid file system corruption. However, the UPnP AV specification does not define an action for unmounting of disks. Therefore, manufacturers of media servers with support for external disks implement a proprietary solution for unmounting of external disks.

In Fig. 3, an unmount method available in many media servers, including residential gateways, is illustrated. The webserver 16 has a webpage 18, dedicated for unmounting
10 of external storage devices. For unmounting one of the storage disks 11, 12, the user has to perform the following steps :

- the user has to open a web browser on the controlling device, i.e. the smartphone 14 as the
15 control point 2, step D,
- the user has to surf to the web interface of the media server 1, step E, so he has to know the IP address of the media server 1,
- the user usually needs to enter a login and/or a
20 password to gain access to the web pages of the media server 1, step F,
- the user should know on which web page: web page 18, the unmount buttons 19 are located, which may not be obvious for a novice user, and
- The user has to surf to the webpage 18, step G, click on the web page 18, step H, so that the web
25 page 18 opens on the display 17 of the smart phone 14, step I, and to click on one of the unmount buttons 19, step J.

30

This method for unmounting a disk in an UPnP AV environment is therefore not user friendly. It is also noted that a web browser is not per definition available on a control point: instead of a smartphone, also any other possible control
35 point device, for example a dedicated remote control unit without a web browser, may be used. The necessity to start

another application and having to know technical details, like the IP address of the media server 1, are against the plug and play philosophy of the UPnP protocol. Since it is so cumbersome in an UPnP AV environment to unmount a disk with this method, it is not uncommon that many users will not use this method, and disconnect a disk without unmounting it. This will almost certainly lead to file system corruption in a percentage of cases, and it may even result in data loss. The user manual can describe that an external disk should always be unmounted before it will be disconnected, which is good as a countermeasure against legal claims, but it will not avoid that users disconnect mounted disks.

As a further remark, the current USB and Firewire specifications do not allow to use a hardware solution for the unmount problem. For instance, it is supposed that the residential gateway 13 has a hardware unmount button close to the USB and Firewire interfaces, and a status LED indicates when it is safe to disconnect the disk. Such a hardware implementation will only work when only one disk is connected to the interface of the residential gateway 13. But since USB and Firewire are bus interfaces, multiple disks can be connected to the interface by making use of a hub. Thus, when using a hub, selective unmounting is not possible with such a hardware implementation, because either all disks will be unmounted at once, or no disk will be unmounted at all.

External, respectively portable storage devices are also used with personal computers and laptops. Unmounting a storage device makes it inaccessible by the computer. In order for a storage device to be unmounted, it must first be mounted. Mounting takes place before a computer can use the respective storage device and is done automatically in accordance with the "Plug and Play" architecture. When a

storage disk is mounted, it is active and the computer can access its contents. Since unmounting a disk prevents the computer from accessing it, there is no risk of the disk being disconnected in the middle of a data transfer.

5 Therefore, before removing an external storage device, such as a USB flash drive or a USB hard disk, the storage device should be unmounted to avoid possible data corruption.

Several types of storage devices can be unmounted,
10 including external hard drives, USB flash drives, iPods, flash memory cards, and disk images. In order to unmount a disk in the Microsoft Windows operating system, the following steps are necessary: opening "My Computer," selecting the disk, and clicking the "Eject this disk"
15 option in the left sidebar. In the Apple Mac OS X operating system, the following steps are necessary: selecting the disk on the desktop and either drag the disk to the trash, which changes to an Eject icon, or selecting "File→Eject" from the Finder's menu bar. Once a removable disk has been
20 unmounted, it can safely be disconnected from the computer.

US 7,234,014 describes a portable storage device including a body, an actuator and an indicator. When the storage device is coupled to a host device, an unmount operation
25 can be performed by a user by depressing the actuator, which causes an interrupt message to be send to the host device for initiating shut-down of the portable storage device by removing it from a host device list of available storage media, and which depowers the portable storage
30 device. After the unmount operation, the indicator then changes to signify that it is safe now to remove the portable storage device from the host device.

US 2006/0200570 describes a method for mounting network
35 file systems to a client arrangement via a peer-to-peer local area network, which uses a network file protocol

being compatible with the client arrangement. A network file system can be unmounted by using the compatible network file protocol in response to a signal for disconnecting the client arrangement from the peer-to-peer
5 local area network.

SUMMARY OF THE INVENTION

The invention defines a method for operating a Universal
10 Plug and Play AV system, which comprises a server device including a media server, a display device including a media renderer and a control device including a control point for controlling the server device and the display device via Universal Plug and Play AV actions. The server
15 device comprises a digital interface for coupling with a removable storage device, and the control device comprises a user interface with a display for displaying a list of media files stored on the storage device. The method comprises the steps of arranging an unmount icon in the
20 display of the control device and unmounting the storage device in case said unmount icon is operated. The unmount icon is displayed in particular in a container or directory of the control device, in which the media files of the storage device are displayed, and is associated with an
25 action on the media server which performs the unmount operation of the storage device. The container or directory is provided by the media server, which arranges advantageously automatically the unmount icon in the container or directory, when a storage device is coupled to
30 the digital interface and mounted.

In a further aspect of the invention, the unmount icon is displayed in a root container or root directory, which includes the containers or directories of the media files.
35 In particular, a device-specific unmount icon is provided in the display of the control device for each storage

device being coupled to the digital interface, and the storage device specific unmount icon is removed from the display, when an unmount operation for a respective storage disk is finished. Advantageously, all unmount icons are
5 arranged in the same container or directory of the control device .

The invention relates further to a system comprising a server device having a digital interface, to which a
10 removable storage device is coupled, a display device, and a control device including a control point for operating the server device and the display device, the control device comprising a user interface with a display for displaying a list of media files stored in the storage
15 device, for utilizing the method. The digital interface is in particular a USB interface, a Firewire interface or a smart card interface, and the system is in a preferred embodiment a UPnP AV system.

20 The invention defines further a control device utilizing the method. The server device is for example a residential gateway or a set-top box, the control device a smartphone, a tablet PC or a remote control, and the display device a smart TV or a computer monitor.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the invention are explained in more detail below by way of example with reference to
30 schematic drawings, which show:

Fig. 1 a generic UPnP AV system including a media server, a control point and a media renderer,
Fig. 2 a UPnP AV system including a residential gateway
35 as the media server, to which two removable storage devices are coupled,

Fig. 3 the UPnP AV system as shown in Fig. 2 illustrating an unmount operation for one of the removable storage devices according to prior art, and
5 Fig. 4 illustrating an unmount operation according to the invention for one of the removable storage devices of a UPnP AV system as shown in Fig. 2.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

10

The method according to the present invention for operating an UPnP AV system, in particular the UPnP AV system as described with regard to Figs. 2 and 3, involves a few essential changes of the media server implementation as
15 included for example in a residential gateway. The Universal Plug and Play AV system comprises a media server, a media renderer and a control point for operating the media server and the media renderer, wherein the control point controls the media server via Universal Plug and Play
20 AV actions, as defined for example in the current UPnP AV v2 standard or any further UPnP AV standard. The media server comprises in particular a digital interface to which a removable storage device is coupled, and includes dedicated executable files, which let a user trigger an
25 unmount operation easily via the control point. When the user triggers the unmount action of the storage device for performing the unmount operation, the storage device will be unmounted and he will be informed when it is safe to disconnect the storage device via a message displayed on
30 the control point and/or the media renderer. For example, an unmount icon is arranged in the display of the display device for each storage device coupled to the server device and each unmount icon is linked with the respective executable file for performing the unmount operation of a
35 storage device, which the user wants to remove.

The unmount icons of the executable files contain advantageously storage device specific information on the display and when an unmount operation is triggered by a user, an information is presented for the user, indicating
5 when it is safe to unmount the respective storage device. This information can be static, i.e. a fixed image, or can be generated on the fly such that it contains storage device specific information, e.g. a recorded voice informing the user about the volume name of the storage
10 device that has been unmounted.

The filename of the executable file as shown in the display of the control point may be displayed for example in addition on the display of the display device, and/or of
15 the control device, when the unmount action of the respective storage device has finished. The executable files contain corresponding metadata to allow annotating each executable file with the respective information.

20 A preferred embodiment of the invention is described now with regard to Fig. 4, which shows a media server 1, a control point 2 and a media renderer 3, as described with regard to Figs. 1-3. The media server 1 is in this embodiment included in a residential gateway 13, to which a
25 first and a second removable and portable storage device, storage disks 11, 12, are connected. The control point 2 is implemented in a smartphone 14 or any other remote control, and the media renderer 3 is implemented in a television set 15. The storage disks 11, 12 are in particular coupled via
30 an USB or a Firewire bus to the residential gateway 13 and therefore to the media server 1. The storage disks 11, 12 are e.g. hard disks or flash memory storage devices and comprise audio and video files, photos and other data files .

The media files may be organized in a hierarchy of file containers, which are arranged for example in a root container or a root directory of the media server 1 and can be displayed in a display 17 of the smartphone 14, as
5 described already with regard to Figs. 2 and 3. By using the software of the control point 2 as included in the smartphone 14, a user can open a file container "Music" or "Pictures" and stream respective audio or video files from the storage disks 11, 12 via the media server 1 to the
10 media renderer 3 for playback.

The smartphone 14 comprises a user interface providing in the display 17 a multitude of smartphone applications and the root container with the file containers, in which the
15 music files, movie files, pictures and other data are listed, and which comprises a browse function 23. In particular, the music files are arranged within a music container, the movie files within a movie container, and the pictures within a picture container. In addition, an
20 unmount icon 21 is arranged in the root container for unmounting the storage disk 11 and an unmount icon 22 for unmounting the storage disk 12, when the root container is opened in the display 17 of the smartphone 14. The unmount icons 21, 22 are e.g. displayed as images in the display
25 17, which can be selected by moving a cursor to an image by means of the buttons of the smartphone 14 and by pushing a respective select button, or by touching the image with a finger in case the display 17 includes a touchscreen.

30 When a user wants to hear music or to see a video file with the UPnP AV system, he switches on the smartphone 14, television set 15 and gateway 13, if not already in operation, and selects and opens on the smartphone the root container in the display 17 for opening the music, movie
35 and picture containers, for a display of the media files on the display 17 of the smartphone 14. He uses e.g. the

browse function 23 for locating a favourite movie in the movie directory, and when the user has selected that video with the browse function 23, the smartphone 14 forwards a respective play command to the media server 1 of the residential gateway 13, e.g. via a WiFi connection. Then, the media server 1 locates the requested video in one of the storage disks 11, 12 and streams the video to the television set 15 for a playback of the video.

10 When a user wants to disconnect one of the storage devices 11, 12, e.g. storage device 12, the user has to unmount the storage device 12. The user opens therefore the root container of the smartphone 14, in which the unmount icon 21 for storage device 11 and unmount icon 22 for storage
15 device 12 are each displayed as a picture, step K. In a further step L, the user selects the unmount icon 21 by using the control elements of the smartphone 14, the control buttons or by simply touching the unmount icon 21 in case of a touch sensitive display, to start the unmount
20 operation for the storage device 12. When the unmount icon 21 is triggered, step M, the smartphone sends a respective unmount request to the media server 1 of the residential gateway 13, step O. The storage device 12 is then logically removed from the media server 1, step P. When the unmount
25 operation has terminated, an image of the storage device 2 or any other storage device specific information is displayed for example on the media renderer 3, the television set 15, and/or in addition any text or an auto information is displayed for informing that the storage
30 device 12 has been unmounted and that it is safe now to remove storage device 12, step R. Alternatively or in addition, the information that the storage device can be safely removed is displayed on the display 17 of the control point 2, smartphone 14. In a further step S, the
35 unmount icon 21 disappears from the display 17, when the

unmount operation for the storage disk 12 has been finished by the media server 1.

When the user connects the storage device 12 again at a later time to the digital interface of the gateway 13, the media server 1 mounts the storage device 12 for the UPnP AV system and arranges the unmount icon 22 again in the root container of the media server 1. Correspondingly, the unmount icon 22 is displayed again in the display 17 of the smartphone 14, when the root container is opened in the display 17.

The method as described is fully compliant to the UPnP AV specification. Although the method will not avoid disconnecting of a mounted disk, which is an inherent flaw is the USB specification, it will provide a convenient and easily visible method to trigger the unmount action also for inexperienced users. Since unmounting requires user interaction, manufacturers of media servers are obliged to make the unmount process as user friendly as possible. The method as described discloses and allows therefore manufacturers to provide a user friendly unmount method for UPnP AV media servers.

The unmount icons 21, 22 are advantageously arranged together with movie, music and picture directories, representing media file directories, in a root directory of the smartphone 14, so that the user is always aware, where the unmount buttons for the storage devices are located. The file directories can be understood also as file containers, and the root directory as a root container.

The method as described with regard to figure 4 is not only applicable to a three box system, as described with regard to figure 4, but may be used also for any two box system or

even a one box system as defined by the UPnP AV specification .

For example, the media server 1 and the media renderer 2
5 may be included within one device, e.g. a television set comprising an USB interface, to which one or several USB hard disks or any other USB storage devices can be connected. The user can browse then with the control point 2, included e.g. in any smartphone or a remote control of
10 the television set, through the audio files, video files and pictures as included in the storage device connected to the television set. An unmounting of this storage device can be performed correspondingly in accordance with the method as described with regard to Fig. 4 .

15

In another embodiment, the UPnP AV system comprises a residential gateway or a set-top box including a media server and a webserver, and the control point function and the media renderer are implemented within an E-book, an I-
20 Pad or any other smart device. The method describes therefore a generically applicable method, via which a user can easily unmount a storage device coupled to a media server within an UPnP system, in particular an UPnP AV system, to avoid that a user disconnects for ease a mounted
25 storage device.

Also other embodiments of the invention may be utilized by one skilled in the art without departing from the scope of the present invention. The invention resides therefore in
30 the claims herein after appended.

Claims

1. A method for operating a Universal Plug and Play AV system comprising
 - 5 a server device (13) including a media server (1) , having a digital interface, to which a removable storage device (11, 12) is coupled,
 - a display device (15) including a media renderer (3) , and
 - 10 a control device (14) including a control point (2) for controlling the server device and the display device, the control device (14) comprising a user interface with a display (17) for displaying a list of media files stored in the storage device and providing
 - 15 defined actions for rendering pictures, music and videos via Universal Plug and Play AV actions, the method **comprising the steps**
 - arranging an unmount icon (21, 22) in the display (17) of the control device (14),
 - 20 unmounting the storage device (11, 12) in case said unmount icon (21, 22) is operated, and
 - providing a feedback on the display device (15) and/or the control device (14) after said unmount action was performed on the server device (13) .
- 25 2. The method of claim 1 , comprising the step of displaying the unmount icon (21, 22) in a container or a directory of the control device (14), in which the media files of the storage device are displayed.
- 30 3. The method of claim 2 , comprising the step of displaying the unmount icon (21, 22) in a root container or a root directory of the control device (14), in which said container or directory is
- 35 displayed .

4. The method of claim 1, 2 or 3, comprising the steps of
providing the unmount icon (21, 22) in said
display (17) when said storage device (11, 12) is
coupled to the digital interface and mounted, and
5 removing said unmount icon (21, 22) from the
display (17), when the unmount operation for the
storage device (11, 12) is finished.
5. The method of one of the preceding claims, comprising
10 the steps of providing a device-specific unmount icon
(21, 22) in the display (17) of the control device (14)
(2) for each storage device being coupled to the
digital interface, and
removing the device specific unmount icon (21,
15 22) from the display (17), when an unmount operation
for said specific storage device (11, 12) is finished.
6. The method of claim 5, comprising the step of
displaying all unmount icons (21, 22) in the same
20 container or directory of the control device (14) .
7. The method of claim 5 or 6, wherein each unmount icon
(21, 22) is linked with an executable file performing
the unmount operation of a respective storage device
25 (11, 12) .
8. The method of one of the preceding claims, comprising
the step of sending after the unmount operation an
information to the control device (14) and/or the media
30 renderer (3) to inform the user that it is now safe to
unplug the storage device (11, 12) .
9. The method of one of the preceding claims, wherein the
digital interface is a USB interface, a Firewire
35 interface or a smart card interface.

10. A method for operating a Universal Plug and Play AV system comprising
- a server device (13) including a media server (1) , having a digital interface, to which a removable storage device (11, 12) is coupled,
 - a display device (15) including a media renderer (3) , and
 - a control device (14) including a control point (2) for controlling the server device and the display device, the control device (14) comprising a user interface with a display (17) for displaying a list of media files stored in the storage device in a container or a directory of the control device (14) and providing defined actions for rendering pictures, music and videos via Universal Plug and Play AV actions, the method **comprising the steps**
 - arranging an unmount icon (21, 22) in said container or directory of the control device (14), in which the media files of the storage device are displayed,
 - unmounting the storage device (11, 12) in case said unmount icon (21, 22) is operated, and
 - providing a feedback on the display device (15) and/or the control device (14) after said unmount action was performed on the server device (13) .
11. The method of claim 10, comprising the steps of
- providing the unmount icon (21, 22) in said container or directory when said storage device (11, 12) is coupled to the digital interface and mounted, and
 - removing said unmount icon (21, 22) from said container or directory, when the unmount operation for the storage device (11, 12) is finished.

12. The method of claim 10 or 11, comprising the step of displaying the unmount icon (21, 22) in a root container or a root directory of the control device (14), in which said container or directory including the media files are displayed.
- 5
13. The method of one of the preceding claims, comprising the steps of providing a device-specific unmount icon (21, 22) in the display (17) of the control device (14) (2) for each storage device being coupled to the digital interface, and removing the storage device specific unmount icon (21, 22) from the display (17), when an unmount operation for said specific storage device (11, 12) is finished.
- 10
- 15
14. The method of one of the preceding claims, comprising the step of displaying all unmount icons (21, 22) in the same container or directory of the control device (14) .
- 20
15. System comprising a server device (13) having a digital interface, to which a removable storage device (11, 12) is coupled, and including a display device (15) including a media renderer (3) , and a control device (14) including a control point (2) for operating the server device and the display device, the control device (14) comprising a user interface with a display (17), for utilizing a method according to one of the preceding claims.
- 25
- 30
16. The system of claim 15, wherein the system is a Universal Plug and Play AV system according to the UPnP AV v2 specification.
- 35

17. A control device (14) including a control point (2) for
controlling a server device (13) including a media
server (1) and a display device (15) including a media
renderer (3), the control device (14) being adapted for
5 controlling the media server and the media renderer and
comprising a user interface with a display (17) for
displaying a list of media files stored in a removable
storage device (11, 12) coupled to the server device
(13) and providing defined actions for rendering
10 pictures, music and videos via Universal Plug and Play
AV actions, **characterized in that** .

an unmount icon (21, 22) is arranged in the
display (17) of the control device (14), and in case
said unmount icon (21, 22) is operated, unmounting the
15 storage device (11, 12) and providing a feedback on
the media device (15) and/or the control device (14)
after said unmount action was performed on the server
device (13) .

20 18. The control device of claim 17, wherein the unmount
icon (21, 22) is displayed in a container or a
directory of the control device (14), in which the
media files of the storage device are displayed.

25 19. The method of claim 18, wherein the unmount icon (21,
22) is displayed in a root container or a root
directory of the control device (14), in which said
container or directory is displayed.




Fig. 1




Fig. 2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2012/075710

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04N21/436 G06F3/06 H04L12/28
 ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04N G06F H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal , WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2008/253747 AI (MIYAZAKI KOJI [JP]) 16 October 2008 (2008-10-16) paragraph [0020] paragraph [0029] - paragraph [0032] paragraph [0063] - paragraph [0068] paragraph [0073] - paragraph [0078] -----	1-19
X	Steven Si nofsky: "Medi a streami ng wi t h Wi ndows 7", , 12 May 2009 (2009-05-12) , XP055054338, Retri eved from the Internet: URL: http ://bl ogs .msdn .com/b/e7/archi ve/200 9/05/ 12/medi a- streami ng-wi t h-wi ndows -7 .asp X [retri eved on 2013-02-22] the whol e document ----- -/- .	1-19

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search 25 February 2013	Date of mailing of the international search report 04/03/2013
--	---

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Bi ro, Zol tan
--	---

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2012/075710

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>Grantemsl ey: "How to safely remove USB drive from batch file", , 22 January 2006 (2006-01-22) , pages 1-12 , XP055025531 , Retri eved from the Internet: URL: http ://portabl eapps .com/node/639 [retri eved on 2012-04-24] the whol e document</p> <p style="text-align: center;">-----</p>	1-19
X	<p>US 2006/200570 AI (STI RBU VLAD [FI] ET AL) 7 September 2006 (2006-09-07) cited in the applicati on the whol e document</p> <p style="text-align: center;">-----</p>	1-19
A	<p>John Ritchi e ET AL: "UPnP AV Archi tecture^ For UPnP Versi on 1.0" , , 31 December 2010 (2010-12-31) , XP055032201 , Retri eved from the Internet: URL: http://upnp.org/specs/av/UPnP-av-AVArc hi tecture-v2 .pdf [retri eved on 2012-07-09] page 7, paragraph 2 page 9, paragraph 4</p> <p style="text-align: center;">-----</p>	1-19

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2012/075710

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
US 2008253747	AI	16-10-2008	JP 5075454 B2	21-11-2012
			JP 2008262627 A	30-10-2008
			US 2008253747 AI	16-10-2008

US 2006200570	AI	07-09-2006	NONE	
