



- (51) International Patent Classification:
G06F 17/50 (2006.01) *G06F 19/00* (2011.01)
- (21) International Application Number:
PCT/SG2012/000143
- (22) International Filing Date:
20 April 2012 (20.04.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/477,241 20 April 2011 (20.04.2011) US
- (71) Applicant (for all designated States except US): **MAS-SACHUSETTS INSTITUTE OF TECHNOLOGY** [US/US]; 77 Massachusetts Avenue, Cambridge, MA 02139-4307 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **PREIS, Amitsur** [IL/SG]; c/o Singapore-MIT Alliance for Research and Technology Centre, 3 Science Drive 2, S16-05-08, Singapore 117543 (SG).
- (74) Agent: **ENGLISH, Matthew**; Marks & Clerk Singapore LLP, Tanjong Pagar, P O Box 636, Singapore 910816 (SG).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A METHOD FOR THE CONSTRUCTION OF A WATER DISTRIBUTION MODEL



(57) Abstract: A method for the determination of demand zones for use with a water distribution model of a water distribution network, the method comprising the steps of: constructing polygons about clusters of consumption nodes; calculating base load consumption of the nodes within each polygon; assigning a consumption type to each polygon, and; aggregating connected polygons of the same consumption type into demand zones.

Figure 3

A Method for the Construction of a Water Distribution Model

Field of the Invention

The Invention relates to the modelling of an urban water distribution system. More specifically
5 the invention relates to the initiation and construction of the model prior to the operation of the system.

Background

Typical urban water distribution systems have complex topology with numerous branches and
10 loops. This composite structure makes the analysis of the system a very difficult task. Therefore, there is a need simplify the distribution network structure by organizing the water consumers in (virtual) demand zones.

Summary of Invention

15

In a first aspect the invention provides a method for the determination of demand zones for use with a water distribution model of a water distribution network, the method comprising the steps of: constructing polygons about clusters of consumption nodes; calculating base load consumption of the nodes within each polygon; assigning a consumption type to each polygon,
20 and; aggregating connected polygons of the same consumption type into demand zones

In one embodiment of the present invention, the consumption nodes are grouped based on a multi-criteria demand zones clustering algorithm at which three criteria were used to identify clusters in the water system such that (1) the within-cluster homogeneity of water consumers' characteristics is maximized; (2) the overall variance between total water consumption of the system's clusters is minimized; and optionally (3) the number of connecting links between neighboring clusters is minimized.

Criterion 1 is used to identify areas in the system at which water customers are having similar characteristics (e.g., residential, commercial, or industrial user types) and therefore will not need large adjustments to achieve calibration. To avoid system partition into groups that are too small, comprised of only a few water consumers, a constraint on the lowest total water consumption in each cluster is added.

Criterion 2 is implemented in parallel to criterion 1 to ensure that the clusters are equal in their total base demand and there are no large variations between demand zones' total consumption that can bias decisions.

Additionally Criterion 3 may be used to reduce the number of connections between each demand zone to its neighboring zones as it is often noted that node clusters should be thought of as sets of nodes with more and/or better intra-connections than inter-connections. When interested in detecting communities and evaluating their quality, it is preferred to maximize the number of sets that are densely linked inside and sparsely linked to the outside.

This multi-criteria problem may be solved using graph search algorithms. For instance Breadth-First search and Best First Search and evolutionary optimization approach which partitions the system into homogeneous demand zones (e.g., residential, commercial, industrial) with equal
5 total base demand, and with minimized number of links between them. As often occurs in this type of multi-objective problems, there is no one optimal solution that satisfies all three criteria at the same time and it is anticipated that the three objectives will mutually compete. Therefore, in several cases it will be impossible to find homogeneous demand zones that also comply with the other criteria, and in those cases, the zones will be categorized as mixed clusters (e.g., mixed
10 residential-commercial or mixed commercial-industrial).

Advantages provided by the invention may include:

a) Effectiveness in hydraulic model calibration procedures:

15 There are thousands of water consumers with unknown variations in their demand patterns to be estimated in a typical urban water system and only a relatively small number of direct measurements are available. This creates an ill-posed, underdetermined calibration problem which leads to non-unique solutions. This can be overcome by grouping the unknown parameters. Grouping is based on identifying areas of the system at which water customers are
20 having the same characteristics (e.g., residential, commercial, or industrial consumption patterns) and therefore will not need large adjustments to achieve calibration. The main advantage of 'grouping' is that the size of the problem is reduced - making it possible to find unique solutions to the optimization problem.

b) Effectiveness in leakage detection and pressure management:

In the UK, district metered areas (DMAs) have been proven to be effective in leakage monitoring and control. The water networks are divided into District Metering Areas (DMAs) which
5 facilitate direct identification and management of water losses and enable flow tracking between different clusters with flow meters at the DMAs boundaries. In addition, pressure management and leakage localization can be implemented by pressure monitoring within the DMAs to achieve improved leakage reduction .

10 c) Effectiveness in improving water security:

Dividing the system into consumption blocks at which all connections between the blocks are known and monitored (e.g., flow rates and water quality parameters) can improve the response to an event of a large scale contamination incident. Combining knowledge about blocks connectivity with the implementation of appropriate operation response (e.g. valves closure and
15 hydrants opening) for isolation and flushing of the contamination from the water network would limit exposure to harmful contaminants and minimize the extent of pipe that would need to be decontaminated.

Brief Description of Drawings

20

It will be convenient to further describe the present invention with respect to the accompanying drawings that illustrate possible arrangements of the invention. Other arrangements of the

invention are possible, and consequently the particularity of the accompanying drawings is not to be understood as superseding the generality of the preceding description of the invention.

Figure 1 is a plan view of an urban water distribution network;

5 Figure 2 is a plan view of a skeleton of the urban water distribution network of Figure 1;

Figure 3 is a plan view of the urban water distribution network of Figure 1 having nodes enmeshed by polygons;

Figure 4 is a connectivity graph according to one embodiment of the present invention; Figure 5 is a Demand Zone Aggregation according to a further embodiment of the present invention;

10 Figure 6 is a plan view of the urban water distribution network of Figure 1 showing the formed demand zones;

Figures 7A to 7C, 8 and 9 are sequential steps of a connectivity minimization process according to a further embodiment of the present invention;

Figure 10 is a plan view of an urban water distribution network following connectivity
15 minimization according to a further embodiment of the present invention.

Detailed Description

The invention provides a method of grouping large numbers of diverse water consumption users
20 to be used in a rational optimization of the water distribution network. Whilst there are a number of procedures for the optimization of such networks dealing with the diversity of users in an urban environment provides a balance between reliable results and managing the needs of said users.

Accordingly, the present invention provides a process to group said users with the following setting out one such method falling within the scope of the invention.

5 Step 1: Initial partition based on the system main skeleton

The main skeleton of the system which is comprised of pipes with diameter $\geq 12''$ (304 mm) is used to construct polygons that bind the system consumption nodes. Figure 1 shows the full water network 5 (with the two service reservoirs, 19415 junctions, and 20072 pipes) and Fig. 2 shows the main skeleton 10 of the system.

- 10 Figure 3 shows the set of 39 polygons 25 constructed based on the system's main skeleton 15. All 1717 water consumers 20 (marked in red dots) in this example network lie inside these polygons 25:

GIS tools can be used for the purpose of constructing polygons out of sets of x, y coordinates and
15 for determining if a point lies on the interior of each polygon. Also it is possible to use one of the known algorithms which are available in the literature for this purpose. In this application, the polygons 25 were constructed out of the main skeleton vertices and demand nodes were assigned to polygons by implementing a procedure for determining if a point lies inside a given polygon.

- 20 At the end of this initial step, the total base demand of each polygon is calculated and a consumption type is assigned to each polygon according to the distribution of water consumption 20 within the block (i.e., if more than 60 % of the base demand in a block has the same

consumption-type then the block is assigned with that consumption type; otherwise the block is assigned with mixed consumption depending on the block components (e.g., mixed residential-commercial, mixed commercial-industrial, and mixed residential-industrial). Table 1 shows these data for the example system:

5

Polygon index	total Base demand (CMH)	Residential use (%)	Commercial use (%)	Industrial use (%)	User type:
1	26	29.2	70.8	0.0	Commercial
2	24	0.0	100.0	0.0	Commercial
3	36	0.0	100.0	0.0	Commercial
4	124	30.0	67.2	2.8	Commercial
5	409	1.6	7.1	91.3	Industrial
6	129	72.2	27.8	0.0	Residential
7	74	98.0	2.0	0.0	Residential
8	198	26.8	72.3	0.9	Commercial
9	246	0.0	0.2	99.8	Industrial
10	38	7.1	30.1	62.7	Industrial
11	403	26.9	70.1	2.9	Commercial
12	74	89.5	10.5	0.0	Residential
13	126	43.6	53.4	3.0	Mixed commercial-residential
14	354	28.7	66.0	5.3	Commercial

15	80	0.0	97.9	2.1	Commercial
16	11	37.9	62.1	0.0	Commercial
17	63	20.4	79.6	0.0	Commercial
18	50	0.0	94.4	5.6	Commercial
19	22	11.2	86.6	2.2	Commercial
20	1	0.0	100.0	0.0	Commercial
21	158	0.0	100.0	0.0	Commercial
22	228	1.3	98.7	0.0	Commercial
23	273	31.7	68.3	0.0	Commercial
24	62	26.7	68.0	5.2	Commercial
25	24	47.3	50.8	1.9	Mixed commercial- residential
26	167	45.4	53.8	0.8	Mixed commercial- residential
27	114	57.9	42.1	0.0	Mixed commercial- residential
28	154	18.6	81.4	0.0	Commercial
29	117	31.6	66.4	1.9	Commercial
30	127	69.9	27.2	2.9	Residential
31	100	61.4	35.8	2.8	Residential
32	105	43.9	53.9	2.2	Mixed commercial- residential
33	22	98.9	1.1	0.0	Residential

34	77	86.6	10.3	3.1	Residential
35	115	88.9	11.1	0.0	Residential
36	3	0.0	36.4	63.6	Industrial
37	64	2.4	33.3	64.3	Industrial
38	210	32.2	6.0	61.8	Industrial
39	323	90.5	9.1	0.4	Residential

Step 2: Aggregation of the network's nodes into demand zones

In this step, the aim is to group polygons into demand zones which will have equal (as possible) total base demands and homogeneous (as possible) consumption within each group. It is important to create groups of polygons with roughly the same water consumption since having a very large variance between different clusters might bias the system's hydraulic model calibration results.

The process of grouping the basic demand blocks is as follows:

1. The polygons are sorted according to their connectivity and are organized in a graph (Figure 4) where the graph vertices are the basic blocks and the edges stand for the connectivity between these blocks:

2. Best First Search technique which is a type of graph search algorithm is implemented on the graph presented in Figure 4 to group the polygons (graph nodes) into equal and homogeneous as

possible demand zones. It starts at a root node 45 and explores all the nodes which are adjacent to the current node before visiting other nodes. The traversal goes a level at a time 40 and adds a node to a group according to the following preference list sorted from option i which is the best choice to option iii which is the least favorable alternative:

- 5 i. Aggregate adjacent nodes with similar consumption type to a group until the total water consumption reaches the maximum consumption threshold (500 CMH)
- ii. If the total consumption is below the minimum consumption threshold (200 CMH) then add nodes with mixed consumption (where at least one of the components of the mixed node is similar to the group's consumption type). Stop when the total base demand
10 exceeds the minimum boundary
- iii. If the total consumption is below the minimum consumption threshold (200 CMH) and there is no better choice, add any adjacent node with any consumption type until the minimum consumption threshold is met
- The 200-500 CMH amplitude allows some flexibility in aggregating the nodes into
15 homogeneous as possible groups while keeping the nodes consumption on the same scale.

Figure 5 demonstrate the results of above procedure on some of the graph nodes:

In this example, polygons 1, 2, 3 and 4 which have all been designated commercial use are
20 grouped as a first demand zone 60. Similarly, polygons 6 and 7 which are categorized as residential notes are grouped as a second demand zone 65. To demonstrate that demand zones may encompass single polygons as demonstrated by the industrial nodes 5 forming a third

demand zone 70, commercial nodes 11 forming a demand zone 75 and residential nodes 39 forming demand zone 80.

At the end of this procedure, the 39 basic blocks were aggregated into 15 demand zones. Table 2 and Figure 6 summarize the results of step 2. Therefore the water network 90 is now divided
 5 into various demand zones 95 comprising categorized consumers 100, 105 within each demand zone.

Demand zone index	Components (aggregated polygons)	Total base demand (CMH)	Consumption type
1	1,2,3,4	209.7	Commercial
2	6,7	202.3	Residential
3	5	408.7	Industrial
4	11	402.6	Commercial
5	9,10	283.8	Industrial
6	8,12,13,15,16	489.4	Mixed commercial-residential
7	14,17	416.4	Mixed commercial-residential
8	18,19,20,23,24,25	431.6	Mixed commercial-residential
9	22,29	344.8	Commercial

10	21,28	311.6	Commercial
11	30,31,35	342.2	Residential
12	26,32	271.3	Mixed commercial-residential
13	27,33,34	213.5	Residential
14	36,37,38	276.6	Industrial
15	39	323.0	Residential

Table 2: Demand zones details

Step 3: Minimizing the number of links between neighboring demand zones

The purpose of this step is to reduce the number of connections between each set and its neighboring sets. This is achieved by solving the following optimization problem for each pair of adjacent demand zones.

The decision variables of this optimization problem are the water system junctions (with no water consumption) in a range of 500 m 125, 130 from both sides of the border 110 between the two zones 115, 120. All the nodes indexes and the zones that these nodes belong to are written to a matrix. Figures 7A to 7C describe this procedure:

The objective function to be minimized with a Genetic Algorithm procedure is the sum of connections between zones i 115 and j 120. The decision variables values are 0 or 1. If the value equals 1 then the node's zone index is switched from i to j and vice versa. If the value is zero the node remain in its original demand zone. In the illustrative example given below, each decision

variables' string is comprised of 7 random Boolean values for the first GA iteration. At the subsequent iterations (using the GA operators) nodes are shifted from zone to zone until the number of connections between the zones is minimized. Figures 8A and 8B demonstrate this procedure.

5

At the end of the GA procedure nodes were switched (or not switched) from zones i and j and as a result the number of connections between the zones is minimized 150. See optimal solution for the illustrative example in Figure 9:

- 10 The results of the implementation of the GA procedure on the FCPH network showed that the average optimal number of connections between each set of two neighboring demand zones is 5 (e.g., the number of connecting pipes for zones 1 and 3 is 2; for zones 3 and 4 its 5; for zones 10 and 11 its 1; and for zones 11 and 12 its 10).
- 15 Figure 10 shows the practical application of the procedure whereby connecting pipes between adjacent zones 2 and 4 are minimized to only 4 pipes. The connection minimization procedure is completed for each of the zonal boundaries throughout the water network.

Claims:

1. A method for the determination of demand zones for use with a water distribution model of a water distribution network, the method comprising the steps of:

constructing polygons about clusters of consumption nodes;

- 5 calculating base load consumption of the nodes within each polygon;

assigning a consumption type to each polygon, and;

aggregating connected polygons of the same consumption type into demand zones

2. The method according to claim 1, wherein the aggregating step includes balancing a
10 uniform total base demand for all demand zones and maintaining a homogenous
consumption within each demand zone.

3. The method according to claim 1 or 2, wherein the consumption types include residential,
industrial and commercial.

15

4. The method according to any one of claims 1 to 3, wherein the consumption types further
include mixed consumption types between residential, industrial and commercial type so
as to facilitate balancing consumption type within each demand zone and equal total base
demand for all demand zone.

5. The method according to any one of claims 1 to 4, wherein the assigning step includes determining the consumption type within a polygon based upon a minimum of 60% of said consumption type nodes within said polygon;

5

6. The method according to claim 5, wherein the mixed consumption type is assigned to a polygon where the maximum proportion of nodes of any one consumption type is less than 60%.

10

7. The method according to any one of claims 1 to 3, wherein the forming step includes aggregating polygons into demand zones based on connectivity.

8. The method according to any one of claims 1 to 7, wherein the aggregating step comprises the steps of :

15

accumulating connected polygons of a similar consumption type, and;

calculating the total water consumption of the aggregated group until the aggregated group has a total water consumption between a minimum and maximum threshold so as to form a homogenous demand zone;

if there are insufficient connected polygons of the same consumption type to meet the minimum threshold type, then;

20

adding polygons of a different consumption type until the minimum threshold is exceeded, so as to form a mixed consumption demand zone.

9. The method according to any one of claims 1 to 8, wherein the minimum threshold is 200
5 Cubic metres per hour and the maximum threshold is 500 Cubic metres per hour.

10. The method according to any one of claims 1 to 9, wherein further including, after the aggregating step, the steps of:

selecting a buffer zone around each demand zone boundary;

10 identifying respective nodes on each side of the boundary within said buffer zone;

calculating the number of connections between nodes crossing said boundary;

reallocating a buffer node in one demand zone to the adjacent demand zone;

recalculating the number of connections crossing said boundary and compare with the first number of connections;

15 repeat reallocating and recalculating steps until a minimum number of connections are found;

finalizing demand zones based on reallocation of buffer nodes having the minimum number of connections crossing the boundary.




Figure 1

Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

Figure 7A




Figure 7B





Figure 7C






Figure 8A

Decision variable index	Decision variable value
1	1
2	0
3	0
4	1
5	0
6	1
7	0




Figure 8B




Figure 9




Figure 10

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG2012/000143

A. CLASSIFICATION OF SUBJECT MATTER

G06F 17/50 (OCT 2005) G06F 19/00 (JAN 2011)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI: KW; "water supply/distribute", network, demand, model, cluster, polygon, zone (and like terms in various combinations)Google Patents: KW; water, supply/distribute, cluster, analysis, demand, zone, model, calculate (in various combinations)Google Scholar: KW; cluster, analysis, water, supply, zones, demand (in various combinations)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	Documents are listed in the continuation of Box C	



Further documents are listed in the continuation of Box C



See patent family annex

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
11 July 2012Date of mailing of the international search report
18 July 2012

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
Email address: pct@ipaustalia.gov.au
Facsimile No.: +61 2 6283 7999

Authorized officer

Emma Francis
AUSTRALIAN PATENT OFFICE
(ISO 9001 Quality Certified Service)
Telephone No. 0399359631

INTERNATIONAL SEARCH REPORT		International application No.
C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		PCT/SG2012/000143
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2003/0101009 A1 (SEEM) 29 May 2003 See Abstract, Figures 3-6 and [0072]-[0073]	
A	US 4,562,552 A (MIYAOKA et al.) 31 December 1985 See Abstract and claim 1	
A	Koo et al. "Estimating regional water demand in Seoul, South Korea, using principal component and cluster analysis" Water Science and Tech: Water Supply (2005) 5(1):1-7 See whole document	
A	US 6,862,540 B1 (WELCH et al.) 01 March 2005 See Abstract and Figures	

INTERNATIONAL SEARCH REPORT Information on patent family members		International application No. PCT/SG2012/000143	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
US 2003/0101009 A1	29 May 2003	EP 1309062 A2	07 May 2003
		JP 2003242212 A	29 Aug 2003
		US 2003101009 A1	29 May 2003
US 4562552 A	31 Dec 1985	JP 58144918 A	29 Aug 1983
		JP 5009809 B	08 Feb 1993
		US 4562552 A	31 Dec 1985
US 6862540 B1	01 Mar 2005	US 6862540 B1	01 Mar 2005
End of Annex			
Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001. Form PCT/ISA/210 (Family Annex)(July 2009)			